

Systeme d'informations et applications web – TD

Semestre 4

Table des matières

1	Rappel sur le SQL – LDD/LMD	4
2	Projection – Sélection – Agrégation	5

Rappel sur le SQL – LDD/LMD

```
1 | create table PROJET(  
2 |   NP varchar(4),  
3 |   nomP varchar(32),  
4 |   ne varchar(4),  
5 |   pbudget decimal(16),  
6 |   constraint pk_projet PRIMARY KEY(np),  
7 |   constraint fk_projet_ne FOREIGN KEY(ne) REFERENCES equipe(ne),  
8 |   constraint ck_projet_pbudget CHECK(ne >= 0)  
9 | );  
  
1 | update PROJET set pbudget = pbudget * 0.80;  
2 | update PROJET set pbudget = pbudget + 5000 where ne='e1';  
  
1 | delete from AFF where nc=(select nc from chercheur where nomc='Jean');  
  
1 | alter table EQUIPE ADD (  
2 |   np decimal(3),  
3 |   bt decimal(3),  
4 |   constraint ck_equipe_bt check(bt >= 0),  
5 |   constraint ck_equipe_np check(np >= 0)  
6 | );  
7 |  
8 | update equipe e1 set np = (select count(*) from projets WHERE projets.ne=e1.ne),  
9 |   bt = (select sum(pbudget) from projets where projets.ne=e1.ne);
```

Projection – Sélection – Agrégation

1. $R = \Pi_{ne} \text{ equipe}$ $R[ne]$
`| select distinct NE from equipe;`
2. $R = \Pi_{nomP, pBudget}(\sigma_{Ne='e1'} \text{ equipe})$ $R[nomp, pbudget]$
`| select distinct nomp, pbudget from projet where ne='e1';`
`| select distinct nomp, pbudget from (select * from projets where ne='e1');`
3. $R = \Pi_{nomC, nc}(\sigma_{nomc \text{ like } '%a\%'} \text{ chercheur})$ $R[nomc]$
`| select distinct nomc from chercheur where nomC like '%a%';`
`| select distinct nomc from (select * from chercheur where nomC like '%a%');`
4. $R = \text{COUNT}(\text{projet}, ne, np)$ $R[ne, count(np)]$
`| select ne, count(np) as COUNT_NP from projet group by ne;`
5. $R = \text{COUNT}(\text{aff}, np, nc)$ $R[np, count(nc)]$
`| select np, count(nc) as COUNT_NC from aff group by np;`
6. $R = \text{SUM}(\text{projet}, ne, pBudget)$ $R[ne, count(pBudget)]$
`| select ne, sum(pBudget) as SUM_PBUDGET from projet group by ne;`
7. $R = \text{COUNT}(\text{aff}, np, nc, count(nc) = 2)$ $R[np, count(nc)]$
`| select np, count(nc) as COUNT_NC from aff group by np having COUNT_NC = 2;`