



Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 1:** The **right sub-tree** of a node x is **non-empty**.
 - **Successor of x :** The **leftmost node** in the right sub-tree.
 - \therefore call **TREE-MINIMUM(right[x])**.




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 1:** The **right sub-tree** of a node x is **non-empty**.
 - **Successor of x :** The **leftmost node** in the right sub-tree.
 - \therefore call `TREE-MINIMUM(right[x])`.
 - **Example:** Successor of 15 is 17.




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The right sub-tree of a node x is empty.
 - **Successor of x :** The lowest ancestor of x whose left child is also an ancestor of x .




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **right sub-tree** of a node x is **empty**.
 - **Successor of x :** The **lowest ancestor of x whose left child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the left child of its parent.
 - **Example:** Consider the node 13.




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **right sub-tree** of a node x is **empty**.
 - **Successor of x :** The **lowest ancestor of x whose left child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the left child of its parent.
 - **Example:** Consider the node 13.




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **right sub-tree** of a node x is **empty**.
 - **Successor of x :** The **lowest ancestor of x whose left child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the left child of its parent.
 - **Example:** Consider the node 13.




Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **right sub-tree** of a node x is **empty**.
 - **Successor of x :** The **lowest ancestor of x whose left child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the left child of its parent.
 - **Example:** Consider the node 13.



Successor

- The structure of BST allows us to determine the successor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **right sub-tree** of a node x is **empty**.
 - **Successor of x :** The **lowest ancestor of x whose left child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the left child of its parent.
 - Then this parent is the successor.
 - **Example:** The successor of 13 is 15.



TREE-SUCCESSOR

TREE-SUCCESSOR(x)

I/P: A node x whose successor we need to find.

O/P: The successor of x .

Begin

if ($right[x] \neq \mathbf{nil}$)

return TREE-MINIMUM($right[x]$);

$y \leftarrow parent[x]$;

while ($y \neq \mathbf{nil}$) and ($x = right[y]$)

$x \leftarrow y$;


$y \leftarrow parent[y]$;

return y ;

End


Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 1:** The **left sub-tree** of a node x is **non-empty**.
 - **Predecessor of x :** The **rightmost node** in the left sub-tree.
 - \therefore call `TREE-MAXIMUM(left[x])`.




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 1:** The left sub-tree of a node x is non-empty.
 - **Predecessor of x :** The rightmost node in the left sub-tree.
 - \therefore call `TREE-MAXIMUM(left[x])`.
 - **Example:** Predecessor of 15 is 13.




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The left sub-tree of a node x is empty.
 - **Predecessor of x :** The lowest ancestor of x whose right child is also an ancestor of x .




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **left sub-tree** of a node x is **empty**.
 - **Predecessor of x :** The **lowest ancestor of x whose right child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the right child of its parent.
 - **Example:** Consider the node 17.




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **left sub-tree** of a node x is **empty**.
 - **Predecessor of x :** The **lowest ancestor of x whose right child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the right child of its parent.
 - **Example:** Consider the node 17.




Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **left sub-tree** of a node x is **empty**.
 - **Predecessor of x :** The **lowest ancestor of x whose right child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the right child of its parent.
 - **Example:** Consider the node 17.



Predecessor

- The structure of BST allows us to determine the Predecessor of a node without ever comparing keys!
- Two cases may arise:
 - **Case 2:** The **left sub-tree** of a node x is **empty**.
 - **Predecessor of x :** The **lowest ancestor of x whose right child is also an ancestor of x** .
 - Go up the tree from x until we encounter a node that is the right child of its parent.
 - Then this parent is the predecessor.
 - **Example:** The Predecessor of 17 is 15.



TREE-PREDECESSOR

TREE-PREDECESSOR(x)

I/P: A node x whose predecessor we need to find.

O/P: The predecessor of x .

Begin

if ($left[x] \neq \mathbf{nil}$)

return TREE-MAXIMUM($left[x]$);

$y \leftarrow parent[x]$;

while ($y \neq \mathbf{nil}$) and ($x = left[y]$)

$x \leftarrow y$;

$y \leftarrow parent[y]$;

return y ;

End