

=== CONFIGURACION GNB (1780306782) ===

amf:

addr: 10.53.1.2  
port: 38412

mcc: 001

mnc: 01

nci: 0x0000000010

tac: 1

cu\_cp:

bind\_addr: 10.53.1.3  
remote\_addr: 10.53.1.2  
port: 38412

du\_f1:

bind\_addr: 10.53.1.3  
remote\_addr: 10.53.1.3  
port: 8805

rf:

device\_name: uhd  
device\_args: "recv\_frame\_size=9216,send\_frame\_size=9216,base\_srate=30.72e6"  
srate: 30.72e6  
tx\_gain: 70  
rx\_gain: 40  
nof\_antennas: 1

nr:

bands: [7]  
dl\_nr\_arfcn: 505000  
ssb\_nr\_arfcn: 505000  
common\_scs: 30  
ssb\_scs: 30  
nof\_prb: 106  
prach\_conf\_idx: 162  
ssb\_period: 20  
ssb\_offset: 0  
ssb\_pattern: "CASE\_A"  
ssb\_power: -25

zmq:

enable: true  
tx\_port: 2000  
rx\_port: 2001

log:

all\_level: info  
filename: /tmp/gnb.log  
file\_max\_size: -1

=== CONFIGURACION UE (1780306782) ===

```
[rf]
freq_offset = 0
tx_gain = 10
rx_gain = 5
srate = 30.72e6
nof_antennas = 1
device_name = uhd
device_args = sync=internal,base_srate=30.72e6
time_adv_nsamples = auto

[rat.nr]
bands = 7
nof_carriers = 1
max_nof_prb = 106
nof_prb = 106
dl_nr_arfcn = 505000
ssb_nr_arfcn = 505000

[pcap]
enable = none
mac_filename = /tmp/ue_mac.pcap
mac_nr_filename = /tmp/ue_mac_nr.pcap
nas_filename = /tmp/ue_nas.pcap

[log]
all_level = info
phy_lib_level = none
all_hex_limit = 32
filename = /tmp/ue.log
file_max_size = -1

[usim]
mode = soft
algo = milenage
opc = 63BFA50EE6523365FF14C1F45F88737D
k = 00112233445566778899aabbccddeeff
imsi = 001010123456789
imei = 353490069873319

[rrc]
release = 15
ue_category = 4

[nas]
apn = srsapn
apn_protocol = ipv4

[gw]
# ip_addr is intentionally omitted as per instructions.

[zmq]
enable = true
remote_addr = 10.53.1.3
tx_port = 2001
rx_port = 2000

[gui]
enable = true
```

=== DOCKER COMPOSE (1780306782) ===

version: '3.8'

networks:

oai-net:

name: oai-net  
ipam:  
config:  
- subnet: 10.53.1.0/24

services:

5gc:

build:  
context: open5gs  
dockerfile: Dockerfile  
container\_name: open5gs  
privileged: true  
networks:  
oai-net:  
ipv4\_address: 10.53.1.2  
ports:  
- "3000:3000" # WebUI  
- "38412:38412/sctp" # AMF  
- "2152:2152/udp" # UPF  
volumes:  
- ./open5gs/config:/open5gs/config  
- ./open5gs/log:/open5gs/log  
command: ["/bin/bash", "-c", "for i in {amf,ausf,nrf,nssf,pcf,smf,udm,udr,upf}; do open5gs-\$i & done && tail -f /dev/null"]  
depends\_on:  
- mongodb

mongodb:

image: mongo:4.4  
container\_name: mongodb  
networks:  
oai-net:  
ipv4\_address: 10.53.1.100  
volumes:  
- ./mongodb:/data/db  
command: mongod --bind\_ip\_all

gnb:

build:  
context: srsran\_gnb  
dockerfile: Dockerfile  
container\_name: srsran\_gnb  
privileged: true  
networks:  
oai-net:  
ipv4\_address: 10.53.1.3  
ports:  
- "2000:2000/udp"  
- "2001:2001/udp"  
volumes:  
- ./srsran\_gnb/config:/srsran/config  
- ./srsran\_gnb/log:/srsran/log  
command: ["/bin/bash", "-c", "srsran\_gnb -c /srsran/config/gnb.yaml"]  
depends\_on:  
- 5gc