

=== CONFIGURACION GNB (1780308754) ===

```
# gNB Configuration for VR E-Sports (URLLC Optimized)
# This configuration sets up a gNB for 5G NR, connecting to a 5GC.
# Optimized for low latency and high reliability for VR applications.

mcc: 001
mnc: 01
nci: 0x12345
tac: 1
amf_addr: 10.53.1.2
amf_port: 38412

ngap:
  bind_addr: 10.53.1.3
  port: 38412

cu_cp:
  bind_addr: 10.53.1.3
  port: 2152

# Radio configuration for high performance
radio:
  band: n78
  srate: 23.04e6 # High sample rate for better bandwidth and responsiveness
  # channel_bandwidth_MHz: 100 # Example, adjust based on actual spectrum
  # dl_freq_MHz: 3500 # Example, adjust based on actual spectrum
  # ul_freq_MHz: 3500 # Example, adjust based on actual spectrum

# ZMQ for communication with UE (simulated radio)
zmq:
  tx_port: 2000
  rx_port: 0.0.0.0:2001 # Listen on all interfaces for UE connection

# Omitted 'cu_up' block as it causes Segmentation Fault.
# The core network (5GC) will handle URLLC QoS policies.
```

=== CONFIGURACION UE (1780308754) ===

UE Configuration for VR E-Sports (URLLC Optimized)
This configuration sets up a UE to connect to the gNB.

[rrc]
Radio configuration must match gNB
band = n78
srate = 23.04e6

[nas]
mcc = 001
mnc = 01
imsi = 001010000000001 # Matches MCC/MNC and RAG context supi_range
key = 63bfa50ee6523365ff14c1f45f88737d
opc = 981d464c7c52eb6e50494983c52849a0
sqn = 0

[zmq]
tx_port = 2001
rx_port = 2000

[gw]
ip_addr is NOT defined here as per strict rule

```
# Copyright 2022-2023 Open5GS Authors.
#
# This file is part of Open5GS.
#
# Open5GS is free software: you can redistribute it and/or modify
# it under the terms of the GNU Affero General Public License as published by
# the Free Software Foundation, either version 3 of the License, or
# (at your option) any later version.
#
# Open5GS is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU Affero General Public License for more details.
#
# You should have received a copy of the GNU Affero General Public License
# along with Open5GS. If not, see <http://www.gnu.org/licenses/>.
```

version: "3.8"

services:

```
5gc:
  build:
    context: .
    dockerfile: ./docker/Dockerfile.5gc
  container_name: open5gs-5gc
  privileged: true
  command: 5gc -c open5gs-5gc.yml
  volumes:
    - ./configs/open5gs:/open5gs/config
  networks:
    ran:
      ipv4_address: 10.53.1.2
  ports:
    - "3000:3000" # WebUI
    - "38412:38412/sctp" # NGAP
    - "2152:2152/udp" # PFCP
  healthcheck:
    test: ["CMD", "pgrep", "open5gs-amfd"]
    interval: 10s
    timeout: 5s
    retries: 5
```

```
gnb:
  build:
    context: .
    dockerfile: ./docker/Dockerfile.gnb
  container_name: srsran-gnb
  privileged: true
  command: nr-gnb -c gnb.yml
  volumes:
    - ./configs/srsran:/srsran/config
  networks:
    ran:
      ipv4_address: 10.53.1.3
  healthcheck:
    test: ["CMD", "pgrep", "nr-gnb"]
    interval: 10s
    timeout: 5s
    retries: 5
```

networks:

```
ran:
  name: ran
  driver: bridge
  ipam:
```

config:

- subnet: 10.53.1.0/24