

=== CONFIGURACION GNB (1779106935) ===

```
cu_cp:
  amf:
    addr: 10.53.1.2
    port: 38412
    bind_addr: 10.53.1.3
    supported_tracking_areas:
      - tac: 7
        plmn_list:
          - plmn: "20893"
            tai_slice_support_list:
              - sst: 1
    inactivity_timer: 7200

ru_sdr:
  device_driver: zmq
  device_args: tx_port=tcp://127.0.0.1:2000,rx_port=tcp://127.0.0.1:2001,base_srate=11.52e6
  srate: 11.52
  tx_gain: 75
  rx_gain: 75

cell_cfg:
  dl_arfcn: 368500
  band: 3
  channel_bandwidth_MHz: 10
  common_scs: 15
  plmn: "20893"
  tac: 7
  pdcch:
    common:
      ss0_index: 0
      coreset0_index: 6
    dedicated:
      ss2_type: common
      dci_format_0_1_and_1_1: false
  prach:
    prach_config_index: 1
  pdsch:
    mcs_table: qam64
  pusch:
    mcs_table: qam64

log:
  filename: /tmp/gnb.log
  all_level: info
  hex_max_size: 0

pcap:
  mac_enable: false
  mac_filename: /tmp/gnb_mac.pcap
  ngap_enable: false
  ngap_filename: /tmp/gnb_ngap.pcap
  e2ap_enable: true
  e2ap_du_filename: /tmp/gnb_du_e2ap.pcap
  e2ap_cu_cp_filename: /tmp/gnb_cu_cp_e2ap.pcap
  e2ap_cu_up_filename: /tmp/gnb_cu_up_e2ap.pcap

metrics:
  layers:
    enable_rlc: true
    enable_sched: true
  periodicity:
    du_report_period: 1000
```

=== CONFIGURACION UE (1779106935) ===

```
[rf]
freq_offset = 0
tx_gain = 50
rx_gain = 40
srate = 11.52e6
nof_antennas = 1
device_name = zmq
device_args = tx_port=tcp://127.0.0.1:2001,rx_port=tcp://127.0.0.1:2000,base_srate=11.52e6

[rat.eutra]
dl_eurfcn = 2850
nof_carriers = 0

[rat.nr]
bands = 3
nof_carriers = 1

[pcap]
enable = none
mac_filename = /tmp/ue_mac.pcap
mac_nr_filename = /tmp/ue_mac_nr.pcap
nas_filename = /tmp/ue_nas.pcap

[log]
all_level = warning
phy_lib_level = none
all_hex_limit = 32
filename = stdout
file_max_size = -1

[usim]
mode = soft
algo = milenage
opc = 63BFA50EE6523365FF14C1F45F88737D
k = 00112233445566778899aabbccddeeff
imsi = 208930000000001
imei = 353490069873319

[rrc]
release = 15
ue_category = 4

[nas]
apn = srsapn
apn_protocol = ipv4

[gw]
netns = ue1
ip_devname = tun_srsue
ip_netmask = 255.255.255.0

[gui]
enable = false
```

=== DOCKER COMPOSE (1779106935) ===

services:

```
5gc:
  container_name: open5gs_5gc
  build:
    context: open5gs
    target: open5gs
    args:
      OS_VERSION: "22.04"
      OPEN5GS_VERSION: "v2.7.0"
  env_file:
    - ${OPEN_5GS_ENV_FILE:-open5gs/open5gs.env} # Ensure this file configures MCC 208, MNC 93, TAC 7 for Open5GS
  privileged: true
  ports:
    - "9898:9999/tcp"
  command: 5gc -c open5gs-5gc.yml
  healthcheck:
    test: [ "CMD-SHELL", "nc -z 127.0.0.20 7777" ]
    interval: 3s
    timeout: 1s
    retries: 60
  networks:
    ran:
      ipv4_address: ${OPEN5GS_IP:-10.53.1.2}
```

```
gnb:
  container_name: srsran_gnb
  image: srsran/gnb
  build:
    context: ..
    dockerfile: docker/Dockerfile
    args:
      OS_VERSION: "24.04"
  privileged: true
  cap_add:
    - SYS_NICE
    - CAP_SYS_PTRACE
  volumes:
    - /dev/bus/usb/:/dev/bus/usb/
    - /usr/share/uhd/images:/usr/share/uhd/images
    - gnb-storage:/tmp
  configs:
    - gnb_config.yml
    - gnb_compose_config.yml
  networks:
    ran:
      ipv4_address: ${GNB_IP:-10.53.1.3}
  metrics:
    ipv4_address: 172.19.1.3
  depends_on:
    5gc:
      condition: service_healthy
  command: gnb -c /gnb_config.yml -c /gnb_compose_config.yml
```

configs:

```
gnb_config.yml:
  content: |
    cu_cp:
      amf:
        addr: 10.53.1.2
        port: 38412
        bind_addr: 10.53.1.3
        supported_tracking_areas:
          - tac: 7
          plmn_list:
```

```

    - plmn: "20893"
      tai_slice_support_list:
        - sst: 1
  inactivity_timer: 7200

ru_sdr:
  device_driver: zmq
  device_args: tx_port=tcp://127.0.0.1:2000,rx_port=tcp://127.0.0.1:2001,base_srate=11.52e6
  srate: 11.52
  tx_gain: 75
  rx_gain: 75

cell_cfg:
  dl_arfcn: 368500
  band: 3
  channel_bandwidth_MHz: 10
  common_scs: 15
  plmn: "20893"
  tac: 7
  pdccch:
    common:
      ss0_index: 0
      coreset0_index: 6
    dedicated:
      ss2_type: common
      dci_format_0_1_and_1_1: false
  prach:
    prach_config_index: 1
  pdsch:
    mcs_table: qam64
  pusch:
    mcs_table: qam64

log:
  filename: /tmp/gnb.log
  all_level: info
  hex_max_size: 0

pcap:
  mac_enable: false
  mac_filename: /tmp/gnb_mac.pcap
  ngap_enable: false
  ngap_filename: /tmp/gnb_ngap.pcap
  e2ap_enable: true
  e2ap_du_filename: /tmp/gnb_du_e2ap.pcap
  e2ap_cu_cp_filename: /tmp/gnb_cu_cp_e2ap.pcap
  e2ap_cu_up_filename: /tmp/gnb_cu_up_e2ap.pcap

metrics:
  layers:
    enable_rlc: true
    enable_sched: true
  periodicity:
    du_report_period: 1000
gnb_compose_config.yml:
content: |
cu_cp:
  amf:
    addr: ${OPEN5GS_IP:-10.53.1.2}
    bind_addr: ${GNB_IP:-10.53.1.3}
metrics:
  autostart_stdout_metrics: true
  enable_json: true
remote_control:
  bind_addr: 0.0.0.0
  enabled: true

```

volumes:

gnb-storage:

networks:

 ran:

 ipam:

 driver: default

 config:

 - subnet: 10.53.1.0/24

metrics:

 ipam:

 driver: default

 config:

 - subnet: 172.19.1.0/24