

=== GNB (1785494454) ===

```
cu_cp:
  amf:
    addr: 10.53.1.2
    port: 38412
    bind_addr: 10.53.1.1
    supported_tracking_areas:
      - tac: 7
        plmn_list:
          - plmn: "21401"
            tai_slice_support_list:
              - sst: 1
    inactivity_timer: 7200

ru_sdr:
  device_driver: zmq
  device_args: tx_port=tcp://127.0.0.1:2000,rx_port=tcp://127.0.0.1:2001,base_srate=11.52e6
  srate: 11.52
  tx_gain: 75
  rx_gain: 75

cell_cfg:
  dl_arfcn: 630000
  band: 78
  channel_bandwidth_MHz: 20
  common_scs: 15
  plmn: "21401"
  tac: 7
  pdccch:
    common:
      ss0_index: 0
      coreset0_index: 6
    dedicated:
      ss2_type: common
      dci_format_0_1_and_1_1: false
  prach:
    prach_config_index: 1
  pdsch:
    mcs_table: qam64
  pusch:
    mcs_table: qam64

log:
  filename: /tmp/gnb.log
  all_level: info
  hex_max_size: 0

pcap:
  mac_enable: false
  mac_filename: /tmp/gnb_mac.pcap
  ngap_enable: false
  ngap_filename: /tmp/gnb_ngap.pcap
  e2ap_enable: true
  e2ap_du_filename: /tmp/gnb_du_e2ap.pcap
  e2ap_cu_cp_filename: /tmp/gnb_cu_cp_e2ap.pcap
  e2ap_cu_up_filename: /tmp/gnb_cu_up_e2ap.pcap

metrics:
  layers:
    enable_rlc: true
    enable_sched: true
  periodicity:
    du_report_period: 1000
```

=== UE (1785494454) ===

```
[rf]
freq_offset = 0
tx_gain = 50
rx_gain = 40
srate = 11.52e6
nof_antennas = 1

device_name = zmq
device_args = tx_port=tcp://127.0.0.1:2001,rx_port=tcp://127.0.0.1:2000,base_srate=11.52e6

[rat.eutra]
dl_eurfcn = 2850
nof_carriers = 0

[rat.nr]
bands = 78
nof_carriers = 1

max_nof_prb = 106
nof_prb = 106

[pcap]
enable = none
mac_filename = /tmp/ue_mac.pcap
mac_nr_filename = /tmp/ue_mac_nr.pcap
nas_filename = /tmp/ue_nas.pcap

[log]
all_level = info
phy_lib_level = none
all_hex_limit = 32
filename = /tmp/ue.log
file_max_size = -1

[usim]
mode = soft
algo = milenage
opc = 63BFA50EE6523365FF14C1F45F88737D
k = deeff112233445566778899aabbccdd
imsi = 214010000000020
imei = 353490069873319

[rrc]
release = 15
ue_category = 4

[nas]
apn = srsapn
apn_protocol = ipv4

[gw]
netns = ue1
ip_devname = tun_srsue
ip_netmask = 255.255.255.0

[gui]
enable = false
```

=== DOCKER (1785494454) ===

```
#
# Copyright 2021-2026 Software Radio Systems Limited
#
# This file is part of srsRAN
#
# srsRAN is free software: you can redistribute it and/or modify
# it under the terms of the GNU Affero General Public License as
# published by the Free Software Foundation, either version 3 of
# the License, or (at your option) any later version.
#
# srsRAN is distributed in the hope that it will be useful,
# but WITHOUT ANY WARRANTY; without even the implied warranty of
# MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
# GNU Affero General Public License for more details.
#
# A copy of the GNU Affero General Public License can be found in
# the LICENSE file in the top-level directory of this distribution
# and at http://www.gnu.org/licenses/.
#
```

services:

```
5gc:
  container_name: open5gs_5gc
  build:
    context: open5gs
    target: open5gs
    args:
      OS_VERSION: "22.04"
      OPEN5GS_VERSION: "v2.7.0"
  environment:
    - MONGODB_IP=127.0.0.1
    - OPEN5GS_IP=10.53.1.2
    - UE_IP_BASE=10.45.0
    - UPF_ADVERTISE_IP=10.53.1.2
    - DEBUG=false
    - SUBSCRIBER_DB=214010000000020, deeff112233445566778899aabbccdd, opc, 63BFA50EE6523365FF14C1F45F88737D, 8000, 9, 10.4
    - NETWORK_NAME_FULL=srsRAN
    - NETWORK_NAME_SHORT=srsRAN
    - TZ=Europe/Madrid
  privileged: true
  ports:
    - "9898:9999/tcp"
  # Uncomment port to use the 5gc from outside the docker network
  # - "38412:38412/sctp"
  # - "2152:2152/udp"
  command: 5gc -c open5gs-5gc.yml
  healthcheck:
    test: [ "CMD-SHELL", "nc -z 127.0.0.20 7777" ]
    interval: 3s
    timeout: 1s
    retries: 60
  networks:
    ran:
      ipv4_address: ${OPEN5GS_IP:-10.53.1.2}

gnb:
  container_name: srsran_gnb
  # Build info
  image: srsran/gnb
  build:
    context: ..
    dockerfile: docker/Dockerfile
    args:
      OS_VERSION: "24.04"
```

```

# privileged mode is required only for accessing usb devices
privileged: true
# Extra capabilities always required
cap_add:
  - SYS_NICE
  - CAP_SYS_PTRACE
volumes:
  # Access USB to use some SDRs
  - /dev/bus/usb/:/dev/bus/usb/
  # Sharing images between the host and the pod.
  # It's also possible to download the images inside the pod
  - /usr/share/uhd/images:/usr/share/uhd/images
  # Save logs and more into gnb-storage
  - gnb-storage:/tmp
# It creates a file/folder into /config_name inside the container
# Its content would be the value of the file used to create the config
configs:
  - gnb_config.yml
  - gnb_compose_config.yml
# Customize your desired network mode.
# current netowrk configuration creastes a private network with both containers attached
# An alterantive would be `network: host`. That would expose your host network into the container. It's the easie
networks:
  ran:
    ipv4_address: ${GNB_IP:-10.53.1.3}
  metrics:
    ipv4_address: 172.19.1.3
# Start GNB container after 5gc is up and running
depends_on:
  5gc:
    condition: service_healthy
# Command to run into the final container
command: gnb -c /gnb_config.yml -c /gnb_compose_config.yml

configs:
  gnb_config.yml:
    content: |
      cu_cp:
        amf:
          addr: 10.53.1.2
          port: 38412
          bind_addr: 10.53.1.1
          supported_tracking_areas:
            - tac: 7
              plmn_list:
                - plmn: "21401"
                  tai_slice_support_list:
                    - sst: 1
          inactivity_timer: 7200

  ru_sdr:
    device_driver: zmq
    device_args: tx_port=tcp://127.0.0.1:2000,rx_port=tcp://127.0.0.1:2001,base_srate=11.52e6
    srate: 11.52
    tx_gain: 75
    rx_gain: 75

  cell_cfg:
    dl_arfcn: 630000
    band: 78
    channel_bandwidth_MHz: 20
    common_scs: 15
    plmn: "21401"
    tac: 7
    pdcch:
      common:
        ss0_index: 0
        coreset0_index: 6

```

```
    dedicated:
      ss2_type: common
      dci_format_0_1_and_1_1: false
  prach:
    prach_config_index: 1
  pdsch:
    mcs_table: qam64
  pusch:
    mcs_table: qam64

log:
  filename: /tmp/gnb.log
  all_level: info
  hex_max_size: 0

pcap:
  mac_enable: false
  mac_filename: /tmp/gnb_mac.pcap
  ngap_enable: false
  ngap_filename: /tmp/gnb_ngap.pcap
  e2ap_enable: true
  e2ap_du_filename: /tmp/gnb_du_e2ap.pcap
  e2ap_cu_cp_filename: /tmp/gnb_cu_cp_e2ap.pcap
  e2ap_cu_up_filename: /tmp/gnb_cu_up_e2ap.pcap

metrics:
  layers:
    enable_rlc: true
    enable_sched: true
  periodicity:
    du_report_period: 1000
gnb_compose_config.yml:
  content: |
    cu_cp:
      amf:
        addr: ${OPEN5GS_IP:-10.53.1.2}
        bind_addr: ${GNB_IP:-10.53.1.3}
  metrics:
    autostart_stdout_metrics: true
    enable_json: true
  remote_control:
    bind_addr: 0.0.0.0
    enabled: true

volumes:
  gnb-storage:

networks:
  ran:
    ipam:
      driver: default
      config:
        - subnet: 10.53.1.0/24
  metrics:
    ipam:
      driver: default
      config:
        - subnet: 172.19.1.0/24
```

=== NOTAS (1785494454) ===

1. PLMN (21401) y TAC (7) actualizados en gNB y SUBSCRIBER_DB (REGLA 1).
2. Banda (78) y dl_arfcn (630000) actualizados en gNB y UE (REGLA 2).
3. IMSI, K y OPC actualizados en UE y SUBSCRIBER_DB (REGLA 7).
4. Bloque ru_sdr copiado exactamente del CAG (REGLA 6).
5. srates de 11.52e6 se mantiene en gNB y UE, a pesar de que 20MHz de ancho de banda con 15kHz SCS idealmente requiere
6. bind_addr en gnb_config.yml se mantiene en 10.53.1.1, siendo sobrescrito por gnb_compose_config.yml a \${GNB_IP:-10.