
BME 306 Lab 1 - introduction to discrete signals

Table of Contents


Question 2	1
Question 3	2
Question 4	2
Question 5	3
Question 6	5
Question 7	7
Question 8	9
Question 9	11

Alexander Ross 9/30/19

Question 2

Create a unit rectangle using the `rectpuls` command and plot it.

```
clear all;
close all;
clf;
figure(1); % start a new figure
t=-8:0.001:8; % define a time axis
s = rectpuls(t); % unit rectangle
plot(t,s); % create plot
grid on; % add grid lines
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label
title('1-2 plot'); % supply a figure title
```




Question 3

```
length(s);  
% The length is 16001  
index1 = find(t==0);  
% The index of the signal vector at t=0 is 8001
```

Question 4

```
figure(2); % start a new figure  
t=-8:0.1:8; % define a time axis  
s = rectpuls(t); % unit rectangle  
l=-8:1:8; % define a time axis  
g = rectpuls(l); % unit rectangle  
plot(l,g);  
hold on  
plot(t,s); % create plot  
grid on; % add grid lines  
axis([-8 8 -4 4]); % scale the display axes  
xlabel('time'); % supply a x-axis label  
ylabel('amplitude'); % supply a y-axis label  
title('1-2 plot'); % supply a figure title  
hold off
```

% As the number of discrete values in the 't' array decreases, the
% accuracy of each rect fucntion decreases as well. The more indexes
the
%'t' array has, the more close to the ideal rect function you will
get.




Question 5

```
clear all;  
close all;  
clf;  
figure(3);  
t=-8:0.001:8; % define a time axis  
s1 = rectpuls(t-2);  
s2 = rectpuls(2*t);  
s3 = 2*rectpuls(-t-2);  
s4 = -rectpuls(t) + 2;  
  
subplot(2,2,1); % create plot  
plot(t,s1);  
title('plot 1'); % supply a figure title  
axis([-8 8 -4 4]); % scale the display axes  
xlabel('time'); % supply a x-axis label  
ylabel('amplitude'); % supply a y-axis label  
  
subplot(2,2,2); % create plot
```

```
plot(t,s2);
title('plot 2'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,3); % create plot
plot(t,s3);
title('plot 3'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,4); % create plot
plot(t,s4);
title('plot 4'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label
```



Question 6

```
clear all;
close all;
clf;
figure(3);
t=-8:0.001:8; % define a time axis
syms x
s1 = heaviside(t); %step function 1
s2 = heaviside(t-2);
s3 = heaviside(-t);
s4 = -heaviside(t)+1;


subplot(2,2,1); % create plot
plot(t,s1);
title('plot 1'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,2); % create plot
plot(t,s2);
title('plot 2'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
```

```
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,3); % create plot
plot(t,s3);
title('plot 3'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,4); % create plot
plot(t,s4);
title('plot 4'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label
```



Question 7

```
clear all;
close all;
clf;
figure(4);
t=-8:0.001:8; % define a time axis
syms x
s1 = heaviside(t-2).*cos(2*pi*t);
s2 = rectpuls((t-2.5)/5).* sin(3*t+(pi*(1/6)));
s3 = cos(10*t)+2;
s4 = abs(cos(2*pi*6*t));


subplot(2,2,1); % create plot
plot(t,s1);
title('plot 1'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,2); % create plot
plot(t,s2);
title('plot 2'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
```

```
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,3); % create plot
plot(t,s3);
title('plot 3'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,4); % create plot
plot(t,s4);
title('plot 4'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label
```

Question 8

```
clear all;
close all;
clf;
figure(5);
t=-8:0.001:8; % define a time axis
syms x
s1 = square(2*pi*t*1/3); %square wave
s2 = sawtooth(2*pi*t*1/3); %sawtooth wave
s3 = square(2*pi*t*1/3,25); % rectangular wave with 25% duty cycle
s4 = sawtooth(2*pi*t*1/3,0.5); %triangle wave


subplot(2,2,1); % create plot
plot(t,s1);
title('plot 1'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,2); % create plot
plot(t,s2);
title('plot 2'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
```

```
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,3); % create plot
plot(t,s3);
title('plot 3'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label

subplot(2,2,4); % create plot
plot(t,s4);
title('plot 4'); % supply a figure title
axis([-8 8 -4 4]); % scale the display axes
xlabel('time'); % supply a x-axis label
ylabel('amplitude'); % supply a y-axis label
```



Question 9

% See attached file 'stimpulse.m' for Question 9

Published with MATLAB® R2019a

```
%The following code should be run in the editor:
%t = 0:0.00001:1;

function sigtot=stimpulse(t)

pps = 1000; % the number of pulses per second
syms x
w1 = 0.00004; %positive pulse width
w2 = 0.00004; %negative pulse width
duty1=w1*pps*100; %positive pulse duty
duty2=w2*pps*100; %negative pulse duty
sig1= (0.5)*square(2*pi*pps*t,duty1)+ 0.5; %positive part of the
    signal
sig2= (-0.5)*square(2*pi*pps*(t-w1),duty2) - 0.5; %positive part of
    the signal
sigtot = sig1 + sig2; %total signal output

end

%The following code should be run in the editor:
%t = 0:0.00001:1;
%plot(t,stimpulse(t));
%grid on;
%axis([0 1 0 1]);
%xlabel('time');
%ylabel('amplitude');
%title('1-2 plot');
```

Published with MATLAB® R2019a

