

# Numerical Methods ITGS219

## Lecture 2: Writing Scripts and Functions

*By: Zahra Abdalla Elashaal*

## Course Contents:

Chapter 1 Simple Calculations with Matlab.

Chapter 2 Writing Scripts and Functions.

Chapter 3 Loops and Conditional Statements.

Chapter 4 Root Finding.

Chapter 5 Interpolation and Extrapolation.

Chapter 6 Matrices.

Chapter 7 Numerical Integration.

Chapter 8 Solving Differential Equations.

Chapter 9 Simulations and Random Numbers.

Chapter 2 Writing Scripts and Functions.

1 Creating Scripts and Functions

1.1 Functions .

1.2 Brief Aside

2 Plotting Simple

2.1 Evaluating Polynomials and Plotting Curves

2.2 More on Plotting

3 Functions of Functions

4 Errors

4.1 Numerical Errors

4.2 User Error.

5 Tasks

# Creating Scripts and Functions

A script is simply a file containing the sequence of MATLAB commands which we wish to execute to solve the task at hand; in other words a script is a computer program written in the language of Matlab.

- To invoke the MATLAB editor we type *edit* at the prompt. This editor has the advantage of understanding MATLAB syntax and producing automatic formatting.

**Example:** We begin by entering and running the code:

```
a = input('First number ');
b = input('Second number ');
disp([' Their sum is ' num2str (a+b)])
disp([' Their product is ' num2str (a*b)])
```

We shall create our first script and save it in a file named *twonums.m*.

MATLAB will have given this code the default name *Untitled.m*.

To execute the file *twonums* enter its name at the prompt of the command window

contents of the file can be displayed by typing *type twonums*.

Example has three new commands, *input*, *num2str* and *disp*

The input command prompts the user with the flag contained within the quotes ' ' and takes the user's response from the standard input,

The second command num2str stands for number-to-string

This is then displayed using the *disp*.

# Creating Scripts and Functions

Use either the command *help* or the command *which* in combination with the *filename*, for instance *help load* or *which load* for the Matlab command load.

to check that you are in the correct directory use the command *pwd* to 'print working directory'

You can also list the files in the current directory by typing *dir* or alternatively all the available MATLAB files can be listed by using *what*. for more details see *help what*.

**Example:** If we create a MATLAB file called *power.m* using the editor it can be saved in the current directory: however the code will not work. The reason for this can be seen by typing *which power* which produces the output

```
>> which power
```

```
power is a built-in function.
```

*So MATLAB will try to run the built-in function.*

## Important Point

- It is very important you give your files a meaningful name and that the files end with *.m*.
- You should avoid using filenames which are the same as the variables you are using and which coincide with Matlab commands.
- Make sure you do not use a dot in the body of the filename and that it does not start with a special character or a number.

# Functions

Functions are codes take inputs and return outputs.

As the next example and we will save as *xsq.m*.

```
function [output] = xsq(input)
output = input.^ 2;
```

The variables *input* and *output* are local variables that are used by the function; they are not accessible to the general Matlab workspace.

- The first line of *xsq.m* tells us this is a function called *xsq* which takes an input called *input* and returns a value called *output*. The input is contained in **round brackets**, and the output is contained within **square brackets**. It is crucial for good practice that the name of the **function *xsq*** corresponds to the name of the file *xsq.m* (without the .m extension).
- The second line is to calculate the square of the value of the input, and storing this result in the variable *output*. Notice that the function uses dot arithmetic *.^* so that this function will work with both vector and matrix inputs (performing the operation **element by element**).

```
>> x = 1:10;
>> y = xsq(x)
```

```
>> A = [1 2 3 4 5 6];
>> y = xsq(A)
y = 1 4 9 16 25 36
```

You can know about variables by typing:  
*who*, which lists all variables in use, or  
*whos*, which lists all variables along with size and type.

# Functions

**Example** Suppose we want to plot contours of a function of two variables  $z = x^2 + y^2$ . We can use the code


```
function [output] = func (x, y)
output = x.^2 + y.^2;
```

should be saved in the file *func.m*.

the vectors *x* and *y* must have the same size

To plot the contours (that is the level curves) of the function

```
x = 0.0:pi/10:pi;
y = x;
[X,Y] = meshgrid(x,y);
f = func(X,Y);
contour(X,Y,f)
axis([0 pi 0 pi])
axis equal
```



# Functions

**Example** Suppose we now want to construct the squares and cubes of the elements of a vector.

```
function [sq, cub] = xpowers (input)
sq = input.^2;
cub = input.^3;
```

This function file must be saved as *xpowers.m* and it can be called as follows:

```
x = 1:10;
[xsq, xcub] = xpowers (x);
```

**Notice that:** when the function is called we must know what form of output we expect, whether it be a scalar, a vector or a matrix. The expected outputs should be placed within square brackets.

**Example** a function can have multiple inputs and outputs:

```
function [out1,out2] = multi(in1,in2,in3)
out1 = in1 + max(in2,in3);
out2 = (in1 + in2 + in3)/3;
```

```
x1 = 2; x2 = 3; x3 = 5;
[y1, y2] = multi(x1,x2,x3);
y1, y2
```

For this example we obtain y1=7 and y2=3.3333.

**Example** Consider a code which returns a scalar result from a vector input.

```
function [output] = sumsq(x)
output = sum(x.^2);
```

```
x = [1 2 4 5 6];
y = sumsq(x)
```

sets y equal to the scalar  $1^2 + 2^2 + 4^2 + 5^2 + 6^2 = 82$ .

## Brief Aside

Work with matrices in the previous example will also work with matrices:

```
>> A=[1 2 3; 4 5 6];
>> sumsq(A)
ans = 17 29 45
```

This has exploited the property that the sum command sums the columns of a matrix. If we want to sum the rows of a matrix we use `sum(A,2)`, so that we have

```
>> sum(A,1) % which is equivalent to sum(A)
ans = 5 7 9
>> sum(A,2) % to sum each row in (A)
ans = 6
15
```

# Plotting Simple Functions

We start with the simplest command **plot** and use this as an opportunity to revisit the ways in which functions can be initialized. We start with initializing an array, in this case  $x$

```
x = 0:pi/20:pi;
```

which as we know sets up a vector whose elements are (that is, a vector whose elements range from 0 to  $\pi$  in steps of  $\pi/20$ ).


the command **size(x)** gives the array size 1x21 and the command **length(x)** (gives the maximum of the dimensions of a matrix).

We can plot simple functions, as:

```
plot(x, sin(x))
```

or more complicated examples such as:

```
plot(x, sin(3*x), x, x.^2.*sin(3*x)+cos(4*x))
```



Try these


```
y = 3*x-1;
plot(x,y)
```

```
y = x.^2+3;
plot(x,y)
```

# Plotting Simple Functions

**Example** To plot the quadratic  $x^2+7x-3$  from  $x$  equals  $-3$  to  $3$  in steps of  $0.2$  we use the code.

```
x = -3:0.2:3;
y = x.^2+7*x-3;
grid on
plot(x,y)
```




**Example** Consider the code:.

Greek letters, using the LATEX construction  $\alpha$  for  $\alpha$  and  $\beta$  for  $\beta$ .

```
x = 0:pi/20:pi;
n = length(x);
r = 1:n/7:n;
y = x.^2+3;
plot(x,y,'b',x(r),y(r),'r*')
axis([-pi/3 pi+pi/3 -1 15])
xlabel('x values')
ylabel('Function values')
title('Demonstration plot','FontSize',24)
text(pi/10,0,'\alpha=\beta^2')
```

**Demonstration plot**






## Plotting Simple Functions

There are a wide of other plotting options available. like *loglog(x,y)* produces a log-log plot. Similarly *semilogx* and *semilogy* produces a log plot for the x and y-axis, respectively.

You should also be aware of the commands *clf* which clears the current figure and *hold* which holds the current figure.

The excellent features of MATLAB is the way in which it handles **two** and **three-dimensional** graphics.

```
x = linspace(-pi/2,pi/2,40);
y = x;
[X,Y] = meshgrid(x,y);
f = sin(X.^2-Y.^2);
figure(1)
contour(X,Y,f)
figure(2)
contourf(X,Y,f,20)
figure(3)
surf(X,Y,f)
```



## Evaluating Polynomials and Plotting Curves

**Example** a code to generate the value of a specific quadratic  $x^2 + x + 1$  at a specific point:

```
x = 3;
y = x^2+x+1;
disp(y)
```

In general suppose we have the general quadratic  $y = a_2x^2 + a_1x + a_0$ .

The script to calculate this equation will call *quadratic.m*

**Note** it is also possible to obtain a complete listing of the code by typing *type quadratic* at the prompt.

There are many ways of writing polynomials, for instance this could have been written recursively as  $a_0 + x(a_1 + xa_2)$ .

```
% quadratic.m
% This program evaluates a quadratic
% at a certain value of x
% The coefficients are stored in a2, a1 and a0.
```

```
str = 'Please enter the ';
a2 = input([str 'coefficient of x squared: ']);
a1 = input([str 'coefficient of x: ']);
a0 = input([str 'constant term: ']);
x = input([str 'value of x: ']);
y = a2*x*x+a1*x+a0;
% Now display the result
disp(['Polynomial value is: ' num2str(y)])
```

by typing *help quadratic* at the Matlab prompt to produce:

```
quadratic.m
This programme evaluates a quadratic
at a certain value of x
The coefficients are stored in a2, a1 and a0.
```

# Evaluating Polynomials and Plotting Curves

**Example** we want to evaluate the quadratic  
 $y = 3x^2 + 2x + 1$ . We could then use the function


```
% evaluate_poly.m
%
function [value] = evaluate_poly(x)
value = 3*x.^2+2*x+1;
```

Now we can use the function *evaluate\_poly*, in the  
 form `evaluate_poly(2)` or  
`x = 2; y = evaluate_poly(x).`

**Note:** within Matlab we are able to call a function  
 with a variety of different inputs; whether this is valid  
 depends upon the structure of the function.  
 This is similar to the idea of **overloading** which is in  
 the object orientated languages like C++ and Java.

we can now use our function to generate a **vector**  
 containing the polynomial values for **x** vector.

```
>> x = -5:0.5:5;
>> y = evaluate_poly(x);
>> plot(x,y)
```



## More on Plotting

Here we extend our plotting capability by  
 considering the impact of a **third argument** of  
 the plot command, such as in `plot(x,y,'r')`.

The colour options are

|          |           |
|----------|-----------|
| y yellow | m magenta |
| c cyan   | r red     |
| g green  | b blue    |
| w white  | k black   |

the choice of **symbols** are

|           |                    |
|-----------|--------------------|
| . point   | v triangle (down)  |
| o circle  | X triangle (up)    |
| x x-mark  | < triangle (left)  |
| + plus    | > triangle (right) |
| * star    | p pentagram        |
| s square  | h hexagram         |
| d diamond |                    |

|             |
|-------------|
| - solid     |
| : dotted    |
| - . dashdot |
| - - dashed  |

It is possible to control the **line**  
**style**. By drawing the line using  
 one of the previous options:


plot more than one curve on the same graph.

**First way**

```
>>x = -pi:pi/20:pi;
>>plot(x,sin(x),'r-',x,cos(x),'b-.')
```

**Second way**

```
x = -pi:pi/20:pi;
clf
plot(x,sin(x),'r-')
hold on
plot(x,cos(x),'b-.')
hold off
legend('sine','cosine')
```



see *help legend* for details.


## More on Plotting

we have already seen that if the function is called with a vector then the “output” is a vector..

Consider the following

```
% evaluate_poly2.m
function [f, fprime] = evaluate_poly2(x)
f = 3*x.^2+2*x+1;
fprime = 6*x+2;
```

```
x = -5:0.5:5;
[func,dfunc] = evaluate_poly2(x);
plot(x,func,'r-',x,dfunc,'b-.')
```



We can further generalize our code by passing the coefficients of the quadratic to the function, either as individual values or a vector.

```
% evaluate_poly3.m
function [f, fprime] = evaluate_poly3(a, x)
f = a(1)*x.^2+a(2)*x+a(3);
fprime = 2*a(1)*x+a(2);
```

```
x = -5:0.5:5;
a = [3 2 1];
[f, fp] = evaluate_poly3(a, x);
```

**Note:** `evaluate_poly3(a,x)` was the same as built-in function, called `polyval`, which also evaluates polynomials.

`help polyval` gives more information

## Functions of Functions:

- One MATLAB command which provides us with considerable freedom in writing versatile code is the command `feval` which loosely translates as *function evaluation*.
- The simplest use for this command is

```
y = feval('sin',x);
```

- evaluate the function `sin` at `x`. This is equivalent to `sin(x)`. In general the arguments for `feval` are the **name of the function**, which must be either a MATLAB built-in function or a user defined function, contained between quotes, and **the value** (or values in the case of a vector) at which the function is to be evaluated.
- Consider the function  $h(x) = 2\sin^2 x + 3\sin x - 1$ .

- One way of writing code that would evaluate this function is

```
function [h] = fnc(x)
h = 2*sin(x).*sin(x)+3*sin(x)-1
```

- However we can recognize this function as a composition of two functions

$$g(x) = \sin(x) \text{ and } f(x) = 2x^2 + 3x - 1 \text{ so that } h(x) = f(g(x))$$

- We can easily write a function file `f.m` to evaluate `f(x)`

```
function [y] = f(x)
y = 2*x.^2+3*x-1;
```



## Functions of Functions:


- To use this in calculating the value of the composite function  $h(x)$  we *need to be* able to pass the function name to `f` as an argument. We can do this with the following modification to our code

```
function [y] = f(fname,x)
z = feval(fname,x);
y = 2*z.^2+3*z-1;
```

- Calculating the function  $h(x)$  is now as simple as

```
x = -pi:pi/20:pi;
y = f('sin',x);
plot(x,y)
```

- This gives a plot of the function  $h(x)$  as




## Functions of Functions:

A more useful example is given by the function *plotf*

```
function plotf(fname, x)
y = feval(fname, x)
plot(x,y)
grid on
axis([min(x) max(x) min(y) max(y)])
xlabel('x')
ylabel([fname '(x)'])
```

- This function takes as input a function name and a vector `x` and produces a labeled plot. Notice although there are two inputs for this function there are no values output; the figure is the output.



The background of the slide is a light blue gradient. It is decorated with several realistic water bubbles of different sizes, some with highlights and shadows, scattered in the corners and along the bottom edge.

# Any Question?