

University of Tripoli Faculty of Information Technology

Department of Software Engineering



CSS3 BASICS (3)

Introduction to Internet Programming ITGS 226 -- S 2022

By: Fatima Ben Lashihar

CSS3 BOX MODEL



 The CSS box model is essentially a box that wraps around every HTML element. It consists of: margins, borders, padding, and the actual content.

Margin Border Padding Content

Where:

Content - The content of the box, where text and images appear

Padding - Clears an area around the content.

Border - A border that goes around the padding and content

Margin - Clears an area outside the border.

CSS3 PADDING



- · Padding is used to create space around an element's content, inside of any defined borders.
- Padding properties can have the following values: specify it in px or % that specifies a padding of the width of the containing element.

```
div {
      padding: 25px 50px 75px 100px;
```

Where top padding is 25px, right padding is 50px, bottom padding is 75px and left padding is 100px

3

CSS Border - Shorthand Property



- The border property is a shorthand property for the following individual border properties:
 - border-width
 - border-style (required)
 - border-color

```
p {
      border: 5px solid red;
```

 Where The border-style property may one of the following values: solid, dotted, dashed, none or hidden.

CSS3 MARGINS



- Margins are used to create space around elements, outside of any defined borders.
- margin properties can have the following values: auto or specify it in px or % that specifies a margin of the width of the containing element.

Where top margin is 25px, right margin is 50px, bottom margin is 75px and left margin is 100px.

5

CSS BACKGROUND



- CSS provide several properties for styling the background of an element.
- The background-color property is used to set the background color of an element .

CSS3 TEXT



- Text Color ---- color
- CSS Text Alignment ---- text-align
- Text Direction --- direction
- CSS Text Decoration --- decoration
- CSS Text Transformation --- text-transform

```
h1 {
  color: blue;
  text-align: left | right | center | justify;
  direction: rtl | ltr;
  text-decoration: none | underline| line-through;
  text-transform: none | capitalize | uppercase | lowercase;
}
```

7

CSS3 FONTS



- CSS font-family --- font-family
- CSS Font Style --- font-style
- CSS Font Weight --- font-weight
- CSS Font Size --- font-size

```
.p1 {
  font-family: "Times New Roman", Times, serif;
  font-style: normal | italic;
  font-weight: normal | bold;
  font-size: 40px;
}
```

• The default size for normal text, like paragraphs, is 16px .

CSS3 LINKS



- The four links states are:
 - a:link a normal, unvisited link
 - a:visited a link the user has visited
 - a:hover a link when the user mouses over it
 - a:active a link the moment it is clicked
- Note: Arrange as this: a:link, a:visited, a:hover and a:active.
- All links in HTML are underlined by default. Sometimes you see that links are styled with no underline. The text-decoration: none; is used to remove the underline from links.

9

CSS3 list-style-type Property



CSS3 TABLES PROPERTIES



- borde: Sets all the border properties in one declaration
- border-collapse: Specifies whether or not table borders should be collapsed

```
table, th, td {
                border: 1px solid;
}
```

 Notice that the table in the examples above have double borders. This is because both the table and the and elements have separate borders. To remove double borders, take a look at the example below.

```
table, td, th {
        border: 1px solid;
}
table {
        border-collapse: collapse;
}
```

〔 11〕

DEMOS



CSS3 BASICS – DEMOS

https://www.w3schools.com/cssref/playdemo.asp?filenam e=playcss_vertical-align&preval=text-bottom

