ISA Groupe G

Pierre-Alexandre Bazin, Mathis Bouverot & Arthur Rousseau

1 Mémoire

La RAM et la ROM sont sur 2^{16} bits, avec donc des adresses sur 16 bits. Les entiers manipulés seront toujours signés et sur 16 bits.

2 Registres

Il y a 8 registres nommés rax, rbx, rcx, rdx, rex, rfx, rgx, rz (registre nul).

Ces registres sont sur 16 bits.

Codage des registres :

rz	rax	rbx	rcx	rdx	rex	rfx	rgx
000	001	010	011	100	101	110	111

3 Instructions

Les instructions sont sur 32 bits. Leur schéma est le suivant :

	imm	funct7	funct3	rs2	rs1	rd	opcode	
--	-----	--------	--------	-----	-----	----	--------	--

avec

- opcode sur 3 bits
- funct3 sur 3 bits
- \bullet funct7 sur 1 bit
- rd, rs2, rs1 sur 3 bits (8 registres)
- \bullet imm sur 16 bits

$Instructions\ possibles:$

Inst	Nom	Opcode	funct3	funct7	Description
add	ADD	011	000	0	rd = rs1 + rs2
sub	SUB	011	000	1	rd = rs1 - rs2
or	OR	011	100	0	rd = rs1 or rs2
nand	NAND	011	100	1	rd = rs1 nand rs2
xor	XOR	011	001	0	rd = rs1 xor rs2
nxor	NXOR	011	001	1	rd = rs1 nxor rs2
and	AND	011	101	0	rd = (rs1 and rs2)
nor	NOR	011	101	1	rd = rs1 nor rs2

		011	011	1 0		
sll	Shift left logical	011	011	0	rd = rs1 « rs2	
srl	Shift right logical	011	010	0	rd = rs1 » rs2	
sra	Shift right Arith	011	010	1	rd = rs1 » rs2	
seq	Set equal	011	111	1	rd = (rs1 = rs2)?1:0	
slt	Set less than	011	110	1	rd = (rs1 < rs2)?1:0	
addi	ADD (immediate)	001	000	0	rd = rs1 + imm	
subi	SUB (immediate)	001	000	1	rd = rs1 - imm	
ori	OR (immediate)	001	100	0	rd = rs1 or imm	
nandi	NAND (immediate)	001	100	1	rd = rs1 nand imm	
xori	XOR (immediate)	001	001	0	rd = rs1 xor imm	
nxori	NXOR (immediate)	001	001	1	rd = rs1 nxor imm	
andi	AND (immediate)	001	101	0	rd = rs1 and imm	
nori	NOR (immediate)	001	101	1	rd = rs1 nor imm	
slli	Shift left logical (immediate)	001	011	0	rd = rs1 « imm	
srli	Shift right logical (immediate)	001	010	0	rd = rs1 » imm	
srai	Shift right Arith (immediate)	001	010	1	rd = rs1 » imm	
seqi	Set equal (immediate)	001	111	1	rd = (rs1 = imm)?1:0	
slti	Set less than (immediate)	001	110	1	rd = (rs1 < imm)?1:0	
lw	Load word	000	000	0	rd=M[rs1]	
sw	Store word	010	000	0	M[rs1]=rs2	
beq	Branch ==	110	100	1	if(rs1 == rs2) PC=imm	
bne	Branch!=	110	101	1	if(rs1 != rs2) PC=imm	
ble	Branch ≤	110	110	1	if(rs1 <= rs2) PC=imm	
blt	Branch <	110	010	1	if(rs1 < rs2) PC=imm	
bge	Branch ≥	110	011	1	if(rs1 >= rs2) PC=imm	
bgt	Branch >	110	111	1	if(rs1 > rs2) PC=imm	
jal	Jump and link	111	000	0	rd=PC+4; PC=imm	
jalr	Jump and link reg	101	000	0	rd=PC+4; PC=rs1	
jr	Jump reg	100	000	0	PC=rs1	
jmp	Jump	110	001	1	PC=imm	

On ajoute du sucre syntaxique:

Inst	Nom	Description
mov	MOV	rd=rs1+0
movi	MOV (immediate)	rd=imm+0