



Institut
Mines-Telecom

INFMDI 341 Advanced Machine Learning, Semi-supervised learning

Florence d'Alché-Buc,
florence.dalche@telecom-paristech.fr





Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References

Learning from unlabeled data


Unlabeled data

- ▶ Available data are unlabeled : documents, webpages, clients database ...
- ▶ Labeling data is expensive and requires some expertise

Learning from unlabeled data

- ▶ Modeling probability distribution → graphical models
- ▶ Dimension reduction → pre-processing for pattern recognition
- ▶ **Clustering** : group data into homogeneous clusters → organize your data, make easier access to them, pre and post processing, application in segmentation, document retrieval, bioinformatics ...

Different clusterings



Learning from labeled and unlabeled data

Semi-supervised learning

- ▶ Benefit from the availability of huge sets of unlabeled data
- ▶ Unlabeled data inform us about the probability distribution of the data $p(x)$
- ▶ Can we use it ? does it improve the performance of the resulting regressors/classifiers ?

Semi-supervised learning

Goal

- ▶ Labeled data : $\mathcal{S}_\ell = \{(x_1, y_1), \dots, (x_\ell, y_\ell)\}$
- ▶ Unlabeled data : $\mathcal{X}_u = \{x_{\ell+1}, \dots, x_{\ell+u}\}$, $n = \ell + u$: available during training!
- ▶ Usually $\ell \ll u$
- ▶ Test data : $\mathcal{X}_{test} = \{x_{n+1}, \dots, x_{n+m}\}$: not available during training
- ▶ **Learn a function $f : \mathcal{X} \rightarrow \mathcal{Y}$ (regression/classification) that behaves well on test data**



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References

Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References


Data as nodes in a graph

- ▶ Data x_1, \dots, x_n with their similarity values $s_{ij} \geq 0$ or with their distance d_{ij} values
- ▶ Build a graph $G = (V, E)$
- ▶ vertex v_i corresponds to data x_i
- ▶ An edge w_{ij} is defined according the ϵ -graph method or the k -nn method


Importance of the initial graph

Several ways to construct adjacency matrix W from similarity matrix S :

- ▶ ϵ -graph : connect all points whose pairwise distance is at most ϵ (alt. whose pairwise similarity is at least ϵ)
- ▶ k -nearest-neighbour-graph : connect v_i and v_j if x_i is among the k -nearest-neighbours of x_j OR x_j is among the k -nearest-neighbours of x_i




Importance of the initial graph



Clustering as a graph cut

Input of the learning algorithm : adjacency matrix W

Output : a partition into two clusters



► $Cut(A, \bar{A}) = \sum_{i \in A, j \in \bar{A}} w_{ij}$

Graph notions

Definitions

- ▶ W matrix : adjacency matrix
- ▶ Degree matrix D : $d_{ii} = \sum_j w_{ij}$, if $i \neq j$, $d_{ij} = 0$
- ▶ Graph Laplacian : $L = D - W$

Graph Laplacian Properties

Eigenvalues/eigenvectors

- ▶ Eigenvector u : $Lu = \lambda u$
- ▶ We notice that $(D-W) \mathbf{1}_n = D \cdot \mathbf{1}_n - W \cdot \mathbf{1}_n = 0$, then the smallest eigenvalue is $\lambda_1 = 0$

Graph Laplacian Properties

Connected components

- ▶ The multiplicity of the smallest eigenvalue (0) of L is the number of connected components in the graph

$$L = \begin{pmatrix} L_1 & & & \\ & L_2 & & \\ & & \ddots & \\ & & & L_k \end{pmatrix}$$

Two-ways Spectral clustering

Clustering with Laplacian graph

- ▶ $f_i, i = 1, \dots, n$: membership of data i to cluster 1
- ▶ $f_i = 1$ if $x_i \in \text{Cluster1}(A)$, -1 otherwise Cluster 2 (\bar{A})
- ▶ Find f that minimizes $J(f)$:

$$\begin{aligned} J(f) &= \frac{1}{4} \sum_{i,j} w_{ij} (f_i - f_j)^2 \\ &= \frac{1}{4} \sum_{i,j} w_{ij} (f_i^2 + f_j^2 - 2f_i f_j) \\ &= \frac{1}{2} f^T (D - W) f \end{aligned}$$

Two-ways spectral clustering

- ▶ Avoid trivial solution : $f \perp 1_n$
- ▶ Control the complexity of f (ℓ_2 regularization) : $\sum_i f_i^2 = n$

$$\min_{f \in \mathbb{R}^n} f^T L f$$

$$\text{subject to : } f \perp 1, \|f\| = \sqrt{n}$$

Two-ways spectral clustering

- ▶ Solve the previous relaxed problem \rightarrow the vector corresponding to the second smallest eigenvalue is solution
- ▶ Threshold the values of f to get discrete values 1 and -1

k-ways spectral clustering

Algorithm

- ▶ Solve the previous relaxed problem \rightarrow take the k eigenvectors (v_1, \dots, v_k) corresponding to the k smallest positive eigenvalues
- ▶ Represent your data in the new space spanned by these k vectors : form the matrix V with the v_k 's as column vectors
- ▶ each row of V represents an individual
- ▶ Apply k -means in the k -dimensional space

Normalized cut

- ▶ Notations : A and B are two disjoint subsets of the nodes set V that form a partition
- ▶ $cut(A, B) = \sum_{t \in A, u \in B} w_{t,u}$
- ▶ $vol(A) = \sum_{t \in A, u \in V} w_{t,u}$
- ▶ Normalized cut (avoid isolated subset) :
$$Ncut(A, B) = \frac{cut(A, B)}{vol(A)} + \frac{cut(B, A)}{vol(B)}$$

$$\min_{f \in \mathbb{R}^n} \frac{f^T L f}{f^T D f}$$

subject to : $f^T D 1 = 0$


Solve the generalized eigenvalue problem :

$(D - W)f = \lambda Df$ which can be re-written as $D^{-\frac{1}{2}}(D - W)D^{-\frac{1}{2}}z = \lambda z$ with $z = D^{-\frac{1}{2}}f$.

Properties of spectral clustering

- ▶ Importance of the initial graph : several ways to construct it (k-neighbours)
- ▶ Able to extract clusters on a manifold
- ▶ Stability
- ▶ Model selection : eigengap

Difficult clustering tasks



► Figure from scikitlearn :

► code : `spectral = cluster.SpectralClustering(n_clusters = 2, eigen_solver = 'arpack', affinity = "nearest_neighbors")`

Eigengap heuristic




Figure 4: Three data sets, and the smallest 10 eigenvalues of L_{rw} .

► Source Tutorial U. Von Luxburg

Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References

Semi-supervised methods

- ▶ Learn f from \mathcal{X} to \mathcal{Y} using $\mathcal{S}_\ell = \{(x_1, y_1), \dots, (x_\ell, y_\ell)\}$ and $\mathcal{X}_u = \{x_{\ell+1}, \dots, x_{\ell+u}\}$
- ▶ Methods
 - ▶ Self-training (including generative approaches)
 - ▶ Loss-based methods
 - ▶ Margin for unlabeled data
 - ▶ Smoothness penalty (graph-based semi-supervised learning)

Self-training

- Any classifier : f


Principle

1. $k=0$
2. Learn f_k by training on $\mathcal{S}_k = \mathcal{S}$
3. Use f to label \mathcal{X}_u and get \mathcal{S}_{k+1} new set of $\ell + u$ labeled data
4. Learn f_{k+1} by training on \mathcal{S}_{k+1}
5. If $D(f_{k+1}, f_k)$ is small then STOP else GOTO 3


Self-training : example with k-NN (1)

- Two nice clusters without outliers [example Piyush Ray]



Base learner: KNN classifier



(a) Iteration 1







(b) Iteration 25



Self-training : example with k-NN (2)

- Two clusters with outliers



Semi-supervised learning with margin maximization


- ▶ Margin : $\rho(x, y, h) = y \cdot h(x)$
- ▶ Which margin for unlabeled data ?
- ▶ Reinforce the confidence of the classifier
 - ▶ $\rho_2(x, h) = h(x)^2$
 - ▶ $\rho_1(x, h) = |h(x)|$
 - ▶ **Implicit assumption** : cluster assumption : data in the same cluster share the same label
- ▶ Worked for SVM, MarginBoost, ...

Semi-supervised MarginBoost

- ▶ $h_t \in \mathcal{H}$: base classifier
- ▶ Boosting model : $H_T(x) = \sum_t \alpha_t h_t(x)$
- ▶ Loss function : $J(H_t) = \sum_{i=1}^{\ell} \exp(-\rho(x_i, y_i, H_t)) + \lambda \sum_{j=\ell+1}^n \exp(-\rho_u(x_j, H_t))$


Semi-supervised MarginBoost

- Toys problems with different level of difficulty (we control Bayes error by mixing more or less the generative models)



[figure : NIPS 2001]

Data used in the previous sample



Transductive Support Vector Machine (Joachims)

In transduction, one wants to predict the outputs of the test set $y_{\ell+1}, \dots, y_{\ell+u}$. Let us call $\mathbf{y}^* = [y_1^*, \dots, y_u^*]$ the prediction vector. Joachims proposed a Transductive SVM with a soft margin :

TSVM

$$\underset{\mathbf{w}, y^*, b}{\text{minimize}} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{i=1}^{\ell} \xi_i + C^* \sum_{j=1}^u \xi_j^*$$

under the constraints

$$y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1 - \xi_i, \quad i = 1, \dots, n$$

$$y_j^*(\mathbf{w}^T \mathbf{x}_{\ell+j} + b) \geq 1 - \xi_j^*, \quad i = 1, \dots, n$$

$$y_j^* \in \{-1, +1\}, \quad j = 1, \dots, u$$

Semi-supervised Support Vector Machine (S3VM)

- ▶ Bennet and Demiriz 1999, 2001
- ▶ Bennet and Demiriz proposed $\rho_1(x, h) = |h(x)|$ and an implementation of S3VM based on Mangasarian's work.
- ▶ Robust Linear Programming

Semi-supervised Support Vector Machine (S3VM) 1/2

SVM formulation :

$$\begin{aligned} \min_{w, b, \eta} \quad & C \sum_{i=1}^t \eta_i + \frac{1}{2} \|w\|^2 \\ \text{s.t.} \quad & y_i [wx_i - b] + \eta_i \geq 1 \\ & \eta_i \geq 0, i = 1, \dots, l \end{aligned}$$

Semi-supervised Support Vector Machine (S3VM) 2/2

S3VM formulation (Bennet and Demiriz) :

$$\begin{aligned} \min_{\mathbf{w}, b, \eta, \xi, z} \quad & C \left[\sum_{i=1}^{\ell} \eta_i + \sum_{j=\ell+1}^{\ell+k} \min(\xi_j, z_j) \right] + \|\mathbf{w}\| \\ \text{subject to} \quad & y_i(\mathbf{w} \cdot \mathbf{x}_i + b) + \eta_i \geq 1 \quad \eta_i \geq 0 \quad i = 1, \dots, \ell \\ & \mathbf{w} \cdot \mathbf{x}_j - b + \xi_j \geq 1 \quad \xi_j \geq 0 \quad j = \ell + 1, \dots, \ell + k \\ & -(\mathbf{w} \cdot \mathbf{x}_j - b) + z_j \geq 1 \quad z_j \geq 0 \end{aligned}$$

With integer variables $d_j = 0 \text{ or } 1$ according it belongs to class 1 or class -1 (d has to be learned as well) :

$$\begin{aligned} \min_{\mathbf{w}, b, \eta, \xi, z, d} \quad & C \left[\sum_{i=1}^{\ell} \eta_i + \sum_{j=\ell+1}^{\ell+k} (\xi_j + z_j) \right] + \|\mathbf{w}\| \\ \text{subject to} \quad & y_i(\mathbf{w} \cdot \mathbf{x}_i - b) + \eta_i \geq 1 \quad \eta_i \geq 0 \quad i = 1, \dots, \ell \\ & \mathbf{w} \cdot \mathbf{x}_j - b + \xi_j + M(1 - d_j) \geq 1 \quad \xi_j \geq 0 \quad j = \ell + 1, \dots, \ell + k \\ & -(\mathbf{w} \cdot \mathbf{x}_j - b) + z_j + Md_j \geq 1 \quad z_j \geq 0 \quad d_j = \{0, 1\} \end{aligned}$$

Mixed integer programming.

Semi-supervised learning with a smoothness constraint

Let k be a positive definite kernel and \mathcal{H}_k the unique RKHS induced by k .

Smoothness constraint / Manifold regularization 1/2


- ▶ Training data : $\mathcal{S}_\ell = \{(x_i, y_i, i =, \dots \ell\}$ and $\mathcal{S}_u = \{x_{\ell+1}, \dots, x_{\ell+u}\}$
- ▶ For $f \in \mathcal{H}_k$ and W a similarity matrix between data
- ▶ Impose an additional penalty that ensures smoothness of function f : for two close inputs, f takes close values
- ▶ Ref : Belkin, Nyogi and Sindwani (2006)

How to use the geometry of the marginal distribution P_x ?

The key ideas :

- ▶ We assume that a better knowledge of the marginal distribution $P_x(x)$ will give us better knowledge of $P(Y|x)$.
- ▶ If two points x_1 and x_2 are close in the intrinsic geometry of P_x then the conditional distribution $P(y|x_1)$ and $P(y|x_2)$ will be close.

Manifold regularization



- If , the support of P_x is a submanifold $\subset \mathbb{R}^p$, then we can try to minimize the penalty :

$$\|f\|_l^2 = \int \|\nabla f\|^2 p(x) dx$$

- ∇f is the gradient of f along the manifold
- Approximation of $\|f\|_l^2$:

$$\|f\|_l^2 \approx \sum w_{ij} (f(x_i) - f(x_j))^2,$$

Semi-supervised learning with a smoothness constraint 2/2

Let k be a positive definite kernel and \mathcal{H}_k the unique RKHS induced by k .

Smoothness constraint / Manifold regularization

Minimize $J(f)$ in \mathcal{H}_k :

$$J(f) = \frac{1}{\ell} \sum_{i=1}^{\ell} V(x_i, y_i, f) + \lambda \|f\|_k^2 + \lambda_u \sum_{ij} w_{ij} (f(x_i) - f(x_j))^2$$

Semi-supervised learning with a smoothness constraint 2/2

Let k be a positive definite kernel and \mathcal{H}_k the unique RKHS induced by k .

Smoothness constraint / Manifold regularization

Minimize $J(f)$ in \mathcal{H}_k :

$$\begin{aligned} J(f) &= \frac{1}{\ell} \sum_{i=1}^{\ell} V(x_i, y_i, f) + \lambda \|f\|_k^2 + \lambda_u \sum_{ij} w_{ij} (f(x_i) - f(x_j))^2 \\ &= \frac{1}{\ell} \sum_{i=1}^{\ell} V(x_i, y_i, f) + \lambda \|f\|_k^2 + \lambda_u f^T L f \end{aligned}$$

Representer theorem

$$\begin{aligned} J(f) &= \frac{1}{\ell} \sum_{i=1}^{\ell} V(x_i, y_i, f) + \lambda \|f\|_k^2 + \lambda_u \sum_{ij=1}^{\ell+u} w_{ij} (f(x_i) - f(x_j))^2 \\ &= \frac{1}{\ell} \sum_{i=1}^{\ell} V(x_i, y_i, f) + \lambda \|f\|_k^2 + \lambda_u f^T L f \end{aligned}$$

Any minimizer of $J(f)$ admits a representation

$$\hat{f}(\cdot) = \sum_{i=1}^{\ell+u} \alpha_i k(x_i, \cdot)$$

Laplacian Regularized Least Square regression

- Closed-form solution : extension of ridge regression

$$V(x_i, y_i, f) = (y_i - f(x_i))^2$$
$$\lambda_L = \frac{\lambda_u}{u + \ell}$$
$$\hat{\alpha} = (JK + \lambda \ell Id + \frac{\lambda_u \ell}{(u + \ell)^2} LK)^{-1} Y$$

K : Gram matrix for all data

J : $(\ell + u) \times (\ell + u)$ diagonal matrix with the first ℓ values equal to 1 and the remaining ones to 0.

Laplacian SVM

We choose the hinge loss functions :

$$\min_{f \in \mathcal{H}_k} \frac{1}{\ell} \sum_{i=1}^{\ell} (1 - y_i f(x_i))_+ + \lambda \|f\|_k^2 + \frac{\lambda_u}{u + \ell} f^T L f$$

We benefit from the representer theorem.


Laplacian SVM

In practise, we solve :

$$\begin{aligned} \min_{\alpha \in \mathbb{R}^{l+u}, \xi \in \mathbb{R}^l} \quad & \frac{1}{l} \sum_{i=1}^l \xi_i + \gamma_A \alpha^T K \alpha + \frac{\gamma_l}{(u+l)^2} \alpha^T K L K \alpha \\ \text{subject to: } & y_i \left(\sum_{j=1}^{l+u} \alpha_j K(x_i, x_j) + b \right) \geq 1 - \xi_i, \quad i = 1, \dots, l \\ & \xi_i \geq 0 \quad i = 1, \dots, l. \end{aligned}$$

Laplacian SVM :results

Results : Belkin et al. 2006, JMLR.



When does semi-supervised learning work ?

- ▶ Clustering condition : if data comes from different clusters or can be easily clustered and you have one labeled data per cluster, these approaches will work
- ▶ Otherwise, and at some point (too few labeled data), it hurts



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References



Outline

Unsupervised and semi-supervised learning

Spectral clustering

Semi-supervised learning

References



References

- ▶ Tutorial : spectral clustering : U. Von Luxburg
- ▶ Book : Semi-supervised learning, Chapelle, Scholkopf, Zien, MIT