

LeetCode 1871: Jump Game VII

Authored by: Arpit Raj, LNMIIT Jaipur

Date: August 14, 2026

Approach & Explanation

- i can use something like `dp[i]` to store if we can reach that index
- and since ek index pe ya to minjump se aa skte ya to maxjump se ya beech se
- to ek sliding window ka range bnaye to
- new element from minjump
- exit element from maxjump-1

Source Code

```
class Solution {
public:
    bool canReach(string s, int minjump, int maxjump) {

        // i can use something like dp[i] to store if we can reach that index
        // and since ek index pe ya to minjump se aa skte ya to maxjump se ya beech se

        // to ek sliding window ka range bnaye to
        // new element from minjump
        // exit element from maxjump-1

        int n = s.size();
        if (s[n-1] != '0') return false;

        vector<int> dp(n, 0);

        dp[0] = 1;
```

```
int cnt = 0;
for (int i = 1; i < n; i++) {

    if (i - minjump >= 0 && dp[i - minjump]) {
        cnt++;
    }

    if (i - maxjump - 1 >= 0 && dp[i - maxjump - 1]) {
        cnt--;
    }

    if (cnt > 0 && s[i] == '0') {
        dp[i] = 1;
    }
}

return dp[n-1];
}
```

```
};
```