

Chapter: LeetCode 731 - My Calendar Two

Logic & Notes

Explanation:

- is baar double booking allowed he lekin triple nahi
- yaha par we can maintain 2 different vector
- booking vector for normal booking
- overlap vector for double bookings

Implementation

```

class MyCalendarTwo {
public:

    //is baar double booking allowed he lekin triple nahi
    //yaha par we can maintain 2 different vector
    //booking vector for normal booking
    //overlap vector for double bookings

    vector<pair<int,int>> booking;
    vector<pair<int,int>> overlap;

    MyCalendarTwo() {

    }

    bool book(int starttime, int endtime) {

        for(auto &it:overlap){
            int olds=it.first;
            int olde=it.second;

            if(starttime>=olde || endtime<=olds) continue;
            return false;
        }

        for(auto &it:booking){
            int olds=it.first;
            int olde=it.second;

            if(starttime>=olde || endtime<=olds) continue;

            int st=max(starttime,olds);
            int end=min(endtime,olde);
            overlap.push_back({st,end});

        }

        booking.push_back({starttime,endtime});
        return true;
    }
};

/**
 * Your MyCalendarTwo object will be instantiated and called as such:
 * MyCalendarTwo* obj = new MyCalendarTwo();
 * bool param_1 = obj->book(startTime,endTime);
 */

```