MTech – Data Engineering

Machine Learning with Big Data

Assignment 2

MIN-HASHING AND LSH

Submited By:

Arpita Kundu

Roll No: M25DE1004

INDIAN INSTITUTE OF TECHNOLOGY JODHPUR

NH 62 Nagaur Road, Karwar, Jodhpur, Rajasthan

For the following questions, use the D1.txt , D2.txt , D3.txt , and D4.txt files in the minhash directory.

Q-1. Create k-Grams:
You will construct several types of k-grams for all documents. All documents only have at most 27 characters: all lowercase letters and space. The space counts as a character in character k-grams.

- Construct 2-grams based on characters for all documents.
- Construct 3-grams based on characters for all documents.
- Construct 2-grams based on words for all documents.

Remember that you should only store each k-gram once. Duplicates are ignored.

PART – A:
Using 3-grams to build a min-hash signature for documents D1 and D2 using:
t = 20, 60, 150, 300, 600 hash functions.

For each value of (t), report the approximate Jaccard similarity between the pair of documents D1 and D2, estimating the Jaccard similarity: You should report 5 numbers.

$$\hat{J}_{S_t}(a,b) = \frac{1}{t}\sum_{i=1}^{t}\{1 \quad \text{if } a_i = b_i \; 0 \quad \text{if } a_i \neq b_i$$

Answer:
For each Document there are 3 k-grams.

- Character 2-grams
- Character 3-grams
- Word 2-grams

```python
def generate_word_ngrams(content, size):
    token_list = content.split()
    word_sequences = set()

    for index in range(len(token_list) - size + 1):
        sequence = " ".join(token_list[index:index + size])
        word_sequences.add(sequence)

    return word_sequences


def generate_char_ngrams(content, size):
    char_sequences = set()

    for index in range(len(content) - size + 1):
        sequence = content[index:index + size]
        char_sequences.add(sequence)

    return char_sequences


# Store all n-gram results
ngram_storage = {}

for document_id, document_text in document_store.items():
    ngram_storage[document_id] = {
        "char_2gram": generate_char_ngrams(document_text, 2),
        "char_3gram": generate_char_ngrams(document_text, 3),
        "word_2gram": generate_word_ngrams(document_text, 2),
    }


# Count n-grams
ngram_statistics = {}

for document_id, ngram_sets in ngram_storage.items():
    ngram_statistics[document_id] = {}

    for gram_label, gram_values in ngram_sets.items():
        ngram_statistics[document_id][gram_label] = len(gram_values)


for document_id, stats in ngram_statistics.items():
    print(f"{document_id}: {stats}")
```

```
D1.txt: {'char_2gram': 263, 'char_3gram': 765, 'word_2gram': 279}
D2.txt: {'char_2gram': 262, 'char_3gram': 762, 'word_2gram': 278}
D3.txt: {'char_2gram': 269, 'char_3gram': 828, 'word_2gram': 337}
D4.txt: {'char_2gram': 255, 'char_3gram': 698, 'word_2gram': 232}
```

PART - B:

Compute the Jaccard similarity between all pairs of documents for each type of k-gram. **You should report: 3 × 6 = 18 different numbers.**

```python
def compute_jaccard(set_a, set_b):
    common_elements = set_a.intersection(set_b)
    combined_elements = set_a.union(set_b)

    if len(combined_elements) == 0:
        return 0

    return len(common_elements) / len(combined_elements)

document_ids = list(ngram_storage.keys()) #  Get document identifiers
document_pairs = []                       # Generate unique document combinations

for index_a in range(len(document_ids)):
    for index_b in range(index_a + 1, len(document_ids)):
        document_pairs.append((document_ids[index_a], document_ids[index_b]))


# Prepare similarity container
similarity_results = {
    "char_2gram": {},
    "char_3gram": {},
    "word_2gram": {}
}


# Compute Jaccard similarity
for gram_category in similarity_results.keys():
    for doc_a, doc_b in document_pairs:
        set_one = ngram_storage[doc_a][gram_category]
        set_two = ngram_storage[doc_b][gram_category]

        similarity_results[gram_category][(doc_a, doc_b)] = compute_jaccard(set_one, set_two)


for gram_category, score_map in similarity_results.items():
    print(f"\nJaccard Similarity for {gram_category}:")

    for pair_label, score_value in score_map.items():
        print(f"{pair_label}: {score_value:.4f}")
```

```
Jaccard Similarity for char_2gram:
('D1.txt', 'D2.txt'): 0.9811
('D1.txt', 'D3.txt'): 0.8157
('D1.txt', 'D4.txt'): 0.6444
('D2.txt', 'D3.txt'): 0.8000
('D2.txt', 'D4.txt'): 0.6413
('D3.txt', 'D4.txt'): 0.6530

Jaccard Similarity for char_3gram:
('D1.txt', 'D2.txt'): 0.9780
('D1.txt', 'D3.txt'): 0.5804
('D1.txt', 'D4.txt'): 0.3051
('D2.txt', 'D3.txt'): 0.5680
('D2.txt', 'D4.txt'): 0.3059
('D3.txt', 'D4.txt'): 0.3121

Jaccard Similarity for word_2gram:
('D1.txt', 'D2.txt'): 0.9408
('D1.txt', 'D3.txt'): 0.1823
('D1.txt', 'D4.txt'): 0.0302
('D2.txt', 'D3.txt'): 0.1737
('D2.txt', 'D4.txt'): 0.0303
('D3.txt', 'D4.txt'): 0.0161
```

Q-2. Min-Hashing:

We will consider a hash family (H) so that any hash function (h ∈H) maps from:

$$h : \text{k-grams} \rightarrow [m]$$

for (m) large enough (To be extra cautious, use (m greater than 10,000)).

PART - A:

Using 3-grams to build a min-hash signature for documents D1 and D2 using:
t = 20, 60, 150, 300, 600 hash functions.

For each value of (t), report the approximate Jaccard similarity between the pair of documents D1 and D2, estimating the Jaccard similarity. You should report 5 numbers.

```python
def create_hash_coefficients(total_hashes, modulus=10000):
    random.seed(42)
    coefficient_list = []

    for _ in range(total_hashes):
        coef_a = random.randint(1, modulus - 1)
        coef_b = random.randint(0, modulus - 1)
        coefficient_list.append((coef_a, coef_b))

    return coefficient_list


def compute_minhash_signature(ngram_set, coefficient_pairs, modulus=10000):
    signature_vector = []

    for coef_a, coef_b in coefficient_pairs:
        minimum_value = min(((coef_a * hash(item) + coef_b) % modulus) for item in ngram_set)
        signature_vector.append(minimum_value)

    return signature_vector


hash_counts = [20, 60, 150, 300, 600]

estimated_similarity = {}

for num_hashes in hash_counts:
    coeffs = create_hash_coefficients(num_hashes)

    signature_doc1 = compute_minhash_signature(doc1_trigrams, coeffs)
    signature_doc2 = compute_minhash_signature(doc2_trigrams, coeffs)

    matching_positions = sum(
        1 for idx in range(num_hashes)
        if signature_doc1[idx] == signature_doc2[idx]
    )

    estimated_similarity[num_hashes] = matching_positions / num_hashes



print("\nEstimated Jaccard Similarity between D1.txt and D2.txt using MinHash:\n")

for h_count, similarity_value in estimated_similarity.items():
    print(f"Number of hashes = {h_count} --> Similarity ≈ {similarity_value:.4f}")
```

```
Estimated Jaccard Similarity between D1.txt and D2.txt using MinHash:

Number of hashes = 20 --> Similarity ≈ 1.0000
Number of hashes = 60 --> Similarity ≈ 0.9833
Number of hashes = 150 --> Similarity ≈ 0.9867
Number of hashes = 300 --> Similarity ≈ 0.9867
Number of hashes = 600 --> Similarity ≈ 0.9867
```

PART - B:

What seems to be a good value for (t)? You may run more experiments. **Justify your answer in terms of both accuracy and time.**

Answer:
We can conclude to a point that if the value of **t** is small, the algorithm runs faster but produces lower accuracy in similarity estimation. On the other hand, increasing **t** improves accuracy because more hash functions reduce estimation error, but it also increases computation time.

Therefore, choosing **t = 300** appears to be a suitable compromise, as it provides a good balance between accuracy and processing time.

Q-3. LSH:

Consider computing an LSH using:
t = 160 hash functions. **We want to find all document pairs with Jaccard similarity above: τ = .7**

PART - A:

Use the formula mentioned in class and the notes to estimate the best values of hash functions (b) within each of the (r) bands to provide the S-curve:

$$f(s) = 1 - (1 - s^b)^r$$

with good separation at (τ). Report these values.

```python
def s_curve_probability(similarity, bands, rows):
    return 1 - (1 - similarity ** bands) ** rows


total_hashes = 160
threshold = 0.7

similarity_range = [value / 100 for value in range(101)]
band_row_options = [(20, 8), (16, 10), (10, 16), (8, 20)]

curve_results = {}

for rows, bands in band_row_options:
    probability_values = [
        s_curve_probability(sim, bands, rows)
        for sim in similarity_range
    ]

    curve_results[(rows, bands)] = probability_values

    print(f"\nS-curve values when rows={rows} and bands={bands}:\n")

    for sim_value, prob in zip(similarity_range, probability_values):
        print(f"Similarity = {sim_value:.2f} --> Probability = {prob:.4f}")


optimal_choice = None
smallest_gap = float("inf")

for (rows, bands), _ in curve_results.items():
    difference = abs(s_curve_probability(threshold, bands, rows) - 0.5)

    if difference < smallest_gap:
        smallest_gap = difference
        optimal_choice = (rows, bands)


print("\nOptimal (rows, bands) configuration near threshold:")
print(f"Threshold = {threshold}")
print(f"Selected rows = {optimal_choice[0]}")
print(f"Selected bands = {optimal_choice[1]}")
```

```
Similarity = 0.74 --> Probability = 0.0192
Similarity = 0.75 --> Probability = 0.0251
Similarity = 0.76 --> Probability = 0.0326
Similarity = 0.77 --> Probability = 0.0421
Similarity = 0.78 --> Probability = 0.0543
Similarity = 0.79 --> Probability = 0.0695
Similarity = 0.80 --> Probability = 0.0886
Similarity = 0.81 --> Probability = 0.1123
Similarity = 0.82 --> Probability = 0.1415
Similarity = 0.83 --> Probability = 0.1771
Similarity = 0.84 --> Probability = 0.2201
Similarity = 0.85 --> Probability = 0.2711
Similarity = 0.86 --> Probability = 0.3308
Similarity = 0.87 --> Probability = 0.3993
Similarity = 0.88 --> Probability = 0.4758
Similarity = 0.89 --> Probability = 0.5588
Similarity = 0.90 --> Probability = 0.6455
Similarity = 0.91 --> Probability = 0.7317
Similarity = 0.92 --> Probability = 0.8123
Similarity = 0.93 --> Probability = 0.8818
Similarity = 0.94 --> Probability = 0.9355
Similarity = 0.95 --> Probability = 0.9713
Similarity = 0.96 --> Probability = 0.9906
Similarity = 0.97 --> Probability = 0.9981
Similarity = 0.98 --> Probability = 0.9999
Similarity = 0.99 --> Probability = 1.0000
Similarity = 1.00 --> Probability = 1.0000

Optimal (rows, bands) configuration near threshold:
Threshold = 0.7
Selected rows = 16
Selected bands = 10
```

```python
import matplotlib.pyplot as plt

plt.figure(figsize=(6, 4))

for (rows, bands), probabilities in curve_results.items():
    plt.plot(
        similarity_range,
        probabilities,
        label=f"rows={rows}, bands={bands}"
    )

plt.title("LSH S-Curve Graph")
plt.xlabel("Similarity Score")
plt.ylabel("Probability of Candidate Selection")
plt.legend()
plt.tight_layout()
plt.show()
```



PART - B:

Using your choice of (r) and (b) and (f(·)), what is the probability of each pair of the four documents (using 3-grams) being estimated to have a similarity greater than (τ)? Report 6 numbers.

```python
def build_trigrams(input_text):
    return {input_text[idx:idx + 3] for idx in range(len(input_text) - 2)}


# Create trigram sets for each document
trigram_map = {
    document_label: build_trigrams(text_data)
    for document_label, text_data in document_store.items()
}

similarity_scores = {}

for doc_a, doc_b in combinations(list(trigram_map.keys()), 2):
    score_value = compute_jaccard(trigram_map[doc_a], trigram_map[doc_b])
    similarity_scores[(doc_a, doc_b)] = score_value


rows = 20
bands = 8
threshold = 0.7

probability_estimates = {}

print("\nProbability that similarity exceeds the chosen threshold:\n")

for pair_key, similarity_value in similarity_scores.items():
    probability_value = s_curve_probability(similarity_value, bands, rows)
    probability_estimates[pair_key] = probability_value

    print(f"Pair {pair_key} --> Probability ≈ {probability_value:.4f}")
```

```
Probability that similarity exceeds the chosen threshold:

Pair ('D1.txt', 'D2.txt') --> Probability ≈ 1.0000
Pair ('D1.txt', 'D3.txt') --> Probability ≈ 0.2282
Pair ('D1.txt', 'D4.txt') --> Probability ≈ 0.0015
Pair ('D2.txt', 'D3.txt') --> Probability ≈ 0.1959
Pair ('D2.txt', 'D4.txt') --> Probability ≈ 0.0015
Pair ('D3.txt', 'D4.txt') --> Probability ≈ 0.0018
```

Q-4: Min-Hashing on MovieLens dataset:

Implement Min-Hashing on the older MovieLens 100k dataset (5MB), which consists of a set of 943 users who have rated 1682 movies. You can download the data from:
http://www.grouplens.org/node/73
Read the Readme file for details about the data, and process it as you need.

For this exercise, we only care about the set of movies that a user has rated and not the ratings. We want to compute the Jaccard similarity between the users.

Compute the exact Jaccard similarity for all pairs of users, and output the pairs of users that have a similarity of at least 0.5.

Then, compute the min-hash signatures for the users and compute the approximate Jaccard similarity.

Use:

- 50 hash functions
- 100 hash functions
- 200 hash functions

For each value, output the pairs that have an estimated similarity of at least 0.5 and report the number of false positives and false negatives that you obtain.

For the false positives and negatives, report the averages for 5 different runs.

```python
def load_movie_ratings(file_location):
    user_movies_map = {}

    with open(file_location, "r") as data_file:
        for record in data_file:
            parts = record.split()

            user_id = int(parts[0])
            movie_id = int(parts[1])

            if user_id not in user_movies_map:
                user_movies_map[user_id] = set()

            user_movies_map[user_id].add(movie_id)

    return user_movies_map


dataset_path = "/content/drive/MyDrive/ml-100k/ml-100k/u.data"

user_movie_data = load_movie_ratings(dataset_path)

similarity_results = {}
user_list = list(user_movie_data.keys())

for idx1 in range(len(user_list)):
    for idx2 in range(idx1 + 1, len(user_list)):
        user_a = user_list[idx1]
        user_b = user_list[idx2]


        intersection_size = len(
            user_movie_data[user_a].intersection(user_movie_data[user_b])
        )
        union_size = len(
            user_movie_data[user_a].union(user_movie_data[user_b])
        )

        jaccard_score = intersection_size / union_size

        if jaccard_score >= 0.5:
            similarity_results[(user_a, user_b)] = jaccard_score


print("\nUser pairs with Jaccard similarity of 0.5 or higher:\n")

for user_pair, score in similarity_results.items():
    print(f"Users {user_pair[0]} & {user_pair[1]} --> Similarity Score = {score:.4f}")
```

```
User pairs with Jaccard similarity of 0.5 or higher:

Users 197 & 600 --> Similarity Score = 0.5000
Users 197 & 826 --> Similarity Score = 0.5130
Users 328 & 788 --> Similarity Score = 0.6730
Users 408 & 898 --> Similarity Score = 0.8387
Users 451 & 489 --> Similarity Score = 0.5333
Users 489 & 587 --> Similarity Score = 0.6299
Users 554 & 764 --> Similarity Score = 0.5170
Users 600 & 826 --> Similarity Score = 0.5455
Users 674 & 879 --> Similarity Score = 0.5217
Users 800 & 879 --> Similarity Score = 0.5000
```

```
Performance Summary for 50 Hash Functions:
False Positives Count: 2604
False Negatives Count: 6
```

```
Performance Summary for 100 Hash Functions:
False Positives Count: 579
False Negatives Count: 7
```

```
Performance Summary for 200 Hash Functions:
False Positives Count: 278
False Negatives Count: 6
```

Q-5. LSH on MovieLens dataset:

Break up the signature table into (b) bands with (r) hash functions per band and implement Locality Sensitive Hashing.

The goal is to find candidate pairs with a similarity of at least 0.6.

Experiment with:

- (r = 5, b = 10) for the table with the 50 hash functions
- (r = 5, b = 20) for the table with the 100 hash functions
- (r = 5, b = 40) and (r = 10, b = 20) for the table with the 200 hash functions

Report the number of false positives and false negatives, taking the average over 5 runs.
How do these numbers change if we want a similarity of at least 0.8?

```
LSH Evaluation Summary (Similarity Threshold = 0.6)

Configuration -> Hashes: 50, Rows per Band: 5, Bands: 10
Mean False Positives: 45412.00
Mean False Negatives: 1.00

Configuration -> Hashes: 100, Rows per Band: 5, Bands: 20
Mean False Positives: 66919.00
Mean False Negatives: 1.00

Configuration -> Hashes: 200, Rows per Band: 5, Bands: 40
Mean False Positives: 121499.00
Mean False Negatives: 0.00

Configuration -> Hashes: 200, Rows per Band: 10, Bands: 20
Mean False Positives: 32080.00
Mean False Negatives: 0.00

LSH Evaluation Summary (Similarity Threshold = 0.8)

Configuration -> Hashes: 50, Rows per Band: 5, Bands: 10
Mean False Positives: 45413.00
Mean False Negatives: 0.00

Configuration -> Hashes: 100, Rows per Band: 5, Bands: 20
Mean False Positives: 66920.00
Mean False Negatives: 0.00

Configuration -> Hashes: 200, Rows per Band: 5, Bands: 40
Mean False Positives: 121501.00
Mean False Negatives: 0.00

Configuration -> Hashes: 200, Rows per Band: 10, Bands: 20
Mean False Positives: 32082.00
Mean False Negatives: 0.00
```

- Increasing the number of bands (**b**) generally reduces false negatives because similar items are more likely to be placed in at least one common band. However, this also increases the chance of false positives, as dissimilar items may collide in one of the bands. Reducing **b** has the opposite effect, lowering false positives but potentially missing truly similar pairs.
- Selecting appropriate values for **r** (rows per band) and **b** (number of bands) requires carefully balancing precision and recall. A higher **r** makes the matching condition stricter within each band, improving precision by reducing false positives. Conversely, a lower **r** increases recall by allowing more candidate pairs, though at the cost of more false positives.
- Increasing the similarity threshold (τ) makes the algorithm more conservative. This reduces false positives because only highly similar pairs are accepted, but it may also increase false negatives by filtering out moderately similar yet relevant pairs. Lowering the threshold improves recall but can reduce precision.

- Overall, the choice of parameters (**r**, **b**, and τ) should depend on the specific application requirements. If minimizing false positives is critical (e.g., in recommendation filtering), higher precision settings are preferable. If capturing as many similar pairs as possible is more important (e.g., in clustering), higher recall settings may be prioritized.

Git Hub link : https://github.com/arpita12-bot/Machine-learning-with-Big-Data/tree/main/Assignment2

-----END----