

Control Statements – 1

1. Which of these selection statements test only for equality?

- a) if
- b) switch
- c) if & switch
- d) none of the mentioned

b) switch

2. Which of these are selection statements in Java?

- a) if()
- b) for()
- c) continue
- d) break

a) if()

3. Which of the following loops will execute the body of loop even when condition controlling the loop is initially false?

- a) do-while
- b) while
- c) for
- d) none of the mentioned

a) do-while

4. Which of these jump statements can skip processing the remainder of the code in its body for a particular iteration?

- a) break
- b) return
- c) exit
- d) continue

d) continue

5. Which of this statement is incorrect?

- a) switch statement is more efficient than a set of nested ifs
- b) two case constants in the same switch can have identical values
- c) switch statement can only test for equality, whereas if statement can evaluate any type of boolean expression
- d) it is possible to create a nested switch statements

b) two case constants in the same switch can have identical values

6. What will be the output of the following Java program?

```
class selection_statements
{
    public static void main(String args[])
    {
        int var1 = 5;
        int var2 = 6;
        if ((var2 = 1) == var1)
            System.out.print(var2);
        else
            System.out.print(++var2);
    }
}
```

- a) 1
- b) 2
- c) 3
- d) 4

b) 2

7. What will be the output of the following Java program?

```
class comma_operator
{
    public static void main(String args[])
    {
        int sum = 0;
        for (int i = 0, j = 0; i < 5 & j < 5; ++i, j = i + 1)
            sum += i;
        System.out.println(sum);
    }
}
```

- a) 5
- b) 6
- c) 14

d) compilation error

a) 5

8. What will be the output of the following Java program?

```
class jump_statments
{
    public static void main(String args[])
    {
        int x = 2;
        int y = 0;
        for ( ; y < 10; ++y)
        {
            if (y % x == 0)
                continue;
            else if (y == 8)
                break;
            else
                System.out.print(y + " ");
        }
    }
}
```

a) 1 3 5 7

b) 2 4 6 8

c) 1 3 5 7 9

d) 1 2 3 4 5 6 7 8 9

a) 1 3 5 7

9. What will be the output of the following Java program?

```
class Output
{
    public static void main(String args[])
    {
        final int a=10,b=20;
        while(a<b)
        {

            System.out.println("Hello");
        }
        System.out.println("World");
    }
}
```

a) Hello

b) run time error

- c) Hello world
- d) compile time error

d) compile time error

10. What will be the output of the following Java program?

```
class Output
{
    public static void main(String args[])
    {
        int a = 5;
        int b = 10;
        first:
        {
            second:
            {
                third:
                {
                    if (a == b >> 1)
                        break second;
                }
                System.out.println(a);
            }
            System.out.println(b);
        }
    }
}
```

- a) 5 10
- b) 10 5
- c) 5
- d) 10

a) 5 10