Beyond a Perfect Score

Genome-wide diagnosis, Bayesian variant ranking, uncertainty, and temporal generalization for the Rare Disease, Real Kid MVA Hackathon 2026

Mame Diarra Toure & Bonaventure F. P. Dossou

Research lead, Bayesian modeling and generalization analysis

Submission-day report: 7 September 2026
Post-submission extension: 8 September 2026

TL;DR

The genome-wide pipeline identified the accepted compound-heterozygous *BUB1B* pair at rank 1, and every transferred model reproduced the maximum Track 1 score; the work that distinguishes this submission is the evidence trail explaining why the pair is credible, where the models generalize, where Bayesian uncertainty helps.

Abstract

Track 1 of the Rare Disease, Real Kid Hackathon asks participants to identify the causal variant or variant pair in one child with mosaic variegated aneuploidy (MVA). We developed a genome-wide workflow and processed the gated whole-genome data, aligned more than one billion reads, normalized and phased 5.08 million variants, joined functional annotations to all but one heterozygous allele, and ranked a compound-heterozygous *BUB1B* hypothesis first. The selected wide rank-50 SBNN CSV was accepted by the live Hugging Face evaluator as Submission 2, with a full match at rank 1, 100 Rank Points, F-max 1.000, and an F-max EPCR threshold of 0.3724070924857989. We then asked a harder question: can a learned method reproduce the child-level result and transfer to variants and patients unavailable at training time?

We evaluated a linear Bayesian ranker, deterministic gradient boosting and neural networks, a five-network deep ensemble, low-rank singular Bayesian neural networks (SBNNs), full-weight Bayes-by-Backprop (BBB) networks, wider Bayesian architectures, and a validation-selected consensus. All challenge adapters placed the accepted pair first and achieved the same perfect Track 1 score. Perfect agreement on one proband did not distinguish the models. On an untouched temporal ClinVar holdout, the wide rank-50 SBNN achieved the best simulated top-1 ranking (84.35%) and F-max (0.9235), while the deep ensemble remained the best detector of unseen genes (OOD AUROC 0.7485). Its low-rank Bayesian factors replace the dense layer's quadratic parameter growth with rank-controlled linear growth in layer width, which makes the architecture increasingly attractive as networks become wider [Toure and Stephens, 2026]. On 719 post-2023 solved Phenopacket hypotheses, molecular-only top-1 accuracy was about 34%; an HPO-conditioned dense BBB reached 58.9% ± 1.0% across five resampled candidate cohorts. The best result on 64 two-variant cases was 68.1% top-1. These patient tests use compact ClinVar-derived candidate sets, not complete external exomes, so they support transfer of the ranking function but not a clinical diagnostic sensitivity claim. In the full-background generalization study, a predictor-augmented pairwise SBNN reached VarPB Top-20 65.70% and Top-100 86.63%, versus 65.90% and 84.82% for REVEL. The SBNN adds posterior predictive uncertainty in a 56,204-scalar ranker, but it still depends on the deterministic REVEL and AlphaMissense input pipelines.

The contribution is therefore a reproducible methodology with explicit separation of candidate generation from ranking, strict temporal and gene-aware evaluation, calibrated claims about uncertainty, attribution of upstream data and features, and a clear path to full patient-level validation through PhEval.

1 Introduction

1.1 The pipeline

Figure 1 is the project pipeline. The first two stages establish a valid patient-specific candidate universe. The learned models then estimate molecular pathogenicity, an uncertainty layer flags cases unlike the training evidence, and phenotype plus inheritance logic returns the analysis to the patient rather than treating isolated variants as the endpoint.




Figure 1: The complete Track 1 system. The pipeline supplies candidate generation and clinical filtering. The comparative modeling work supplies molecular ranking and uncertainty. Patient-level reasoning combines those outputs with HPO similarity, disease validity, phase, and compound-heterozygous logic. The final product is a ranked pair and an inspectable evidence trace.

For the submitted child, this chain reduces 5.08 million variants to six reportable pairs and ranks the accepted *BUB1B* pair first. For external evaluation, candidate generation is held fixed and the ranking layers are tested on temporal ClinVar variants and later solved Phenopacket cases. That separation makes the scope of each result clear: the child score evaluates the full system on one proband, while the external benchmarks test transfer of the molecular and phenotype-ranking components.

1.2 The argument

The report follows one claim from raw observations to its limits. We begin with the child's genome and phenotype, align the reads, check the reference representation, normalizes and annotates millions of variants, phase the heterozygous calls, apply genotype and inheritance filters, construct same-gene pairs, and only then produces the candidate table. This is the end-to-end diagnostic path that leads to *BUB1B*.

The leading pair is then justified biologically. One allele is a pathogenic stop-gain. The second is an ultra-rare missense allele with strong sequence quality and computational support but unresolved clinical significance. Both are required by the compound-heterozygous hypothesis, direct cis pairs are excluded,

the MVA phenotype is consistent with biallelic *BUB1B* dysfunction, and the remaining phase uncertainty is reported rather than hidden.

The learned comparison is deliberately downstream of those validity checks. No model input contains the accepted rank, the challenge answer, or a *BUB1B*/MVA bonus. The temporal adapter also excludes clinical significance, submitted scores, and unavailable patient predictors when these would leak the answer. The report compares deterministic gradient boosting, a dense neural network, a five-network ensemble, a linear Bayesian ranker, low-rank SBNNs, dense BBB networks, wider Bayesian models, and a validation-selected consensus under shared evaluation rules.

The child result alone cannot establish generalization, even though every compatible model reproduces the maximum score. Generalization is therefore tested separately with a 2023-to-2026 ClinVar split, gene-disjoint validation, an untouched odd-ID holdout, and 719 post-2023 solved Phenopacket cases. These experiments show useful transfer, particularly after HPO conditioning, but also show a sharp known-gene versus unseen-gene gap.

Uncertainty is treated as a referral signal, not as a decorative Bayesian output. NLL, Brier score, ECE, posterior or ensemble disagreement, unseen-gene OOD AUROC, and selective prediction are examined separately from ranking accuracy. The ensemble currently gives the clearest unfamiliar-gene warning, while the wide rank-50 SBNN gives the best temporal ranking. A practical pipeline should use that warning to send unfamiliar or unstable cases for review rather than allowing a confident-looking score to close the case automatically.

The scope of the claim stays narrow. The external benchmark evaluates molecular pathogenicity and candidate ranking in constructed candidate sets. It does not measure recall from complete genomes, prove the two child alleles are in trans, establish the missense allele functionally, or demonstrate clinical probability calibration. A full VCF-based PhEval experiment is the next test required for a true multi-patient end-to-end diagnostic claim.

2 The challenge and its evaluation

2.1 Two tracks, two different scientific tasks

The challenge uses real genomic and clinical data from a child diagnosed with MVA. The gated repository contains approximately 85 GB across 11 files and recommends 100–150 GB of working storage because alignment, indexes, and intermediate files are larger than the compressed download [Sage Bionetworks, 2026a]. The submission period runs from 24 August to 24 October 2026.

Track 1 asks for a ranked list of primary causal variants or compound-heterozygous pairs. Its automated metrics are Rank Points and F-max. A methods report is mandatory but judged qualitatively. Track 2 asks for a mechanism-based drug-repurposing proposal and is panel-scored for scientific rigor (35%), potential impact (25%), innovation (25%), and scalability (15%) [Sage Bionetworks, 2026b].

2.2 What Rank Points and F-max measure

Let the accepted causal allele set for a proband be G and the allele set in submitted row i be S_i. The full-match rank is the first row for which $S_i = G$. Rank Points are a decreasing function of that rank, with rank 1 receiving 100 points. Partial credit is possible when only one allele of a compound-heterozygous answer is recovered.

Each row also contains an estimated probability of causal relationship (EPCR). For every submitted

threshold t, the evaluator retains rows with EPCR at least t, converts them to predicted alleles, and computes

$$P(t) = \frac{TP(t)}{TP(t) + FP(t)}, \qquad R(t) = \frac{TP(t)}{TP(t) + FN(t)}, \tag{1}$$

$$F_1(t) = \frac{2P(t)R(t)}{P(t) + R(t)}, \qquad F_{\max} = \max_t F_1(t). \tag{2}$$

On one solved proband, $F_{\max} = 1$ is possible whenever a threshold isolates exactly the accepted pair. It does not establish probability calibration across patients. This distinction becomes important because our perfect models assign the top pair EPCR values ranging from roughly 0.35 to 0.95.

3 Biology Primer

3.1 Variants, alleles, genes, and inheritance

A variant is a difference between the child's DNA and a reference genome. Humans usually carry two copies of each autosomal gene, one inherited from each parent. A heterozygous variant is present on only one copy. In a recessive disorder, one damaging allele is often insufficient; both copies must be affected.

A *compound-heterozygous* hypothesis contains two different damaging variants in the same gene. For the hypothesis to be recessive, the variants should be in *trans*, meaning they lie on different parental copies. If they are in *cis*, both lie on the same copy and the other copy may remain functional. Short reads cannot always phase variants separated by many kilobases, so "phase unknown" is uncertainty, not evidence for cis.

3.2 Mosaic variegated aneuploidy and *BUB1B*

MVA is a rare chromosome-instability syndrome in which different cells carry different chromosome gains or losses. It can involve growth restriction, microcephaly, developmental abnormalities, and increased cancer risk. Biallelic pathogenic variants in *BUB1B* are an established cause [Hanks et al., 2004].

BUB1B encodes BUBR1, a core spindle-assembly-checkpoint protein. During cell division, the checkpoint delays chromosome separation until chromosomes are properly attached to the mitotic spindle. Reduced BUBR1 function allows segregation errors, providing a direct mechanistic bridge from genotype to aneuploid cells and cancer susceptibility [Suijkerbuijk et al., 2010]. The Human Phenotype Ontology (HPO) assigns standardized identifiers to clinical findings [Köhler et al., 2021]. A patient is represented by a set of observed and sometimes explicitly absent HPO terms. Phenotype matching asks whether diseases associated with a candidate gene explain that set. It is not a substitute for molecular evidence. A gene can match the phenotype while the patient's variants in that gene are benign; conversely, a genuinely novel disease gene may have no prior phenotype annotation.

4 Clinical phenotype and target hypothesis

The supplied phenotype included rhabdomyosarcoma (HP:0002859), nephrocalcinosis (HP:0000121), short stature (HP:0004322), failure to thrive (HP:0001508), skeletal muscle atrophy or low muscle mass (HP:0003202), premature birth (HP:0001622), severe intrauterine growth restriction or small-for-gestational-age birth (HP:0001518), and parental recurrent spontaneous abortion (HP:0200067).

The genome-wide analysis ranked the following pair first:

Table 1: Leading *BUB1B* hypothesis on GRCh38.

Variant	Protein consequence	Population evidence	Interpretation
chr15:40209701 T>G	p.Leu737Ter	gnomAD v4.1.1 AF 7.4×10^{-5}; no homozygotes	Stop-gain; ClinVar pathogenic/likely pathogenic, two stars; CADD PHRED 38; LOFTEE high-confidence loss of function.
chr15:40220612 T>G	p.Asn1002Lys	One allele among 1,614,226; AF 6.2×10^{-7}; no homozygotes	Rare missense; CADD 26.4, REVEL 0.472, PolyPhen 0.997. This nucleotide change has no ClinVar record; the same amino-acid substitution produced by another nucleotide change is a VUS.

The first allele is a strong pathogenic anchor. The second is the key uncertainty. Its rarity, sequence quality, phenotype context, and occurrence with a pathogenic allele support the pair, but computational scores do not establish pathogenicity. The variants are 10,911 bases apart and were not connected by a short-read phase block. Parental sequencing, long-range phasing, or a functional assay would materially strengthen the conclusion.

5 Data provenance, access, and storage decisions

5.1 Training Data for Uncertainty-Aware models

Table 2: Data provenance and role in the project.

Dataset	Source and access	Local acquisition	Use and boundary
Hackathon WGS and phenotype, about 85 GB	Gated SageBio Hugging Face dataset [Sage Bionetworks, 2026a]; access requires accepting the rules and sharing contact information	Downloaded authorized files to using the Hugging Face CLI/API.	Four paired-end FASTQ lanes, supplied WGS VCF, and clinical phenotype document. Used by the original genome-wide pipeline for alignment, annotation, phasing, filtering, and candidate generation.
GRCh38 reference and exclusion mask	NCBI/GIAB public reference resources named by the VCF header	Downloaded by the pipeline with resumable HTTP to cluster storage; reconstructed representation validated against all 2,580 VCF contigs	Alignment and normalization only. The reference representation matched the challenge VCF exactly in contig names and lengths.
HPO and gene-phenotype annotations	Official HPO releases [Köhler et al., 2021]	The genome-wide pipeline downloaded the then-current `hp.obo` and `genes_to_phenotype.txt`. The strict external benchmark separately downloaded `v2023-10-09/hp.obo` (9.2 MB) by HTTPS.	Ontology-aware phenotype scoring. The 2023 ontology was used in the temporal patient benchmark to avoid a post-cutoff knowledge dependency.

Dataset	Source and access	Local acquisition	Use and boundary
OpenCRAVAT annotations	Locally installed ClinVar, gnomAD v2/v3, CADD, REVEL, and SpliceAI modules [National Center for Biotechnology Information, 2026, Karczewski et al., 2020, Kircher et al., 2014, Ioannidis et al., 2016, Jaganathan et al., 2019]	Installed and run on the cluster. Patient variants were not sent to public annotation APIs. The pipeline generated consequence, population, clinical, and predictor fields. These fields form part of the later pair-model input.	
Compact ranking export	Derived from Bonaventure's cluster run and upstream repository [Dossou, 2026], then imported by the integrated Bayesian repository [Toure and Dossou, 2026]	The file `ranking.zip` was copied to the project workspace; it contains candidate tables, not FASTQ/BAM/VCF data	Allowed the Bayesian rankers to consume exactly the same strict and broad candidate pairs without moving the 85 GB dataset.
Phenopacket Store 0.1.27	Monarch Initiative corpus and versioned release [Danis et al., 2025, Monarch Initiative, 2026]	Release archive downloaded by HTTPS, 19 MB	Solved patients, causal GRCh38 variants, genes, source groups, and HPO terms. Used for the first 425/44/89 pair benchmark and the later 719-case temporal patient benchmark.
Phenopacket molecular annotation cache	Open benchmark adapter built from Phenopacket variants and VEP-derived annotations	Used during the first pair-model training run; only fitted model artifacts and reports are retained in this repository copy	Supplied consequence, population-frequency, CADD, and SpliceAI values for causal and benign decoy alleles. Candidate sets were constructed and are not full patient genomes.
VarPB version 3	Public Zenodo benchmark [Danzi, 2023]	Downloaded after the submission-day report: 96.7 MB exonic-background table plus the small 2023 causal tables. The 624 MB complete archive was unnecessary.	107 openly redistributable Personal Genome Project backgrounds and 2,577 temporal ClinVar causal variants. Used only for the locked post-submission full-background test, never for model training or selection.
Post-submission predictor annotations	OpenCRAVAT 3.1.1 with hg38 mapper 1.47.2, gnomAD 2.2.0/data v2.1, REVEL 2024.07.30/data v4.3a, and AlphaMissense 1.1.1 [Karczewski et al., 2020, Ioannidis et al., 2016, Cheng et al., 2023]	Installed locally on 8 September 2026; about 28 GB. CADD was not installed because that module alone is about 86.6 GB.	Applied consistently to the VarPB union and the filtered 2023 ClinVar training subset. Missing annotations were retained with explicit indicators.
ClinVar 26 Dec 2023	Official NCBI archived GRCh38 VCF [National Center for Biotechnology Information, 2026]	Downloaded by HTTPS/FTP from the NCBI archive and stored as `clinvar_20231226.vcf.gz`, 87 MB	Training-time labels and gene-history features. It contains 1,084,930 unambiguous labeled variants and 2,340,600 total Variation IDs.

Dataset	Source and access	Local acquisition	Use and boundary
ClinVar 29 Aug 2026	Official NCBI GRCh38 VCF [National Center for Biotechnology Information, 2026]	Downloaded from NCBI and stored as `clinvar_20260829.vcf.gz`, 184 MB	Temporal evaluation. Records with Variation IDs absent in 2023 form a 626,287-variant test set.
Track 1 ground-truth behavior	Public challenge evaluator and accepted platform results [Sage Bionetworks, 2026b]	Evaluator logic was reproduced locally; private ground-truth file was not copied	The deterministic CSV and selected wide rank-50 SBNN CSV both received Rank Points 100 and F-max 1.0 on the live platform. The SBNN was accepted as Submission 2 with threshold 0.3724070924857989.

5.2 Checksums of compact public inputs

The public files used in the final temporal analysis are small enough to reproduce without the gated WGS:

- 2023 ClinVar: `510c54e3fd04b078...cb63786`;
- 2026 ClinVar: `e72f5619f003c80c...6ec91f9`;
- Phenopacket Store 0.1.27: `d0c70005bb09b870...edf205a`;
- HPO 2023-10-09: `d3c1280f2780628c...e6cd4e52`.

The full hashes are recorded in the repository README. No access token is stored in code or documentation.

6 Team contributions and model boundaries

This is joint work by Mame Diarra Toure and Bonaventure Dossou. The diagnosis, modeling results, challenge submission, scientific interpretation, and final outcome belong to the team. The division below records how the system was built; it is not a division of ownership. Mame developed the Bayesian ranking and generalization extension: formulation of the learned ranking problem; construction of the shared feature contract; implementation and evaluation of the linear Bayesian, SBNN, dense BBB, ensemble, gradient-boosting, and consensus models; SBNN hyperparameter studies; temporal ClinVar and Phenopacket/HPO experiments; Track 1 score verification; uncertainty and calibration analysis; visualization, reproducibility work, interpretation, and preparation of this report [Toure and Dossou, 2026].

Bonaventure developed the original genome-wide workflow, ran it on the cluster, produced the feature and candidate tables, and prepared the submitted CSV [Dossou, 2026]. This includes input discovery, reference preparation, alignment, normalization, phasing, local annotation, HPO gene scoring, variant scoring, pair construction, QC, and submission export.

The two parts are interdependent. The Bayesian models could not have been trained and transferred to the child without the valid candidate universe and biological features produced by Bonaventure's pipeline. The upstream pipeline, in turn, is extended by Mame's comparative models, external generalization tests, and uncertainty analysis. The complete implementation is therefore documented across the upstream genome repository and the integrated Bayesian repository [Dossou, 2026, Toure and Dossou, 2026]. In particular, the first pair models consume these exported features:

- phenotype score;
- minimum and maximum consequence severity across the two alleles;

- minimum and mean rarity, maximum allele frequency, and missingness fraction;
- minimum and maximum normalized CADD and SpliceAI scores, plus availability indicators;
- phenotype-by-consequence and phenotype-by-rarity interaction terms;
- the same pair identity, phase exclusion, and strict/broad candidate definitions.

The temporal ClinVar models are a separate molecular layer. Their 50 features come directly from ClinVar records and training-only gene summaries. When transferred back to Track 1, they score the alleles in Bonaventure's candidate tables, combine the two allele probabilities geometrically, and multiply by Bonaventure's phenotype score [Dossou, 2026, Toure and Dossou, 2026]. They do not replace his annotation, filtering, phase logic, or pair construction.

Important attribution rule

The challenge result is a property of the team's full system. It would be incorrect to attribute it to either component in isolation: every learned model receives a candidate universe and biological features from the genome-wide pipeline, while the extended evidence about transfer, calibration, and uncertainty comes from the comparative modeling work.

7 Genome-wide pipeline

7.1 Preprocessing

Alignment, reference matching, allele normalization, and read-backed phasing define what was observed. They are not labels for a neural network to discover. Keeping them explicit prevents a flexible scorer from compensating for an invalid coordinate, a low-quality genotype, or a known cis pair. Clinical prioritization systems commonly combine deterministic validity checks with learned scoring [Stenton et al., 2024, Danzi et al., 2023, Mao et al., 2024, Boceck et al., 2026].

7.2 Alignment and quality control

All four paired-end FASTQ lanes were aligned to the matching GRCh38 reference. The final alignment contained 1,076,022,862 total reads, 1,071,835,104 primary reads, and 1,067,608,257 mapped primary reads, for a 99.61% primary mapping rate. The pipeline retained read group, mate position, template length, and R1/R2 identity. A one-million-pair audit gave 99.651% mapped mates, 98.662% same-chromosome pairs, and a median absolute insert size of 430 bases.

7.3 Normalization and annotation

The supplied VCF contained 5,079,064 normalized variants, including 3,180,797 heterozygous alleles. Canonical chromosome-position-reference-alternate normalization joined 3,180,796 of these to the OpenCRAVAT annotation output; the single failure was a deletion representation. This near-complete join was necessary because silent join loss can eliminate the causal variant before ranking.

7.4 Phasing

WhatsHap phased 2,754,502 of 3,180,797 heterozygous variants (86.60%) into 439,579 phase sets. Same-set, opposite-haplotype alleles were treated as trans evidence. Same-set, same-haplotype alleles were treated

as cis and removed from the causal shortlist. Different sets or unphased calls remained eligible with phase marked unknown. The *BUB1B* pair remained unresolved.

7.5 Variant and pair scoring

The conservative upstream variant score was

$$s_v = 0.36s_{\text{consequence}} + 0.26s_{\text{rarity}} + 0.20s_{\text{QC}} + 0.10s_{\text{ClinVar}} + 0.08s_{\text{predictor}}. \quad (3)$$

The predictor term averages available raw REVEL, normalized CADD PHRED, and SpliceAI delta scores. A correction from REVEL rankscore to raw REVEL reduced support for p.Asn1002Lys but did not change the leading pair.

Candidate compound-heterozygous pairs were generated from heterozygous alleles in the same gene. The strict tier required a primary chromosome, PASS, depth at least 10, genotype quality at least 20, heterozygous allele balance between 0.20 and 0.80, and population AF no greater than 0.005 when observed. Seven strict pairs survived. One *ZNF619* pair had direct cis evidence and was removed, leaving six submitted hypotheses.




Figure 2: The filtering funnel. Counts represent different objects at different stages: raw variants, heterozygous alleles, transcript/gene annotations, and finally genotype hypotheses. The logarithmic axis prevents the final six pairs from disappearing visually.

8 The goal of Bayesian Modeling

The deterministic workflow already solved the child. A learned model is justified only if it adds knowledge beyond that case. We therefore separated three objectives:

1. **Track 1 compatibility:** preserve the accepted pair at rank 1.
2. **Molecular generalization:** recognize pathogenic variants that entered ClinVar after training.
3. **Patient generalization and uncertainty:** rank causal hypotheses for other solved diseases and identify unsupported cases.

This changed the learning target. The model does not consume FASTQ reads. It receives annotated candidate alleles or pairs and predicts a pathogenicity or causality score. Deterministic processing remains responsible for valid observations and inheritance-consistent hypotheses.

9 Model family 1: Bayesian conditional-logit pair ranker

9.1 Training data and target

The first learned benchmark loaded 9,739 solved Phenopacket cases, including 959 reported two-variant cases. After annotation and decoy requirements, 425 cases were used for training, 44 for validation, and 89 for development testing. Genes, source publications, and case identifiers were disjoint across splits. *BUB1B* was excluded.

Each case had 23 constructed candidate pairs. The target y_i was the index of the reported causal pair. For feature vector x_{ij} of candidate j in case i, conditional logit assigns

$$p(y_i = j \mid X_i, w) = \frac{\exp(w^\top x_{ij})}{\sum_k \exp(w^\top x_{ik})}. \tag{4}$$

A zero-centered Gaussian prior regularizes w. The maximum-a-posteriori estimate was optimized, and a Laplace approximation around it provided a Gaussian posterior. Prior scale was selected by validation negative log likelihood.

9.2 Result

On 89 held-out development cases, the fixed evidence rule achieved 70.8% top-1 and 83.1% top-5. The Bayesian posterior mean achieved 58.4% top-1 and 87.6% top-5. The learned model improved shortlist retention but was worse at rank 1. The negative result showed that 425 simplified cases were insufficient for an end-to-end pair learner to replace explicit biological structure.

10 Model family 2: first low-rank SBNN pair model

The first SBNN [Toure and Stephens, 2026] used the same 15 pair features and 425/44/89 split. Its hidden widths were 32 and 16, with factor ranks $(8, 8, 1)$. For a Bayesian layer, a sampled weight matrix is represented by low-rank factors

$$W = AB^\top, \qquad q(A)q(B)q(b) = \prod_r \mathcal{N}(\mu_r, \sigma_r^2). \tag{5}$$

Training minimizes a Monte Carlo estimate of

$$\mathcal{L} = \mathbb{E}_{q(W)}[-\log p(y \mid X, W)] + \lambda \,\mathrm{KL}[q(W) \| p(W)]. \tag{6}$$

Both random and SVD-based mean initialization were tested. Posterior predictive probabilities average softmax predictions over sampled weights. Mutual information between the sampled predictions and their mean estimates epistemic uncertainty.

The SBNN achieved 56.2% top-1 and 87.6% top-5 on the same development set. The result did not justify replacing the rule. It motivated a larger and cleaner variant-level task.

11 Temporal ClinVar experiment

11.1 Why a temporal split

Random ClinVar splits leak stable gene and annotation patterns. A temporal split asks a more useful question: can a model trained on the 26 December 2023 knowledge state classify records whose Variation IDs were absent then and appeared by 29 August 2026? Archived ClinVar releases make this test reproducible [National Center for Biotechnology Information, 2026].

The historical release supplied 1,084,930 unambiguous benign/pathogenic labels. A balanced 60,000-variant training set contained 30,000 pathogenic variants across 5,043 genes. A 15,000-variant gene-disjoint validation set contained 1,209 genes. The temporal test contained 626,287 new records, including 117,147 pathogenic variants across 14,715 genes.

11.2 Fifty molecular features

No clinical-significance label or disease name was used as an input. Features included reference/alternate length, variant type, transition status, substitution class, population frequency and missingness, dbSNP availability, germline/inherited/de-novo origin flags, review-level indicators, molecular consequence categories, and three gene-history quantities computed only from the training split: training count, pathogenic rate, and an unseen-gene flag.

11.3 Core baselines

Four aligned models used the same data and features:

- histogram gradient boosting, a strong nonlinear tabular baseline;
- a dense 50-32-16-1 MLP;
- a five-member independently trained MLP ensemble [Lakshminarayanan et al., 2017];
- a low-rank SBNN with ranks $(8, 8, 1)$ [Toure and Stephens, 2026].

The temporal set was then split by ClinVar Variation-ID parity. Even IDs selected a consensus weight; 313,171 odd IDs remained untouched. The selected consensus was 0.30 gradient boost, 0.20 deep ensemble, and 0.50 SBNN.




Figure 3: Every transferred model places the accepted pair first, but the EPCR threshold that isolates it varies widely. A perfect F-max on one child is not a calibration comparison.

The pair remains first because the upstream candidate construction is already strong: only biologically plausible same-gene pairs survive, direct cis evidence is removed, the *BUB1B* pair combines a pathogenic stop-gain with an ultra-rare coding partner, and its phenotype score is high. The learned models order this compact set consistently. This is reassuring for robustness but cannot identify the best generalizing model.

12 Temporal molecular results

Table 3: Untouched odd-ID temporal holdout. Ranking cases contain one pathogenic variant and 99 temporal benign variants.

Model	PR-AUC	F-max	NLL	Top-1	Top-5	OOD AUROC
Gradient boost	0.9674	0.9030	0.1924	81.50%	94.05%	–
Deep ensemble	0.9688	0.9095	**0.1245**	80.25%	95.00%	**0.7485**
Small SBNN	0.9691	0.9173	0.1332	82.10%	94.30%	0.6020*
Consensus	0.9731	0.9181	0.1358	83.65%	94.80%	–
Dense BBB	0.9729	0.9202	0.1245	83.00%	94.55%	0.6665
Wide rank-50 SBNN	**0.9736**	**0.9235**	0.1232	**84.35%**	94.85%	0.6284
Wide dense BBB	0.9718	0.9200	0.1276	81.35%	**95.05%**	0.6567

*The original small-SBNN OOD result was computed on the full temporal set; it is context rather than a perfectly matched holdout value.

13 Bayesian architecture experiments

13.1 Factorial SBNN sweep

We tested the interaction between rank, KL weight, posterior scale initialization, and broad prior scale rather than changing one variable at a time. The full grid contained 375 configurations:

- ranks $(8, 4, 1)$, $(8, 8, 1)$, $(16, 8, 1)$, $(16, 16, 1)$, and $(32, 16, 1)$;
- KL weights 0.001, 0.01, 0.1, 1, and 3;
- posterior scale multipliers 0.1, 0.3, 1, 3, and 10;
- broad prior standard deviations 0.3, 1, and 3.

The best confirmed compact configuration used ranks $(8, 4, 1)$, KL 0.01, posterior multiplier 0.1, and prior scale 0.3. Its unseen-gene OOD AUROC was 0.6231, up from 0.6020, but below the deep ensemble's 0.7485. Some screen configurations exceeded 0.70 OOD AUROC only by degrading classification toward chance. These were rejected rather than promoted as uncertainty improvements.

13.2 Full-weight Bayes by Backprop

The low-rank posterior couples uncertainty through A and B. A dense BBB model instead assigns every weight and bias an independent Gaussian mean and rho [Blundell et al., 2015]. A 75-cell grid crossed rho initialization $\{-8, -6, -5, -4, -3\}$, KL weight $\{0.001, 0.01, 0.1, 1, 3\}$, and prior scale $\{0.3, 1, 3\}$. The winner used rho -4, KL 0.1, and prior scale 0.3.

Dense BBB used 4,354 variational scalars, versus 10,885 fitted weights across the five-network ensemble. On the untouched holdout it achieved 83.0% top-1, F-max 0.9202, and OOD AUROC 0.6665. It improved ranking over the ensemble but did not match ensemble OOD detection.

13.3 Wider low-rank and dense models

To test whether the original network was simply too small, widths increased from 32-16 to 200-100. Ranks 8, 16, 32, 50, and the algebraically full factorization were crossed with KL and posterior-scale settings. The selected rank-50 SBNN used 55,804 variational scalars, only 8% fewer than the matching wide dense BBB. It achieved the best temporal top-1 (84.35%), PR-AUC (0.9736), F-max (0.9235), and 80%-coverage balanced accuracy (99.12%). Its OOD AUROC remained 0.6284.

This is an important result: increasing rank and width improved the main classification task but did not create ensemble-like function-space diversity.

13.4 Why the SBNN is the scalable Bayesian component

The parameterization changes how Bayesian memory and optimization cost grow with layer width. For a dense layer $W \in \mathbb{R}^{d_{\text{in}} \times d_{\text{out}}}$, mean-field BBB stores a posterior mean and scale for every weight, requiring approximately

$$2 d_{\text{in}} d_{\text{out}} \tag{7}$$

variational scalars before biases. An SBNN factorizes $W = AB^{\top}$ with rank r and places variational distributions on the factors. Its corresponding count is approximately

$$2r \left(d_{\text{in}} + d_{\text{out}} \right). \tag{8}$$

Dense BBB therefore grows quadratically for equal-width layers, while a fixed-rank SBNN grows linearly with width [Toure and Stephens, 2026, Blundell et al., 2015]. The ratio is approximately $r(d_{\text{in}} + d_{\text{out}})/(d_{\text{in}}d_{\text{out}})$, or $2r/d$ for a square width-d layer.

The distinction matters beyond this compact experiment. The selected rank-50 SBNN used 55,804 variational scalars, only 8% fewer than the matched wide dense BBB because rank 50 is not very small relative to widths 200 and 100. This measured saving should not be exaggerated. For substantially wider layers with rank held below the layer widths, the gap grows quickly. Training state, gradients, and optimizer memory follow the same parameter-count reduction. A single fitted SBNN posterior also avoids storing and optimizing M complete networks as required by an M-member deep ensemble [Lakshminarayanan et al., 2017]. Monte Carlo inference still costs multiple forward passes, but those samples share one learned posterior and can be batched. The practical advantage is reduced model and training-state memory with a tunable rank–accuracy tradeoff, not free uncertainty estimation.

14 Track 1 comparison: every compatible model finds the pair

The official evaluator logic was reproduced locally against the accepted pair. The earlier deterministic CSV and the selected wide rank-50 SBNN CSV were both uploaded and independently confirmed by the live Hugging Face evaluator. The remaining learned CSVs were scored locally using the same logic. For the SBNN submission, the live threshold of 0.3724070924857989 exactly matches the locally reproduced threshold.

Table 4: Exact child-level results.

Method	Rows	Pair rank	Rank Points	F-max	Status
Bonaventure deterministic WGS	6	1	100	1.000	Uploaded and leaderboard-confirmed
Linear Bayesian, strict	6	1	100	1.000	Local official-equivalent score
Linear Bayesian, broad	10	1	100	1.000	Local official-equivalent score
Pair SBNN, strict	6	1	100	1.000	Local official-equivalent score
Pair SBNN, broad	10	1	100	1.000	Local official-equivalent score
Gradient boost adapter	6	1	100	1.000	Local official-equivalent score
Dense MLP adapter	6	1	100	1.000	Local official-equivalent score
Deep ensemble adapter	6	1	100	1.000	Local official-equivalent score
Small SBNN adapter	6	1	100	1.000	Local official-equivalent score
Dense BBB adapter	6	1	100	1.000	Local official-equivalent score
Wide rank-50 SBNN adapter	6	1	100	1.000	Uploaded as Submission 2; platform-confirmed
Wide dense BBB adapter	6	1	100	1.000	Local official-equivalent score

Method	Rows	Pair rank	Rank Points	F-max	Status	
Temporal consensus adapter	6	1	100	1.000	Local score	official-equivalent
Predictor-augmented SBNN adapter	6	1	100	1.000	Local score	official-equivalent

14.1 Result Analysis

Every entry in the table uses the same 50 molecular features and the same untouched odd-ID test cases. For the ranking columns, 2,000 pathogenic temporal variants were each placed among 99 benign temporal variants sampled with a fixed seed. Top-1 and top-5 report where the known pathogenic item appears in that 100-candidate list. PR-AUC and F-max are calculated over all 313,171 odd-ID records. NLL evaluates probability quality and penalizes confident errors. OOD AUROC asks whether a model-specific uncertainty score can distinguish variants in genes absent from the 2023 training set; it is not another pathogenicity score. The consensus weights were chosen on even Variation IDs before the odd-ID table was evaluated.

Gradient boosting is the strong non-Bayesian tabular baseline. Its 81.5% top-1 and 0.9674 PR-AUC show that much of the signal is already present in the engineered molecular features. It has no posterior or independently trained members, so we do not assign it a stochastic OOD score.

The five-network ensemble averages five dense networks trained independently from different initial conditions. Its top-1 result, 80.25%, is not the best ranking result, but its NLL of 0.1245 and unseen-gene AUROC of 0.7485 are the strongest tested calibration and OOD combination. The disagreement is useful because independently optimized networks reach different function-space solutions.

The original small SBNN replaces deterministic dense layers with low-rank Gaussian factors and averages Monte Carlo weight samples. It improves top-1 to 82.1%, but its 0.602 OOD AUROC is weak. This negative result is why rank, width, posterior initialization, prior scale, and KL weight were studied jointly rather than assuming that a Bayesian label guarantees useful uncertainty.

The temporal consensus combines gradient boosting, the ensemble, and the small SBNN using weights selected on the even-ID partition. It raises top-1 to 83.65% and PR-AUC to 0.9731. This is evidence that their errors are complementary, although its score is a predictive mixture rather than a single coherent posterior.

Dense BBB assigns an independent Gaussian mean and scale to every network parameter. Its 83.0% top-1, 0.9729 PR-AUC, and 0.6665 OOD AUROC improve on the small SBNN's ranking and OOD behavior. It still does not match the ensemble's unseen-gene detection.

The wide rank-50 SBNN uses 200- and 100-unit hidden layers and much less restrictive factors. It gives the best tested ranking: 84.35% top-1, PR-AUC 0.9736, and F-max 0.9235. Its OOD AUROC remains 0.6284, so the result supports the larger SBNN as a pathogenicity ranker, not as the final uncertainty gate.

The wide dense BBB is the matching full-weight Bayesian comparison. It reaches 81.35% top-1 and 0.6567 OOD AUROC, with the best top-5 value at 95.05%. Widening alone therefore does not explain the rank-50 SBNN's top-1 gain, and a dense posterior does not automatically reproduce the ensemble's diversity.




Figure 4: Task ranking, F-max, and unseen-gene detection favor different models. Empty OOD bars indicate that no model-specific stochastic uncertainty was defined for that method.




Figure 5: Parameter count alone does not explain performance. The wide rank-50 SBNN gives the best ranking, while the smaller deep ensemble gives the strongest OOD signal because its members occupy independently optimized function-space modes.

15 External patient-level generalization

15.1 Construction without test leakage

We next used Phenopacket Store cases with one or two exact GRCh38 causal variants. A causal hypothesis entered the test only when every causal coordinate was absent from the raw 2023 ClinVar snapshot and

pathogenic in the 2026 snapshot. Repeated causal hypotheses were deduplicated. This retained 719 post-2023 cases from 265 genes: 655 single-variant and 64 two-variant cases.

Each case had one causal hypothesis and nine temporally new benign ClinVar hypotheses. Single-variant decoys were matched on variant type and consequence group when possible. Two-variant decoys contained two benign alleles in one gene. The molecular score of a pair was the geometric mean of its allele probabilities. Ten candidates imply a 10% random top-1 baseline.

The HPO layer used only the 9 October 2023 ontology. Older solved cases were split into 1,388 phenotype-reference cases and 843 weight-selection cases. The validation split included familiar genes and genes entirely removed from the reference. For candidate gene g and patient phenotype set Q, the score was the best symmetric Resnik similarity between Q and an older case for g. Each model selected a molecular/HPO coefficient and missing-gene prior on the 843 older cases; the 719 post-2023 patients remained untouched.

Five independent benign candidate cohorts tested sensitivity to decoy composition. Reported means and sample standard deviations therefore reflect candidate resampling, not five independent patient cohorts.

15.2 Results

Table 5: Mean top-1 generalization across five candidate cohorts.

Model	Molecular	Molecular+HPO	Change	HPO top-5	Two-variant top-1
Gradient boost	30.6±1.3	56.5±0.6	+25.9	86.5	66.2
Dense MLP	29.2±0.8	55.9±2.0	+26.6	84.3	65.9
Deep ensemble	30.6±0.7	54.2±1.9	+23.6	85.0	64.1
Small SBNN	32.9±1.0	55.9±1.9	+23.1	85.3	61.6
Dense BBB	34.1±1.0	**58.9±1.0**	+24.8	88.5	65.6
Wide rank-50 SBNN	32.8±1.2	58.2±1.1	+25.4	86.6	64.7
Wide dense BBB	**34.2±1.4**	58.6±1.4	+24.4	85.9	**68.1**
Temporal consensus	34.0±0.5	57.3±1.7	+23.3	**88.6**	64.4




Figure 6: External patient-level ranking. Error bars in the left panel are standard deviations over five decoy cohorts. The two-variant subset is closest to the challenge's compound-heterozygous structure.

For dense BBB, HPO conditioning improved top-1 accuracy by 23.5–26.1 percentage points in every cohort. Each paired comparison gained 175–194 cases while losing only 2–6, with exact McNemar p-values between approximately 10^{-44} and 10^{-53}. The effect is statistically clear within this benchmark.

15.3 Known-gene and unseen-gene behavior

Of the 719 test cases, 337 had a causal gene represented in older phenotype cases and 382 did not. Dense BBB rose from 34.7% to 88.1% top-1 on the known-gene subset, but stayed near baseline on unseen genes (33.6% to 33.1%). The tuned missing-gene prior prevents a catastrophic penalty when phenotype knowledge is absent, but it does not invent knowledge about novel genes.




Figure 7: Phenotype matching works when the candidate gene has older phenotype evidence. Novel-gene diagnosis remains a molecular and discovery problem.

15.4 Phenotype corruption and disease novelty

We froze each model's HPO mixing coefficient after older-case validation and created three additional versions of the same 719-patient test: removal of 20% of observed HPO terms, removal of 40%, and addition of 20% unrelated terms. No coefficient was retuned on a corrupted test. On the fixed candidate cohort, temporal-consensus top-1 changed from 59.81% with the original HPO terms to 58.83%, 58.55%, and 59.39%, respectively. Wide rank-50 SBNN changed from 57.44% to 57.16%, 56.33%, and 56.88%. Moderate phenotype corruption therefore causes limited degradation in this compact setting.




Figure 8: Top-1 robustness after fixed phenotype corruption. This is one fixed candidate cohort, and the HPO weights remain those selected on older validation cases.

Disease novelty remains difficult. Among 390 test cases whose disease identifier was absent from the older reference, temporal consensus reached 34.36% top-1; among the 382 unseen-gene cases it reached 33.77%, compared with 89.32% on 337 seen-gene cases. The robustness result therefore does not erase the central limitation: ontology matching transfers well when older knowledge covers the causal gene or disease, but does not solve gene discovery.

The case-level evaluator records the causal hypothesis independently from the prediction table. If upstream filtering removes the truth, reciprocal rank is set to zero and end-to-end Top-k is a failure. In the current compact experiment, however, the causal hypothesis is inserted by construction, so the observed candidate recall of 1.0 is only a pipeline-integrity check. It is not an estimate of full-genome filtering sensitivity.

16 Full-background generalization beyond Track 1

16.1 Motivation and evaluation question

After achieving the maximum Track 1 score, we asked whether the trained ranking models could generalize beyond the challenge child to independent rare-disease cases. We therefore evaluated their ability to prioritize known causal variants in VarPB against exonic candidate backgrounds derived from 107 real genomes. Neither the challenge child nor the VarPB causal answers were used for model training. This experiment complements the compact Phenopacket analysis by testing the models in a substantially larger and more realistic candidate space, allowing us to distinguish success on one solved case from transferable variant-ranking performance.

16.2 From the initial stress test to the revised model

We downloaded the 96.7 MB VarPB background and the two small 2023 causal tables, not the 624 MB convenience archive or precomputed method matrices [Danzi, 2023]. A disk-backed SQLite index reduced 17,872,513 sample rows to 891,753 unique background variants. Adding the causal tables produced a union of 894,327 hg19 variants. OpenCRAVAT mapped 893,268; the exporter retained 1,059 failures as explicit missing values, including two causal variants, so all 2,577 causal keys remained evaluable.

The generalization study had two stages. We first applied the submission-era models without changing their training or features. Each method was evaluated on every causal variant crossed with all 107 backgrounds, giving 275,739 trials per method. ClinVar review and training-gene history were neutralized. The original small SBNN reached median rank 522, MRR 0.00213, and Top-100 0.20%; the wide rank-50 SBNN reached median rank 1,562. These results did not end the experiment. They showed that a feature contract designed for compact candidate reranking did not contain enough protein-level information to prioritize causal missense variants against a full exonic background.

We then evaluated REVEL and AlphaMissense as external pretrained comparators. Missing scores were set to zero rather than dropped, preserving all 894,327 keys. REVEL reached median rank 8.5 and Top-20 65.90%; AlphaMissense reached median rank 29 and Top-20 44.24%. This comparison identified the missing information and motivated a revised SBNN that combines the original molecular descriptors with both predictor scores and explicit missingness indicators. The final augmented model, described below, recovered competitive full-background recall while retaining a Bayesian posterior over its learned ranking function.

16.3 Predictor-augmented Bayesian ranking

The revised model is still an SBNN; it is not REVEL or AlphaMissense followed by a conventional dense classifier. The exact ClinVar GRCh38 archive from 26 December 2023 was downloaded from NCBI and matched the SHA-256 already recorded for the temporal experiment. A deterministic filter retained unambiguous pathogenic/likely-pathogenic or benign/likely-benign, biallelic SNVs whose molecular consequence contains `missense_variant`. From 2,340,600 input records, this produced 146,810 labeled missense SNVs: 54,548 pathogenic and 92,262 benign. The same REVEL and AlphaMissense modules annotated 146,786; 24 mapper failures remained as a zero value plus a separate missingness flag. REVEL and AlphaMissense were fixed feature generators: their parameters were neither updated nor treated as Bayesian.

The augmented vector has 54 inputs: the original 50 sequence, consequence, allele-frequency, review, origin, substitution, and training-only gene-history features, followed by the REVEL score, a REVEL-missing indicator, the AlphaMissense score, and an AlphaMissense-missing indicator. The previous wide SBNN used 50 inputs, a balanced cap of 30,000 variants per class, and pointwise pathogenic-versus-benign binary cross-entropy. The revised model uses the complete 146,810-variant labeled missense set and optimizes pairwise ordering. Genes were split 80/20 before fitting, yielding 117,700 training and 29,110 validation variants. VarPB and the challenge child were absent from training, validation, and hyperparameter selection.

For layer ℓ, the model places independent Gaussian variational posteriors on two low-rank factors and the bias. A posterior draw is

$$\begin{aligned} A_\ell^{(m)} &\sim q_\phi(A_\ell), \qquad B_\ell^{(m)} \sim q_\phi(B_\ell), \qquad b_\ell^{(m)} \sim q_\phi(b_\ell), \\ W_\ell^{(m)} &= A_\ell^{(m)} B_\ell^{(m)\top}, \qquad \sigma_\ell = \mathrm{softplus}(\rho_\ell), \qquad \ell = 1, 2, 3. \end{aligned} \tag{9}$$

Here $q_\phi(A_\ell)$, $q_\phi(B_\ell)$, and $q_\phi(b_\ell)$ are elementwise Gaussian distributions parameterized by learned means

and ρ values. Equation 9 is where the SBNN enters: the sampled dense weight matrix is never assigned an independent posterior; it is constructed from the sampled low-rank factors A_ℓ and B_ℓ. The architecture is 54-200-100-1 with ReLU hidden layers and ranks $(50, 50, 1)$. Its output $s_\phi(x)$ is a scalar pathogenicity logit.

Training uses Bayesian pairwise RankNet. For every minibatch, a pathogenic missense variant x_i^+ is paired with a benign missense variant x_i^-. Both pass through the same posterior draw, and the optimized objective is

$$\begin{aligned}\mathcal{L}(\phi) = \frac{1}{B}\sum_{i=1}^{B}\log\Big(1+\exp[-(s_\phi^{(m)}(x_i^+) - s_\phi^{(m)}(x_i^-))]\Big) \\ + \lambda\sum_{\ell=1}^{3}[\mathrm{KL}(q_\phi(A_\ell)\|p(A_\ell)) + \mathrm{KL}(q_\phi(B_\ell)\|p(B_\ell)) \\ +\mathrm{KL}(q_\phi(b_\ell)\|p(b_\ell))]\,.\end{aligned} \tag{10}$$

Here, "pairwise" refers to a pathogenic-versus-benign training pair; it does not mean that the neural network consumes a compound-heterozygous allele pair as one input. Using one draw for both training members ensures that the likelihood learns their ordering rather than differences caused by two unrelated posterior samples. The prior is a zero-mean Gaussian scale mixture with mixing probability 0.5, a tunable wide scale, and a narrow scale $\exp(-6)$. The complete $3 \times 2 \times 2 \times 2$ screen varied ranks {(16,16,1),(32,32,1),(50,50,1)}, KL weights {0.001,0.01}, posterior initialization scales {0.05,0.1}, and prior scales {0.3,1.0}. Widths, gene split, training budget, and selection metrics stayed fixed. The selected model used ranks $(50, 50, 1)$, KL weight 0.001, posterior scale 0.1, and prior scale 1.0. After full retraining, gene-disjoint validation reached Top-1 62.15%, Top-10 96.15%, MRR 0.7449, and mean rank 2.684 among 100 candidates.

Table 6: What changed between the submission-era wide SBNN and the predictor-augmented SBNN.

Component	Submission-era wide SBNN	Predictor-augmented SBNN
Input	50 ClinVar-derived molecular features	Same 50 features plus REVEL, AlphaMissense, and two missingness flags
Training cases	Balanced cap of 30,000 variants per class	All 146,810 eligible labeled missense variants
Objective	Pointwise binary cross-entropy plus KL	Shared-posterior-draw RankNet loss plus factorwise KL
Architecture	50-200-100-1, ranks $(50, 50, 1)$	54-200-100-1, ranks $(50, 50, 1)$
Selected regularization	KL 0.01; posterior scale 0.1; prior scale 0.3	KL 0.001; posterior scale 0.1; prior scale 1.0
Purpose	General molecular pathogenicity baseline	Full-background causal-variant prioritization with posterior uncertainty




Figure 9: Complete predictor-augmented SBNN workflow. Model selection uses only pre-2023 ClinVar with a gene-disjoint validation split. The frozen posterior is then evaluated independently on VarPB full-genome backgrounds and on the Track 1 compound-heterozygous shortlist.

Table 7: Locked VarPB v3 full-background generalization results. All methods retain complete score-file coverage.

Method	Median rank	Top-1	Top-20	Top-100	MRR
Augmented pairwise SBNN	14	7.26%	65.70%	**86.63%**	0.1596
REVEL	**8.5**	**12.48%**	**65.90%**	84.82%	**0.2516**
AlphaMissense	29	8.84%	44.24%	69.72%	0.1632
Original small SBNN	522	0.00%	0.00%	0.20%	0.0021
Wide rank-50 SBNN	1,562	0.00%	0.00%	0.08%	0.0011




Figure 10: Full-background ranking across 275,739 spike-in trials. Lower median rank is better. The augmented SBNN essentially matches REVEL at Top-20 and exceeds it at Top-100, but REVEL remains stronger at the top of the list.

The new result is competitive for clinically useful shortlist recall, not uniformly superior. Its Top-20 is within 0.20 percentage points of REVEL and its Top-100 is 1.81 points higher, while its Top-1 and MRR remain lower. It substantially exceeds AlphaMissense at Top-20 and Top-100 but is slightly weaker at Top-1 and MRR. Because REVEL and AlphaMissense are inputs, the contribution is Bayesian evidence integration and uncertainty-aware ranking, not independent rediscovery of their learned biology. VarPB still lacks native HPO and pedigree data and therefore remains a molecular-ranking benchmark rather than a complete clinical diagnostic cohort.

16.4 Transfer of the augmented model to the challenge child

We finally froze the same augmented checkpoint and applied it to the Track 1 candidates. This was a transfer evaluation, not another training or selection stage. Each candidate allele received the same 54-feature representation used in the VarPB experiment. For posterior draw m, the score of compound-heterozygous hypothesis j was

$$e_j^{(m)} = h_j \sqrt{\mathrm{sigmoid}(s_\phi^{(m)}(x_{j1}))\,\mathrm{sigmoid}(s_\phi^{(m)}(x_{j2}))}, \qquad \mathrm{EPCR}_j = \frac{1}{M}\sum_{m=1}^{M} e_j^{(m)}, \tag{11}$$

where h_j is Bonaventure's HPO phenotype-similarity score. The same weight draw was used for both alleles, and $M = 128$. Missing predictor values were represented by zero together with the corresponding missingness flag; among the 12 alleles in the strict six-pair shortlist, REVEL and AlphaMissense each covered nine.

The accepted *BUB1B* pair ranked first in both the strict and broad candidate sets. Under the locally reproduced official evaluator, the strict six-row file achieved Rank Points 100 and F-max 1.000, with an F-max threshold of 0.4332283540. The posterior standard deviation of the top pair's integrated score was 0.00788. Thus the model developed for stronger external transfer preserves the maximum child-level result achieved by every earlier adapter. This result is locally official-equivalent; unlike the selected submission-era wide SBNN, this augmented CSV has not been uploaded to the live evaluator.

16.5 Scalability and uncertainty of the augmented SBNN

For the architecture-matched 54-200-100-1 comparison, the augmented rank-50 SBNN contains 56,204 variational scalars. A dense BBB with identical widths contains 62,402, while five deterministic networks contain 156,005 stored weights. The SBNN therefore uses 9.9% fewer fitted scalars than dense BBB and 64.0% fewer than the five-network ensemble. With Adam, parameters plus two optimizer arrays require 168,612 scalars for the SBNN and 187,206 for dense BBB, excluding activations. Ensemble members can be trained sequentially to lower peak optimizer memory, but all five point estimates are retained at inference. The SBNN checkpoint, which also contains the scaler and gene statistics, is 670,999 bytes.

The modest 9.9% dense-BBB saving should not be overstated: rank 50 is close to the smaller hidden width. The structural advantage appears as width grows. A dense BBB square layer requires approximately $2d^2$ variational scalars, whereas a fixed-rank SBNN requires approximately $4rd$; training gradients and optimizer state follow the same scaling. Posterior Monte Carlo inference still requires repeated forward passes and therefore trades compute for uncertainty estimates.

REVEL and AlphaMissense return deterministic pathogenicity scores in their standard outputs [Ioannidis et al., 2016, Cheng et al., 2023]. They do not natively return posterior samples, predictive standard deviation, or epistemic mutual information. The SBNN produces these quantities from one learned posterior. This is an architectural capability, not automatic evidence of good calibration: the augmented model's gene-disjoint validation mean mutual information was 0.000118 and mean predictive standard deviation was 0.00337, while VarPB supplies no OOD label with which to validate them. A separate distribution-shift benchmark is required before claiming superior uncertainty or referral performance.

Finally, the count above describes the added Bayesian ranker, not the complete annotation stack. Because REVEL and AlphaMissense are inputs, the augmented system inherits their upstream compute and storage. The defensible scalability claim is that evidence integration and posterior uncertainty add only a compact, rank-controlled model, not that the full pipeline replaces its external predictors.




Figure 11: Left: fitted-scalar counts for architecture-matched rankers. Right: uncertainty quantities available directly from each standard model output. Deep ensembles provide member-disagreement uncertainty but require multiple separately fitted networks; REVEL and AlphaMissense provide deterministic scores rather than posterior uncertainty.

17 Calibration, uncertainty, and what Bayesian means here

Three distinct probability concepts occur in the project:

1. the deterministic EPCR submitted for one child, a monotone ranking confidence;
2. posterior predictive probabilities from Bayesian weight distributions;
3. the clinical posterior probability of pathogenicity under ACMG/AMP evidence.

They are not interchangeable. ACMG/AMP evidence can be expressed in Bayesian odds [Tavtigian et al., 2018], but that does not make a neural posterior clinically calibrated.

For posterior samples $p_m(y \mid x)$, predictive entropy is

$$H[\bar{p}], \qquad \bar{p} = \frac{1}{M} \sum_{m=1}^{M} p_m, \tag{12}$$

and epistemic mutual information is

$$I[y, W \mid x, D] = H[\bar{p}] - \frac{1}{M} \sum_{m=1}^{M} H[p_m]. \tag{13}$$

More Monte Carlo draws estimate the same posterior more accurately; they do not turn one narrow posterior into an ensemble of independently optimized modes.

This may explain the observed OOD gap. The tuned low-rank SBNN's mean predictive standard deviation rose from 0.00157 on known genes to 0.00403 on unseen genes. The deep ensemble rose from 0.01179 to 0.03569. Both react to shift, but the ensemble's function-space dispersion is roughly an order of magnitude larger. The honest conclusion is that the current Bayesian models improve several ranking and selective-prediction metrics, while the deterministic deep ensemble remains the strongest unseen-gene detector.

18 How this compares with real rare-disease ML

Production systems are hybrid. Exomiser combines frequency, predicted pathogenicity, pedigree, and phenotype evidence [Smedley et al., 2015]. LIRICAL uses interpretable phenotype likelihood ratios with genotype information [Robinson et al., 2020]. MAVERICK trains on large variant datasets and adds structured inheritance reasoning [Danzi et al., 2023]. AI-MARRVEL trained a random forest on more than 3.5 million variants from diagnosed cases and combined learned predictions with expert-engineered features [Mao et al., 2024]. In the CAGI Rare Genomes Project, leading teams recovered up to 13 of 14 solved test families in their top five while still requiring clinical review [Stenton et al., 2024].

Our design follows the same layered logic at smaller scale. The causal hypothesis must survive candidate generation before any ranker can score it. Molecular pathogenicity, phenotype compatibility, inheritance, phase, and read validity are distinct evidence sources. The Bayesian contribution is most defensible where uncertainty changes a decision: referral, abstention, reanalysis, or selection of an additional experiment.

19 Summary of established results

19.1 Established by executed artifacts

- The uploaded deterministic pipeline found the accepted *BUB1B* pair at rank 1 and achieved Rank Points 100 and F-max 1.0.

- The uploaded wide rank-50 SBNN reproduced the full match at rank 1, Rank Points 100, and F-max 1.000 on the live Hugging Face evaluator. Its reported F-max EPCR threshold, 0.3724070924857989, matches the local audit exactly.
- Every other compatible learned adapter also ranks the pair first under the locally reproduced official evaluator.
- The temporal training corpus contains more than one million historical labeled variants and 626,287 new-ID test variants.
- Wide rank-50 SBNN gives the best temporal simulated ranking and F-max among tested models.
- Deep-ensemble disagreement is the best tested unseen-gene detector.
- HPO conditioning selected only on older cases materially improves compact post-2023 patient ranking.
- With frozen HPO weights, moderate term removal or unrelated-term addition changes top-1 by only a few percentage points on the fixed compact cohort.
- Case-level outputs now support end-to-end Top-k, MRR, calibration, selective prediction, and seen/unseen gene and disease audits without relying on aggregate summaries.
- Tests, seeds, model artifacts, and metric JSON files are retained.

19.2 Remaining gaps and next steps

- The second *BUB1B* allele has not been functionally proven pathogenic.
- The two alleles have not been directly shown to be in trans.
- The external 58.9% result is not full-exome diagnostic sensitivity.
- Candidate-generation recall has not been measured on an independent patient cohort.
- The submitted EPCR is not clinically calibrated across patients.
- No Bayesian model has beaten the deep ensemble on unseen-gene OOD detection.

20 Track 2 bridge: from diagnosis to a testable rescue strategy

The Track 1 mechanism suggests a Track 2 assay rather than an immediate drug claim. The p.Leu737Ter allele is loss of function. p.Asn1002Lys may affect BUBR1 abundance, localization, or kinase/checkpoint function, but this remains untested. The first experiment should therefore measure BUBR1 protein abundance and spindle-checkpoint function in patient-derived cells, with a CRISPR-corrected isogenic control and a *BUB1B* add-back positive control.

A compound screen should measure BUBR1 abundance/localization, mitotic timing under spindle perturbation, lagging chromosomes, micronuclei, premature chromatid separation, viability, proliferation, and DNA-damage signals. A Bayesian hierarchical dose-response model can estimate the posterior probability of meaningful multi-endpoint rescue without unacceptable toxicity and choose follow-up compound-dose combinations by expected information gain.

The NAD+/SIRT2/BUBR1 stabilization axis is a mechanistic lead because SIRT2-mediated deacetylation can stabilize BUBR1 and NMN increased BUBR1 abundance in a mouse context [North et al., 2014]. The balance among BUBR1, PP2A-B56, and Aurora B is another mechanistic control: loss of the BUBR1 pseudokinase domain reduces kinetochore PP2A-B56 recruitment and produces chromosome-alignment errors consistent with unbalanced Aurora B activity [Braga et al., 2020]. Neither study establishes an approved treatment for constitutional *BUB1B* deficiency. A winning Track 2 proposal should preregister rescue and toxicity endpoints and reject compounds that only suppress proliferation or kill aneuploid cells.

21 Reproducibility

21.1 Two computational environments

The WGS pipeline and the later Bayesian experiments ran in different environments because they solve very different computational problems.

Cluster WGS environment. Bonaventure's pipeline [Dossou, 2026] ran in an existing pip environment, using CPU execution and six alignment threads. The memory-safe alignment settings were 2,000 read pairs per Python batch, 2,000,000 read pairs per process-isolated shard, and a 10,000,000-base BWA chunk. Sharding bounds worker memory; it does not downsample reads. The repository pins `pysam==0.24.0`; it also requires pybwa, WhatsHap, OpenCRAVAT, python-docx, openpyxl, certifi, pandas, NumPy, SciPy, and tqdm. The locally installed OpenCRAVAT resources observed during analysis were ClinVar 2026.07.01, gnomAD v2.1, gnomAD3 v3, REVEL v4.3a, SpliceAI v4.0, and CADD v1.6. Their combined storage requirement was about 160 GB.

Bayesian ML and reporting environment. Every temporal model evaluation, HPO generalization run, statistical aggregation, unit test, and report-specific plot in the integrated repository [Toure and Dossou, 2026] was executed on CPU on a MacBook Pro with an Apple M2 chip, 8 CPU cores (4 performance and 4 efficiency), 8 GB RAM, and macOS 15.2 arm64. No GPU, PyTorch, TensorFlow, or accelerator backend was used. Python was 3.12.7 from Anaconda, compiled with Clang 14.0.6. NumPy used OpenBLAS 0.3.21.

Table 8: Exact local package versions.

Package	Version	Package	Version
NumPy	1.26.4	SciPy	1.13.1
scikit-learn	1.5.1	Matplotlib	3.9.2
pandas	2.2.2	joblib	1.4.2
threadpoolctl	3.5.0	pytest	7.4.4
Pillow	10.4.0	huggingface-hub	0.36.0

The pinned local environment is stored in `requirements-report.txt`. Running `python capture_environment.py` regenerates `report/environment_manifest.json`, including hardware, Python, package versions, and SHA-256 hashes for the compact public inputs.

21.2 Randomness and numerical execution

All temporal experiments use seed 20260905 unless an output records a different seed. The five patient-level candidate cohorts use seeds 20260905 through 20260909. Data partitions are deterministic: the first pair benchmark separates genes and source publications, the temporal consensus uses even Variation IDs for selection and odd IDs for holdout, and the post-2023 Phenopacket test is separated by exact coordinate absence from the 2023 ClinVar snapshot. Posterior draw counts are stored in each result JSON. The Track 1 linear Bayesian and pair-SBNN runs used 2,048 posterior draws; temporal experiments used the model-specific counts written to their experiment reports.

The implementations clip probabilities before logarithms, standardize features using training-only statistics, replace near-zero feature scales with one, and keep pair scoring symmetric through a geometric mean. These details avoid seed-dependent NaNs, division by zero, and allele-order artifacts.

21.3 Code map

The code map combines the imported genome-wide workflow with the Bayesian modeling, evaluation, and reporting modules maintained in the integrated repository [Dossou, 2026, Toure and Dossou, 2026].

File	Role
`mva_track1_pipeline.py`	Bonaventure's genome-wide processing, annotation, phenotype scoring, filtering, pair construction, and export.
`shared_pair_features.py`	Fifteen features shared by pair training and Track 1 inference.
`bayesian_pair_ranker.py`	Conditional-logit MAP fit and Laplace posterior.
`sbnn_pair_ranker.py`	Low-rank SBNN and dense BBB layers, posterior sampling, and KL terms.
`clinvar_temporal_experiment.py`	Temporal dataset parsing, 50-feature construction, baselines, ranking, calibration, and uncertainty.
`tune_sbnn_temporal.py`	Factorial SBNN hyperparameter sweep.
`full_bbb_temporal_experiment.py`	Dense Bayes-by-Backprop comparison.
`wide_rank_temporal_experiment.py`	Width and rank experiment.
`verify_temporal_models_track1.py`	Common Track 1 adapter and exact scoring audit for temporal models.
`phenopacket_hpo_generalization.py`	Leakage-controlled post-2023 patient benchmark with HPO conditioning.
`patient_generalization_benchmark.py`	Case-level candidate recall, ranking, calibration, OOD, selective prediction, and novelty strata.
`score_varpb_models.py`	Bounded-memory export of all fitted models in the public VarPB new-tool format.
`prepare_varpb_opencravat.py`	Disk-backed VarPB union construction, original-coordinate recovery, and coverage-preserving exports.
`prepare_clinvar_predictor_training.py`	Deterministic leakage-controlled filter for the pre-2023 labeled-missense training set.
`augmented_sbnn_varpb_experiment.py`	Joint factorial screen, shared-draw pairwise SBNN training, and locked VarPB inference.
`models/augmented_pairwise_sbnn.py`	Fixed architecture and selected hyperparameters for the augmented SBNN.
`evaluate_augmented_sbnn_track1.py`	Frozen augmented-SBNN transfer to the Track 1 pairs, posterior pair integration, and exact score audit.
`evaluate_varpb_2023.py`	Exact causal-by-background rank evaluator for the 2023 VarPB protocol.
`evaluate_varpb_suite.py`	Multi-model VarPB aggregation and plotting.
`aggregate_hpo_generalization.py`	Five-seed aggregation and uncertainty summaries.
`report_visualizations.py`	Rebuilds every report-specific figure from JSON artifacts.

21.4 Rebuilding figures and PDF

From the repository root:

```
./build_report.sh
```

This one command captures the local environment, rebuilds the eleven figures, runs the unit suite, re-scores the stored Track 1 outputs, and compiles the cited PDF. It uses retained checkpoints and compact result artifacts; it neither downloads the 85 GB challenge bundle nor retrains the expensive models. The individual report commands are:

```
python report_visualizations.py --output-dir report/figures
cd report
```

```
pdflatex main.tex
bibtex main
pdflatex main.tex
pdflatex main.tex
```

The unit suite is:

```
python -m pytest test_sbnn_pair_ranker.py \
  test_bayesian_integration.py test_audit_submission.py \
  test_clinvar_temporal_experiment.py -q
```

21.5 AI assistance disclosure

Coding agents helped with implementation, documentation, and reproducibility checks. The team reviewed the code, experimental design, outputs, and scientific claims.

22 Conclusions

22.1 Track 1 result and comparative evidence

The child's result is stable. A pathogenic *BUB1B* stop-gain and an ultra-rare missense partner explain the MVA phenotype better than the retained alternatives, and the pair remains first under deterministic, linear Bayesian, ensemble, low-rank Bayesian, full-weight Bayesian, wide, consensus, phenotype-conditioned, and predictor-augmented scoring.

The perfect leaderboard score is the beginning of the argument, not the end. The evidence that distinguishes the submission is the genome-wide discovery without a manual disease-gene bonus, the nearly complete annotation join, conservative handling of phase and the uncertain second allele, exact attribution of upstream features, temporal training and holdout design, factorial Bayesian experiments, honest negative OOD results, and patient-level transfer across hundreds of later solved cases.

No one model wins every metric. The wide rank-50 SBNN is the strongest tested temporal ranker and the Bayesian architecture with the clearest path to larger networks because its parameter and optimizer-state costs are controlled by rank rather than the full weight-matrix size. Dense BBB is the strongest overall HPO-conditioned external model. Wide dense BBB is strongest on the challenge-like two-variant subset. The deep ensemble is the strongest OOD detector. The correct final system is modular: deterministic biological validity, learned molecular evidence, ontology-aware phenotype matching, explicit inheritance logic, and uncertainty used to decide when evidence is insufficient.

To test whether the learned ranking functions transferred beyond the challenge child, we next used PhEval-style evaluation structure and VarPB's 107 genome backgrounds [Bridges et al., 2025, Danzi, 2023].

22.2 Generalization beyond the challenge child

The first full-background test showed that the original 50-feature models did not transfer from compact candidate sets to exome-scale missense ranking. Treating that result as a model-design diagnosis led to the predictor-augmented pairwise SBNN. The revised model is competitive with REVEL for Top-20 recall, exceeds it at Top-100, and retains complete coverage across 275,739 trials. When the same frozen

checkpoint is transferred back to Track 1, it ranks the accepted *BUB1B* pair first and reproduces Rank Points 100 and F-max 1.000 under the local official-equivalent evaluator. The combined evidence supports transfer of the learned ranking function beyond one child, but not universal superiority: REVEL remains better at Top-1, median rank, and MRR, and an independent clinical cohort with native HPO, pedigree, and VCF data remains necessary.

A Feature definitions for the first pair models

Feature	Meaning
`phenotype_score`	Bonaventure pipeline's HPO-based compatibility between the patient's terms and the candidate gene.
`min/max_consequence`	Weakest and strongest normalized consequence severity among the two alleles. The minimum matters because both alleles must plausibly damage a recessive gene.
`min/mean_rarity`	Rarity evidence across the pair. A frequent second allele weakens a recessive hypothesis.
`max_population_af`	Largest observed AF among the two alleles.
`af_observed_fraction`	Fraction of alleles with a measured AF, separating missingness from a true zero.
`min/max_cadd`	CADD PHRED divided by 40 and clipped to $[0, 1]$.
`cadd_observed_fraction`	Whether zero means missing or measured.
`min/max_spliceai`	SpliceAI delta evidence across alleles.
`spliceai_observed_fraction`	Availability of splice predictions.
`phenotype x min consequence`	Interaction requiring phenotype and both-allele molecular plausibility.
`phenotype x min rarity`	Interaction requiring phenotype and two rare alleles.

B Metric definitions

Top-k Fraction of ranking cases whose causal item is among the first k candidates.
MRR Mean reciprocal rank, $N^{-1} \sum_i 1/r_i$.
PR-AUC Area under precision-recall curve; emphasized because pathogenic variants are the minority in the temporal test.
NLL Negative log likelihood; penalizes confident wrong predictions.
Brier score Mean squared error of predicted probabilities.
ECE Expected calibration error over 15 bins; descriptive and bin-dependent.
OOD AUROC Ability of an uncertainty score to distinguish variants from genes unseen during training.
Selective accuracy Accuracy after retaining only the least-uncertain fraction of predictions.

C Public input checksums

```
510c54e3fd04b0786f0a110bab63853e9e8fc3e9dde9e07ce7bc83f10cb63786 clinvar_20231226.vcf.gz
e72f5619f003c80cb3051afcb0c1f11c4409741054b48bbfd0ced03046ec91f9 clinvar_20260829.vcf.gz
d0c70005bb09b87035087516252b6b539fbc0415be7c664b73c9cde7eedf205a all_phenopackets_v0.1.27.zip
d3c1280f2780628cc2adc41d43ad92eab8fa4c2bab0f421e6334c7b1e6cd4e52 hp_2023-10-09.obo
```

References

Mame Diarra Toure and David A. Stephens. Singular bayesian neural networks. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL https://arxiv.org/abs/2602.00387. Accepted at ICML 2026; final proceedings volume and page numbers were not yet available at the time of this report. Preprint: arXiv:2602.00387.

Sage Bionetworks. Rare disease, real kid: MVA hackathon 2026 dataset. Hugging Face dataset repository, 2026a. URL https://huggingface.co/datasets/SageBio/mva-hackathon-2026-data. Gated CC BY 4.0 dataset; accessed by an authorized participant.

Sage Bionetworks. Rare disease, real kid: MVA hackathon 2026. Hugging Face Space, 2026b. URL https://huggingface.co/spaces/SageBio/rare-disease-real-kid-mva-hackathon-2026. Challenge rules and scoring; accessed 7 September 2026.

Sandra Hanks, Kim Coleman, Sarah Reid, Alberto Plaja, Helen Firth, David FitzPatrick, Alexa Kidd, Károly Méhes, Richard Nash, Nathanial Robin, Nora Shannon, John Tolmie, John Swansbury, Alexandre Irrthum, Jenny Douglas, and Nazneen Rahman. Constitutional aneuploidy and cancer predisposition caused by biallelic mutations in BUB1B. *Nature Genetics*, 36(11):1159–1161, 2004. doi: 10.1038/ng1449. URL https://doi.org/10.1038/ng1449.

Saskia J. E. Suijkerbuijk, Maria H. J. van Osch, Frank L. Bos, Sandra Hanks, Nazneen Rahman, and Geert J. P. L. Kops. Molecular causes for BUBR1 dysfunction in the human cancer predisposition syndrome mosaic variegated aneuploidy. *Cancer Research*, 70(12):4891–4900, 2010. doi: 10.1158/0008-5472.CAN-09-4319. URL https://doi.org/10.1158/0008-5472.CAN-09-4319.

Sebastian Köhler et al. The Human Phenotype Ontology in 2021. *Nucleic Acids Research*, 49(D1): D1207–D1217, 2021. doi: 10.1093/nar/gkaa1043. URL https://doi.org/10.1093/nar/gkaa1043.

National Center for Biotechnology Information. ClinVar: Downloads. NCBI data documentation, 2026. URL https://www.ncbi.nlm.nih.gov/clinvar/docs/downloads/. GRCh38 VCF release and archive access; accessed 7 September 2026.

Konrad J. Karczewski et al. The mutational constraint spectrum quantified from variation in 141,456 humans. *Nature*, 581(7809):434–443, 2020. doi: 10.1038/s41586-020-2308-7. URL https://doi.org/10.1038/s41586-020-2308-7.

Martin Kircher, Daniela M. Witten, Preti Jain, Brian J. O'Roak, Gregory M. Cooper, and Jay Shendure. A general framework for estimating the relative pathogenicity of human genetic variants. *Nature Genetics*, 46(3):310–315, 2014. doi: 10.1038/ng.2892. URL https://doi.org/10.1038/ng.2892.

Nilah M. Ioannidis et al. REVEL: An ensemble method for predicting the pathogenicity of rare missense variants. *The American Journal of Human Genetics*, 99(4):877–885, 2016. doi: 10.1016/j.ajhg.2016.08.016. URL https://doi.org/10.1016/j.ajhg.2016.08.016.

Kishore Jaganathan et al. Predicting splicing from primary sequence with deep learning. *Cell*, 176(3):535–548.e24, 2019. doi: 10.1016/j.cell.2018.12.015. URL https://doi.org/10.1016/j.cell.2018.12.015.

Bonaventure Dossou. hf_rare_disease. GitHub repository, 2026. URL https://github.com/bonaventuredossou/hf_rare_disease. Original genome-wide pipeline and Track 1 submission code; accessed 7 September 2026.

Mame Diarra Toure and Bonaventure F. P. Dossou. Rare disease, real kid: Bayesian ranking and generalization. GitHub repository, 2026. URL https://github.com/arradiat/Rare-Disease--Real-Kid.

Integrated challenge repository containing the imported genome-wide workflow, Bayesian modeling, comparative evaluation, external generalization experiments, visualizations, and reproducibility report; accessed 7 September 2026.

Daniel Danis et al. A corpus of GA4GH phenopackets: Case-level phenotyping for genomic diagnostics and discovery. *Human Genetics and Genomics Advances*, 6(1):100371, 2025. doi: 10.1016/j.xhgg.2024.100371. URL https://doi.org/10.1016/j.xhgg.2024.100371.

Monarch Initiative. Phenopacket Store, release 0.1.27. GitHub release archive, 2026. URL https://github.com/monarch-initiative/phenopacket-store/releases/tag/0.1.27. Dataset version used in this study; accessed 7 September 2026.

Matt Danzi. The variant prioritization benchmark (VarPB), 2023. URL https://doi.org/10.5281/zenodo.10291114.

Jun Cheng, Guido Novati, Joshua Pan, Clare Bycroft, Akvilė Žemgulytė, Taylor Applebaum, Alexander Pritzel, Lai Hong Wong, Michal Zielinski, Tobias Sargeant, Rosalia G. Schneider, Andrew W. Senior, John Jumper, Demis Hassabis, Pushmeet Kohli, and Žiga Avsec. Accurate proteome-wide missense variant effect prediction with AlphaMissense. *Science*, 381(6664):eadg7492, 2023. doi: 10.1126/science.adg7492. URL https://doi.org/10.1126/science.adg7492.

Sarah L. Stenton et al. Critical assessment of variant prioritization methods for rare disease diagnosis within the Rare Genomes Project. *Human Genomics*, 18(1):44, 2024. doi: 10.1186/s40246-024-00604-w. URL https://doi.org/10.1186/s40246-024-00604-w.

Matt C. Danzi, Maike F. Dohrn, Sarah Fazal, Danique Beijer, Adriana P. Rebelo, Vivian Cintra, and Stephan Züchner. Deep structured learning for variant prioritization in mendelian diseases. *Nature Communications*, 14(1):4167, 2023. doi: 10.1038/s41467-023-39306-7. URL https://doi.org/10.1038/s41467-023-39306-7.

Dongxue Mao, Chaozhong Liu, Linhua Wang, Rami Al-Ouran, Cole Deisseroth, Sasidhar Pasupuleti, Seon Young Kim, Lucian Li, Jill A. Rosenfeld, Linyan Meng, Lindsay C. Burrage, Michael F. Wangler, Shinya Yamamoto, Undiagnosed Diseases Network, Michael Santana, Victor Perez, Priyank Shukla, Christine M. Eng, Brendan Lee, Bo Yuan, Fan Xia, Hugo J. Bellen, Pengfei Liu, and Zhandong Liu. AI-MARRVEL—a knowledge-driven AI system for diagnosing mendelian disorders. *NEJM AI*, 1(5): AIoa2300009, 2024. doi: 10.1056/AIoa2300009. URL https://doi.org/10.1056/AIoa2300009.

Dominic Boceck, Lucia Laugwitz, Marc Sturm, Daniela Bezdan, Axel Gschwind, Tobias B. Haack, and Stephan Ossowski. aiDIVA–hybrid AI for rare disease diagnostics using evidence-based, machine learning and language models. *npj Genomic Medicine*, 11(1):49, 2026. doi: 10.1038/s41525-026-00611-x. URL https://doi.org/10.1038/s41525-026-00611-x.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in Neural Information Processing Systems 30*, 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/hash/9ef2ed4b7fd2c810847ffa5fa85bce38-Abstract.html.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural network. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 1613–1622. PMLR, 2015. URL https://proceedings.mlr.press/v37/blundell15.html.

Sean V. Tavtigian, Marc S. Greenblatt, Steven M. Harrison, Robert L. Nussbaum, Snehit A. Prabhu, Kenneth M. Boucher, and Leslie G. Biesecker. Modeling the ACMG/AMP variant classification guidelines as a bayesian classification framework. *Genetics in Medicine*, 20(9):1054–1060, 2018. doi: 10.1038/gim.2017.210. URL https://doi.org/10.1038/gim.2017.210.

Damian Smedley, Julius O. B. Jacobsen, Marten Jäger, Sebastian Köhler, Manuel Holtgrewe, Max Schubach, Enrico Siragusa, Tomasz Zemojtel, Orion J. Buske, Nicole L. Washington, William P. Bone, Melissa A. Haendel, and Peter N. Robinson. Next-generation diagnostics and disease-gene discovery with the Exomiser. *Nature Protocols*, 10(12):2004–2015, 2015. doi: 10.1038/nprot.2015.124. URL https://doi.org/10.1038/nprot.2015.124.

Peter N. Robinson, Vida Ravanmehr, Julius O. B. Jacobsen, Daniel Danis, Xingmin Aaron Zhang, Leigh C. Carmody, Michael A. Gargano, Courtney L. Thaxton, Guy Karlebach, Justin Reese, Manuel Holtgrewe, Sebastian Köhler, Julie A. McMurry, Melissa A. Haendel, and Damian Smedley. Interpretable clinical genomics with a likelihood ratio paradigm. *The American Journal of Human Genetics*, 107(3):403–417, 2020. doi: 10.1016/j.ajhg.2020.06.021. URL https://doi.org/10.1016/j.ajhg.2020.06.021.

Brian J. North, Michael A. Rosenberg, Karthik B. Jeganathan, Angela V. Hafner, Shaday Michan, Jing Dai, Darren J. Baker, Yana Cen, Lindsay E. Wu, Anthony A. Sauve, Jan M. van Deursen, Anthony Rosenzweig, and David A. Sinclair. SIRT2 induces the checkpoint kinase BubR1 to increase lifespan. *The EMBO Journal*, 33(13):1438–1453, 2014. doi: 10.15252/embj.201386907. URL https://doi.org/10.15252/embj.201386907.

Luciano Gama Braga, Angel F. Cisneros, Michelle M. Mathieu, Maxime Clerc, Pauline Garcia, Baptiste Lottin, Chantal Garand, Philippe Thebault, Christian R. Landry, and Sabine Elowe. BUBR1 pseudokinase domain promotes kinetochore PP2A-B56 recruitment, spindle checkpoint silencing, and chromosome alignment. *Cell Reports*, 33(7):108397, 2020. doi: 10.1016/j.celrep.2020.108397. URL https://doi.org/10.1016/j.celrep.2020.108397.

Yasemin Bridges, Vinicius de Souza, Katherina G. Cortes, Melissa Haendel, Nomi L. Harris, Daniel R. Korn, Nikolaos M. Marinakis, Nicolas Matentzoglu, James A. McLaughlin, Christopher J. Mungall, Aaron Odell, David Osumi-Sutherland, Peter N. Robinson, Damian Smedley, and Julius O. B. Jacobsen. Towards a standard benchmark for phenotype-driven variant and gene prioritisation algorithms: PhEval—phenotypic inference evaluation framework. *BMC Bioinformatics*, 26(1):87, 2025. doi: 10.1186/s12859-025-06105-4. URL https://doi.org/10.1186/s12859-025-06105-4.