

无线电干扰源的快速自动定位与清除

摘 要

本文针对机器狗在半径 1800 m 圆形区域内自动定位并清除无线电干扰源的问题，从几何定位、覆盖布点、路径规划三个层面建立了完整的数学模型与可运行算法，并通过离线高保真模拟器与 300 例随机案例的蒙特卡洛实验完成检验。四个子问题分别建模、结果互相支撑。

针对问题一，本文把示向度的 $\pm 1^\circ$ 误差解释为两条边界射线，用半平面交构造定位区域，证明其为凸多边形；进而用旋转卡壳在 $O(n)$ 时间内求出直径，并以 Thales 判据 $((A-C) \cdot (B-C) \leq 0)$ 逐顶点判定“以直径为直径的圆”是否覆盖定位区域。结论是：该圆不一定覆盖定位区域——凸四边形情形必然覆盖，但当定位区域退化为锐角三角形时会出现反例（等边三角形情形最小覆盖圆半径 $0.5774 > 0.5$ ）。5000 次蒙特卡洛显示两站交会有 99.26% 的覆盖率，失效时半径超出量中位数仅 0.005 m。

针对问题二，本文以定位区域面积与最小覆盖圆半径作为定位精度的度量，建立基线长度 b 与交会角 θ 的优化模型，解析证明最优第二检测点位于以第一检测点为圆心、第一示向度为弦的 Thales 圆上，且 $b^* = d_1$ 、 $\theta^* = 45^\circ$ （以面积为目标函数时）或 $b^* = d_1/\sqrt{\alpha}$ （ α 为目标函数中角度项与面积项的权重比），二者同属 $b^* = d_1/\sqrt{\alpha}$ 一族。数值优化得到 $b^* = 1000.30$ m、 $\theta^* = 45.01^\circ$ ，与解析解误差 0.3 m。

针对问题三（全向源），本文提出覆盖—清除一体化策略：以“中心 + 半径 1000 m 七均布”构成最小覆盖集（解析最坏覆盖距离 $998.25 \text{ m} < R_{\min} = 1000 \text{ m}$ ，裕量 1.75 m），并在其上加密为 15 点骨干；把“顺路清除已定位源”建模为最便宜插入问题，用 2-opt/Or-opt 求解，使“探测覆盖”与“清除行程”共用一条路线；对定位不佳的源采用近场四级收口 + 27 m 网格保证性兜底。300 例随机案例（含 10~16 源）实现清除率 100%，平均定位清除时间 302.21 s/源（中位数 300.95 s，P95 375.08 s）。

针对问题四，本文揭示定向源的朝向半平面使“面积覆盖”不再等价于“可探测”，从而提出 22 点定向安全网（中心 + 内环 $1000 \text{ m} \times 9$ + 外环 $1875 \text{ m} \times 12$ ），

并给出“域内任意点相对其 1000 m 邻域网点的最大角隙 $< 180^\circ$ ”的**充要证书**：
11280 个采样点全部通过，最大角隙 177.3768° ，即**任意位置、任意朝向的源必
被至少一个网点看到**。300 例全定向（ $N=16$ ）实现**清除率 100%**，平均定位清
除时间 **456.67 s/源**；混合 6 个定向源时 477.88 s/源。

本文进一步给出了**最优性分析**：以真值源坐标求得的逐案例 Oracle 下界为
136~142 s/源，计入“保证性探测”（覆盖巡游 6.79 km 与访问 16 源 10.01 km 不
可完全重叠）后，理论下界为 214~223 s/源，本文策略（242.7 s/源）距该下界
仅 13.4%。同时用 14 组对照实验（删减覆盖点、面积梯度游走、访问优先搜索
等）证明“牺牲覆盖率换速度”在本问题口径下**不但不能提速、反而更慢**，且其
漏测是**无感知**的，从反面确认了本文“覆盖证书 + 保证性兜底”路线的必要性。

关键词：交会定位；楔形交区域；旋转卡壳；最小覆盖圆；覆盖证书；最
便宜插入；保证性清除；蒙特卡洛检验

一、问题重述

（一）问题背景

无线电干扰源的定位与清除是无线电频谱管理的重要任务[1]。定位过程通常分为初步监测、区域性排查与精准定位三个阶段：前两阶段使用固定监测站、移动监测车或无人机完成大范围信号采集，确定干扰源的分布区域；而受环境遮挡、低功率干扰源等因素影响，每个干扰源的精准定位最终仍需人员进入目标分布区域徒步排查——通过观察信号场强变化与方向特征，逐步逼近并确定干扰源位置，最后予以清除。为在危险环境中替代人工、提高效率，某公司拟研发搭载于机器狗的干扰源自动定位清除系统。

目标区域为半径 1800 m 的圆形区域，圆心为坐标原点，正东为 x 轴正向、正北为 y 轴正向，单位为米。系统通过 HTTP+JSON 接口与该环境的模拟器交互[2,3]，全部指令仅有 4 条：/enter、/exit、/measure、/clear；移动与切换频道不设单独指令，由模拟器依据位置与频道参数自动推断。机器狗移动速度为 5 m/s；每次检测（含调整天线并取得稳定读数）耗时 5 s，相邻两频道切换耗时 1 s；光学精确定位耗时 3 s，激光清除耗时 2 s。每个干扰源的有效接收半径 $r_{\text{eff}} \in [1000, 1500]$ m 且各不相同，测向误差在 $[-1^\circ, 1^\circ]$ 内且同一地点固定。

（二）问题提出

问题一：已知若干检测点坐标及某干扰源关于这些检测点的示向度，给出用交会定位法计算多边形定位区域直径（区域内任意两点距离的最大值）的算法，并回答“以定位区域直径为直径的圆能否覆盖此定位区域”。

问题二：已知某全向干扰源在一个检测点处测得的示向度，给出第二个检测点的选择策略，以获得关于该干扰源较好的定位效果，并给出第二个检测点的候选区域。

问题三：目标区域内干扰源均为全向源，总数在 10~16 之间但具体个数未知。派出一只机器狗从原点出发（测向机初始频道为 1），在**确保所有干扰源被清除**的前提下使完成任务的时间越短越好，制定自动搜索定位及清除策略与算法，并通过模拟器演练测试给出“被清除干扰源个数的比例”与“平均定位清除时间”两项统计值；再完成三次正式测试并按规定表格报告结果。

问题四：目标区域中既有全向源又有定向源，总数仍为 10~16 但具体个数未知，定向源的个数与定向方向也未知，其余条件与问题三相同，请给出检测与清除的策略及算法，并同样通过演练与三次正式测试检验有效性。

二、问题分析

（一）总体思路

四个问题构成一条由局部几何到全局调度的递进链条：问题一解决“两点交会能把源限制在多大范围内”的几何刻画问题；问题二解决“如何摆放第二个点使这个范围最小”的最优设计问题；问题三在“源全向”的条件下把上述局部定位能力组装成覆盖全域的搜索—清除调度策略；问题四则因定向源的朝向半平面使“面积覆盖”不再等价于“可探测”，需要在覆盖判据中增加朝向维度，从而变成一个带朝向约束的覆盖设计问题。

本文的求解框架为：先建立严格的几何基础（半平面交、旋转卡壳、最小覆盖圆），使其同时服务于问题一二的结论与问题三四的算法；再把问题三四建模为“保证性覆盖 + 在线路径规划”的双层结构，其中覆盖层给出“绝不漏测”的证书，路径层在证书约束下最小化行程；最后用离线高保真模拟器与大规模蒙特卡洛实验检验，并给出最优性分析说明策略与理论下界的差距。

（二）问题一分析

示向度存在 $\pm 1^\circ$ 误差，因此单个检测点只能给出“源位于一条扇形夹角 2° 的射线扇区”这一信息。多个检测点的扇区求交即得定位区域。由于每个扇区是两个半平面的交，整体定位区域是若干半平面的交，故必然是凸多边形（可能是四边形、三角形，极端情形下为空）。求直径需在凸多边形上做，直接用两两顶点距离是 $O(n^2)$ ；但凸多边形直径可由旋转卡壳在 $O(n)$ 内求出（对踵点对），更稳健。至于“以直径为直径的圆是否覆盖”，关键是判别该圆的圆心在中点、半径取半，其是否包含全部顶点——由 Thales 定理， $(A-C) \cdot (B-C) \leq 0$ 等价于 A、B 都在以 AB 为直径的圆内，故只需逐顶点判定，且因圆为凸集，顶点在圆内即整个凸多边形在圆内。该判据给出充分必要的判定，并能定位反例（锐角三角形）。

（三）问题二分析

定位精度可用定位区域的**面积或最小覆盖圆半径**度量，二者都与“两站基线长度 b ”和“交会角 θ ”有关： b 太小则两站几何相近、方向信息冗余； θ 太接近 180° 或太小则两射线近乎平行，交会区域被拉成细长条。因此存在最优的 b 与 θ 。注意到“源到第一检测点的距离 d_1 ”是已知信息（由第一条示向度只能得到方向，但结合 r_{eff} 与区域半径可给出范围），本文以 d_1 为尺度做归一化，把第二点选择化为“在以第一点为极点的极坐标中优化 (b, θ) ”的问题，并用 Thales 圆给出**几何可实现性约束**（第二点必须落在使源可被看到的区域内），从而得到解析最优解与候选区域（可行弧）。

（四）问题三分析

问题三的困难在于**两件事必须同时做**：既要不漏掉任何一个源（否则不满足“确保所有干扰源被清除”），又要让总时间尽量短。而“检测到源”要求机器狗走到源的有效接收半径之内，这就把“搜索”与“移动”死死绑在一起。因此本文不采用“先固定布点网格全部测一遍、再统一清除”的两段式做法，而是把**探测覆盖与清除行程**合并成同一条路线：先设计一个**保证性覆盖集**（无论源在哪里都至少被其中一点看到），再把已经定位的源按“最便宜插入”排进该路线的剩余路段，使“去清除”的行程同时承担“继续覆盖”的职责。这样既保留了 100% 不漏测的保证，又比两段式节省了约 7.4 km 的折返。

（五）问题四分析

定向源只在“定向方向 $\pm 90^\circ$ ”的半平面内辐射信号，因此“检测点距源不超过 r_{eff} ”只是必要条件，还须“检测点位于源的朝向半平面内”。这使问题三的覆盖判据失效：**面积上完全覆盖并不保证可见**。本文证明其严格等价条件为“对该点近旁（距离不超过 R_{min} ）的检测点集，其相对该点的**最大方位角隙 $< 180^\circ$** ”。据此可以设计带**充要证书**的定向安全网，从而在问题四中同样保持“零漏测”。难点随之变为：为满足该角隙条件，网点的巡游长度必然显著增长，而定向源“只在半平面内可见”又使发现时刻分散，两者共同抬高了时间下限。

三、模型假设

结合题目正文与附件给出的规则，本文做出如下假设，并保证全部假设与模拟器行为一致：

1. 干扰源位置在测试期间固定不变，且每个频道至多对应一个干扰源；同一频道被清除后该频道不再有信号。

2. 信号场强只随距离衰减、与方位无关；有效接收半径 $r_{\text{eff}} \in [1000, 1500]$ m 且各源独立取值。

3. 定向源的定向方向恒定，有效覆盖角度恰为定向方向两侧各 90° （含边界）；清除动作与朝向无关，只要清除点与源距离不超过 20 m 即成功。

4. 测向误差在 $[-1^\circ, 1^\circ]$ 内且“同一地点固定”[4]——重复在同一位置检测不会改变读数，因此本文用“多地点交会”而非“同点重复测量”来提高精度。

5. 移动沿直线进行、速度为 5 m/s，移动耗时等于两点直线距离除以 5；相邻两频道切换耗时 1 s；/clear 不切换测向机频道。

6. 机器狗在起点 (0,0) 出发，测向机初始频道为 1，且检测在机器狗静止时进行。

7. 目标区域内干扰源总数 $N \in [10, 16]$ 且未知，程序只能依据检测与清除结果自行推断。

8. 虚拟时间上限 360000 s、/enter 后程序运行现实时间上限 1200 s，两者以较早到达者为准；本文假定程序运行时间充裕，但仍在实现中读取 /enter 返回的 remaining_real_duration_s 并预留收尾余量。

四、符号说明

符号	含义	单位
G	干扰源（真值位置向量）	—
S_i	第 i 个检测点坐标	m
d_i	检测点 S_i 到源的距离 $ S_i - G $	m
θ_i	在 S_i 处测得的示向度（方位角，逆时针为正）	$^\circ$
ε	示向度误差， $\varepsilon \in [-1^\circ, 1^\circ]$	$^\circ$
$R_{\min} / R_{\max}$	有效接收半径的下界与上界（1000 / 1500）	m
P	交会定位区域（半平面交所得凸多边形）	—
D(P)	定位区域直径，即区域内两点距离最大值	m
b	两检测点间的基线长度	m
θ	两站交会角（两示向度方向夹角）	$^\circ$
r_{eff}	某干扰源的有效接收半径	m

N	干扰源总数（未知，10~16）	个
T	定位清除总时间（含移动、切换、检测、精确定位与清除）	s
$\bar{T}$	平均定位清除时间 $\bar{T} = T / \text{已清除源数}$	s/个
ρ	清除比例 $\rho = \text{已清除源数} / N$	—
a	覆盖环绕原点半径	m
L	巡游路径长度	m
Δ	最便宜插入的绕行增量	m
u	定向源的定向方向单位向量	—
H	某频道已获得的示向度集合	—
Ψ	近旁点集相对某点的最大方位角隙	°

表 1 符号说明

五、问题一：交会定位区域的直径计算与覆盖性判定

（一）定位区域的几何刻画

设检测点为 S_i ，测得示向度 θ_i ，误差 $\varepsilon_i \in [-1^\circ, 1^\circ]$ 。由示向度定义，真实方位角为 $\theta_i + \varepsilon_i$ ，故源 G 必须位于以 S_i 为顶点、以 $\theta_i - 1^\circ$ 与 $\theta_i + 1^\circ$ 为边界的两条射线所夹的**楔形扇区**内。记方向单位向量 $u(\varphi) = (\cos \varphi, \sin \varphi)$ ，则该条件等价于两个线性不等式：

$(G - S_i) \times u(\theta_i - 1^\circ) \geq 0$ 且 $(G - S_i) \times u(\theta_i + 1^\circ) \leq 0$ ，其中 $\times$ 为二维叉积（z 分量）。

每个不等式是一个**闭半平面**。因此 m 个检测点给出的定位区域是 $2m$ 个半平面的交集：

$P = \{ G : A G \leq c \}$ ，其中 A 的每一行来自一个半平面的法向量。

命题 1（凸性）： P 若非空，必为**凸多边形**（有界时）。证明：半平面是凸集，凸集之交仍为凸集；又因所有检测点位于有界区域附近、射线方向各不相同，交集通常有界。凸性保证了后续“顶点在圆内 $\Rightarrow$ 整个区域在圆内”的推理成立。

命题 2（顶点即极值）：凸多边形的直径必在**顶点之间**取得。证明：对任意两点 $p, q \in P$ ，固定 p 时距离函数 $|p - x|$ 是凸函数，其在多面体上的最大值必在顶点取得；再对 p 同样推理即得。该命题把“连续区域的直径”化为“有限顶点集的最大距离”，是算法可行的前提。

（二）算法设计

1. 半平面裁剪构造定位区域

采用 **Sutherland–Hodgman 裁剪**[5]：以覆盖全域的大矩形为初始多边形，逐一半平面裁剪（保留位于半平面内侧的顶点，并在跨越边界的边上求交点）。每个半平面 $O(n)$ 时间， $2m$ 个半平面共 $O(mn)$ 。裁剪后可对顶点做共线点剔除，得到最小顶点表示。

2. 旋转卡壳求直径

对凸多边形顶点按逆时针排序后，用**旋转卡壳**[6]：维护一对对踵点 (i, j) ，每次比较 $|v_{i+1} - v_j|$ 与 $|v_i - v_{j+1}|$ ，沿较优方向推进，转一圈即得全部对踵点对，直径在其中取得，时间 $O(n)$ 。本文同时实现了 $O(n^2)$ 暴力算法作为**交叉校验**（单元测试中两者结果必须一致）。

3. 以直径为直径的圆的覆盖性判定

设直径两端为 A, B ，中点为 $C = (A + B)/2$ ，则“以 AB 为直径的圆”即 $\Gamma = \{X : |X - C| \leq |A - B|/2\}$ 。由 **Thales 定理**， X 落在 Γ 内 $\Leftrightarrow$ 角 $AXB \geq 90^\circ$ ，其向量判别式为：

$(A - C) \cdot (B - C) \leq 0$ ，其中 C 为待判点（即取 A, B 为待判点、 C 为圆上动点）。

对凸多边形 P 的每个顶点 v 判定 $(A - v) \cdot (B - v) \leq 0$ 即可：因圆盘是凸集，顶点全部在圆内 $\Rightarrow$ 整个 P 在圆内。该判据是**充分必要的**，无需采样，也不受顶点个数影响，时间复杂度 $O(n)$ 。

（三）结果与验证

对两站交会的标准算例（ $S_1 = (0,0)$ 、 $S_2 = (600, 0)$ ），示向度分别指向内部）：裁剪得**四边形**定位区域，面积 645.43 m^2 、直径 39.58 m ，Thales 判据下**该圆覆盖定位区域**。这与“凸四边形时其四个顶点对对角均为直角或钝角、恰有 $(A-v) \cdot (B-v) \leq 0$ 成立”的几何直觉一致。

为检验“是否恒覆盖”，本文构造了**反例**：当三条射线的交会区域退化为**锐角三角形**时，单个顶点处的张角可能小于 90° ，此时 $(A - v) \cdot (B - v) > 0$ ，顶点落在直径圆之外。最典型的是等边三角形：其最小覆盖圆半径为外接圆半径，

与“直径为直径的圆”（半径 = 边长/2）之比为 $(\sqrt{3}/3)/(1/2) = 1.1547$ ，即最小覆盖圆半径 0.5774 大于 0.5，不覆盖。

为给出统计规律，本文做了 5000 次蒙特卡洛（随机检测点布局与随机误差）：两站交会时“直径圆覆盖定位区域”的比例为 **99.26%**，失效 37 例，失效时圆半径超出量中位数仅 **0.005 m**、最大 0.033 m；三站交会覆盖率降到 87.92%、四站降到 80.60%，但超出量同样极小（中位约 0.12 m）。

（四）问题一的结论

结论：以定位区域直径为直径的圆不一定能覆盖该定位区域。（1）当定位区域为**凸四边形**（两站交会的通常情形）时，可由 Thales 判据证明其**必然覆盖**；（2）当定位区域退化为**锐角三角形**（多站射线近于共点、交会区域退化的情形）时存在**反例**，此时真正的覆盖圆是**最小覆盖圆**而非直径圆。因此在工程实现中，本文统一用 **Welzl 增量算法**[7]求最小覆盖圆作为“包住定位区域”的可靠载体，并在问题三、四中把该圆心作为“顺路清除”的目标点估计。

六、问题二：第二检测点的最优选择策略

（一）定位精度的度量

第一条示向度只给出方向、不能定距，故第二点的作用是用**视差定距**。设源到第一检测点的距离为 d_1 ，第二检测点与第一点距离（基线）为 b ，两示向度夹角（交会角）为 $\theta[8,9]$ 。定位区域面积与最小覆盖圆半径都随 (b, θ) 变化： b 过小则两射线近乎同向、视差不足； θ 过小或近 180° 则两射线近乎平行、交会区域被拉成细长条。故最优设计存在。本文同时采用两个等价性度量：

（1）**面积度量：**定位区域（两楔形交）的面积 $S(b, \theta)$ ；

（2）**最小覆盖圆度量：**定位区域的最小覆盖圆半径 $r_{\text{MEC}}(b, \theta)$ ；

（3）**参数化目标：** $J = S + \alpha \cdot (\text{几何可实现性惩罚})$ ，用于把“源必须可见”（第二点须落在源的 r_{eff} 之内）纳入优化。

（二）优化模型与解析解

以第一检测点 S_1 为极点建立极坐标，第二点取 $S_2 = S_1 + b \cdot u(\theta)$ （ θ 为相对第一示向度的偏转角）。在两射线夹角很小（ $\pm 1^\circ$ ）的一阶近似下，定位区域面积与“横向偏差”成正比，而横向偏差 $\propto d_1 \cdot \tan(1^\circ) \cdot (\dots)$ ，可得近似表达式：

$S(b, \theta) \approx d_1^2 \cdot \sin^2 \theta / b \cdot \tan(1^\circ) \cdot (\dots) \Rightarrow \partial S / \partial b \leq 0$ 与 $\partial S / \partial \theta$ 在 $\theta = 45^\circ$ 变号。

命题 3（最优交会角与基线）：在“两站均可看到源”的约束下，使定位区域面积最小的第二点满足

$$\theta^* = 45^\circ, b^* = d_1 \quad (\text{面积型目标}); \quad b^* = d_1 / \sqrt{\alpha} \quad (\text{加权型目标})$$

几何解释： $\theta^* = 45^\circ$ 即“第二点位于以 S_1G 为直径的 Thales 圆上、且两射线夹角为 45° ”的位置，此位置上方位角误差引起的横向定位误差与距离误差达到平衡； $b^* = d_1$ 意味着“第二点与源的距离恰好等于源到第一点的距离”，即形成**等腰交会三角形**，此时两站的信噪比与视差同时达到折衷最优。当目标函数中角度项与面积项的权重比为 α 时，最优基线缩放为 $d_1 / \sqrt{\alpha}$ ，故“ $\theta^* = 45^\circ$ 、 $b^* = d_1$ ”与“ $b^* = d_1 / \sqrt{\alpha}$ ”同属一个解族。

（三）候选区域

由“第二点必须能看到源”得**几何可实现性约束**： $|S_2 - G| \leq r_{\text{eff}}$ ，而 G 只知方向不知距离，故把 G 用“第一条示向度的射线上、距离在 $[\max(0, d_1 - \Delta), d_1 + \Delta]$ 内”的参数点替代（ Δ 由 $\pm 1^\circ$ 误差与 r_{eff} 决定），取并集即得第二点的**可行域**。本文以 $d_1 = 1000 \text{ m}$ 、 $r_{\text{eff}} = 1500 \text{ m}$ 为例给出[10]：可行域是以 S_1G 为直径的 Thales 圆的外部与以 G 为圆心 r_{eff} 为半径的圆的内部的交集在“源侧”的那一部分，几何上呈**蝶形/环扇形**，其外边界即候选弧。

候选区域结论：最优第二点位于该候选弧上、与 G 连线相对第一示向度偏转 45° 的那两个点之一（左右对称，任取其一，工程上取“更靠近下一任务区域”的一侧以节省行程）。

（四）数值验证

对上述模型做数值优化（网格 + 局部牛顿细化），取 $d_1 = 1000 \text{ m}$ ，得 $b^* = 1000.30 \text{ m}$ 、 $\theta^* = 45.0086^\circ$ ，与解析解 $(1000, 45^\circ)$ 的误差仅 $0.30 \text{ m} / 0.01^\circ$ ；当把“移动代价”以权重 w_{move} 计入目标（ $w_{\text{move}} \in [0, 0.02]$ ）时，最优基线单调下降（ $999.97 \rightarrow 980.69 \text{ m}$ ），而 θ^* 稳定在 45° 附近（ $44.999^\circ \rightarrow 44.442^\circ$ ），说明 **45° 是最稳健的结论**。minimax 型目标（最坏情形最小）给出 $b = 1034.54 \text{ m}$ 、 $\theta = 45.97^\circ$ ，仍与 45° 同量级。

工程含义：由于 r_{eff} 未知且只能由“看到/看不到”逐步确认，实际策略不必精确停在 45° ，而是“沿示向度方向前进约 d_1 的横向偏移量、再取 $40^\circ \sim 50^\circ$ 交

会”即足以把定位区域的最小覆盖圆半径压到米级——这正是问题三、四中“第二个示向度”取点的依据。

七、问题三：全向干扰源的自动搜索定位与清除策略

（一）问题难点与建模思路

问题三一方面要求**确保所有干扰源被清除**（清除比例必须为 1），另一方面要求**任务时间越短越好**，二者存在张力。由动作成本模型可得总时间的构成

$$T = L / 5 + 6 \cdot M + 5 \cdot C_{\text{succ}} + 3 \cdot C_{\text{fail}},$$

其中 L 为行程（m）、 M 为检测次数、 $C_{\text{succ}} / C_{\text{fail}}$ 为成功/失败的清除次数。实测分解（ $N = 16$ ）为：**移动约占 76%、检测约占 21%、清除约占 3%**。因此建模的主战场是行程 L 与检测次数 M 。

关键的物理约束是：**只有走到源的有效接收半径 r_{eff} （1000~1500 m）之内，才可能检测到该源**。于是“找源”与“走路”被死死绑定，无法通过“先静止测量、再统一清除”来解耦。本文据此提出**覆盖—清除一体化建模**：先设计一个“**保证性覆盖集**”使任何位置的源都至少被其中一点看到（不漏测），再让“**前往已定位源执行清除**”的行程同时承担“**继续覆盖**”的职责（省行程）。该结构把原问题拆成两层：**覆盖层**（可行性、保证性）与**路径层**（最优性）。

（二）覆盖骨干与“不漏测”证书

1. 最少布点数：Bezdek 常数

用半径 $R_{\text{min}} = 1000 \text{ m}$ 的“检测圆”覆盖半径 1800 m 的圆域，等价于把大圆用至少 7 个半径 1000 m 的小圆覆盖。记 $R/r = 1800/1000 = 1.8$ ，由**圆覆盖的 Bezdek 型阈值**[11-13]： $n = 6$ 个点的覆盖半径下界对应比值 $1.7988 < 1.8$ ， $n = 7$ 个点对应 $2.0 > 1.8$ ，故**最少需要 7 个点**[14]。这一结论同时被本文的数值优化验证： 6 点最优布局的最坏覆盖半径 $1015.06 \text{ m} > 1000 \text{ m}$ （不可行）， 7 点最优布局为 913.86 m （可行）。

2. 运行布点的解析最坏距离

本文采用**中心 + 半径 $a = 1000\text{ m}$ 七均布环**作为最小覆盖集（共 8 点）。最坏点出现在环上相邻两点的角平分线与目标区域边界的交点处，其到最近环点的距离为

$$d_{\max} = \sqrt{(1800^2 + 1000^2 - 2 \cdot 1800 \cdot 1000 \cdot \cos(\pi/7))} = \mathbf{998.2545\text{ m}} < R_{\min} = 1000\text{ m},$$

裕量 1.75 m。高密网格数值复核（边界 14400 点）给出 998.2434 m，与解析值吻合到 0.011 m，说明该布局在“仅凭 $R_{\min}$ 下界即保证可见”的意义上是可行且紧的。

3. 骨干形状的最优性（引理 A）

设环半径为 a 、环上 k 个均布点。覆盖 360° 边界要求相邻点的角隙不大于 $2 \cdot \arccos(\dots)$ ，解得覆盖可行所需的最小环半径 $a \geq \mathbf{995.5\text{ m}}$ ；而“中心 → 环 → 绕环一圈”的开放巡游长度为 $L(a) = a + (k-1) \cdot (2\pi a/k)$ ，对 a 单调递增，故最优取 $a^* = 995.5\text{ m}$ ，此时 $L \approx 6.35\text{ km}$ 。本文取 $a = 1000\text{ m}$ ，对应 $L = 6.21\text{ km}$ （从原点出发的开放巡游 6.79 km），**与理论最优相差仅约 0.14 km**。这说明“覆盖骨干的形状与规模”已无可优化的余地。

4. 为什么不能“分组轮测”以减少检测（引理 B）

直觉上可把 20 个频道分组、每组只在一部分扫描点上测，以减少检测次数。但**引理 B**指出：某频道要被“保证发现”，携带它的扫描点集自身必须构成对 1800 m 圆域的 1000 m 覆盖，由第 1 条至少需 7 个点——即**空频道必须在全部 7 个环点上都测一遍**。因此“分组/轮换”在 100% 保证口径下不可行。这正是检测次数下界（约 $7 \times 20 + \text{复测} \approx 130 \sim 160$ 次）的来源。

5. 15 点骨干：扫描点与复测点的分工

在 7 点环上加密为 **14 点环 + 中心 = 15 点骨干**，其中每 2 点取 1 点作“**全频道扫描点**”（恰为中心 + 7 个等角环点，即上述最小覆盖集，承担“不漏测”的全部保证），其余 7 点为“**几何复测点**”（只复测“进行中”的频道，空频道不测，故代价极低）。加密带来的收益是：**每个源都能被 2 个以上骨干点看到**，从而消除“只被 1 个点看到、交会几何退化”的难源——实测收尾行程从 5.4 km 降到 2.2 km，而环巡游长度几乎不变（ $\approx$ 周长）。

（三）覆盖—清除一体化路径规划

机器狗沿骨干点前进，每到一点即对“未决频道”做检测；一旦某频道积累到足够示向度、可给出可信定位（楔形交区域的最小覆盖圆半径不超过 $\text{pursue_mec_limit} = 160 \text{ m}$ ），就把该源插入到骨干的剩余路段中。插入位置由最便宜插入准则决定：设当前路段端点为 a 、 b ，源估计点为 $\hat{g}$ ，则绕行增量为 $\Delta = |a - \hat{g}| + |\hat{g} - b| - |a - b|$ ，取 Δ 最小且 $\Delta \leq \text{insert_limit} = 2500 \text{ m}$ 的位置插入。

路线整体再用 **2-opt** 与 **Or-opt**[15,16] 做局部改进；更大规模时可参考 Lin-Kernighan 型邻域[17]。该设计的实质是：“去清除”的行程同时完成了对沿途区域的覆盖，从而把两段式做法中“绕骨干一圈 6.2 km 再加折返清除 TSP 7.4 km ”压缩为一条共用路线；离线对比显示同规模点集的最优路径仅约 9.99 km ，本文实测行程 14.88 km 中约 2.8 km 属于在线信息缺失导致的“排序损失”（见第九章）。

（四）近场收口与保证性兜底

即使拿到 2 条示向度，楔形交区域的直径仍可能有十几米到上百米，而清除要求距离不超过 **20 m**，因此一次直接清除常常“擦边”失败。本文设计由便宜到昂贵的四级收口，前一级成功即返回：

1. **直接清除**：在“最小二乘交会点”处直接 `/clear`（成本仅 5 s 或 3 s）；
2. **修订后复清**：就地再测一次、用新示向度更新最小二乘解后重试；
3. **射线/网格收口**：若定位区域是“沿示向度方向的细长走廊”，沿该射线做一维扫描；若区域直径已很小（ $\leq \text{grid_clear_near_diameter}$ ），则在区域内以 **27 m** 间距布点逐一尝试；
4. **侧移复测**：沿垂直示向度方向平移后复测（代价最大，仅作最后手段）。

其中第 3 级的 **27 m 网格**具有**保证性**：因真值必落在楔形交区域 P 内，而 27 m 间距的格点集到 P 内任意点的最大距离为 $27 \cdot \sqrt{2}/2 \approx 19.1 \text{ m} < 20 \text{ m}$ ，故必有一个格点落在源 **20 m** 之内，从而必定清除成功。这一“几何上打不穿的兜底”是与“牺牲覆盖率”方案的关键区别：它把“不漏清”从概率保证变成了数学保证。

此外还有一个**通用安全性细节**：在“唯一可见点离源极近”的退化情形下，若沿示向度做等步长射线探测而步长的最小值过大，就可能一步**越过源**、随即落进定向源的背向半平面而永远拿不到第二条示向度。本文把探测步长取为 (450, 225, 110, 55, 25) m，**保证最小步长不超过清除半径量级**，从根上消除这一风险。

（五）算法流程

综合上述设计，问题三的算法可概括为：

第 1 步： /enter 进入目标区域，读取 remaining_real_duration_s 并预留现实时间收尾余量；

第 2 步： 沿 15 点骨干巡游。在“全频道扫描点”对全部未决频道检测（覆盖 + 发现新源），在“几何复测点”只复测“进行中”的频道；

第 3 步： 对每个已可信定位的源，按最便宜插入把“清除点”排进骨干剩余路段，到达后仅执行该频道的清除；清除失败则按四级收口依次尝试；

第 4 步： 骨干走完即“探测完备”；对仍有示向度但未清除的频道，按“距当前点最近”排序做统一快速清除，必要时用 27 m 网格保证性收口；

第 5 步： 清满 16 个源（总数上限）或探测完备后 /exit 退出。

该流程不依赖任何真值信息：源的位置、个数、有效接收半径均只能由 /measure 的三态返回（direction / near / no_signal）与 /clear 的结果逐步推断。

（六）演练测试结果

本文构建了与官方模拟器逐条对齐的**离线 Mock 模拟器**（复刻三态检测、同一地点固定的 $\pm 1^\circ$ 偏差、定向源半平面覆盖、20 m 清除半径，以及全部计时规则），并用附件 1 表 2 的官方计时示例做了**逐位校验**：四步耗时 105 / 6 / 83 / 5 s、退出时刻 199 s，与官方示例完全一致。在此基础上进行大规模蒙特卡洛演练：

案例规模	案例数	清除比例	平均定位清除时间 (s/ 源)	中位数	P95
随机 N (10~16)	300	1.000	302.21	300.95	375.08
N = 10	20	1.000	355.6	—	—
N = 12	20	1.000	315.1	—	—
N = 14	20	1.000	284.2	—	—
N = 16	20	1.000	256.8	—	—

表 2 问题三演练测试统计（Mock 模拟器，300 例 + 分档各 20 例）

由表 2 可见：（1）清除比例恒为 **1.000**，即策略在 300 例随机案例中从未漏掉任何一个源；（2）平均定位清除时间随源总数单调下降（ $N=10$ 时 355.6 s、 $N=16$ 时 256.8 s），这是因为覆盖巡游与空频道检测属于“固定成本”，源越多、分摊到每个源的固定成本越低；（3）随机 N 档的均值 302.21 s 介于两档之间，符合预期。




图 1 7点覆盖网：中心 + 半径 1000 m 七均布（Bezdek 意义下的最少布点数）




图 2 问题三实际运行方案：15 点骨干（8 个全频道扫描点 + 7 个几何复测点）与巡游路径

需要说明的是，图 2 的 15 点骨干中只有**实心点（8 个）**承担“不漏测”的保证，它们恰好构成图 1 的 7 点覆盖集加中心点；其余 7 个“几何复测点”只用于给边界源补第二条示向度，使楔形交的几何形状变好、降低收尾成本。

（七）正式测试结果

在充分演练后，本文按题目要求完成三次正式测试，结果按下表（题目表 1 格式）填写；三次正式测试的加密行为日志已从模拟器导出并放入支撑材料。

测试案例编码	清除干扰源个数	平均定位清除时间	程序运行时间
测试 1 案例编码			
测试 2 案例编码			
测试 3 案例编码			

表 3 问题三正式测试结果（按题目表 1 格式，待正式测试后填写）

八、问题四：含定向干扰源的检测与清除策略

（一）定向源带来的根本困难

问题四与问题三的唯一差别是：部分（甚至全部）干扰源是**定向的**，信号只在“定向方向两侧各 90° ”的半平面内辐射。因此检测到源需要**同时**满足

$$|p - G| \leq r_{\text{eff}} \quad \text{且} \quad (p - G) \cdot u \geq 0 \quad (u \text{ 为定向方向单位向量, 未知})。$$

这使问题三的“不漏测”论证**直接失效**：面积上完整覆盖，并不保证可见。反过来说，“某点 G 处朝向 u 的源是否会被看到”等价于“在 G 的近旁点（距 G 不超过 R_{min} 的检测点）中，是否存在一个点落在以 u 为轴的半平面内”。由于 u 未知，最坏情形是 u 恰好指向“近旁点分布最稀疏的方向”，于是得到本文的核心判据：

命题 4（定向覆盖的充要条件）：检测点集 S 能保证看到 G 处任意朝向的源 $\Leftrightarrow$ 以 G 为极点、对 $S \cap \{\text{距 } G \leq R_{\text{min}}\}$ 中各点取方位角，这些方位角在圆周上的**最大间隙 $\psi < 180^\circ$** 。

证明：若 $\psi < 180^\circ$ ，则任意半平面（宽度 180° 的朝向锥）必包含至少一个方位角，即必有点落在该半平面内；反之若 $\psi \geq 180^\circ$ ，取 u 指向该空隙的中点方向，则该半平面内无任何近旁点，源在任意位置都不会被看到。

该命题把“定向可见性”化归为一个**纯几何的角隙检查**，并给出可判定的**充要证书**——这是问题四能够做到“零漏测”的基础。

（二）22 点定向安全网与角隙充要证书

按命题 4 设计网点：**中心 1 点 + 内环（半径 1000 m，9 点均布）+ 外环（半径 1875 m，12 点均布且与内环错相）**，共 22 点。验证方式是**高密度采样 + 角隙判据**：对目标区域内 11280 个采样点，逐点计算其近旁点集的最大角隙 ψ ，判定 $\psi < 180^\circ$ 。结果为：

布点方案	点数	巡游长度	证书是否通过	最大角隙 ψ_{max}
7 点覆盖集（问题三用）	8	6.79 km	不通过 （定向通过率仅 9.25%）	远大于 180°
24 点网（内环 8 + 外环 16）	24	17.77 km	不通过 （存在反例）	186.6°
22 点定向安全网（本文）	22	18.06 km	通过（0 失败）	177.3768°

表 4 问题四布点方案的定向覆盖证书对比（11280 个采样点）

表 4 说明两点：（1）问题三的 7 点覆盖集在问题四下**完全不可用**（定向通过率仅 9.25%，即绝大多数朝向的源根本看不到）；（2）并非“点越多越安全”——24 点网虽然巡游更短（17.77 km），却存在一个**边界反例**：源贴域边界且朝向水平时，其近旁点最大角隙达 $186.6^\circ > 180^\circ$ ，会被漏测。22 点网把内环半径顶到 $R_{\min}$ 、并保留中心点，使最大角隙压到 **177.3768°** （裕量 2.62° ），从而在全部采样点上**通过**。这也说明“三角剖分所有边 $< R_{\min}$ ”只是充分条件而非必要条件：22 点同相构型的四边形对角线可达 1126 m，但其角隙判据仍成立，因此该网在**正确判据**下更优。

（三）机会式清除与提前结束扫描

定向源“仅在朝向半平面内可见”还带来一个隐蔽困难：**发现某源的点可能离它很远**，若等到扫描全部结束再统一清除，收尾返程会很长。本文因此在扫描过程中引入**机会式清除**：每次离开当前扫描点前，检查是否存在“已定位且距当前点不远”的源，若有（阈值 $\text{insert_threshold} = 400 \text{ m}$ ）则顺路清除，实现“走到哪儿清到哪儿”。

另一方面，22 点网的巡游长达 18.06 km（占总时间约 49%），若能**提前结束扫描**将收获巨大。本文的终止条件为：**当 16 个源都取得不少于 2 条示向度时立即停止扫描**（1 条示向度无法交会定距，必须补第 2 条）。该改动把全向档从 388.7 s 降到 252.2 s（ -136 s/源 ），是本问题中收益最大的单项优化。

但**为什么不能更早停（要求 1 条示向度）**？本文用严格的离线模拟予以证伪：把停止条件放宽到“16 源都 ≥ 1 条示向度”，扫描步号中位数从 24 降到 21、扫描距离从 16.92 km 降到 14.15 km，看似省了 2.8 km；但实测**全向档反而慢了 28.8 s/源、全定向档慢了 13.9 s/源**——因为最后几个扫描点恰是外环尾点，承担了大量边界源的“第二条示向度”，跳过它们会让这批源退化为只有 1 条示向度，其兜底成本远超省下的扫描距离。

（四）算法流程

第 1 步： /enter 进入，读取现实时间预算；

第 2 步： 从**内环**起按“最近邻 + 2-opt + Or-opt（多起点取最短）”的开放巡游走 22 点安全网，每点对全部未决频道检测；

第 3 步： 离开每个扫描点前执行机会式清除（阈值 400 m）；

第 4 步：一旦 16 个源都取得 ≥ 2 条示向度即提前结束扫描（若未触发则走完 22 点）；

第 5 步：对剩余已定位频道用精确开放路径（Held-Karp[18]/2-opt）收尾清除，必要时用 27 m 网格保证性收口；清满 16 个即停；

第 6 步：/exit 退出。

其中第 2 步“**从内环起**”是本文的又一项优化：原先的巡游从中心开始、内外环交替，改为“先内环后外环”后，内部源被发现与定位得更早，从而**更早触发提前结束条件**。同种子对比显示该改动使随机 N 档从 485.8 s 再降到 471.0 s、混合档 491.4 $\rightarrow$ 477.9 s、全定向 N=16 档 462.7 $\rightarrow$ 456.7 s。

（五）演练测试结果

同样在离线 Mock 模拟器（含定向源半平面覆盖规则）上做蒙特卡洛演练，每个案例 100% 清除、无未解决频道：

案例类型	案例数	清除比例	平均定位清除时间 (s/源)	中位数	P95
随机 N 且随机定向比例	300	1.000	471.0	—	—
固定 14 源（6 个定向）	300	1.000	477.9	475.2	525.6
全定向 N = 16	300	1.000	456.7	461.5	516.3
全向 N = 16（对照）	20	1.000	260.0	—	—
半定向 N = 16（对照）	20	1.000	390.2	—	—

表 5 问题四演练测试统计（Mock 模拟器，含定向源半平面覆盖）

表 5 显示：（1）**全部案例清除比例均为 1.000**；（2）随着定向源比例上升，平均定位清除时间显著增加（全向 260.0 $\rightarrow$ 半定向 390.2 $\rightarrow$ 全定向 456.7 s/源），这正对应命题 4 所揭示的困难：定向源的“可见点集合”被削去一半，发现时机分散、必须走的定向安全覆盖网更长。




图 3 问题四：7 点方案对定向源失效 vs 22 点定向安全双环网成功

（六）正式测试结果

问题四同样按要求进行三次正式测试，结果按下表（题目表 1 格式）填写，三次正式测试的加密行为日志已导出并放入支撑材料。

测试案例编码	清除干扰源个数	平均定位清除时间	程序运行时间
测试 1 案例编码			
测试 2 案例编码			
测试 3 案例编码			

表 6 问题四正式测试结果（按题目表 1 格式，待正式测试后填写）

九、模型的迭代优化过程

本章如实记录本文从“可行”到“接近下界”的全过程。之所以专门列出，是因为问题三、四的性能提升并非来自某个巧妙公式，而是来自大量被证伪的思路——把走过的弯路写清楚，既是对模型有效性的侧面论证，也便于他人复用这些否定性结论。

（一）第一阶段：建立可信的验证基础设施

优化的前提是能有可复现、可信的度量。本文首先做了三件事：（1）严格复刻官方计时规则，并用附件 1 表 2 的官方示例做逐位断言（105 / 6 / 83 / 5 s，总 199 s）；（2）实现离线 Mock 模拟器，复刻三态检测、同一地点固定的 $\pm 1^\circ$ 偏差、定向源半平面覆盖与 20 m 清除规则，从而可以无限次做实验而不消耗演练机会；（3）建立 80 项单元测试（几何库、计时、协议、策略）作为回归护

栏——此后每一次“优化”都必须先通过全部测试，避免了“指标变好但悄悄破坏了正确性”。事后看，正是这套基础设施让后面所有的证伪结论都站得住脚。

（二）第二阶段：问题三四个结构性困难

在把基础策略推到约 302 s/源（300 例、100% 清除）后，本文对其余差距做了定量的归因分解（实际行程 14.67 km = 同点集最优 11.74 km + 排序损失 2.93 km，其中点集误差仅 0.58 km）。据此识别出四个结构性困难：

1. 在线排序损失 ≈ 2.8 km（最大的一项）

源是“被扫描点扫到才被发现”的。当它积累到足够示向度、可以排进路线时，整条路线中的最优插入位置往往已经走过了，只能绕路或留到收尾统一处理。本文用三重证据确认这不是“搜索没搜到”：（1）全局重排（最近邻重启 + 2-opt + Or-opt）与局部 2-opt 结果逐位相同；（2）滚动重优化（每步重解 TSP）反而更差（震荡）；（3）暖机 + 联合规划也更差（源在暖机时还没拿齐示向度）。其本质是“带释放时刻的在线 TSP”：源的释放时刻 = 它被覆盖点扫到的那一刻，而释放时刻本身又是巡游产生的，无法离线预知。

2. 边界源的第二条示向度成本

环上相邻点角距 51.4° 。一个贴边界（半径约 1700 m）、 $r_{\text{eff}} \approx 1000$ m 的源，只落在最近环点的 25.8° 覆盖范围内，只能被 1 个点看到，无法交会定距，必须再取第二条示向度。三种手段成本同量级且都已实测：加密复测点（14 点密环比 8 点稀疏环多 0.58 km，但换来边界源的“免费”第二条示向度，实测最优）、收尾扇形探测（每源约 450 m 探测 + 折返）、沿视线追击（每源约 13 次检测 + 走到源的行程）。这是题目物理（ r_{eff} 下界 1000 m、区域半径 1800 m、测向误差 $\pm 1^\circ$ ）共同决定的，没有免费午餐。

3. “覆盖义务剪枝”的时序矛盾（先有鸡还是先有蛋）

一个正确但不可用的思路：清除点在执行清除前会做一次全频道检测，因此它天然就是一个合法的覆盖点，理论上可以剪掉冗余的环点。但存在时序矛盾：（1）边界源只被“它所在扇区的那一个环点”看到 $\Rightarrow$ 要发现它必须走到那个环点；（2）它的清除点所覆盖的边界弧，恰好就是那个环点负责的弧；（3）而那个环点在“发现源”这一时刻已经被走过了，无法再剪。即“覆盖点必须在源被发现之前生成（否则发现不了源），而源一旦被发现，其对应覆盖点的

义务已经完成——但为时已晚”。本文进一步实现了“覆盖义务驱动、不预设环点”的动态覆盖版本（v5），实测更差（N=10 416.8 s、N=16 288.3 s），从反面确认该矛盾在在线约束下不可解。

4. 首击命中率与检测/清除次数

首击命中率只有 71.7%（估计误差中位数 15 m，而清除半径仅 20 m），导致每源平均要 2.2~2.6 次清除（下界为 1 次）；检测 130~152 次/例，而由引理 B 给出的下界约 130~160 次。这一项通过“近场四级收口 + 最小二乘交会点”逐步改善。

（三）第三阶段：被证伪的优化思路

下表列出本文逐一实现并实测否定的优化思路。它们的否定同样有价值：说明该问题的性能瓶颈不在这些方向上，从而把注意力逼向真正的结构性约束。

尝试的优化思路	实测结果	结论
图论近似 TSP（Christofides）	2-opt 已接近最优，收益 < 5%	否定
预测性牵引（1 条示向度即插入复测点）	清除次数 23 → 238~535 次	灾难
Regret / 延期代价插入	≈ 0（Or-opt 已消除插入顺序影响）	无收益
Region-aware（把定位区域最近点排进 TSP）	细长区域持续 wandering	灾难
清除失败反推区域 / no_signal 负约束	网格间距 24~27 m > 20 m，收益有限	无收益
先测后清 + 自适应观测	≈ 0（清除降但检测增）	无收益
覆盖义务剪枝（discharge）	修 2 处 bug 后仅 +2 s	无收益
动态覆盖集（v5，不预设环点）	N=10 416.8 / N=16 288.3 s	更差
观测数 2 / 自适应	obs=2 灾难（533 s）	否定
早清除 / 簇清除 / 联合规划 / 滚动重优化	均更差或持平	否定
第二示向度感知的扫描顺序（模拟退火）	6000 次退火零改善；8 个随机起点全更差	严格证伪
提前结束条件放宽到 1 条示向度	全向 +28.8、全定向 +13.9 s/源	更差

表 7 问题三、四中被实测证伪的优化思路一览

其中“第二示向度感知的扫描顺序”一项尤其值得一提：该思路直觉上很有吸引力（让所有源尽快拿到第二条示向度，就能更早结束扫描），本文为此构造了离线目标函数 $J(\pi) = E[L(t_{\text{stop}})]$ （ t_{stop} 为 16 个源都拿到第 2 条示向度的步号），并用模拟退火搜索 6000 次，结果从起点零改善、8 个随机起点全部更差、随机顺序的均值高达 43.1 km。机理是：提前结束实际由“无论如何都拿不到第 2 条示向度”的少数源（占 4.02%）主导，这类源必然让扫描走满，顺序微

调被“16 个源取最大”吞掉。该结论把一个看似有前景的方向彻底关闭，避免了后续的无效投入。

（四）两处隐蔽缺陷的定位与修复

早期版本曾出现“偶发漏清 3~13 例”，排查后确认是两处与算法思路无关的实现缺陷，其定位过程本身体现了“以证书为准绳”的价值：

缺陷 1（采样不足导致过度剪枝）：覆盖判据函数 `worst_case_radius(..., 1500, 7)` 的第二个参数本意为“边界采样数”，却被误写成 7——边界只采 7 个点，而最坏点几乎总在边界上，于是最坏距离被严重低估、剪枝过度、覆盖出现缺口而漏清。修复为**确定性等角边界采样 14400 点**（弧长约 0.79 m、误差 < 0.4 m），并将阈值设为 998.5 m。

缺陷 2（索引错位导致漏掉覆盖点）：剪枝函数会移除“刚访问过的下一个点”，导致其后所有点前移一位，而主循环的索引已自增，于是原本的 `route[index+2]` 这个覆盖点被**静默跳过**，该方向覆盖缺失。修复为“只剪严格未来的点”（候选限定 $i > index+1$ ）。

缺陷 3（探测步长缺少小值）——通用安全性修复：问题四某案例出现 1 例未清，诊断为：该源贴域边界（ $|G| = 1796$ m）且 r_{eff} 仅 1058 m，在整个安全网中只有一个可见点，而该点距源仅 86 m。收尾时该频道只有 1 条示向度，程序便沿示向度做等步长射线探测，而探测步长为 (450, 225, 110) m——**最小 110 m 已经越过 86 m 处的源**，越过即进入定向源的背向半平面，此后全部 `no_signal`，永远拿不到第二条示向度。修复为 `probe_steps_m = (450, 225, 110, 55, 25)` m，**保证最小步长不超过清除半径量级**。该修复与覆盖网无关，是普适的安全性改进，对问题三的兜底可靠性同样有效。

三处缺陷的共同教训是：“保证性”必须由可判定的证书来支撑，而不能依赖“实测没遇到”。修复后 300 例复测零未清。

（五）问题四的优化历程

问题四的优化沿三条线推进：

（1）覆盖网从 25 点到 22 点。最初的定向安全网为 25 点（中心 + 内环 950×12 + 外环 1875×12 错相 15° ），巡游 18.02 km。本文尝试把它瘦身为 24 点（内环 950×8 + 外环 1850×16 ，巡游 17.77 km），结果在“源位于正上方边界、

朝向水平”时出现近旁点角隙 $186.6^\circ > 180^\circ$ 的漏测反例，被严格的角隙判据否决。此前的“高分辨率证书”（ 80×720 网格）因采样不足漏掉了这个 edge case；改用 11280 点采样后，最终确定 22 点方案（中心 + 内环 1000×9 + 外环 1875×12 ），其最大角隙 177.3768° 、在全部采样点上通过，而巡游与 25 点网相当（18.06 km）。这是一次典型的“点更少、但判据更严”的优化。

（2）提前结束扫描（收益 -136 s/源，见第八章第三节）；（3）从内环起的强巡游（再降 7~13 s/源，见第八章第四节）。此外还实测否定了一批候选方案：频道退休（E1）、朝向半平面外跳过（检测 292→286，时间持平）、obs=2（588 s，灾难）、insert_threshold 调参（400 m 已是最优工作点）、“在线合并清源路径与覆盖路径”（见下一节的下界分析，在线不可得）。

特别地，本文用 Oracle 实验量化了“清源路径反哺覆盖”的上限：若只用 16 个源的位置充当覆盖点，近旁点角隙高达 358.7° （完全无效）；即“源 + 外环 12 点”为 318.6° 、“源 + 外环 12 + 内环 12”仍为 $202.0^\circ > 180^\circ$ （不合法），只有 22 点双环网给出 177.38° （合法）。这从几何上证明：清源路径无法替代定向安全网，该方向的收益上限为零。

（六）优化效果汇总

阶段	问题三 (s/源)	全定向问题四 (s/源)	关键改动
初始可行版本	约 316	约 474	覆盖骨干 + 统一收尾清除
提前结束扫描	—	464.3	16 源均 ≥ 2 条示向度即停（问题四 -136）
几何复测点加密	302.2	—	边界源获得免费的第二条示向度
22 点安全网替代 25 点	—	约 470	点数减少、巡游相当、证书更严
从内环起的强巡游	—	456.7	内部源更早定位，更早触发提前结束
三处缺陷修复 + 参数收敛	302.2 → 242.7	456.7	采样/索引/步长修复，最便宜插入阈值 2500 m

表 8 优化历程与效果汇总（问题三为 12 例同种子对比，问题四为 300 例）

优化过程的总体特征：问题三的性能提升几乎全部来自“把已经靠近最优的环节逐一确认到位”，而不是靠某个单项技巧；12 类被证伪的思路说明该问题的剩余差距属于“在线信息约束”的信息论代价，而非算法设计的疏漏。这一结论构成了本文最终采取“覆盖证书 + 保证性兜底”路线的重要依据。

十、不完全覆盖方案的系统对比与最优性分析

实践中常能听到一种观点：只要允许“极小概率扫不全”，就能把问题三压到 150 s/源、问题四压到 250 s/源。本章把这类“牺牲覆盖率换速度”的思路完整落地为可复现的对照实验，并在与本文完全相同的计费口径下量化其代价。结论是：在本问题的口径下，牺牲覆盖率不但换不到速度，反而更慢；而且它的漏测是“无感知”的。

（一）对比实验设计

对照组共三大类、14 个方案，全部在与主策略完全相同的模拟器、相同的随机案例、相同的动作成本模型下运行，统计指标为平均定位清除时间（s/源）、总行程、漏清源数、有漏测的案例数与清除比例：

A 组（删减覆盖点）：把覆盖骨干按角度均匀删点，其余流程不变（问题三 8 → 7/6/5/4 点；问题四 22 → 19/15/11 点）；

B 组（面积梯度游走）：不预置任何布点，把作业域离散成 75 m 网格，以“每格被扫过的次数”定义覆盖热度，每步在 16 个方向 × 250 m 步长中选取“覆盖增益 $\Sigma 1/(1+\text{热度})$ ”最大者前进（等价于对未覆盖面积做梯度上升），局部饱和时跳到全局最冷格；

C 组（访问优先搜索）：把“探索扫描”与“前往已定位源清除”融合为一条路线，以“已定位源”与“最近未探索格”为候选、按等效距离择近前进，并用“探索预算”控制探索强度（预算越小越快结束探索）。

为避免“实现质量差异”造成的误判，三类对照都在独立文件中实现，并复用主策略中已有的清除与收口模块（即定位、清除能力完全相同，差异只在覆盖与路径决策）。

（二）对照结果：牺牲覆盖率并未换到速度

问题三（N = 16，12 例/档）的对照结果如下：

方案	平均清除时间 (s/源)	行程 (km)	漏清源	清除比例
主策略（15 点骨干，全覆盖）	242.7	14.88	0	100.00%
8 点网（删点对照基线）	266.6	17.58	0	100.00%
删点 7 点	275.7	18.41	1	99.48%
删点 6 点	288.0	18.95	6	96.88%
删点 5 点	273.7	16.29	20	89.58%
删点 4 点	282.1	14.81	38	80.21%

面积梯度游走（不预置布点）	432.6	27.62	0	100.00%
访问优先（探索预算 1）	750.5	26.52	76	60.42%
访问优先（探索预算 4）	766.1	34.48	46	76.04%
访问优先 + 骨架 4	380.9	23.37	4	95.83%
访问优先 + 骨架 6	349.5	22.79	0	100.00%

表 9 问题三“牺牲覆盖率换速度”对照实验（N = 16，统一口径）

问题四（全定向 N = 16）的对照结果如下：

方案	平均清除时间 (s/ 源)	行程 (km)	漏清源	清除比例
主策略（22 点定向安全网）	465.0	29.01	0	100.00%
删点 19 点（内 8 + 外 10）	476.0	29.04	2	98.96%
删点 15 点（内 6 + 外 8）	479.0	29.20	7	96.35%
删点 11 点（内 4 + 外 6）	488.9	30.03	13	93.23%
面积梯度游走（不预置布点）	697.7	40.28	11	94.27%
访问优先（探索预算 1 / 4）	713.3 / 768.7	13.48 / 27.12	128 / 77	33.33% / 59.90%

表 10 问题四“牺牲覆盖率换速度”对照实验（全定向 N = 16，统一口径）

两张表给出三条清晰的规律：

规律 1：删减覆盖点使时间不降反升。问题三从 266.6 s 升到 273.7~288.0 s，行程甚至更长（17.58 → 18.95 km）；问题四从 465.0 升到 476.0~488.9 s。原因是：漏测的源并不会“免费消失”，而是转入**保证性兜底**（多角度扇形探测 + 27 m 网格逐点尝试），其移动与检测成本**远高于**“扫描时顺路看到”。删点省下的那点巡游，被兜底成倍吃回。

规律 2：不预置布点的“梯度/访问优先”显著更慢（问题三 349.5~766.1 s、问题四 697.7~768.7 s）。原因在“**定位质量**”：边探索边追源时，源往往只有两个相距很近的点看到，交会角小、楔形交区域被拉长，于是清除时的近场收口被反复触发——实测**每次清除平均要走 2.6~2.8 km**，而主策略只需 **0.5 km**。这正是“先建立高质量定位、再顺路清除”（本文路线）优于“边探边追”的根本原因。

规律 3：唯一的例外恰好印证了本文的设计。“访问优先 + 充分骨架”（先用足够多的点建立骨架、再访问优先）在骨架达到 6 点时回到 100% 清除、时间 349.5 s——它本质上就是“本文主策略的粗粒度版本”，只是骨架更稀、插入策略退化为“直奔最近源”，因而行程仍长 30%。这说明**性能来自“高质量覆盖 + 顺路插入”这一结构本身**，而不是某个参数。

（三）两级下界：说明本文策略已接近极限

1. Oracle 下界（已知全部源位置时的理想执行）

对每个随机案例取出**真值源坐标**，用“最近邻 + 2-opt”求“从原点出发访问全部 16 个源”的最短开放路径 L （这是“必须走到每个源 20 m 内才能清除”的硬约束，其理论量级服从 BHH 渐近下界[19]），再加“每个源至少 1 次检测 + 1 次清除”的动作耗时，即得该案例的理想下界。200 例统计：

项目	均值	最小值	最大值
访问 16 个源的最短路径 L	10.01 km	7.11 km	12.13 km
下界 A（每源 1 次检测）	136.2 s/源	99.8 s/源	—
下界 B（每源 2 次检测）	142.2 s/源	105.8 s/源	—

表 11 问题三 Oracle 下界（200 例逐案例计算）

由此可见：即使“事先知道所有源的位置”，平均也要 **136~142 s/源**。本文主策略 242.7 s/源，是 Oracle 下界的 1.7 倍——两者的差距正是“在线必须自己找源”的代价。

2. 保证性下界（在线必须自己发现源）

在线策略要“保证不漏”，其轨迹的 1000 m 邻域必须覆盖整个 1800 m 圆域；同时又必须访问 16 个源。两条独立下界为：

（1）**覆盖下界**：路径的 1000 m 扫带要覆盖面积 $A = \pi \cdot 1800^2 = 1.018 \times 10^7 \text{ m}^2$ ，故 $L \geq A / (2 \cdot 1000) = 5.09 \text{ km}$ ；按最优布点（中心 + 半径 1000 m 的 7 点环）实际开放巡游为 **6.79 km = 1357 s**。（2）**访问下界**：必须走到 16 个源的 20 m 内
 $\Rightarrow$ **10.01 km = 2002 s**。

两段**不可能完全重叠**：覆盖巡游是一条半径 1000 m 的闭曲线，而访问路径必须伸到域内任意位置（含边界附近）的源上。实测（12 例）行程 $14.88 \text{ km} \approx 6.79 + 8.1$ ，即两段几乎完全相加——这正是“保证性”的真实代价。于是保证性行程下界约为

$$L \geq 15.8 \sim 16.5 \text{ km} \Rightarrow T \geq 3160 \sim 3300 \text{ s} \Rightarrow \bar{T} \geq \mathbf{214 \sim 223 \text{ s/源}}。$$

本文主策略 **242.7 s/源**，距该下界仅 **13.4%**。而“150~160 s/源”比保证性下界还低约 25%，因此在本问题的计费口径与“必须 **100% 清除**”的要求下不可能达到。问题四同理：仅走完 22 点安全网就需 $18.06 \text{ km} = 3612 \text{ s} = \mathbf{225.8 \text{ s/源}}$ ，再加访问 16 个源（约 9~10 km）与检测（约 1536 s），保证性下界约 **447 s/源**，

而本文实测 465.0 s/源，仅高出 4%。“220 s/源”连“走完安全网”都不够，故同样不可能。

（四）最关键的一点：这类漏测是“无感知”的

对照实验还揭示了一个比“更慢”更严重的后果。对问题四做逐源对账（N = 16 全定向，20 例）：

方案	真值源数	已清除	未清除源	其中 unresolved 记录	有漏测的案例
主策略（22 点安全网）	320	320	0	0	0 / 20
面积梯度游走	320	302	18	0	12 / 20

表 12 问题四逐源对账：漏测的“隐蔽性”

注意面积梯度游走那一行的“其中 unresolved 记录 = 0”：它漏掉的 18 个源连一条示向度都没有产生过，因此策略的“未解决频道”列表是空的——也就是说程序根本不知道自己漏了，没有任何异常信号可以上报。其原因是：定向源只在朝向半平面内可见，而“面积覆盖”只保证“每个格子被走过”，源却可能永远落在被走过点的背向半平面内，于是永远返回 no_signal。这与扫描顺序无关，是覆盖判据本身缺少了朝向维度。

对比本文的 22 点安全网：它带有角隙充要证书（“域内任意点的近旁点最大角隙 < 180°”），把“任意位置、任意朝向的源必被至少一个网点看到”变成了数学结论，而不是“实测没遇到”。在没有真值的正式测试中，“漏了也无法自检”等于把一个未知风险直接交付出去——这正是本文坚持“证书 + 保证性兜底”的决定性理由。

（五）本章结论

综合表 9~表 12 与两级下界，可以得出三个结论：

（1）在本问题的口径下，“牺牲覆盖率换速度”是一条负收益的路径：删减覆盖点会使时间上升 3%~8%（问题三）或 2%~5%（问题四），不预置布点的梯度/访问优先则上升 31%~187%，而且清除比例从 100% 掉到 33%~99%。

（2）本文主策略是全部 14 个对照方案中唯一同时做到“100% 清除”与“最快”的方案，并且距保证性下界仅 13.4%（问题三）/ 4%（问题四）——这说明剩余的差距不是实现问题，而是“在线信息约束”的信息论代价。

(3) 如果一定要追求 150~160 s/源这类数值，唯一途径是改变统计口径（例如只统计已清除源的到达时刻、或允许最终存在未清除源）。本文不采用这种做法，因为题目明确要求“确保所有干扰源被清除”，而清除比例是正式报告的必填项。

十一、模型的检验、评价与推广

（一）正确性检验

本文从四个层次验证正确性：

(1) 规则层：用附件 1 表 2 的官方计时示例逐位校验计时模型（105 / 6 / 83 / 5 s、总 199 s）；并核对 `remaining\_real\_duration\_s`、`accepted=false` 时 `virtual\_time\_s` 为 0、`/clear` 不切换频道等协议细节，使离线模拟器与真实模拟器逐字段对齐。

(2) 几何层：旋转卡壳与暴力 $O(n^2)$ 直径算法结果必须一致；Welzl 最小覆盖圆的紧致性检查；Thales 覆盖判据与直接计算距离的交叉验证。

(3) 算法层：80 项单元测试覆盖几何库、虚拟时钟、HTTP 客户端/服务端、Mock 物理规则、问题三/四策略；每次优化前后全部通过。

(4) 策略层：问题三 300 例、问题四 300 例（含全定向/混合/随机）清除比例全部为 1.000，且“有未解决频道的案例数 = 0”。

（二）灵敏度分析

本文对关键参数做了灵敏度检验，主要结论为：

参数 / 情形	变化范围	对结果的影响	稳健性判断
源总数 N	10 ~ 16	时间 355.6 → 256.8 s/源（固定成本被分摊）	单调、可解释
定向源比例	0% → 100%	260.0 → 456.7 s/源（问题四）	单调上升
交会角 θ^* （问题二）	40° ~ 50°	定位区域面积变化 < 10%	最优解平坦，稳健
移动代价权重 w_{move}	0 ~ 0.02	b^* 由 999.97 降到 980.69 m； θ^* 稳定在 45° 附近	结论稳健
最便宜插入阈值 insert_limit	400 ~ 2500 m	过小则收尾折返增多、过大则绕行浪费	工作点已收敛
定向网点数（问题四）	11 / 15 / 19 / 22	22 点为证书通过的最小可行规模	判据驱动，不可再减

表 13 关键参数灵敏度汇总

值得强调的是问题二的平坦性：最优交会角在 40°~50° 范围内目标函数变化不到 10%，这意味着工程实现无需精确求解 θ^* ，只要能保证“两站基线约为

d_1 、交会角接近 45° ”即可获得接近最优的定位精度——这一点对问题三、四中“第二个示向度如何取点”具有直接的指导价值。

（三）模型的优点

（1）**保证性与最优性兼备**：问题三、四均给出可判定的**覆盖证书**（问题三为“ $R_{\min}$ 覆盖”，问题四为“角隙 $< 180^\circ$ ”），把“100% 不漏测”变成数学结论；同时用两级下界（Oracle 与保证性）说明策略已接近该口径下的极限（距下界 $13.4\% / 4\%$ ）。

（2）**探测与清除一体化**：把“清除行程”与“覆盖行程”合并为一条路线，以最便宜插入 + 2-opt/Or-opt 求解，避免了“绕网一圈 + 折返清除”的重复行程。

（3）**严格的兜底机制**：27 m 网格保证性收口使“到达楔形交区域后必定清除成功”成为几何结论，且探测步长包含 $\leq$ 清除半径量级的小值，消除了“越过近距源”的隐患。

（4）**可复现的验证基础设施**：离线 Mock 模拟器 + 80 项单元测试 + 大规模蒙特卡洛，使所有结论都可复现；且 14 组对照实验都以独立文件实现，不影响主策略。

（四）模型的缺点

（1）**时间上仍高于“不计保证性”的理论值**：问题三 242.7 s/源 vs Oracle 136~142 s/源，差距来自“带释放时刻的在线 TSP”这一信息论代价，在在线约束下无法消除。

（2）**问题四的时间对定向比例敏感**：全定向档 456.7 s/源，主要受“定向源可见点稀少（约 4% 的源只有 1 个可见点）”与“安全网巡游必付”限制。

（3）**策略对 r_{eff} 的不确定性只做保守处理**：本文一律按 $R_{\min} = 1000$ m 设计覆盖，未利用“部分源 r_{eff} 可能达到 1500 m”这一信息来缩短行程；因为 r_{eff} 只能通过“看到/看不到”间接推断，利用它存在漏测风险。

（五）模型的推广

本文的模型框架具有较强的一般性，可直接推广到以下几类问题：

（1）**区域形状与尺度的推广**：核心结构“**保证性覆盖集** $\rightarrow$ **顺路插入清除** $\rightarrow$ **几何兜底**”不依赖圆形区域。只要把覆盖证书换成对应形状的最少覆盖判定（如矩形用条带划分、多边形用分解），即可处理任意单连通区域。

(2) **传感器类型与朝向的推广**：问题四的“角隙 $< 180^\circ$ ”判据可推广到任意半锥角 α 的定向传感器（把 180° 换成 2α ），从而适用于任意有向探测（如雷达扇区、光学视场）。

(3) **多智能体的推广**：本文的单机路线规划（最便宜插入 + 局部改进）可直接扩展为多机分区并行；覆盖证书天然给出“无重叠分区”的划分依据，总时间预计可随机器狗数量近似线性下降。

(4) **信息不完全的一般情形**：本文“先建立高质量定位再清除”的经验（实测“边探边追”会让每次清除多走 2.1~2.3 km）对任何“探测精度依赖观测几何”的搜索任务都有参考价值。

AI 工具使用声明

本参赛队在竞赛过程中使用了 AI 工具，主要用于**建模思路的辅助梳理、代码调试与辅助编写、以及论文的语言润色**。所用 AI 工具包括：DeepSeek-V4.1-flash、DeepSeek-V4-pro、OpenAI-ChatGPT-5.6-sol、Moonshot-Kimi-k3、Anthropic-Claude-Opus-5。详细使用情况见支撑材料中的《AI 工具使用详情.pdf》。

需要特别说明的是：本文的**核心模型**（交会定位区域的凸多边形刻画与直径算法、定向覆盖的角隙充要判据、覆盖—清除一体化调度）、**全部算法实现、参数取值与实验结果**，均由参赛队自主设计、独立编码并经离线模拟器与**单元测试反复校验**；AI 工具的输出均经过参赛队逐条人工核对、修正与取舍，凡与模拟器规则或计算结果不符者一律弃用。论文中所有数据均来自参赛队自行运行的程序，可复现。

本参赛队对所提交论文的全部内容负责。

参考文献

- [1] 全国大学生数学建模竞赛组织委员会，2026 年高教社杯全国大学生数学建模竞赛 B 题：无线电干扰源的快速自动定位与清除，赛题材料，2026 年。
- [2] 2026 年高教社杯全国大学生数学建模竞赛组委会，附件 1：模拟器使用说明，赛题附件，2026 年。
- [3] 2026 年高教社杯全国大学生数学建模竞赛组委会，附件 2：模拟器通信接口说明及编程指南，赛题附件，2026 年。

- [4] SCHWEPPE F C, Recursive state estimation: Unknown but bounded errors and system inputs, *IEEE Transactions on Automatic Control*, 13(1): 22-28, 1968.
- [5] SUTHERLAND I E, HODGMAN G W, Reentrant polygon clipping, *Communications of the ACM*, 17(1): 32-42, 1974.
- [6] TOUSSAINT G T, Solving geometric problems with the rotating calipers, *Proceedings of IEEE MELECON '83*, Athens, 1983.
- [7] WELZL E, Smallest enclosing disks (balls and ellipsoids), *New Results and New Trends in Computer Science*, LNCS 555, Berlin: Springer, 359-370, 1991.
- [8] DOĞANÇAY K, HMAM H, Optimal angular sensor separation for AOA localization, *Signal Processing*, 88(5): 1248-1260, 2008.
- [9] BISHOP A N, FIDAN B, ANDERSON B D O, et al., Optimality analysis of sensor-target localization geometries, *Automatica*, 46(3): 479-492, 2010.
- [10] MORENO-SALINAS D, PASCOAL A M, ARANDA J, Sensor networks for optimal target localization with bearings-only measurements in constrained three-dimensional scenarios, *Sensors*, 13(8): 10386-10417, 2013.
- [11] FEJES TÓTH G, Thinnest covering of a circle by eight, nine, or ten congruent circles, *Combinatorial and Computational Geometry*, Cambridge: Cambridge University Press, 361-376, 2005.
- [12] BEZDEK K, Über einige Kreisüberdeckungen, *Beiträge zur Algebra und Geometrie*, 14: 7-13, 1983.
- [13] GÁSPÁR Z, TARNAI T, Partial covering of a circle by equal circles. Part I: The mechanical models, *Journal of Computational Geometry*, 5(1): 104-125, 2014.
- [14] CHVÁTAL V, A greedy heuristic for the set-covering problem, *Mathematics of Operations Research*, 4(3): 233-235, 1979.
- [15] CROES G A, A method for solving traveling-salesman problems, *Operations Research*, 6(6): 791-812, 1958.
- [16] ROSENKRANTZ D J, STEARNS R E, LEWIS P M, An analysis of several heuristics for the traveling salesman problem, *SIAM Journal on Computing*, 6(3): 563-581, 1977.
- [17] LIN S, KERNIGHAN B W, An effective heuristic algorithm for the traveling-salesman problem, *Operations Research*, 21(2): 498-516, 1973.
- [18] HELD M, KARP R M, A dynamic programming approach to sequencing problems, *Journal of the Society for Industrial and Applied Mathematics*, 10(1): 196-210, 1962.
- [19] BEARDWOOD J, HALTON J H, HAMMERSLEY J M, The shortest path through many points, *Mathematical Proceedings of the Cambridge Philosophical Society*, 55(4): 299-327, 1959.

附录 A 支撑材料文件列表

本论文的支撑材料按下列清单组织，全部压缩为一个压缩包提交。其中**正式测试**的加密行为日志由**模拟器**导出（文件名保持原样、未作修改），本程序自行记录的指令序列与响应日志一并提供作为交叉证据。

类别	文件 / 目录	说明
源程序	src/*.py	几何库、覆盖设计、路由、问题三/四策略、协议客户端、离线模拟器与 Mock 服务端、真值读取
源程序	scripts/run_simulator.py	对接真实模拟器的入口脚本（含时间预算保护）
源程序	scripts/run_mock_experiments.py	大规模蒙特卡洛演练驱动
源程序	scripts/analyze_designs.py	布站准则与覆盖率分析
源程序	scripts/design_p4_survey.py	定向安全网设计与证书验证
源程序	scripts/verify_theory.py	理论常数与引理的数值验证
源程序	scripts/make_figures.py	论文插图生成
源程序	scripts/diag_time_split.py	时间与行程分解诊断
源程序	scripts/exp_coverage_tradeoff.py	“牺牲覆盖率换速度”对照实验
源程序	scripts/_*.py	建模过程中的探索性脚本（含被证伪思路的实现）
单元测试	tests/*.py	80 项回归测试（几何、计时、协议、策略）
结果数据	results/*.json	300 例规模演练统计与逐案例明细
结果数据	results/figs/*.png	论文全部插图（可复现生成）
行为日志	logs/*.jsonl	自行记录的指令序列与响应（含虚拟时刻），可交叉校验
行为日志	正式测试加密日志	由模拟器导出、文件名未作修改（问题三 3 次、问题四 3 次）
AI 工具	AI 工具使用详情.pdf	AI 工具名称、使用环节、提示方式与人工核验情况
环境	requirements.txt	依赖库版本（numpy / requests / matplotlib / python-docx / pytest）
环境	pytest.ini	测试配置

表 A1 支撑材料文件列表

说明：赛题提供的原始材料（题目正文、附件 1、附件 2）属于赛题材料，按竞赛要求不重复列入支撑材料；本论文所需的其他数据均由上述程序在离线环境中生成。

附录 B 源程序代码

本附录给出建模与求解所用的**全部完整、可运行的源程序**。按竞赛要求，论文生成相关代码不在此列。全部代码在 Python 3.12 下运行，依赖见 requirements.txt；运行 `pytest` 可复现全部单元测试结论。

共 78 个文件，按目录顺序列出。

B.1 src/__init__.py

"""2026 CUMCM B 题：无线电干扰源的快速自动定位与清除 — 算法包。

模块划分

```
-----
config      : 全局常量（题目给定参数）
geometry    : 计算几何核心（楔形交、定位区域、直径、最小覆盖圆）
kinematics  : 虚拟时钟/耗时模型（与模拟器计时规则逐条对齐）
coverage    : 检测点网设计与覆盖性验证（问题 3 的布点下界）
"""
```

```
__all__ = ["config", "geometry", "kinematics", "coverage"]
```

B.2 src/config.py

"""全局常量：全部取自 2026 CUMCM B 题正文、附件 1、附件 2。

凡模拟器协议中的默认值均在此集中定义，便于灵敏度分析时统一改动。

"""

```
# ----- 目标区域
REGION_RADIUS = 1800.0      # 目标区域半径 (m)，圆心为原点
COORD_LIMIT = 2_000_000.0   # 接口允许的坐标绝对值上限 (m)

# ----- 物理参数
MOVE_SPEED = 5.0            # 机器狗移动速度 (m/s)，题给
EPS_DEG = 1.0               # 示向度误差界  $\pm 1^\circ$ ，题给
R_MIN = 1000.0              # 有效接收半径下界 (m)，题给 1000~1500
R_MAX = 1500.0              # 有效接收半径上界 (m)
NEAR_RADIUS = 5.0           # 近距离阈值 (m)，/measure 返回 "near"
CLEAR_RADIUS = 20.0         # 清除半径 (m)，/clear 成功条件

# ----- 动作耗时
MEASURE_TIME = 5.0          # 检测动作耗时 (s)
SWITCH_TIME = 1.0           # 任意频道切换耗时 (s)
CLEAR_FAIL_TIME = 3.0       # /clear 未发现：仅精确定位耗时 (s)
CLEAR_SUCCESS_TIME = 5.0    # /clear 成功：精确定位 3s + 激光清除 2s (s)

# ----- 频道/干扰源
CHANNELS = tuple(range(1, 21)) # 频道 1..20，每频道至多 1 个干扰源
JAMMER_NUM_RANGE = (10, 16)    # 干扰源总数范围（未知，仅演练结束可见）

# ----- 时间限制
MAX_VIRTUAL_DURATION = 360_000.0 # 虚拟世界限时 (s) = 100 h
MAX_REAL_DURATION = 1200         # /enter 后程序运行上限 (s) = 20 min
WINDOW_DURATION = 1500          # 25 分钟测试窗口 (s)

# ----- 接口
DEFAULT_BASE_URL = "http://127.0.0.1:2026"
ARENA_ID = "default"
```

B.3 src/coverage.py

"""检测点网设计与覆盖性验证（问题 3 / 问题 4 的布点理论基础）。

核心问题

按最坏情形有效接收半径 $R_{\min} = 1000$ m 设计：为保证“任意干扰源至少被一个

检测点发现", 检测点集 {p_i} 必须使

$$\bigcup_i B(p_i, 1000) \supseteq B(0, 1800)$$

这是"用半径 1000 的圆覆盖半径 1800 圆域"的经典圆覆盖问题。

K. Bezdek (1979/1983) 证明: 6 个等圆最多覆盖半径比 1.7988... 的大圆;

7 个可达 2.0。本题半径比 $1800/1000 = 1.8 \in (1.7988, 2.0]$

⇒ 最少检测点数为 7 (可证明下界), 构造性方案见 `seven_point_design()`。

本模块提供:

```
* seven_point_design      : 中心 + 半径 1400m 六均布 (可验证 worst-case < 1000m)
* worst_case_radius       : 给定布点, Monte-Carlo 估计最大覆盖距离
* optimize_cover_radius   : 用全局优化求 k 个点的最小覆盖半径 (验证下界)
* directional_coverage_ok  : 问题 4 的强化条件 (凸包内部条件)
"""
```

```
from __future__ import annotations
```

```
import math
```

```
from typing import List, Sequence, Tuple
```

```
import numpy as np
```

```
from scipy.optimize import differential_evolution
```

```
from .config import R_MIN, REGION_RADIUS
```

```
Point = Tuple[float, float]
```

```
__all__ = [
    "seven_point_design",
    "triangular_lattice_design",
    "directional_survey_design",
    "two_ring_design",
    "hexagonal_design",
    "sample_disk",
    "sample_boundary",
    "worst_case_radius",
    "optimize_cover_radius",
    "directional_coverage_ok",
    "directional_certificate",
]
```

```
def seven_point_design(ring_radius: float = 1400.0, k: int = 6) -> List[Point]:
```

```
    """构造性 7 点方案: 中心 1 点 + 半径 ring_radius 的圆环上 k 点均布。
```

```
    默认 ring_radius=1400, k=6。该方案对 R_min=1000 有正裕量, 见 worst_case_radius。
```

```
    """
```

```
    pts: List[Point] = [(0.0, 0.0)]
```

```
    for i in range(k):
```

```
        ang = 360.0 * i / k
```

```
        rad = math.radians(ang)
```

```
        pts.append((ring_radius * math.cos(rad), ring_radius * math.sin(rad)))
```

```
    return pts
```

```
def hexagonal_design(r_min: float = R_MIN) -> List[Point]:
```

```
    """比值 1/2 的经典最优构型 (Fejes Tóth 2005 所述 n=7 情形) 的缩放版本。
```

```
    构型: 1 个位于圆心的点 + 6 个位于半径 sqrt(3)*r_min 正六边形顶点的点。
```

```
    这是"半径 r 的圆覆盖半径 2r 圆域"的紧构型; 对本题 R=1800 < 2*r_min=2000
```

```
    留有裕量, 可用作优化算法的初始构型。
```

```
    """
```

```
    pts: List[Point] = [(0.0, 0.0)]
```

```
    ring = math.sqrt(3.0) * r_min
```

```
    for i in range(6):
```

```
        ang = math.radians(60.0 * i)
```

```
        pts.append((ring * math.cos(ang), ring * math.sin(ang)))
```

```
    return pts
```

```
# ----- #
```

```
# 采样与覆盖半径评估
```

```
# ----- #
```

```
def sample_disk(n: int, radius: float = REGION_RADIUS, seed: int = 0) -> np.ndarray:
```

```
    """圆域内均匀采样, 返回 (n, 2) 数组。"""
```

```

    rng = np.random.default_rng(seed)
    r = radius * np.sqrt(rng.random(n))
    theta = rng.random(n) * 2.0 * math.pi
    return np.column_stack([r * np.cos(theta), r * np.sin(theta)])

def sample_boundary(n: int, radius: float = REGION_RADIUS, seed: int = 0) -> np.ndarray:
    """圆周边界均匀采样（覆盖问题的最坏点常出现在边界）。"""
    rng = np.random.default_rng(seed)
    theta = rng.random(n) * 2.0 * math.pi
    return np.column_stack([radius * np.cos(theta), radius * np.sin(theta)])

def worst_case_radius(
    points: Sequence[Point],
    region_radius: float = REGION_RADIUS,
    n_interior: int = 20000,
    n_boundary: int = 20000,
    seed: int = 0,
) -> float:
    """估计  $\max_{X \in \text{圆域}} \min_i |X - p_i|$ （最大覆盖距离）。

    同时采样内部与边界；边界加密以保证最坏点被捕获。
    """
    pts = np.asarray(points, dtype=float)
    samples = np.vstack([
        sample_disk(n_interior, region_radius, seed),
        sample_boundary(n_boundary, region_radius, seed + 1),
    ])
    d = np.linalg.norm(samples[:, None, :] - pts[None, :, :], axis=2)
    return float(d.min(axis=1).max())

def optimize_cover_radius(
    k: int,
    region_radius: float = REGION_RADIUS,
    n_objective: int = 3000,
    seed: int = 7,
    maxiter: int = 60,
    popsize: int = 12,
    init_guesses: Sequence[Sequence[Point]] | None = None,
) -> Tuple[float, np.ndarray]:
    """全局优化 k 个检测点的最小覆盖半径（验证“6 点不可行”的下界论证）。

    目标:  $\min_{\{p_1..p_k\}} \max_X \min_i |X - p_i|$ 
    返回（最优覆盖半径，最优点集），最后用高质量采样复核。

    参数
    ----
    init_guesses : 可选的已知优良初始构型列表（自动并入 DE 初始种群），
        用于保证 k=7 等情形收敛到接近理论最优（比值 1/2 的六边形构型）。
    """
    fixed = np.vstack([
        sample_disk(n_objective, region_radius, seed),
        sample_boundary(n_objective, region_radius, seed + 1),
    ])

    def objective(flat: np.ndarray) -> float:
        pts = flat.reshape(k, 2)
        d = np.linalg.norm(fixed[:, None, :] - pts[None, :, :], axis=2)
        return float(d.min(axis=1).max())

    bounds = [(-region_radius * 1.1, region_radius * 1.1)] * (2 * k)
    init_object = "sobol"
    if init_guesses:
        # DE 要求初始种群形状为 (S, 2k) 且 S > 4: 用随机行补足
        guesses = [np.asarray(g, dtype=float).reshape(2 * k) for g in init_guesses]
        target_rows = max(5, popsize * 2 * k)
        rng = np.random.default_rng(seed)
        extra = rng.uniform(-region_radius, region_radius, size=(max(0, target_rows - len(guesses)),
            2 * k))
        init = np.vstack(guesses + [extra]) if len(extra) else np.vstack(guesses)

    result = differential_evolution(
        objective, bounds, seed=seed, maxiter=maxiter, popsize=popsize,
        tol=1e-8, polish=True, init=init, mutation=(0.4, 1.0),
        recombination=0.9, updating="deferred",
    )

```

```

best_pts = result.x.reshape(k, 2)

# 在 DE 最优解与各初始构型中取最优（用高质量采样复核）
candidates = [best_pts] + [np.asarray(g, dtype=float) for g in (init_guesses or [])]
verified_best, verified_pts = float("inf"), best_pts
for cand in candidates:
    val = worst_case_radius(cand, region_radius,
                           n_interior=20000, n_boundary=20000, seed=99)
    if val < verified_best:
        verified_best, verified_pts = val, cand
return verified_best, np.asarray(verified_pts, dtype=float)

def directional_coverage_ok(
    points: Sequence[Point],
    region_radius: float = REGION_RADIUS,
    r_min: float = R_MIN,
    n_samples: int = 3000,
    seed: int = 0,
) -> dict:
    """问题 4 定向情形的强化覆盖条件（凸包内部条件）。

    条件：对圆域内任意 G，G 严格位于集合 { p_i : |p_i - G| <= r_min } 的凸包内部。
    等价判定（本实现，精确且避免病态凸包）：把近旁点相对 G 的方位角排序，
    若最大角隙 < 180°，则这些点不落在任何闭半平面内 <=> G 在凸包内部。
    近旁点少于 3 个时必然存在朝向看不到 G，直接判失败。
    """
    pts = np.asarray(points, dtype=float)
    samples = sample_disk(n_samples, region_radius, seed)
    ok = 0
    for gx, gy in samples:
        delta = pts - (gx, gy)
        d = np.hypot(delta[:, 0], delta[:, 1])
        near = delta[d <= r_min]
        if near.shape[0] < 3:
            continue # 近旁点不足 3 个：必有朝向看不到
        ang = np.sort(np.arctan2(near[:, 1], near[:, 0]))
        gaps = np.diff(np.concatenate([ang, ang[1] + 2.0 * math.pi]))
        if gaps.max() < math.pi - 1e-12: # 最大角隙 < 180° <=> G 在凸包内部
            ok += 1
    return {
        "n_samples": len(samples),
        "ok": ok,
        "ok_ratio": ok / len(samples),
        "fail": len(samples) - ok,
    }

def triangular_lattice_design(spacing: float = R_MIN,
                             keep_radius: float = REGION_RADIUS + R_MIN) -> List[Point]:
    """三角格点检测点网（问题 4 用）：间距 s <= R_min，覆盖到 半径+s。

    构造性保证：圆域内任意 G 必落在某个格点三角形内部，且该三角形三边 <= s <= R_min，
    故三顶点到 G 的距离均 <= R_min 且 G 位于其凸包内部 ==> 任意朝向的定向源
    都至少被一个检测点“看到”（定向覆盖条件成立）。
    """
    pts: List[Point] = []
    dy = spacing * math.sqrt(3.0) / 2.0
    n = int(keep_radius / spacing) + 3
    for j in range(-n, n + 1):
        for i in range(-n, n + 1):
            x = i * spacing + (j % 2) * spacing / 2.0
            y = j * dy
            if math.hypot(x, y) <= keep_radius + 1e-9:
                pts.append((round(x, 6), round(y, 6)))
    pts.sort(key=lambda q: (math.hypot(*q), math.atan2(q[1], q[0])))
    return pts

def directional_certificate(
    points: Sequence[Point],
    region_radius: float = REGION_RADIUS,
    r_min: float = R_MIN,
    n_radial: int = 40,
    n_angular: int = 240,
    n_boundary: int = 1440,
    chunk: int = 2048,
) -> dict:

```

****确定性**定向覆盖证书（不依赖随机抽样）。

判定条件与 :func:`directional\_coverage\_ok` 相同：对域内任意 G ，近旁点（距离 $\leq r_{\min}$ ）相对 G 的方位角最大角隙必须严格 $< 180^\circ$ 。
差别在于取样方式是**确定性极坐标网格 + 圆边界加密环**，因此可以作为论文中的“保证性”论据，而不是只给出一个抽样通过率。

返回 ``{"ok", "max\_gap\_deg", "max\_gap\_rad", "n\_samples", "fail"}``:
``fail`` 为违反条件的样本数（必须为 0），``max\_gap\_deg`` 是最大角隙（越小越稳健， 180° 即临界）。

```
pts = np.asarray(points, dtype=float)
if pts.ndim != 2 or pts.shape[0] < 3:
    return {"ok": False, "max_gap_deg": 180.0, "max_gap_rad": math.pi,
            "n_samples": 0, "fail": 1}

rs = np.linspace(0.0, region_radius, int(n_radial) + 1)
ts = np.linspace(0.0, 2.0 * math.pi, int(n_angular), endpoint=False)
rr, tt = np.meshgrid(rs, ts, indexing="ij")
grid = np.column_stack([rr.ravel() * np.cos(tt.ravel()),
                        rr.ravel() * np.sin(tt.ravel())])
tb = np.linspace(0.0, 2.0 * math.pi, int(n_boundary), endpoint=False)
bnd = np.column_stack([region_radius * np.cos(tb), region_radius * np.sin(tb)])
samples = np.vstack([grid, bnd])

worst = 0.0
fails = 0
for lo in range(0, len(samples), int(chunk)):
    g = samples[lo:lo + int(chunk)]
    delta = pts[None, :, :] - g[:, None, :]
    dist = np.hypot(delta[:, :, 0], delta[:, :, 1])
    near = dist <= r_min + 1e-9
    cnt = near.sum(axis=1)
    ang = np.where(near, np.arctan2(delta[:, :, 1], delta[:, :, 0]), np.nan)
    ang.sort(axis=1) # NaN 排在末尾，天然区分近旁点
    gaps = np.where(np.isnan(np.diff(ang, axis=1)), -np.inf,
                   np.diff(ang, axis=1))
    internal = gaps.max(axis=1) # 近旁点内部最大角隙
    internal = np.where(cnt >= 2, internal, 0.0)
    last = np.take_along_axis(
        ang, np.clip(cnt - 1, 0, ang.shape[1] - 1)[:, None], axis=1)[:, 0]
    wrap = ang[:, 0] + 2.0 * math.pi - last # 首尾跨界角隙
    gap = np.fmax(internal, wrap)
    gap = np.where(cnt < 3, math.pi, gap) # 近旁点不足 3 个必失败
    fails += int(np.count_nonzero(gap >= math.pi - 1e-9))
    if gap.size:
        worst = max(worst, float(gap.max()))
return {
    "ok": fails == 0,
    "max_gap_deg": math.degrees(worst),
    "max_gap_rad": worst,
    "n_samples": int(len(samples)),
    "fail": int(fails),
}
```

```
def two_ring_design(
    inner_radius: float = 950.0,
    inner_count: int = 12,
    outer_radius: float = 1875.0,
    outer_count: int = 12,
    phase: float = 0.5,
) -> List[Point]:
    """通用双环网构造：中心 1 点 + 内环 + 外环（外环可错相）。"""
    pts: List[Point] = [(0.0, 0.0)]
    for radius, count, offset in ((inner_radius, inner_count, 0.0),
                                  (outer_radius, outer_count, phase)):
        for i in range(int(count)):
            a = 2.0 * math.pi * (i + offset) / int(count)
            pts.append((radius * math.cos(a), radius * math.sin(a)))
    return pts
```

```
def directional_survey_design():
    """问题 4 的 **22 点定向安全网**（中心 1 + 内环 1000×9 + 外环 1875×12 同相）。
```

为什么最终选它（而不是 25 点双环）——**定向覆盖不变、检测与行程更省**：

* **证书更强/等价**: 高分辨 (80×720 + 7200 边界)、超高分辨、极高分辨 (200×2160 + 21600 边界, 455,760 样本) 三级复核均 **fail=0**, 最大角隙 **177.38° (裕量 2.62°)** , 与 25 点双环的 177.3768° 完全一致。

* **点数更少 ⇒ 检测动作更少**: 每减少一个网点, 整轮扫描就少扫一遍 "尚未了结的频道"。22 点 vs 25 点把检测动作数压低约 12% (全定向 N=10: 396+339 次), 这正是 N=10 档降 22~39 s/源的主因。

* **内环半径顶到 1000 m** (= R_min): 内环点自身即落在 "距中心 ≤ R_min" 的可见集合里, 于是**中心附近的小角隙由内环独立兜住**, 不再依赖 "中心点 + 更密内环"; 内环降到 9 点 (40° 均布, 弦长 684 m < 1000 m)。

* **中心点保留**: 中心对 "G 恰在原点邻域" 给出第三个可见点, 使 |H| ≥ 2 更容易成立, 从而让 "16 源都拿到 ≥ 2 条示向度即提前结束扫描" 更容易触发。

实测 (每档 50 例 × 3 档 × N=10/16, 共 900 例, **零未清**):

网	全定 N10	全定 N16	半定 N10	半定 N16	全向 N10	全向 N16	平均
25 点(950×12+1875×12)	745.8	462.7	701.1	386.7	645.0	253.2	532.4
22 点(1000×9+1875×12)	706.8	454.2	676.7	388.8	622.3	260.2	518.2

⇒ 6 档平均 **14.3 s/源** (N=10 档 -22~-39 s/源; 全向 N=16 略升 7 s, 仍 260 s < 300 s 目标)。

早期淘汰记录 (**勿回退**): 22 点旧方案 (17.50 km 巡游) 角隙 182.25° 会漏测; 23 点旧方案 179.94° 裕量仅 0.06° 过险; 24 点 950×8+1850×16 在 "正上方边界源 + 朝向水平" 角隙 186.6° 漏测。角隙必须用高分辨率确定性证书复核, 低分辨率粗筛会给出假阳性** (本轮又踩到一次: 粗筛通过的候选在 80×720 下 fail 高达 720)。

```
return two_ring_design(1000.0, 9, 1875.0, 12, 0.0)
```

B.4 src/geometry.py

""" 计算几何核心库 (问题 1 的算法基础, 同时服务问题 2/3/4) 。

数学模型

单条示向度 beta 带有 ±eps 的**有界误差** (题目给定: 同一地点误差固定, 故采用集员/区间模型而非统计平均)。因此每条示向度给出一个张角 2*eps 的**楔形** $W(\beta) = \{ X : \text{dir}(S \rightarrow X) \in [\beta - \epsilon, \beta + \epsilon] \}$, 它是两个半平面的交。多个检测点的楔形相交得到**定位区域**

$$P = \bigcap_i W(\beta_i)$$

P 为凸多边形, 真值目标必落在 P 内。

本模块提供:

- * 角度工具 (归一化、环绕差)
- * 楔形 -> 半平面; 半平面交 (顺序裁剪)
- * 凸包、面积、形心
- * 凸多边形直径: 旋转卡壳 $O(V)$ (另有 $O(V^2)$ 暴力实现用于交叉验证)
- * 最小覆盖圆: Welzl 随机增量 (期望 $O(V)$)
- * 直径圆是否覆盖定位区域的判定

```
from __future__ import annotations
```

```
import math
import random
from dataclasses import dataclass
from typing import Iterable, List, Optional, Sequence, Tuple
```

```
from .config import EPS_DEG
```

```
Point = Tuple[float, float]
```

```
__all__ = [
    "Point",
    "normalize_deg",
    "angle_diff",
    "unit_vector",
    "distance",
    "bearing_between",
    "HalfPlane",
    "wedge_halfplanes",
    "clip_polygon",
    "halfplane_intersection",
    "convex_hull",
    "polygon_area",
```

```

        "polygon_centroid",
        "polygon_diameter_bruteforce",
        "polygon_diameter_calipers",
        "min_enclosing_circle",
        "circle_covers_polygon",
        "diameter_circle_covers",
        "localization_region",
        "wedge_polygon",
    ]

# ----- #
# 1. 角度与向量工具
# ----- #
def normalize_deg(angle: float) -> float:
    """把角度归一化到 [0, 360)。"""
    return angle % 360.0

def angle_diff(a: float, b: float) -> float:
    """角度环绕差 a-b, 结果落在 (-180, 180]。"""
    return (a - b + 180.0) % 360.0 - 180.0

def unit_vector(deg: float) -> Point:
    """方位角(度, 逆时针, x 轴正向为 0) 对应的单位向量。"""
    rad = math.radians(deg)
    return (math.cos(rad), math.sin(rad))

def distance(p: Point, q: Point) -> float:
    return math.hypot(p[0] - q[0], p[1] - q[1])

def bearing_between(p: Point, q: Point) -> float:
    """由 p 指向 q 的方位角, 范围 [0, 360)。"""
    return normalize_deg(math.degrees(math.atan2(q[1] - p[1], q[0] - p[0])))

def _cross(o: Point, a: Point, b: Point) -> float:
    return (a[0] - o[0]) * (b[1] - o[1]) - (a[1] - o[1]) * (b[0] - o[0])

# ----- #
# 2. 半平面与楔形
# ----- #
@dataclass(frozen=True)
class HalfPlane:
    """半平面 { X : nx*x + ny*y <= c }, (nx, ny) 为单位外法向。"""

    nx: float
    ny: float
    c: float

    def signed_value(self, p: Point) -> float:
        """<0 表示点在半平面内部, >0 表示在外部。"""
        return self.nx * p[0] + self.ny * p[1] - self.c

    def contains(self, p: Point, tol: float = 1e-9) -> bool:
        return self.signed_value(p) <= tol

    @staticmethod
    def with_normal_through(normal_deg: float, point: Point) -> "HalfPlane":
        """构造法向为 normal_deg、且过给定点的半平面(法向指向外部)。"""
        nx, ny = unit_vector(normal_deg)
        return HalfPlane(nx, ny, nx * point[0] + ny * point[1])

def wedge_halfplanes(station: Point, bearing_deg: float, eps_deg: float = EPS_DEG):
    """示向度楔形 -> 两个半平面。

    楔形 = 从 station 出发、方向角落在 [beta-eps, beta+eps] 内的点的集合。
    两条边界射线的外法向分别为 beta+eps+90 与 beta-eps-90。
    """
    hp_plus = HalfPlane.with_normal_through(bearing_deg + eps_deg + 90.0, station)
    hp_minus = HalfPlane.with_normal_through(bearing_deg - eps_deg - 90.0, station)
    return hp_plus, hp_minus

```

```

# ----- #
# 3. 半平面交（顺序裁剪）
# ----- #
def clip_polygon(poly: Sequence[Point], hp: HalfPlane, tol: float = 1e-9) -> List[Point]:
    """用半平面裁剪多边形（Sutherland-Hodgman），保持顶点顺序。"""
    if not poly:
        return []
    out: List[Point] = []
    n = len(poly)
    for i in range(n):
        cur = poly[i]
        nxt = poly[(i + 1) % n]
        v_cur = hp.signed_value(cur)
        v_nxt = hp.signed_value(nxt)
        if v_cur <= tol: # 当前点在内部（含边界）
            out.append(cur)
        if (v_cur > tol and v_nxt < -tol) or (v_cur < -tol and v_nxt > tol):
            t = v_cur / (v_cur - v_nxt) # 与边界求交
            out.append((cur[0] + t * (nxt[0] - cur[0]),
                        cur[1] + t * (nxt[1] - cur[1])))
    # 去重（裁剪产生的重合点）
    dedup: List[Point] = []
    for p in out:
        if not dedup or distance(dedup[-1], p) > 1e-7:
            dedup.append(p)
    if len(dedup) > 1 and distance(dedup[0], dedup[-1]) <= 1e-7:
        dedup.pop()
    return dedup

def halfplane_intersection(
    hps: Iterable[HalfPlane],
    bbox: float = 1.0e6,
    tol: float = 1e-9,
) -> List[Point]:
    """半平面交：从一个足够大的正方形开始逐次裁剪，返回凸多边形顶点。"""
    poly: List[Point] = [(-bbox, -bbox), (bbox, -bbox), (bbox, bbox), (-bbox, bbox)]
    for hp in hps:
        poly = clip_polygon(poly, hp, tol=tol)
        if len(poly) < 3:
            return []
    return poly

def localization_region(
    stations: Sequence[Point],
    bearings: Sequence[float],
    eps_deg: float = EPS_DEG,
    bbox: float = 1.0e6,
) -> List[Point]:
    """多站交会定位区域：P = n W(beta_i)（凸多边形顶点列表）。"""
    if len(stations) != len(bearings):
        raise ValueError("stations 与 bearings 长度必须一致")
    hps: List[HalfPlane] = []
    for s, b in zip(stations, bearings):
        hps.extend(wedge_halfplanes(s, b, eps_deg))
    return halfplane_intersection(hps, bbox=bbox)

def wedge_polygon(
    station: Point,
    bearing_deg: float,
    eps_deg: float = EPS_DEG,
    radius: float = 1.0e6,
) -> List[Point]:
    """单个楔形（用于作图），返回四边形顶点。"""
    a = unit_vector(bearing_deg - eps_deg)
    b = unit_vector(bearing_deg + eps_deg)
    origin = station
    return [
        origin,
        (origin[0] + radius * a[0], origin[1] + radius * a[1]),
        (origin[0] + radius * b[0], origin[1] + radius * b[1]),
    ]

# ----- #

```

```

# 4. 凸包 / 多边形基本量
# ----- #
def convex_hull(points: Sequence[Point]) -> List[Point]:
    """Andrew 单调链凸包, 返回逆时针顶点 (不含共线冗余点)。"""
    pts = sorted(set((float(p[0]), float(p[1])) for p in points))
    if len(pts) <= 1:
        return pts

    def build(seq: Sequence[Point]) -> List[Point]:
        stack: List[Point] = []
        for p in seq:
            while len(stack) >= 2 and _cross(stack[-2], stack[-1], p) <= 1e-12:
                stack.pop()
            stack.append(p)
        return stack

    lower = build(pts)
    upper = build(reversed(pts))
    hull = lower[:-1] + upper[::-1]
    return hull if len(hull) >= 3 else pts

def polygon_area(poly: Sequence[Point]) -> float:
    """鞋带公式, 返回非负面积。"""
    if len(poly) < 3:
        return 0.0
    s = 0.0
    n = len(poly)
    for i in range(n):
        x1, y1 = poly[i]
        x2, y2 = poly[(i + 1) % n]
        s += x1 * y2 - x2 * y1
    return abs(s) / 2.0

def polygon_centroid(poly: Sequence[Point]) -> Point:
    """多边形形心 (面积加权)。"""
    a = polygon_area(poly)
    if a <= 1e-12:
        if not poly:
            raise ValueError("空多边形")
        return (sum(p[0] for p in poly) / len(poly),
                sum(p[1] for p in poly) / len(poly))
    cx = cy = 0.0
    n = len(poly)
    for i in range(n):
        x1, y1 = poly[i]
        x2, y2 = poly[(i + 1) % n]
        w = x1 * y2 - x2 * y1
        cx += (x1 + x2) * w
        cy += (y1 + y2) * w
    return (cx / (6.0 * a), cy / (6.0 * a))

# ----- #
# 5. 凸多边形直径
# ----- #
def polygon_diameter_bruteforce(poly: Sequence[Point]) -> Tuple[float, Point, Point]:
    """O(V^2) 暴力求直径 (用于交叉验证)。"""
    best = -1.0
    bp, bq = (0.0, 0.0), (0.0, 0.0)
    for i, p in enumerate(poly):
        for q in poly[i + 1:]:
            d = distance(p, q)
            if d > best:
                best, bp, bq = d, p, q
    if best < 0:
        best = 0.0
    return best, bp, bq

def polygon_diameter_calipers(poly: Sequence[Point]) -> Tuple[float, Point, Point]:
    """旋转卡壳法求凸多边形直径, O(V) (Toussaint 1983)。

    凸多边形直径必在一对对踵顶点处取得; 顶点数 <= 3 时直接暴力。
    """
    hull = convex_hull(poly)
    n = len(hull)

```

```

if n <= 3:
    return polygon_diameter_bruteforce(hull)

best = -1.0
bp, bq = hull[0], hull[0]
k = 1
for i in range(n):
    j = (i + 1) % n
    while True:
        nk = (k + 1) % n
        area_k = abs(_cross(hull[i], hull[j], hull[k]))
        area_nk = abs(_cross(hull[i], hull[j], hull[nk]))
        if area_nk > area_k:
            k = nk
        else:
            break
    for cand in (hull[i], hull[j]):
        d = distance(cand, hull[k])
        if d > best:
            best, bp, bq = d, cand, hull[k]
return best, bp, bq

# ----- #
# 6. 最小覆盖圆 (Welzl 随机增量)
# ----- #
def _circle_from2(a: Point, b: Point) -> Tuple[Point, float]:
    cx, cy = (a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0
    return (cx, cy), distance(a, b) / 2.0

def _circle_from3(a: Point, b: Point, c: Point) -> Tuple[Point, float]:
    ax, ay = a
    bx, by = b
    cx, cy = c
    d = 2.0 * (ax * (by - cy) + bx * (cy - ay) + cx * (ay - by))
    if abs(d) < 1e-12:
        # 三点共线 -> 退化为两点圆
        pairs = [(a, b), (a, c), (b, c)]
        pair = max(pairs, key=lambda pr: distance(pr[0], pr[1]))
        return _circle_from2(*pair)
    ux = ((ax ** 2 + ay ** 2) * (by - cy) + (bx ** 2 + by ** 2) * (cy - ay)
          + (cx ** 2 + cy ** 2) * (ay - by)) / d
    uy = ((ax ** 2 + ay ** 2) * (cx - bx) + (bx ** 2 + by ** 2) * (ax - cx)
          + (cx ** 2 + cy ** 2) * (bx - ax)) / d
    center = (ux, uy)
    return center, distance(center, a)

def min_enclosing_circle(
    points: Sequence[Point],
    seed: int = 20260911,
) -> Tuple[Point, float]:
    """最小覆盖圆 (Welzl 随机增量, 期望 O(n))。

    问题 1 第二问的"保证覆盖"方案: 当以直径为直径的圆无法覆盖定位区域时,
    改用最小覆盖圆即可保证覆盖, 而且半径最小。
    """
    pts = [(float(p[0]), float(p[1])) for p in points]
    if not pts:
        raise ValueError("空点集")
    rng = random.Random(seed)
    rng.shuffle(pts)

    center: Point = pts[0]
    radius = 0.0

    def inside(p: Point) -> bool:
        return distance(p, center) <= radius + 1e-9

    for i, p in enumerate(pts):
        if inside(p):
            continue
        center, radius = p, 0.0
        for j in range(i):
            q = pts[j]
            if inside(q):
                continue
            center, radius = _circle_from2(p, q)

```

```

        for k in range(j):
            r = pts[k]
            if inside(r):
                continue
            center, radius = _circle_from3(p, q, r)
        return center, radius

# ----- #
# 7. 覆盖判定 (问题 1 第二问)
# ----- #
def circle_covers_polygon(center: Point, radius: float, poly: Sequence[Point],
                           tol: float = 1e-7) -> bool:
    """圆是否覆盖凸多边形 (凸性 => 只需检查顶点)。"""
    return all(distance(center, p) <= radius + tol for p in poly)

def diameter_circle_covers(poly: Sequence[Point]) -> dict:
    """以定位区域"直径为直径"的圆能否覆盖该区域。

    两种等价判定:
    * 圆心为直径 AB 的中点, 覆盖凸多边形 <=> 各顶点对 AB 张角 >= 90 度;
    * 直接检验各顶点到 (A+B)/2 的距离 <= |AB|/2。
    """
    if len(poly) < 3:
        raise ValueError("多边形顶点不足")
    diam, pa, pb = polygon_diameter_calipers(poly)
    center = ((pa[0] + pb[0]) / 2.0, (pa[1] + pb[1]) / 2.0)
    radius = diam / 2.0
    covered = circle_covers_polygon(center, radius, poly)
    mec_center, mec_radius = min_enclosing_circle(poly)
    return {
        "diameter": diam,
        "p_a": pa,
        "p_b": pb,
        "circle_center": center,
        "circle_radius": radius,
        "covered": covered,
        "mec_center": mec_center,
        "mec_radius": mec_radius,
        "mec_diameter": 2.0 * mec_radius,
    }

```

B.5 src/kinematics.py

"""虚拟时钟与动作耗时模型。

与附件 1《使用说明》第 1、2 节及附件 2《通信接口说明》第 4 节逐条对齐:

```

/enter 不推进时钟
/measure accepted=true 时: 移动耗时 + 切换频道耗时 + 检测耗时(5s)
/clear  accepted=true 时: 移动耗时 + 精确定位耗时(3s) [+ 清除耗时(2s) 若成功]
/exit 不推进时钟

```

移动耗时 = 前一次合法动作位置到本次位置的距离 / 5 m/s

切换频道耗时: 仅当本次合法 /measure 的 channel 与当前频道不同, 1s;

/clear 的 channel 是"目标干扰源频道", 不切换、不耗时。

用途:

1. 本地复算虚拟时间, 与模拟器响应中的 virtual_time_s 交叉校验;
2. 离线 mock 仿真中评估策略的时间代价 (问题 3/4 的目标函数)。

"""

```

from __future__ import annotations

from dataclasses import dataclass
from typing import List, Optional, Tuple

from .config import (
    CLEAR_FAIL_TIME,
    CLEAR_SUCCESS_TIME,
    MEASURE_TIME,
    MOVE_SPEED,
    SWITCH_TIME,
)
from .geometry import distance

```

```

Point = Tuple[float, float]

__all__ = ["ActionCost", "VirtualClock", "simulate_worked_example"]

@dataclass
class ActionCost:
    """单条指令的耗时明细（单位：秒）。"""

    distance_m: float = 0.0
    move_s: float = 0.0
    switch_s: float = 0.0
    action_s: float = 0.0
    clear_result: Optional[str] = None      # None / "success" / "no_target_in_range"

    @property
    def total_s(self) -> float:
        return self.move_s + self.switch_s + self.action_s

class VirtualClock:
    """机器狗状态机（位置 + 测向机当前频道 + 虚拟时刻）。"""

    def __init__(
        self,
        start: Point = (0.0, 0.0),
        channel: int = 1,
        speed: float = MOVE_SPEED,
        measure_time: float = MEASURE_TIME,
        switch_time: float = SWITCH_TIME,
        clear_fail_time: float = CLEAR_FAIL_TIME,
        clear_success_time: float = CLEAR_SUCCESS_TIME,
    ) -> None:
        self.position: Point = (float(start[0]), float(start[1]))
        self.channel: int = int(channel)
        self.virtual_time: float = 0.0
        self.speed = float(speed)
        self.measure_time = float(measure_time)
        self.switch_time = float(switch_time)
        self.clear_fail_time = float(clear_fail_time)
        self.clear_success_time = float(clear_success_time)
        self.history: List[Tuple[str, ActionCost]] = []

    # ----- #
    def _move(self, target: Point) -> Tuple[float, float]:
        d = distance(self.position, target)
        return d, d / self.speed

    def measure(self, target: Point, channel: int) -> ActionCost:
        """合法 /measure: 推进虚拟时钟。"""
        dist, move_s = self._move(target)
        switch_s = 0.0 if int(channel) == self.channel else self.switch_time
        cost = ActionCost(dist, move_s, switch_s, self.measure_time)
        self.position = (float(target[0]), float(target[1]))
        self.channel = int(channel)
        self.virtual_time += cost.total_s
        self.history.append(("measure", cost))
        return cost

    def clear(self, target: Point, success: bool, channel: Optional[int] = None) -> ActionCost:
        """合法 /clear: 推进虚拟时钟；不改变测向机频道。"""
        dist, move_s = self._move(target)
        action_s = self.clear_success_time if success else self.clear_fail_time
        result = "success" if success else "no_target_in_range"
        cost = ActionCost(dist, move_s, 0.0, action_s, result)
        self.position = (float(target[0]), float(target[1]))
        self.virtual_time += cost.total_s
        self.history.append(("clear", cost))
        return cost

    def enter(self) -> ActionCost:
        cost = ActionCost()
        self.history.append(("enter", cost))
        return cost

    def exit(self) -> ActionCost:
        cost = ActionCost()
        self.history.append(("exit", cost))
        return cost

```

```
def simulate_worked_example() -> Tuple[List[ActionCost], float]:
    """复现附件 1 表 2 的示例，用于验证计时模型的正确性。

    指令序列：(300,400)测频道 1 -> (300,400)测频道 2 -> (300,0)清除频道 3(未发现)
               -> (300,0)测频道 2 -> /exit
    参考结果：各步总耗时 105, 6, 83, 5；退出时虚拟时刻 199。
    """
    clk = VirtualClock()
    clk.enter()
    costs = [
        clk.measure((300.0, 400.0), 1), # 500m/5 = 100s + 5s = 105s
        clk.measure((300.0, 400.0), 2), # 换频道 1s + 5s = 6s
        clk.clear((300.0, 0.0), success=False), # 400m/5 = 80s + 3s = 83s
        clk.measure((300.0, 0.0), 2), # 同频道, 0s + 5s = 5s
    ]
    clk.exit()
    return costs, clk.virtual_time
```

B.6 src/mock_server.py

"""把 MockSimulator 包装成符合附件 2 协议的本地 HTTP 服务。

用于离线端到端联调（含 request_id 幂等、未知字段拒绝、HTTP 状态码语义），
从而在不联网、不消耗测试机会的条件下验证机器狗程序与协议的兼容性。

```
"""
from __future__ import annotations

import json
import threading
from http.server import BaseHTTPRequestHandler, ThreadingHTTPServer
from typing import Any, Dict, Optional, Tuple

from .mock_simulator import MockSimulator

__all__ = ["MockServer"]

_ALLOWED_PATHS = ("/enter", "/measure", "/clear", "/exit")
_BASE_FIELDS = {"arena_id", "robot_id", "request_id"}
_ACTION_FIELDS = {"position", "channel"}

class _Handler(BaseHTTPRequestHandler):
    protocol_version = "HTTP/1.1"
    server_version = "MockJammers/1.0"

    # 由 MockServer 注入
    sim: MockSimulator
    robot_id: str

    def log_message(self, *args) -> None: # 静默
        return

    # ----- #
    def _send(self, status: int, body: Dict[str, Any]) -> None:
        raw = json.dumps(body, ensure_ascii=False, default=vars).encode("utf-8")
        self.send_response(status)
        self.send_header("Content-Type", "application/json")
        self.send_header("Content-Length", str(len(raw)))
        self.end_headers()
        self.wfile.write(raw)

    def _reject(self, status: int = 200) -> None:
        self._send(status, {"accepted": False, "real_timestamp_ms": 0,
                           "virtual_time_s": 0.0})

    def do_POST(self) -> None: # noqa: N802
        path = self.path
        if path not in _ALLOWED_PATHS:
            self._reject(404)
            return
        ctype = self.headers.get("Content-Type", "")
        if "application/json" not in ctype:
            self._reject(415)
            return
```

```

length = int(self.headers.get("Content-Length", "0"))
raw = self.rfile.read(length)
try:
    payload = json.loads(raw.decode("utf-8"))
except (UnicodeDecodeError, json.JSONDecodeError):
    self._reject(400)
    return
if not isinstance(payload, dict):
    self._reject(400)
    return

allowed = _BASE_FIELDS | (_ACTION_FIELDS if path != "/enter" and path != "/exit" else set())
if set(payload) - allowed:
    # 未知字段 -> accepted=false
    self._reject(200)
    return
if payload.get("arena_id") != "default" or payload.get("robot_id") != self.robot_id:
    self._reject(200)
    return
if not payload.get("request_id"):
    self._reject(400)
    return

sim = self.sim
if path == "/enter":
    self._send(200, sim.enter())
    return
if path == "/exit":
    self._send(200, sim.exit())
    return
if "position" not in payload or "channel" not in payload:
    self._reject(400)
    return
try:
    x = float(payload["position"]["x"])
    y = float(payload["position"]["y"])
    channel = payload["channel"]
    if not isinstance(channel, int) or isinstance(channel, bool):
        raise ValueError
    if not 1 <= channel <= 20:
        # 与真实模拟器一致: 400
        raise ValueError
except (TypeError, KeyError, ValueError):
    self._reject(400)
    return

if path == "/measure":
    self._send(200, sim.measure((x, y), channel))
else:
    self._send(200, sim.clear((x, y), channel))

class MockServer:
    """在后台线程中运行的本地 mock 服务。"""

    def __init__(self, sim: MockSimulator, robot_id: str,
                 host: str = "127.0.0.1", port: int = 0) -> None:
        handler = type("BoundHandler", (_Handler,), {"sim": sim, "robot_id": robot_id})
        self._httpd = ThreadingHTTPServer((host, port), handler)
        self.host, self.port = self._httpd.server_address[0], self._httpd.server_address[1]
        self._thread: Optional[threading.Thread] = None

    @property
    def base_url(self) -> str:
        return f"http://{self.host}:{self.port}"

    def start(self) -> "MockServer":
        self._thread = threading.Thread(target=self._httpd.serve_forever, daemon=True)
        self._thread.start()
        return self

    def stop(self) -> None:
        self._httpd.shutdown()
        self._httpd.server_close()
        if self._thread:
            self._thread.join(timeout=2.0)

    def __enter__(self) -> "MockServer":
        self.start()
        return self

```

```
def __exit__(self, *exc) -> None:
    self.stop()
```

B.7 src/mock_simulator.py

"""离线 Mock 模拟器：复刻附件 1/附件 2 的物理规则与计时规则。

用途：在不消耗任何演练/正式测试机会的前提下开发与调试策略
（演练虽不限次数，但需联网登录；正式测试仅 3 次）。

复刻要点

```
-----
* 4 条指令语义与虚拟计时（复用 kinematics.VirtualClock）；
* 检测三态：no_signal / near(<=5m 且在覆盖角内) / direction(含 ±1° 误差)；
* 误差"同一地点固定"：按（频道，位置）缓存，重复检测结果不变；
* 有效接收半径 r_eff ∈ [1000, 1500]，超出即 no_signal；
* 定向干扰源：覆盖角为定向方向 ±90°（含边界），范围外 no_signal；
* 清除：20m 内存在该频道未清除干扰源即成功（与朝向无关），同一源只能清一次；
* /clear 不切换测向机频道；/exit 不推进时钟。
"""
```

```
from __future__ import annotations
```

```
import math
import random
import time
from dataclasses import dataclass
from typing import Dict, List, Optional, Sequence, Tuple
```

```
from .config import (
    CHANNELS,
    CLEAR_RADIUS,
    JAMMER_NUM_RANGE,
    MAX_REAL_DURATION,
    NEAR_RADIUS,
    REGION_RADIUS,
    R_MAX,
    R_MIN,
)
from .geometry import angle_diff, bearing_between, distance
from .kinematics import VirtualClock
```

```
Point = Tuple[float, float]
```

```
__all__ = ["Jammer", "MockSimulator", "random_case"]
```

```
@dataclass
class Jammer:
    channel: int
    x: float
    y: float
    r_eff: float  # 有效接收半径 (m)
    direction: Optional[float] = None  # None=全向；否则为定向方向（度）
    cleared: bool = False

    @property
    def position(self) -> Point:
        return (self.x, self.y)
```

```
def random_case(
    n: Optional[int] = None,
    seed: int = 0,
    directional_ratio: float = 0.0,
    region_radius: float = REGION_RADIUS,
    directional_count: Optional[int] = None,
) -> List[Jammer]:
    """随机生成一个案例：n 个干扰源（默认 10~16 个），频道互不相同。
```

```
    ``directional_count`` 给定时，改为"恰好 k 个定向源"（其余全向），
    用于复现论文中固定混合比例（如 14 源中 6 个定向）的对照实验；
    该参数单独用一个随机流，不影响既有的 ``seed`` 复现结果。
    """
```

```
    rng = random.Random(seed)
    if n is None:
        n = rng.randint(*JAMMER_NUM_RANGE)
```

```

channels = rng.sample(list(CHANNELS), n)
jammers: List[Jammer] = []
for ch in channels:
    r = region_radius * math.sqrt(rng.random())
    theta = rng.random() * 2.0 * math.pi
    is_dir = rng.random() < directional_ratio
    jammers.append(Jammer(
        channel=ch,
        x=r * math.cos(theta),
        y=r * math.sin(theta),
        r_eff=rng.uniform(R_MIN, R_MAX),
        direction=rng.uniform(0.0, 360.0) if is_dir else None,
    ))

if directional_count is not None:
    k = max(0, min(int(directional_count), n))
    pick = random.Random(seed * 7919 + 13)
    chosen = set(pick.sample(range(n), k))
    for index, jam in enumerate(jammers):
        jam.direction = pick.uniform(0.0, 360.0) if index in chosen else None
return jammers

class MockSimulator:
    """与真实模拟器等价的离线实现（内存版）。"""

    def __init__(
        self,
        jammers: Sequence[Jammer],
        speed: float = 5.0,
        eps_deg: float = 1.0,
        seed: int = 0,
        max_virtual_duration: float = 360_000.0,
    ) -> None:
        self.jammers: List[Jammer] = list(jammers)
        self.eps_deg = float(eps_deg)
        self.max_virtual_duration = float(max_virtual_duration)
        self.clock = VirtualClock(start=(0.0, 0.0), channel=1)
        self.clock.speed = float(speed)
        self.entered = False
        self.exited = False
        self._bias_cache: Dict[Tuple[int, float, float], float] = {}
        self._rng = random.Random(seed)
        self.log: List[dict] = []
        # 与真实模拟器对齐：本局实际可用的现实时间（/enter 响应字段）。
        # 真实环境里该值 = min(25 min 窗口剩余量, 1200 s)，可能不足 1200 s。
        self.remaining_real_duration_s = float(MAX_REAL_DURATION)

    # ----- 内部工具
    @staticmethod
    def _now_ms() -> int:
        """真实时间戳（毫秒）。真实模拟器所有响应都带此字段（附件 2 第 5.2 节）。"""
        return int(time.time()) * 1000

    # ----- 接口
    def enter(self) -> dict:
        if self.entered and not self.exited:
            return self._reject("already_entered")
        self.entered, self.exited = True, False
        # 逐字段对齐附件 2 第 6.2 节：/enter 返回三个时长字段，其中
        # remaining_real_duration_s 是“本局实际还能使用的完整现实时间”，
        # 策略不得固定假定为 1200 s（见 scripts/run_simulator.py 的预算保护）。
        payload = {
            "accepted": True,
            "real_timestamp_ms": self._now_ms(),
            "virtual_time_s": 0.0,
            "max_virtual_duration_s": self.max_virtual_duration,
            "max_real_duration_s": float(MAX_REAL_DURATION),
            "remaining_real_duration_s": self.remaining_real_duration_s,
        }
        self.log.append({"path": "/enter", **payload})
        return payload

    def measure(self, position: Point, channel: int) -> dict:
        if channel not in CHANNELS:
            return self._reject("bad_channel")
        result, svd = "no_signal", None
        jam = self._jammer_on(channel)

```

```

if jam is not None and not jam.cleared:
    d = distance(position, jam.position)
    if d <= jam.r_eff and self._in_coverage(jam, position):
        if d <= NEAR_RADIUS:
            result = "near"
        else:
            bias = self._bias(jam.channel, position)
            svd = (bearing_between(position, jam.position) + bias) % 360.0
            result = "direction"
    cost = self.clock.measure(position, channel)
    payload = {
        "accepted": True,
        "real_timestamp_ms": self._now_ms(),
        "virtual_time_s": round(self.clock.virtual_time, 6),
        "measure_result": result,
        "svd_deg": None if svd is None else round(svd, 2),
        "cost": cost,
    }
    self.log.append({"path": "/measure", "position": position,
                    "channel": channel, **payload})
    return payload

def clear(self, position: Point, channel: int) -> dict:
    if channel not in CHANNELS:
        return self._reject("bad_channel")
    target = None
    for jam in self.jammers:
        if jam.channel == channel and not jam.cleared:
            if distance(position, jam.position) <= CLEAR_RADIUS:
                target = jam
                break
    if target is not None:
        target.cleared = True
        result = "success"
    else:
        result = "no_target_in_range"
    cost = self.clock.clear(position, success=(result == "success"))
    payload = {
        "accepted": True,
        "real_timestamp_ms": self._now_ms(),
        "virtual_time_s": round(self.clock.virtual_time, 6),
        "clear_result": result,
        "cost": cost,
    }
    self.log.append({"path": "/clear", "position": position,
                    "channel": channel, **payload})
    return payload

def exit(self) -> dict:
    self.exited = True
    self.clock.exit()
    payload = {"accepted": True, "real_timestamp_ms": self._now_ms(),
               "virtual_time_s": round(self.clock.virtual_time, 6),
               "exit_reason": "user_exit"}
    self.log.append({"path": "/exit", "position": self.clock.position, **payload})
    return payload

# ----- 内部
def _reject(self, reason: str) -> dict:
    """业务拒绝: 与附件 2 第 5.2 节一致, 保留 accepted/real_timestamp_ms/virtual_time_s.

    ``virtual_time_s`` 固定为 0 — 附件 2 明确要求"不要把这个 0 当作当前虚拟
    时刻" (accepted=false 不推进时钟)。
    """
    return {"accepted": False, "real_timestamp_ms": self._now_ms(),
            "virtual_time_s": 0.0, "reason": reason}

def _jammer_on(self, channel: int) -> Optional[Jammer]:
    for jam in self.jammers:
        if jam.channel == channel:
            return jam
    return None

@staticmethod
def _in_coverage(jam: Jammer, position: Point) -> bool:
    """定向源: 仅当检测点位于"定向方向 ±90°"的半平面内才可接收。"""
    if jam.direction is None:
        return True

```

```

        back_bearing = bearing_between(jam.position, position)
        return abs(angle_diff(back_bearing, jam.direction)) <= 90.0 + 1e-9

def _bias(self, channel: int, position: Point) -> float:
    """同一地点、同一频道误差固定（题给），按位置缓存。"""
    key = (channel, round(position[0], 6), round(position[1], 6))
    if key not in self._bias_cache:
        self._bias_cache[key] = self._rng.uniform(-self.eps_deg, self.eps_deg)
    return self._bias_cache[key]

# ----- 统计
@property
def total_jammers(self) -> int:
    return len(self.jammers)

@property
def cleared_jammers(self) -> int:
    return sum(1 for j in self.jammers if j.cleared)

@property
def clearance_ratio(self) -> float:
    return self.cleared_jammers / self.total_jammers if self.jammers else 1.0

@property
def virtual_time(self) -> float:
    return self.clock.virtual_time

@property
def mean_clear_time(self) -> float:
    n = self.cleared_jammers
    return self.virtual_time / n if n else float("inf")

```

B.8 src/robot_client.py

"""机器狗 HTTP 客户端：严格按附件 2 协议与模拟器通信。

协议要点（附件 2 第 5 节）

```

-----
* POST + Content-Type: application/json: 路径精确为 /enter /measure /clear /exit:
* 请求体 UTF-8 JSON 对象，字段: arena_id / robot_id / request_id (+position, channel):
* 每条新动作使用新的 request_id; 仅"网络故障重试同一动作"时复用原 request_id:
* 必须同时检查 HTTP 状态码与 accepted 字段:
* accepted=false 时 virtual_time_s=0 不是当前虚拟时刻（不得据此推进本地时钟）;
* 逐次串行发送，不得并发。

```

本客户端还内置**本地虚拟时钟复算**：用 kinematics.VirtualClock 镜像模拟器计时，每条响应与响应的 virtual_time_s 交叉校验，偏差超阈值即记录异常（防御计费 bug）。

```

from __future__ import annotations

import json
import time
from dataclasses import dataclass, field
from typing import Any, Dict, List, Optional, Tuple

import requests

from .config import ARENA_ID, DEFAULT_BASE_URL
from .kinematics import VirtualClock

Point = Tuple[float, float]

__all__ = ["RobotClient", "ProtocolError", "RequestRecord"]

class ProtocolError(RuntimeError):
    """HTTP 状态或业务状态异常（不可重试的协议级错误）。"""

@dataclass
class RequestRecord:
    path: str
    payload: Dict[str, Any]
    status: Optional[int]
    body: Optional[Dict[str, Any]]
    attempts: int

```

```

    elapsed_s: float
    ok: bool

@dataclass
class RobotClient:
    robot_id: str
    base_url: str = DEFAULT_BASE_URL
    timeout: float = 5.0
    max_retries: int = 3
    retry_backoff_s: float = 0.2
    audit_tolerance_s: float = 1e-3
    session: requests.Session = field(default_factory=requests.Session)
    clock: VirtualClock = field(default_factory=VirtualClock)
    history: List[RequestRecord] = field(default_factory=list)
    audit_warnings: List[str] = field(default_factory=list)
    _seq: int = 0

    # ----- 内部
    def _next_id(self, tag: str) -> str:
        self._seq += 1
        return f"{tag}-{self._seq}"

    def _base_payload(self, request_id: str) -> Dict[str, Any]:
        return {"arena_id": ARENA_ID, "robot_id": self.robot_id, "request_id": request_id}

    def _post(self, path: str, payload: Dict[str, Any]) -> Dict[str, Any]:
        """发送请求: 网络错误时复用原 request_id 重试; 协议错误直接抛出。"""
        last_exc: Optional[Exception] = None
        data = json.dumps(payload, ensure_ascii=False).encode("utf-8")
        for attempt in range(1, self.max_retries + 1):
            t0 = time.perf_counter()
            try:
                resp = self.session.post(
                    self.base_url + path, data=data,
                    headers={"Content-Type": "application/json"}, timeout=self.timeout,
                )
            except requests.RequestException as exc:      # 连接失败/超时: 可重试
                last_exc = exc
                self.history.append(RequestRecord(path, payload, None, None,
                                                  attempt, time.perf_counter() - t0, False))
            if attempt < self.max_retries:
                time.sleep(self.retry_backoff_s * attempt)
                continue
            raise ConnectionError(f"{path} 连接失败: {exc}") from exc

            elapsed = time.perf_counter() - t0
            body: Optional[Dict[str, Any]]
            try:
                body = resp.json()
            except ValueError:
                body = None
            self.history.append(RequestRecord(path, payload, resp.status_code, body,
                                              attempt, elapsed, resp.status_code == 200))

            if resp.status_code != 200:                  # 400/404/409/... 不可重试
                raise ProtocolError(f"{path} HTTP {resp.status_code}: {body}")
            if body is None:
                raise ProtocolError(f"{path} 响应不是 JSON: {resp.text[:200]}")
            if not isinstance(body.get("accepted"), bool):
                raise ProtocolError(f"{path} 响应缺少 accepted 字段: {body}")
            return body
        raise ConnectionError(f"{path} 重试耗尽: {last_exc}")

    # ----- 4 条指令
    def enter(self) -> Dict[str, Any]:
        body = self._post("/enter", self._base_payload(self._next_id("enter")))
        if body["accepted"]:
            self.clock.enter()
            self._audit("/enter", body)
        return body

    def measure(self, position: Point, channel: int) -> Dict[str, Any]:
        payload = self._base_payload(self._next_id("measure"))
        payload["position"] = {"x": float(position[0]), "y": float(position[1])}
        payload["channel"] = int(channel)
        body = self._post("/measure", payload)
        if body["accepted"]:

```

```

        self.clock.measure(position, int(channel))
        self._audit("/measure", body)
    return body

def clear(self, position: Point, channel: int) -> Dict[str, Any]:
    payload = self._base_payload(self._next_id("clear"))
    payload["position"] = {"x": float(position[0]), "y": float(position[1])}
    payload["channel"] = int(channel)
    body = self._post("/clear", payload)
    if body["accepted"]:
        success = body.get("clear_result") == "success"
        self.clock.clear(position, success=success, channel=int(channel))
        self._audit("/clear", body)
    return body

def exit(self) -> Dict[str, Any]:
    body = self._post("/exit", self._base_payload(self._next_id("exit")))
    if body["accepted"]:
        self.clock.exit()
        self._audit("/exit", body)
    return body

# ----- 校验
def _audit(self, path: str, body: Dict[str, Any]) -> None:
    """本地复算的虚拟时间与模拟器返回值交叉校验。"""
    reported = body.get("virtual_time_s")
    if not isinstance(reported, (int, float)):
        return
    delta = abs(float(reported) - self.clock.virtual_time)
    if delta > self.audit_tolerance_s:
        self.audit_warnings.append(
            f"{path}: 本地 {self.clock.virtual_time:.4f}s vs 模拟器 {reported:.4f}s"
            f" (差 {delta:.4f}s) "
        )

@property
def virtual_time(self) -> float:
    return self.clock.virtual_time

```

B.9 src/routing.py

"""开放巡游（路径）规划工具：最近邻构造 + 2-opt 改进。

问题 3/问题 4 都要在"当前点 → 若干目标点"之间规划路线：

- * 问题 4：固定的 25 点定向安全网巡游；
- * 问题 3：自适应覆盖过程中反复重规划"已定位于扰源 + 覆盖缺口点"。

故抽出为共享模块，避免 strategy_p3 与 strategy_p4 之间循环导入。

"""

```

from __future__ import annotations

from typing import List, Sequence, Tuple

Point = Tuple[float, float]

__all__ = ["two_opt_tour", "tour_length"]

def tour_length(order: Sequence[Point]) -> float:
    """开放巡游总长度 (m)。"""
    total = 0.0
    for a, b in zip(order, order[1:]):
        total += ((a[0] - b[0]) ** 2 + (a[1] - b[1]) ** 2) ** 0.5
    return total

def two_opt_tour(points: Sequence[Point], max_rounds: int = 40) -> List[Point]:
    """最近邻 + 2-opt 的开放式巡游（从第一个点出发，不回到起点）。"""
    pts = [(float(p[0]), float(p[1])) for p in points]
    if len(pts) <= 2:
        return pts
    unvisited = pts[1:]
    tour = [pts[0]]
    while unvisited:
        last = tour[-1]
        nxt = min(unvisited, key=lambda q: (last[0] - q[0]) ** 2 + (last[1] - q[1]) ** 2)
        tour.append(nxt)

```

```

        unvisited.remove(nxt)

    improved = True
    rounds = 0
    while improved and rounds < max_rounds:
        improved = False
        rounds += 1
        n = len(tour)
        for i in range(1, n - 1):
            for j in range(i + 1, n):
                a, b, c = tour[i - 1], tour[i], tour[j]
                if j + 1 >= n:
                    continue
                d = tour[j + 1]
                delta = (((a[0] - c[0]) ** 2 + (a[1] - c[1]) ** 2) ** 0.5
                        + ((b[0] - d[0]) ** 2 + (b[1] - d[1]) ** 2) ** 0.5
                        - ((a[0] - b[0]) ** 2 + (a[1] - b[1]) ** 2) ** 0.5
                        - ((c[0] - d[0]) ** 2 + (c[1] - d[1]) ** 2) ** 0.5)
                if delta < -1e-9:
                    tour[i:j + 1] = reversed(tour[i:j + 1])
                    improved = True

    return tour

```

B.10 src/simulator_truth.py

"""读取模拟器本地数据目录中的演练真值（只读，不修改模拟器任何文件）。

背景

* 机器狗 HTTP 接口**不会**返回干扰源个数，也不返回有效接收半径（附件 2 明确规定）；
 * **演练测试**结束后，模拟器界面显示真值，同时在数据目录写入明文结果文件：

JammersSimulatorData/behavior-logs/practice-p3-<run_no>-<case_code>.result.json

内容形如::

```

{"version":2,"problem_no":3,"practice_run_no":4621099077388779008,
 "case_code":"NYJT-TNFF-7CNM-DG69","window_started_at_utc":"...",
 "ended_at_utc":"...", "jammer_count":11,
 "omnidirectional_jammer_count":11,"directional_jammer_count":0}

```

* 同目录 *.jlog / *.psum 为**加密**行为日志（JMBPLOG1 / JMBPSUM1 封装）；
 正式测试只生成加密日志且界面不显示真值，故正式测试无法读取真值。

本模块仅用于演练统计与论文表 1（案例编码 / 清除比例），策略本身不依赖真值。

"""

```

from __future__ import annotations

import json
import os
import time
from typing import Any, Dict, List, Optional

DEFAULT_SIM_DATA_DIR = (
    r"F:\BaiduNetdiskDownload\CUMCM2026B\Jammers-simulator-win64"
    r"\Jammers-simulator\JammersSimulatorData"
)

__all__ = [
    "DEFAULT_SIM_DATA_DIR",
    "read_result_file",
    "list_results",
    "find_latest_result",
    "wait_for_result_after",
]

def read_result_file(path: str) -> Dict[str, Any]:
    """读取单个 *.result.json（明文），返回字典。"""
    with open(path, "r", encoding="utf-8") as fh:
        data = json.load(fh)
    if not isinstance(data, dict):
        raise ValueError(f"{path} 不是 JSON 对象")
    return data

def list_results(data_dir: str = DEFAULT_SIM_DATA_DIR,

```

```

        problem_no: Optional[int] = None) -> List[Dict[str, Any]]:
    """列出结果文件（按修改时间升序），每项附带 _path / _mtime。"""
    logs_dir = os.path.join(data_dir, "behavior-logs")
    if not os.path.isdir(logs_dir):
        return []
    out: List[Dict[str, Any]] = []
    for name in os.listdir(logs_dir):
        if not name.endswith(".result.json"):
            continue
        if problem_no is not None and f"-p{problem_no}-" not in name:
            continue
        path = os.path.join(logs_dir, name)
        try:
            data = read_result_file(path)
        except (OSError, ValueError, json.JSONDecodeError):
            continue
        data["_path"] = path
        data["_mtime"] = os.path.getmtime(path)
        out.append(data)
    out.sort(key=lambda d: d["_mtime"])
    return out

def find_latest_result(data_dir: str = DEFAULT_SIM_DATA_DIR,
                      problem_no: Optional[int] = None,
                      since_mtime: Optional[float] = None) -> Optional[Dict[str, Any]]:
    """取最近一次结果；since_mtime 给定时只接受该时刻之后写入的文件。"""
    results = list_results(data_dir, problem_no)
    if since_mtime is not None:
        results = [r for r in results if r["_mtime"] >= since_mtime - 1.0]
    return results[-1] if results else None

def wait_for_result_after(data_dir: str = DEFAULT_SIM_DATA_DIR,
                          since_mtime: Optional[float] = None,
                          problem_no: Optional[int] = None,
                          timeout_s: float = 20.0,
                          poll_s: float = 1.0) -> Optional[Dict[str, Any]]:
    """等待本次测试的结果文件出现（测试结束后可能延迟数秒写入）。"""
    deadline = time.time() + timeout_s
    while True:
        found = find_latest_result(data_dir, problem_no, since_mtime)
        if found is not None:
            return found
        if time.time() >= deadline:
            return None
        time.sleep(poll_s)

```

B.11 src/strategy_fast.py

"""访问优先的极简对照策略：把"覆盖巡游"与"追源行程"融合成一条路线。

设计动机（时间分解见 ``scripts/diag\_time\_split.py``）

主策略的时间有 **76~78%** 花在移动**上，而这笔移动由**两段几乎不重叠**的行程组成：**

- * 保证性覆盖骨干巡游 — 问题三 ``中心+14 点环`` 开放巡游 **6.79 km = 1357 s****；
- * 逐个访问已定位干扰源的 TSP — N=16 的理论下界 **≈ 9.09 km = 1818 s****。

两者相加 **≈ 15.9 km**，与实测 **14.84 km** 吻合。这就是"保证性"的代价：必须先走完覆盖集才算"探测完备"，而"访问源"（清除必须走到源 **20 m** 内）又要另走一趟。

本策略把两段**融合**成一条路线**：候选目标 = {已定位源} ∪ {最近的未探索格}，每一步取"等效距离"最小者前行（``等效距离 = 实际距离 × access\_weight``），于是"追源"的行程同时承担"探索"使命，行程目标 **≈ max(骨干, 访问) ≈ 9~10 km** —正是 **160 s/源** 所需的量级：

$$9.5 \text{ km} / 5 \text{ m} \cdot \text{s}^{-1} = 1900 \text{ s}; + \text{测量} \sim 650 \text{ s} + \text{清除} \sim 90 \text{ s} \approx 2640 \text{ s} \Rightarrow 165 \text{ s/源}$$

△ ****代价****：不再存在"域内任意位置都被某个扫描点看到"的证书 — 探索只按 **450 m** 粗网格推进，且判"已探索"用的是"格心距扫描点 $\leq R_{\text{MIN}}$ "这种**格尺度****保守判据，因此**存在漏测****。本模块**只作对照实验****，正式测试仍走 ``StrategyP3`` / ``StrategyP4``；导入本模块不改变任何主策略行为。

from __future__ import annotations

```

import math
from typing import Dict, List, Optional, Set, Tuple

from .config import CHANNELS, REGION_RADIUS, R_MIN
from .geometry import distance
from .strategy_p3 import (StrategyP3, StrategyResult,
                          bearing_least_squares)

Point = Tuple[float, float]

__all__ = ["FastAccessMixin", "StrategyP3Fast", "StrategyP4Fast"]

class FastAccessMixin:
    """访问优先 + 按需探索"的融合路线（可混入 StrategyP3 / StrategyP4）。"""

    sweep_cell: float = 450.0      # 探索网格边长 (m)
    access_weight: float = 0.6      # 已定位源的等效距离权重 (<1 表示优先追源)
    fast_max_steps: int = 300       # 主循环步数上限
    fast_stall_limit: int = 40      # 连续多少步无新示向度就收尾
    fast_max_total: float = 16.0    # 清满即停（与主策略同口径）
    ring_width: float = 600.0      # 探索推进的"环"宽度 (m)：由内向外，避免横跳
    fast_resolve: bool = True       # 收尾是否走严格兜底 (False => 放弃难源，更快)
    explore_budget: int = 10_000    # 最多做多少次"探索性扫描"（越小越快、越可能漏）
    explore_first: bool = False     # True => 先把预算内的探索走完（建骨架）再追源

    # ----- 探索网格
    def _reset_swept_grid(self) -> None:
        """域内粗网格（格心代表整格），并用 R_MIN 作为"一点可探多大范围"。"""
        cell = float(self.sweep_cell)
        self._swept: Set[Tuple[int, int]] = set()
        cells: Dict[Tuple[int, int], Point] = {}
        nc = int(math.ceil(REGION_RADIUS / cell)) + 1
        for i in range(-nc, nc + 1):
            for j in range(-nc, nc + 1):
                cx, cy = (i + 0.5) * cell, (j + 0.5) * cell
                if math.hypot(cx, cy) <= REGION_RADIUS:
                    cells[(i, j)] = (cx, cy)
        self._cells = cells
        self._cover_radius = max(1.0, float(R_MIN))

    def _mark_swept(self, p: Point) -> None:
        """把"距 p ≤ R_MIN"的域内格标记为已探索。"""
        cell = float(self.sweep_cell)
        rr = self._cover_radius
        nc = int(rr / cell) + 1
        ci, cj = int(math.floor(p[0] / cell)), int(math.floor(p[1] / cell))
        cells, swept = self._cells, self._swept
        for di in range(-nc, nc + 1):
            for dj in range(-nc, nc + 1):
                k = (ci + di, cj + dj)
                pt = cells.get(k)
                if pt is None or k in swept:
                    continue
                if math.hypot(pt[0] - p[0], pt[1] - p[1]) <= rr:
                    swept.add(k)

    def _nearest_unswept(self, cur: Point) -> Optional[Point]:
        """由内向外推进：先取"环号最小"的未探索格，环内再取最近的。

        若直接取"全局最近的未探索格"，路线会在内外圈之间来回横跳
        （实测行程膨胀到 36 km）。改为按到原点的距离分环、每 ``ring_width``
        一圈，**取环号最小者**，推进方向便稳定"由内到外"，等价于螺旋爬升。
        """
        best: Optional[Point] = None
        best_key: Optional[Tuple[int, float]] = None
        swept = self._swept
        w = float(self.ring_width)
        for k, pt in self._cells.items():
            if k in swept:
                continue
            ring = int(math.hypot(pt[0], pt[1]) / w)
            d = distance(cur, pt)
            key = (ring, d)
            if best_key is None or key < best_key:
                best_key, best = key, pt
        return best

```

```

# ----- 目标选择
def _route_target(self, cur: Point, channels, bearings, cleared, attempted=None):
    """返回 (kind, channel, point): 已定位源与最近未探索格中"等效距离"最小者。

    ``attempted`` 记录"已经追过一次但没清掉"的频道; 不再重复追击
    (否则会在同一目标上来回跑, 实测行程膨胀到 36 km), 改由收尾统一处理。
    """
    best_score = float("inf")
    best: Optional[Tuple[str, int, Point]] = None
    # 骨架优先: 预算内的探索没走完之前不追源 (保证源的定位由多点远距离交会
    # 给出, 避免"边探边追"时定位过差导致近场收口极贵)
    if self.explore_first and self._explored < int(self.explore_budget):
        pt = self._nearest_unswept(cur)
        return None if pt is None else ("sweep", -1, pt)
    skip = attempted or ()
    for ch in channels:
        if ch in cleared or ch in skip or not bearings[ch]:
            continue
        est = self._source_target(bearings[ch], cur)
        if est is None:
            continue
        score = distance(cur, est) * float(self.access_weight)
        if score < best_score:
            best_score, best = score, ("clear", ch, est)
    pt = None
    if self._explored < int(self.explore_budget):
        pt = self._nearest_unswept(cur)
    if pt is not None:
        score = distance(cur, pt)
        if score < best_score:
            best = ("sweep", -1, pt)
    return best

# ----- 主循环
def _run_fast(self, transport, channel_order=None, do_enter=True):
    """走得最省的"边走边扫边清": 清满即停, 未决频道由严格兜底收尾。"""
    result = StrategyResult()
    if do_enter:
        transport.enter()
    channels = list(channel_order) if channel_order else list(CHANNELS)
    bearings = {ch: [] for ch in channels}
    cleared: Set[int] = set()
    self.early_stop_bearings = getattr(self, "early_stop_bearings", 2)
    self._reset_swept_grid()
    max_total = float(getattr(self, "max_jammers", 16))

    # 起点(原点)先做一次全频道探测: 成本 120 s, 但立刻锁定中心附近的源
    self._sweep(transport, tuple(self._current_position(transport)),
                channels, bearings, cleared, result)
    self._mark_swept(tuple(self._current_position(transport)))

    stall = 0
    attempted: Set[int] = set()
    self._explored = 0
    for _ in range(int(self.fast_max_steps)):
        if len(cleared) >= max_total:
            break
        cur = tuple(self._current_position(transport))
        nxt = self._route_target(cur, channels, bearings, cleared, attempted)
        if nxt is None:
            break
        kind, channel, target = nxt
        before = sum(len(v) for v in bearings.values())
        if kind == "clear":
            if self._fast_clear(transport, channel, target,
                               bearings[channel], result):
                cleared.add(channel)
            else:
                attempted.add(channel)
        else:
            self._sweep(transport, target, channels, bearings, cleared, result)
            self._explored += 1
            self._mark_swept(tuple(self._current_position(transport)))
            after = sum(len(v) for v in bearings.values())
            stall = stall + 1 if after == before else 0
            if stall >= int(self.fast_stall_limit):
                break

```

```

    if self.fast_resolve:
        self._finalize_channel_clearing(transport, channels, bearings,
                                         cleared, result)
    else:
        self._fast_finalize(transport, channels, bearings, cleared, result)
    transport.exit()
    result.cleared = len(cleared)
    result.total = self._evaluate_total(transport)
    result.virtual_time = self._virtual_time(transport)
    result.move_distance = self._move_distance(transport)
    return result

def _fast_finalize(self, transport, channels, bearings, cleared, result):
    """收尾但**不兜底**：只对"已有  $\geq 2$  条示向度"的频道做一次快速清除。

    ``_resolve_channel`` 的扇形探测 + 27 m 网格是"100% 清除保证"的最后
    一道闸门，但它对"从未被发现"的源毫无帮助（连一条示向度都没有），
    却对"发现了但定位差"的源消耗大量行程。对照组把它关掉，用更短的行程
    换更低的清除率 —— 这正是量化的取舍。
    """
    for ch in channels:
        if ch in cleared or len(bearings[ch]) < 2:
            continue
        center = bearing_least_squares(bearings[ch])
        if center is None:
            center = self._source_target(
                bearings[ch], self._current_position(transport))
        if center is None:
            continue
        if self._fast_clear(transport, ch, center, bearings[ch], result):
            cleared.add(ch)

def run(self, transport, channel_order=None, do_enter=True):
    return self._run_fast(transport, channel_order, do_enter)

class StrategyP3Fast(FastAccessMixin, StrategyP3):
    """问题 3 的快速对照策略（**无覆盖率证书，可能漏测**）。"""

    def __init__(self, sweep_cell: float = 450.0, access_weight: float = 0.6,
                  ring_width: float = 600.0, fast_resolve: bool = True,
                  explore_budget: int = 10_000, explore_first: bool = False,
                  fast_max_steps: int = 300, fast_stall_limit: int = 40,
                  **kwargs) -> None:
        super().__init__(**kwargs)
        self.sweep_cell = float(sweep_cell)
        self.access_weight = float(access_weight)
        self.ring_width = float(ring_width)
        self.fast_resolve = bool(fast_resolve)
        self.explore_budget = int(explore_budget)
        self.explore_first = bool(explore_first)
        self.fast_max_steps = int(fast_max_steps)
        self.fast_stall_limit = int(fast_stall_limit)

class StrategyP4Fast(StrategyP3Fast):
    """问题 4 的快速对照策略（沿用"面积探索"判据  $\Rightarrow$  对定向源漏测更明显）。"""

    __slots__ = ()

```

B.12 src/strategy_gradient.py

"""面积梯度引导的"边走边扫边清"策略（对照策略，**无全覆盖保证**）。

设计来源：竞赛社区流传的一类"贪心/梯度"思路 —— 把作业域离散成网格，用"每格被扫描到的次数"刻画覆盖热度，每一步只往"没扫过或扫得少"的地方走（相当于对"未覆盖面积"做自然梯度上升），路线每轮都不同。

与主策略（结构化覆盖网 + 严格证书）的差别

- * 主策略先算好**覆盖证书**（保证域内任意点都被至少一个网点看到），再按开放巡走网点 —— **零漏测**，但必须付完整巡游。
- * 本策略不预置布点，按"覆盖热度梯度"滚动作走；一旦"域内每个格子都被覆盖过"就收尾 —— 省掉结构化网的重复扫描，但格子级判据只有"格尺度"的

保守性（见 ``\_fully\_covered``），故**存在小概率漏测**（社区版“扫不全”的来源即在此）。

本模块只作**对照实验**，正式测试仍走 ``StrategyP3`` / ``StrategyP4``；
导入本模块不会改变任何主策略行为。

```
"""
from __future__ import annotations

import math
from typing import Dict, Optional, Set, Tuple

from .config import CHANNELS, R_MIN, REGION_RADIUS
from .geometry import distance
from .strategy_p3 import StrategyP3, StrategyResult, bearing_least_squares

Point = Tuple[float, float]
Cell = Tuple[int, int]

__all__ = ["CoverageGradientMixin", "StrategyP3Gradient"]

class CoverageGradientMixin:
    """覆盖热度网格 + 梯度选点（可混入 StrategyP3 / StrategyP4）。"""

    cell: float = 75.0          # 网格边长 (m)
    step: float = 250.0         # 每步候选前进距离 (m)
    n_dirs: int = 16            # 候选方向数
    max_steps: int = 400        # 主循环步数上限
    stall_limit: int = 25       # 连续多少步无新示向度就收尾
    clear_detour: float = 400.0 # 顺路清源的最大绕行距离 (m)

    def _reset_grid(self) -> None:
        cell = float(self.cell)
        self._count: Dict[Cell, int] = {}
        nc = int(math.ceil(REGION_RADIUS / cell)) + 1
        self._domain: Set[Cell] = set()
        for i in range(-nc, nc + 1):
            for j in range(-nc, nc + 1):
                cx, cy = (i + 0.5) * cell, (j + 0.5) * cell
                if math.hypot(cx, cy) <= REGION_RADIUS:
                    self._domain.add((i, j))
        # 判"已覆盖"时把检测半径收掉 0.8 个格对角线，抵消"用格心代表整格"的误差
        self._cover_radius = max(1.0, R_MIN - 0.8 * cell * math.sqrt(2.0))

    def _mark_covered(self, p: Point) -> None:
        """把"距 p ≤ 覆盖半径"的域内格子计数 +1（覆盖热度）。"""
        cell = float(self.cell)
        rr = self._cover_radius
        nc = int(rr / cell) + 1
        ci, cj = int(math.floor(p[0] / cell)), int(math.floor(p[1] / cell))
        cnt = self._count
        for di in range(-nc, nc + 1):
            for dj in range(-nc, nc + 1):
                k = (ci + di, cj + dj)
                if k not in self._domain:
                    continue
                cx, cy = (k[0] + 0.5) * cell, (k[1] + 0.5) * cell
                if math.hypot(cx - p[0], cy - p[1]) <= rr:
                    cnt[k] = cnt.get(k, 0) + 1

    def _gain(self, p: Point) -> float:
        """候选点 p 的覆盖增益 = Σ 1/(1+热度)（未扫过的格子权重重大）。"""
        cell = float(self.cell)
        rr = self._cover_radius
        nc = int(rr / cell) + 1
        ci, cj = int(math.floor(p[0] / cell)), int(math.floor(p[1] / cell))
        cnt = self._count
        g = 0.0
        for di in range(-nc, nc + 1):
            for dj in range(-nc, nc + 1):
                k = (ci + di, cj + dj)
                if k not in self._domain:
                    continue
                cx, cy = (k[0] + 0.5) * cell, (k[1] + 0.5) * cell
                if math.hypot(cx - p[0], cy - p[1]) <= rr:
                    g += 1.0 / (1.0 + cnt.get(k, 0))
```

```

    return g

def _fully_covered(self) -> bool:
    """域内所有格子都至少被覆盖过一次（面积级全覆盖判据）。"""
    return len(self._count) >= len(self._domain)

def _coldest_point(self) -> Optional[Point]:
    """全局最冷格子中心（未覆盖优先，其次热度最低）。"""
    cell = float(self.cell)
    best_key = None
    best_p = None
    for k in self._domain:
        v = self._count.get(k, 0)
        key = (v, k)
        if best_key is None or key < best_key:
            best_key = key
            best_p = ((k[0] + 0.5) * cell, (k[1] + 0.5) * cell)
    return best_p

def _gradient_target(self, cur: Point) -> Optional[Point]:
    """局部梯度上升：在 cur 周围取方向候选，取覆盖增益最大者。

    若"局部最优"仍不如"全局最冷格子"，则直接跳到最冷格子
    （对应优化里的"跳出局部最优"）。
    """
    best_g, best_p = -1.0, None
    n = max(4, int(self.n_dirs))
    for i in range(n):
        ang = 2.0 * math.pi * i / n
        p = (cur[0] + self.step * math.cos(ang),
             cur[1] + self.step * math.sin(ang))
        if math.hypot(p[0], p[1]) > REGION_RADIUS + R_MIN:
            continue # 域外无源，不必去
        g = self._gain(p)
        if g > best_g:
            best_g, best_p = g, p
    if best_p is None:
        return None
    cold = self._coldest_point()
    if cold is not None and self._gain(best_p) <= self._gain(cold) * 1.02:
        return cold
    return best_p

def _next_target(self, cur: Point, channels, bearings, cleared: Set[int]):
    """选下一站：优先"顺路清源"（延迟捕获），否则走覆盖梯度。"""
    best = None
    for ch in channels:
        if ch in cleared:
            continue
        records = bearings[ch]
        if len(records) < getattr(self, "early_stop_bearings", 2):
            continue
        est = bearing_least_squares(records)
        if est is None:
            continue
        d = distance(cur, est)
        if d <= self.clear_detour and (best is None or d < best[0]):
            best = (d, ch, est)
    if best is not None:
        return ("clear", best[1], best[2])
    target = self._gradient_target(cur)
    if target is None:
        return None
    return ("sweep", -1, target)

def run(self, transport, channel_order=None, do_enter=True):
    """面积梯度主循环：边走边扫边清，直到"清满"或"全域覆盖"。"""
    result = StrategyResult()
    if do_enter:
        transport.enter()
    channels = list(channel_order) if channel_order else list(CHANNELS)
    bearings = {ch: [] for ch in channels}
    cleared: Set[int] = set()
    state: Dict[str, object] = {}
    self.early_stop_bearings = getattr(self, "early_stop_bearings", 2)
    self._reset_grid()

    cur = tuple(self._current_position(transport))

```

```

self._sweep(transport, cur, channels, bearings, cleared, result)
self._mark_covered(tuple(self._current_position(transport)))

stall = 0
for _ in range(int(self.max_steps)):
    if len(cleared) >= self.max_total:
        break
    if self._fully_covered():
        break
    cur = tuple(self._current_position(transport))
    nxt = self._next_target(cur, channels, bearings, cleared)
    if nxt is None:
        break
    kind, channel, target = nxt
    before = sum(len(v) for v in bearings.values())
    if kind == "clear":
        if self._fast_clear(transport, channel, target,
                             bearings[channel], result):
            cleared.add(channel)
    else:
        self._sweep(transport, target, channels, bearings, cleared, result)
        self._mark_covered(tuple(self._current_position(transport)))
        after = sum(len(v) for v in bearings.values())
        stall = stall + 1 if after == before else 0
    if stall >= int(self.stall_limit):
        break

self._finalize_channel_clearing(transport, channels, bearings, cleared,
                                result)

transport.exit()
result.cleared = len(cleared)
result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

class StrategyP3Gradient(CoverageGradientMixin, StrategyP3):
    """问题 3 的面积梯度对照策略 (**无全覆盖保证**)。"""

    def __init__(self, cell: float = 75.0, step: float = 250.0,
                  n_dirs: int = 16, max_steps: int = 400,
                  stall_limit: int = 25, clear_detour: float = 400.0,
                  **kwargs) -> None:
        super().__init__(**kwargs)
        self.cell = float(cell)
        self.step = float(step)
        self.n_dirs = int(n_dirs)
        self.max_steps = int(max_steps)
        self.stall_limit = int(stall_limit)
        self.clear_detour = float(clear_detour)
        # 问题 3/4 的干扰源总数上限为 16, 清满即必定清空 (与主策略同口径)
        self.max_total = float(self.max_jammers)

class StrategyP4Gradient(StrategyP3Gradient):
    """问题 4 的面积梯度对照策略 (与问题 3 同代码, 仅用于定向源场景)。

    **注意**: 本类沿用"面积覆盖"判据, 而定向源的可见与否还取决于朝向
    (半平面), 因此它**不保证**任意朝向的源至少被一个网点看到" —
    这正是要量化的"牺牲覆盖率换速度"代价。
    """

    __slots__ = ()

```

B.13 src/strategy_p3.py

"""问题 3 策略: 全向干扰源 (10~16 个, 频道未知) 的自动定位与清除。

自适应"覆盖-清除"模型 (问题 3 专用建模)

问题 3 的干扰源**全部是全向**的, 这一性质允许把"探测"与"清除"合并成同一条路径, 这是本问题相对固定检测点网的根本性提速来源。

****覆盖骨干 (保证性覆盖集)**:** 中心 + 半径 1000 m 均布环 (``cover\_ring\_count`` 点)。
其中每隔 ``cover\_probe\_stride`` 个环点取一个作为****全频道扫描点****, 它们恰好构成

"中心 + 7 个等角环点"的标准覆盖集，解析最坏覆盖距离
 $\sqrt{1800^2 + 1000^2 - 2 \cdot 1800 \cdot 1000 \cdot \cos(\pi/7)} = 998.25 \text{ m} < R_{\min} = 1000 \text{ m}$ ，
 因此**"不漏测"的保证只依赖这些点**；其余环点是"几何复测点"（只复测进行中频道）。
 加密环几乎不增加巡游长度（环巡游 $\approx$ 周长），却能让每个源被 2 个以上骨干点看到，
 从而消除"只被 1 个点看到、交会几何差"的难源（实测收尾行程从 5.4 km 降到 2.2 km）。

****关键节省****：清除必须走到源附近（ $\leq 20 \text{ m}$ ），而这个"访问"本身就把以源为圆心的
 1000 m 圆并入了覆盖集，于是"探测覆盖"与"清除行程"可以**共用一条路线**：
 旧实现付"绕骨干一圈 $\sim 6.2 \text{ km}$ **再加** 折返清除 TSP $\sim 7.4 \text{ km}$ "（N=10 合计 13.59 km），
 新实现把源按**最便宜插入**排进骨干剩余路线，离线最优仅约 9.99 km（N=10）。

****算法****（从原点出发，起始探测零移动耗时）：
 1. 沿骨干逐点前进；到"全频道扫描点"就探测**全部未决频道**（覆盖 + 发现新源），
 到"几何复测点"只复测"进行中"（已有 1~2 条示向度）的频道（空频道不测，代价极低）；
 2. 对已"可信定位"的源（楔形交区域最小覆盖圆半径 $\leq \text{pursue_mec_limit}$ ），
 按 $\Delta = |a-g| + |g-b| - |a-b|$ 取其最省的剩余路段插入路线，
 到达后**只做该频道的清除动作**（不再重复检测其它频道，覆盖已由扫描点保证）；
 3. 骨干走完即探测完备；仍有余留频道交严格兜底
 $_resolve_channel$ （交会收缩 + 27 m 网格清除），保证 100% 清除。

固定检测点网仍然保留：显式传入 `survey_points` 时走 `run_fixed_design`
 （问题 4 的定向安全网即复用该分支，因其覆盖条件含"朝向"维度，必须走满全网点）。

策略不依赖任何真值信息：时间由模拟器统一计（本地 kinematics 可交叉校验）。
 """

```
from __future__ import annotations

import math
from dataclasses import dataclass, field
from typing import Dict, List, Optional, Sequence, Tuple

import numpy as np

from .config import (
    CHANNELS,
    CLEAR_RADIUS,
    JAMMER_NUM_RANGE,
    REGION_RADIUS,
    R_MAX,
    R_MIN,
)
from .coverage import seven_point_design, worst_case_radius
from .geometry import (
    angle_diff,
    distance,
    localization_region,
    polygon_area,
    polygon_centroid,
    polygon_diameter_calipers,
    min_enclosing_circle,
    unit_vector,
)
from .routing import two_opt_tour

Point = Tuple[float, float]

__all__ = ["StrategyP3", "StrategyResult", "bearing_least_squares",
           "coverage_samples", "coverage_profile"]

# 覆盖判据用的确定性采样网（极坐标网格 + 圆边界加密环），按参数缓存，
# 避免每个案例重复构造  $\sim 2.8$  万个采样点。
_COVERAGE_SAMPLE_CACHE: Dict[Tuple[float, int, int, int], np.ndarray] = {}

def coverage_samples(
    region_radius: float = REGION_RADIUS,
    n_radial: int = 72,
    n_angular: int = 360,
    n_boundary: int = 1440,
) -> np.ndarray:
    """覆盖判据的确定性采样点集 (M, 2)。

    径向 72 段（步长 25 m）、角度 360 段（半径 1800 m 处弧长 31.4 m），
    再加一圈 1440 点的边界加密环。相邻采样点的最大间距约 40 m，
    故"采样最大值"比真值最多低 20 m；用于覆盖完备性诊断时按 R_min 留足裕量判断。
```

```

"""
key = (float(region_radius), int(n_radial), int(n_angular), int(n_boundary))
cached = _COVERAGE_SAMPLE_CACHE.get(key)
if cached is not None:
    return cached
rs = np.linspace(0.0, float(region_radius), int(n_radial) + 1)
ts = np.linspace(0.0, 2.0 * math.pi, int(n_angular), endpoint=False)
rr, tt = np.meshgrid(rs, ts, indexing="ij")
grid = np.column_stack([rr.ravel() * np.cos(tt.ravel()),
                        rr.ravel() * np.sin(tt.ravel())])
tb = np.linspace(0.0, 2.0 * math.pi, int(n_boundary), endpoint=False)
bnd = np.column_stack([float(region_radius) * np.cos(tb),
                        float(region_radius) * np.sin(tb)])
samples = np.vstack([grid, bnd])
_COVERAGE_SAMPLE_CACHE[key] = samples
return samples

def coverage_profile(visited: Sequence[Point],
                    region_radius: float = REGION_RADIUS) -> Tuple[float, Point]:
    """返回 ``(最坏最近距离, 最深处采样点)``。

    最坏最近距离 =  $\max_{X \in \text{圆域}} \min_{p \in \text{已访问}} |X - p|$  (采样估计);
    最深处即达到该值的采样点, 用作"去补哪一个洞"的目标。
    """
    samples = coverage_samples(region_radius)
    if not visited:
        return float("inf"), (0.0, 0.0)
    pts = np.asarray(visited, dtype=float)
    d = np.sqrt(((samples[:, None, :] - pts[None, :, :]) ** 2).sum(axis=2))
    nearest = d.min(axis=1)
    idx = int(np.argmax(nearest))
    return float(nearest[idx]), (float(samples[idx, 0]), float(samples[idx, 1]))

def bearing_least_squares(
    records: Sequence[Tuple[Point, float]],
    region_radius: float = REGION_RADIUS,
) -> Optional[Point]:
    """用示向中心线的正交距离最小二乘估计目标位置。

    对第  $i$  条示向线, 令法向量  $n_i = (-\sin(\beta_i), \cos(\beta_i))$ , 求解
     $\min_x \sum_i [n_i^T (x - p_i)]^2$ 。与直接取有界楔形交的最小覆盖圆
    圆心相比, 该估计不会被 ``bbox`` 的人工截断边界拖向远处。最后投影到
    题设目标圆域, 避免少量近共线观测产生物理上不可能的远端估计。
    """
    if len(records) < 2:
        return None
    a00 = a01 = a11 = z0 = z1 = 0.0
    for (px, py), bearing in records:
        rad = math.radians(float(bearing))
        nx, ny = -math.sin(rad), math.cos(rad)
        rhs = nx * px + ny * py
        a00 += nx * nx
        a01 += nx * ny
        a11 += ny * ny
        z0 += nx * rhs
        z1 += ny * rhs
    det = a00 * a11 - a01 * a01
    if det <= 1e-8:
        return None
    x = (z0 * a11 - z1 * a01) / det
    y = (a00 * z1 - a01 * z0) / det
    radius = math.hypot(x, y)
    if radius > region_radius:
        scale = region_radius / radius
        x, y = x * scale, y * scale
    return (x, y)

@dataclass
class StrategyResult:
    cleared: int = 0
    total: int = 0
    virtual_time: float = 0.0
    measures: int = 0
    clears: int = 0
    failed_clears: int = 0

```

```

move_distance: float = 0.0          # 累计移动距离 (m), 用于区分"移动/动作"耗时
unresolved: List[int] = field(default_factory=list)

@property
def clearance_ratio(self) -> float:
    return self.cleared / self.total if self.total else 1.0

@property
def mean_clear_time(self) -> float:
    return self.virtual_time / self.cleared if self.cleared else float("inf")

@property
def mean_move_distance(self) -> float:
    return self.move_distance / self.cleared if self.cleared else float("inf")

class StrategyP3:
    """问题 3 的搜索-定位-清除策略。"""

    def __init__(
        self,
        survey_points: Optional[Sequence[Point]] = None,
        clear_diameter_threshold: float = 2.0 * CLEAR_RADIUS,
        max_homing_steps: int = 25,
    ) -> None:
        # 默认走**自适应"覆盖-清除"路径(问题 3 全向专用);
        # 显式传入 survey_points 时走固定检测点网络(问题 4 定向安全网需要)。
        self.survey_points = list(survey_points) if survey_points else []
        self.clear_diameter_threshold = float(clear_diameter_threshold)
        self.max_homing_steps = int(max_homing_steps)
        # 清除个数达到该值即可提前结束(问题 4 总数上限 16)
        self.max_total: float = float("inf")
        # ---- 自适应覆盖参数(仅 _run_adaptive 使用) ----
        # 覆盖骨干: 中心 + 半径 1000 m 的 cover_ring_count 点均布。
        # 解析最坏覆盖距离 = sqrt(1800^2+a^2-2*1800*a*cos(pi/k)):
        # k=7 时 998.25 m
        # k=14 时, 每隔 2 取一个(共 7 点, 等角 2pi/7) 仍是 998.25 m —
        # 即**加密环并不改变覆盖保证**, 只增加"几何复测点"(见 _probe)。
        self.cover_ring_radius = 1000.0
        self.cover_ring_count = 14
        self.cover_probe_stride = 2
        # 实际到访的"几何复测点"个数(7 = 全部; 实测 4 个即够; N=16 由 248.5→245.6 s、
        # 检测 147.6→137.6 次; 再减少(3/0)反而变差, 因为更多源被迫留到收尾折返)。
        self.probe_keep = 4
        # 干扰源总数上限(题给 10~16): 清满即必定清空, 可提前结束
        self.max_jammers = int(JAMMER_NUM_RANGE[1])
        # 只有楔形交最小覆盖圆半径 <= 该值时才把它作为追踪目标(否则继续沿骨干
        # 探测、等几何条件变好再前往), 避免带着坏估计白跑并导致清除失败。
        self.pursue_mec_limit = 160.0
        # 细长区域源(近共线、MEC 半径超限)不排进路线: 交给收尾统一处理。
        # 实测强行插入会让 N=10 劣化 357→473 s、行程 13→17 km(形心不可信)。
        # 单次"顺路插入"允许的额外路程上限(实测 2500 m 最优: N=10/12/16 分别
        # 366/329/267 → 357/328/256 s); 超过就留给收尾阶段的统一 TSP。
        self.insert_limit = 2500.0
        # regret 插入: 只有当"延迟到收尾的代价 - 现在插入的代价"超过该阈值才插入
        self.insert_min_regret = 0.0
        # 覆盖点剪枝阈值("剪后仍 <= cover_limit 才算安全")。
        # 删 1 个坏点后, 即使清除点完美填补缺口, 剩余 6 环点的 5 个 51.4° 间隙最坏
        # 仍是 998.25 m(7 环点固有值), 故阈值必须略高于 998.25 才剪得动;
        # 998.5 + 采样误差(~0.1 m) < 1000, 安全裕量 ~1.4 m。
        self.cover_limit = 998.5
        # ---- 「覆盖 discharge」开关(默认开启) ----
        # 清除点做一次"只测零观测频道"的全频道扫描 ⇒ 升级为合法覆盖点 ⇒ 剪掉冗余环点。
        self.inplace_sweep_after_clear = True
        self.prune_coverage_points = True
        self.inplace_sweep_min_gain = 300.0
        # 只在"复扫能换来剪点"时才复扫(见 _inplace_would_help)
        self.inplace_sweep_targeted = True
        # 迭代逼近阈值: 推进到该距离以内后, 1° 示向度误差的横向偏差只有
        # 382·tan(1°)= 6.7 m(累计 3° 时约 20 m = 清除半径), 此时按示向度
        # 直接清除是可靠的(参考"迭代逼近"思路)。
        self.approach_threshold = 382.0
        # 侧移复测的偏移量与开关(问题 3 全向源适用; 见 _tighten_and_clear)
        self.shift_step = 250.0
        # 侧移复测的**多档偏移**: 定向源的可测半平面有限, 一次 250 m 侧移常直接

```

```

# 走出可见区（实测 no_signal），而 30~120 m 的小侧移既留在可见区内、又能
# 与原有示向度形成足够视差，把长条形定位区域收紧到可网格清除的尺度。
self.shift_steps = (250.0, 120.0, 60.0, 30.0)
# 沿示向度射线做 1-D 扫描的步长与范围（见 _ray_scan_clear 的保证性推导）
self.ray_scan_step = 18.0
self.ray_scan_range = 600.0
# _corridor_like 的判据参数（决定是否启用 1-D 射线扫描）
self.corridor_min_diameter = 120.0
self.corridor_ratio = 4.0
# 示向度交会区域的裁剪外接框（源必在 1800 m 圆域内）；调大可复现历史行为
self.region_bbox = 1.0e6
# 是否允许把"细长区域源"（近共线、MEC 半径 > pursue_mec_limit）排进路线。
# False = 拒插，留给收尾统一处理（实测更省，见 _source_target 注释）
self.insert_sliver_sources = False
self.tighten_shift = True
# 仅 1 条示向度时的"切向复测探测点"参数（见 _source_target）：
# 垂直于视线切向偏移 500 m，到源的距离 <= sqrt(800^2+500^2)=943 m < R_min，
# 因此**必定仍在接收范围内**；同时与视线成约 90°，视差充足
# （测距误差  $\approx d^2 \cdot \tan \epsilon / b \approx 26$  m），随后 27 m 网格即可保证性收口。
self.probe_angle_deg = 90.0
self.probe_distance_m = 500.0
# 近场保证性网格的面积上限：楔形交区域是细长条，面积小则网格点数很少，
# 按面积（而不是直径）触发可以把"斜长但很窄"的区域也纳入保证性收口。
self.grid_clear_near_area = 60000.0
# 允许"顺路插入"所需的最少示向度条数。保持 2：单条示向度源在覆盖扫描期间
# 极多（刚扫 1~2 个点就一大堆），立即追击会破坏环形巡游结构（实测 21~31 km）。
# 它们交给收尾阶段的追击处理（见 _resolve_channel），那时覆盖扫描已完成、
# 只剩少数边界源，追击才划算。
self.insert_min_observations = 2
# 单条示向度时，沿视线前进的追击步长（保守小步，避免越过真值后漏掉）
self.pursuit_step = 150.0
self.pursuit_max_steps = 20
# 1 条示向度时的"预测性牵引复测点"：沿示向度前进 + 侧向视差
self.pursuit_side = 300.0
# 定位区域最小覆盖圆半径超过该值  $\Rightarrow$  "定位差"，先测后清（省一次必失败的 clear，
# 且近场示向度高视差，最小二乘重估后偏差压到几米内）。定位好则先清（省 6 s 检测）。
self.measure_first_mec = 40.0
# 自适应观测：2 条示向度且 MEC <= obs_mec_limit 即视为定位足够（不再要第 3 条）
self.adaptive_obs = True
self.obs_mec_limit = 30.0
# 阶段 3（区域网格清除）参数
self.max_resolve_rounds = 6
self.grid_clear_max_diameter = 1200.0
self.probe_angles_deg = (20.0, -20.0, 0.0)
# 探测步长：由远及近。必须包含 <= CLEAR_RADIUS 量级的小步长，
# 否则当"唯一可见点离源极近"（例如 86 m）时，沿示向度探测会直接
# **越过源**（越过即进入定向源的背向半平面  $\Rightarrow$  全部 no_signal），
# 拿不到第 2 条示向度就永远无法交会定位（曾导致 22 点网 1/300 未清）。
self.probe_steps_m = (450.0, 225.0, 110.0, 55.0, 25.0)
# 保证性网格间距：格点间距 s 时，区域 P 内任一点到最近格点距离 <= s/√2，
# 取 24 m 得 17.0 m < 20 m 清除半径（原为 27 m，最坏 19.1 m 只剩 0.9 m 裕量，
# 实测出现"格点恰好差 2~3 m 清不掉"的失败）。
self.grid_spacing = 24.0
# 仍失败时再补一遍**半格偏移**格点（等效间距 s/2，最坏 8.5 m），
# 用于兜住"定位区域 P 边缘真值"与浮点临界。
self.grid_offset_pass = True
self.grid_max_points = 400
# 近场保证性网格：楔形交区域直径小于该值时直接布 27 m 网格收口
self.grid_clear_near_diameter = 180.0
# 三条示向线可消除两线近共线造成的长尾误差；试验中首次清除命中率
# 由约 78% 提升到 91% 以上，而检测动作数仅小幅增加。
self.observations_target = 3
self.direct_attempt_max_radius = 180.0
self.fast_ray_step = 35.0
self.fast_ray_max_distance = 90.0
# 估计点邻域微网格步长（见 _local_grid_clear）
self.local_grid_step = 24.0

# ----- #
# 主流程（按是否给定固定检测点网分派）
# ----- #
def run(self, transport, channel_order=None, do_enter=True):
    """问题 3 主入口：默认自适应"覆盖-清除"，给定 survey_points 时走固定网。"""
    if self.survey_points:
        return self._run_fixed_design(transport, channel_order, do_enter)

```

```

        return self._run_adaptive(transport, channel_order, do_enter)

# ----- #
# 自适应"覆盖-清除" (问题 3 默认路径)
# ----- #
def _run_adaptive(self, transport, channel_order=None, do_enter=True):
    """覆盖骨干 + 动态路径重规划: 把"探测覆盖"与"清除行程"合并成一条路线。

    做法 (每次只走一步, 然后按最新信息重规划):
    1. **覆盖骨干**: 中心 + 半径 1000 m 七均布 (解析最坏覆盖距离 998.25 m),
       它是一个"保证性覆盖集", 走完即保证任意全向源都被探测到;
    2. 在当前位置用 **2-opt 重规划** ``[当前位置] + 剩余骨干点 + 已定位源的
       估计点``, 取巡游的第一站作为下一步;
    3. 走到骨干点 → 对该点做一次全频道探测 (覆盖 + 发现新源);
       走到源估计点 → 只做该频道的清除动作 (**不再重复检测其它频道**,
       覆盖已由骨干保证, 省下每个源访问点 ~10 个空频道的检测动作);
    4. 骨干走完且无待清除源时结束; 失败/仅 1 条示向度的频道交严格兜底。

    为什么快: 旧实现付"绕骨干一圈 ~6.2 km + 折返清除 TSP ~7.4 km";
    本实现付一条把源顺路插进骨干的合并巡游 (离线最优约 9.99 km, N=10),
    并且不在源访问点重复检测空频道。
    """
    result = StrategyResult()
    if do_enter:
        transport.enter()
    channels = list(channel_order) if channel_order else list(CHANNELS)
    bearings = {ch: [] for ch in channels}
    cleared = set()
    attempted: set = set() # 已顺路清除尝试过的频道 (每频道至多一次)
    scheduled: set = set() # 已排进路线的频道 (避免重复插入)

    origin = self._current_position(transport)
    ring = seven_point_design(self.cover_ring_radius, self.cover_ring_count)
    # "全频道扫描点": 每隔 stride 取一个。stride=2 且 count=14 时,
    # 被选中的 7 个点恰好等角 (2π/7) 分布 — 就是标准 7 点覆盖集,
    # 解析最坏覆盖距离 998.25 m < R_min, 因此**不漏测的保证只依赖它们**。
    sweep_points = {ring[i] for i in range(0, len(ring), self.cover_probe_stride)}
    probe_candidates = [p for i, p in enumerate(ring)
                        if i % self.cover_probe_stride]
    keep = min(int(self.probe_keep), len(probe_candidates))
    if keep <= 0:
        probe_points: List[Point] = []
    elif keep >= len(probe_candidates):
        probe_points = list(probe_candidates)
    else:
        # 均匀抽稀 (保留几何分布最散的那几个)
        step = len(probe_candidates) / float(keep)
        probe_points = [probe_candidates[int(k * step)] for k in range(keep)]
    backbone = two_opt_tour([origin] + [p for p in ring
                                       if p in sweep_points or p in probe_points])

    # 路线元素: (点, 频道或 None, 是否全频道扫描)
    route: List[Tuple[Point, Optional[int], bool]] = [
        (p, None, p in sweep_points or p == origin) for p in backbone]
    visited: List[Point] = []
    self._pruned_at = -1

    # 起点探测: 不产生任何移动耗时, 直接拿下 1000 m 内的所有源
    self._sweep(transport, origin, channels, bearings, cleared, result)
    visited.append(self._current_position(transport))
    # 合法覆盖点集合: 只有在这里面做过**全频道扫描**的位置才能计入覆盖判据
    swept: List[Point] = [tuple(self._current_position(transport))]

    index = 0
    while index < len(route) - 1 and len(cleared) < self.max_jammers:
        # 把新定位到的源插进"剩余路线"最省的那一段
        self._schedule_sources(route, index, channels, bearings,
                               cleared, attempted, scheduled)
        # 注意: 这里**不做**"剪枝剩余覆盖点"。曾试验过按覆盖判据删除冗余网点,
        # 但那会漏清 — 因为复测点只测"进行中"频道、源清除点也只测目标频道,
        # 它们不能充当"让每个频道都被测过一遍"的覆盖点; 唯一合法的覆盖点是
        # 做过**全频道扫描**的点 (7+1 个), 而对圆域覆盖而言它们一个都不能少
        # (k=6 需要 a>=1122 m, k=7 需要 a>=997 m, 删任一点即破覆盖)。
        point, channel, full = route[index + 1]
        if channel is None:
            if full:
                # 覆盖扫描点: 全频道探测 (覆盖 + 发现新源)
                self._sweep(transport, point, channels, bearings,

```

```

        cleared, result)
    swept.append(tuple(self._current_position(transport)))
else:
    # 几何复测点: 只复测"进行中"频道 (见 _probe)
    self._probe(transport, point, channels, bearings,
                cleared, result)
else:
    # 顺路清除: 只做该频道动作, 不重复检测其它频道 (覆盖由覆盖点保证)
    scheduled.discard(channel)
    attempted.add(channel)
    if self._fast_clear(transport, channel, point,
                        bearings[channel], result):
        cleared.add(channel)
    # 「发现即清除 + 原地复扫」: 清除点若离已扫点足够远, 就地做一次
    # 全频道扫描, 把它升级为**合法覆盖点**, 为后续剪枝创造合法性。
    if self.inplace_sweep_after_clear:
        here = tuple(self._current_position(transport))
        gap = min((distance(here, q) for q in swept),
                  default=float("inf"))
        if gap >= self.inplace_sweep_min_gain and (
            not self.inplace_sweep_targeted
            or self._inplace_would_help(route, index,
                                         swept, here)):
            self._discharge_sweep(transport, here, channels,
                                  bearings, cleared, result)
            swept.append(tuple(self._current_position(transport)))
    visited.append(self._current_position(transport))
    # 合法剪枝: 已扫点 U 剩余覆盖点仍能覆盖全域时, 删掉冗余的剩余覆盖点
    if self.prune_coverage_points:
        self._prune_coverage(route, index, swept)
    index += 1

self._finalize_channel_clearing(transport, channels, bearings, cleared, result)

transport.exit()
result.cleared = len(cleared)
result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

def _inplace_would_help(self, route, index: int, swept, here) -> bool:
    """在 ``here`` 复扫, 能否换来**剪掉至少一个剩余覆盖点**?

    discharge 一次要测 4~14 个零观测频道 (24~84 s), 被剪的覆盖点省下
    "走到它 + 它那里的全频道扫描" (≈240~260 s)。只有能换剪点才复扫。
    """
    base = list(swept) + [here]
    for i in [i for i, (p, ch, full) in enumerate(route)
              if i > index + 1 and ch is None and full]:
        if i > index + 1 and ch is None and full:
            plan = [q for j, (q, ch, full) in enumerate(route)
                   if j > index + 1 and ch is None and full and j != i]
            if self._covers(base + plan):
                return True
    return False

def _covers(self, points) -> bool:
    """覆盖判据: 点集对 1800 m 圆域的最坏最近距离 <= ``cover_limit``。

    覆盖圆域问题时, **最坏点必在边界** (圆域边界或两覆盖圆交点; 交点处
    min-distance <= 相邻覆盖点, 恒 <= 边界角中点的最坏值), 故只采样边界即可
    (确定性等角 14400 点, 弧长 0.79 m, 误差 <0.4 m), 比内部网格快一个量级。
    """
    pts = np.asarray(list(points), dtype=float)
    th = np.linspace(0.0, 2.0 * math.pi, 14400, endpoint=False)
    bnd = 1800.0 * np.column_stack([np.cos(th), np.sin(th)])
    d = np.linalg.norm(bnd[:, None, :] - pts[None, :, :], axis=2)
    return float(d.min(axis=1).max()) <= self.cover_limit

def _prune_coverage(self, route, index: int, swept) -> None:
    """删除"已冗余"的剩余覆盖点 (**合法性由 swept 保证**)。

    覆盖义务: 每个**零观测频道**的源位置都要落在某个"做全频道扫描"的点的
    1000 m 内。sweep 点与 discharge 点都做了全频道扫描 (discharge 测当时
    所有零观测频道), 故 ``swept`` (起点 + sweep 点 + discharge 点) 都是合法
    覆盖点。已有示向度的频道发现义务已尽, 不再需要覆盖。

```

```

只剪 ``index`` 之后的剩余覆盖点；剪之前用"剪后仍 <= cover_limit"验证；
每次剪一个，反复直到不能再剪。
"""
while True:
    candidates = [i for i, (p, ch, full) in enumerate(route)
                   if i > index + 1 and ch is None and full]
    if not candidates:
        return
    removed = False
    for i in candidates:
        plan = [q for j, (q, ch, full) in enumerate(route)
                 if j > index + 1 and ch is None and full and j != i]
        if self._covers(list(swept) + plan):
            route.pop(i)
            removed = True
            break
    if not removed:
        return

def _schedule_sources(self, route, index, channels, bearings, cleared,
                      attempted, scheduled) -> None:
    """把"已可信定位"的源按**最便宜插入**排进剩余路线。

    为什么用插入而不是每步重规划：覆盖骨干本身已是一条约 6.2 km 的最近最优
    巡游，把源插到它最省的那一段上能保住骨干结构，从而兑现"探测与清除共用
    一条路径"的收益 — 离线最优 N=10 约 9.99 km，而"绕骨干 + 折返清除"
    需要 13.59 km。逐步 2-opt 重规划会让巡游在骨干与源之间反复改道，
    实测行程反而涨到 13.6 km。

    ``insert_limit`` 限制单次插入的额外路程：代价过大的源不硬插，
    留给收尾阶段的统一 TSP 处理（那里没有后续骨干约束，更省）。
    """
    while True:
        seq = [route[index][0]] + [p for p, _, _ in route[index + 1:]]
        best = None
        for ch in channels:
            if ch in cleared or ch in attempted or ch in scheduled:
                continue
            records = bearings[ch]
            if len(records) < self.insert_min_observations:
                continue
            estimate = self._source_target(records, seq[0])
            if estimate is None:
                continue
            for k in range(len(seq) - 1):
                a, b = seq[k], seq[k + 1]
                cost = (distance(a, estimate) + distance(estimate, b)
                       - distance(a, b))
                if cost > self.insert_limit:
                    continue
                if best is None or cost < best[0]:
                    best = (cost, index + 1 + k, ch, estimate)
            if best is None:
                return
            _, position, channel, estimate = best
            route.insert(position, (estimate, channel, False))
            scheduled.add(channel)
            self._improve_remaining(route, index)

    @staticmethod
    def _improve_remaining(route, index: int, rounds: int = 4) -> None:
        """对**未走过的剩余路线**做 2-opt + Or-opt 局部改进（严格只接受变短的移动）。

        "最便宜插入"是启发式：逐个把源插进剩余路线后难免留下绕行段。实测问题 3
        N=16: 实际 14.84 km，而**同一到访点集**的最优巡游只要 12.61 km — 2.23 km
        (=446 s、28 s/源)花在排序上。纯 2-opt 只能回收 0.06 km，因为它的弱点恰好
        是"把一段长绕行中的点搬到别处"；这里补上 **Or-opt**（整段 1~3 点搬迁），
        这才是对这种"顺路插入 + 绕行"结构的有效算子。

        安全性：只对 ``route[index:]``（当前位置 + 尚未到访的点）做**严格变短**的
        移动，所有点仍然都会被走到，因此**覆盖保证不受影响**（覆盖只依赖"走过"）；
        也不会像"逐步全规划"那样在骨干与源之间来回改道（那种做法实测劣化到 13.6 km）。
        """
        m = len(route)
        if m - index < 4:
            return
        # --- 2-opt ---

```

```

for _ in range(rounds):
    improved = False
    for i in range(index, m - 2):
        a, b = route[i][0], route[i + 1][0]
        for j in range(i + 2, m - 1):
            c, d = route[j][0], route[j + 1][0]
            if (distance(a, b) + distance(c, d)
                > distance(a, c) + distance(b, d) + 1e-9):
                route[i + 1:j + 1] = route[i + 1:j + 1][::-1]
                improved = True
    if not improved:
        break
# --- Or-opt: 把长度 1~3 的连续段移到别处 ---
for seg_len in (1, 2, 3):
    moved = True
    while moved and m - index > seg_len + 2:
        moved = False
        for s in range(index + 1, m - seg_len):
            seg = route[s:s + seg_len]
            prev, nxt = route[s - 1][0], route[s + seg_len][0]
            gain_out = (distance(prev, seg[0][0])
                        + distance(seg[-1][0], nxt)
                        - distance(prev, nxt))
            if gain_out <= 1e-9:
                continue
            rest = route[:s] + route[s + seg_len:]
            best = None
            for t in range(index, len(rest) - 1):
                u, v = rest[t][0], rest[t + 1][0]
                add_in = (distance(u, seg[0][0]) + distance(seg[-1][0], v)
                          - distance(u, v))
                if best is None or add_in < best[0]:
                    best = (add_in, t + 1)
            if best is not None and best[0] < gain_out - 1e-9:
                route[:] = rest[:best[1]] + seg + rest[best[1]:]
                moved = True
                break

def _probe(self, transport, point: Point, channels, bearings, cleared,
           result: StrategyResult) -> int:
    """几何复测点：只复测"进行中"的频道（已有示向度但不足观测目标）。

    这些点不承担覆盖义务，因此**不检测零观测频道**（空频道），
    代价仅几次检测动作；却能把"只被 1 个骨干点看到"的难源补足到可交会定位，
    使其清除动作能并进主路线，避免收尾阶段再折返一趟。
    """
    done = 0
    for ch in channels:
        if ch in cleared:
            continue
        records = bearings[ch]
        if not records or self._observations_complete(records):
            continue
        if self._beyond_reachable(point, records):
            continue
        resp = transport.measure(point, ch)
        result.measures += 1
        done += 1
        kind = resp.get("measure_result")
        if kind == "direction":
            bearings[ch].append((point, float(resp["svd_deg"])))
        elif kind == "near" and self._try_clear(transport, ch, point, result):
            cleared.add(ch)
    return done

def _source_target(self, records, here: Optional[Point] = None) -> Optional[Point]:
    """给出"顺路即可清除"的目标点（决定每个源插到路线哪一段）。

    分三种情形，覆盖从"定位很准"到"只有 1 条示向度"的全部已发现源：
    1. 示向度 >= 2 且楔形交区域最小覆盖圆半径 <= ``pursue_mec_limit``:
       取**最小二乘交会点**（比最小覆盖圆圆心更准：实测首次清除命中率
       62.5%→64.2%、每源 clear 次数 39.3→37.3、时间 362.2→360.7 s）；
       最小二乘失败时回退到圆心 — 真值必在区域内，圆心误差不超过该半径。
    2. 示向度 >= 2 但区域偏大（典型：两条示向度近共线 ⇒ 区域是**细长条**）：
       此时**不能用形心** — 近共线的交会区域被裁剪到 ``bbox``，形心可能落在
       几千米之外（实测曾出现 6350 km 的荒谬行程）。改用"区域内离当前位置

```

最近的点”：它落在细长条靠近我们的一端，走过去的行程最小，到了再复测一次就能把条带收紧（这本质上是**沿视线逼近**，而非绕到远端）。

3. **只有 1 条示向度**：无法交会定距。**重写**：不再做 90° 切向复测点（那是一次几百米的绕行，且实测把主路线拉到 23.4 km），而是沿视线前进 ``pursuit\_step`` 米——这是一个“朝源走”的点，行程是必付的；到达后复测一次拿到更近的示向度，再沿视线追击（_ray_scan_clear 指数+二分）收敛。

```

"""
if len(records) >= 2:
    poly = self._region_of(records)
    if poly:
        center, radius = min_enclosing_circle(poly)
        if radius <= self.pursue_mec_limit:
            lsq = bearing_least_squares(records)
            if lsq is not None and distance(lsq, center) <= radius:
                return (float(lsq[0]), float(lsq[1]))
            return (float(center[0]), float(center[1]))
        # 细长区域：默认**不排程**（交给收尾的统一处理）。
        # 依据：细长条的形心不可信（近共线时甚至可达千米级偏差）；
        # 实测“强行插入细长条源”会让 N=10 劣化 357→514 s。
        if not self.insert_sliver_sources:
            return None
        centroid = polygon_centroid(poly)
        return (float(centroid[0]), float(centroid[1]))
base, bearing = records[-1]
ux, uy = unit_vector(bearing)
sx, sy = unit_vector(bearing + 90.0)
return (base[0] + self.pursuit_step * ux + self.pursuit_side * sx,
        base[1] + self.pursuit_step * uy + self.pursuit_side * sy)

def _region_of(self, records) -> List[Point]:
    """示向度交会区域（裁剪到目标区域外接框，见 ``region_bbox``）。"""
    return localization_region([p for p, _ in records],
                               [b for _, b in records],
                               bbox=float(self.region_bbox))

@classmethod
def _nearest_point_in(cls, poly: Sequence[Point],
                      here: Optional[Point]) -> Point:
    """凸多边形内离 ``here`` 最近的点；``here`` 为空时退回形心。

    先判内部：``here`` 在 P 内就直接用它（零行程）。否则沿各边取最近点。
    """
    if here is None:
        centroid = polygon_centroid(poly)
        return (float(centroid[0]), float(centroid[1]))
    if cls._inside_convex(poly, here):
        return (float(here[0]), float(here[1]))
    best, best_d = None, float("inf")
    n = len(poly)
    for i in range(n):
        a, b = poly[i], poly[(i + 1) % n]
        k = cls._project_on_segment(here, a, b)
        d = distance(here, k)
        if d < best_d:
            best, best_d = k, d
    if best is None:
        centroid = polygon_centroid(poly)
        return (float(centroid[0]), float(centroid[1]))
    return (float(best[0]), float(best[1]))

@staticmethod
def _project_on_segment(q: Point, a: Point, b: Point) -> Point:
    """q 在线段 ab 上的投影点。"""
    ax, ay = a
    dx, dy = b[0] - ax, b[1] - ay
    denom = dx * dx + dy * dy
    if denom <= 1e-12:
        return (float(ax), float(ay))
    t = ((q[0] - ax) * dx + (q[1] - ay) * dy) / denom
    t = 0.0 if t < 0.0 else (1.0 if t > 1.0 else t)
    return (float(ax + t * dx), float(ay + t * dy))

def _confident_target(self, records) -> Optional[Point]:
    """返回“可信追踪目标”：楔形交区域的**最小覆盖圆圆心**。

    真值必落在楔形交区域 P 内，因此该圆心到真值的距离不超过 P 的最小覆盖圆半径。只有该半径 <= ``pursue_mec_limit`` 时才值得专门跑一趟：

```

半径小 $\Rightarrow$ 估计可信 $\Rightarrow$ 一击命中率高，且失败时的补救代价有界。
半径过大（例如两条近共线示向度形成的细长平行四边形）则返回 `None`。
继续沿覆盖骨干探测，等更多示向度把区域收缩后再前往。

```

"""
poly = localization_region([p for p, _ in records],
                             [b for _, b in records])

if not poly:
    return None
center, radius = min_enclosing_circle(poly)
if radius > self.pursue_mec_limit:
    return None
return (float(center[0]), float(center[1]))

@staticmethod
def _point_segment_distance(q: Point, a: Point, b: Point) -> float:
    """点 q 到线段 ab 的最短距离。"""
    ax, ay = a
    bx, by = b
    qx, qy = q
    dx, dy = bx - ax, by - ay
    denom = dx * dx + dy * dy
    if denom <= 1e-12:
        return distance(q, a)
    t = ((qx - ax) * dx + (qy - ay) * dy) / denom
    t = 0.0 if t < 0.0 else (1.0 if t > 1.0 else t)
    return distance(q, (ax + t * dx, ay + t * dy))

@classmethod
def _distance_to_polygon(cls, q: Point, poly: Sequence[Point]) -> float:
    """点 q 到凸多边形 poly 的最短距离（内部返回 0）。"""
    if cls._inside_convex(poly, q):
        return 0.0
    n = len(poly)
    return min(cls._point_segment_distance(q, poly[i], poly[(i + 1) % n])
               for i in range(n))

def _region_mec(self, records) -> float:
    """定位区域（楔形交）的最小覆盖圆半径；示向度 <2 或区域为空返回 inf。"""
    if len(records) < 2:
        return float("inf")
    poly = self._region_of(records)
    if not poly:
        return float("inf")
    _, radius = min_enclosing_circle(poly)
    return float(radius)

def _beyond_reachable(self, point: Point, records) -> bool:
    """该频道在 ``point`` 处是否**必然 no_signal**（严格判据，可安全跳过检测）。

    依据：单次测向误差  $\leq 1^\circ$ （题给），故真值必落在全部示向度决定的**楔形交区域 P** 内；而有效接收半径  $r_{\text{eff}} \leq R_{\text{MAX}} = 1500 \text{ m}$ （题给上界）。于是
    ``dist(point, P) > 1500``  $\Rightarrow$  ``dist(point, G) > r_eff``  $\Rightarrow$  测了也是 no_signal。
    跳过它能省下一次 5 s 检测 + 至多 1 s 切换，**且无损任何保证**（该次检测
    无论如何都不携带信息）。
    """
    poly = localization_region([p for p, _ in records],
                               [b for _, b in records])

    if not poly:
        return False
    return self._distance_to_polygon(point, poly) > R_MAX

def _discharge_sweep(self, transport, point: Point, channels, bearings, cleared,
                     result: StrategyResult) -> int:
    """清除点的**discharge 扫描**：只测零观测频道（覆盖义务），返回检测次数。

    覆盖义务：一个频道若真有源但尚未被发现，源必落在某个“会做全频道扫描”的点 1000 m 内。discharge 点在这里做全频道扫描后，就承担了这个义务。

    **为何只测零观测频道**：obs>=1 的频道已经被发现（源距某个观测点  $\leq r_{\text{eff}}$ ，发现义务已尽），额外的观测只改善定位、不是发现义务，测不测都行。所以这里只测零观测频道，把成本压到 4~14 次检测（24~84 s），而不是全 20 频道。
    对零观测频道而言，sweep 点与 discharge 点都测过它，故二者都是合法覆盖点。
    """
    done = 0
    for ch in channels:
        if ch in cleared or bearings[ch]:
            continue

```

```

        resp = transport.measure(point, ch)
        result.measures += 1
        done += 1
        kind = resp.get("measure_result")
        if kind == "direction":
            bearings[ch].append((tuple(point), float(resp["svd_deg"])))
        elif kind == "near" and self._try_clear(transport, ch, point, result):
            cleared.add(ch)
    return done

def _sweep(self, transport, point: Point, channels, bearings, cleared,
          result: StrategyResult) -> int:
    """移动到 ``point`` 并对所有未决频道做一次探测，返回实际检测次数。

    首个 /measure 会把机器人带到 ``point`` (模拟器按位置差计费)，因此
    "前往该点"与"在该点探测"是同一条指令；若没有任何频道需要检测，
    则机器人不会移动（调用方用 ``_current_position`` 记录真实到访位置）。
    """
    done = 0
    for ch in channels:
        if ch in cleared or self._observations_complete(bearings[ch]):
            continue
        # 严格无损的检测削减：该点必定收不到信号则跳过（见 _beyond_reachable）
        if bearings[ch] and self._beyond_reachable(point, bearings[ch]):
            continue
        resp = transport.measure(point, ch)
        result.measures += 1
        done += 1
        kind = resp.get("measure_result")
        if kind == "direction":
            bearings[ch].append((point, float(resp["svd_deg"])))
        elif kind == "near" and self._try_clear(transport, ch, point, result):
            cleared.add(ch)
    return done

# ----- #
# 固定检测点网路径（问题 4 定向安全网复用）
# ----- #
def _run_fixed_design(self, transport, channel_order=None, do_enter=True):
    """按预定检测点网逐点扫描，再统一清除，并以有界楔形法兜底。

    实测对比（全定向 N=16, 25 例）：“逐点扫描 + 收尾 TSP” 478.6 s；
    改成“把每个已定位源最便宜插入剩余路线”反而 **519.8 s**（且出现未清除）——
    因为定向源可见点极少、发现得晚，插入位置离路线很远；当源较密时
    “收尾阶段对估计点做精确 TSP”本来就是最优的。故问题 4 保留本路径，
    插入机制只在问题 3（全向、发现早）使用。
    """
    result = StrategyResult()
    if do_enter:
        transport.enter()
    channels = list(channel_order) if channel_order else list(CHANNELS)
    bearings = {ch: [] for ch in channels}
    cleared = set()
    # 每次 run 独立的状态袋（机会式清除的次数记录等），避免跨次运行串味
    state: Dict[str, object] = {}
    self.early_stop_bearings = getattr(self, "early_stop_bearings", 2)

    tour = self._tour_order()
    for index, p in enumerate(tour):
        self._sweep(transport, p, channels, bearings, cleared, result)
        # 提前结束扫描：``early_stop_bearings`` 条示向度齐备的源数达到总数上限 16
        # 即停。默认 2（交会定位）；若收尾对 1 条示向度的源有可靠兜底（如沿示向度
        # 追击），可降为 1 以更早结束。
        if sum(1 for ch in channels
              if len(bearings[ch]) >= self.early_stop_bearings) >= self.max_total:
            break
        # 机会式清除：离开当前扫描点之前，允许子类顺路清除已定位的频道
        if index + 1 < len(tour):
            self._opportunistic_clear(transport, channels, bearings, cleared,
                                     result, p, tour[index + 1], state)
            if len(cleared) >= self.max_total:
                break

    self._finalize_channel_clearing(transport, channels, bearings, cleared, result)

    transport.exit()
    result.cleared = len(cleared)

```

```

result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

def _finalize_channel_clearing(self, transport, channels, bearings, cleared,
                              result: StrategyResult) -> None:
    """收尾：对已产生示向度但仍未清除的频道做统一快速清除 + 严格兜底。"""
    candidates = {}
    for ch in channels:
        if ch in cleared or len(bearings[ch]) < 2:
            continue
        center = bearing_least_squares(bearings[ch])
        if center is not None:
            candidates[ch] = center
        else:
            target = self._source_target(
                bearings[ch], self._current_position(transport))
            if target is not None:
                candidates[ch] = target

    for ch in self._channel_tour(candidates, self._current_position(transport)):
        if self._fast_clear(transport, ch, candidates[ch], bearings[ch], result):
            cleared.add(ch)

    # 只处理"已产生过示向度"的未决频道：频道空间有 20 个，而干扰源只有
    # 10~16 个，因此**零观测频道绝大多数本来就没有干扰源**（空频道）。
    # 覆盖判据保证"若某频道真有源，全域已被探测过 => 它必已被发现"，
    # 故跳过零观测频道是正确行为；切勿为其添加"重走检测点"的兜底
    # （实测每例会白走近 10 km，耗时劣化数倍）。
    pending = [ch for ch in channels if ch not in cleared and bearings[ch]]
    while pending and len(cleared) < self.max_total:
        cur = self._current_position(transport)
        ch = min(pending, key=lambda c: distance(cur, self._resolve_anchor(bearings[c])))
        pending.remove(ch)
        if self._resolve_channel(transport, ch, bearings[ch], result):
            cleared.add(ch)
        else:
            result.unresolved.append(ch)

    transport.exit()
    result.cleared = len(cleared)
    result.total = self._evaluate_total(transport)
    result.virtual_time = self._virtual_time(transport)
    result.move_distance = self._move_distance(transport)
    return result

# ----- #
# 机会式清除钩子（问题 3 默认不启用；问题 4 重写为"顺路清除"）
# ----- #
def _opportunistic_clear(self, transport, channels, bearings, cleared,
                        result: StrategyResult, current: Point,
                        next_point: Point, state: Dict[str, object]) -> None:
    """在离开扫描点 ``current`` 前顺路清除已定位频道。

    问题 3 的 8 点扫描行程短、快速清除已在扫描后统一用精确开放路径完成，
    故基类此钩子为空实现（无副作用，不改变问题 3 行为）。
    """
    return None

@staticmethod
def _move_distance(transport) -> float:
    """累计移动距离 (m)：读机器人时钟历史（Mock 与真实客户端均有）。"""
    clock = getattr(transport, "clock", None)
    if clock is None:
        clock = getattr(getattr(transport, "client", None), "clock", None)
    history = getattr(clock, "history", None) or []
    return float(sum(getattr(cost, "distance_m", 0.0) for _, cost in history))

def _fast_clear(self, transport, channel: int, estimate: Point,
                records: List[Tuple[Point, float]], result: StrategyResult) -> bool:
    """统计估计直接清除；失败时按"迭代逼近"在近场保证性收口。

    三级收口（由便宜到昂贵，第一级成功即返回）：
    1. 直接在估计点清除（楔形交最小覆盖圆圆心，误差 <= pursue_mec_limit）；
    2. 修订估计后再试一次（用估计点的新示向度更新最小二乘）；
    3. **保证性收口**：若楔形交区域 P 直径已很小，按 27 m 间距在 P 内布点

```

```

        逐一清除 — 因真值必在 P 内且间距  $\leq 20\sqrt{2}$ , 必有一点落在清除半径内;
        否则沿示向度在估计点**两侧**按 382 m 阈值内的步长逼近清除
        (1° 误差在 382 m 处的横向偏差仅 6.7 m, 远小于 20 m 清除半径)。
    """
    # 自适应: 定位好(MEC 小)先清; 定位差(MEC 大)先测后清 —
    # 定位差的源直接清必失败(偏差可达上百米), 先测一次拿高视差近场示向度,
    # 最小二乘重估后偏差压到几米内再清, 省掉那次必失败的 clear。
    if self._region_mec(records) <= self.measure_first_mec:
        if self._try_clear(transport, channel, estimate, result):
            return True
    m = transport.measure(estimate, channel)
    result.measures += 1
    kind = m.get("measure_result")
    if kind == "near":
        return self._try_clear(transport, channel, estimate, result)

    bearing = None
    if kind == "direction":
        bearing = float(m["svd_deg"])
        records.append((estimate, bearing))
        revised = bearing_least_squares(records)
        if revised is not None and distance(revised, estimate) <= self.fast_ray_max_distance:
            if self._try_clear(transport, channel, revised, result):
                return True

    # 阶段 2.5-沿最后示向度射线的 1-D 扫描收口(对付"定向源沿波束轴观测"的病态
    # 楔形交: 解析保证命中, 见 _ray_scan_clear)。
    # **仅在真正病态时启用**: 定位区域沿示向度方向被拉得很长(细长走廊)才需要
    # 1-D 扫描; 否则该阶段命中率低(实测调用 9.8 次仅成功 3.0 次), 白花检测。
    if records and self._corridor_like(records):
        bpoint, bbearing = records[-1]
        if self._ray_scan_clear(transport, channel, bpoint, bbearing, result):
            return True

    # 阶段 2.6-估计点邻域**微网格**: 楔形交直径常只有几十米、真值在 20 m 清除半径
    # 边缘"擦边"漏掉, 此时做 250 m 级侧移(一次来回 500 m)极不划算; 3×3 微网格
    # 单步  $\leq 24$  m、最坏 9 点约 40 s 即可补救(见 _local_grid_clear)。
    if self._local_grid_clear(transport, channel, estimate, result):
        return True

    # 阶段 3-保证性收口: 区域小而窄时直接布 27 m 网格(真值必在 P 内)
    if len(records) >= 2:
        poly = localization_region([p for p, _ in records],
                                   [b for _, b in records])

        if poly:
            diam, _, _ = polygon_diameter_calipers(poly)
            if (diam <= self.grid_clear_near_diameter
                or polygon_area(poly) <= self.grid_clear_near_area):
                return self._grid_clear(transport, channel, poly, result)

    # 阶段 3.5-沿示向度**短距**双向逼近 (span<=90 m): 失败时最多走 180 m 来回,
    # 比原 210 m 级(420 m 来回)省一半; 远距离的病态情形已由阶段 2.5 的射线
    # 扫描负责, 因此把这一级的射程收紧。
    if bearing is not None and self._ray_clear_both(transport, channel, estimate,
                                                    bearing, result):
        return True

    # 阶段 4-**最后手段**: 侧移复测(垂直示向度偏移, 代价最大: 一个来回数百米)
    if self.tighten_shift and self._tighten_and_clear(transport, channel,
                                                    records, result):
        return True
    return False

def _corridor_like(self, records) -> bool:
    """定位区域是否是"沿示向度方向的细长走廊"(此时才需要 1-D 射线扫描)。

    判据: 楔形交区域的**直径**远大于其在垂直示向度方向上的宽度,
    即 ``diam >= corridor_ratio * width``, 或区域直径本身超过
    ``corridor_min_diameter`` (几十米以上就意味着沿轴测距不可靠)。
    典型触发场景: 定向源沿其波束轴被观测、或多条示向度近共线。
    """
    if len(records) < 2:
        return True
    poly = localization_region([p for p, _ in records],
                               [b for _, b in records])

    if not poly:
        return True
    diam, _, _ = polygon_diameter_calipers(poly)
    if diam >= self.corridor_min_diameter:
        return True

```

```

_, bearing = records[-1]
ux, uy = unit_vector(bearing + 90.0)
proj = [q[0] * ux + q[1] * uy for q in poly]
width = max(proj) - min(proj)
return diam >= self.corridor_ratio * max(width, 1e-6)

def _local_grid_clear(self, transport, channel: int, center: Point,
                      result: StrategyResult) -> bool:
    """估计点邻域的 3x3 **微网格**收口（廉价、先于大范围侧移）。

    楔形交的直径通常只有几十米，而估计点（最小覆盖圆圆心 / 形心）未必正中，
    真值常落在 20 m 清除半径**边缘**：此时直接做 250 m 级侧移要一个来回 500 m，
    极不划算。改为在估计点  $\pm$  `local_grid_step` 内布 3x3 网格（单步  $\leq$  24 m，
    最坏 9 次清除约 40 s、行程  $\leq$  170 m），命中率高且代价低；真正病态的情形
    （细长走廊）交给阶段 2.5 的射线扫描与阶段 4 的侧移兜底。
    """
    step = self.local_grid_step
    offs = (0.0, step, -step)
    pts = [(center[0] + dx, center[1] + dy) for dx in offs for dy in offs]
    current = self._current_position(transport)
    pts.sort(key=lambda q: distance(current, q))
    for q in pts:
        if self._try_clear(transport, channel, q, result):
            return True
    return False

def _pursuit_clear(self, transport, channel: int, base: Point, bearing: float,
                   result: StrategyResult) -> bool:
    """**重瞄追击**：沿示向度向源逼近，每步用当前实测示向度**重瞄**方向。

    这是"1 条示向度"源的定位手段：把"走到源附近"的必付行程本身当作定位。
    关键在**重瞄**——每步沿当前实测示向度走，横向误差只相对于"当前剩余距离"
    ( $\leq 0.0175 \times$  剩余距离)，随收敛趋零；这正是之前固定射线追击在  $d > 1140$  m 时
    横向偏差超 20 m 而漏过的原因。对**全向源**（问题 3 全是全向），朝源走距离
    单调递减  $\Rightarrow$  必先"direction"后"near"；一旦示向度翻转  $180^\circ$ （越过真值）就二分。
    """
    cur = base
    b = bearing
    step = self.pursuit_step
    for _ in range(self.pursuit_max_steps):
        q = self._point_along(cur, b, step)
        if self._try_clear(transport, channel, q, result):
            return True
        resp = transport.measure(q, channel)
        result.measures += 1
        kind = resp.get("measure_result")
        if kind == "near":
            return self._try_clear(transport, channel, q, result)
        if kind == "direction":
            nb = float(resp["svd_deg"])
            if abs(angle_diff(nb, b)) > 90.0:
                # 越过了真值：源在 cur 与 q 之间，二分
                return self._pursuit_bisect(transport, channel, cur, q, result)
            cur = q
            b = nb
            step = min(step * 1.3, 300.0) # 越走越近，可加大步长
        else:
            # no_signal: 全向源罕见，退回小步
            step = max(step / 2.0, 20.0)
            if step <= 20.0:
                return False
    return False

def _pursuit_bisect(self, transport, channel: int, a: Point, b: Point,
                    result: StrategyResult) -> bool:
    """在"未越过点 a"与"已越过点 b"之间二分找源（源在 ab 附近）。"""
    for _ in range(14):
        mid = ((a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0)
        if self._try_clear(transport, channel, mid, result):
            return True
        resp = transport.measure(mid, channel)
        result.measures += 1
        kind = resp.get("measure_result")
        if kind == "near":
            return self._try_clear(transport, channel, mid, result)
        if kind == "direction":
            nb = float(resp["svd_deg"])
            ux, uy = unit_vector(nb)

```

```

        toward_a = (a[0] - mid[0]) * ux + (a[1] - mid[1]) * uy
        if toward_a > 0.0:
            b = mid
            # 源在 a 侧
        else:
            a = mid
            # 源在 b 侧
    else:
        a = mid
        # no_signal: 源在另一侧
    if distance(a, b) <= 10.0:
        break
    return self._try_clear(transport, channel,
                          ((a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0), result)

def _ray_scan_clear(self, transport, channel: int, base: Point, bearing: float,
                    result: StrategyResult) -> bool:
    """沿**最后一条示向度射线**按固定步长扫描并逐点试清除（保证性收口）。

    设最后一条示向度取自 ``base``、报告值 ``bearing``。题目保证单次测向误差
    <= 1°, 故真值必落在“以 base 为起点、方向 bearing 的射线两侧各 1° 的楔形”内；
    射线上距 base 为 t 的点到真值的**横向偏差** <= t·tan1° = 0.0175t。因此沿射线
    以步长 s 扫描时，命中条件为 ``sqrt((s/2)² + (0.0175t)²) <= 20``：取
    s=18 m、t=600 m，最坏 ``sqrt(81+110) = 13.8 m < 20 m``，**必然命中**。

    这专门解决“**定向源沿其波束轴被观测**”的病态情形：此时三条示向度几乎同向，
    楔形退化为沿轴 1000 m 的细长走廊，测距完全不可用，而本方法把“2-D 定位”降级
    为“1-D 扫描”，反而必然收敛。每两步复测一次示向度，一旦发现已越过真值即停止
    延伸，避免无谓长走；成功则直接返回。
    """
    step = self.ray_scan_step
    t = step
    while t <= self.ray_scan_range + 1e-9:
        q = self._point_along(base, bearing, t)
        if self._try_clear(transport, channel, q, result):
            return True
        if abs(t / (2.0 * step) - round(t / (2.0 * step))) < 1e-9:
            resp = transport.measure(q, channel)
            result.measures += 1
            kind = resp.get("measure_result")
            if kind == "near":
                return self._try_clear(transport, channel, q, result)
            if kind == "direction" and \
                abs(angle_diff(float(resp["svd_deg"]), bearing)) > 90.0:
                return False
                # 已越过真值：前方不会再有
        t += step
    return False

def _tighten_and_clear(self, transport, channel: int,
                       records: List[Tuple[Point, float]],
                       result: StrategyResult) -> bool:
    """**侧移复测**收紧定位区域后保证性清除。

    三角交会的测距精度取决于**基线（视差）**：两点相距 d 时，测距相对误差
    约为 ``d²·tan(ε)/b``——基线 b 不够大时测距误差可达百米量级，这正是
    “顺路插入”失败、被迫折返的原因。这里在最后一條示向度的垂直方向上偏移
    一小段复测（代价约 250 m + 1 次检测），新示向度与原有示向度形成足够
    视差，把楔形交区域直径压到 180 m 以内后，用 27 m 间距网格保证性清除。

    仅在近场使用（偏移后源仍在接收范围内的概率高），因此适合问题 3 的全向源；
    对定向源若偏移后收不到信号，会自动跳过（不增加错误动作）。
    """
    if not records:
        return False
    base, bearing = records[-1]
    for offset in [mag * sgn for mag in self.shift_steps for sgn in (1.0, -1.0)]:
        probe = self._point_along(base, bearing + 90.0, offset)
        resp = transport.measure(probe, channel)
        result.measures += 1
        kind = resp.get("measure_result")
        if kind == "near":
            return self._try_clear(transport, channel, probe, result)
        if kind != "direction":
            continue
        records.append((probe, float(resp["svd_deg"])))
        poly = localization_region([p for p, _ in records],
                                   [b for _, b in records])
        if not poly:
            continue
        diam, _, _ = polygon_diameter_calipers(poly)

```

```

        if diam <= self.grid_clear_near_diameter:
            return self._grid_clear(transport, channel, poly, result)
        return False

def _ray_clear_both(self, transport, channel: int, estimate: Point,
                    bearing: float, result: StrategyResult) -> bool:
    """沿示向度在估计点**两侧**按 35 m 步长试清除。

    只向正方向扫描会漏掉"估计距离偏远"的情形（楔形交区域沿示向度方向被
    拉长，测距误差有正有负）；双向扫描把两侧都覆盖，实测显著降低清除失败率，
    从而避免失败的频道被推到收尾阶段再跑一趟。
    """
    step = self.fast_ray_step
    span = max(self.fast_ray_max_distance, self.pursue_mec_limit)
    offset = step
    while offset <= span + 1e-9:
        for sign in (1.0, -1.0):
            q = self._point_along(estimate, bearing, sign * offset)
            if self._try_clear(transport, channel, q, result):
                return True
            offset += step
    return False

def _ray_recover(self, transport, channel, origin, max_distance, records, result):
    """At an estimate, turn 2-D uncertainty into a covered 1-D bearing ray."""
    m = transport.measure(origin, channel)
    result.measures += 1
    kind = m.get("measure_result")
    if kind == "near":
        return self._try_clear(transport, channel, origin, result)
    if kind != "direction":
        return False
    bearing = float(m["svd_deg"])
    records.append((origin, bearing))
    lateral = max_distance * math.sin(math.radians(1.0))
    if lateral >= CLEAR_RADIUS:
        return False
    half = math.sqrt(max(1.0, CLEAR_RADIUS ** 2 - lateral ** 2))
    spacing = max(8.0, 1.9 * half)
    d = spacing
    while d <= max_distance + spacing:
        q = self._point_along(origin, bearing, d)
        if self._try_clear(transport, channel, q, result):
            return True
        d += spacing
    return False

def _observations_complete(self, records):
    """观测是否足够（默认 3 条；自适应：2 条 + MEC 足够小即可，第 3 条只在该拿时才拿）。

    依据：2 条示向度已能把定位区域的最小覆盖圆半径压到 ``obs_mec_limit`` 以内，
    再配 ``fast_clear`` 的"到点先测后清"，第三条示向度省下的清除成本已不抵再测
    一次的 6 s。仅在 MEC 仍大时才继续拿第 3 条。
    """
    if len(records) >= self.observations_target:
        return True
    if self.adaptive_obs and len(records) == 2:
        return self._region_mec(records) <= self.obs_mec_limit
    return False

@staticmethod
def _resolve_anchor(records):
    p, b = records[-1]
    ux, uy = unit_vector(b)
    return (p[0] + 350.0 * ux, p[1] + 350.0 * uy)

@staticmethod
def _channel_tour(candidates, start):
    """Exact Held-Karp open TSP for at most 16 targets."""
    ids = list(candidates)
    n = len(ids)
    if not n:
        return []
    dp = {}
    for i in range(n):
        dp[(2 ** i, i)] = (distance(start, candidates[ids[i]]), -1)
    for mask in range(1, 2 ** n):
        for last in range(n):

```

```

        state = (mask, last)
        if state not in dp:
            continue
        base = dp[state][0]
        for nxt in range(n):
            bit = 2 ** nxt
            if mask & bit:
                continue
            ns = (mask | bit, nxt)
            cost = base + distance(candidates[ids[last]], candidates[ids[nxt]])
            if ns not in dp or cost < dp[ns][0]:
                dp[ns] = (cost, last)
    full = 2 ** n - 1
    last = min(range(n), key=lambda j: dp[(full, j)][0])
    order = []
    mask = full
    while last >= 0:
        order.append(ids[last])
        prev = dp[(mask, last)][1]
        mask -= 2 ** last
        last = prev
    order.reverse()
    return order

def _try_clear(self, transport, channel: int, point: Point,
               result: StrategyResult) -> bool:
    r = transport.clear(point, channel)
    result.clears += 1
    if r.get("clear_result") == "success":
        return True
    result.failed_clears += 1
    return False

def _tour_order(self) -> List[Point]:
    """扫描顺序：先中心，再按环上角度顺序（六边形环行程为最优量级）。"""
    pts = list(self.survey_points)
    if not pts:
        return []
    center = min(pts, key=lambda p: p[0] ** 2 + p[1] ** 2)
    rest = [p for p in pts if p != center]
    rest.sort(key=lambda p: math.atan2(p[1], p[0]))
    return [center] + rest

# ----- #
# 阶段 3: 交会定位 + 区域网格清除（保证性收敛）
# ----- #

def _resolve_channel(self, transport, channel: int,
                    observations: List[Tuple[Point, float]],
                    result: StrategyResult) -> bool:
    """为一个频道补足示向度 -> 定位区域 -> 网格清除。

    依据：楔形交区域 P 必含真值 G ( $\leq 1^\circ$  有界误差)；在 P 内以
    间距  $\leq 20\sqrt{2} = 28.3$  m 布清除点，则必有一点落在 G 的 20 m 清除半径内，
    因此该过程必然成功（问题 3/4 通用；对定向源而言，清除与朝向无关，
    即使“看不到”也能清）。

    若 P 过大，则沿最后一条示向度推进再测，以新示向度缩小 P；
    沿示向度向源逼近时，定向源的覆盖条件保持成立（内积保号）。
    """
    records: List[Tuple[Point, float]] = list(observations)
    for _ in range(self.max_resolve_rounds):
        if len(records) >= 2:
            poly = self._region_of(records)
            if poly:
                diam, _, _ = polygon_diameter_calipers(poly)
                if diam <= 2.0 * CLEAR_RADIUS:
                    if self._try_clear(transport, channel,
                                       polygon_centroid(poly), result):
                        return True
                if diam <= self.grid_clear_max_diameter:
                    if self._grid_clear(transport, channel, poly, result):
                        return True
            if not self._extend_observation(transport, channel, records, result):
                return False
    return False

def _extend_observation(self, transport, channel: int,
                       records: List[Tuple[Point, float]],

```

```

        result: StrategyResult) -> bool:
    """获取新的示向度：在基准点周围做射线扇形探测。

    为何不只沿示向度推进：
    * 沿向推进虽然保持覆盖（内积保号），但两条示向度近似平行，
      交会出来的区域是细长条，定位效果差；
    * 而当年 $\pm 1^\circ$ 误差下沿向推进较远时可能越出定向覆盖，
      故用“垂直方向 $\pm 20^\circ$  / 沿向”的射线扇形探测，既保证交会角度，
      又在失联时自动退到更保守的沿向探测。
    """
    if not records:
        return False
    base_point, base_bearing = records[-1]
    for angle_off in self.probe_angles_deg:
        for step in self.probe_steps_m:
            point = self._point_along(base_point, base_bearing + angle_off, step)
            m = transport.measure(point, channel)
            result.measures += 1
            kind = m.get("measure_result")
            if kind == "near":
                return self._try_clear(transport, channel, point, result)
            if kind == "direction":
                records.append((point, float(m["svd_deg"])))
            return True
    return False

def _grid_clear(self, transport, channel: int, poly: Sequence[Point],
                result: StrategyResult) -> bool:
    """在定位区域 P 内布格点逐一尝试清除（间距  $\leq 20 \times \sqrt{2}$ ，保证命中）。"""
    pts = self._grid_points_in_polygon(poly, self.grid_spacing)
    # 补入形心 / 顶点 / 边中点（小区域时网格可能为空）
    pts = list(pts) + [polygon_centroid(poly)]
    n = len(pts)
    for i in range(n):
        a, b = poly[i], poly[(i + 1) % n]
        pts.append(a)
        pts.append(((a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0))
    if not pts:
        return False
    current = self._current_position(transport)
    pts.sort(key=lambda q: distance(current, q))
    for q in pts[:self.grid_max_points]:
        if self._try_clear(transport, channel, q, result):
            return True
    if not self.grid_offset_pass:
        return False
    # 第二轮：半格偏移格点。两套格点合起来等效间距  $s/2$ ，最坏离真值
    #  $\leq s/(2\sqrt{2}) \approx 8.5$  m，远超清除半径裕量，兜住“真值贴 P 边界/浮点临界”。
    off = self.grid_spacing / 2.0
    shifted = [(x + off, y + off) for x, y in pts]
    shifted = [q for q in shifted if self._inside_convex(poly, q, tol=1e-6)]
    shifted.sort(key=lambda q: distance(current, q))
    for q in shifted[:self.grid_max_points]:
        if self._try_clear(transport, channel, q, result):
            return True
    return False

@staticmethod
def _grid_points_in_polygon(poly: Sequence[Point], spacing: float) -> List[Point]:
    xs = [q[0] for q in poly]
    ys = [q[1] for q in poly]
    out: List[Point] = []
    x = min(xs)
    while x <= max(xs):
        y = min(ys)
        while y <= max(ys):
            if StrategyP3._inside_convex(poly, (x, y)):
                out.append((x, y))
            y += spacing
        x += spacing
    return out

@staticmethod
def _inside_convex(poly: Sequence[Point], q: Point, tol: float = 1e-9) -> bool:
    n = len(poly)
    sign = 0
    for i in range(n):
        x1, y1 = poly[i]

```

```

        x2, y2 = poly[(i + 1) % n]
        cross = (x2 - x1) * (q[1] - y1) - (y2 - y1) * (q[0] - x1)
        cur = 0 if abs(cross) <= tol else (1 if cross > 0 else -1)
        if cur == 0:
            continue
        if sign == 0:
            sign = cur
        elif sign != cur:
            return False
    return True

    @staticmethod
    def _current_position(transport) -> Point:
        clock = getattr(transport, "clock", None)
        pos = getattr(clock, "position", None)
        return (float(pos[0]), float(pos[1])) if pos else (0.0, 0.0)

    @staticmethod
    def _point_along(origin: Point, bearing_deg: float, dist: float) -> Point:
        ux, uy = unit_vector(bearing_deg)
        return (origin[0] + dist * ux, origin[1] + dist * uy)

# ----- #
# 统计适配 (兼容 MockSimulator 与 RobotClient)
# ----- #
    @staticmethod
    def _virtual_time(transport) -> float:
        if hasattr(transport, "virtual_time"):
            return float(getattr(transport, "virtual_time"))
        clock = getattr(transport, "clock", None)
        return float(getattr(clock, "virtual_time", 0.0))

    @staticmethod
    def _evaluate_total(transport) -> int:
        if hasattr(transport, "total_jammers"):
            return int(transport.total_jammers)
        sim = getattr(transport, "sim", None)
        if sim is not None and hasattr(sim, "total_jammers"):
            return int(sim.total_jammers)
        return 0

```

B.14 src/strategy_p3_v5.py

"""问题 3 v5: 覆盖义务驱动 (Coverage-obligation-driven) 在线规划。

与 v1 (固定 8 环点骨干 + 最便宜插入 + 收尾 TSP) 的核心区别:

- v1 把"发现顺序"和"覆盖顺序"绑定: 先走固定 7 环点, 途中把源插进剩余路线。
这天然产生"源被发现时其最优位置已走过"的结构性损失。
- v5 只保证"未发现源的可能位置 U 被已扫点集覆盖": 每一步动态生成下一扫描点
(贪心集合覆盖), 而源清除点 (discharge) 本身就是覆盖点, 能替代环点。
于是"清除行程"与"覆盖行程"合流, 逼近 Oracle (Oracle 正是靠走到源旁边
就完成覆盖而省掉绕环)。

保留不动: _sweep/_discharge_sweep/_fast_clear/_grid_clear/_covers/几何定位。
只重写主循环 run(): 覆盖义务 + 贪心补洞 + 顺路清除。

```

"""
from __future__ import annotations

import math
from typing import List, Tuple

import numpy as np

from .config import CHANNELS, REGION_RADIUS, R_MIN
from .geometry import distance, unit_vector
from .strategy_p3 import StrategyP3, StrategyResult

Point = Tuple[float, float]

class StrategyP3V5(StrategyP3):
    """覆盖义务驱动版: 动态覆盖集 = 起点 + 贪心补洞点 + 源清除点(discharge)。"""

    def __init__(self):
        super().__init__()

```

```

        self.cover_duty_limit = 998.0 # 覆盖义务"满足"判定: 最坏覆盖距离 <= 该值

# ----- #
def _worst_angle(self, swept) -> Tuple[float, float]:
    """边界上距 swept 最远的点: 返回 (角, 最坏距离)。确定性采样。"""
    pts = np.asarray(list(swept), dtype=float)
    th = np.linspace(0.0, 2.0 * math.pi, 720, endpoint=False)
    bnd = REGION_RADIUS * np.column_stack([np.cos(th), np.sin(th)])
    d = np.linalg.norm(bnd[:, None, :] - pts[None, :, :], axis=2)
    md = d.min(axis=1)
    idx = int(md.argmax())
    return float(th[idx]), float(md[idx])

def _next_cover(self, swept, here):
    """贪心补洞: 在"最坏边界点"方向、半径 R_MIN 处放下一覆盖点。"""
    ang, worst = self._worst_angle(swept)
    if worst <= self.cover_duty_limit:
        return None
    return (R_MIN * math.cos(ang), R_MIN * math.sin(ang))

def _covers_duty(self, swept) -> bool:
    """覆盖义务是否满足: swept 对圆域最坏覆盖距离 <= cover_duty_limit。"""
    pts = np.asarray(list(swept), dtype=float)
    th = np.linspace(0.0, 2.0 * math.pi, 14400, endpoint=False)
    bnd = REGION_RADIUS * np.column_stack([np.cos(th), np.sin(th)])
    d = np.linalg.norm(bnd[:, None, :] - pts[None, :, :], axis=2)
    return float(d.min(axis=1).max()) <= self.cover_duty_limit

def _open_tour(self, start, nodes, rounds=6):
    """最近邻 + 2-opt 开放巡游 (从 start 出发, 访问所有 nodes)。"""
    tour = [start]
    pool = list(nodes)
    while pool:
        nxt = min(pool, key=lambda q: distance(tour[-1], q))
        pool.remove(nxt)
        tour.append(nxt)
    n = len(tour)
    for _ in range(rounds):
        imp = False
        for i in range(n - 2):
            for j in range(i + 2, n - 1):
                a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                if (distance(a, b) + distance(c, d)
                    > distance(a, c) + distance(b, d) + 1e-9):
                    tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                    imp = True
        if not imp:
            break
    return tour[1:]

def _generate_covers(self, swept):
    """贪心生成满足当前覆盖义务所需的全部覆盖点。"""
    covers = []
    tmp = list(swept)
    for _ in range(9):
        ang, worst = self._worst_angle(tmp)
        if worst <= self.cover_duty_limit:
            break
        p = (R_MIN * math.cos(ang), R_MIN * math.sin(ang))
        covers.append(p)
        tmp.append(p)
    return covers

def _covers_duty(self, swept) -> bool:
    """覆盖义务是否满足: swept 对圆域最坏覆盖距离 <= cover_duty_limit。"""
    pts = np.asarray(list(swept), dtype=float)
    th = np.linspace(0.0, 2.0 * math.pi, 14400, endpoint=False)
    bnd = REGION_RADIUS * np.column_stack([np.cos(th), np.sin(th)])
    d = np.linalg.norm(bnd[:, None, :] - pts[None, :, :], axis=2)
    return float(d.min(axis=1).max()) <= self.cover_duty_limit

# ----- #
def run(self, transport, channel_order=None, do_enter=True):
    result = StrategyResult()
    if do_enter:
        transport.enter()
    channels = list(channel_order) if channel_order else list(CHANNELS)
    bearings = {ch: [] for ch in channels}

```

```

cleared: set = set()
attempted: set = set()

origin = self._current_position(transport)
swept: List[Point] = []

self._sweep(transport, origin, channels, bearings, cleared, result)
swept.append(tuple(self._current_position(transport)))

while len(cleared) < self.max_jammers:
    here = tuple(self._current_position(transport))

    nodes = []          # (point, channel or None)
    ch_of_point = {}

    # 覆盖点: 批量贪心生成 (当前 swept 所需的全部)
    for cover in self._generate_covers(swept):
        nodes.append(cover)

    # 源清除点
    for ch in channels:
        if ch in cleared or ch in attempted:
            continue
        if len(bearings[ch]) < self.insert_min_observations:
            continue
        est = self._source_target(bearings[ch], here)
        if est is not None:
            k = (round(est[0], 1), round(est[1], 1))
            if k not in ch_of_point:
                nodes.append(est)
                ch_of_point[k] = ch

    if not nodes:
        pending = [ch for ch in channels
                    if ch not in cleared and ch not in attempted
                    and bearings[ch]]
        if pending:
            ch = min(pending, key=lambda c: distance(
                here, self._resolve_anchor(bearings[c])))
            if self._resolve_channel(transport, ch, bearings[ch], result):
                cleared.add(ch)
                swept.append(tuple(self._current_position(transport)))
            continue
        break

    order = self._open_tour(here, nodes)
    point = order[0]
    k = (round(point[0], 1), round(point[1], 1))
    ch = ch_of_point.get(k)
    if ch is not None:
        attempted.add(ch)
        if self._fast_clear(transport, ch, point, bearings[ch], result):
            cleared.add(ch)
            here2 = tuple(self._current_position(transport))
            if min((distance(here2, q) for q in swept),
                    default=float("inf")) >= self.inplace_sweep_min_gain:
                self._discharge_sweep(transport, here2, channels,
                                       bearings, cleared, result)
            swept.append(here2)
    else:
        self._sweep(transport, point, channels, bearings, cleared, result)
        swept.append(tuple(self._current_position(transport)))

self._finalize_channel_clearing(transport, channels, bearings,
                                cleared, result)

transport.exit()
result.cleared = len(cleared)
result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

```

B.15 src/strategy_p4.py

"""问题 4 策略: 全向 + 定向混合干扰源的自动定位与清除。

与问题 3 的差异

-
- **检测点网必须定向安全****: 定向源只在"定向方向 $\pm 90^\circ$ "半平面内可被接收, 同一个 G 若其朝向背离所有检测点, 则在任何检测点都是 `no_signal`。
因此要求: 对域内任意 G 与任意朝向 u , 存在 p 使 $|p-G| \leq R_{\min}$ 且 $(p-G) \cdot u \geq 0$
 $\Leftrightarrow G$ 严格位于近旁点凸包内部 $\Leftrightarrow$ 近旁点相对 G 的最大角隙 $< 180^\circ$ 。
本策略采用 ****22 点定向安全网**** (中心 1 + 半径 1000 m 九点 + 半径 1875 m 十二点, 见 `coverage.directional_survey_design`), 它带****严格判据****而不只是随机抽样通过:
* 外环正十二边形内切半径 1811.11 m > 1800 m, 故目标圆域整体落在内环/外环构成的三角剖分内部;
* 采用****充要判据****: 对域内任意 G , 若"距 G 不超过 $R_{\min} = 1000$ m 的网点"相对 G 的最大角隙 $< 180^\circ$, 则 G 严格位于这些点的凸包内部, 于是任意朝向的定向源都至少被一个网点看到。该判据已用 3 级确定性密网复核 (最高 200×2160 极坐标 + 21600 边界环 = 455,760 样本): `fail = 0`, 最大角隙 177.38° (裕量 2.62°)。
相比 25 点双环网 (内环 950×12 + 外环 1875×12 错相 15°), 22 点网把内环半径顶到 $R_{\min} = 1000$ m 并把内环压到 9 点: ****覆盖证书强度不变**** (角隙同为 177.3768°), 但每轮扫描少扫 3 个网点 $\Rightarrow$ 检测动作数低约 12%, 实测 6 档平均 -14.3 s/源 ($N=10$ 档 $-22 \sim -39$ s/源)。相比 31 点三角格点 (开放巡游约 30.0 km), 22 点网把巡游压到约 18.06 km。
 - **总数上限 16****: 总数为 10~16, 故清满 16 个即已清空, 可提前结束; 未再扫描的频道无需确认 (省下大量检测与行程)。
 - **三条观测即停 + 顺路机会式清除****: 同一频道积累三条示向度后用中心线最小二乘定位; 若"绕到估计点再回到下一扫描点"的额外路程不超过 `insert_threshold` (默认 400 m), 就在扫描途中顺路清除, 从而减少扫描结束后的返程; 每频道至多插入一次。
 - **朝向推断**** (论文用): 由"在点 p 有信号 / 无信号"的符号约束 $(p-G) \cdot u \geq 0$ 与 < 0 , 可交出一段可行的定向方向弧, 用于辅助选点。

清除环节与问题 3 相同: `/clear` 与朝向无关, 距离 ≤ 20 m 必成功; 机会式/快速清除失败者由 `StrategyP3._resolve_channel` 的"楔形交收缩 + 27 m 网格"保证性兜底接住, 故不影响 100% 清除率。
"""

```
from __future__ import annotations

import math
from typing import Dict, List, Optional, Sequence, Tuple

from .config import CHANNELS, CLEAR_RADIUS, R_MIN
from .coverage import directional_survey_design, two_ring_design
from .geometry import angle_diff, distance, unit_vector
from .routing import tour_length as _tour_length, two_opt_tour
from .strategy_p3 import StrategyP3, StrategyResult, bearing_least_squares

Point = Tuple[float, float]

__all__ = ["StrategyP4", "two_opt_tour", "estimate_direction_arc"]

# ----- #
# 定向朝向的可行弧估计 (论文用; 也可用于选点)
# ----- #
def estimate_direction_arc(
    estimate: Point,
    detections: Sequence[Point],
    misses: Sequence[Point],
    r_min: float = R_MIN,
    step_deg: float = 1.0,
) -> List[float]:
    """由符号约束求定向方向 u 的可行弧 (返回可行角度列表, 空列表=无解)。

    有信号:  $(p - G) \cdot u \geq 0$ ; 无信号 (且  $|p-G| \leq r_{\min}$ ):  $(p - G) \cdot u < 0$ 。
    仅用  $|p-G| \leq r_{\min}$  的无信号点作为有效约束 (更远的无信号可能因超距)。
    """
    cons_det = [d for d in detections]
    cons_miss = [m for m in misses if distance(m, estimate) <= r_min]
    feasible: List[float] = []
    k = int(round(360.0 / step_deg))
    for i in range(k):
        ang = i * step_deg
        ux, uy = unit_vector(ang)
        ok = True
        for p in cons_det:
            if (p[0] - estimate[0]) * ux + (p[1] - estimate[1]) * uy < -1e-9:
```

```

        ok = False
        break
    if ok:
        for p in cons_miss:
            if (p[0] - estimate[0]) * ux + (p[1] - estimate[1]) * uy > 1e-9:
                ok = False
                break
    if ok:
        feasible.append(ang)
return feasible

```

```
class StrategyP4(StrategyP3):
```

```
    """问题4 策略：定向安全双环网 + 顺路机会式清除 + 严格楔形兜底。"""
```

```

def __init__(self, survey_points: Optional[Sequence[Point]] = None,
              insert_threshold: float = 400.0, **kwargs) -> None:
    # 默认用 22 点定向安全网 (directional_survey_design: 内环 1000×9 +
    # 外环 1875×12)。注意：曾用 25 点双环网 (950×12+1875×12 错相 15°),
    # 其"三角剖分全部边 < R_min"的充分条件更漂亮, 但 22 点网的角隙与之
    # 完全相同 (177.3768°) 而检测动作少约 12%, 故改用 22 点。
    # 另注意: 24 点网 (950×8+1850×16) 在"正上方边界源 + 朝向水平"角隙达
    # 186.6° > 180° 会漏测, 坚持用本网。
    default = survey_points or directional_survey_design()
    super().__init__(survey_points=default, **kwargs)
    self.max_total: float = 16.0 # 总数上限: 清满 16 个必然是全部
    # 顺路插入阈值: 直接把源插进"剩余路线最省的那一段" (与问题3 同款机制),
    # 只有额外路程不超过该值才插入, 其余留给收尾 TSP。
    # 400 m 为 Mock 消融实验的最优工作点。
    self.insert_limit = float(insert_threshold)

```

```
def _tour_order(self) -> List[Point]:
```

```
    """扫描顺序: **从内环起**的最近邻 + 2-opt + Or-opt (开放巡游)。
```

```

为什么从内环起: 内环点 (半径 950, 12 点) 负责"内部源", 外环点 (半径 1875,
12 点) 负责"边界源"; 先扫内环能让内部源更早被发现与定位, 从而更早触发

```

```
"16 源都 ≥2 条示向度即提前结束扫描"。实测 (15 例/档):
```

```
    全向 N=16 259.2→252.1、半定向 400.6→379.3、全定向 477.3→458.9 s/源;
```

```
    N=10 各档亦降 10~18 s/源。
```

```
    """
```

```

    pts = list(self.survey_points)
    # 中心 (原点) 本身就是起点, 不放进巡游列表; 内环按角排序后先走
    inner = [p for p in pts if 1.0 <= math.hypot(p[0], p[1]) < 1400.0]
    outer = [p for p in pts if math.hypot(p[0], p[1]) >= 1400.0]
    inner.sort(key=lambda q: math.atan2(q[1], q[0]))
    outer.sort(key=lambda q: math.atan2(q[1], q[0]))
    return self._strong_tour((0.0, 0.0), inner + outer)

```

```
@staticmethod
```

```

def _strong_tour(start: Point, points: Sequence[Point],
                 rounds: int = 10, warm: int = 4) -> List[Point]:
    """最近邻 + 2-opt + Or-opt 的开放巡游 (多起点取最短)。"""
    pts = list(points)
    if not pts:
        return [start]
    best: Optional[List[Point]] = None
    best_len = float("inf")
    for k in range(min(warm, len(pts))):
        tour = [start, pts[k]]
        pool = pts[k:] + pts[k + 1:]
        while pool:
            nxt = min(pool, key=lambda q: distance(tour[-1], q))
            pool.remove(nxt)
            tour.append(nxt)
        n = len(tour)
        for _ in range(rounds):
            improved = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                    if (distance(a, b) + distance(c, d)
                        > distance(a, c) + distance(b, d) + 1e-9):
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        improved = True
            for seg in (1, 2, 3):
                s = 1
                while s + seg < len(tour):

```

```

        blk = tour[s:s + seg]
        prev = tour[s - 1]
        nxt = tour[s + seg] if s + seg < len(tour) else None
        out = distance(prev, blk[0])
        if nxt is not None:
            out += distance(blk[-1], nxt) - distance(prev, nxt)
        rest = tour[:s] + tour[s + seg:]
        b2 = None
        for t in range(len(rest) - 1):
            u, v = rest[t], rest[t + 1]
            add = (distance(u, blk[0]) + distance(blk[-1], v)
                  - distance(u, v))
            if b2 is None or add < b2[0]:
                b2 = (add, t + 1)
        tail = distance(rest[-1], blk[0])
        if b2 is None or tail < b2[0]:
            b2 = (tail, len(rest))
        if b2[0] < out - 1e-9:
            tour = rest[:b2[1]] + blk + rest[b2[1]:]
            improved = True
        else:
            s += 1
    if not improved:
        break
    L = sum(distance(tour[i], tour[i + 1]) for i in range(len(tour) - 1))
    if L < best_len:
        best, best_len = tour, L
    return best if best is not None else [start]

def _observations_complete(self, records):
    """三条观测即可定位。

    楔形交在三条示向线下可消除两线近共线造成的公里级长尾误差；
    Mock 消融显示三条即停可以把检测动作数压到约 295 次，同时保持
    100% 清除率（定位失败的频道由 ``_resolve_channel`` 严格兜底）。
    """
    return len(records) >= self.observations_target

# ----- #
# 机会式清除：扫描途中顺路清除，减少扫描后的返程
# ----- #
def _opportunistic_clear(self, transport, channels, bearings, cleared,
                        result: StrategyResult, current: Point,
                        next_point: Point, state: Dict[str, object]) -> None:
    """在离开 ``current`` 之前，顺路清除已经定位得足够准的频道。

    判定：候选频道的额外路程
    delta = |cur-g| + |g-next| - |cur-next|
    不超过 ``insert_limit``（问题 4 默认由 ``insert_threshold`` 传入，400 m）时才插入清除动作，这里
    取机器人
    实际当前位置（清除动作可能已经把我们带离扫描点）。

    每个频道在一次运行中至多触发一次机会式插入（``state`` 中记录），
    避免同一“定位失败”的频道在后续每条扫描边上重复绕行；插入失败者
    仍会在扫描结束后的统一快速清除与严格兜底中被处理，因此不影响
    保证性。
    """
    attempted = state.setdefault("insert_attempted", set())
    assert isinstance(attempted, set)

    while True:
        cur = self._current_position(transport)
        best: Optional[Tuple[float, int, Point]] = None
        for ch in channels:
            if ch in cleared or ch in attempted:
                continue
            records = bearings[ch]
            if len(records) < self.observations_target:
                continue
            estimate = bearing_least_squares(records)
            if estimate is None:
                continue
            detour = (distance(cur, estimate) + distance(estimate, next_point)
                      - distance(cur, next_point))
            if detour > self.insert_limit:
                continue
            if best is None or detour < best[0]:

```

```

        best = (detour, ch, estimate)
    if best is None:
        return
    _, channel, estimate = best
    attempted.add(channel)
    if self._fast_clear(transport, channel, estimate,
                       bearings[channel], result):
        cleared.add(channel)
        continue
    return
# 继续检查这条边上是否还有其他顺路频道
# 该边不再插入；失败频道留给扫描后的统一清除

# ----- #
def direction_arc(self, estimate: Point, detections: Sequence[Point],
                 misses: Sequence[Point]) -> List[float]:
    return estimate_direction_arc(estimate, detections, misses)

```

B.16 scripts/_A2bear.py

"""实验 A-诊断：25 点网下"每个源可见点数 |H|"与"第二个 bearing 的位置"。

物理（与 mock_simulator 一致）：

源 $s=(G,u,r_{\text{eff}})$ 在检测点 P 可见 $\Leftrightarrow |P-G| \leq r_{\text{eff}}$ 且 $(P-G) \cdot u \geq 0$
 $|H(s)| \leq 1 \Rightarrow$ 该源永远拿不到第 2 条示向度 $\Rightarrow$ 提前结束不可能触发（必扫满）

```

import math
import random
import statistics
import sys

```

```
sys.path.insert(0, r"G:\C\CUMCM B 题")
```

```

from src.coverage import directional_survey_design # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

```

```

PTS = directional_survey_design()
N = len(PTS)

```

```

def visible(G, ux, uy, reff):
    out = []
    for i, (px, py) in enumerate(PTS):
        dx, dy = px - G[0], py - G[1]
        if dx * dx + dy * dy <= reff * reff and dx * ux + dy * uy >= -1e-9:
            out.append(i)
    return out

```

```

def sample_sources(m, seed=0, mode="directional"):
    rng = random.Random(seed)
    out = []
    for _ in range(m):
        r = 1800.0 * math.sqrt(rng.random())
        th = rng.random() * 2 * math.pi
        ang = rng.uniform(0.0, 360.0) if mode == "all" else rng.uniform(0.0, 360.0) * 0
        if mode == "mixed": # 一半全向一半定向
            ang = rng.uniform(0.0, 360.0) if rng.random() < 0.5 else None
        elif mode == "all":
            ang = rng.uniform(0.0, 360.0)
        ux, uy = (1.0, 0.0) if ang is None else (math.cos(math.radians(ang)),
                                                math.sin(math.radians(ang)))
        out.append(((r * math.cos(th), r * math.sin(th)), ux, uy,
                    rng.uniform(1000.0, 1500.0), ang is None))
    return out

```

```

M = 20000
srcs = sample_sources(M, seed=1, mode="all")
hist = {}
one = 0
for G, ux, uy, re, omn in srcs:
    k = len(visible(G, ux, uy, re))
    hist[k] = hist.get(k, 0) + 1
    if k <= 1:
        one += 1
print(f"【诊断1】{M} 个虚拟定向源在 25 点网上的 |可见点数| 分布：")
print(" " + " ".join(f"|H|={k}:{100.0*v/M:.1f}%" for k, v in sorted(hist.items())))
print(f" |H|<=1（永远拿不到第 2 条示向度 => 提前结束不可触发）= {100.0*one/M:.2f}%")

```

```

# 当前扫描顺序
tour = StrategyP4()._tour_order()
pos = {tuple(round(c, 6) for c in p): i for i, p in enumerate(tour)}
order_idx = []
for p in PTS:
    order_idx.append(pos[tuple(round(c, 6) for c in p)])
print(f"【诊断2】扫描顺序 rk[i]=该覆盖点在第几步被访问 (0 起): ")
print(" " + " ".join(f"{i}:{order_idx[i]}" for i in range(N)))

# t_stop = 最后一个源拿到第 2 条 bearing 的步号
r2 = []
for G, ux, uy, re, omn in srCs:
    H = visible(G, ux, uy, re)
    if len(H) < 2:
        r2.append(N) # 扫满 25 点也拿不到
    else:
        r2.append(sorted(order_idx[i] for i in H)[1])
r2.sort()
print(f"【诊断3】第 2 条 bearing 出现步号\分位: "
      f" 中位={r2[M//2]} P90={r2[int(0.9*M)]} P99={r2[int(0.99*M)]} max={r2[-1]}")
print(f" 平均={statistics.fmean(r2):.2f} 提前结束步号(max over sources)= {r2[-1]}")
print(f" 步号>=23 (即尾两点才有) 的比例 = {100.0*sum(1 for v in r2 if v >= 23)/M:.1f}%")

```

B.17 scripts/_A2bear2.py

"""实验 A-诊断 2: early=1(≥ 1 bearing) vs early=2(≥ 2 bearings) 的触发步号与代价。

```

- t_first = 16 个源全被"看到" ( $\geq 1$  bearing) 的步号 — early=1 的停止点
- t_2nd = 16 个源全拿到第 2 条 bearing 的步号 — early=2 的停止点 (当前)
- early=1 的额外代价: 停止时仍只有 1 条示向度的源, 必须由收尾兜底 (追击/网格)
"""
import math
import random
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import directional_survey_design # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

PTS = directional_survey_design()
NI = len(PTS)
TOUR = StrategyP4()._tour_order()
POS = {tuple(round(c, 6) for c in p): i for i, p in enumerate(TOUR)}
RK = [POS[tuple(round(c, 6) for c in p)] for p in PTS] # rk[i]=第几步访问点 i

# 累计路径长度 (步号 -> 已走距离)
CUM = [0.0]
for i in range(len(TOUR) - 1):
    CUM.append(CUM[-1] + math.dist(TOUR[i], TOUR[i + 1]))

def visible(G, ux, uy, reff):
    out = []
    for i, (px, py) in enumerate(PTS):
        dx, dy = px - G[0], py - G[1]
        if dx * dx + dy * dy <= reff * reff and dx * ux + dy * uy >= -1e-9:
            out.append(i)
    return out

def sample(ns, rng):
    """生成 ns 个源的可见点集。"""
    out = []
    for _ in range(ns):
        r = 1800.0 * math.sqrt(rng.random())
        th = rng.random() * 2 * math.pi
        ang = rng.uniform(0.0, 360.0)
        G = (r * math.cos(th), r * math.sin(th))
        out.append(visible(G, math.cos(math.radians(ang)),
                           math.sin(math.radians(ang)),
                           rng.uniform(1000.0, 1500.0)))
    return out

rng = random.Random(7)

```

```

M = 20000
tf, t2, n_one, n_zero = [], [], [], []
for _ in range(M):
    sracs = sample(16, rng)
    f = max((min(RK[i] for i in H) if H else NI - 1) for H in sracs)
    s = max((sorted(RK[i] for i in H)[1] if len(H) >= 2 else NI - 1) for H in sracs)
    tf.append(f)
    t2.append(s)
    n_one.append(sum(1 for H in sracs if len(H) == 1))
    n_zero.append(sum(1 for H in sracs if not H))

def q(v, p):
    return sorted(v)[int(p * (len(v) - 1))]

print(f"【诊断 4】16 源案例 ({M} 次), 步号分位 [中位 / P75 / P90]: ")
print(f"    t_first (early=1 停止) : {q(tf,0.5):2d} / {q(tf,0.75):2d} / {q(tf,0.90):2d}")
print(f"    t_2nd (early=2 停止) : {q(t2,0.5):2d} / {q(t2,0.75):2d} / {q(t2,0.90):2d}")
print(f"    差值 t_2nd-t_first : {statistics.fmean(t2)-statistics.fmean(tf):.2f} 步 (均值)")
print(f"    扫描距离 均值: early=2 停止处 {statistics.fmean([CUM[t] for t in t2])/1000:.2f} km"
      f" | 扫满 25 点 {CUM[-1]/1000:.2f} km"
      f" | early=1 停止处 {statistics.fmean([CUM[t] for t in tf])/1000:.2f} km")
print(f"    提前结束触发率: early=1 {(1-sum(1 for v in tf if v==NI-1)/M)*100:.1f}%"
      f"    early=2 {(1-sum(1 for v in t2 if v==NI-1)/M)*100:.1f}%"
      f"    t_first 处「仅 1 条示向度」的源数: 均值 {statistics.fmean(n_one):.2f}"
      f"    中位 {q(n_one,0.5)} P90 {q(n_one,0.9)}")
print(f"    0 可见点 (漏测风险) 的源数: 均值 {statistics.fmean(n_zero):.4f}"
      f"    max {max(n_zero)}")

```

B.18 scripts/_A2early.py

```

"""实验 A: early=1 (16 源都 ≥1 bearing 即停) 实测收益 vs early=2 (当前) 。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

class V(StrategyP4):
    def __init__(self, early=2, **kw):
        super().__init__(**kw)
        self.early_stop_bearings = early

def bench(ratio, n, early, seeds=30, **kw):
    T, M, U, DD = [], [], 0, 0
    for s in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=s, directional_ratio=ratio),
                             seed=s)
        r = V(early=early, **kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        DD += r.total
        U += len(r.unresolved)
    return statistics.fmean(T), statistics.fmean(M), U, DD / seeds

print("early=1 vs early=2 (30 例/档, 全定向比例 1.0 / 0.5 / 0.0, N=16) ")
for ratio, tag in [(1.0, "全定向"), (0.5, "半定向"), (0.0, "全向")]:
    for early in (2, 1):
        t, m, u, dd = bench(ratio, 16, early)
        print(f"    {tag} early={early}: {t:6.1f} s/源 行程{m:5.2f}km "
              f"    f未清{u} 总耗时{dd:7.0f}s")

```

B.19 scripts/_A2opt.py

```

"""实验 A-优化器: 直接以 J(pi)=E[L(t_stop)] 为目标搜索扫描顺序。

t_stop(pi) = max over 16 sources of 「该源第 2 个可见点在 pi 中的步号」
              (|H|<=1 的源记 t=24, 即无论如何都扫满 — 与在线一致)
L(t)        = 走完 pi 前 t+1 个点的累计路程
目标        : min E[L(t_stop)], 比「最短 Hamilton 路」更贴近真实提前结束口径

```

```

"""
import math
import random
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import directional_survey_design # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

PTS = directional_survey_design()
NI = len(PTS)
LAST = NI - 1
INIT = StrategyP4()._tour_order() # [(0,0)] + 24 点
START = INIT[0]

# ---- 预计算虚拟源的可见集 H（返回点序号列表） ----
def sample_H(m, seed):
    rng = random.Random(seed)
    out = []
    for _ in range(m):
        r = 1800.0 * math.sqrt(rng.random())
        th = rng.random() * 2 * math.pi
        ang = rng.uniform(0.0, 360.0)
        ux, uy = math.cos(math.radians(ang)), math.sin(math.radians(ang))
        re = rng.uniform(1000.0, 1500.0)
        G = (r * math.cos(th), r * math.sin(th))
        H = []
        for i, (px, py) in enumerate(PTS):
            dx, dy = px - G[0], py - G[1]
            if dx * dx + dy * dy <= re * re and dx * ux + dy * uy >= -1e-9:
                H.append(i)
        out.append(H)
    return out

H_POOL = sample_H(200 * 16, seed=11)
CASES = [H_POOL[i * 16:(i + 1) * 16] for i in range(200)]

IDX = {tuple(round(c, 6) for c in p): i for i, p in enumerate(PTS)}

def parse(order):
    """[(0,0)] + 24 点 -> 点序号排列（中心=0 恒在首位）+ 累计路程。"""
    seq = [IDX[tuple(round(c, 6) for c in START)]]
    for p in order[1:]:
        seq.append(IDX[tuple(round(c, 6) for c in p)])
    cum = [0.0]
    for i in range(len(order) - 1):
        cum.append(cum[-1] + math.dist(order[i], order[i + 1]))
    return seq, cum

def objective(order):
    seq, cum = parse(order)
    rk = [0] * NI
    for step, i in enumerate(seq):
        rk[i] = step
    tot = 0.0
    for case in CASES:
        t = 0
        for H in case:
            if len(H) >= 2:
                v = sorted(rk[i] for i in H)[1]
            else:
                v = LAST
            if v > t:
                t = v
        tot += cum[t]
    return tot / len(CASES)

def anneal(order, iters=4000, seed=3):
    rng = random.Random(seed)
    cur = list(order)
    val = objective(cur)
    best, bestv = list(cur), val
    for it in range(iters):

```

```

cand = list(cur)
if rng.random() < 0.5:
    # swap
    i, j = rng.randrange(1, len(cand)), rng.randrange(1, len(cand))
    cand[i], cand[j] = cand[j], cand[i]
else:
    # 2-opt 段反转
    i = rng.randrange(1, len(cand) - 1)
    j = rng.randrange(i + 1, len(cand))
    cand[i:j] = cand[i:j][::-1]
v = objective(cand)
T = max(0.5, 90.0 * (1 - it / iters))
if v < val or rng.random() < math.exp((val - v) / T):
    cur, val = cand, v
    if v < bestv:
        best, bestv = list(cand), v
return best, bestv

print(f"起点顺序 J = {objective(INIT)/1000:.3f} km (t_stop 处平均已走路程)")
best, bv = anneal(INIT, iters=6000, seed=3)
print(f"优化后 J = {bv/1000:.3f} km ({len(CASE5)} 组 16 源案例)")
print("优化后顺序 (步号:点序号):", parse(best)[0])
print("原顺序 (步号:点序号):", parse(INIT)[0])

# 保存供策略实验使用
import json # noqa: E402
with open(r"G:\C\CUMCM B 题\_A2order.json", "w", encoding="utf-8") as fh:
    json.dump({"order": [list(p) for p in best]}, fh)
print("已写出 _A2order.json")

# ----- 证伪检验 1: 随机顺序的 J -----
rng2 = random.Random(99)
rv = []
for _ in range(40):
    perm = list(INIT[1:])
    rng2.shuffle(perm)
    rv.append(objective([START] + perm))
print(f"[证伪 1] 随机顺序 J 均值 = {statistics.fmean(rv)/1000:.3f} km "
      f"(min {min(rv)/1000:.3f} / max {max(rv)/1000:.3f})"
      f" vs 起点顺序 {objective(INIT)/1000:.3f} km")

# ----- 证伪检验 2: 以「最短巡游」为目标优化 -----
def length_of(order):
    return sum(math.dist(order[i], order[i + 1]) for i in range(len(order) - 1))

def anneal_len(order, iters=6000, seed=5):
    rng = random.Random(seed)
    cur = list(order)
    val = length_of(cur)
    best, bestv = list(cur), val
    for it in range(iters):
        cand = list(cur)
        if rng.random() < 0.5:
            i, j = rng.randrange(1, len(cand)), rng.randrange(1, len(cand))
            cand[i], cand[j] = cand[j], cand[i]
        else:
            i = rng.randrange(1, len(cand) - 1)
            j = rng.randrange(i + 1, len(cand))
            cand[i:j] = cand[i:j][::-1]
        v = length_of(cand)
        if v < val or rng.random() < math.exp((val - v) / max(0.5, 60.0 * (1 - it / iters))):
            cur, val = cand, v
            if v < bestv:
                best, bestv = list(cand), v
    return best, bestv

b2, l2 = anneal_len(INIT, iters=6000, seed=5)
print(f"[证伪 2] 最短巡游: 起点 {length_of(INIT)/1000:.3f} km -> 优化 {l2/1000:.3f} km"
      f" (省 {(length_of(INIT)-l2)/1000:.3f} km), 但其 J = {objective(b2)/1000:.3f} km")

```

B.20 scripts/_Dcert.py

```

"""最终安全验证: 22 点候选网的超高分辨率定向覆盖证书。"""
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

```

```

sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from src.coverage import directional_certificate as cert # noqa: E402
from _Dtest import build # noqa: E402

for lbl, pts in (("基准 25 点 (950x12+1875x12)", build(950.0, 12, 1875.0, 12, 0.5)),
                 ("候选 22 点 (1000x9+1875x12)", build(1000.0, 9, 1875.0, 12, 0.0))):
    print(f"--- {lbl} ({len(pts)} 点) ---")
    for tag, (nr, na, nb) in (("高分辨 ", (80, 720, 7200)),
                             ("超高分辨", (120, 1440, 14400)),
                             ("极高分辨", (200, 2160, 21600))):
        r = cert(pts, n_radial=nr, n_angular=na, n_boundary=nb)
        print(f" {tag}: fail={r['fail']:4d} 最大角隙={r['max_gap_deg']:.4f}° "
              f"样本={r['n_samples']}")

```

B.21 scripts/_Dfail.py

```

"""诊断: 22 点网下 channel=12 为何清不掉 (1 条示向度 + 极近可见点 86m)。"""
import math
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")
sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from _Dtest import build, V # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402

for lbl, pts in (("22 点", build(1000.0, 9, 1875.0, 12, 0.0)),
                 ("23 点", build(1000.0, 10, 1875.0, 12, 0.5))):
    jam = random_case(n=16, seed=20, directional_ratio=0.5)
    src = [j for j in jam if j.channel == 12][0]
    sim = MockSimulator(jam, seed=20)
    r = V(pts).run(sim)
    acts = [e for e in sim.log if e.get("channel") == 12]
    meas = [e for e in acts if e["path"] == "/measure"]
    clr = [e for e in acts if e["path"] == "/clear"]
    n_dir = sum(1 for e in meas if e["measure_result"] == "direction")
    print(f"\n===== {lbl}: 未清={r.unresolved} =====")
    print(f" 源({src.x:.0f},{src.y:.0f}) dir={src.direction:.1f} r_eff={src.r_eff:.0f}"
          f" 动作: measure={len(meas)} (direction={n_dir}) clear={len(clr)}"
          f" 成功={sum(1 for e in clr if e['clear_result']=='success')}")
    for e in meas[:12]:
        print(f"    measure@({e['position'][0]:.0f},{e['position'][1]:.0f})"
              f" -> {e['measure_result']} svd={e['svd_deg']}")
    for e in clr[:12]:
        print(f"    clear @({e['position'][0]:.0f},{e['position'][1]:.0f})"
              f" d(源)={math.dist(e['position'], (src.x, src.y)):.1f} ->"
              f" {e['clear_result']}")

```

B.22 scripts/_Dfinal.py

```

"""实验 D-最终基准: 22 点网 vs 基准 25 点网 (修复探测步长后, 300+ 例)。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")
sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from _Dtest import bench, build # noqa: E402

BASE = build(950.0, 12, 1875.0, 12, 0.5)
N22 = build(1000.0, 9, 1875.0, 12, 0.0)
N23 = build(1000.0, 10, 1875.0, 12, 0.5)
SEEDS = 50

for label, pts in (("基准 25 点(950x12+1875x12)", BASE),
                   ("22 点(1000x9+1875x12)", N22),
                   ("23 点(1000x10+1875x12)", N23)):
    print(f"\n### {label}")
    tot, ust = [], 0
    for ratio, tag in ((1.0, "全定向"), (0.5, "半定向"), (0.0, "全向")):
        for n in (10, 16):
            t, m, u, a = bench(pts, ratio, n, seeds=SEEDS)
            tot.append(t)
            ust += u

```

```

        print(f"    {tag} N={n:<2d}: {t:6.1f} s/源 行程{m:5.2f}km "
              f"动作{a:4.0f} 未清{u}")
    print(f"    → 6 档平均 {statistics.fmean(tot):.2f} s/源, 未清合计 {ust}")

```

B.23 scripts/_Dnet.py

```

"""实验 D: 搜索"更少点的定向安全双环网" (证书 + 巡游长度双重筛选)。"""
import itertools
import math
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import directional_certificate # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

START = (0.0, 0.0)

def build(r1, n1, r2, n2, phase, with_center=True):
    pts = [START] if with_center else []
    for i in range(n1):
        a = 2 * math.pi * i / n1
        pts.append((r1 * math.cos(a), r1 * math.sin(a)))
    for i in range(n2):
        a = 2 * math.pi * (i + phase) / n2
        pts.append((r2 * math.cos(a), r2 * math.sin(a)))
    return pts

def tour_len(pts):
    t = StrategyP4._strong_tour(START, [p for p in pts if p != START],
                                rounds=6, warm=3)
    return sum(math.dist(t[i], t[i + 1]) for i in range(len(t) - 1))

def coarse(pts):
    return directional_certificate(pts, n_radial=24, n_angular=144,
                                   n_boundary=720)

def fine(pts):
    return directional_certificate(pts, n_radial=80, n_angular=720,
                                   n_boundary=7200)

def mid(pts):
    return directional_certificate(pts, n_radial=20, n_angular=180,
                                   n_boundary=1440)

results = []
cands = []
for n2 in (12, 14, 16, 18, 20, 24, 30):
    r2min = 1800.0 / math.cos(math.pi / n2)
    for dr in (3.0, 15.0):
        for n1 in (10, 12, 14, 16):
            for r1 in (800.0, 950.0, 1050.0):
                for phase in (0.0, 0.5):
                    cands.append((r1, n1, r2min + dr, n2, phase))
print(f"候选 {len(cands)} 个, 中精度筛查 (20×180 + 1440 边界) ...")
for r1, n1, r2, n2, phase in cands:
    pts = build(r1, n1, r2, n2, phase)
    c = mid(pts)
    if c["fail"] or c["max_gap_deg"] > 178.0:
        continue
    results.append((tour_len(pts), n1 + n2 + 1, r1, n1, r2, n2, phase,
                    c["max_gap_deg"], pts))

results.sort()
print(f"中精度通过 {len(results)} 个: 按巡游升序前 10: ")
print("  巡游 km 点数 r1 n1 r2 n2 ph 角隙°")
for l, np_, r1, n1, r2, n2, ph, gap, _ in results[:10]:
    print(f"  {l/1000:6.3f} {np_:4d} {r1:5.0f} {n1:3d} {r2:7.1f} {n2:3d}"
          f" {ph:4.2f} {gap:6.2f}")

print("\n 精筛 (80×720 + 7200 边界): ")
ok_any = False

```

```

for L, np_, r1, n1, r2, n2, ph, gap, pts in results[:6]:
    f = fine(pts)
    flag = "OK " if f["fail"] == 0 else "FAIL"
    if f["fail"] == 0:
        ok_any = True
    print(f" [{flag}] 巡游{L/1000:6.3f}km {np_:2d}点"
          f" (r1={r1:.0f}×{n1} + r2={r2:.1f}×{n2} ph={ph})"
          f" fail={f['fail']} 角隙={f['max_gap_deg']:.2f}°")
cur = build(950.0, 12, 1875.0, 12, 0.5)
cf = fine(cur)
print(f"\n 基准 25 点网: 巡游{tour_len(cur)/1000:.3f}km fail={cf['fail']}")
    f" 角隙={cf['max_gap_deg']:.2f}° ← 有无候选全面超越: {ok_any}")

```

B.24 scripts/_Dnet2.py

```

"""实验 D-细化: 细粒度搜索巡游更短的定向安全网 (中精度筛 + 精筛复核)。"""
import itertools
import math
import sys

sys.path.insert(0, r"G:\CUMCM B 题")

from src.coverage import directional_certificate # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

START = (0.0, 0.0)

def build(r1, n1, r2, n2, phase):
    pts = [START]
    for i in range(n1):
        a = 2 * math.pi * i / n1
        pts.append((r1 * math.cos(a), r1 * math.sin(a)))
    for i in range(n2):
        a = 2 * math.pi * (i + phase) / n2
        pts.append((r2 * math.cos(a), r2 * math.sin(a)))
    return pts

def tour_len(pts):
    t = StrategyP4._strong_tour(START, [p for p in pts if p != START],
                                rounds=10, warm=4)
    return sum(math.dist(t[i], t[i + 1]) for i in range(len(t) - 1))

def mid(pts):
    return directional_certificate(pts, n_radial=20, n_angular=180,
                                   n_boundary=1440)

def fine(pts):
    return directional_certificate(pts, n_radial=80, n_angular=720,
                                   n_boundary=7200)

cands = []
for n2, r2 in ((12, 1875.0), (12, 1890.0), (13, 1876.0), (14, 1860.0)):
    for n1 in (8, 9, 10, 11, 12):
        for r1 in (850.0, 900.0, 950.0, 1000.0):
            for phase in (0.0, 0.25, 0.5, 0.75):
                cands.append((r1, n1, r2, n2, phase))
print(f"候选 {len(cands)} 个 (中精度筛) ...")
results = []
for r1, n1, r2, n2, phase in cands:
    pts = build(r1, n1, r2, n2, phase)
    c = mid(pts)
    if c["fail"] or c["max_gap_deg"] > 178.0:
        continue
    results.append((tour_len(pts), n1 + n2 + 1, r1, n1, r2, n2, phase,
                      c["max_gap_deg"], pts))
results.sort()
print(f"中精度通过 {len(results)} 个; 按巡游升序前 8 (已用 rounds=10 强巡游): ")
print(" 巡游 km 点数 r1 n1 r2 n2 ph 角隙°")
for L, np_, r1, n1, r2, n2, ph, gap, _ in results[:8]:
    print(f" {L/1000:6.3f} {np_:4d} {r1:5.0f} {n1:3d} {r2:7.1f} {n2:3d}"
          f" {ph:4.2f} {gap:6.2f}")
print("\n 精筛复核: ")
best = None

```

```

for L, np_, r1, n1, r2, n2, ph, gap, pts in results[:8]:
    f = fine(pts)
    tag = "OK " if f["fail"] == 0 else "FAIL"
    print(f" [{tag}] {L/1000:6.3f}km {np_:2d}点 (r1={r1:.0f}x{n1} + "
          f" r2={r2:.1f}x{n2} ph={ph}) fail={f['fail']}")
          f" 角隙={f['max_gap_deg']:.2f}°")
    if f["fail"] == 0 and (best is None or L < best[0]):
        best = (L, pts, n1, r1, n2, r2, ph, f["max_gap_deg"])
cur = build(950.0, 12, 1875.0, 12, 0.5)
cf = fine(cur)
print(f"\n 基准: 巡游{tour_len(cur)/1000:.3f}km fail={cf['fail']}")
      f" 角隙={cf['max_gap_deg']:.2f}°")
if best:
    print(f"最优候选: 巡游{best[0]/1000:.3f}km 角隙{best[7]:.2f}°")
      f" (r1={best[2]:.0f}x{best[1]}, r2={best[5]:.1f}x{best[4]}, ph={best[6]})"
      f" 净省 {(tour_len(cur)-best[0])/1000:.3f} km"
      f" = {(tour_len(cur)-best[0])/5.0/16:.2f} s/源")

```

B.25 scripts/_Dtest.py

```

"""实验 D-端到端: 新候选网 (21/25 点) vs 基准 25 点网的 Mock 实测。"""
import math
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

START = (0.0, 0.0)

def build(r1, n1, r2, n2, phase, center=True):
    pts = [START] if center else []
    for i in range(n1):
        a = 2 * math.pi * i / n1
        pts.append((r1 * math.cos(a), r1 * math.sin(a)))
    for i in range(n2):
        a = 2 * math.pi * (i + phase) / n2
        pts.append((r2 * math.cos(a), r2 * math.sin(a)))
    return pts

NETS = {
    "基准 25 点(950x12+1875x12)": build(950.0, 12, 1875.0, 12, 0.5),
    "21 点(1000x8+1875x12)": build(1000.0, 8, 1875.0, 12, 0.0),
    "21 点(1000x8+1875x12,ph.5)": build(1000.0, 8, 1875.0, 12, 0.5),
    "25 点(950x10+1860x14)": build(950.0, 10, 1860.0, 14, 0.5),
}

class V(StrategyP4):
    def __init__(self, pts, **kw):
        super().__init__(survey_points=pts, **kw)

def bench(pts, ratio, n, seeds=25):
    T, M, U, A = [], [], 0, 0
    for s in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=s, directional_ratio=ratio),
                             seed=s)
        r = V(pts).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        A += len(sim.log)
        U += len(r.unresolved)
    return statistics.fmean(T), statistics.fmean(M), U, A / seeds

for label, pts in NETS.items():
    row = [f"{label:28s}"]
    for ratio, tag in ((1.0, "全定向"), (0.0, "全向")):
        for n in (16, 10):
            t, m, u, a = bench(pts, ratio, n)
            row.append(f"{tag}N{n}: {t:6.1f}/{m:5.2f}km/动作{a:4.0f}/未清{u}")
    print(" ".join(row))

```

B.26 scripts/_Dtest2.py

```
"""实验 D-最终: 多候选网 (证书 + 端到端) 综合选优."""
import math
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")
sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from src.coverage import directional_certificate # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402
from _Dtest import bench, build # noqa: E402

CANDS = [
    ("基准 950x12+1875x12", 950.0, 12, 1875.0, 12, 0.5),
    ("950x12+1860x14", 950.0, 12, 1860.0, 14, 0.5),
    ("950x12+1845x16", 950.0, 12, 1845.0, 16, 0.5),
    ("950x12+1832x18", 950.0, 12, 1832.0, 18, 0.5),
    ("950x11+1865x13", 950.0, 11, 1865.0, 13, 0.5),
    ("950x10+1860x14", 950.0, 10, 1860.0, 14, 0.5),
    ("1000x10+1875x12", 1000.0, 10, 1875.0, 12, 0.5),
]
SEEDS = 40
print(f"证书 + 巡游 + 端到端 ({SEEDS} 例/档, 3 档 x N=10/16) x ")
hdr = f"{'候选':22s} {'巡游 km':>7s} {'角隙°':>7s} {'fail':>5s}"
for r, tag in ((1.0, "全定向"), (0.5, "半定向"), (0.0, "全向")):
    for n in (10, 16):
        hdr += f" {tag[:2]}N{n:<2d}"
print(hdr)
summary = []
for label, r1, n1, r2, n2, ph in CANDS:
    pts = build(r1, n1, r2, n2, ph)
    cert = directional_certificate(pts, n_radial=80, n_angular=720,
                                  n_boundary=7200)
    tl = StrategyP4._strong_tour((0.0, 0.0), pts[1:], rounds=10, warm=4)
    L = sum(math.dist(tl[i], tl[i + 1]) for i in range(len(tl) - 1))
    line = f"{label:22s} {L/1000:7.3f} {cert['max_gap_deg']:7.2f}" \
           f" {cert['fail']:5d}"
    vals = []
    for ratio, _ in ((1.0, 0), (0.5, 0), (0.0, 0)):
        for n in (10, 16):
            t, m, u, a = bench(pts, ratio, n, seeds=SEEDS)
            line += f" {t:5.0f}"
            vals.append(t)
    summary.append((statistics.fmean(vals), label, cert["fail"]))
    print(line)
print("\n按 6 档平均排序 (越小越好): ")
for avg, label, fail in sorted(summary):
    print(f" {avg:7.2f} s/源 {label} (cert_fail={fail})")
```

B.27 scripts/_Dtest3.py

```
"""实验 D-极值: r1=1000 (中心可见性上限) 下压点数."""
import math
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")
sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from src.coverage import directional_certificate # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402
from _Dtest import bench, build # noqa: E402

CANDS = [
    ("1000x8+1875x12 (21)", 1000.0, 8, 1875.0, 12, 0.0),
    ("1000x9+1875x12 (22)", 1000.0, 9, 1875.0, 12, 0.0),
    ("1000x10+1875x12 (23)", 1000.0, 10, 1875.0, 12, 0.5),
    ("1000x11+1875x12 (24)", 1000.0, 11, 1875.0, 12, 0.5),
    ("1000x10+1860x13 (24)", 1000.0, 10, 1860.0, 13, 0.5),
    ("1000x10+1850x14 (25)", 1000.0, 10, 1850.0, 14, 0.5),
    ("1000x9+1860x14 (24)", 1000.0, 9, 1860.0, 14, 0.5),
    ("基准 950x12+1875x12", 950.0, 12, 1875.0, 12, 0.5),
]
SEEDS = 25
```

```

print(f"候选 ( {SEEDS} 例/档) ")
hdr = f"{'候选':22s} {'巡游 km':>7s} {'角隙°':>7s} {'fail':>5s}"
for tag in ("全定", "半定", "全向"):
    for n in (10, 16):
        hdr += f" {tag}N{n:<2d}"
print(hdr)
summary = []
for label, r1, n1, r2, n2, ph in CANDS:
    pts = build(r1, n1, r2, n2, ph)
    cert = directional_certificate(pts, n_radial=80, n_angular=720,
                                  n_boundary=7200)
    tl = StrategyP4._strong_tour((0.0, 0.0), pts[1:], rounds=10, warm=4)
    L = sum(math.dist(tl[i], tl[i + 1]) for i in range(len(tl) - 1))
    line = f"{label:22s} {L/1000:7.3f} {cert['max_gap_deg']:7.2f} {cert['fail']:5d}"
    vals = []
    for ratio in (1.0, 0.5, 0.0):
        for n in (10, 16):
            t, m, u, a = bench(pts, ratio, n, seeds=SEEDS)
            line += f" {t:5.0f}"
            vals.append(t)
        summary.append((statistics.fmean(vals), label, cert["fail"]))
    print(line)
print("\n按 6 档平均排序: ")
for avg, label, fail in sorted(summary):
    print(f" {avg:7.2f} s/源 {label} (cert_fail={fail})")

```

B.28 scripts/_christofides.py

"""验证: 2-opt 的 TSP 是否接近最优 (对比 Christofides 图论方法)。

若 2-opt 与 Christofides 差距很小 $\Rightarrow$ "排序损失"是信息论代价而非 TSP 次优性;
若差距大 $\Rightarrow$ 换更强的图论 TSP 求解器可回收一部分。

```

"""
import sys
import statistics
import itertools

sys.path.insert(0, r"G:\C\CUMCM B 题")

import numpy as np
from scipy.sparse.csgraph import minimum_spanning_tree
from scipy.sparse import csr_matrix

from src.coverage import seven_point_design
from src.geometry import distance
from src.mock_simulator import random_case
from src.routing import two_opt_tour, tour_length

def christofides(points):
    """Christofides 近似 TSP (图论: MST + 奇度点最小权完美匹配 + 欧拉回路 + 捷径)。"""
    pts = [tuple(p) for p in points]
    n = len(pts)
    if n < 3:
        return sum(distance(pts[i], pts[(i + 1) % n]) for i in range(n))
    D = np.array([[distance(pts[i], pts[j]) for j in range(n)] for i in range(n)])
    # MST
    mst = minimum_spanning_tree(csr_matrix(D)).toarray()
    # 奇度点
    deg = (mst > 0).sum(axis=1)
    odd = [i for i in range(n) if deg[i] % 2 == 1]
    # 贪心完美匹配 (近似最小权匹配)
    matched = [False] * n
    for i in odd:
        if matched[i]:
            continue
        j = min((k for k in odd if k != i and not matched[k]),
                key=lambda k: D[i, k])
        matched[i] = matched[j] = True
        mst[i, j] = mst[j, i] = 1.0
    # Hierholzer 欧拉回路 (多重边  $\rightarrow$  邻接列表)
    adj = {i: [] for i in range(n)}
    for i in range(n):
        for j in range(i + 1, n):
            if mst[i, j] > 0:
                adj[i].append(j)
                adj[j].append(i)

```

```

# 找欧拉回路（迭代）
stack = [0]
circuit = []
while stack:
    v = stack[-1]
    if adj[v]:
        w = adj[v].pop()
        adj[w].remove(v)
        stack.append(w)
    else:
        circuit.append(stack.pop())
# 捷径
seen = set()
order = []
for v in circuit:
    if v not in seen:
        seen.add(v)
        order.append(v)
return sum(distance(pts[order[i]], pts[order[(i + 1) % len(order)]])
           for i in range(len(order)))

for n in (10, 16):
    t2 = tc = []
    t2, tc = [], []
    for seed in range(12):
        jam = random_case(n=n, seed=seed)
        cover = list(seven_point_design(1000.0, 7))
        pts = [(0.0, 0.0)] + cover + [tuple(j.position) for j in jam]
        # 闭合 2-opt
        l2 = tour_length(two_opt_tour(pts)) + distance(pts[-1], pts[0])
        # Christofides
        lc = christofides(pts)
        t2.append(l2 / 1000)
        tc.append(lc / 1000)
    a2, ac = statistics.fmean(t2), statistics.fmean(tc)
    print(f"N={n}: 2-opt 闭合 {a2:.2f} km | Christofides {ac:.2f} km | "
          f"2-opt 超出 {(a2/ac-1)*100:.1f}%")

```

B.29 scripts/_dbg11.py

```

"""诊断: seed=2 漏清频道 11 — 它距所有 swept 点(起点+sweep+discharge) 的真实距离。"""
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

class Rec(StrategyP3):
    def __init__(self):
        super().__init__()
        self.swept_all = []
        self.discharge = []
        self.pruned = []

    def _sweep(self, transport, point, channels, bearings, cleared, result):
        n = super()._sweep(transport, point, channels, bearings, cleared, result)
        self.swept_all.append(("sweep", tuple(point)))
        return n

    def _discharge_sweep(self, transport, point, channels, bearings, cleared, result):
        n = super()._discharge_sweep(transport, point, channels, bearings, cleared, result)
        self.discharge.append(tuple(point))
        self.swept_all.append(("discharge", tuple(point)))
        return n

    def _prune_coverage(self, route, index, swept):
        before = [(p, ch, f) for p, ch, f in route if f]
        super()._prune_coverage(route, index, swept)
        after = [(p, ch, f) for p, ch, f in route if f]
        removed = [p for p, _, _ in before if p not in [q for q, _, _ in after]]
        for p in removed:
            self.pruned.append(p)

```

```

jam = random_case(seed=2)
sim = MockSimulator(jam, seed=2)
st = Rec()
res = st.run(sim)

src11 = [tuple(j.position) for j in jam if j.channel == 11][0]
print("源 11", tuple(round(v, 1) for v in src11))
print(f"\n 剪掉的环点数: {len(st.pruned)}")
for p in st.pruned:
    print(f" 剪掉 {tuple(round(v,1) for v in p)} 距源 11 {distance(p, src11):.0f} m")
print(f"\ndischarge 点数: {len(st.discharge)}")
dmin = min((distance(p, src11) for p in st.discharge), default=float("inf"))
print(f" 源 11 距最近 discharge 点 {dmin:.1f} m")
print(f"\n全部 swept 点 {len(st.swept_all)} 个, 源 11 距最近 swept 点 "
      f"{min(distance(p, src11) for _, p in st.swept_all):.1f} m")

```

B.30 scripts/_diag_legs.py

```

"""诊断: 问题 3 N=10 单例逐动作行程账本 (找出 3.07 km 超支的确切位置)。"""
from __future__ import annotations

import os
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.coverage import seven_point_design # noqa: E402
from src.geometry import distance # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.routing import tour_length, two_opt_tour # noqa: E402
from src.strategy_p3 import StrategyP3 # noqa: E402

SEED = 0
N = 10
jam = random_case(n=N, seed=SEED)
sim = MockSimulator(jam, seed=SEED)
res = StrategyP3().run(sim)

ring = seven_point_design(1000.0, 7)
ideal = tour_length(two_opt_tour([(0.0, 0.0)] + list(ring)
                                + [tuple(j.position) for j in jam]))
print(f"N={N} seed={SEED}: 实际 {res.move_distance/1000:.2f} km | "
      f"理想合并 {ideal/1000:.2f} km | 时间 {res.mean_clear_time:.1f} s/源")
print(f"检测 {res.measures} 次、清除成功 {res.clears}、失败 {res.failed_clears}\n")

# 逐动作账本: 把移动 > 50 m 的动作按"目的"归类打印
pos = (0.0, 0.0)
ring_set = {(round(p[0], 3), round(p[1], 3)) for p in ring}
src_pos = {j.channel: tuple(j.position) for j in jam}
legs = []
for e in sim.log:
    if e["path"] not in ("/measure", "/clear"):
        continue
    p = tuple(e["position"])
    d = distance(pos, p)
    if d > 50.0:
        key = (round(p[0], 3), round(p[1], 3))
        if key in ring_set:
            kind = "覆盖点(全频道扫描)"
        elif e["path"] == "/clear":
            g = src_pos.get(e["channel"])
            kind = f"清除 ch{e['channel']}(距真值{distance(p, g):.0f}m) if g else "清除"
        else:
            g = src_pos.get(e["channel"])
            kind = (f"复测 ch{e['channel']}(距真值{distance(p, g):.0f}m) if g
                  else f"探测点 ch{e['channel']}(空频道)")
        legs.append((d, kind, e.get("measure_result") or e.get("clear_result")))
    pos = p

print(f"{'行程 m':>8} {'目的':<34} 结果")
for d, kind, r in legs:
    print(f"{d:8.0f} {'kind':<34} {r}")
print(f"\n>50 m 的移动共 {len(legs)} 段、合计 {sum(d for d, _, _ in legs)/1000:.2f} km")

```

B.31 scripts/_diag_ready.py

```
"""诊断：源在"第几个覆盖点扫描后"才集齐 2 条示向度（决定能否顺路清除）。"""
from __future__ import annotations

import collections
import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.coverage import seven_point_design # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p3 import StrategyP3 # noqa: E402

RING = {(round(p[0], 3), round(p[1], 3)) for p in seven_point_design(1000.0, 7)}

for n in (10, 16):
    ready_at, late, nsrc = [], [], []
    for seed in range(12):
        jam = random_case(n=n, seed=seed)
        sim = MockSimulator(jam, seed=seed)
        StrategyP3().run(sim)
        seen = collections.Counter()
        order, ncov = [], 0
        seen_cov = set()
        for e in sim.log:
            if e["path"] != "/measure":
                continue
            key = (round(e["position"][0], 3), round(e["position"][1], 3))
            if key in RING and key not in seen_cov:
                seen_cov.add(key)
                ncov += 1
            if e["measure_result"] == "direction":
                seen[e["channel"]] += 1
                if seen[e["channel"]] == 2:
                    order.append(ncov)
        if order:
            ready_at.append(statistics.fmean(order))
            late.append(sum(1 for k in order if k >= 6) / len(order))
            nsrc.append(len(order))
    print(f"N={n}: 平均在第 {statistics.fmean(ready_at):.2f} 个覆盖点后集齐 2 条示向度；"
          f"其中 {100*statistics.fmean(late):.0f}% 的源要等到第 6 个覆盖点之后"
          f"（可交会源 {statistics.fmean(nsrc):.1f} 个）")
```

B.32 scripts/_exp_cluster.py

```
"""实验：把"首击失败"的代价降到最低（问题 3 最后的可压空间）。

**实测**：首击误差中位 14.3~16.6 m（清除半径 20 m），**无系统偏置**
（偏远占比 47.5%/53.1%），故无法靠"偏置修正"提高命中率。
清除阶段行程构成（12 例/档）：去估计点的主行程 `first` 5.38/8.23 km 是主体，
近场收口仅 0.4 km。因此**唯一可压的是"首击失败后的补救效率**"。

**变体**：
R 首击失败后立即用**极密微网格**（步长 14 m、5×5，覆盖 ±28 m）
S 首击前不动，先在**估计点 20 m 内布 4 个偏移点**依次尝试（等价于把
一次 clear 变成"小簇 clear"，每次失败只花 3 s + 极短行程）
T R + 关闭昂贵的 rayscan/shift（仅保留网格类收口）
"""
from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.geometry import distance # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p3 import StrategyP3 # noqa: E402
```

```

class V(StrategyP3):
    def __init__(self, cluster=0, step=14.0, no_ray=False, no_shift=False):
        super().__init__()
        self.cluster = int(cluster) # 首击点周围额外尝试的点数 (0=关闭)
        self.cluster_step = float(step)
        if no_ray:
            self.corridor_min_diameter = 1e9 # 实际关闭 rayscan
            self.corridor_ratio = 1e9
        if no_shift:
            self.tighten_shift = False

    def _fast_clear(self, transport, channel, estimate, records, result):
        if self.cluster:
            # 小簇清除: 估计点 + 周围 cluster 个点 (半径 cluster_step)
            # 误差中位 15 m 且无偏置 ⇒ 在 ±14~20 m 处补几个点命中率提升明显,
            # 而每次失败只付 3 s + 十几米行程 (远比走 200 m 收口便宜)。
            import math
            pts = [tuple(estimate)]
            for k in range(self.cluster):
                ang = 2.0 * math.pi * k / self.cluster
                pts.append((estimate[0] + self.cluster_step * math.cos(ang),
                           estimate[1] + self.cluster_step * math.sin(ang)))
            here = self._current_position(transport)
            pts.sort(key=lambda q: distance(here, q))
            for q in pts:
                if self._try_clear(transport, channel, q, result):
                    return True
            return super()._fast_clear(transport, channel, estimate, records, result)

def bench(n, seeds=12, **kw):
    t, mv, ms, c, ur = [], [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        res = V(**kw).run(sim)
        t.append(res.mean_clear_time)
        mv.append(res.move_distance / 1000.0)
        ms.append(res.measures)
        c.append(res.clears + res.failed_clears)
        ur += len(res.unresolved)
    return (statistics.fmean(t), statistics.fmean(mv), statistics.fmean(ms),
            statistics.fmean(c), ur)

if __name__ == "__main__":
    print("目标 176~300; 下界 272.6/235.6/205.4/184.0")
    print("格式: 时间 s / 行程 km / 检测 / clear 次数")
    for label, kw in [
        ("A 基线", {}),
        ("R 簇 4@14m", dict(cluster=4, step=14.0)),
        ("R2 簇 6@16m", dict(cluster=6, step=16.0)),
        ("R3 簇 8@18m", dict(cluster=8, step=18.0)),
        ("T 簇 6+关 ray", dict(cluster=6, step=16.0, no_ray=True)),
        ("T2 簇 6+关 ray+关 shift", dict(cluster=6, step=16.0, no_ray=True,
                                         no_shift=True)),
    ]:
        cells, bad = [], 0
        for n in (10, 12, 14, 16):
            a, b, c, d, u = bench(n, **kw)
            cells.append(f"{a:6.1f}/{b:5.2f}/{c:4.0f}/{d:5.1f}")
            bad += u
        print(f"{label:22s} " + " | ".join(cells) + f" 未清={bad}")

```

B.33 scripts/_exp_fast.py

"""实验: 问题 3 逼近理论下界的两个真实杠杆 (早清除 + 自适应观测数)。

"""理论下界** (20 例/档, 离线已知真值 + 动作下界):

N=10 272.6 s/源 | N=12 235.6 | N=14 205.4 | N=16 184.0

"""现状**: N=10 362.2 | N=12 329.9 | N=14 290.9 | N=16 244.2

归因 (10 例/档实测): N=10 共 155.8 次检测、13.00 km, 下界是 110 次、9.93 km

⇒ 检测超 45 次 (≈270 s)、行程超 3.07 km (≈614 s)。

****注意"空频道检测"不是浪费****: 频道 20 个、源 10~16 个, 有 20-N 个空频道;
要断言某频道无源, 必须在**一个完整覆盖集** (8 点) 上都测到 no_signal (覆盖判据),
故 $8 \times (20 - N)$ 次检测是**硬下界** (N=10 时 80 次), 已计入上表。

****两个真实杠杆****:

1. ****早清除****: 源在清除前, 会在后续每个覆盖点被重复检测, 越早清掉越省。
2. ****自适应观测数****: 固定 3 条示向度, 但 2 条几何足够好时第 3 条纯浪费, 还推迟了清除时机。

```

"""
from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.geometry import (
    distance, localization_region, min_enclosing_circle,
)
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

# noqa: E402
# noqa: E402
# noqa: E402

class Fast(StrategyP3):
    """可开关的提速变体 (覆盖保证不变: 8 个全频道扫描点全部走到) 。”"""

    def __init__(self, adaptive_obs=False, obs_mec_limit=60.0,
                  clear_now=False, clear_now_limit=600.0):
        super().__init__()
        self.adaptive_obs = adaptive_obs
        self.obs_mec_limit = obs_mec_limit
        self.clear_now = clear_now
        self.clear_now_limit = clear_now_limit

    def _observations_complete(self, records):
        if len(records) >= self.observations_target:
            return True
        if self.adaptive_obs and len(records) == 2:
            poly = localization_region([p for p, _ in records],
                                       [b for _, b in records])
            if poly:
                _, radius = min_enclosing_circle(poly)
                return radius <= self.obs_mec_limit
        return False

    def _schedule_sources(self, route, index, channels, bearings, cleared,
                          attempted, scheduled) -> None:
        if self.clear_now:
            # 先把"很便宜就能马上清掉"的源插到**下一站**, 尽早停止重复检测
            while True:
                here = route[index][0]
                nxt = route[index + 1][0] if index + 1 < len(route) else None
                best = None
                for ch in channels:
                    if ch in cleared or ch in attempted or ch in scheduled:
                        continue
                    if len(bearings[ch]) < self.insert_min_observations:
                        continue
                    est = self._source_target(bearings[ch])
                    if est is None:
                        continue
                    detour = distance(here, est)
                    if nxt is not None:
                        detour += distance(est, nxt) - distance(here, nxt)
                    if detour <= self.clear_now_limit and (
                        best is None or detour < best[0]):
                        best = (detour, ch, est)
                if best is None:
                    break
                _, ch, est = best
                route.insert(index + 1, (est, ch, False))
                scheduled.add(ch)
        super()._schedule_sources(route, index, channels, bearings, cleared,
                                attempted, scheduled)

```

```

def bench(n, seeds=12, **kw):
    times, moves, meas, ur = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        res = Fast(**kw).run(sim)
        times.append(res.mean_clear_time)
        moves.append(res.move_distance / 1000.0)
        meas.append(res.measures)
        ur += len(res.unresolved)
    return (statistics.fmean(times), statistics.fmean(moves),
            statistics.fmean(meas), ur)

if __name__ == "__main__":
    print("目标 176~300 s/源; 下界 N=10/12/14/16 = 272.6/235.6/205.4/184.0")
    print("格式: 时间 s / 行程 km / 检测次数")
    for label, kw in [
        ("A 基线", {}),
        ("B 自适应 obs 60m", dict(adaptive_obs=True)),
        ("C 自适应 obs 120m", dict(adaptive_obs=True, obs_mec_limit=120.0)),
        ("D 早清除 600m", dict(clear_now=True)),
        ("E B+D", dict(adaptive_obs=True, clear_now=True)),
        ("F C+早清除 1200m", dict(adaptive_obs=True, obs_mec_limit=120.0,
                                clear_now=True, clear_now_limit=1200.0)),
    ]:
        cells, bad = [], 0
        for n in (10, 12, 14, 16):
            t, mv, ms, u = bench(n, **kw)
            cells.append(f"{t:6.1f}/{mv:5.2f}/{ms:5.1f}")
            bad += u
        print(f"{label:17s} " + " | ".join(cells) + f" 未清={bad}")

```

B.34 scripts/_exp_hit.py

"""实验：提高首次清除命中率（问题3 的真正瓶颈）。

****实验瓶颈****（12 例/档）：首次清除误差中位 14.3~15.6 m、**命中率仅 62.5%/70.3%**，平均每源要 2.4~2.5 次 `/clear`。每次失败 = 3 s + 往返行程，且触发近场收口（更多行程）。
****根因****：`\_source\_target` 用“最小覆盖圆圆心”，其误差可达 `pursue_mec_limit=80 m`；而清除半径只有 20 m。

```

**变体**:
M 收紧 `pursue_mec_limit`（只在估计足够准时才前往，否则先补示向度）
N 到达估计点后**先测一次向**（拿到近距离高精度示向度）再清除
O 用**最小二乘交会**替代最小覆盖圆圆心作为清除点
P M+N
"""

from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.geometry import (
    distance, localization_region, min_enclosing_circle,
)
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import (
    StrategyP3, bearing_least_squares,
)

class V(StrategyP3):
    """可开关变体: mec 阈值 / 到点先测向 / 最小二乘估计点。"""

    def __init__(self, mec=None, premeasure=False, use_lsq=False, insert=None,
                 sliver=False, bbox=None):
        super().__init__()
        if mec is not None:
            self.pursue_mec_limit = mec
        if insert is not None:
            self.insert_limit = insert

```

```

        if bbox is not None:
            self.region_bbox = bbox
            self.insert_sliver_sources = bool(sliver)
            self.premeasure = premeasure
            self.use_lsq = use_lsq

    def _source_target(self, records, here=None):
        if self.use_lsq and len(records) >= 2:
            est = bearing_least_squares(records)
            if est is not None:
                poly = localization_region([p for p, _ in records],
                                           [b for _, b in records])
                if poly:
                    _, radius = min_enclosing_circle(poly)
                    if radius <= self.pursue_mec_limit:
                        return (float(est[0]), float(est[1]))
        return super()._source_target(records, here)

    def _fast_clear(self, transport, channel, estimate, records, result):
        if self.premeasure:
            # 先在估计点做一次测向: 近距离示向度的横向误差极小( $d \cdot \tan 1^\circ$ ),
            # 与已有示向度交会可把定位区域压到几米级, 再清除。
            resp = transport.measure(estimate, channel)
            result.measures += 1
            kind = resp.get("measure_result")
            if kind == "near":
                if self._try_clear(transport, channel, estimate, result):
                    return True
            elif kind == "direction":
                records = list(records) + [(tuple(estimate), float(resp["svd_deg"]))]
                refined = bearing_least_squares(records)
                if refined is not None and distance(refined, estimate) <= 600.0:
                    if self._try_clear(transport, channel, refined, result):
                        return True
        return super()._fast_clear(transport, channel, estimate, records, result)

def bench(n, seeds=12, **kw):
    times, moves, meas, clr, ur = [], [], [], [], 0
    hit = []
    for seed in range(seeds):
        jam = random_case(n=n, seed=seed)
        sim = MockSimulator(jam, seed=seed)
        res = V(**kw).run(sim)
        times.append(res.mean_clear_time)
        moves.append(res.move_distance / 1000.0)
        meas.append(res.measures)
        clr.append(res.clears + res.failed_clears)
        ur += len(res.unresolved)
        src = {j.channel: tuple(j.position) for j in jam}
        seen = {}
        for e in sim.log:
            if e["path"] == "/clear" and e["channel"] not in seen \
               and e["channel"] in src:
                seen[e["channel"]] = distance(tuple(e["position"]),
                                             src[e["channel"]])
            hit += [1.0 if v <= 20.0 else 0.0 for v in seen.values()]
    return (statistics.fmean(times), statistics.fmean(moves),
            statistics.fmean(meas), statistics.fmean(clr),
            100 * statistics.fmean(hit), ur)

if __name__ == "__main__":
    print("目标 176~300; 下界 272.6/235.6/205.4/184.0")
    print("格式: 时间 s / 行程 km / 检测 / clear 次数 / 首击命中%")
    for label, kw in [
        ("A 基线(拒插细长)", {}),
        ("mec=120", dict(mec=120.0)),
        ("mec=160", dict(mec=160.0)),
        ("mec=200", dict(mec=200.0)),
        ("insert=4000", dict(insert=4000.0)),
        ("mec160+insert4000", dict(mec=160.0, insert=4000.0)),
        ("mec200+insert6000", dict(mec=200.0, insert=6000.0)),
        ("细长也插(对照)", dict(sliver=True, bbox=1800.0)),
    ]:
        cells, bad = [], 0
        for n in (10, 16):
            t, mv, ms, c, h, u = bench(n, **kw)

```

```

        cells.append(f"{t:6.1f}/{mv:5.2f}/{ms:5.0f}/{c:5.1f}/{h:4.1f}%")
        bad += u
    print(f"{label:16s} " + " | ".join(cells) + f" 未清={bad}")

```

B.35 scripts/_exp_joint.py

"""实验：一次性联合规划（信息早已齐备 $\Rightarrow$ 不需要滚动插入）。

****关键实测****：所有源平均在第 ****2.04** 个**覆盖点扫描后就集齐 2 条示向度（0% 的源需要等到第 6 个覆盖点之后）。也就是说走完 2~3 个覆盖点，几乎**全部源的位置都已知**；此后的问题退化为一个**离线 TSP**：

起点 = 当前位置；必访点 = 剩余覆盖点 $\cup$ 所有已定位源估计点
 于是不该再“逐个最便宜插入 + 收尾折返”，而应**一次性联合求解**并按序执行。

变体：

K 走完 ``warmup`` 个覆盖点后，对（剩余覆盖点 $\cup$ 全部已定位源）做一次全局开放路径优化（贪心 + 2-opt + Or-opt），之后**严格按该序执行**（不再重排）。
 L 同 K，但每清除一个源后允许再做一次全局重优化（吸收新发现的源）。
 """

```

from __future__ import annotations

```

```

import os
import statistics
import sys

```

```

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

```

```

from src.config import CHANNELS, REGION_RADIUS                # noqa: E402
from src.coverage import seven_point_design                   # noqa: E402
from src.geometry import (                                     # noqa: E402
    distance, localization_region, min_enclosing_circle,
)
from src.mock_simulator import MockSimulator, random_case    # noqa: E402
from src.strategy_p3 import StrategyP3, StrategyResult        # noqa: E402

```

```

def open_tour(start, points, rounds: int = 8):
    """贪心最近邻 + 2-opt + Or-opt 的开放路径（起点固定，不回起点）。"""
    rest = list(points)
    tour = [start]
    while rest:
        nxt = min(rest, key=lambda q: distance(tour[-1], q))
        rest.remove(nxt)
        tour.append(nxt)
    if len(tour) < 4:
        return tour
    for _ in range(rounds):
        improved = False
        n = len(tour)
        for i in range(n - 2):
            for j in range(i + 2, n - 1):
                a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                if (distance(a, b) + distance(c, d)
                    > distance(a, c) + distance(b, d) + 1e-9):
                    tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                    improved = True
        for seg in (1, 2, 3):
            s = 1
            while s + seg <= len(tour) - 1:
                block = tour[s:s + seg]
                prev = tour[s - 1]
                nxt = tour[s + seg] if s + seg < len(tour) else None
                out = distance(prev, block[0])
                if nxt is not None:
                    out += distance(block[-1], nxt) - distance(prev, nxt)
                rest2 = tour[:s] + tour[s + seg:]
                best = None
                for t in range(len(rest2) - 1):
                    u, v = rest2[t], rest2[t + 1]
                    add = (distance(u, block[0]) + distance(block[-1], v)
                        - distance(u, v))
                    if best is None or add < best[0]:
                        best = (add, t + 1)
                tail = distance(rest2[-1], block[0])
                if best is None or tail < best[0]:

```

```

        best = (tail, len(rest2))
        if best[0] < out - 1e-9:
            tour = rest2[:best[1]] + block + rest2[best[1]:]
            improved = True
        else:
            s += 1
    if not improved:
        break
    return tour

```

```

class Joint(StrategyP3):
    """两阶段：短暖机（拿信息）+ 一次性联合 TSP（覆盖点与源共用一条路）。"""

    def __init__(self, warmup: int = 3, requick: bool = False,
                  plan_mec_limit: float = 300.0):
        super().__init__()
        self.warmup = int(warmup)
        self.requick = bool(requick)
        self.plan_mec_limit = float(plan_mec_limit)

    def _plan_target(self, records):
        """联合规划用的目标点：**必须有界可信**，否则不纳入本轮 TSP。

        `_source_target` 在“两条示向度近共线”时会返回**细长无界区域的形心**，
        它可能落在几千米之外（实测导致联合规划出现 6350 km 的荒谬行程）。
        这里只接受“最小覆盖圆半径  $\leq$  plan_mec_limit 且落在目标区域内”的估计，
        其余源留给后续覆盖点补足示向度（或收尾处理）。
        """
        if len(records) < 2:
            return None
        poly = localization_region([p for p, _ in records],
                                   [b for _, b in records])
        if not poly:
            return None
        center, radius = min_enclosing_circle(poly)
        if radius > self.plan_mec_limit:
            return None
        if distance((0.0, 0.0), center) > REGION_RADIUS + 50.0:
            return None
        return (float(center[0]), float(center[1]))

    def run(self, transport, channel_order=None, do_enter=True):
        result = StrategyResult()
        if do_enter:
            transport.enter()
            channels = list(channel_order) if channel_order else list(CHANNELS)
            bearings = {ch: [] for ch in channels}
            cleared: set = set()
            attempted: set = set()

            origin = self._current_position(transport)
            ring = list(seven_point_design(self.cover_ring_radius, 7))
            # --- 阶段1 暖机：按最近邻走前 warmup 个覆盖点，快速积累示向度 ---
            self._sweep(transport, origin, channels, bearings, cleared, result)
            pending_cov = list(ring)
            for _ in range(min(self.warmup, len(ring))):
                here = self._current_position(transport)
                nxt = min(pending_cov, key=lambda q: distance(here, q))
                pending_cov.remove(nxt)
                self._sweep(transport, nxt, channels, bearings, cleared, result)

            # --- 阶段2 联合规划：剩余覆盖点 U 所有已定位源，一次性求最短开放路径 ---
            while True:
                here = self._current_position(transport)
                targets = {}
                for ch in channels:
                    if ch in cleared or ch in attempted:
                        continue
                    if len(bearings[ch]) < self.insert_min_observations:
                        continue
                    est = self._plan_target(bearings[ch])
                    if est is not None:
                        targets[tuple(est)] = ch
                nodes = list(pending_cov) + list(targets.keys())
                if not nodes:
                    break

```

```

plan = open_tour(here, nodes)[1:]
for point in plan:
    if point in targets:
        ch = targets[point]
        if ch in cleared or ch in attempted:
            continue
        attempted.add(ch)
        if self._fast_clear(transport, ch, point, bearings[ch], result):
            cleared.add(ch)
    else:
        if point not in pending_cov:
            continue
        pending_cov.remove(point)
        got = self._sweep(transport, point, channels, bearings,
                          cleared, result)
        # 发现了新的可定位源 ⇒ 打断当前计划, 重做联合规划
        if self.requick and got:
            fresh = any(ch not in cleared and ch not in attempted
                        and self._plan_target(bearings[ch]) is not None
                        and tuple(self._plan_target(bearings[ch]))
                        not in targets
                        for ch in channels)
            if fresh:
                break
        else:
            continue
    if not self.requick:
        break

self._finalize_channel_clearing(transport, channels, bearings, cleared, result)
transport.exit()
result.cleared = len(cleared)
result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

def bench(cls, n, seeds=12, **kw):
    times, moves, meas, ur = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        res = cls(**kw).run(sim)
        times.append(res.mean_clear_time)
        moves.append(res.move_distance / 1000.0)
        meas.append(res.measures)
        ur += len(res.unresolved)
    return (statistics.fmean(times), statistics.fmean(moves),
            statistics.fmean(meas), ur)

if __name__ == "__main__":
    print("目标 176~300: 下界 272.6/235.6/205.4/184.0 (N=10/12/14/16) ")
    for label, cls, kw in [
        ("A 基线", StrategyP3, {}),
        ("K 暖机 2+联合", Joint, dict(warmup=2)),
        ("K 暖机 3+联合", Joint, dict(warmup=3)),
        ("K 暖机 4+联合", Joint, dict(warmup=4)),
        ("L 暖机 3+联合+重规划", Joint, dict(warmup=3, requick=True)),
    ]:
        cells, bad = [], 0
        for n in (10, 12, 14, 16):
            t, mv, ms, u = bench(cls, n, **kw)
            cells.append(f"{t:6.1f}/{mv:5.2f}/{ms:5.0f}")
            bad += u
        print(f"{label:20s} " + " | ".join(cells) + f" 未清={bad}")

```

B.36 scripts/_exp_oracle.py

""" 上界检验: **真值已知** (作弊) 时能做到多少 s/源?

用途: 区分"策略不够好"与"下界本身不可达"。

Oracle-A: 直接走 (原点 → 所有真源) 的最优 TSP, 每源一次成功 clear,
 完全不做覆盖扫描 (不合法, 但给出绝对下界)

Oracle-B: 覆盖扫描 + 真值清除 (合法所需的扫描 + 完美清除),
 即"策略层完美"时的极限

"""

```

from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.config import CHANNELS # noqa: E402
from src.coverage import seven_point_design # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.routing import tour_length, two_opt_tour # noqa: E402

def oracle(n, seed, with_cover=True):
    """按真值执行：覆盖扫描（可选）+ 每源一次 clear。返回虚拟总时间。"""
    jam = random_case(n=n, seed=seed)
    sim = MockSimulator(jam, seed=seed)
    sim.enter()
    ring = list(seven_point_design(1000.0, 7)) if with_cover else []
    src = [(tuple(j.position), j.channel) for j in jam]
    nodes = list(ring) + [p for p, _ in src]
    order = two_opt_tour([(0.0, 0.0)] + nodes)[1:]
    ch_of = {p: c for p, c in src}
    pending = set(CHANNELS)
    for p in order:
        if p in ch_of:
            sim.clear(p, ch_of[p])
        else:
            for ch in sorted(pending):
                r = sim.measure(p, ch)
                if r["measure_result"] == "no_signal":
                    pass
            pending.remove(ch)
    sim.exit()
    return sim.clock.virtual_time, sim.cleared_jammers, len(jam)

if __name__ == "__main__":
    print("Oracle（真值已知）上界检验：")
    for with_cover in (False, True):
        tag = "含覆盖扫描" if with_cover else "仅清除(不合法)"
        cells = []
        for n in (10, 12, 14, 16):
            per = []
            for seed in range(12):
                t, c, tot = oracle(n, seed, with_cover)
                per.append(t / max(c, 1))
            cells.append(f"N={n}:{statistics.fmean(per):6.1f}s")
        print(f" {tag:16s} " + " | ".join(cells))

```

B.37 scripts/_exp_replan.py

"""实验：问题3「滚动重优化（receding-horizon）」新模型 vs 现方案。

思路：把问题看成**带强制点的在线 TSP**—

强制点 = 尚未到访的覆盖扫描点（保证不漏测，必须全部走到）

动态点 = 已定位但未清除的源（发现后才出现）

每走完一步，用“贪心最近邻 + 2-opt + 0r-opt”对（当前位置 ∪ 剩余强制点 ∪ 待清源）

从头重解一条开放路径，只提交第一站（滚动时域）。

比“最便宜插入”更接近理想合并巡游：插入法一旦把源放错段就无法整体重排。

"""

```

from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.coverage import seven_point_design # noqa: E402
from src.geometry import ( # noqa: E402
    distance, localization_region, min_enclosing_circle,
)
from src.mock_simulator import MockSimulator, random_case # noqa: E402

```

```
from src.strategy_p3 import CHANNELS, StrategyP3, StrategyResult # noqa: E402
```

```
def open_tour(start, points, rounds: int = 6):
    """贪心最近邻 + 2-opt + Or-opt 的开放路径（固定起点，不回到起点）。"""
    remaining = list(points)
    tour = [start]
    while remaining:
        nxt = min(remaining, key=lambda q: distance(tour[-1], q))
        remaining.remove(nxt)
        tour.append(nxt)
    if len(tour) < 4:
        return tour
    for _ in range(rounds):
        improved = False
        n = len(tour)
        for i in range(n - 2):
            for j in range(i + 2, n - 1):
                a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                if (distance(a, b) + distance(c, d)
                    > distance(a, c) + distance(b, d) + 1e-9):
                    tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                    improved = True
        for seg in (1, 2, 3):
            for s in range(1, len(tour) - seg):
                block = tour[s:s + seg]
                prev = tour[s - 1]
                nxt = tour[s + seg] if s + seg < len(tour) else None
                out = distance(prev, block[0])
                if nxt is not None:
                    out += distance(block[-1], nxt) - distance(prev, nxt)
                rest = tour[:s] + tour[s + seg:]
                best = None
                for t in range(len(rest) - 1):
                    u, v = rest[t], rest[t + 1]
                    add = (distance(u, block[0]) + distance(block[-1], v)
                        - distance(u, v))
                    if best is None or add < best[0]:
                        best = (add, t + 1)
                tail = distance(rest[-1], block[0])
                if best is None or tail < best[0]:
                    best = (tail, len(rest))
                if best[0] < out - 1e-9:
                    tour = rest[:best[1]] + block + rest[best[1]:]
                    improved = True
        if not improved:
            break
    return tour
```

```
class StrategyReplan(StrategyP3):
    """滚动重优化版问题 3 策略（覆盖保证与 StrategyP3 完全一致：7 均布环全走到）。"""

    def __init__(self, adaptive_obs: bool = True, obs_mec_limit: float = 45.0):
        super().__init__()
        self.adaptive_obs = adaptive_obs
        self.obs_mec_limit = obs_mec_limit

    def _observations_complete(self, records):
        """自适应观测目标：2 条示向度已把定位区域压得足够小就不必要第 3 条。

        原实现固定要 3 条（省下长尾误差），但当两条示向度**视差已经很好**时，
        第 3 条纯属浪费（一次检测 6 s，且会推迟“顺路插入”的时机）。
        """
        if len(records) >= self.observations_target:
            return True
        if self.adaptive_obs and len(records) == 2:
            poly = localization_region([p for p, _ in records],
                                       [b for _, b in records])
            if poly:
                _, radius = min_enclosing_circle(poly)
                return radius <= self.obs_mec_limit
        return False

    def run(self, transport, channel_order=None, do_enter=True):
        result = StrategyResult()
        if do_enter:
            transport.enter()
```

```

channels = list(channel_order) if channel_order else list(CHANNELS)
bearings = {ch: [] for ch in channels}
cleared: set = set()
attempted: set = set()

origin = self._current_position(transport)
# 覆盖保证: 半径 1000 m 的 7 均布环 (解析最坏 998.25 m < R_min)
mandatory = list(seven_point_design(self.cover_ring_radius, 7))

self._sweep(transport, origin, channels, bearings, cleared, result)

while len(cleared) < self.max_jammers:
    here = self._current_position(transport)
    targets = {}
    for ch in channels:
        if ch in cleared or ch in attempted:
            continue
        if len(bearings[ch]) < self.insert_min_observations:
            continue
        est = self._source_target(bearings[ch])
        if est is not None:
            targets[tuple(est)] = ch
    nodes = list(mandatory) + list(targets.keys())
    if not nodes:
        break
    nxt = open_tour(here, nodes)[1]
    if nxt in targets:
        # 下一站是源: 清除
        ch = targets[nxt]
        attempted.add(ch)
        if self._fast_clear(transport, ch, nxt, bearings[ch], result):
            cleared.add(ch)
    else:
        # 下一站是覆盖点: 全频道扫描
        mandatory = [p for p in mandatory if p != nxt]
        self._sweep(transport, nxt, channels, bearings, cleared, result)

self._finalize_channel_clearing(transport, channels, bearings, cleared, result)
transport.exit()
result.cleared = len(cleared)
result.total = self._evaluate_total(transport)
result.virtual_time = self._virtual_time(transport)
result.move_distance = self._move_distance(transport)
return result

def bench(cls, n, seeds=12, **kw):
    times, moves, meas, ur = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        res = cls(**kw).run(sim)
        times.append(res.mean_clear_time)
        moves.append(res.move_distance / 1000.0)
        meas.append(res.measures)
        ur += len(res.unresolved)
    return (statistics.fmean(times), statistics.fmean(moves),
            statistics.fmean(meas), ur)

if __name__ == "__main__":
    for label, cls, kw in (
        ("现方案 StrategyP3", StrategyP3, {}),
        ("滚动重优化+obs 自适应", StrategyReplan, {}),
        ("滚动重优化+obs 固定 3", StrategyReplan, dict(adaptive_obs=False)),
    ):
        cells, bad = [], 0
        for n in (10, 12, 14, 16):
            t, mv, ms, u = bench(cls, n, **kw)
            cells.append(f"N={n}: {t:6.1f}s / {mv:5.2f}km / {ms:5.1f}")
            bad += u
        print(f"{label:22s} " + " ".join(cells) + f" 未清={bad}")

```

B.38 scripts/_exp_tail.py

"""实验: 消除"收尾折返"— 问题 3 的真正瓶颈。

**账本 (12 例/档) **:

N=10: 主阶段 8.77 km + **收尾折返 4.23 km** ($\approx 846 \text{ s} \approx 85 \text{ s/源}$), 清除失败 14.7 次
 N=16: 主阶段 11.49 km + **收尾折返 3.34 km**, 清除失败 21.7 次

收尾折返之所以贵：这些源要么只有 1 条示向度（`insert\_min\_observations=2` 不给排程）、要么估计质量差被 `pursue\_mec\_limit=80 m` 挡住，于是全部堆到最后，形成一趟额外 TSP。

```

**变体**:
G 放宽 `pursue_mec_limit`（允许带较差估计前往，就地用 1-D 射线扫描收口）
H 允许**单条示向度**排程（`insert_min_observations=1`，用切向复测点定位）
I G+H
J I + 在最后一个覆盖点前**强制清空**所有已发现频道（禁止留到收尾）
"""
from __future__ import annotations

import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.mock_simulator import MockSimulator, random_case          # noqa: E402
from src.strategy_p3 import StrategyP3                             # noqa: E402

class V(StrategyP3):
    def __init__(self, mec=None, min_obs=None, insert=None):
        super().__init__()
        if mec is not None:
            self.pursue_mec_limit = mec
        if min_obs is not None:
            self.insert_min_observations = min_obs
        if insert is not None:
            self.insert_limit = insert

def bench(n, seeds=12, **kw):
    times, moves, meas, ur, fail = [], [], [], 0, []
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        res = V(**kw).run(sim)
        times.append(res.mean_clear_time)
        moves.append(res.move_distance / 1000.0)
        meas.append(res.measures)
        fail.append(res.failed_clears)
        ur += len(res.unresolved)
    return (statistics.fmean(times), statistics.fmean(moves),
            statistics.fmean(meas), statistics.fmean(fail), ur)

if __name__ == "__main__":
    print("目标 176~300; 下界 272.6/235.6/205.4/184.0 (N=10/12/14/16)")
    print("格式: 时间 s / 行程 km / 检测 / 清除失败")
    for label, kw in [
        ("A 基线", {}),
        ("G mec=200", dict(mec=200.0)),
        ("G2 mec=400", dict(mec=400.0)),
        ("H min_obs=1", dict(min_obs=1)),
        ("I mec=400+obs1", dict(mec=400.0, min_obs=1)),
        ("I2 mec=1e9+obs1", dict(mec=1e9, min_obs=1)),
        ("J I2+insert=1e9", dict(mec=1e9, min_obs=1, insert=1e9)),
    ]:
        cells, bad = [], 0
        for n in (10, 12, 14, 16):
            t, mv, ms, f, u = bench(n, **kw)
            cells.append(f"{t:6.1f}/{mv:5.2f}/{ms:5.0f}/{f:4.1f}")
            bad += u
        print(f"{label:17s} " + " | ".join(cells) + f" 未清={bad}")

```

B.39 scripts/_exp_tradeoff.py

"""关键分析：176~300 s/源 的区间意味着什么？

****Oracle 上界检验****（真值已知、完美清除、零浪费；12 例/档）：

仅清除（**不做覆盖扫描**，不合法）： N=10 161.3 | N=12 141.3 | N=14 140.5 | N=16 129.2
 含完整覆盖扫描（合法所需）： N=10 300.8 | N=12 265.1 | N=14 233.1 | N=16 208.4

结论：****"完整覆盖扫描"这一项就占了 140~170 s/源****（N=10 时 300.8-161.3 = 139.5 s）。

因此若某方案在 $N=10$ 也能做到 ~ 176 s/源, 它**必然没有做完整的覆盖扫描** (也就无法保证“不漏测”), 或者它使用了不同的统计口径。

本脚本用于量化“少扫多少覆盖点 $\Rightarrow$ 快多少 / 漏检概率多大”, 给出**可选的快速模式**。
漏检概率用蒙特卡洛估计: 随机源位置落在“未被任何扫描点 1000 m 圆覆盖”的区域内即漏检。

```

"""
from __future__ import annotations

import math
import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

import numpy as np # noqa: E402

from src.config import CHANNELS, REGION_RADIUS, R_MIN # noqa: E402
from src.coverage import seven_point_design # noqa: E402
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.routing import two_opt_tour # noqa: E402

def miss_probability(points, samples=200000, seed=0):
    """单个源的漏检概率 (**用真实 r_eff 分布**, 而非保守的 R_MIN)。


题给  $r_{\text{eff}} \in [1000, 1500]$  均匀分布; 源被发现  $\Leftrightarrow$  存在扫描点  $p$  使  $\text{dist}(p, G) \leq r_{\text{eff}}$ 。用  $R_{\text{MIN}}=1000$  保守判定会**高估**漏检率  
(例如完整 8 点覆盖集的保守值是 3.59%, 而真实值为 0: 因为覆盖集的最坏覆盖距离  $998.25 \text{ m} < 1000 \text{ m} \leq r_{\text{eff}}$ )。


    """
    rng = np.random.default_rng(seed)
    r = REGION_RADIUS * np.sqrt(rng.random(samples))
    th = rng.random(samples) * 2 * math.pi
    gx, gy = r * np.cos(th), r * np.sin(th)
    reff = 1000.0 + 500.0 * rng.random(samples) # r_eff ~ U[1000,1500]
    best = np.full(samples, np.inf)
    for px, py in points:
        best = np.minimum(best, np.hypot(gx - px, gy - py))
    return float((best > reff).mean())

def run_partial(n, seed, keep):
    """只访问 keep 个覆盖点 (其余跳过) 的 Oracle 时间 (真值清除)。”””
    jam = random_case(n=n, seed=seed)
    sim = MockSimulator(jam, seed=seed)
    sim.enter()
    ring = list(seven_point_design(1000.0, 7))
    cover = [(0.0, 0.0)] + ring
    cover = cover[:keep]
    src = {tuple(j.position): j.channel for j in jam}
    order = two_opt_tour([(0.0, 0.0)] + cover[1:] + list(src.keys()))[1:]
    for p in order:
        if p in src:
            sim.clear(p, src[p])
        else:
            for ch in CHANNELS:
                sim.measure(p, ch)
    sim.exit()
    return sim.clock.virtual_time / max(sim.cleared_jammers, 1)

if __name__ == "__main__":
    ring = list(seven_point_design(1000.0, 7))
    print("覆盖点数  $\rightarrow$  单源漏检概率 / Oracle 时间 (真值已知, 12 例/档)")
    for keep in (8, 7, 6, 5, 4, 3, 2, 1):
        pts = [(0.0, 0.0)] + ring[:keep]
        p_miss = miss_probability(pts)
        cells = []
        for n in (10, 12, 14, 16):
            per = [run_partial(n, s, keep) for s in range(12)]
            cells.append(f"N={n}:{statistics.fmean(per):6.1f}s")
        exp_miss = 1.0 - (1.0 - p_miss) ** 13 # 13 = 平均源数
        print(f" {keep:2d} 点 漏检/源 {100*p_miss:5.2f}% 整例至少漏 1 个 "
              f"{100*exp_miss:5.1f}% " + " | ".join(cells))

```

B.40 scripts/_gap2.py

```
"""精确 gap 分析: 实际行程 vs 同点集最优开放巡游 vs 理想点集最优开放巡游。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import seven_point_design
from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3
from src.routing import tour_length

def open_tour_len(start, points, rounds=15):
    """开放巡游长度 (最近邻 + 2-opt + Or-opt, 多起点取最短)。"""
    best = None
    for s in [start] + list(points)[:0] + [None]:
        tour = [start]
        rest = list(points)
        while rest:
            nxt = min(rest, key=lambda q: distance(tour[-1], q))
            rest.remove(nxt)
            tour.append(nxt)
        n = len(tour)
        for _ in range(rounds):
            imp = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                    if distance(a, b) + distance(c, d) > distance(a, c) + distance(b, d) + 1e-9:
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        imp = True
            for seg in (1, 2, 3):
                s2 = 1
                while s2 + seg < len(tour):
                    blk = tour[s2:s2 + seg]
                    prev = tour[s2 - 1]
                    nxt = tour[s2 + seg] if s2 + seg < len(tour) else None
                    out = distance(prev, blk[0])
                    if nxt is not None:
                        out += distance(blk[-1], nxt) - distance(prev, nxt)
                    rest2 = tour[:s2] + tour[s2 + seg:]
                    best2 = None
                    for t in range(len(rest2) - 1):
                        u, v = rest2[t], rest2[t + 1]
                        add = distance(u, blk[0]) + distance(blk[-1], v) - distance(u, v)
                        if best2 is None or add < best2[0]:
                            best2 = (add, t + 1)
                    tail = distance(rest2[-1], blk[0])
                    if best2 is None or tail < best2[0]:
                        best2 = (tail, len(rest2))
                    if best2[0] < out - 1e-9:
                        tour = rest2[:best2[1]] + blk + rest2[best2[1]:]
                        imp = True
                    else:
                        s2 += 1
            if not imp:
                break
        L = sum(distance(tour[i], tour[i + 1]) for i in range(n - 1))
        if best is None or L < best:
            best = L
    return best

for n in (10, 16):
    actual, same, ideal = [], [], []
    for seed in range(8):
        jam = random_case(n=n, seed=seed)
        sim = MockSimulator(jam, seed=seed)
        st = StrategyP3()
        res = st.run(sim)
        actual.append(res.move_distance / 1000)
    # 同点集: 收集到访点 (从日志)
    pts = set()
    for e in sim.log:
        if e["path"] in ("/measure", "/clear"):
```

```

        pts.add((round(e["position"][0], 1), round(e["position"][1], 1)))
    same.append(open_tour_len((0.0, 0.0), list(pts)) / 1000)
    # 理想点集: 8 覆盖点 + 真源
    cover = list(seven_point_design(1000.0, 7))
    ideal.append(open_tour_len((0.0, 0.0),
                              cover + [tuple(j.position) for j in jam]) / 1000)
    a, s, i = (statistics.fmean(x) for x in (actual, same, ideal))
    print(f"N={n}: 实际 {a:5.2f} km | 同点集最优 {s:5.2f} km | 理想点集最优 {i:5.2f} km")
    print(f"    排序损失 {a-s:5.2f} km ({(a-s)*1000/5:.0f} s) | 点集损失 {s-i:5.2f} km ({(s-
i)*1000/5:.0f} s)")

```

B.41 scripts/_ledger.py

```

"""精确行程账本: 把问题 3 总行程拆到"骨干/复测/源访问/近场收口/收尾"五类。"""
import collections
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import seven_point_design
from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

def ledger(n, seed):
    jam = random_case(n=n, seed=seed)
    sim = MockSimulator(jam, seed=seed)
    src = {j.channel: tuple(j.position) for j in jam}
    ring = seven_point_design(1000.0, 7)
    sweep_pts = {(round(p[0], 1), round(p[1], 1)) for p in ring}
    st = StrategyP3()
    res = st.run(sim)

    acc = collections.Counter()
    pos = (0.0, 0.0)
    last_kind = "other"
    for e in sim.log:
        if e["path"] not in ("/measure", "/clear"):
            continue
        p = tuple(e["position"])
        d = distance(pos, p)
        key = (round(p[0], 1), round(p[1], 1))
        if key in sweep_pts:
            kind = "cover" # 到覆盖扫描点
        elif e["path"] == "/measure" and e.get("channel") in src:
            kind = "src_meas" # 到源附近的复测
        elif e["path"] == "/clear" and e.get("channel") in src:
            g = src[e["channel"]]
            if distance(p, g) <= 20:
                kind = "src_hit" # 到真源(命中)
            else:
                kind = "src_miss" # 到估计点(未命中)
        else:
            kind = "other"
        acc[kind] += d
        pos = p
    return acc, res

def main():
    for n in (10, 16):
        A = collections.Counter()
        T, M, Me, C, U = [], [], [], [], 0
        for seed in range(20):
            acc, res = ledger(n, seed)
            A.update(acc)
            T.append(res.mean_clear_time)
            M.append(res.move_distance / 1000)
            Me.append(res.measures)
            C.append(res.clears + res.failed_clears)
            U += len(res.unresolved)
        tot = sum(A.values()) / 20 / 1000
        print(f"N={n}: {statistics.fmean(T):6.1f} s/源 总行程 {tot:5.2f} km")
        for k in ("cover", "src_hit", "src_miss", "src_meas", "other"):
            v = A[k] / 20 / 1000
            print(f"    {k:10s} {v:5.2f} km")

```

```

        print(f"    检测 {statistics.fmean(Me):5.1f} 次 清除动作 {statistics.fmean(C):5.1f} 未清
{U}")

```

```

main()

```

B.42 scripts/_obs.py

"""组合杠杆：观测数 / 追击兜底 对 N=10/16 的影响（当前追击代码已就位）。"""

```

import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import localization_region, min_enclosing_circle
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

class V(StrategyP3):
    def __init__(self, obs=None, adapt=None, mec=None):
        super().__init__()
        if obs is not None:
            self.observations_target = obs
        self.adapt = adapt
        if mec is not None:
            self.pursue_mec_limit = mec

    def _observations_complete(self, records):
        if len(records) >= self.observations_target:
            return True
        if self.adapt and len(records) == 2:
            poly = localization_region([p for p, _ in records],
                                       [b for _, b in records])
            if poly:
                _, r = min_enclosing_circle(poly)
                if r <= self.adapt:
                    return True
        return False

def bench(n, seeds=20, **kw):
    T, M, Me, C, U = [], [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        C.append(r.clears + r.failed_clears)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me),
            statistics.fmean(C), U)

for label, kw in [
    ("基线 obs=3", {}),
    ("obs=2", dict(obs=2)),
    ("obs=2+adapt40", dict(obs=2, adapt=40.0)),
    ("obs=3+adapt60", dict(adapt=60.0)),
    ("obs=3+adapt120", dict(adapt=120.0)),
]:
    cells, bad = [], 0
    for n in (10, 16):
        t, m, me, c, u = bench(n, **kw)
        cells.append(f"N{n}:{t:6.1f}/{m:5.2f}/{me:5.0f}/{c:5.1f}")
        bad += u
    print(f"{label:16s} " + " | ".join(cells) + f" 未清={bad}")

```

B.43 scripts/_oracle2.py

"""精确下界：完美 Oracle（最优开巡游 + 最少检测 + 100% 命中）。

与之前“含覆盖扫描”Oracle 的区别：只测“尚未决定”的频道（已清/已定位就跳过），即真实的最少检测策略：巡游用“最近邻 + 2-opt + Or-opt”的开放路径（起点原点）。"""

```

import statistics

```

```

import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.config import CHANNELS, REGION_RADIUS, R_MIN, R_MAX
from src.coverage import seven_point_design
from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.routing import two_opt_tour

def open_tour(start, points, rounds=12):
    """最近邻 + 2-opt + Or-opt 开放路径。"""
    tour = [start]
    rest = list(points)
    while rest:
        nxt = min(rest, key=lambda q: distance(tour[-1], q))
        rest.remove(nxt)
        tour.append(nxt)
    n = len(tour)
    if n >= 4:
        for _ in range(rounds):
            imp = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                    if distance(a, b) + distance(c, d) > distance(a, c) + distance(b, d) + 1e-9:
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        imp = True
            for seg in (1, 2, 3):
                s = 1
                while s + seg < len(tour):
                    blk = tour[s:s + seg]
                    prev = tour[s - 1]
                    nxt = tour[s + seg] if s + seg < len(tour) else None
                    out = distance(prev, blk[0])
                    if nxt is not None:
                        out += distance(blk[-1], nxt) - distance(prev, nxt)
                    rest2 = tour[:s] + tour[s + seg:]
                    best = None
                    for t in range(len(rest2) - 1):
                        u, v = rest2[t], rest2[t + 1]
                        add = distance(u, blk[0]) + distance(blk[-1], v) - distance(u, v)
                        if best is None or add < best[0]:
                            best = (add, t + 1)
                    tail = distance(rest2[-1], blk[0])
                    if best is None or tail < best[0]:
                        best = (tail, len(rest2))
                    if best[0] < out - 1e-9:
                        tour = rest2[:best[1]] + blk + rest2[best[1]:]
                        imp = True
                    else:
                        s += 1
                if not imp:
                    break
            return tour[1:]

def oracle(n, seed):
    jam = random_case(n=n, seed=seed)
    sim = MockSimulator(jam, seed=seed)
    sim.enter()
    cover = list(seven_point_design(1000.0, 7)) # center + 7 ring = 8 点
    src = {tuple(j.position): j.channel for j in jam}
    ch_of = {c: p for p, c in src.items()}
    order = open_tour((0.0, 0.0), cover + list(src.keys()))
    # 每个频道需要的"已定位"示向度条数: 完美 Oracle 假设访问到源即 100% 命中,
    # 因此只需"在覆盖点上每频道测到它为止"; 空频道测满 8 个覆盖点。
    swept = 0 # 已访问覆盖点数
    for p in order:
        if p in ch_of:
            sim.clear(p, ch_of[p]) # 完美命中, 1 次成功清除
        else:
            # 覆盖点: 全频道扫描 (只测未决频道)
            swept += 1
            # 完美 Oracle: 每个频道只测到"已发现"为止。空频道仍要测满 8 点。
            for ch in CHANNELS:
                if ch in ch_of:

```

```

        g = ch_of[ch]
        if distance(p, g) <= sim.jammers_by_channel.get(ch) or True:
            # 已被覆盖点发现过就跳过（完美 Oracle 已知真值）
            pass
        else:
            pass
    sim.exit()
    return sim.clock.virtual_time, sim.cleared_jammers, len(jam)

# 简化：直接按"最小检测数"估算 — 空频道 8 点、源 2 次测向 + 1 次清除
def oracle_simple(n, seed):
    jam = random_case(n=n, seed=seed)
    sim = MockSimulator(jam, seed=seed)
    sim.enter()
    cover = list(seven_point_design(1000.0, 7))
    src = {tuple(j.position): j.channel for j in jam}
    order = open_tour((0.0, 0.0), cover + list(src.keys()))
    for p in order:
        if p in src:
            sim.clear(p, src[p])
        else:
            # 覆盖点扫描：只测真正需要测的（模拟最少检测，这里直接跳过 measure，
            # 用真实动作成本近似：空频道 4×(8 点)=32 次 + 源 16×2=32 次）
            pass
    # 手动加检测成本：空频道 = (20-n)*8 次检测；源 = n*2 次检测（用时钟推进）
    n = len(jam)
    for _ in range((20 - n) * 8 + n * 2):
        sim.clock.measure(sim.clock.position, 1) # 占用 6s（近似）
    sim.exit()
    return sim.clock.virtual_time, sim.cleared_jammers, n

if __name__ == "__main__":
    for n in (10, 12, 14, 16):
        per = []
        for seed in range(20):
            t, c, tot = oracle_simple(n, seed)
            per.append(t / max(c, 1))
        print(f"N={n}: 精确下界 ≈ {statistics.fmean(per):6.1f} s/源")

```

B.44 scripts/_oracle_p4.py

"""Oracle: 问题 4"清源路径反哺覆盖"的理论可回收里程。

思路（用户提出）：25 点双环只是"定向安全覆盖"的**充分条件**；真正必需的只是"实际 measure 点集构成合法定向覆盖证书"。而"走到源清除"的路径本身也是 measure 点（清除点做 discharge 即成为合法覆盖点）。于是：
 基线 = 25 点定向安全网巡游 + 收尾清源 TSP（两段）
 Oracle = TSP 过「16 个源位置（清除必走）+ 贪心补洞点（凑够定向安全证书）」
 可回收里程 = 基线 - Oracle。若平均 > 0.7 km/源 ⇒ 该方向值得重兵投入。

注意：源位置用**真值**（离线 Oracle，只用于估计上限，不用于正式策略）。
 """

```

import math
import statistics
import sys

```

```

sys.path.insert(0, r"G:\C\CUMCM B 题")

```

```

from src.coverage import directional_certificate, directional_survey_design
from src.geometry import distance
from src.mock_simulator import random_case

```

```

def open_tour_len(start, points, rounds=8, warm_starts=3):
    """开放巡游长度（最近邻 + 2-opt + 0r-opt，多次起点取最短）。"""
    pts = list(points)
    if not pts:
        return 0.0
    best = None
    for k in range(warm_starts):
        head = pts[k]
        rest = pts[:k] + pts[k + 1:]
        tour = [start, head]
        pool = list(rest)
        while pool:

```

```

        nxt = min(pool, key=lambda q: distance(tour[-1], q))
        pool.remove(nxt)
        tour.append(nxt)
    n = len(tour)
    for _ in range(rounds):
        imp = False
        for i in range(n - 2):
            for j in range(i + 2, n - 1):
                a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                if (distance(a, b) + distance(c, d)
                    > distance(a, c) + distance(b, d) + 1e-9):
                    tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                    imp = True
        for seg in (1, 2, 3):
            s = 1
            while s + seg < len(tour):
                blk = tour[s:s + seg]
                prev = tour[s - 1]
                nxt = tour[s + seg] if s + seg < len(tour) else None
                out = distance(prev, blk[0])
                if nxt is not None:
                    out += distance(blk[-1], nxt) - distance(prev, nxt)
                rest2 = tour[s:] + tour[s + seg:]
                b2 = None
                for t in range(len(rest2) - 1):
                    u, v = rest2[t], rest2[t + 1]
                    add = (distance(u, blk[0]) + distance(blk[-1], v)
                        - distance(u, v))
                    if b2 is None or add < b2[0]:
                        b2 = (add, t + 1)
                tail = distance(rest2[-1], blk[0])
                if b2 is None or tail < b2[0]:
                    b2 = (tail, len(rest2))
                if b2[0] < out - 1e-9:
                    tour = rest2[:b2[1]] + blk + rest2[b2[1]:]
                    imp = True
                else:
                    s += 1
            if not imp:
                break
        L = sum(distance(tour[i], tour[i + 1]) for i in range(len(tour) - 1))
        if best is None or L < best:
            best = L
    return best

def cover_candidates():
    """候选补洞点: 外环(1875, 每 10°) + 内环(950, 每 30°) + 中心。"""
    out = [(0.0, 0.0)]
    out += [(1875.0 * math.cos(2 * math.pi * i / 36),
              1875.0 * math.sin(2 * math.pi * i / 36)) for i in range(36)]
    out += [(950.0 * math.cos(2 * math.pi * i / 12),
              950.0 * math.sin(2 * math.pi * i / 12)) for i in range(12)]
    return out

def oracle_cover(src, cand):
    """源位置 + 贪心补洞点, 直到定向安全证书通过。返回 (点数, max_gap_deg)。"""
    pts = list(src)
    used = []
    for _ in range(12):
        cert = directional_certificate(pts)
        if cert["ok"]:
            return len(used), cert["max_gap_deg"]
        best, best_gap = None, 1e9
        for c in cand:
            if any(distance(c, q) < 1.0 for q in pts):
                continue
            gap = directional_certificate(pts + [c])["max_gap_deg"]
            if gap < best_gap:
                best_gap, best = gap, c
        if best is None:
            break
        pts.append(best)
        used.append(best)
    return len(used), directional_certificate(pts)["max_gap_deg"]

design = [(0.0, 0.0)] + list(directional_survey_design())

```

```

cands = cover_candidates()
rows = []
for seed in range(15):
    jam = random_case(n=16, seed=seed, directional_ratio=1.0)
    src = [tuple(j.position) for j in jam]
    # 基线: 25 点巡游 (开放) + 收尾从最后点到所有源的巡游
    base_cov = open_tour_len((0.0, 0.0), design)
    base_tail = open_tour_len(design[-1], src)
    base = base_cov + base_tail
    # Oracle: 源 + 补洞点的合并巡游
    n_extra, gap = oracle_cover(src, cands)
    orc = open_tour_len((0.0, 0.0), src + [c for c in cands][:0]) # 占位
    orc = open_tour_len((0.0, 0.0), src) # 源本身巡游
    # 补洞点在 oracle 里也要走: 用 oracle_cover 返回的 used
    pts = list(src)
    for _ in range(n_extra):
        best, best_gap = None, 1e9
        for c in cands:
            if any(distance(c, q) < 1.0 for q in pts):
                continue
            g = directional_certificate(pts + [c])["max_gap_deg"]
            if g < best_gap:
                best_gap, best = g, c
        if best is not None:
            pts.append(best)
    orc = open_tour_len((0.0, 0.0), pts)
    rows.append((base / 1000, orc / 1000, n_extra, gap))

print(f"{'seed':>4} {'基线 km':>8} {'Oraclekm':>9} {'补洞点':>6} {'角隙':>7}")
for i, (b, o, ne, g) in enumerate(rows):
    print(f"{i:>4} {b:8.2f} {o:9.2f} {ne:>6} {g:7.2f}")
mb = statistics.fmean(r[0] for r in rows)
mo = statistics.fmean(r[1] for r in rows)
print(f"\n 平均: 基线 {mb:.2f} km | Oracle {mo:.2f} km | "
      f"可回收 {mb-mo:.2f} km = {(mb-mo)*1000/5/16:.1f} s/源 (N=16)")

```

B.45 scripts/_oracle_p4b.py

"""Oracle2: 问题 4「覆盖+清除合并巡游」vs「覆盖巡游 + 收尾清除」(分离)。

问题: 把 25 点覆盖与 16 个源清除合成一条 TSP, 理论上比"先扫完 25 点、再收尾清源"省多少? (这就是"清源路程反哺覆盖"的上限: 源位置用真值, 仅离线估计)

```

"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import directional_survey_design
from src.geometry import distance
from src.mock_simulator import random_case

def tour_len(start, points, rounds=8, warm=3):
    """开放巡游长度 (NN + 2-opt + Or-opt, 多起点取最短)。"""
    pts = list(points)
    if not pts:
        return 0.0
    best = None
    for k in range(min(warm, len(pts))):
        head = pts[k]
        tour = [start, head]
        pool = pts[:k] + pts[k + 1:]
        while pool:
            nxt = min(pool, key=lambda q: distance(tour[-1], q))
            pool.remove(nxt)
            tour.append(nxt)
        n = len(tour)
        for _ in range(rounds):
            imp = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                    if (distance(a, b) + distance(c, d)
                        > distance(a, c) + distance(b, d) + 1e-9):
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        imp = True

```

```

for seg in (1, 2, 3):
    s = 1
    while s + seg < len(tour):
        blk = tour[s:s + seg]
        prev = tour[s - 1]
        nxt = tour[s + seg] if s + seg < len(tour) else None
        out = distance(prev, blk[0])
        if nxt is not None:
            out += distance(blk[-1], nxt) - distance(prev, nxt)
        rest = tour[s:] + tour[s + seg:]
        b2 = None
        for t in range(len(rest) - 1):
            u, v = rest[t], rest[t + 1]
            add = (distance(u, blk[0]) + distance(blk[-1], v)
                  - distance(u, v))
            if b2 is None or add < b2[0]:
                b2 = (add, t + 1)
        tail = distance(rest[-1], blk[0])
        if b2 is None or tail < b2[0]:
            b2 = (tail, len(rest))
        if b2[0] < out - 1e-9:
            tour = rest[:b2[1]] + blk + rest[b2[1]:]
            imp = True
        else:
            s += 1
    if not imp:
        break
    L = sum(distance(tour[i], tour[i + 1]) for i in range(len(tour) - 1))
    if best is None or L < best:
        best = L
return best

```

```

design = [(0.0, 0.0)] + list(directional_survey_design())
for ratio, tag in [(1.0, "全定向"), (0.0, "全向")]:
    base_all, merged_all = [], []
    for seed in range(15):
        jam = random_case(n=16, seed=seed, directional_ratio=ratio)
        src = [tuple(j.position) for j in jam]
        # 分离式 (当前范式): 25 点巡游 + 从终点收尾清源
        sep = tour_len((0.0, 0.0), design) + tour_len(design[-1], src)
        # 合并式 (Oracle): 25 点 + 16 源 一条 TSP
        mer = tour_len((0.0, 0.0), design + src)
        base_all.append(sep / 1000)
        merged_all.append(mer / 1000)
    a, b = statistics.fmean(base_all), statistics.fmean(merged_all)
    print(f"{tag} N=16: 分离 {a:5.2f} km | 合并(理想) {b:5.2f} km | "
          f"可回收 {a-b:5.2f} km = {(a-b)*1000/5/16:5.1f} s/源")

```

B.46 scripts/_p4diag.py

```

"""诊断: 问题 4 的扫描点数、源发现时机、检测构成、收尾返程。"""
import collections
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4

def diag(ratio, n, seeds=15):
    scanned = [] # 清满 16 时扫了多少个覆盖点
    first_obs = [] # 每个源在第几个扫描点首次被发现
    meas_kind = collections.Counter()
    tail_move = []
    T = []
    for seed in range(seeds):
        jam = random_case(n=n, seed=seed, directional_ratio=ratio)
        sim = MockSimulator(jam, seed=seed)
        res = StrategyP4(insert_threshold=400.0).run(sim)
        T.append(res.mean_clear_time)
        # 统计扫描点 (sweep 是全频道扫描; P4 里每个 survey point 都 sweep)
        pts = [(0.0, 0.0)] + list(StrategyP4().survey_points)
        # 遍历日志: 统计 measure 的 result 分布 + 每个频道的首次 direction 时机

```

```

ncov = 0
seen_cov = set()
first = {}
last_cover_idx = 0
for i, e in enumerate(sim.log):
    if e["path"] != "/measure":
        continue
    meas_kind[e.get("measure_result")] += 1
    key = (round(e["position"][0], 1), round(e["position"][1], 1))
    if key not in seen_cov:
        seen_cov.add(key)
        ncov += 1
    if e.get("measure_result") == "direction" and e["channel"] not in first:
        first[e["channel"]] = ncov
first_obs += list(first.values())
# 收尾返程: 最后一个覆盖点之后的行程
ring = {(round(p[0], 1), round(p[1], 1)) for p in pts}
last = 0
for i, e in enumerate(sim.log):
    if e["path"] == "/measure" and (round(e["position"][0], 1), round(e["position"][1], 1))
in ring:
    last = i
    p = (0.0, 0.0)
    tm = 0.0
    for i, e in enumerate(sim.log):
        if e["path"] not in ("/measure", "/clear"):
            continue
        d = distance(p, tuple(e["position"]))
        if i > last:
            tm += d
        p = tuple(e["position"])
    tail_move.append(tm / 1000)
    scanned.append(ncov)
print(f"{{ratio*100:.0f}}%定向 N={{n}}: 平均 {{statistics.fmean(T):.1f}}s "
      f"扫{{statistics.fmean(scanned):.1f}}点 源首现第{{statistics.fmean(first_obs):.1f}}点 "
      f"收尾返程{{statistics.fmean(tail_move):.2f}}km")
return meas_kind

```

```

mk = diag(1.0, 16)
print(f" 检测结果分布: {dict(mk)}")

```

B.47 scripts/_p4dirskip.py

"""实验: 问题4 定向源"朝向半平面外"检测跳过 (减少 no_signal 浪费)。"""

```

import math
import statistics
import sys

```

```

sys.path.insert(0, r"G:\C\CUMCM B 题")

```

```

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4, bearing_least_squares

```

```

class V(StrategyP4):
    def __init__(self, insert=400.0, dir_skip=False, deg=95.0):
        super().__init__(insert_threshold=insert)
        self.dir_skip = dir_skip
        self.dir_deg = deg

    def _directional_invisible(self, point, records):
        """定向源在 point 处是否**一定 no_signal** (保守: 只用检测点正约束)。

        源被检测点 d_i 看到  $\Rightarrow (d_i - G) \cdot u \geq 0$ , 即源的朝向 u 落在"所有检测点方向
        的  $\pm 90^\circ$  交集"内。若 point 到估计 G 的方向与**每个**检测点方向都  $> \text{dir\_deg}^\circ$ ,
        则对任何可行朝向 u 都有  $(\text{point} - G) \cdot u < 0 \Rightarrow \text{point}$  一定 no_signal, 可跳过。
        只用正约束  $\Rightarrow$  保守 (只会跳过"确定 no_signal"的, 不会漏)。
        """
        if len(records) < 2:
            return False
        est = bearing_least_squares(records)
        if est is None:
            return False
        dirs = [math.atan2(est[1] - p[1], est[0] - p[0]) for p, _ in records]
        tp = math.atan2(est[1] - point[1], est[0] - point[0])

```

```

        for d in dirs:
            diff = abs((tp - d + math.pi) % (2 * math.pi) - math.pi)
            if diff <= math.radians(self.dir_deg):
                return False
        return True

def _sweep(self, transport, point, channels, bearings, cleared, result):
    done = 0
    for ch in channels:
        if ch in cleared or self._observations_complete(bearings[ch]):
            continue
        if bearings[ch] and self._beyond_reachable(point, bearings[ch]):
            continue
        if self.dir_skip and bearings[ch] and \
            self._directional_invisible(point, bearings[ch]):
            continue
        resp = transport.measure(point, ch)
        result.measures += 1
        done += 1
        kind = resp.get("measure_result")
        if kind == "direction":
            bearings[ch].append((point, float(resp["svd_deg"])))
        elif kind == "near" and self._try_clear(transport, ch, point, result):
            cleared.add(ch)
    return done

def bench(ratio, n, seeds=15, **kw):
    T, M, Me, U = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                             seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me), U)

print("问题4 朝向跳过扫描 (全定向 N=16, 15 例/档)")
for label, kw in [
    ("基线(不跳过)", {}),
    ("朝向跳过 95°", dict(dir_skip=True, deg=95.0)),
    ("朝向跳过 100°", dict(dir_skip=True, deg=100.0)),
    ("朝向跳过 110°", dict(dir_skip=True, deg=110.0)),
    ("朝向跳过 120°", dict(dir_skip=True, deg=120.0)),
]:
    t, m, me, u = bench(1.0, 16, **kw)
    print(f"{label:16s} {t:6.1f}s 行程{m:5.2f}km 检测{me:4.0f}次 未清{u}")

```

B.48 scripts/_p4early.py

```

"""实验: 问题4 更早停止 (early_stop_bearings=1) + 收尾 1-bearing 用追击。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4

class V(StrategyP4):
    def __init__(self, insert=400.0, early=2, pursuit=False):
        super().__init__(insert_threshold=insert)
        self.early_stop_bearings = early
        self.use_pursuit = pursuit

    def _resolve_channel(self, transport, channel, observations, result):
        """1 条示向度: 优先沿示向度追击 (定向源沿轴走必在朝向半平面内)。"""
        if self.use_pursuit and len(observations) == 1:
            b, br = observations[-1]
            if self._pursuit_clear(transport, channel, b, br, result):
                return True
        return super()._resolve_channel(transport, channel, observations, result)

```

```

def bench(ratio, n, seeds=20, **kw):
    T, M, Me, U = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                             seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me), U)

print("问题4 更早停止扫描 (全定向 N=16, 20 例/档)")
for label, kw in [
    ("基线 early=2", dict(early=2)),
    ("early=1 无追击", dict(early=1)),
    ("early=1 + 追击", dict(early=1, pursuit=True)),
]:
    t, m, me, u = bench(1.0, 16, **kw)
    print(f"{label:16s} {t:6.1f}s 行程{m:5.2f}km 检测{me:4.0f}次 未清{u}")
# 半定向也测
for label, kw in [
    ("半定向 early=2", dict(early=2)),
    ("半定向 early=1+追击", dict(early=1, pursuit=True)),
]:
    t, m, me, u = bench(0.5, 16, **kw)
    print(f"{label:16s} {t:6.1f}s 未清{u}")

```

B.49 scripts/_p4opt.py

```

"""实验: 问题4 优化 — obs 自适应 + insert 阈值 + 检测跳过."""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import localization_region, min_enclosing_circle, distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4

class V(StrategyP4):
    def __init__(self, insert=400.0, adapt=None, obs=None):
        super().__init__(insert_threshold=insert)
        self.adapt = adapt
        if obs is not None:
            self.observations_target = obs

    def _observations_complete(self, records):
        if len(records) >= self.observations_target:
            return True
        if self.adapt and len(records) == 2:
            poly = localization_region([p for p, _ in records],
                                       [b for _, b in records])
            if poly:
                _, r = min_enclosing_circle(poly)
                if r <= self.adapt:
                    return True
        return False

def bench(ratio, n, seeds=15, **kw):
    T, M, Me, U = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                             seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me), U)

print("问题4 优化扫描 (全定向 N=16, 15 例/档)")
for label, kw in [

```

```

("基线 obs=3", {}),
("obs=2", dict(obs=2)),
("obs=3+adapt60", dict(adapt=60.0)),
("obs=3+adapt120", dict(adapt=120.0)),
("obs=3+adapt200", dict(adapt=200.0)),
]:
    t, m, me, u = bench(1.0, 16, **kw)
    print(f"{label:16s} {t:6.1f}s 行程{m:5.2f}km 检测{me:4.0f}次 未清{u}")

```

B.50 scripts/_p4order.py

```

"""实验: 问题 4 扫描顺序 / 巡游 TSP 的变体 (影响"源发现时机"与总距离)。"""
import math
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.routing import two_opt_tour
from src.strategy_p4 import StrategyP4

def strong_tour(start, pts, rounds=10, warm=4):
    """NN + 2-opt + Or-opt, 多起点取最短 (比 two_opt_tour 更强)。"""
    pts = list(pts)
    if not pts:
        return [start]
    best, bestL = None, None
    for k in range(min(warm, len(pts))):
        tour = [start, pts[k]]
        pool = pts[:k] + pts[k + 1:]
        while pool:
            nxt = min(pool, key=lambda q: distance(tour[-1], q))
            pool.remove(nxt)
            tour.append(nxt)
        n = len(tour)
        for _ in range(rounds):
            imp = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i], tour[i + 1], tour[j], tour[j + 1]
                    if (distance(a, b) + distance(c, d)
                        > distance(a, c) + distance(b, d) + 1e-9):
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        imp = True
            for seg in (1, 2, 3):
                s = 1
                while s + seg < len(tour):
                    blk = tour[s:s + seg]
                    prev, nxt = tour[s - 1], (tour[s + seg]
                                                if s + seg < len(tour) else None)
                    out = distance(prev, blk[0])
                    if nxt is not None:
                        out += distance(blk[-1], nxt) - distance(prev, nxt)
                    rest = tour[s:] + tour[s + seg:]
                    b2 = None
                    for t in range(len(rest) - 1):
                        u, v = rest[t], rest[t + 1]
                        add = (distance(u, blk[0]) + distance(blk[-1], v)
                              - distance(u, v))
                        if b2 is None or add < b2[0]:
                            b2 = (add, t + 1)
                    tail = distance(rest[-1], blk[0])
                    if b2 is None or tail < b2[0]:
                        b2 = (tail, len(rest))
                    if b2[0] < out - 1e-9:
                        tour = rest[:b2[1]] + blk + rest[b2[1]:]
                        imp = True
                    else:
                        s += 1
            if not imp:
                break
        L = sum(distance(tour[i], tour[i + 1]) for i in range(len(tour) - 1))
        if bestL is None or L < bestL:
            best, bestL = tour, L
    return best

```

```

def by_ring(pts):
    """按半径分组: 中心 / 内环 / 外环。"""
    c = [p for p in pts if math.hypot(*p) < 1.0]
    mid = [p for p in pts if 1.0 <= math.hypot(*p) < 1400.0]
    out = [p for p in pts if math.hypot(*p) >= 1400.0]
    key = lambda q: math.atan2(q[1], q[0])
    return c, sorted(mid, key=key), sorted(out, key=key)

class V(StrategyP4):
    def __init__(self, order="tsp", **kw):
        super().__init__(**kw)
        self.order = order

    def _tour_order(self):
        pts = list(self.survey_points)
        if self.order == "tsp":
            return two_opt_tour([(0.0, 0.0)] + pts)
        if self.order == "strong":
            return strong_tour((0.0, 0.0), pts)
        c, mid, out = by_ring(pts)
        if self.order == "inner_first":
            return [(0.0, 0.0)] + mid + out
        if self.order == "outer_first":
            return [(0.0, 0.0)] + out + mid
        if self.order == "inner_first_strong":
            return strong_tour((0.0, 0.0), mid + out)
        return two_opt_tour([(0.0, 0.0)] + pts)

def bench(ratio, n, seeds=15, **kw):
    T, M, U = [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                             seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        U += len(r.unresolved)
    return statistics.fmean(T), statistics.fmean(M), U

print("扫描顺序 / 巡游变体 (全定向 N=16, 15 例/档)")
for label, kw in [
    ("tsp(当前)", dict(order="tsp")),
    ("strong(NN+2opt+0rOpt)", dict(order="strong")),
    ("inner_first", dict(order="inner_first")),
    ("outer_first", dict(order="outer_first")),
    ("inner_first_strong", dict(order="inner_first_strong")),
]:
    t, m, u = bench(1.0, 16, **kw)
    print(f"{label:22s} {t:6.1f}s 行程{m:5.2f}km 未清{u}")

```

B.51 scripts/_p4order2.py

```

"""验证 inner_first_strong 全档效果 (复用 _p4order 的 V/bench)。"""
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")
sys.path.insert(0, r"G:\C\CUMCM B 题\scripts")

from _p4order import bench # noqa: E402

print("全档对比: tsp(当前) vs inner_first_strong (30 例/档, 同种子)")
for ratio, tag in [(0.0, "全向"), (0.5, "半定向"), (1.0, "全定向")]:
    row = [f"{tag:4s}"]
    for order in ("tsp", "inner_first_strong"):
        cells = []
        for n in (10, 16):
            t, m, u = bench(ratio, n, seeds=30, order=order)
            cells.append(f"N{n}:{t:6.1f}/{m:5.2f}")
        row.append(f"{order:18s} " + " ".join(cells))
    print(" | ".join(row))

```

B.52 scripts/_p4retire.py

```
"""实验：问题 4 E1 频道退休（第一次 direction 后从主扫描退休）+ 收尾补测方式。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4

class V(StrategyP4):
    """E1: 主扫描只测零观测频道；已发现源退休，收尾补第二条示向度。"""

    def __init__(self, insert=400.0, retire=True, pursuit=False, early=2):
        super().__init__(insert_threshold=insert)
        self.retire = retire
        self.use_pursuit = pursuit
        self.early_stop_bearings = early

    def _sweep(self, transport, point, channels, bearings, cleared, result):
        done = 0
        for ch in channels:
            if ch in cleared:
                continue
            # 频道退休：第一次 direction 后，从主扫描集合退休（不再承担“发现”任务）
            if self.retire and bearings[ch]:
                continue
            if bearings[ch] and self._beyond_reachable(point, bearings[ch]):
                continue
            resp = transport.measure(point, ch)
            result.measures += 1
            done += 1
            kind = resp.get("measure_result")
            if kind == "direction":
                bearings[ch].append((point, float(resp["svd_deg"])))
            elif kind == "near" and self._try_clear(transport, ch, point, result):
                cleared.add(ch)
        return done

    def _resolve_channel(self, transport, channel, observations, result):
        if self.use_pursuit and len(observations) == 1:
            b, br = observations[-1]
            if self._pursuit_clear(transport, channel, b, br, result):
                return True
        return super()._resolve_channel(transport, channel, observations, result)

    def bench(ratio, n, seeds=20, **kw):
        T, M, Me, U = [], [], [], 0
        for seed in range(seeds):
            sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                                seed=seed)
            r = V(**kw).run(sim)
            T.append(r.mean_clear_time)
            M.append(r.move_distance / 1000)
            Me.append(r.measures)
            U += len(r.unresolved)
        return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me), U)

print("E1 频道退休（全定向 N=16, 20 例/档）")
for label, kw in [
    ("基线(不退休)", dict(retire=False)),
    ("E1 退休+扇形探测", dict(retire=True)),
    ("E1 退休+追击", dict(retire=True, pursuit=True)),
    ("E1+追击+early1", dict(retire=True, pursuit=True, early=1)),
]:
    t, m, me, u = bench(1.0, 16, **kw)
    print(f"{label:18s} {t:6.1f}s 行程{m:5.2f}km 检测{me:4.0f}次 未清{u}")
```

B.53 scripts/_p4sweep.py

```
"""诊断：问题 4 清满 16 时实际扫了多少覆盖点（巡游能否提前结束）。"""
import statistics
import sys
```

```

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import directional_survey_design
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p4 import StrategyP4

class Rec(StrategyP4):
    def __init__(self, insert=400.0):
        super().__init__(insert_threshold=insert)
        self.nswept = 0
        self.sweep_pts = []

    def _sweep(self, t, p, c, b, cl, r):
        self.sweep_pts.append((round(p[0], 1), round(p[1], 1)))
        return super()._sweep(t, p, c, b, cl, r)

pts = [(0.0, 0.0)] + list(directional_survey_design())
print(f"覆盖网点数: {len(pts)}")
for ratio, tag in [(1.0, "全定向"), (0.0, "全向")]:
    for n in (10, 16):
        ns = []
        T = []
        U = 0
        for seed in range(15):
            sim = MockSimulator(random_case(n=n, seed=seed, directional_ratio=ratio),
                                seed=seed)

            st = Rec()
            r = st.run(sim)
            # 统计扫描的"覆盖点"数量 (去重后与设计点匹配的)
            swept = {(round(p[0], 1), round(p[1], 1)) for p in st.sweep_pts}
            design = {(round(p[0], 1), round(p[1], 1)) for p in pts}
            ns.append(len(swept & design))
            T.append(r.mean_clear_time)
            U += len(r.unresolved)
        print(f"{tag} N={n}: 扫{statistics.fmean(ns):.1f}个覆盖点/{len(pts)} 时间
{statistics.fmean(T):.1f}s 未清{U}")

```

B.54 scripts/_predictive.py

```

"""实验: 预测性牵引 (1 条示向度就插入复测点) 的参数扫描。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

class V(StrategyP3):
    def __init__(self, minobs, step, side):
        super().__init__()
        self.insert_min_observations = minobs
        self.pursuit_step = step
        self.pursuit_side = side

def bench(n, seeds=20, **kw):
    T, M, C, U = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        C.append(r.clears + r.failed_clears)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(C), U)

print("预测性牵引参数扫描 (20 例/档)")
for label, kw in [
    ("基线 obs=2", dict(minobs=2, step=150, side=300)),
    ("obs=1 step600 side300", dict(minobs=1, step=600, side=300)),
    ("obs=1 step700 side300", dict(minobs=1, step=700, side=300)),
    ("obs=1 step800 side400", dict(minobs=1, step=800, side=400)),

```

```

("obs=1 step600 side200", dict(minobs=1, step=600, side=200)),
]:
    cells, bad = [], 0
    for n in (10, 16):
        t, m, c, u = bench(n, **kw)
        cells.append(f"N{n}:{t:6.1f}/{m:5.2f}/{c:5.0f}")
        bad += u
    print(f"{label:24s} " + " | ".join(cells) + f" 未清={bad}")

```

B.55 scripts/_restart.py

"""测试: 插入后对剩余路线做"最近邻重启 + 2-opt + Or-opt"全局重排, 回收排序损失。"""

```

import statistics
import sys

```

```

sys.path.insert(0, r"G:\C\CUMCM B 题")

```

```

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

```

```

class V(StrategyP3):
    """用全局重排替换局部 2-opt/Or-opt。"""

    def _improve_remaining(self, route, index, rounds=6):
        m = len(route)
        if m - index < 4:
            return
        # 提取剩余点 (保持 (point, channel, full) 三元组)
        seg = route[index:]
        start = seg[0][0]
        rest = seg[1:]
        # 最近邻重启
        tour = [seg[0]]
        pool = list(rest)
        while pool:
            nxt = min(pool, key=lambda t: distance(tour[-1][0], t[0]))
            pool.remove(nxt)
            tour.append(nxt)
        n = len(tour)
        def tot_len(t):
            return sum(distance(t[i][0], t[i + 1][0]) for i in range(len(t) - 1))
        # 2-opt + Or-opt (多轮, 只接受变短)
        for _ in range(rounds):
            imp = False
            for i in range(n - 2):
                for j in range(i + 2, n - 1):
                    a, b, c, d = tour[i][0], tour[i + 1][0], tour[j][0], tour[j + 1][0]
                    if distance(a, b) + distance(c, d) > distance(a, c) + distance(b, d) + 1e-9:
                        tour[i + 1:j + 1] = tour[i + 1:j + 1][::-1]
                        imp = True
            for seg_len in (1, 2, 3):
                s = 1
                while s + seg_len < len(tour):
                    blk = tour[s:s + seg_len]
                    prev = tour[s - 1][0]
                    nxt = tour[s + seg_len][0] if s + seg_len < len(tour) else None
                    out = distance(prev, blk[0][0])
                    if nxt is not None:
                        out += distance(blk[-1][0], nxt) - distance(prev, nxt)
                    rest2 = tour[s:] + tour[s + seg_len:]
                    best = None
                    for t in range(len(rest2) - 1):
                        u, v = rest2[t][0], rest2[t + 1][0]
                        add = distance(u, blk[0][0]) + distance(blk[-1][0], v) - distance(u, v)
                        if best is None or add < best[0]:
                            best = (add, t + 1)
                    tail = distance(rest2[-1][0], blk[0][0])
                    if best is None or tail < best[0]:
                        best = (tail, len(rest2))
                    if best[0] < out - 1e-9:
                        tour = rest2[:best[1]] + blk + rest2[best[1]:]
                        imp = True
                    else:
                        s += 1
            if not imp:
                break

```

```

route[index:] = tour

def bench(n, seeds=20, **kw):
    T, M, Me, U = [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        r = V(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me), U)

for label, cls in (("基线(局部 2opt+0r0pt)", StrategyP3), ("全局重排(NN 重启)", V)):
    cells, bad = [], 0
    for n in (10, 12, 14, 16):
        t, m, me, u = bench(n)
        cells.append(f"N{n}:{t:6.1f}/{m:5.2f}/{me:5.0f}")
        bad += u
    print(f"{label:20s} " + " | ".join(cells) + f" 未清={bad}")

```

B.56 scripts/_tail.py

```

"""诊断: 多少源被收尾处理、收尾行程多大、哪些源进收尾。"""
import collections
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.coverage import seven_point_design
from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

for n in (10, 16):
    main_clear = tail_clear = 0
    tail_travel = []
    tail_bearings = []
    for seed in range(15):
        jam = random_case(n=n, seed=seed)
        sim = MockSimulator(jam, seed=seed)
        st = StrategyP3()
        res = st.run(sim)
        ring = {(round(p[0], 1), round(p[1], 1)) for p in seven_point_design(1000.0, 7)}
        # 找最后一个覆盖点扫描的日志位置
        last_cov = 0
        for i, e in enumerate(sim.log):
            if e["path"] == "/measure" and (round(e["position"][0], 1), round(e["position"][1], 1))
in ring:
            last_cov = i
        # 统计: 主路线 (<= last_cov) 清除的频道 vs 收尾清除的频道
        cleared_in_main = set()
        cleared_in_tail = set()
        tail_move = 0.0
        pos = None
        # 重新走一遍日志累计行程
        p = (0.0, 0.0)
        for i, e in enumerate(sim.log):
            if e["path"] not in ("/measure", "/clear"):
                continue
            d = distance(p, tuple(e["position"]))
            if i > last_cov:
                tail_move += d
            p = tuple(e["position"])
            if e["path"] == "/clear" and e.get("clear_result") == "success":
                if i <= last_cov:
                    cleared_in_main.add(e["channel"])
                else:
                    cleared_in_tail.add(e["channel"])
        main_clear += len(cleared_in_main)
        tail_clear += len(cleared_in_tail)
        tail_travel.append(tail_move / 1000)
        # 尾程源的示向度条数
        bearings = collections.defaultdict(int)
        for i, e in enumerate(sim.log):

```

```

        if e["path"] == "/measure" and e.get("measure_result") == "direction" and i <= last_cov:
            bearings[e["channel"]] += 1
        tail_bearings += [bearings[c] for c in cleared_in_tail]
    print(f"N={n}: 主路线清除 {main_clear/15:.1f} 个源 | 收尾清除 {tail_clear/15:.1f} 个源 | "
          f"收尾行程 {statistics.fmean(tail_travel):.2f} km | 尾程源在覆盖扫描结束时的示向度数 "
          f"{statistics.fmean(tail_bearings) if tail_bearings else 0:.1f}")

```

B.57 scripts/_trace.py

```

"""追踪: 主循环每次访问的点, 以及 route 里 full 覆盖点是否齐全。"""
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.geometry import distance
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

TARGET = (-623.5, 781.8)

class Rec(StrategyP3):
    def _sweep(self, t, p, c, b, cl, r):
        tag = " <== 目标点!" if distance(p, TARGET) < 5 else ""
        print(f" sweep ({p[0]:6.0f},{p[1]:6.0f}){tag}")
        return super()._sweep(t, p, c, b, cl, r)

    def _probe(self, t, p, c, b, cl, r):
        tag = " <== 目标点!" if distance(p, TARGET) < 5 else ""
        print(f" probe ({p[0]:6.0f},{p[1]:6.0f}){tag}")
        return super()._probe(t, p, c, b, cl, r)

    def _fast_clear(self, t, ch, est, rec, r):
        tag = " <== 目标点!" if distance(est, TARGET) < 5 else ""
        print(f" clear ch{ch} @ ({est[0]:6.0f},{est[1]:6.0f}){tag}")
        return super()._fast_clear(t, ch, est, rec, r)

    def _schedule_sources(self, route, index, *a):
        has = any(distance(p, TARGET) < 5 for p, _, _ in route)
        super()._schedule_sources(route, index, *a)
        has2 = any(distance(p, TARGET) < 5 for p, _, _ in route)
        if has and not has2:
            print(f" [schedule] index={index} 目标点消失!")

    def _prune_coverage(self, route, index, swept):
        has = any(distance(p, TARGET) < 5 for p, _, _ in route)
        super()._prune_coverage(route, index, swept)
        has2 = any(distance(p, TARGET) < 5 for p, _, _ in route)
        if has and not has2:
            print(f" [prune] index={index} 目标点被剪!")

jam = random_case(seed=2)
sim = MockSimulator(jam, seed=2)
st = Rec()
res = st.run(sim)
print(f"\ncleared={res.cleared}/{res.total}")

```

B.58 scripts/_v2.py

```

"""问题 3 v2 验证: 追击模型 + 无复测点 (8 点覆盖骨干)。"""
import statistics
import sys

sys.path.insert(0, r"G:\C\CUMCM B 题")

from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3

class V2(StrategyP3):
    """v2: 8 个覆盖扫描点、无复测点, 追击处理 1 示向度/细长源。"""

    def __init__(self):
        super().__init__()
        self.cover_ring_count = 7          # center + 7 环 = 8 点
        self.cover_probe_stride = 1        # 全部作为覆盖扫描点

```

```

        self.probe_keep = 0                                # 无几何复测点

def bench(cls, n, seeds=20, **kw):
    T, M, Me, C, U = [], [], [], [], 0
    for seed in range(seeds):
        sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
        r = cls(**kw).run(sim)
        T.append(r.mean_clear_time)
        M.append(r.move_distance / 1000)
        Me.append(r.measures)
        C.append(r.clears + r.failed_clears)
        U += len(r.unresolved)
    return (statistics.fmean(T), statistics.fmean(M), statistics.fmean(Me),
            statistics.fmean(C), U)

print("格式: 时间 s / 行程 km / 检测 / 清除动作 / 未清")
for label, cls in (("v1 基线", StrategyP3), ("v2 追击无复测", V2)):
    cells, bad = [], 0
    for n in (10, 12, 14, 16):
        t, m, me, c, u = bench(cls, n)
        cells.append(f"N{n}:{t:6.1f}/{m:5.2f}/{me:5.0f}/{c:5.1f}")
        bad += u
    print(f"{label:14s} " + " | ".join(cells) + f" 未清={bad}")

```

B.59 scripts/analyze_designs.py

"""问题 1/2/3 的定量分析与设计优化验证。

一、布站准则对照（回应"45° vs 54.74°"）

模型: $S1=(0,0)$, 目标 $G=(d1,0)$, 第二点 $S2=(0,b)$ （垂直于示向度），
则 $d2=\sqrt{d1^2+b^2}$, 交会角 $\theta=\arctan(b/d1)$ 。

设第 i 个测向的**横向误差** $e_i = c \cdot d_i^\alpha$:

* $\alpha=1$: 纯角度误差（本题附件给的有界 $\pm 1^\circ$, 横向误差 = $d \cdot \tan \varepsilon$ ） $\rightarrow b*=d1, \theta*=45^\circ$

* $\alpha=0.5$: 角度误差部分随距离加权 $\rightarrow b*=\sqrt{2} \cdot d1, \theta*=54.74^\circ$

* $\alpha=2$: 强距离加权 $\rightarrow b*=d1/\sqrt{2}, \theta*=35.26^\circ$

推导: 定位区域面积 $A \propto e1 \cdot e2 / \sin \theta = c^2 \cdot d1^\alpha \cdot d2^{\alpha+1} / b$,

对 b 求导得 $b* = d1/\sqrt{\alpha} \Rightarrow \theta* = \arctan(1/\sqrt{\alpha})$ 。**两个数字同属一个族**，

只是横向误差模型不同: 本题附件明确"误差范围 $\pm 1^\circ$ "（有界） $\Rightarrow$ 取 $\alpha=1$ 、 $b*=d1$ 。

再做极小极大（ α 不确定）与机动成本两种稳健化，给出推荐区间。

二、问题 1: 蒙特卡洛验证"直径圆覆盖定位区域"的失败率（论文表格）

三、问题 3: 覆盖环设计优化（回应"把交点放到 1800 圆周上、让环更靠近圆心"）

"""

```

from __future__ import annotations

import json
import math
import os
import random
import sys

import numpy as np

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.config import EPS_DEG, REGION_RADIUS, R_MIN                # noqa: E402
from src.coverage import seven_point_design, worst_case_radius      # noqa: E402
from src.geometry import (                                          # noqa: E402
    bearing_between,
    diameter_circle_covers,
    localization_region,
)
from src.routing import tour_length, two_opt_tour                    # noqa: E402

D1 = 1000.0
EPS = math.radians(EPS_DEG)

def area_factor(b: float, d1: float = D1, alpha: float = 1.0) -> float:
    """定位区域面积的比例因子（去掉与  $\varepsilon$  无关的常数）:  $d1^\alpha \cdot d2^{\alpha+1} / b$ 。"""
    d2 = math.hypot(d1, b)
    return (d1 ** alpha) * (d2 ** (alpha + 1.0)) / b

```

```

def optimal_b_analytic(d1: float = D1, alpha: float = 1.0) -> float:
    """解析最优基线  $b^* = d1/\sqrt{\alpha}$  ( $\alpha \leq 0$  表示纯横向误差, 随  $b$  单调变优  $\rightarrow$  退化)。"""
    if alpha <= 0.0:
        return float("inf")
    return d1 / math.sqrt(alpha)

def optimal_b_numeric(d1: float = D1, alpha: float = 1.0,
                     b_hi: float = 8000.0) -> float:
    bs = np.linspace(d1 * 0.05, b_hi, 40000)
    vals = np.array([area_factor(float(b), d1, alpha) for b in bs])
    return float(bs[int(np.argmin(vals))])

def analyse_criteria() -> dict:
    alphas = (0.5, 2.0 / 3.0, 0.8, 1.0, 1.25, 1.5, 2.0)
    rows = []
    for a in alphas:
        b_an = optimal_b_analytic(D1, a)
        b_num = optimal_b_numeric(D1, a)
        rows.append({"alpha": a, "b_star": b_an, "b_star_numeric": b_num,
                    "theta_star_deg": math.degrees(math.atan2(b_an, D1)),
                    "numeric_error_m": abs(b_an - b_num)})
    print("=== 布站准则对照 (横向误差  $e \propto d^{\alpha}$ ) ===")
    print(" alpha | 解析  $b^*$  | 数值  $b^*$  |  $\theta^*$  (deg) | 数值误差(m)")
    for r in rows:
        print(f" {r['alpha']:5.2f} | {r['b_star']:7.1f} | {r['b_star_numeric']:7.1f} | "
              f"{r['theta_star_deg']:8.2f} | {r['numeric_error_m']:8.1f}")
    key = {a: next(r for r in rows if abs(r["alpha"] - a) < 1e-9) for a in (0.5, 1.0)}
    print(f"\n alpha=1.0 (本题: 有界  $\pm 1^\circ$ )  $\rightarrow b^*=\{key[1.0]['b_star']:.1f\}$  m, "
          f" $\theta^*=\{key[1.0]['theta_star_deg']:.2f\}^\circ$  (本方案采用)")
    print(f" alpha=0.5 (误差随距离加权)  $\rightarrow b^*=\{key[0.5]['b_star']:.1f\}$  m, "
          f" $\theta^*=\{key[0.5]['theta_star_deg']:.2f\}^\circ$  ( $= \sqrt{2} \cdot d1$ , 与参考思路一致)")

    print("\n 面积惩罚 (相对各自最优, 1.000 为最优): ")
    print(" 设计\真值 " + " ".join(f" $\alpha=\{a:4.2f\}$ " for a in (0.5, 1.0, 2.0)))
    penalty = {}
    for design_alpha in (0.5, 1.0, 2.0):
        b_design = optimal_b_analytic(D1, design_alpha)
        row = [area_factor(b_design, D1, t)
              / area_factor(optimal_b_analytic(D1, t), D1, t)
              for t in (0.5, 1.0, 2.0)]
        penalty[design_alpha] = row
    print(f"  $\alpha=\{design\_alpha:4.2f\}$  " + " ".join(f" $v:6.3f\}$ " for v in row))

    cand = np.linspace(0.5 * D1, 2.2 * D1, 3000)
    worst = [max(area_factor(float(b), D1, a)
                / area_factor(optimal_b_analytic(D1, a), D1, a)
                for a in (0.5, 0.75, 1.0, 1.25, 1.5)) for b in cand]
    i = int(np.argmin(worst))
    b_minimax, worst_minimax = float(cand[i]), float(worst[i])
    print(f"\n 极小极大稳健设计 ( $\alpha \in [0.5, 1.5]$ ):  $b=\{b\_minimax:.1f\}$  m "
          f" $\theta=\{b\_minimax / D1:.2f\} \cdot d1$ ,  $\theta=\{math.degrees(math.atan2(b\_minimax, D1)):.2f\}^\circ$ , "
          f"最坏面积惩罚= $\{worst\_minimax:.3f\}$ ")

    print("\n 计入机动成本 (总价 = 归一面积惩罚 +  $w \cdot b/d1$ ): ")
    base = area_factor(optimal_b_analytic(D1, 1.0), D1, 1.0)
    move_rows = []
    for w in (0.0, 0.02, 0.05, 0.10, 0.20):
        vals = [area_factor(float(b), D1, 1.0) / base + w * (b / D1) for b in cand]
        b_star = float(cand[int(np.argmin(vals))])
        move_rows.append({"w_move": w, "b_star": b_star,
                        "theta_star_deg": math.degrees(math.atan2(b_star, D1)),
                        "area_penalty_vs_pure": area_factor(b_star, D1, 1.0) / base})
    print(f" w= $\{w:5.2f\}$ :  $b^*=\{b\_star:7.1f\}$  m, "
          f" $\theta^*=\{move\_rows[-1]['theta\_star\_deg']:5.2f\}^\circ$ , "
          f"面积惩罚= $\{move\_rows[-1]['area\_penalty\_vs\_pure']:.3f\}$ ")
    return {"alpha_family": rows, "penalty": penalty,
            "minimax": {"b": b_minimax, "penalty": worst_minimax,
                        "theta_deg": math.degrees(math.atan2(b_minimax, D1))},
            "move_cost": move_rows}

def monte_carlo_problem1(n_cases: int = 5000, seed: int = 7) -> dict:
    """问题 1 蒙特卡洛: 不同站数下"以区域直径为直径的圆"能否覆盖定位区域。"""

```

采样设定与题目一致：站点与目标都落在半径 1800 m 的目标区域内，
 示向度误差 $\pm 1^\circ$ 均匀分布。统计三类结果：

- * **空区域**： $\pm 1^\circ$ 楔形互不相交（真值仍在内，但交会失败）→ 必须增加观测站，这正是问题 3/4 采用“三观测/多站交会”的直接依据；
- * **直径圆覆盖**：能否用“区域直径为直径的圆”覆盖整个定位区域；
- * 2 站时由平行四边形定理**必然覆盖**（对角线互相平分）；
- * ≥ 3 站不保证（锐角三角形反例），失败时的半径超出量是米级。

```

"""
rng = random.Random(seed)
out = {}
for k in (2, 3, 4):
    covered = empty = total = 0
    excess = []
    for _ in range(n_cases):
        stations = []
        for _ in range(k):
            r = 1800.0 * math.sqrt(rng.random())
            th = rng.random() * 2.0 * math.pi
            stations.append((r * math.cos(th), r * math.sin(th)))
        r = 1800.0 * math.sqrt(rng.random())
        th = rng.random() * 2.0 * math.pi
        target = (r * math.cos(th), r * math.sin(th))
        bearings = []
        skip = False
        for s in stations:
            if math.dist(s, target) < 1.0:
                skip = True
                break
            bearings.append(bearing_between(s, target)
                           + rng.uniform(-EPS_DEG, EPS_DEG))
        if skip:
            continue
        total += 1
        poly = localization_region(stations, bearings)
        if not poly or len(poly) < 3:
            empty += 1
            continue
        info = diameter_circle_covers(poly)
        if info["covered"]:
            covered += 1
        else:
            excess.append(info["mec_radius"] - info["circle_radius"])
    valid = total - empty
    rate = covered / valid if valid else float("nan")
    out[k] = {"cases": total, "empty": empty,
             "empty_ratio": empty / total if total else float("nan"),
             "coverage_ratio": rate, "fails": valid - covered,
             "excess_median_m": float(np.median(excess)) if excess else 0.0,
             "excess_max_m": max(excess) if excess else 0.0}
    print(f" 站数 K={k}: 空区域率 {out[k]['empty_ratio']:.4f}; "
          f"直径圆覆盖率 {rate:.4f} (失败 {out[k]['fails']}/{valid}); "
          f"半径超出量中位 {out[k]['excess_median_m']:.4f} m "
          f"最大 {out[k]['excess_max_m']:.4f} m")
print(" 结论: 2 站 (平行四边形) 必然覆盖;  $\geq 3$  站不保证, 失效构型的半径超出量为米级; ")
print("      空区域的存在说明『两站交会』在  $\pm 1^\circ$  误差下并不总可用, 多站/多次观测是必要的。")
return out

```

```

def ring_radius_min(k: int, region_radius: float = REGION_RADIUS,
                    r_min: float = R_MIN) -> float:
    """k 个均布环点 + 中心点覆盖圆域所需的**最小环半径** (解析)。
```

约束：边界“角平分点”恰好落在覆盖圆周上（即相邻两覆盖圆的交点正好在 R 圆周上）：

$$\sqrt{R^2 + a^2 - 2Ra \cdot \cos(\pi/k)} = r_{\min}$$

$$\Rightarrow a^2 - 2R \cdot \cos(\pi/k) \cdot a + (R^2 - r_{\min}^2) = 0, \text{ 取较小根。}$$

这就是“把交点放到 1800 圆周上”的精确数学表达。

```

"""
c = math.cos(math.pi / k)
disc = (region_radius * c) ** 2 - (region_radius ** 2 - r_min ** 2)
return region_radius * c - math.sqrt(max(disc, 0.0))

```

```

def analyse_p3_ring() -> dict:
    print("\n=== 问题 3 覆盖环: 点数 k 与环半径/巡游/检测代价 ===")
    print(" k | 最小环半径 a_min(m) | 数值复核最坏最近距离 | 2-opt 巡游(km) | "
          " 全频道扫描点数 | N=10 代价(s) | N=16 代价(s)")

```

```

rows = []
for k in (6, 7, 8, 10, 12, 14, 16, 20):
    a = ring_radius_min(k)
    design = seven_point_design(a, k)
    wc = worst_case_radius(design, REGION_RADIUS, 6000, 6000)
    tour = tour_length(two_opt_tour(design))
    sweeps = k + 1 # 中心 + k 个环点都要做全频道扫描
    row = {"k": k, "a_min": a, "worst_case_m": wc, "tour_m": tour,
           "sweeps": sweeps}
    for n in (10, 16):
        row[f"cost_N{n}"] = tour / 5.0 + sweeps * (20 - n) * 6.0
    rows.append(row)
    print(f" {k:2d} | {a:16.1f} | {wc:19.1f} | {tour / 1000:11.2f} | "
          f" {sweeps:12d} | {row['cost_N10']:12.0f} | {row['cost_N16']:12.0f}")
best10 = min(rows, key=lambda r: r["cost_N10"])
best16 = min(rows, key=lambda r: r["cost_N16"])
print(f"\n 最小总代价: N=10 → k={best10['k']} ( {best10['cost_N10']:.0f} s ) : "
      f"N=16 → k={best16['k']} ( {best16['cost_N16']:.0f} s ) ")
print(" 说明: 环半径随 k 减小 (k=7→999 m、k=14→839 m、极限 800 m = 1800-1000), "
      " 巡游也随之变短; \n 但每个环点都要做一次全频道扫描 (空频道也要测), "
      " 每多点约多 (20-N)×6 s, 而巡游每多点只省约 20 s。")
return {"rows": rows, "best_N10": best10["k"], "best_N16": best16["k"]}

```

```

def analyse_intersection_variant() -> dict:
    """验证"让相邻覆盖圆的外侧交点落在 R=1800 圆周上"这一构造。

```

几何: 环上相邻两点 (半径 a 、夹角 $2\pi/k$) 的覆盖圆 (半径 $R_{\min}$) 有两个交点, 其中**外侧交点**位于角平分线方向, 到原点距离为

$p_{\text{outer}}(a, k) = a \cdot \cos(\pi/k) + \sqrt{R_{\min}^2 - (a \cdot \sin(\pi/k))^2}$
 令 $p_{\text{outer}} = R$ 即得到"外侧交点正好落在 1800 圆周上"的环半径。

注意: 它与"边界角平分点恰好被覆盖"是**同一条件**

$\sqrt{R^2 + a^2 - 2Ra \cdot \cos(\pi/k)} = R_{\min}$,
 因此也等于 `ring\_radius\_min(k)` 的解析解。
 """

```

print("\n== 构造验证: 相邻覆盖圆外侧交点落在 R=1800 圆周上 ==")
rows = {}
for k in (6, 7, 8):
    a_analytic = ring_radius_min(k)
    # 直接按"外侧交点"定义做数值求根, 与解析式互证
    lo, hi = 100.0, 2600.0
    for _ in range(200):
        mid = (lo + hi) / 2.0
        rho = (mid * math.cos(math.pi / k)
               + math.sqrt(max(R_MIN ** 2 - (mid * math.sin(math.pi / k)) ** 2, 0.0)))
        if rho < REGION_RADIUS:
            lo = mid
        else:
            hi = mid
    a_numeric = (lo + hi) / 2.0
    design = seven_point_design(a_analytic, k)
    wc = worst_case_radius(design, REGION_RADIUS, 8000, 8000)
    tour = tour_length(two_opt_tour(design))
    rows[k] = {"a_analytic": a_analytic, "a_numeric": a_numeric,
              "worst_case_m": wc, "tour_m": tour, "sweeps": k + 1}
    print(f" k={k}: 环半径 a={a_analytic:.1f} m (数值求根 {a_numeric:.1f}) "
          f" 最坏最近距离={wc:.1f} m 巡游={tour / 1000:.2f} km")
a6, a7 = rows[6]["a_analytic"], rows[7]["a_analytic"]
print(f"\n ⇒ k=6 的『外侧交点落在 1800 圆周上』要求 a={a6:.1f} m, "
      f"比 k=7 的 {a7:.1f} m **更远**:")
print(f" 巡游也随之更长 ( {rows[6]['tour_m'] / 1000:.2f} km vs "
      f" {rows[7]['tour_m'] / 1000:.2f} km ) — 与『更靠近圆心』的直觉相反。")
print(" 原因: 点数越少, 相邻角隙  $2\pi/k$  越大, 边界角平分点离环点越远; ")
print(" 要让半径 1000 的圆仍能够到它, 环只能往外挪。")

print("\n 验证不等式方向 (环点到边界角平分点的距离, 须  $\leq R_{\min}=1000$ ): ")
print(" a(m) | k=6 (30°) | k=7 (25.71°) | k=8 (22.5°)")
for a in (800.0, 900.0, 997.0, 1050.0, 1122.9):
    cells = []
    for k in (6, 7, 8):
        d = math.sqrt(REGION_RADIUS ** 2 + a ** 2
                       - 2 * REGION_RADIUS * a * math.cos(math.pi / k))
        cells.append(f"{d:6.1f}{'√' if d <= R_MIN else 'X'}")
    print(f" {a:6.1f} | " + " | ".join(cells))
print(" ⇒ 半径越小越难够到边界: a 的下界由角隙决定 (k=6→1122.9、k=7→997.2、k=8→938.1)。")

```

```

        return rows

def main() -> None:
    report = {"criteria": analyse_criteria(),
              "problem1_mc": monte_carlo_problem1(),
              "problem3_ring": analyse_p3_ring(),
              "intersection_variant": analyse_intersection_variant()}
    out = os.path.join(ROOT, "results", "design_analysis.json")
    with open(out, "w", encoding="utf-8") as fh:
        json.dump(report, fh, ensure_ascii=False, indent=2)
    print(f"\n 结果已写入: {out}")

if __name__ == "__main__":
    main()

```

B.60 scripts/design_p4_survey.py

"""问题 4 检测点网设计: 定向安全双环网 + 确定性证书 + 巡游最短化搜索。

理论条件 (问题 4 的核心)

对圆域内任意 G 与任意定向朝向 u , 必须存在检测点 p 满足

$$|p - G| \leq R_{\min} \quad \text{且} \quad (p - G) \cdot u \geq 0$$

等价条件: G 严格位于集合 $\{p : |p - G| \leq R_{\min}\}$ 的凸包内部

$\Leftrightarrow$ 近旁点相对 G 的方位角最大角隙 $< 180^\circ$ 。

****当前方案 (25 点双环网) 的解析证书****

中心 1 点 + 内环 $r=950 \text{ m} \times 12$ + 外环 $r=1875 \text{ m} \times 12$ (错相 15°)。

* 外环正十二边形内切半径 $1875 \cdot \cos 15^\circ = 1811.11 \text{ m} > 1800 \text{ m}$

$\Rightarrow$ 目标圆域整体含于"中心-内环-外环"三角剖分内部;

* 该剖分全部边长 $< R_{\min} = 1000 \text{ m}$:

中心-内环 950.0 、内环相邻边 491.76 、外环相邻边 970.57 、交叉边 988.44 (最长)。

$\Rightarrow$ 域内任意 G 落在某个三角形内, 其三顶点都在接收半径内且包围 G

$\Rightarrow$ 任意朝向的定向源必被至少一个检测点看到 (**严格保证, 非抽样**).

****为什么是双环而不是 31 点三角格点****

开放巡游长度 $\approx$ 各环多段线之和 $\approx 2\pi(r_{\text{in}} + r_{\text{out}})$:

双环 $2\pi(950+1875) = 17.75 \text{ km}$ (实测 2-opt 18.02 km);

31 点格点必须铺到 $r \approx 2800 \text{ m} \Rightarrow$ 巡游约 30 km 。双环缩短约 40% 。

****本脚本做什么****

1. 用确定性证书 + 蒙特卡洛复核当前方案;

2. 在双环参数族 $(r_{\text{in}}, m_{\text{in}}, r_{\text{out}}, m_{\text{out}}, \text{phase})$ 中搜索"巡游最短且证书通过"的候选, 输出对照表, 说明当前方案的巡游已接近该族下界。

用法: `python scripts/design_p4_survey.py`

输出: `results/p4_survey_design.json`

"""

```
from __future__ import annotations
```

```
import io
import json
import math
import os
import sys
```

```
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
```

```
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)
```

```
from src.config import REGION_RADIUS, R_MIN                                # noqa: E402
from src.coverage import (                                                # noqa: E402
    directional_certificate,
    directional_coverage_ok,
    directional_survey_design,
    two_ring_design,
)
from src.strategy_p4 import two_opt_tour                                  # noqa: E402
```

```
def tour_length(points) -> float:
```

```

"""从原点出发的最近邻 + 2-opt 开放巡游长度 (m)。"""
tour = two_opt_tour([(0.0, 0.0)] + list(points))
return sum(math.dist(a, b) for a, b in zip(tour, tour[1:]))

def main() -> None:
    current = directional_survey_design()
    cert = directional_certificate(current)
    mc = directional_coverage_ok(current, n_samples=20000, seed=7)
    length = tour_length(current)
    edges = {
        "center_inner": 950.0,
        "inner_edge": 2.0 * 950.0 * math.sin(math.pi / 12.0),
        "outer_edge": 2.0 * 1875.0 * math.sin(math.pi / 12.0),
        "cross_edge": math.sqrt(950.0 ** 2 + 1875.0 ** 2
                                - 2.0 * 950.0 * 1875.0 * math.cos(math.pi / 12.0)),
    }
    print(f"当前方案: {len(current)} 点, 巡游 {length / 1000:.2f} km")
    print(f"  确定性证书 ok={cert['ok']} fail={cert['fail']} ")
    print(f"    f"最大角隙 {cert['max_gap_deg']:.2f}° (裕量 {180 - cert['max_gap_deg']:.2f}°)")
    print(f"  蒙特卡洛 20000 次通过率 {mc['ok_ratio']:.4f}")
    print(f"  三角剖分最长边 {max(edges.values()):.2f} m (< {R_MIN:.0f}), "
          f"  外环内切半径 {1875.0 * math.cos(math.pi / 12.0):.2f} m (> {REGION_RADIUS:.0f})")

# ----- 双环参数族搜索: 巡游最短且证书通过 -----
candidates = []
for r_in in range(300, 1001, 50):
    for m_in in (6, 8, 10, 12):
        for r_out in range(1800, 1951, 25):
            for m_out in (12, 14, 16):
                for phase in (0.0, 0.5):
                    pts = two_ring_design(r_in, m_in, r_out, m_out, phase)
                    # 先用中等密度证书筛(快速), 通过的才计算巡游长度
                    quick = directional_certificate(
                        pts, n_radial=25, n_angular=72, n_boundary=720)
                    if not quick["ok"]:
                        continue
                    dense = directional_certificate(pts)
                    if not dense["ok"]:
                        continue
                    candidates.append({
                        "inner_radius": float(r_in), "inner_count": m_in,
                        "outer_radius": float(r_out), "outer_count": m_out,
                        "phase": phase, "n_points": len(pts),
                        "tour_m": tour_length(pts),
                        "max_gap_deg": dense["max_gap_deg"],
                    })
candidates.sort(key=lambda c: c["tour_m"])
print(f"\n 双环族中通过确定性证书的构型共 {len(candidates)} 个; 巡游最短 5 个: ")
for c in candidates[:5]:
    print(f"  巡游 {c['tour_m'] / 1000:6.2f} km 最大角隙 {c['max_gap_deg']:.2f}° "
          f"  点数 {c['n_points']:2d}  r_in={c['inner_radius']:.0f}×{c['inner_count']} "
          f"  r_out={c['outer_radius']:.0f}×{c['outer_count']}  phase={c['phase']}")

best = candidates[0] if candidates else None
if best:
    gain = length - best["tour_m"]
    print(f"\n 结论: 最优候选比现方案省 {gain / 1000:.2f} km "
          f"  ({100.0 * gain / length:.1f}%), 但角隙裕量 "
          f"  {180 - best['max_gap_deg']:.2f}° vs 现方案 {180 - cert['max_gap_deg']:.2f}°: "
          f"  收益不足 3% 时保留现方案。")

out = os.path.join(ROOT, "results", "p4_survey_design.json")
io.open(out, "w", encoding="utf-8").write(json.dumps({
    "current": {
        "n_points": len(current), "tour_m": length,
        "certificate": cert, "directional_pass_ratio": mc["ok_ratio"],
        "triangulation_longest_edge_m": max(edges.values()),
        "outer_inradius_m": 1875.0 * math.cos(math.pi / 12.0),
        "points": current,
    },
    "feasible_two_ring_candidates": len(candidates),
    "shortest_candidates": candidates[:10],
}, ensure_ascii=False, indent=2))
print("\n 已保存:", out)

```

```
if __name__ == "__main__":
    main()
```

B.61 scripts/diag_time_split.py

"""诊断：问题三/四的时间与行程分解，定位可压缩瓶颈（诊断用脚本）。

用法：

```
& 'D:\Anaconda3\envs\CUMCM\python.exe' scripts\diag_time_split.py
```

```
from __future__ import annotations
```

```
import statistics
```

```
import sys
```

```
from pathlib import Path
```

```
ROOT = Path(__file__).resolve().parents[1]
```

```
if str(ROOT) not in sys.path:
```

```
    sys.path.insert(0, str(ROOT))
```

```
from src.config import MOVE_SPEED # noqa: E402
```

```
from src.coverage import seven_point_design # noqa: E402
```

```
from src.mock_simulator import MockSimulator, random_case # noqa: E402
```

```
from src.routing import tour_length, two_opt_tour # noqa: E402
```

```
from src.strategy_p3 import StrategyP3 # noqa: E402
```

```
from src.strategy_p4 import StrategyP4 # noqa: E402
```

```
def backbone_length() -> float:
```

```
    """问题三覆盖骨干（中心 + 14 点环）从原点出发的开放巡游长度（m）。"""
```

```
    ring = seven_point_design(1000.0, 14)
```

```
    return tour_length(two_opt_tour([(0.0, 0.0)] + list(ring)))
```

```
def split(tag: str, factory, n: int, ratio: float, seeds: int = 10) -> None:
```

```
    times, moves, meas, clr = [], [], [], []
```

```
    for s in range(seeds):
```

```
        sim = MockSimulator(random_case(n=n, seed=s, directional_ratio=ratio),
                             seed=s)
```

```
        r = factory().run(sim)
```

```
        times.append(r.virtual_time)
```

```
        moves.append(r.move_distance)
```

```
        meas.append(r.measures)
```

```
        clr.append(r.clears)
```

```
    t = statistics.fmean(times)
```

```
    mv = statistics.fmean(moves)
```

```
    ms = statistics.fmean(meas)
```

```
    cl = statistics.fmean(clr)
```

```
    move_s = mv / MOVE_SPEED
```

```
    meas_s = ms * 6.0 # 5 s 检测 + 1 s 切换
```

```
    clear_s = cl * 5.0
```

```
    other = t - move_s - meas_s - clear_s
```

```
    print(f"{tag}: 总 {t:7.1f}s = 移动 {move_s:7.1f}s ({100*move_s/t:4.1f}%) "
```

```
          f"+ 测量 {meas_s:6.1f}s ({100*meas_s/t:4.1f}%) "
```

```
          f"+ 清除 {clear_s:5.1f}s + 其他 {other:6.1f}s")
```

```
    print(f"      行程 {mv/1000:6.2f} km      测量 {ms:5.1f} 次      清除 {cl:4.1f} 次")
```

```
def main() -> None:
```

```
    bl = backbone_length()
```

```
    print(f"问题三覆盖骨干（中心+14 点环）开放巡游 = {bl/1000:.2f} km "
```

```
          f"f= {bl/MOVE_SPEED:.0f}s（保证性覆盖的固定成本）")
```

```
    print(f"访问 16 个源的 TSP 下界 ≈ 0.7124*sqrt(16*pi*1800^2) = "
```

```
          f"{0.7124*(16*3.14159265*1800**2)**0.5/1000:.2f} km "
```

```
          f"f= {0.7124*(16*3.14159265*1800**2)**0.5/MOVE_SPEED:.0f}s")
```

```
    print()
```

```
    split("P3 现状", StrategyP3, 16, 0.0)
```

```
    split("P4 现状", StrategyP4, 16, 1.0)
```

```
if __name__ == "__main__":
```

```
    main()
```

B.62 scripts/exp_coverage_tradeoff.py

"""对照实验：**牺牲覆盖率换速度**的几条路线（不改动任何主策略文件）。

包含三组：

- A. 删减覆盖点（问题3的8点网、问题4的22点网）——直接少扫点。
- B. 乐观半径布点——按“ $r_{\text{eff}} \approx 1500 \text{ u}$ ”而不是保守的 $R_{\text{min}} = 1000 \text{ m}$ 布点。
- C. 面积梯度游走（`strategy_gradient.StrategyP3Gradient`）——不预置布点。

统一口径：s/源（`mean_clear_time`）、行程 km、**未清源总数**、**有漏测的案例数**。

用法：

```
python scripts/exp_coverage_tradeoff.py --problem 3 --seeds 30
python scripts/exp_coverage_tradeoff.py --problem 4 --seeds 30
"""
from __future__ import annotations

import argparse
import math
import statistics
import sys
from pathlib import Path
from typing import List, Sequence, Tuple

ROOT = Path(__file__).resolve().parents[1]
if str(ROOT) not in sys.path:
    sys.path.insert(0, str(ROOT))

from src.coverage import (directional_survey_design, # noqa: E402
                           directional_certificate, seven_point_design,
                           two_ring_design)
from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p3 import StrategyP3 # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402
from src.strategy_fast import StrategyP3Fast, StrategyP4Fast # noqa: E402
from src.strategy_gradient import (StrategyP3Gradient, # noqa: E402
                                   StrategyP4Gradient)

Point = Tuple[float, float]

def p3_base_design() -> List[Point]:
    """问题3的默认8点覆盖网（中心+半径1000m七均布）。"""
    return seven_point_design(1000.0, 7)

def drop_points(design: Sequence[Point], keep_ring: int) -> List[Point]:
    """保留中心点+前`keep_ring`个环上点（其余删掉）。"""
    center = [p for p in design if math.hypot(*p) <= 1e-9]
    ring = [p for p in design if math.hypot(*p) > 1e-9]
    return center + ring[:keep_ring]

def run_case(strategy_factory, jammer_seed: int, n: int, ratio: float):
    jammers = random_case(n=n, seed=jammer_seed, directional_ratio=ratio)
    sim = MockSimulator(jammers, seed=jammer_seed)
    result = strategy_factory().run(sim)
    return result, len(jammers)

def bench(label: str, factory, n: int, ratio: float, seeds: int) -> dict:
    times, moves, unresolved, bad_cases, missed = [], [], 0, 0, 0
    for s in range(seeds):
        result, total = run_case(factory, s, n, ratio)
        times.append(result.mean_clear_time)
        moves.append(result.move_distance / 1000.0)
        unresolved += len(result.unresolved)
        missed += max(0, total - result.cleared)
        if result.unresolved or result.cleared < total:
            bad_cases += 1
    return {
        "label": label, "time": statistics.fmean(times),
        "move": statistics.fmean(moves), "unresolved": unresolved,
        "missed": missed, "bad_cases": bad_cases, "seeds": seeds, "n": n,
    }

def report(rows: List[dict]) -> None:
    print(f"{'方案':>36s} {'s/源':>7s} {'行程 km':>7s} {'漏清源':>6s} "
          f"{'漏测案例':>8s} {'清除率':>7s}")
    for r in rows:
        denom = max(1, r["seeds"] * r["n"])
        print(f"{'label':>36s} {'time':>7.1f} {'move':>7.2f} "
```

```

f"{r['missed']:6d} {r['bad_cases']:8d} "
f"{100.0*(1-r['missed']/denom):6.2f}%"

def subsample_ring(ring: Sequence[Point], k: int) -> List[Point]:
    """从环上点里按角度均匀取 k 个（用于构造“减点”对照网）。"""
    if k >= len(ring):
        return list(ring)
    idx = sorted([int(round(i * len(ring) / k)) % len(ring) for i in range(k)])
    return [ring[i] for i in idx]

def p4_shrink(inner_k: int, outer_k: int) -> List[Point]:
    """问题 4 减点网：中心 + 内环取 inner_k 个 + 外环取 outer_k 个。"""
    base = directional_survey_design()
    inner = [p for p in base if 1.0 <= math.hypot(*p) < 1400.0]
    outer = [p for p in base if math.hypot(*p) >= 1400.0]
    return [(0.0, 0.0)] + subsample_ring(inner, inner_k) + \
        subsample_ring(outer, outer_k)

def main() -> None:
    ap = argparse.ArgumentParser(description="牺牲覆盖率换速度的对照实验")
    ap.add_argument("--problem", type=int, choices=(3, 4), default=3)
    ap.add_argument("--seeds", type=int, default=20)
    ap.add_argument("--n", type=int, default=16)
    ap.add_argument("--ratio", type=float, default=0.0,
                    help="定向源比例（问题 4 常用 1.0 全定向）")
    args = ap.parse_args()

    rows: List[dict] = []
    if args.problem == 3:
        rows.append(bench("★ P3 主策略(默认骨干,全覆盖)",
                          lambda: StrategyP3(),
                          args.n, args.ratio, args.seeds))
        base = p3_base_design()
        rows.append(bench("P3 8 点网(删点对照基线)",
                          lambda: StrategyP3(survey_points=base),
                          args.n, args.ratio, args.seeds))
        for k in (6, 5, 4, 3):
            pts = drop_points(base, k)
            rows.append(bench(
                f"P3 {k+1}点(删环点,无证书)",
                lambda pts=pts: StrategyP3(survey_points=pts),
                args.n, args.ratio, args.seeds))
        rows.append(bench("P3 面积梯度(不预置布点)",
                          lambda: StrategyP3Gradient(),
                          args.n, args.ratio, args.seeds))
        for b in (1, 4):
            rows.append(bench(
                f"P3 访问优先(探索预算{b})",
                lambda b=b: StrategyP3Fast(explore_budget=b),
                args.n, args.ratio, args.seeds))
    else:
        rows.append(bench("P4 22 点(基准,全覆盖)",
                          lambda: StrategyP4(),
                          args.n, args.ratio, args.seeds))
        for ik, ok in ((8, 10), (6, 8), (4, 6)):
            pts = p4_shrink(ik, ok)
            rows.append(bench(
                f"P4 {len(pts)}点(内{ik}+外{ok},无证书)",
                lambda pts=pts: StrategyP4(survey_points=pts),
                args.n, args.ratio, args.seeds))
        rows.append(bench("P4 面积梯度(不预置布点)",
                          lambda: StrategyP4Gradient(),
                          args.n, args.ratio, args.seeds))
        for b in (1, 4):
            rows.append(bench(
                f"P4 访问优先(探索预算{b})",
                lambda b=b: StrategyP4Fast(explore_budget=b),
                args.n, args.ratio, args.seeds))
    report(rows)

if __name__ == "__main__":
    main()

```

B.63 scripts/make_figures.py

"""生成论文图件 (results/figs/*.png)。

包含:

fig1_problem1.png 问题 1: 两站交会定位区域 + 直径圆 + 最小覆盖圆; 锐角三角形反例
fig2_problem2.png 问题 2: 面积/det(FIM) 关于基线 b 的曲线 (最优点 $b*=d1$, $\theta=45^\circ$) + 蝶形候选区
fig3_problem3.png 问题 3: 经典 7 点覆盖网 (说明"最少 7 点"的下界)
fig3b_problem3_scheme.png 问题 3 **实际运行方案**: 中心+14 点加密环 (8 个全频道扫描点 + 7 个几何复测点) 与真实巡游路径
fig4_problem4.png 问题 4: 7 点方案定向失败 vs 25 点定向安全双环网成功

中文显示: 优先使用微软雅黑, 缺失时自动回退。

```
"""  
  
from __future__ import annotations  
  
import math  
import os  
import sys  
  
import matplotlib  
matplotlib.use("Agg")  
import matplotlib.pyplot as plt  
import numpy as np  
  
ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))  
if ROOT not in sys.path:  
    sys.path.insert(0, ROOT)  
from matplotlib.figure import Figure  
  
# Windows 下保存 png 偶发 OSError(22) (杀软扫描 / 图片预览器占用), 加重试更稳。  
_orig_savefig = Figure.savefig  
  
def _retrying_savefig(self, fname, *args, **kwargs):  
    import time  
  
    last = None  
    for _ in range(6):  
        try:  
            return _orig_savefig(self, fname, *args, **kwargs)  
        except OSError as exc:      # pragma: no cover - 环境相关  
            last = exc  
            time.sleep(0.8)  
    raise last  
  
Figure.savefig = _retrying_savefig  
  
  
from src.config import EPS_DEG, REGION_RADIUS, R_MIN  
from src.coverage import (  
    directional_coverage_ok,  
    directional_survey_design,  
    seven_point_design,  
)  
from src.geometry import (  
    bearing_between,  
    diameter_circle_covers,  
    localization_region,  
    unit_vector,  
    wedge_polygon,  
)  
  
FIG_DIR = os.path.join(ROOT, "results", "figs")  
os.makedirs(FIG_DIR, exist_ok=True)  
  
for font in ("Microsoft YaHei", "SimHei", "DejaVu Sans"):  
    plt.rcParams["font.sans-serif"] = [font]  
    plt.rcParams["font.family"] = "sans-serif"  
    break  
plt.rcParams["axes.unicode_minus"] = False  
plt.rcParams["figure.dpi"] = 130
```

```

def circle(ax, center, radius, **kw):
    th = np.linspace(0, 2 * math.pi, 400)
    ax.plot(center[0] + radius * np.cos(th), center[1] + radius * np.sin(th), **kw)

def fig_problem1():
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(11.5, 5.2))
    jammer = (620.0, 430.0)
    s1, s2 = (0.0, 0.0), (900.0, -200.0)
    b1, b2 = bearing_between(s1, jammer), bearing_between(s2, jammer)
    poly = localization_region([s1, s2], [b1, b2])
    info = diameter_circle_covers(poly)

    for s, b, name in ((s1, b1, "S1"), (s2, b2, "S2")):
        tri = wedge_polygon(s, b, EPS_DEG, radius=1600.0)
        ax1.fill([p[0] for p in tri], [p[1] for p in tri], color="tab:blue", alpha=0.12)
        for sgn in (-1, 1):
            ux, uy = unit_vector(b + sgn * EPS_DEG)
            ax1.plot([s[0], s[0] + 1600 * ux], [s[1], s[1] + 1600 * uy],
                    color="tab:blue", lw=0.8)
            ax1.plot(*s, "ko")
            ax1.annotate(name, s, textcoords="offset points", xytext=(6, 6))
    ax1.fill([p[0] for p in poly], [p[1] for p in poly], color="tab:red", alpha=0.35,
            label="定位区域 P (楔形交)")
    circle(ax1, info["circle_center"], info["circle_radius"], color="tab:red",
           ls="--", lw=1.2, label="以直径为直径的圆 (覆盖)")
    circle(ax1, info["mec_center"], info["mec_radius"], color="tab:green", ls=":",
           lw=1.2, label="最小覆盖圆")
    ax1.plot(*jammer, "r*", ms=12, label="干扰源真值")
    ax1.set_title("问题 1: 两站交会定位区域 (平行四边形必被直径圆覆盖)")
    ax1.legend(fontsize=8, loc="upper left")
    ax1.set_aspect("equal")
    ax1.grid(alpha=0.3)

    acute = [(0.0, 0.0), (1.0, 0.0), (0.5, math.sqrt(3) / 2)]
    info2 = diameter_circle_covers(acute)
    ax2.fill([p[0] for p in acute], [p[1] for p in acute], color="tab:orange", alpha=0.35,
            label="锐角三角形定位区域")
    circle(ax2, info2["circle_center"], info2["circle_radius"], color="tab:red", ls="--",
           label="直径圆 (覆盖失败)")
    circle(ax2, info2["mec_center"], info2["mec_radius"], color="tab:green", ls=":",
           label="最小覆盖圆 (可覆盖)")
    ax2.set_title("问题 1: 锐角三角形反例 (直径圆不能覆盖)")
    ax2.legend(fontsize=8, loc="upper right")
    ax2.set_aspect("equal")
    ax2.grid(alpha=0.3)
    fig.tight_layout()
    out = os.path.join(FIG_DIR, "fig1_problem1.png")
    fig.savefig(out)
    plt.close(fig)
    return out

def fig_problem2():
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(11.5, 4.8))
    d1 = 1000.0
    eps = math.radians(EPS_DEG)
    bs = np.linspace(0.2 * d1, 3.0 * d1, 800)
    d2 = np.sqrt(d1 ** 2 + bs ** 2)
    sin_th = bs / d2
    area = 4.0 * (math.tan(eps) ** 2) * d1 * d2 / sin_th
    det_fim = (sin_th / (d1 * d2)) ** 2
    ax1.plot(bs / d1, area / area.min(), label="定位区域面积 (归一化)")
    ax1.plot(bs / d1, det_fim / det_fim.max(), label="det(FIM) (归一化)")
    ax1.axvline(1.0, color="tab:red", ls="--", lw=1.0)
    ax1.annotate("最优基线 b* = d1\\n (交会角 45°)", xy=(1.0, 0.55),
                xytext=(1.35, 0.45), arrowprops=dict(arrowstyle=">", lw=0.9), fontsize=8)
    ax1.set_xlabel("垂直基线 b / d1")
    ax1.set_ylabel("归一化指标")
    ax1.set_title("问题 2: 面积与 Fisher 信息的最优基线一致 (b*=d1)")
    ax1.legend(fontsize=8)
    ax1.grid(alpha=0.3)

    s1 = (0.0, 0.0)
    b1 = 30.0
    ux, uy = unit_vector(b1)
    ax2.plot([0, 1800 * ux], [0, 1800 * uy], color="tab:blue", lw=1.0, label="示向度方向")
    for sgn in (-1, 1):

```

```

        nx, ny = unit_vector(b1 + sgn * 90.0)
        for frac in (0.5, 1.0, 1.5):
            cx, cy = frac * d1 * nx, frac * d1 * ny
            ax2.plot([cx - 350 * ux, cx + 350 * ux], [cy - 350 * uy, cy + 350 * uy],
                    color="tab:orange", lw=0.8, alpha=0.9)
    for sgn in (-1, 1):
        nx, ny = unit_vector(b1 + sgn * 90.0)
        ax2.plot([0], [0], marker="o", color="k")
        ax2.annotate("S1", (0, 0), textcoords="offset points", xytext=(6, 4))
        ax2.annotate("候选区域(蝶形)" if sgn > 0 else "",
                    (d1 * nx, d1 * ny), textcoords="offset points", xytext=(6, 6), fontsize=8)
    g = (d1 * ux, d1 * uy)
    ax2.plot(*g, "r*", ms=10, label="目标(未知距离 d1)")
    ax2.plot([0, d1 * unit_vector(b1 + 90.0)[0]],
            [0, d1 * unit_vector(b1 + 90.0)[1]], "k:", lw=0.8)
    ax2.set_title("问题 2: 第二检测点候选区域(示向度两侧垂直带)")
    ax2.legend(fontsize=8, loc="lower right")
    ax2.set_aspect("equal")
    ax2.grid(alpha=0.3)
    fig.tight_layout()
    out = os.path.join(FIG_DIR, "fig2_problem2.png")
    fig.savefig(out)
    plt.close(fig)
    return out

def fig_problem3():
    fig, ax = plt.subplots(figsize=(6.4, 6.4))
    circle(ax, (0, 0), REGION_RADIUS, color="k", lw=1.4, label="目标区域 R=1800 m")
    pts = seven_point_design(1400.0, 6)
    for p in pts:
        circle(ax, p, R_MIN, color="tab:blue", lw=0.4, alpha=0.35)
    ax.plot([p[0] for p in pts], [p[1] for p in pts], "o", color="tab:red", ms=6,
            label="7 点检测网(中心+环 1400m)")
    from src.coverage import worst_case_radius
    wc = worst_case_radius(pts, REGION_RADIUS, 6000, 6000)
    ax.set_title("问题 3: 7 点覆盖网(6 点不可行, 7 点最优)\n"
                "实测最坏覆盖距离 %.1f m < %.0f m" % (wc, R_MIN), fontsize=10)
    ax.legend(fontsize=8, loc="upper right")
    ax.set_aspect("equal")
    ax.grid(alpha=0.3)
    fig.tight_layout()
    out = os.path.join(FIG_DIR, "fig3_problem3.png")
    fig.savefig(out)
    plt.close(fig)
    return out

def fig_problem4():
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(12.0, 6.0))
    # 左: 7 点方案在定向情形失败
    circle(ax1, (0, 0), REGION_RADIUS, color="k", lw=1.2)
    pts7 = seven_point_design(1400.0, 6)
    ax1.plot([p[0] for p in pts7], [p[1] for p in pts7], "o", color="tab:red", ms=5,
            label="7 点网")
    g = (1750.0, 0.0)
    for p in pts7:
        if math.dist(p, g) <= R_MIN:
            circle(ax1, p, R_MIN, color="tab:blue", lw=0.4, alpha=0.3)
    ax1.plot(*g, "k*", ms=13, label="定向源 G")
    ux, uy = unit_vector(180.0) # 背向唯一检测点的朝向
    ax1.annotate("", xy=(g[0] + 500 * ux, g[1] + 500 * uy), xytext=g,
                arrowprops=dict(arrowstyle="->", lw=1.4, color="tab:purple"))
    ax1.annotate("定向方向(背向检测点)\n=> 所有点都 no_signal", xy=(g[0] - 420, g[1]),
                fontsize=8, color="tab:purple")
    r7 = directional_coverage_ok(pts7, n_samples=2000, seed=3)
    ax1.set_title("问题 4: 7 点方案定向覆盖通过率 %.1f%%(不可用)" % (100 * r7["ok_ratio"]),
                fontsize=10)
    ax1.legend(fontsize=8, loc="upper left")
    ax1.set_aspect("equal")
    ax1.grid(alpha=0.3)

    # 右: 25 点定向安全双环网满足定向覆盖
    circle(ax2, (0, 0), REGION_RADIUS, color="k", lw=1.2, label="目标区域")
    design = directional_survey_design()
    ax2.plot([p[0] for p in design], [p[1] for p in design], "^", color="tab:red", ms=4.5,
            label="25 点定向安全双环网(r=950/1875 m, 证书 fail=0)")

```

```

g2 = (500.0, 300.0)
near = [p for p in design if math.dist(p, g2) <= R_MIN]
for p in near:
    circle(ax2, p, R_MIN, color="tab:blue", lw=0.35, alpha=0.25)
for p in near:
    ax2.plot([p[0], g2[0]], [p[1], g2[1]], color="tab:green", lw=0.7, alpha=0.8)
ax2.plot(*g2, "k*", ms=13, label="定向源 G (任取)")
r4 = directional_coverage_ok(design, n_samples=4000, seed=3)
ax2.set_title("问题 4: 双环网定向覆盖抽样通过率 %.1f%% (近旁 %d 点包围 G) "
              % (100 * r4["ok_ratio"], len(near)), fontsize=10)
ax2.legend(fontsize=8, loc="upper left")
ax2.set_aspect("equal")
ax2.grid(alpha=0.3)
fig.tight_layout()
out = os.path.join(FIG_DIR, "fig4_problem4.png")
fig.savefig(out)
plt.close(fig)
return out

def fig_problem3_scheme():
    """问题 3 **当前运行方案**示意图: 覆盖骨干 + 几何复测点 + 实际巡游。

    与 fig3 (经典"7 点覆盖网", 说明最少 7 点的下界结论) 配套保留:
    fig3 讲下界, 本图讲实际落地方案 (中心 + 14 点加密环, 其中 8 个全频道
    扫描点承担"不漏测"保证, 另 7 个只复测"进行中"频道以改善交会几何)。
    """
    from src.coverage import seven_point_design, worst_case_radius
    from src.routing import tour_length, two_opt_tour
    from src.strategy_p3 import StrategyP3

    strat = StrategyP3()
    ring = seven_point_design(strat.cover_ring_radius, strat.cover_ring_count)
    sweep = [ring[i] for i in range(0, len(ring), strat.cover_probe_stride)]
    sweep_set = set(sweep)
    probes = [p for p in ring[1:] if p not in sweep_set]
    tour = two_opt_tour(ring)
    tl = tour_length(tour)
    worst = worst_case_radius(sweep, REGION_RADIUS, 6000, 6000)

    fig, ax = plt.subplots(figsize=(7.2, 7.2))
    circle(ax, (0, 0), REGION_RADIUS, color="k", lw=1.4, label="目标区域 R=1800 m")
    for p in sweep:
        circle(ax, p, R_MIN, color="tab:red", lw=0.45, alpha=0.30)
    ax.plot([p[0] for p in tour], [p[1] for p in tour], "-", color="0.55", lw=1.0,
            zorder=1, label="实际巡游 %.2f km" % (tl / 1000.0))
    ax.plot([p[0] for p in probes], [p[1] for p in probes], "o", color="tab:blue",
            ms=6.5, zorder=4, label="几何复测点 x7 (只测进行中频道)")
    ax.plot([p[0] for p in sweep], [p[1] for p in sweep], "*", color="tab:red",
            ms=13, zorder=5, label="全频道扫描点 x8 (中心 + 7, 保证不漏测)")
    ax.annotate("中心 (0,0)", xy=(0, 0), xytext=(120, -260), fontsize=8,
               arrowprops=dict(arrowstyle="->", lw=0.8))
    ax.annotate("环半径 1000 m", xy=(707, 707), xytext=(950, 1250), fontsize=8,
               arrowprops=dict(arrowstyle="->", lw=0.8))
    ax.set_title("问题 3 运行方案: 中心 + 14 点加密环\n"
                "覆盖保证只依赖 8 个扫描点: 解析最坏 %.2f m < %.0f m (实测 %.1f m) "
                % (998.2545, R_MIN, worst), fontsize=9.5)
    ax.legend(fontsize=8, loc="upper right")
    ax.set_aspect("equal")
    ax.grid(alpha=0.3)
    fig.tight_layout()
    out = os.path.join(FIG_DIR, "fig3b_problem3_scheme.png")
    fig.savefig(out)
    plt.close(fig)
    return out

def main():
    for fn in (fig_problem1, fig_problem2, fig_problem3, fig_problem3_scheme,
              fig_problem4):
        print("已保存:", fn())

if __name__ == "__main__":
    main()

```

B.64 scripts/run_mock_experiments.py

"""在 Mock 模拟器上批量演练问题 3/问题 4 策略，产出演练统计数据。

对应题目要求的两项统计量：

- * 被清除干扰源个数 / 干扰源总数（清除比例，必须为 1）
- * 平均定位清除时间 = 定位清除总时间 / 被清除干扰源个数

除均值外还输出中位数、P95、最大值与移动距离，便于对照“移动耗时占 80% 以上”的耗时账本，判断优化是否真的作用在行程而不是动作次数上。

用法：

```
python scripts/run_mock_experiments.py --problem 3 --cases 300
python scripts/run_mock_experiments.py --problem 4 --cases 300 \
    --n 14 --directional-count 6
python scripts/run_mock_experiments.py --problem 4 --cases 300 \
    --n 16 --directional-count 16 --label alldir
"""

from __future__ import annotations

import argparse
import json
import os
import statistics
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.mock_simulator import MockSimulator, random_case # noqa: E402
from src.strategy_p3 import StrategyP3 # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

def percentile(values, q: float) -> float:
    """线性插值分位数 (q ∈ [0, 1])，与 numpy 默认定义一致。"""
    ordered = sorted(values)
    if not ordered:
        return float("nan")
    if len(ordered) == 1:
        return float(ordered[0])
    pos = q * (len(ordered) - 1)
    lo = int(pos)
    hi = min(lo + 1, len(ordered) - 1)
    frac = pos - lo
    return float(ordered[lo] * (1.0 - frac) + ordered[hi] * frac)

def main() -> None:
    ap = argparse.ArgumentParser()
    ap.add_argument("--problem", type=int, default=3, choices=[3, 4])
    ap.add_argument("--cases", type=int, default=20)
    ap.add_argument("--directional-ratio", type=float, default=0.0)
    ap.add_argument("--n", type=int, default=None,
                    help="固定干扰源总数（默认 10~16 随机）")
    ap.add_argument("--directional-count", type=int, default=None,
                    help="恰好 k 个定向源（其余全向），优先于 --directional-ratio")
    ap.add_argument("--insert-threshold", type=float, default=400.0,
                    help="问题 4 机会式清除的额外路程阈值 (m)")
    ap.add_argument("--label", type=str, default="",
                    help="输出文件名后缀，用于区分不同实验配置")
    args = ap.parse_args()

    rows = []
    for seed in range(args.cases):
        jammers = random_case(
            n=args.n, seed=seed,
            directional_ratio=args.directional_ratio,
            directional_count=args.directional_count,
        )
        strategy = (StrategyP3() if args.problem == 3
                    else StrategyP4(insert_threshold=args.insert_threshold))
        sim = MockSimulator(jammers, seed=seed)
        res = strategy.run(sim)
        n_dir = sum(1 for j in jammers if j.direction is not None)
```

```

rows.append({
    "seed": seed, "n_jammers": sim.total_jammers, "n_directional": n_dir,
    "cleared": res.cleared, "clearance_ratio": res.clearance_ratio,
    "virtual_time_s": res.virtual_time,
    "mean_clear_time_s": res.mean_clear_time,
    "move_distance_m": res.move_distance,
    "mean_move_distance_m": res.mean_move_distance,
    "measures": res.measures, "clears": res.clears,
    "failed_clears": res.failed_clears, "unresolved": res.unresolved,
})
print(f"seed={seed:3d} N={sim.total_jammers:2d}(定向{n_dir:2d}) 清除={res.cleared:2d} "
      f"比例={res.clearance_ratio:.3f} 总时间={res.virtual_time:8.1f}s "
      f"平均={res.mean_clear_time:7.2f}s "
      f"移动={res.move_distance / 1000.0:6.2f}km "
      f"检测={res.measures:3d} 清除={res.clears:3d} 失败={res.failed_clears:3d}")

ratios = [r["clearance_ratio"] for r in rows]
times = [r["mean_clear_time_s"] for r in rows]
summary = {
    "problem": args.problem, "cases": args.cases,
    "n": args.n, "directional_ratio": args.directional_ratio,
    "directional_count": args.directional_count,
    "insert_threshold": args.insert_threshold if args.problem == 4 else None,
    "clearance_ratio_min": min(ratios),
    "clearance_ratio_mean": statistics.fmean(ratios),
    "all_cleared": all(abs(r - 1.0) < 1e-12 for r in ratios),
    "mean_clear_time_mean_s": statistics.fmean(times),
    "mean_clear_time_median_s": statistics.median(times),
    "mean_clear_time_p95_s": percentile(times, 0.95),
    "mean_clear_time_min_s": min(times),
    "mean_clear_time_max_s": max(times),
    "mean_clear_time_std_s": statistics.pstdev(times) if len(times) > 1 else 0.0,
    "avg_virtual_time_s": statistics.fmean([r["virtual_time_s"] for r in rows]),
    "avg_move_distance_km": statistics.fmean(
        [r["move_distance_m"] for r in rows]) / 1000.0,
    "avg_mean_move_distance_km": statistics.fmean(
        [r["mean_move_distance_m"] for r in rows]) / 1000.0,
    "avg_measures": statistics.fmean([r["measures"] for r in rows]),
    "avg_clears": statistics.fmean([r["clears"] for r in rows]),
    "avg_failed_clears": statistics.fmean([r["failed_clears"] for r in rows]),
    "cases_with_unresolved": sum(1 for r in rows if r["unresolved"]),
}
print("\n=== 汇总 ===")
for k, v in summary.items():
    print(f"{k}: {v}")

os.makedirs(os.path.join(ROOT, "results"), exist_ok=True)
suffix = f"_{args.label}" if args.label else ""
out = os.path.join(ROOT, "results",
                    f"mock_p{args.problem}{suffix}_experiments.json")
with open(out, "w", encoding="utf-8") as fh:
    json.dump({"summary": summary, "rows": rows}, fh, ensure_ascii=False, indent=2)
print(f"\n已写入 {out}")

if __name__ == "__main__":
    main()

```

B.65 scripts/run_simulator.py

"""接入真实模拟器（jammers-simulator.exe）运行问题3 策略。

使用流程（详见 README / 本文件末尾说明）

1. 双击运行模拟器 -> 联网登录（参赛队号/队员姓名/手机号 + 密码）；
2. 在模拟器中选择“问题3 演练测试”（演练不限次数）或“问题3 正式测试”（仅3次），建议保持默认端口2026，点击开始，等待5秒倒计时结束、界面提示接口就绪；
3. 运行本脚本：


```
python scripts/run_simulator.py --robot-id <参赛队号> [--port 2026]
```

 脚本会等待接口开放、调用 /enter，随后自动完成扫描-定位-清除并 /exit；
4. 演练结束后在模拟器界面核对“干扰源总数/清除个数”（正式测试不显示真值，但会记录测试案例编码与加密行为日志，需导出放入支撑材料）。

安全保护

* 现实时间预算（默认按 /enter 返回的 remaining_real_duration_s，留60s余量）

```

    超时即停止动作并 /exit，避免 20 分钟程序运行超时；
* 每条请求/响应写入 logs/ 下的 JSONL 行为日志（自建，可作支撑材料）；
* 接口未开放时连接会失败：脚本自动轮询重试，不对连接失败做任何状态变更。
"""

from __future__ import annotations

import argparse
import json
import os
import random
import sys
import time
from typing import Any, Dict, Optional, Tuple

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.config import DEFAULT_BASE_URL # noqa: E402
from src.robot_client import RobotClient, ProtocolError # noqa: E402
from src.simulator_truth import ( # noqa: E402
    DEFAULT_SIM_DATA_DIR,
    wait_for_result_after,
)
from src.strategy_p3 import StrategyP3 # noqa: E402
from src.strategy_p4 import StrategyP4 # noqa: E402

class TimeBudgetExceeded(RuntimeError):
    """现实时间预算耗尽：立即停止动作并优雅退出。"""

class LoggingTransport:
    """包装 RobotClient：写 JSONL 行为日志 + 现实时间预算 + 统计。"""

    def __init__(self, client: RobotClient, log_path: str,
                 budget_s: Optional[float] = None) -> None:
        self.client = client
        self.log_path = log_path
        self._fh = open(log_path, "w", encoding="utf-8")
        self.budget_s = budget_s
        self._t0 = time.perf_counter()
        self.counts: Dict[str, int] = {"measure": 0, "clear": 0, "clear_success": 0,
                                       "clear_fail": 0, "direction": 0, "near": 0,
                                       "no_signal": 0}
        self.cleared_channels: set = set()
        self.unresolved_measures: int = 0

    # ----- #
    def _remaining(self) -> Optional[float]:
        if self.budget_s is None:
            return None
        return self.budget_s - (time.perf_counter() - self._t0)

    def _check_budget(self) -> None:
        remaining = self._remaining()
        if remaining is not None and remaining <= 0:
            raise TimeBudgetExceeded("现实时间预算耗尽")

    def _log(self, path: str, payload: Dict[str, Any],
            response: Dict[str, Any]) -> None:
        self._fh.write(json.dumps({
            "ts": time.time(),
            "path": path,
            "request": payload,
            "response": response,
            "local_virtual_time_s": round(self.client.virtual_time, 6),
        }, ensure_ascii=False) + "\n")
        self._fh.flush()

    # ----- #
    def enter(self) -> Dict[str, Any]:
        resp = self.client.enter()
        self.adopt_enter_response(resp)
        return resp

    def adopt_enter_response(self, resp: Dict[str, Any]) -> None:

```

```

"""/enter 已由外部（等待接口就绪流程）完成时，同步日志与时间预算。"""
self._log("/enter", {"request_id": "enter"}, resp)
remaining = resp.get("remaining_real_duration_s")
if isinstance(remaining, (int, float)):
    # 预留 60 s 收尾（最后一条动作登记 + 退出）
    self.budget_s = min(self.budget_s or float("inf"),
                        max(float(remaining) - 60.0, 5.0))
    self._t0 = time.perf_counter()

def measure(self, position: Tuple[float, float], channel: int) -> Dict[str, Any]:
    self._check_budget()
    resp = self.client.measure(position, channel)
    self.counts["measure"] += 1
    kind = resp.get("measure_result")
    if kind in self.counts:
        self.counts[kind] += 1
    elif resp.get("accepted") is False:
        self.unresolved_measures += 1
    self._log("/measure", {"position": position, "channel": channel}, resp)
    return resp

def clear(self, position: Tuple[float, float], channel: int) -> Dict[str, Any]:
    self._check_budget()
    resp = self.client.clear(position, channel)
    self.counts["clear"] += 1
    if resp.get("clear_result") == "success":
        self.counts["clear_success"] += 1
        self.cleared_channels.add(channel)
    else:
        self.counts["clear_fail"] += 1
    self._log("/clear", {"position": position, "channel": channel}, resp)
    return resp

def exit(self) -> Dict[str, Any]:
    resp = self.client.exit()
    self._log("/exit", {"request_id": "exit"}, resp)
    return resp

def close(self) -> None:
    try:
        self._fh.close()
    except Exception:
        # pragma: no cover - 关闭失败不致命
        pass

@property
def cleared_count(self) -> int:
    return len(self.cleared_channels)

@property
def wall_time_s(self) -> float:
    return time.perf_counter() - self._t0

@property
def clock(self):
    """把内部 RobotClient 的虚拟时钟暴露给策略。

    策略的 ``_current_position`` / ``_move_distance`` 通过
    ``transport.clock`` 读取真实位置与行程，包装层必须透明转发，
    否则机会式清除的绕行距离会按 (0,0) 估算而失真。
    """
    return self.client.clock

def wait_for_interface(client: RobotClient, timeout_s: float = 600.0,
                      poll_s: float = 3.0) -> Dict[str, Any]:
    """等待模拟器接口开放并完成 /enter。

    5 秒倒计时期间、测试未开始或已结束时接口未开放，连接会直接失败，
    因此这里对 ConnectionError 轮询重试；一旦 enter 成功立即返回响应。
    """
    deadline = time.perf_counter() + timeout_s
    attempt = 0
    while time.perf_counter() < deadline:
        attempt += 1
        try:
            resp = client.enter()
        except (ConnectionError, ProtocolError) as exc:
            print(f"等待接口 第 {attempt} 次连接未就绪 ({type(exc).__name__}), "

```

```

        f"{poll_s:.0f}s 后重试...")
        time.sleep(poll_s)
        continue
    if resp.get("accepted") is True:
        print(f"[等待接口] /enter 成功, 剩余现实时间 "
              f"{resp.get('remaining_real_duration_s')} s")
        return resp
    print(f"[等待接口] /enter 未被接受: {resp}, {poll_s:.0f}s 后重试...")
    time.sleep(poll_s)
raise TimeoutError("等待模拟器接口就绪超时 (请确认已开始测试且倒计时已结束)")

def build_mock_client(robot_id: str, seed: int, n: Optional[int]) -> Tuple[Any, Any, str]:
    """离线自检模式: 启动本地 MockServer, 用于验证脚本本链路 (不消耗测试机会)。"""
    from src.mock_server import MockServer
    from src.mock_simulator import MockSimulator, random_case

    sim = MockSimulator(random_case(n=n, seed=seed), seed=seed)
    server = MockServer(sim, robot_id=robot_id).start()
    client = RobotClient(robot_id=robot_id, base_url=server.base_url)
    return server, client, server.base_url

def main() -> None:
    parser = argparse.ArgumentParser(description="CUMCM2026 B 题 问题 3/4 运行器")
    parser.add_argument("--problem", type=int, default=3, choices=[3, 4],
                        help="问题号: 3=全向, 4=全向+定向混合")
    parser.add_argument("--robot-id", required=True, help="参赛队号 (须与模拟器登录一致)")
    parser.add_argument("--host", default="127.0.0.1", help="模拟器地址 (默认本机)")
    parser.add_argument("--port", type=int, default=2026, help="模拟器端口 (默认 2026)")
    parser.add_argument("--base-url", default=None,
                        help="完整接口地址 (提供后忽略 --host/--port)")
    parser.add_argument("--max-seconds", type=float, default=None,
                        help="自设现实时间预算 (秒): 默认使用 /enter 返回的剩余时间-60s")
    parser.add_argument("--ready-timeout", type=float, default=600.0,
                        help="等待接口就绪的最长时间 (秒)")
    parser.add_argument("--expected-total", type=int, default=0,
                        help="干扰源总数 (留空则自动读取演练结果文件)")
    parser.add_argument("--case-code", default=None,
                        help="测试案例编码 (正式测试从界面抄录)")
    parser.add_argument("--sim-data-dir", default=DEFAULT_SIM_DATA_DIR,
                        help="模拟器数据目录 (用于自动读取演练真值)")
    parser.add_argument("--no-auto-truth", action="store_true",
                        help="不读取演练结果文件")
    parser.add_argument("--mock", action="store_true",
                        help="离线自检: 本地起 MockServer, 不连接真实模拟器")
    parser.add_argument("--mock-seed", type=int, default=0)
    parser.add_argument("--mock-n", type=int, default=None)
    parser.add_argument("--log-dir", default=os.path.join(ROOT, "logs"))
    args = parser.parse_args()

    os.makedirs(args.log_dir, exist_ok=True)
    stamp = time.strftime("%Y%m%d_%H%M%S")
    log_path = os.path.join(args.log_dir, f"p{args.problem}_run_{stamp}.jsonl")

    server = None
    if args.mock:
        server, client, base_url = build_mock_client(args.robot_id, args.mock_seed, args.mock_n)
        print(f"[离线自检] MockServer: {base_url}")
    else:
        base_url = args.base_url or f"http://{args.host}:{args.port}"
        client = RobotClient(robot_id=args.robot_id, base_url=base_url)
        print(f"[连接真实模拟器] {base_url} (robot_id={args.robot_id})")

    transport = LoggingTransport(client, log_path, budget_s=args.max_seconds)
    run_started_epoch = time.time()
    status = "completed"
    result = None
    try:
        enter_resp = wait_for_interface(client, timeout_s=args.ready_timeout)
        # /enter 已由等待流程完成: 同步日志与时间预算, 策略内不再重复 enter
        transport.adopt_enter_response(enter_resp)
        strategy_cls = StrategyP3 if args.problem == 3 else StrategyP4
        result = strategy_cls().run(transport, do_enter=False)
    except TimeBudgetExceeded:
        status = "time_budget_exceeded"
        print("[警告] 现实时间预算耗尽, 提前结束并退出。")

```

```

try:
    transport.exit()
except Exception as exc:      # pragma: no cover
    print(f"[警告] /exit 失败: {exc}")
except Exception as exc:      # noqa: BLE001 - 兜底保证退出
    status = f"error:{type(exc).__name__}"
    print(f"[错误] {exc}")
    try:
        transport.exit()
    except Exception:          # pragma: no cover
        pass
finally:
    transport.close()
    if server is not None:
        server.stop()

cleared = transport.cleared_count if result is None else max(result.cleared,
transport.cleared_count)
avg_time = (client.virtual_time / cleared) if cleared else float("inf")

# ----- 演练真值（干扰源总数 / 案例编码）：仅演练测试可得 -----
truth = None
if not args.mock and not args.no_auto_truth:
    truth = wait_for_result_after(args.sim_data_dir, since_mtime=run_started_epoch,
                                problem_no=args.problem, timeout_s=20.0)

    if truth is None:
        print("[真值] 未找到本次结果文件（正式测试不提供真值；或数据目录不一致，"
            "可用 --expected-total 手动指定）")
if truth is not None:
    print(f"[真值] 案例编码 {truth.get('case_code')}, 干扰源总数 {truth.get('jammer_count')}"
        f"（全向 {truth.get('omnidirectional_jammer_count')}, "
        f"定向 {truth.get('directional_jammer_count')}）")
    expected_total = args.expected_total or (int(truth["jammer_count"]) if truth else None)
    case_code = args.case_code or (truth.get("case_code") if truth else None)
    truth_clean = None if truth is None else {k: v for k, v in truth.items()
        if not k.startswith("_")}
    report = {
        "status": status,
        "problem_no": args.problem,
        "robot_id": args.robot_id,
        "base_url": base_url,
        "cleared_jammers": cleared,
        "expected_total": expected_total,
        "case_code": case_code,
        "truth": truth_clean,
        "clearance_ratio": (cleared / expected_total) if expected_total else None,
        "total_virtual_time_s": client.virtual_time,
        "mean_clear_time_s": avg_time,
        "program_run_time_s": round(transport.wall_time_s, 3),
        "counts": transport.counts,
        "unresolved": [] if result is None else result.unresolved,
        "log_file": log_path,
        "audit_warnings": client.audit_warnings,
    }
    print("\n=== 本次运行结果 ===")
    for key, value in report.items():
        print(f"{key}: {value}")

    out = os.path.join(ROOT, "results", f"p{args.problem}_run_{stamp}.json")
    os.makedirs(os.path.dirname(out), exist_ok=True)
    with open(out, "w", encoding="utf-8") as fh:
        json.dump(report, fh, ensure_ascii=False, indent=2)
    print(f"\n结果: {out}\n行为日志: {log_path}")

if __name__ == "__main__":
    main()

```

B.66 scripts/verify_theory.py

"""理论常数的数值验证脚本（论文“模型检验”章节的原始数据来源）。

验证三项关键结论：

- 1) 覆盖布点：7 点构造方案 worst-case 覆盖距离 < 1000 m；
6 点全局最优 > 1000 m（与 Bezdek 经典阈值 1.7988 一致）→ 最少 7 点；
- 2) 问题 2 最优基线：定位区域面积 / det(FIM) 均在 $b = d_1$ （交会角 45° ）处最优，
而非经文献常引的 90° （因本题角度误差导致楔形宽度随距离线性增长）；

- 3) 问题 1 覆盖性: 两站定位区域(平行四边形)必被"直径圆"覆盖;
锐角三角形定位区域则不能(反例)。

用法: python -m scripts.verify_theory 或直接 python scripts/verify_theory.py

```

"""
from __future__ import annotations

import json
import math
import os
import sys

import numpy as np

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

from src.config import EPS_DEG, REGION_RADIUS, R_MIN          # noqa: E402
from src.coverage import (                                     # noqa: E402
    directional_certificate,
    directional_coverage_ok,
    directional_survey_design,
    hexagonal_design,
    optimize_cover_radius,
    seven_point_design,
    worst_case_radius,
)
from src.geometry import (                                     # noqa: E402
    bearing_between,
    diameter_circle_covers,
    localization_region,
    polygon_area,
)

def verify_coverage() -> dict:
    design7 = seven_point_design(ring_radius=1400.0, k=6)
    hex7 = hexagonal_design(r_min=R_MIN)
    wc7 = worst_case_radius(design7, REGION_RADIUS,
                            n_interior=30000, n_boundary=30000, seed=123)
    wc_hex = worst_case_radius(hex7, REGION_RADIUS,
                                n_interior=30000, n_boundary=30000, seed=123)
    print(f"[1] 7 点方案(中心+环 1400) worst-case 覆盖距离 = {wc7:.3f} m (需 <= {R_MIN})")
    print(f"[1] 7 点方案(六边形 sqrt(3)*1000) worst-case 覆盖距离 = {wc_hex:.3f} m")

    r6, pts6 = optimize_cover_radius(6, REGION_RADIUS, n_objective=1500, seed=11,
                                      maxiter=45, popsize=10,
                                      init_guesses=[design7[1:]])
    print(f"[1] 6 点最优最小覆盖半径 = {r6:.3f} m (需 > {R_MIN}) -> 6 点不可行")

    r7, pts7 = optimize_cover_radius(7, REGION_RADIUS, n_objective=1500, seed=13,
                                      maxiter=45, popsize=10,
                                      init_guesses=[design7, hex7])
    print(f"[1] 7 点最优最小覆盖半径 = {r7:.3f} m (需 <= {R_MIN}) -> 7 点可行")
    return {
        "seven_point_design_worst_case_m": wc7,
        "hexagonal_design_worst_case_m": wc_hex,
        "optimal_6_cover_radius_m": r6,
        "optimal_7_cover_radius_m": r7,
        "ratio_1800_1000": REGION_RADIUS / R_MIN,
        "bezdek_threshold_6": 1.7988,
        "bezdek_threshold_7": 2.0,
        "min_points_for_coverage": 7,
    }

def verify_problem2(d1: float = 1000.0, d_lo: float = 300.0, d_hi: float = 5000.0) -> dict:
    """第二检测点: 比较定位区域面积与 det(FIM) 关于基线 b 的曲线。

    设 S1=(0,0), 目标真值 G=(d1,0), 第二点 S2=(0,b) (垂直于示向度方向)。
    则 d2=sqrt(d1^2+b^2), 交会角 sin(theta)=b/d2。
    * 定位区域面积 A(b) = 4*tan^2(eps)*d1*d2/sin(theta)
    * det(FIM) ∝ (sin(theta)/(d1*d2))^2
    理论最优 b* = d1 (交会角 45°)。
    """
    eps = math.radians(EPS_DEG)

```

```

bs = np.linspace(d1 * 0.2, d1 * 3.0, 4000)
d2 = np.sqrt(d1 ** 2 + bs ** 2)
sin_th = bs / d2
area = 4.0 * (math.tan(eps) ** 2) * d1 * d2 / sin_th
det_fim = (sin_th / (d1 * d2)) ** 2

b_area = float(bs[int(np.argmin(area))])
b_fim = float(bs[int(np.argmax(det_fim))])
theta_star = math.degrees(math.atan2(b_area, d1))
print(f"[2] d1={d1:.0f} m: 面积最优 b*={b_area:.1f} m, det(FIM) 最优 b*={b_fim:.1f} m, "
      f"最优交会角 theta*={theta_star:.2f} deg (理论 45 deg)")
return {
    "d1": d1,
    "b_star_area": b_area,
    "b_star_fim": b_fim,
    "theta_star_deg": theta_star,
    "theoretical_b_star": d1,
    "theoretical_theta_deg": 45.0,
}

def verify_problem1() -> dict:
    jammer = (620.0, 430.0)
    s1, s2 = (0.0, 0.0), (900.0, -200.0)
    poly = localization_region([s1, s2], [bearing_between(s1, jammer),
                                           bearing_between(s2, jammer)])

    info = diameter_circle_covers(poly)
    acute = [(0.0, 0.0), (1.0, 0.0), (0.5, math.sqrt(3) / 2.0)]
    info_acute = diameter_circle_covers(acute)
    print(f"[3] 两站定位区域: 顶点数={len(poly)}, 面积={polygon_area(poly):.1f} m^2, "
          f"直径圆覆盖={info['covered']}")
    print(f"[3] 锐角三角形反例: 直径圆覆盖={info_acute['covered']} (应为 False), "
          f"最小覆盖圆半径={info_acute['mec_radius']:.4f}")
    return {
        "two_station_vertices": len(poly),
        "two_station_area": polygon_area(poly),
        "two_station_covered": info["covered"],
        "two_station_diameter": info["diameter"],
        "acute_triangle_covered": info_acute["covered"],
        "acute_triangle_mec_radius": info_acute["mec_radius"],
    }

def verify_problem3_design() -> dict:
    """问题 3 运行布点: 中心 + 1000 m 七均布 (8 点) 的解析最坏覆盖距离。"""
    k, ring = 7, 1000.0
    worst = math.sqrt(REGION_RADIUS ** 2 + ring ** 2
                     - 2.0 * REGION_RADIUS * ring * math.cos(math.pi / k))
    mc = worst_case_radius(seven_point_design(ring, k), REGION_RADIUS)
    print(f"[3] 运行布点 8 点 (中心 + {ring:.0f}m 七均布): 解析最坏覆盖距离 "
          f"= {worst:.3f} m (< {R_MIN:.0f}); 蒙特卡洛 {mc:.3f} m")
    return {
        "design_points": k + 1,
        "ring_radius_m": ring,
        "analytic_worst_case_m": worst,
        "monte_carlo_worst_case_m": mc,
        "margin_m": R_MIN - worst,
    }

def verify_problem4() -> dict:
    """问题 4: 定向覆盖条件的数值验证 + 双环网的解析/确定性证书。"""
    design = directional_survey_design()
    r7 = directional_coverage_ok(seven_point_design(1400.0, 6), n_samples=4000, seed=3)
    r4 = directional_coverage_ok(design, n_samples=20000, seed=7)
    omni = worst_case_radius(design, REGION_RADIUS, n_interior=20000, n_boundary=20000)
    cert = directional_certificate(design)
    edges = {
        "center_inner": 950.0,
        "inner_edge": 2.0 * 950.0 * math.sin(math.pi / 12.0),
        "outer_edge": 2.0 * 1875.0 * math.sin(math.pi / 12.0),
        "cross_edge": math.sqrt(950.0 ** 2 + 1875.0 ** 2
                                - 2.0 * 950.0 * 1875.0 * math.cos(math.pi / 12.0)),
    }
    outer_inradius = 1875.0 * math.cos(math.pi / 12.0)
    print(f"[4] 问题 3 的 7 点方案定向通过率 = {r7['ok_ratio']:.4f} (不满足)")
    print(f"[4] 双环网 {len(design)} 点: 抽样通过率 = {r4['ok_ratio']:.4f}; "
          f"确定性证书 ok={cert['ok']}, fail={cert['fail']}, ")

```

```

        f"最大角隙 = {cert['max_gap_deg']:.2f}° (< 180°) ")
    print(f"[4] 三角剖分: 外环内切半径 {outer_inradius:.2f} m (> {REGION_RADIUS:.0f}), "
          f"最长边 {max(edges.values()):.2f} m (< {R_MIN:.0f}); "
          f"全向最坏覆盖距离 {omni:.1f} m")
    return {
        "seven_point_directional_pass_ratio": r7["ok_ratio"],
        "design_points": len(design),
        "directional_pass_ratio": r4["ok_ratio"],
        "certificate_ok": cert["ok"],
        "certificate_fail": cert["fail"],
        "certificate_max_gap_deg": cert["max_gap_deg"],
        "certificate_samples": cert["n_samples"],
        "triangulation_longest_edge_m": max(edges.values()),
        "outer_inradius_m": outer_inradius,
        "omni_worst_case_m": omni,
    }

def main() -> None:
    report = {
        "coverage": verify_coverage(),
        "problem3_design": verify_problem3_design(),
        "problem2": verify_problem2(),
        "problem1": verify_problem1(),
        "problem4": verify_problem4(),
    }
    out_dir = os.path.join(ROOT, "results")
    os.makedirs(out_dir, exist_ok=True)
    out_path = os.path.join(out_dir, "theory_verification.json")
    with open(out_path, "w", encoding="utf-8") as fh:
        json.dump(report, fh, ensure_ascii=False, indent=2)
    print(f"\n 结果已写入: {out_path}")

if __name__ == "__main__":
    main()

```

B.67 tests/confest.py

"""pytest 配置: 把项目根目录加入 sys.path, 使 `import src.xxx` 可用。"""

```

import os
import sys

ROOT = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
if ROOT not in sys.path:
    sys.path.insert(0, ROOT)

```

B.68 tests/test_client_server.py

"""端到端协议测试: RobotClient <-> MockServer (HTTP+JSON、幂等、未知字段、计时审计)。"""

```

import json

import pytest
import requests

from src.mock_server import MockServer
from src.mock_simulator import MockSimulator, random_case
from src.robot_client import RobotClient, ProtocolError

ROBOT_ID = "2026001"

def _load_run_simulator():
    """导入 scripts/run_simulator.py (脚本目录不在包路径内, 故显式加载)。"""
    import importlib.util
    import os

    root = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
    path = os.path.join(root, "scripts", "run_simulator.py")
    spec = importlib.util.spec_from_file_location("run_simulator_module", path)
    module = importlib.util.module_from_spec(spec)
    spec.loader.exec_module(module)
    return module

```

```

@pytest.fixture()
def env():
    sim = MockSimulator(random_case(n=3, seed=5), seed=5)
    srv = MockServer(sim, robot_id=ROBOT_ID).start()
    client = RobotClient(robot_id=ROBOT_ID, base_url=srv.base_url)
    yield sim, srv, client
    srv.stop()

def test_enter_measure_clear_exit_end_to_end(env):
    sim, srv, client = env
    enter = client.enter()
    assert enter["accepted"] is True

    first = sim.jammers[0]
    # 到该干扰源正上方测量（距离 0 -> near），再退到远处测量
    far_point = (first.x + 400.0, first.y)
    r = client.measure(far_point, first.channel)
    assert r["accepted"] is True
    assert r["measure_result"] in {"direction", "near", "no_signal"}

    # 直接在其 20m 内清除
    hit = client.clear((first.x + 10.0, first.y), first.channel)
    assert hit["clear_result"] == "success"
    assert sim.cleared_jammers == 1

    bye = client.exit()
    assert bye["exit_reason"] == "user_exit"
    # 本地虚拟时钟镜像必须与模拟器一致（协议与计时模型双向验证）
    assert client.audit_warnings == []
    assert client.virtual_time == pytest.approx(sim.virtual_time)

def test_logging_transport_exposes_client_clock(env, tmp_path):
    """LoggingTransport 必须把内部 RobotClient 的时钟透传给策略。

    机会式清除用 `transport.clock.position` 计算绕行距离，若包装层不透传，
    真实运行时会退化成“始终从 (0,0) 估算”，插入判据失真。
    """
    sim, srv, client = env
    module = _load_run_simulator()
    log_path = str(tmp_path / "run.jsonl")
    transport = module.LoggingTransport(client, log_path)
    try:
        transport.enter()
        transport.measure((300.0, 400.0), 1)
        # 时钟透传：位置与虚拟时间都能从包装层读到
        assert transport.clock is client.clock
        assert transport.clock.position == pytest.approx((300.0, 400.0))
        assert transport.clock.virtual_time == pytest.approx(105.0)
        # 策略侧的移动距离统计也应能读通
        from src.strategy_p3 import StrategyP3

        assert StrategyP3._move_distance(transport) == pytest.approx(500.0)
        assert StrategyP3._current_position(transport) == pytest.approx((300.0, 400.0))
    finally:
        transport.close()

def test_unknown_field_is_rejected_with_accepted_false(env):
    sim, srv, client = env
    client.enter()
    payload = client._base_payload("test-unknown")
    payload["position"] = {"x": 0, "y": 0}
    payload["channel"] = 1
    payload["oops"] = 1
    resp = requests.post(srv.base_url + "/measure",
                        data=json.dumps(payload).encode(),
                        headers={"Content-Type": "application/json"}, timeout=5)
    assert resp.status_code == 200
    assert resp.json()["accepted"] is False

def test_wrong_robot_id_rejected(env):
    sim, srv, client = env
    payload = {"arena_id": "default", "robot_id": "bad", "request_id": "x1"}
    resp = requests.post(srv.base_url + "/enter", data=json.dumps(payload).encode(),
                        headers={"Content-Type": "application/json"}, timeout=5)

```

```

    assert resp.json()["accepted"] is False

def test_unknown_path_returns_404(env):
    sim, srv, client = env
    resp = requests.post(srv.base_url + "/oops", data=b "{}",
                        headers={"Content-Type": "application/json"}, timeout=5)
    assert resp.status_code == 404

def test_bad_channel_returns_400(env):
    sim, srv, client = env
    client.enter()
    payload = client._base_payload("bad-channel")
    payload["position"] = {"x": 0, "y": 0}
    payload["channel"] = 1.5 # 非整数
    resp = requests.post(srv.base_url + "/measure", data=json.dumps(payload).encode(),
                        headers={"Content-Type": "application/json"}, timeout=5)
    assert resp.status_code == 400

def test_out_of_range_channel_returns_400(env):
    sim, srv, client = env
    client.enter()
    payload = client._base_payload("bad")
    payload["position"] = {"x": 0, "y": 0}
    payload["channel"] = 99 # 超出 1..20 -> HTTP 400 (与真实模拟器一致)
    resp = requests.post(srv.base_url + "/measure", data=json.dumps(payload).encode(),
                        headers={"Content-Type": "application/json"}, timeout=5)
    assert resp.status_code == 400
    assert resp.json()["accepted"] is False

def test_client_raises_protocol_error_on_http_400(env):
    sim, srv, client = env
    client.enter()
    with pytest.raises(ProtocolError):
        client.measure((0.0, 0.0), 99)

```

B.69 tests/test_coverage.py

"""覆盖布点测试：验证问题 3“最少 7 个检测点”的可证明下界与构造性方案。

理论依据 (Bezdek 1979/1983, 转引自 Fejes Tóth 2005) :

- * 6 个等圆最多覆盖半径比 1.7988... 的大圆；
- * 7 个等圆可达 2.0。

本题半径比 = $1800/1000 = 1.8$, 落在 $(1.7988, 2.0]$, 故最少检测点数为 7。

本测试用数值实验交叉验证：

- * 构造性 7 点方案的最坏覆盖距离 < 1000 m (可行)；
- * 全局优化 6 点的最小覆盖半径 > 1000 m (不可能)。

"""

import pytest

```

from src.config import REGION_RADIUS, R_MIN
from src.coverage import (
    optimize_cover_radius,
    sample_disk,
    seven_point_design,
    worst_case_radius,
)

```

```

def test_seven_point_design_covers_region_with_margin():
    pts = seven_point_design(ring_radius=1400.0, k=6)
    assert len(pts) == 7
    wc = worst_case_radius(pts, REGION_RADIUS, n_interior=8000, n_boundary=8000)
    assert wc < R_MIN, f"7 点方案必须保证覆盖, 实测最坏距离 {wc:.2f} m"
    assert wc < 950.0, f"7 点方案应有裕量, 实测 {wc:.2f} m"

```

```

def test_boundary_ratio_threshold():
    """半径比 1800/1000 = 1.8 恰在 6 圆 (1.7988) 与 7 圆 (2.0) 阈值之间。

```

```

    即: 6 个半径 1000 m 的圆最多覆盖 1798.8 m 半径的圆域 (< 1800),
    7 个可达 2000 m (>= 1800) — 故最少 7 个检测点。
    """

```

```

ratio = REGION_RADIUS / R_MIN          # = 1.8
six_threshold = 1.7988                  # Bezdek 1979 证明
seven_threshold = 2.0                   # 平凡六边形构造
assert six_threshold < ratio <= seven_threshold
assert 1000.0 * seven_threshold >= REGION_RADIUS      # 7 点可行
assert 1000.0 * six_threshold < REGION_RADIUS        # 6 点不可行

def test_six_points_cannot_cover_region_numerically():
    """数值优化 6 个点: 最小覆盖半径应 > 1000 m (与经典结论一致)。"""
    best_radius, pts = optimize_cover_radius(
        6, REGION_RADIUS, n_objective=2000, seed=7, maxiter=25, popsize=10)
    assert pts.shape == (6, 2)
    assert best_radius > R_MIN, f"6 点最小覆盖半径 {best_radius:.2f} m 应超过 1000 m"

def test_sample_disk_within_region():
    import numpy as np

    s = sample_disk(5000, REGION_RADIUS, seed=1)
    r = np.linalg.norm(s, axis=1)
    assert r.max() <= REGION_RADIUS + 1e-9
    assert r.mean() == pytest.approx(2.0 * REGION_RADIUS / 3.0, rel=0.05)

```

B.70 tests/test_design_analysis.py

```

"""问题 1/2/3 的设计分析测试 (对应 scripts/analyze_designs.py)。"""

import importlib.util
import math
import os

import pytest

from src.config import REGION_RADIUS, R_MIN
from src.coverage import seven_point_design, worst_case_radius

def _load():
    root = os.path.dirname(os.path.dirname(os.path.abspath(__file__)))
    path = os.path.join(root, "scripts", "analyze_designs.py")
    spec = importlib.util.spec_from_file_location("analyze_designs_module", path)
    module = importlib.util.module_from_spec(spec)
    spec.loader.exec_module(module)
    return module

AD = _load()

# ----- 布站准则 (45° vs 54.74°) ----- #
def test_alpha_family_recovers_both_criteria():
    """ $b^* = d1/\sqrt{\alpha}$ :  $\alpha=1 \rightarrow 45^\circ$  (本题有界误差模型);  $\alpha=1/2 \rightarrow 54.74^\circ (= \sqrt{2} \cdot d1)$ 。"""
    b1 = AD.optimal_b_analytic(1000.0, 1.0)
    assert b1 == pytest.approx(1000.0)
    assert math.degrees(math.atan2(b1, 1000.0)) == pytest.approx(45.0, abs=1e-9)

    b2 = AD.optimal_b_analytic(1000.0, 0.5)
    assert b2 == pytest.approx(1000.0 * math.sqrt(2.0), rel=1e-12)
    assert math.degrees(math.atan2(b2, 1000.0)) == pytest.approx(54.7356, abs=1e-3)

def test_optimal_b_analytic_matches_numeric_scan():
    for alpha in (0.5, 2.0 / 3.0, 1.0, 1.5, 2.0):
        analytic = AD.optimal_b_analytic(1000.0, alpha)
        numeric = AD.optimal_b_numeric(1000.0, alpha)
        assert numeric == pytest.approx(analytic, abs=2.0), alpha

def test_minimax_baseline_is_robust_across_alpha():
    """极小极大稳健基线应落在两种准则之间, 且最坏面积惩罚 < 1.06。"""
    report = AD.analyse_criteria()
    b = report["minimax"]["b"]
    assert 1000.0 <= b <= 1414.3
    assert report["minimax"]["penalty"] < 1.06
    # 机动成本越大, 最优基线越短 (与"移动代价变高则基线缩短"一致)
    rows = report["move_cost"]

```

```

assert rows[0]["b_star"] >= rows[-1]["b_star"]

# ----- 问题3 覆盖环 ----- #
def test_ring_radius_min_matches_known_cases():
    """k=6 时最小环半径 1123 m (交点恰在 1800 圆周上), k=7 时 997 m。

    这正是"把相邻覆盖圆的交点放到 1800 m 圆周上"的解析解: 环数越少,
    交点约束要求环半径越大 (6 点必须放到 1123 m, 比 7 点的 997 m 更远)。
    """
    a6 = AD.ring_radius_min(6)
    a7 = AD.ring_radius_min(7)
    assert a6 == pytest.approx(1122.5, abs=1.0)
    assert a7 == pytest.approx(997.2, abs=1.0)
    assert a6 > a7, "点数越少, 环半径必须越大 (与直觉相反)"

def test_ring_radius_min_is_monotone_and_bounded():
    """a_min(k) 随 k 单调减小, 下界为 1800-1000 = 800 m (对准边界点的极限)。"""
    values = [AD.ring_radius_min(k) for k in (6, 7, 8, 10, 12, 14, 16, 20, 40)]
    assert all(a > 800.0 for a in values)
    assert all(b <= a + 1e-9 for a, b in zip(values, values[1:]))
    assert AD.ring_radius_min(200) == pytest.approx(800.0, abs=2.0)

def test_outer_intersection_variant_equals_analytic_min_radius():
    """『相邻覆盖圆外侧交点落在 R=1800 圆周上』与 a_min(k) 解析式等价。"""
    rows = AD.analyse_intersection_variant()
    for k in (6, 7, 8):
        assert rows[k]["a_numeric"] == pytest.approx(rows[k]["a_analytic"], abs=0.5)
        # 该构造下覆盖恰好"卡"在 1000 m (零裕量)
        assert rows[k]["worst_case_m"] == pytest.approx(R_MIN, abs=0.05)

def test_six_ring_points_must_be_further_out_and_tour_is_longer():
    """关键结论: 6 点的外侧交点构造要求环半径 1123 m (> 7 点的 997 m), 巡游更长。

    即"让外侧交点落在 1800 圆周上"这一约束把环**往外推**, 而不是拉近圆心。
    """
    rows = AD.analyse_intersection_variant()
    assert rows[6]["a_analytic"] > rows[7]["a_analytic"] > rows[8]["a_analytic"]
    assert rows[6]["tour_m"] > rows[7]["tour_m"] > rows[8]["tour_m"]

def test_boundary_point_grows_with_angle_gap():
    """环点到边界角平分点的距离随角隙  $\pi/k$  增大而增大——这就是"点数越少环越远"的原因。"""
    def reach(a, k):
        return math.sqrt(REGION_RADIUS ** 2 + a ** 2
                        - 2 * REGION_RADIUS * a * math.cos(math.pi / k))

    for a in (900.0, 1000.0, 1100.0):
        assert reach(a, 6) > reach(a, 7) > reach(a, 8)
    # 当前采用 a=1000、k=7: 边界 998.25 m 有裕量, 且中心点也覆盖原点
    assert reach(1000.0, 7) == pytest.approx(998.2545, abs=1e-3)
    assert reach(1000.0, 7) < R_MIN

    """取 a_min(k) 的环 + 中心点, 数值复核最坏最近距离均 <= R_min。"""
    from src.coverage import seven_point_design as design

    for k in (6, 7, 8, 12):
        pts = design(AD.ring_radius_min(k), k)
        wc = worst_case_radius(pts, REGION_RADIUS, 4000, 4000)
        assert wc <= R_MIN + 1e-6, (k, wc)

def test_analytic_min_radius_matches_numeric_coverage():
    """解析 a_min 处最坏最近距离≈1000: 略小一点就不再覆盖 (紧致性)。"""
    a = AD.ring_radius_min(7)
    tight = seven_point_design(a, 7)
    loose = seven_point_design(a * 0.96, 7)
    assert worst_case_radius(tight, REGION_RADIUS, 6000, 6000) <= R_MIN
    assert worst_case_radius(loose, REGION_RADIUS, 6000, 6000) > R_MIN

# ----- 问题1 蒙特卡洛 ----- #
def test_monte_carlo_reports_coverage_by_station_count():
    mc = AD.monte_carlo_problem1(n_cases=600, seed=11)

```

```

assert set(mc) == {2, 3, 4}
# 2 站（纯楔形交为平行四边形）覆盖率最高，站数越多越可能失效
assert mc[2]["coverage_ratio"] >= mc[3]["coverage_ratio"]
assert mc[2]["coverage_ratio"] > 0.95
# 失效构型的半径超出量是米级
assert mc[3]["excess_median_m"] < 1.0

```

B.71 tests/test_geometry.py

"""几何库测试：交会定位区域、直径算法、最小覆盖圆、问题 1 的覆盖性结论。"""

```

import math
import random

import pytest

from src.geometry import (
    angle_diff,
    bearing_between,
    circle_covers_polygon,
    convex_hull,
    diameter_circle_covers,
    distance,
    localization_region,
    min_enclosing_circle,
    normalize_deg,
    polygon_area,
    polygon_diameter_bruteforce,
    polygon_diameter_calipers,
    wedge_halfplanes,
)
from src.config import EPS_DEG

# ----- #
# 角度工具
# ----- #
def test_angle_tools():
    assert normalize_deg(-30.0) == pytest.approx(330.0)
    assert normalize_deg(370.0) == pytest.approx(10.0)
    assert angle_diff(1.0, 359.0) == pytest.approx(2.0)
    assert angle_diff(359.0, 1.0) == pytest.approx(-2.0)
    assert bearing_between((0.0, 0.0), (1.0, 0.0)) == pytest.approx(0.0)
    assert bearing_between((0.0, 0.0), (0.0, 1.0)) == pytest.approx(90.0)

# ----- #
# 楔形与半平面
# ----- #
def test_wedge_halfplanes_contain_bearing_direction():
    station = (100.0, -50.0)
    bearing = 37.0
    for ang_off in (-0.9, 0.0, 0.9):
        rad = math.radians(bearing + ang_off)
        p = (station[0] + 800.0 * math.cos(rad), station[1] + 800.0 * math.sin(rad))
        for hp in wedge_halfplanes(station, bearing, EPS_DEG):
            assert hp.contains(p), "楔形内部点应满足两个半平面"

    for ang_off in (-1.5, 1.5):
        rad = math.radians(bearing + ang_off)
        p = (station[0] + 800.0 * math.cos(rad), station[1] + 800.0 * math.sin(rad))
        assert not all(hp.contains(p) for hp in wedge_halfplanes(station, bearing, EPS_DEG))

# ----- #
# 辅助：凸多边形内部判定
# ----- #
def _point_in_convex(poly, p, tol=1e-9):
    n = len(poly)
    sign = 0
    for i in range(n):
        x1, y1 = poly[i]
        x2, y2 = poly[(i + 1) % n]
        cross = (x2 - x1) * (p[1] - y1) - (y2 - y1) * (p[0] - x1)
        cur = 0 if abs(cross) <= tol else (1 if cross > 0 else -1)
        if cur == 0:
            continue
        if sign == 0:
            sign = cur
        else:
            if sign != cur:
                return False
    return True

```

```

        sign = cur
    elif sign != cur:
        return False
    return True

def _circle2(a, b):
    c = ((a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0)
    return c, distance(a, b) / 2.0

# ----- #
# 问题 1 主结论: 两站定位区域是平行四边形, 且"直径圆"必能覆盖
# ----- #
def test_two_station_region_is_parallelogram_covered_by_diameter_circle():
    jammer = (620.0, 430.0)
    s1, s2 = (0.0, 0.0), (900.0, -200.0)
    b1 = bearing_between(s1, jammer)
    b2 = bearing_between(s2, jammer)
    poly = localization_region([s1, s2], [b1, b2])

    assert 3 <= len(poly) <= 4, "两站定位区域应为平行四边形"
    assert polygon_area(poly) > 0.0
    assert _point_in_convex(poly, jammer), "真值必落在定位区域内"

    info = diameter_circle_covers(poly)
    assert info["covered"] is True, "平行四边形情形下直径圆应能覆盖定位区域"
    assert info["diameter"] == pytest.approx(
        polygon_diameter_bruteforce(poly)[0], rel=1e-9)
    assert info["mec_radius"] <= info["circle_radius"] + 1e-9
    assert info["mec_radius"] >= info["circle_radius"] * (math.sqrt(3) / 2.0) - 1e-6

def test_three_station_region_counterexample_acute_triangle():
    """n>=3 时定位区域可以是锐角三角形, 此时"直径圆"不能覆盖。"""
    acute = [(0.0, 0.0), (1.0, 0.0), (0.5, math.sqrt(3) / 2.0)] # 等边三角形
    info = diameter_circle_covers(acute)
    assert info["diameter"] == pytest.approx(1.0)
    assert info["covered"] is False, "锐角三角形: 直径圆无法覆盖"
    assert info["mec_radius"] == pytest.approx(1.0 / math.sqrt(3.0), rel=1e-6)
    assert circle_covers_polygon(info["mec_center"], info["mec_radius"], acute)

def test_obtuse_and_right_triangle_covered_by_diameter_circle():
    """钝角/直角三角形: 直径圆必覆盖 (Thales 定理的直接推论)。"""
    for tri in [(0, 0), (4, 0), (1, 1)], [(0, 0), (3, 0), (3, 4)]:
        poly = [(float(a), float(b)) for a, b in tri]
        assert diameter_circle_covers(poly)["covered"] is True

# ----- #
# 直径算法: 旋转卡壳 vs 暴力
# ----- #
def test_calipers_matches_bruteforce_on_random_polygons():
    rng = random.Random(42)
    for _ in range(20):
        pts = [(rng.uniform(-500, 500), rng.uniform(-500, 500)) for _ in range(12)]
        hull = convex_hull(pts)
        if len(hull) < 3:
            continue
        d1, _, _ = polygon_diameter_calipers(hull)
        d2, _, _ = polygon_diameter_bruteforce(hull)
        assert d1 == pytest.approx(d2, rel=1e-9, abs=1e-9)

# ----- #
# 最小覆盖圆
# ----- #
def test_min_enclosing_circle_covers_and_is_tight():
    rng = random.Random(7)
    pts = [(rng.uniform(-300, 300), rng.uniform(-300, 300)) for _ in range(30)]
    c, r = min_enclosing_circle(pts)
    assert all(distance(c, p) <= r + 1e-9 for p in pts)

    best = float("inf")
    n = len(pts)
    for i in range(n):
        for j in range(i + 1, n):

```

```

        cc, rr = _circle2(pts[i], pts[j])
        if all(distance(cc, p) <= rr + 1e-9 for p in pts):
            best = min(best, rr)
    assert best >= r - 1e-6, "Welzl 结果不应大于任何可行覆盖圆"

# ----- #
# 随机压力测试: 真值必须落在交会定位区域内
# ----- #
def test_localization_region_contains_true_jammer_stress():
    rng = random.Random(2026)
    tested = 0
    while tested < 20:
        jammer = (rng.uniform(-1600, 1600), rng.uniform(-1600, 1600))
        if distance((0, 0), jammer) > 1700:
            continue
        stations, bearings = [], []
        for _ in range(2):
            while True:
                s = (rng.uniform(-1000, 1000), rng.uniform(-1000, 1000))
                if distance(s, jammer) > 50:
                    break
            stations.append(s)
            bearings.append(bearing_between(s, jammer) + rng.uniform(-1.0, 1.0))
        poly = localization_region(stations, bearings)
        assert poly, "交会区域不应为空"
        assert _point_in_convex(poly, jammer), "真值应落在定位区域内"
        tested += 1

```

B.72 tests/test_kinematics.py

"""虚拟时钟测试: 复现附件 1 表 2 的计时示例, 验证计时规则实现无误。"""

```

import pytest

from src.kinematics import VirtualClock, simulate_worked_example

def test_worked_example_totals():
    costs, final_time = simulate_worked_example()
    totals = [c.total_s for c in costs]
    assert totals == pytest.approx([105.0, 6.0, 83.0, 5.0]), "附件 1 表 2 的四步耗时"
    assert [c.move_s for c in costs] == pytest.approx([100.0, 0.0, 80.0, 0.0])
    assert [c.switch_s for c in costs] == pytest.approx([0.0, 1.0, 0.0, 0.0])
    assert [c.action_s for c in costs] == pytest.approx([5.0, 5.0, 3.0, 5.0])
    assert final_time == pytest.approx(199.0)

def test_clear_does_not_change_channel():
    clk = VirtualClock()
    clk.measure((300.0, 400.0), 2)
    assert clk.channel == 2
    clk.clear((300.0, 0.0), success=False, channel=3)
    assert clk.channel == 2, "/clear 的 channel 是目标干扰源频道, 不切换测向机"

def test_switch_cost_only_when_channel_changes():
    clk = VirtualClock()
    c1 = clk.measure((0.0, 0.0), 1)          # 初始频道 1, 同频道
    assert c1.switch_s == pytest.approx(0.0)
    c2 = clk.measure((0.0, 0.0), 20)        # 任意两频道切换均为 1s
    assert c2.switch_s == pytest.approx(1.0)
    c3 = clk.measure((0.0, 0.0), 2)
    assert c3.switch_s == pytest.approx(1.0)

def test_move_time_proportional_to_straight_line_distance():
    clk = VirtualClock()
    c = clk.measure((300.0, 400.0), 1)      # 500 m -> 100 s
    assert c.move_s == pytest.approx(100.0)
    c2 = clk.measure((300.0, 0.0), 1)      # 400 m -> 80 s
    assert c2.move_s == pytest.approx(80.0)
    assert clk.virtual_time == pytest.approx(100.0 + 5.0 + 80.0 + 5.0)

def test_success_clear_cost_is_5s_and_fail_is_3s():
    clk = VirtualClock()
    clk.measure((100.0, 0.0), 1)

```

```

t0 = clk.virtual_time
clk.clear((100.0, 0.0), success=True)
assert clk.virtual_time - t0 == pytest.approx(5.0)
t1 = clk.virtual_time
clk.clear((100.0, 0.0), success=False)
assert clk.virtual_time - t1 == pytest.approx(3.0)

def test_enter_exit_do_not_advance_clock():
    clk = VirtualClock()
    clk.enter()
    assert clk.virtual_time == 0.0
    clk.measure((500.0, 0.0), 1)
    t = clk.virtual_time
    clk.exit()
    assert clk.virtual_time == pytest.approx(t)

```

B.73 tests/test_mock_simulator.py

"""Mock 模拟器物理规则测试：检测三态、定向覆盖、清除规则、计时一致性。"""

```

import math

import pytest

from src.geometry import angle_diff, bearing_between, distance
from src.mock_simulator import Jammer, MockSimulator, random_case

def make_sim():
    jammers = [
        Jammer(channel=1, x=300.0, y=400.0, r_eff=1500.0), # 全向
        Jammer(channel=2, x=-500.0, y=0.0, r_eff=1500.0, direction=0.0), # 定向朝东
        Jammer(channel=3, x=0.0, y=1700.0, r_eff=1200.0), # 超距
    ]
    return MockSimulator(jammers, seed=3)

def test_enter_and_initial_state():
    sim = make_sim()
    sim.enter()
    assert sim.clock.position == (0.0, 0.0)
    assert sim.clock.channel == 1
    assert sim.virtual_time == 0.0

def test_measure_direction_with_pm1deg_error_and_fixed_bias():
    sim = make_sim()
    sim.enter()
    r1 = sim.measure((0.0, 0.0), 1)
    true_bearing = bearing_between((0.0, 0.0), (300.0, 400.0))
    assert r1["measure_result"] == "direction"
    assert abs(angle_diff(r1["svd_deg"], true_bearing)) <= 1.0 + 1e-9

    r2 = sim.measure((0.0, 0.0), 1) # 同一地点重复检测：误差固定
    assert r2["svd_deg"] == pytest.approx(r1["svd_deg"])

    r3 = sim.measure((0.0, 100.0), 1) # 不同地点：误差可不同，但仍 <=1 度
    assert abs(angle_diff(r3["svd_deg"], bearing_between((0.0, 100.0), (300.0, 400.0)))) <= 1.0

def test_measure_near_within_5m():
    sim = make_sim()
    sim.enter()
    r = sim.measure((300.0 + 3.0, 400.0), 1)
    assert r["measure_result"] == "near"
    assert r["svd_deg"] is None

def test_measure_no_signal_beyond_effective_radius():
    sim = make_sim()
    sim.enter()
    r = sim.measure((0.0, 0.0), 3) # 距离 1700 m > r_eff 1200 m
    assert r["measure_result"] == "no_signal"

def test_directional_jammer_coverage_half_plane():
    sim = make_sim()

```

```

sim.enter()
behind = sim.measure((-900.0, 0.0), 2) # 位于西侧: 不在朝东覆盖角内
assert behind["measure_result"] == "no_signal"
front = sim.measure((0.0, 0.0), 2) # 位于东侧且在接收半径内
assert front["measure_result"] == "direction"
assert abs(angle_diff(front["svd_deg"], bearing_between((0.0, 0.0), (-500.0, 0.0)))) <= 1.0

def test_clear_rules_and_channel_unchanged():
    sim = make_sim()
    sim.enter()
    sim.measure((0.0, 0.0), 5) # 切到频道 5
    assert sim.clock.channel == 5

    miss = sim.clear((0.0, 0.0), 1) # (0,0) 距 (300,400) 500m > 20m
    assert miss["clear_result"] == "no_target_in_range"
    assert sim.clock.channel == 5, "/clear 不应切换测向机频道"

    hit = sim.clear((310.0, 400.0), 1) # 10m 内 -> 成功
    assert hit["clear_result"] == "success"
    assert sim.clock.channel == 5

    again = sim.clear((310.0, 400.0), 1) # 同一源只能清除一次
    assert again["clear_result"] == "no_target_in_range"

def test_timing_matches_rules():
    sim = make_sim()
    sim.enter()
    c1 = sim.measure((300.0, 400.0), 1)["cost"] # 500m/5 + 0 切换 + 5s
    assert c1.move_s == pytest.approx(100.0)
    assert c1.switch_s == pytest.approx(0.0)
    assert c1.total_s == pytest.approx(105.0)

    c2 = sim.measure((300.0, 400.0), 2)["cost"] # 原地换频道
    assert c2.switch_s == pytest.approx(1.0)
    assert c2.total_s == pytest.approx(6.0)

    c3 = sim.clear((300.0, 0.0), 3)["cost"] # 400m/5 + 3s(未发现)
    assert c3.total_s == pytest.approx(83.0)
    assert sim.virtual_time == pytest.approx(194.0)

def test_random_case_counts_and_channels():
    jammers = random_case(seed=1)
    assert 10 <= len(jammers) <= 16
    channels = [j.channel for j in jammers]
    assert len(set(channels)) == len(channels)
    assert all(1 <= c <= 20 for c in channels)
    assert all(distance((0.0, 0.0), j.position) <= 1800.0 + 1e-9 for j in jammers)
    assert all(1000.0 <= j.r_eff <= 1500.0 for j in jammers)

def test_directional_ratio_produces_directional_jammers():
    jammers = random_case(n=16, seed=9, directional_ratio=1.0)
    assert all(j.direction is not None for j in jammers)
    assert all(0.0 <= j.direction < 360.0 for j in jammers)

def test_protocol_response_fields_match_spec():
    """附件 2 第 5.2 / 6.2 节: 响应字段与真实模拟器逐字段对齐。

    真实模拟器的每个业务响应都带 ``real_timestamp_ms``: ``/enter`` 还额外返回
    三个时长字段, 其中 ``remaining_real_duration_s`` 是"本局实际可用现实时间",
    策略不得固定假定为 1200 s (见 scripts/run_simulator.py 的预算保护)。
    """
    sim = MockSimulator(random_case(n=10, seed=3), seed=3)
    enter = sim.enter()
    assert enter["virtual_time_s"] == 0.0
    assert enter["max_real_duration_s"] == 1200.0
    assert enter["max_virtual_duration_s"] > 0.0
    assert 0.0 <= enter["remaining_real_duration_s"] <= 1200.0
    measure = sim.measure((300.0, 400.0), 1)
    cleared = sim.clear((300.0, 0.0), 3)
    exit_body = sim.exit()
    for body in (enter, measure, cleared, exit_body):
        assert isinstance(body["real_timestamp_ms"], int)

```

```
# accepted=false 时同样要给出三个字段, 且 virtual_time_s 固定为 0
rejected = sim.measure((0.0, 0.0), 99)
assert rejected["accepted"] is False
assert rejected["virtual_time_s"] == 0.0
assert isinstance(rejected["real_timestamp_ms"], int)
```

B.74 tests/test_simulator_truth.py

"""演练真值读取模块测试（在临时目录内构造结果文件，不触碰真实模拟器数据）。"""

```
import json
import os
import time

from src.simulator_truth import (
    find_latest_result,
    list_results,
    read_result_file,
    wait_for_result_after,
)

SAMPLE = {
    "version": 2,
    "problem_no": 3,
    "practice_run_no": 4621099077388779008,
    "case_code": "NYJT-TNFF-7CNM-DG69",
    "window_started_at_utc": "2026-09-10T16:30:36.318Z",
    "ended_at_utc": "2026-09-10T16:30:42.859Z",
    "jammer_count": 11,
    "omnidirectional_jammer_count": 11,
    "directional_jammer_count": 0,
}

def _make(tmp_path, name="practice-p3-4621099077388779008-NYJT-TNFF-7CNM-DG69.result.json",
          payload=None):
    logs = tmp_path / "behavior-logs"
    logs.mkdir(parents=True, exist_ok=True)
    path = logs / name
    with open(path, "w", encoding="utf-8") as fh:
        json.dump(payload or SAMPLE, fh)
    return str(tmp_path), str(path)

def test_read_result_file(tmp_path):
    _, path = _make(tmp_path)
    data = read_result_file(path)
    assert data["jammer_count"] == 11
    assert data["case_code"] == "NYJT-TNFF-7CNM-DG69"

def test_list_and_find_latest(tmp_path):
    data_dir, path = _make(tmp_path)
    results = list_results(data_dir, problem_no=3)
    assert len(results) == 1
    assert results[0]["_path"] == path
    assert find_latest_result(data_dir, problem_no=3)["jammer_count"] == 11
    # 频道/问题号过滤: 要求不存在的结果文件时返回 None
    assert find_latest_result(data_dir, problem_no=4) is None
    # since_mtime 在未来 -> 视为本次测试没有新结果
    assert find_latest_result(data_dir, since_mtime=time.time() + 3600) is None

def test_missing_directory_returns_empty(tmp_path):
    assert list_results(str(tmp_path / "nope")) == []

def test_wait_for_result_after(tmp_path):
    data_dir, _ = _make(tmp_path)
    found = wait_for_result_after(data_dir, since_mtime=time.time() - 60,
                                  problem_no=3, timeout_s=2.0, poll_s=0.2)
    assert found is not None and found["jammer_count"] == 11
    none_found = wait_for_result_after(data_dir, since_mtime=time.time() + 3600,
                                        problem_no=3, timeout_s=0.5, poll_s=0.2)
    assert none_found is None
```

```
def test_encrypted_logs_are_ignored(tmp_path):
    data_dir, _ = _make(tmp_path)
    (tmp_path / "behavior-logs" / "practice-p3-1-AAAA.jlog").write_bytes(b"JMBLOG1\x00\xff")
    results = list_results(data_dir, problem_no=3)
    assert len(results) == 1, "加密 .jlog/.psum 不应被当作结果文件"
```

B.75 tests/test_strategy_p3.py

"""问题3 策略测试：在 Mock 模拟器上的端到端清除能力。"""

```
import math
```

```
import pytest
```

```
from src.config import CHANNELS, REGION_RADIUS, R_MIN
from src.coverage import seven_point_design
from src.mock_simulator import MockSimulator, random_case
from src.strategy_p3 import StrategyP3
```

```
# ----- 默认布点 ----- #
def test_default_design_is_dense_ring_with_covering_subset():
    """问题3 默认自适应模型：骨干是“加密环”，其中每 stride 个点取一个，
    这些“全频道扫描点”必须恰好构成标准 7 点覆盖集（不漏测保证只依赖它们）；"""
    strategy = StrategyP3()
    assert strategy.survey_points == [], "默认应为自适应路径（不给定固定检测点网）"
    ring = seven_point_design(strategy.cover_ring_radius, strategy.cover_ring_count)
    assert len(ring) == strategy.cover_ring_count + 1, "seven_point_design 含中心点"
    sweep = [ring[i] for i in range(0, len(ring), strategy.cover_probe_stride)]
    assert len(sweep) == 8, "全频道扫描点 = 中心 + 7 个等角环点（覆盖集）"
    assert sweep[0] == (0.0, 0.0)
    radii = [math.hypot(x, y) for x, y in sweep[1:]]
    assert all(abs(r - 1000.0) < 1e-9 for r in radii)
    angles = sorted(math.degrees(math.atan2(y, x)) % 360.0 for x, y in sweep[1:])
    gaps = [b - a for a, b in zip(angles, angles[1:])] + [360.0 - angles[-1] + angles[0]]
    assert all(abs(g - 360.0 / 7.0) < 1e-9 for g in gaps), "必须是等角 2π/7 分布"
```

```
def test_adaptive_backbone_covers_region_analytically_and_numerically():
    """覆盖性：解析 998.25 m + 高密极坐标网格复核，均 < R_min。"""
    from src.coverage import worst_case_radius

    design = seven_point_design(1000.0, 7)
    worst = math.sqrt(REGION_RADIUS ** 2 + 1000.0 ** 2
                      - 2.0 * REGION_RADIUS * 1000.0 * math.cos(math.pi / 7))
    assert worst == pytest.approx(998.2545144156829, rel=1e-12)
    assert worst < R_MIN
    assert worst_case_radius(design, REGION_RADIUS) < R_MIN
```

```
def test_schedule_sources_uses_cheapest_insertion():
    """最便宜插入：源应被插到剩余路线中“额外路程最小”的那一段。"""
    strategy = StrategyP3()
    route = [((0.0, 0.0), None, True), ((0.0, 1000.0), None, True)]
    # 三条示向度交于 (0, 500) — 正好在 (0,0)→(0,1000) 这一段的中点
    bearings = {7: [((500.0, 500.0), 180.0), ((-500.0, 500.0), 0.0),
                    ((0.0, 1000.0), 270.0)]}
    strategy._schedule_sources(route, 0, [7], bearings, set(), set(), set())
    assert len(route) == 3
    assert route[1][1] == 7, "应插在 0→1 段中间"
    assert math.dist(route[1][0], (0.0, 500.0)) < 5.0, route[1][0]
```

```
def test_schedule_sources_skips_when_insert_limit_exceeded():
    """插入代价超过阈值时不得硬插（留给收尾 TSP）。"""
    strategy = StrategyP3()
    strategy.insert_limit = 100.0
    # 估计点在路线外 999 m 处，插入代价远大于 100 m
    route = [((0.0, 0.0), None, True), ((0.0, 1000.0), None, True)]
    bearings = {7: [((500.0, 1500.0), 180.0), ((-500.0, 1500.0), 0.0),
                    ((0.0, 2000.0), 270.0)]}
    strategy._schedule_sources(route, 0, [7], bearings, set(), set(), set())
    assert len(route) == 2
    assert all(ch is None for _, ch, _ in route)
```

```
def test_adaptive_run_visits_backbone_without_jammers():
```

```

"""无干扰源时：走完覆盖骨干、无清除、无未解决、仍正常退出。"""
sim = MockSimulator([], seed=1)
strategy = StrategyP3()
res = strategy.run(sim)
assert res.cleared == 0
assert res.unresolved == []
# 8 个骨干点各做一次全频道探测
assert res.measures >= (1 + strategy.cover_ring_count)
assert res.virtual_time > 0.0

def test_strategy_p3_inserts_sources_on_route():
    """端到端：自适应模型应把大部分源"顺路"清除（插入率不低于 40%）。"""
    inserted_total = 0
    cases = 6
    for seed in range(cases):
        jammers = random_case(n=12, seed=seed)
        sim = MockSimulator(jammers, seed=seed)
        strategy = StrategyP3()
        original = strategy._schedule_sources

        counter = {"n": 0}

        def counting(route, index, channels, bearings, cleared, attempted,
                     scheduled, _c=counter):
            before = len(route)
            original(route, index, channels, bearings, cleared, attempted,
                     scheduled)
            _c["n"] += len(route) - before

        strategy._schedule_sources = counting
        res = strategy.run(sim)
        assert res.cleared == 12
        inserted_total += counter["n"]
    assert inserted_total >= 0.4 * 12 * cases, "顺路插入率过低，合并收益会丢失"

@pytest.mark.parametrize("seed", [0, 1, 2])
def test_strategy_clears_all_omni_jammers(seed):
    jammers = random_case(seed=seed)
    sim = MockSimulator(jammers, seed=seed)
    res = StrategyP3().run(sim)

    assert res.total == sim.total_jammers
    assert res.cleared == sim.total_jammers, f"存在未清除: {res.unresolved}"
    assert res.clearance_ratio == 1.0
    assert res.unresolved == []
    assert res.virtual_time > 0.0
    assert res.mean_clear_time > 0.0
    assert res.move_distance > 0.0
    assert res.mean_move_distance > 0.0

def test_empty_channels_are_not_reported_unresolved():
    """频道空间 20 个而干扰源仅若干个：空频道不得被当成"未清除"或反复重扫。

    回归测试：曾错误地为"零观测频道"加了重走检测点的兜底，导致每例白走
    约 6×18 km（耗时劣化 4 倍）。自适应模型下每个骨干点做一次全频道探测，
    因此检测次数必须与"骨干点数 × 频道数"同量级。
    """
    jammers = random_case(n=10, seed=3)
    sim = MockSimulator(jammers, seed=3)
    strategy = StrategyP3()
    res = strategy.run(sim)

    assert res.cleared == 10
    assert res.unresolved == []
    empty_channels = [ch for ch in CHANNELS
                      if ch not in {j.channel for j in jammers}]
    assert len(empty_channels) == len(CHANNELS) - 10
    backbone_points = 1 + strategy.cover_ring_count # 中心 + 环点
    sweep_points = len(range(0, strategy.cover_ring_count,
                             strategy.cover_probe_stride)) + 1
    # 覆盖扫描点做全频道探测；复测点只测"进行中"频道；不应出现"整圈重扫"的量级
    assert res.measures <= sweep_points * len(CHANNELS) + 60
    # 行程应与"骨干巡扫 + 各源清除"同量级（不会出现每空频道数公里的白跑）
    assert res.move_distance < 25_000.0

```

```

def test_strategy_handles_empty_channel_space():
    """无干扰源（极端情形）：策略应正常退出且无异常。"""
    sim = MockSimulator([], seed=0)
    res = StrategyP3().run(sim)
    assert res.cleared == 0
    assert res.unresolved == []
    assert res.clearance_ratio == 1.0

def test_strategy_handles_far_and_near_jammers():
    """边界情形：干扰源在区域边缘（远）与原点的附近（近）。"""
    from src.mock_simulator import Jammer

    jammers = [
        Jammer(channel=1, x=1750.0, y=0.0, r_eff=1000.0), # 边缘 + 最小接收半径
        Jammer(channel=2, x=8.0, y=0.0, r_eff=1500.0), # 距原点 8m
        Jammer(channel=3, x=-900.0, y=-1200.0, r_eff=1100.0),
    ]
    sim = MockSimulator(jammers, seed=11)
    res = StrategyP3().run(sim)
    assert res.cleared == 3, f"未清除: {res.unresolved}"
    assert sim.cleared_jammers == 3

```

B.76 tests/test_strategy_p4.py

```

"""问题 4 策略测试：含完全定向干扰源的端到端清除能力与定向布点条件。"""

import math

import pytest

from src.config import REGION_RADIUS, R_MIN
from src.coverage import (
    directional_certificate,
    directional_coverage_ok,
    directional_survey_design,
    seven_point_design,
    triangular_lattice_design,
    worst_case_radius,
)
from src.mock_simulator import Jammer, MockSimulator, random_case
from src.strategy_p4 import StrategyP4, estimate_direction_arc, two_opt_tour

# ----- 布点条件 ----- #
def test_seven_point_design_fails_directional_condition():
    """问题 3 的 7 点方案不能满足定向覆盖（定向源可能背向所有检测点）。"""
    r = directional_coverage_ok(seven_point_design(1400.0, 6), n_samples=800, seed=1)
    assert r["ok_ratio"] < 1.0

# ----- 定向安全证书 ----- #
def test_two_ring_design_has_analytic_certificate():
    """22 点定向安全网的证书：外环含域 + 角隙充要判据零失败。"""
    design = directional_survey_design()
    assert len(design) == 22
    outer_inradius = 1875.0 * math.cos(math.pi / 12.0) # 正十二边形内切半径
    assert outer_inradius > REGION_RADIUS, "目标圆域必须整体含于外环正十二边形内"
    # 「三角剖分全部边 < R_min」是**充分**条件：中心-内环 1000、内环边 684.04、
    # 外环边 970.57、最近交叉边 906.98 均 < 1000；但同相构型下"四边形对角线"
    # 可达 1126 m，故充分条件不再整体成立，正式保证改用**充要判据**
    # ( $G \in \text{conv}(\text{距 } G \leq R_{\min} \text{ 的网点}) \iff \text{这些点相对 } G \text{ 的最大角隙} < 180^\circ$ )。
    edges = {
        "center_inner": 1000.0,
        "inner_edge": 2.0 * 1000.0 * math.sin(math.pi / 9.0),
        "outer_edge": 2.0 * 1875.0 * math.sin(math.pi / 12.0),
        "cross_edge": math.dist(
            (1000.0 * math.cos(2 * math.pi / 9), 1000.0 * math.sin(2 * math.pi / 9)),
            (1875.0 * math.cos(math.pi / 6), 1875.0 * math.sin(math.pi / 6))),
    }
    assert edges["inner_edge"] < R_MIN and edges["outer_edge"] < R_MIN, edges
    assert edges["cross_edge"] < R_MIN, edges
    # 证书函数（确定性极坐标密网 + 边界加密）必须零失败
    cert = directional_certificate(design)
    assert cert["ok"] is True, cert
    assert cert["fail"] == 0

```

```

    assert cert["max_gap_deg"] < 179.0, cert

def test_certificate_rejects_incomplete_design():
    """去掉外环后（仅中心 + 内环）定向条件必须被证书判否。"""
    design = directional_survey_design()[:10]
    cert = directional_certificate(design)
    assert cert["ok"] is False
    assert cert["fail"] > 0

def test_lattice_design_satisfies_directional_condition():
    """定向安全网满足定向覆盖（用 20000 次抽样验证）。"""
    design = directional_survey_design()
    assert len(design) == 22
    r = directional_coverage_ok(design, n_samples=20000, seed=7)
    assert r["ok_ratio"] == 1.0, r

def test_lattice_design_also_covers_omni():
    """定向安全布点同时满足全向覆盖（最坏距离 < R_min）。"""
    design = directional_survey_design()
    wc = worst_case_radius(design, REGION_RADIUS, n_interior=8000, n_boundary=8000)
    assert wc < R_MIN

def test_spacing_must_not_exceed_r_min():
    """间距超过 R_min 时定向条件不再成立（理论边界的数值印证）。"""
    coarse = triangular_lattice_design(spacing=1500.0)
    r = directional_coverage_ok(coarse, n_samples=3000, seed=11)
    assert r["ok_ratio"] < 1.0

# ----- 巡逻与方向弧 ----- #
def test_two_opt_tour_is_complete_and_shorter_than_naive():
    design = directional_survey_design()
    tour = two_opt_tour([(0.0, 0.0)] + design)
    assert len(tour) == len(design) + 1
    assert set(tour) == set([(0.0, 0.0)] + design)

    def length(seq):
        return sum(math.dist(seq[i], seq[i + 1]) for i in range(len(seq) - 1))

    assert length(tour) <= length([(0.0, 0.0)] + design) + 1e-9

def test_direction_arc_estimation():
    """由有信号/无信号约束交出的可行方向弧应包含真实朝向。"""
    g = (0.0, 0.0)
    true_dir = 90.0
    detections = [(math.cos(math.radians(a)) * 500, math.sin(math.radians(a)) * 500)
                  for a in (40.0, 90.0, 140.0)] # 在朝北半平面内
    misses = [(500.0, -300.0)] # 背面点: 无信号
    arc = estimate_direction_arc(g, detections, misses)
    assert arc, "可行弧不应为空"
    assert any(abs(((a - true_dir + 180) % 360) - 180) <= 2.0 for a in arc)

# ----- 机会式清除（顺路清除） ----- #
class _FakeClock:
    def __init__(self, position):
        self.position = position
        self.history = []
        self.virtual_time = 0.0

class _FakeTransport:
    """最小传输桩：只实现策略实际调用的协议动作，用于确定性单测。"""

    def __init__(self, position=(0.0, 0.0), clear_success=True,
                 measure_kind="no_signal"):
        self.clock = _FakeClock((float(position[0]), float(position[1])))
        self.clear_calls = []
        self.measure_calls = []
        self._clear_success = clear_success
        self._measure_kind = measure_kind

    def measure(self, position, channel):

```

```

        self.measure_calls.append((position, channel))
        self.clock.position = (float(position[0]), float(position[1]))
        return {"measure_result": self._measure_kind, "svd_deg": None}

def clear(self, position, channel):
    self.clear_calls.append((position, channel))
    self.clock.position = (float(position[0]), float(position[1]))
    return {"clear_result": ("success" if self._clear_success
                             else "no_target_in_range")}

def enter(self):
    return {"accepted": True}

def exit(self):
    return {"accepted": True}

# 三条示向线均精确指向原点 ⇒ 最小二乘估计恰为 (0, 0)
_TRIANGULATING_RECORDS = [((100.0, 0.0), 180.0), ((0.0, 100.0), 270.0),
                           ((-100.0, 0.0), 0.0)]

def test_opportunistic_clear_respects_detour_threshold():
    """额外路程 = |cur-g|+|g-next|-|cur-next| = 900+100-800 = 200 m。

    阈值 150 m 时不得插入；阈值 400 m 时恰好插入一次并标记该频道已清除。
    """
    from src.strategy_p3 import StrategyResult, bearing_least_squares

    estimate = bearing_least_squares(_TRIANGULATING_RECORDS)
    assert estimate == pytest.approx((0.0, 0.0), abs=1e-9)

    for threshold, expected in ((150.0, 0), (400.0, 1)):
        transport = _FakeTransport(position=(0.0, 900.0))
        strategy = StrategyP4(insert_threshold=threshold)
        bearings = {3: list(_TRIANGULATING_RECORDS)}
        cleared, state = set(), {}
        strategy._opportunistic_clear(transport, [3], bearings, cleared,
                                     StrategyResult(), (0.0, 900.0),
                                     (0.0, 100.0), state)
        assert len(transport.clear_calls) == expected, (threshold, transport.clear_calls)
        assert (3 in cleared) is (expected == 1)

def test_opportunistic_clear_marks_cleared_and_never_repeats():
    """回归：插入成功必须立即标记 cleared，且同一频道至多插入一次。

    曾漏写 cleared.add(channel)，导致已清除频道在下一条扫描边被反复尝试，
    端到端清除率从 100% 掉到约 69%。
    """
    from src.strategy_p3 import StrategyResult

    transport = _FakeTransport(position=(0.0, 900.0))
    strategy = StrategyP4(insert_threshold=400.0)
    bearings = {3: list(_TRIANGULATING_RECORDS)}
    cleared, state = set(), {}
    result = StrategyResult()

    strategy._opportunistic_clear(transport, [3], bearings, cleared, result,
                                  (0.0, 900.0), (0.0, 100.0), state)

    assert 3 in cleared
    assert len(transport.clear_calls) == 1

    # 再次调用（模拟后续扫描边）：该频道已清除，不得再产生任何动作
    strategy._opportunistic_clear(transport, [3], bearings, cleared, result,
                                  (0.0, 900.0), (0.0, 100.0), state)
    assert len(transport.clear_calls) == 1

def test_opportunistic_clear_failure_does_not_loop():
    """插入失败（清除不中且测不到示向度）时：失败频道不得在后续扫描边重复插入。

    注意：单次 `_fast_clear` 内部会做“双向射线 + 近场网格”等多次尝试，
    因此这里比较的是“再次调用钩子是否新增动作”，而不是绝对次数。
    """
    from src.strategy_p3 import StrategyResult

    transport = _FakeTransport(position=(0.0, 900.0), clear_success=False,

```

```

        measure_kind="no_signal")
strategy = StrategyP4(insert_threshold=400.0)
bearings = {3: list(_TRIANGULATING_RECORDS)}
cleared, state = set(), {}
result = StrategyResult()

strategy._opportunistic_clear(transport, [3], bearings, cleared, result,
                              (0.0, 900.0), (0.0, 100.0), state)
attempted_once = len(transport.clear_calls)
assert attempted_once >= 1, "失败也应至少尝试一次"
assert 3 not in cleared
assert result.failed_clears >= 1

strategy._opportunistic_clear(transport, [3], bearings, cleared, result,
                              (0.0, 900.0), (0.0, 100.0), state)
assert len(transport.clear_calls) == attempted_once, "失败频道不得在后续扫描边重复插入"

def test_observations_complete_stops_at_three():
    """问题 4 三条观测即停（减少检测动作），定位质量由严格兜底保证。"""
    strategy = StrategyP4()
    assert strategy.observations_target == 3
    assert strategy._observations_complete([]) is False
    assert strategy._observations_complete([(0.0, 0.0), 10.0]) is False
    assert strategy._observations_complete([(0.0, 0.0), 10.0],
                                           ((1.0, 0.0), 20.0)) is False
    assert strategy._observations_complete(list(_TRIANGULATING_RECORDS)) is True

# ----- 端到端清除 ----- #
@pytest.mark.parametrize("seed", [0, 1, 2])
def test_strategy_p4_clears_all_directional_jammers(seed):
    jammers = random_case(seed=seed, directional_ratio=1.0)
    sim = MockSimulator(jammers, seed=seed)
    res = StrategyP4().run(sim)
    assert res.cleared == sim.total_jammers, f"未清除: {res.unresolved}"
    assert res.clearance_ratio == 1.0
    assert res.unresolved == []

def test_strategy_p4_handles_mixed_and_edge_cases():
    jammers = [
        Jammer(channel=1, x=1700.0, y=0.0, r_eff=1000.0, direction=0.0), # 边界+背向圆心
        Jammer(channel=2, x=-1600.0, y=900.0, r_eff=1100.0), # 全向
        Jammer(channel=3, x=10.0, y=0.0, r_eff=1500.0, direction=270.0), # 近原点
        Jammer(channel=4, x=0.0, y=1750.0, r_eff=1300.0, direction=90.0), # 朝外
    ]
    sim = MockSimulator(jammers, seed=42)
    res = StrategyP4().run(sim)
    assert res.cleared == 4, f"未清除: {res.unresolved}"

def test_strategy_p4_early_stops_at_16():
    """总数上限 16: 清满 16 个即提前结束（不再扫描剩余频道）。"""
    jammers = random_case(n=16, seed=5, directional_ratio=0.5)
    sim = MockSimulator(jammers, seed=5)
    res = StrategyP4().run(sim)
    assert res.cleared == 16
    assert res.total == 16

```

B.77 requirements.txt

```

numpy>=1.24
scipy>=1.10
matplotlib>=3.7
requests>=2.31
shapely>=2.0
pytest>=7.4

```

B.78 pytest.ini

```

[pytest]
testpaths = tests
python_files = test_*.py
addopts = -q

```