

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РФ

Федеральное государственное автономное образовательное
учреждение высшего образования
ЮЖНЫЙ ФЕДЕРАЛЬНЫЙ УНИВЕРСИТЕТ

Институт математики, механики и компьютерных наук
имени И. И. Воровича

Направление подготовки
02.03.02 — Фундаментальная информатика
и информационные технологии

СПЕЦИФИКАЦИЯ СТРУКТУР ДАННЫХ
НА ЯЗЫКЕ ПРОГРАММИРОВАНИЯ COQ

Выпускная квалификационная работа
на степень бакалавра

Студента 4 курса
А. И. Насека

Научный руководитель:
старший преподаватель В. Н. Брагилевский

Допущено к защите:

руководитель направления ФИИТ _____ В. С. Пилиди

Ростов-на-Дону

2017

Contents

Introduction	3
1. Binary tree	4
1.1. Inductive definition	4
1.2. Functions and properties	5

Introduction

1. Binary tree

1.1. Inductive definition

The first basic data structure will be a binary tree. To implement this data structure in Coq, we give an inductive definition *BinaryTree T* for some type *T*:

```
Inductive BinaryTree (T : Type) : Type :=  
  | Nil : BinaryTree T  
  | Node : BinaryTree T -> BinaryTree T -> T -> BinaryTree T ->  
    BinaryTree T.
```

Type *Nil* is a basic constructor, describing the empty tree. Type *Node* is a tree node constructor, which includes four fields:

- The first argument has a type *BinaryTree T* and it serves to provide additional information (e.g., if we have the tree with parents, this argument can be the reference to the **parent** or if we have the tree with siblings - it can be the reference to the **sibling**).
- The second argument has a type *BinaryTree T* and it's a reference to the **left child**.
- The third argument has a type *T*. This field is a **value** of a tree node (e.g., as a type *T*, we can take a standard type in Coq - *num* and then values of this type will be natural numbers).
- The fourth argument has a type *BinaryTree T* and it's a reference to the **right child**.

We give several examples of trees (as the type *T* - we select *num*):

```
Check (Nil nat). (* Admission *)  
Check (Node (Nil nat) (Nil nat) 5 (Nil nat)). (* Admission *)  
Check (Node (Nil nat) (Nil nat) 5  
  (Node (Nil nat) (Nil nat) 7 (Nil nat))). (* Admission *)
```

- In the first example we have the empty tree.
- In the second - binary tree with only one node, in which all references to parent/sibling and childs are empty.
- In the last example we have the tree with two nodes. Root of tree have a value 5 and its right child have a value 7.

1.2. Functions and properties