

Get started

Open in app



Follow

589K Followers



You have **1** free member-only story left this month. [Sign up for Medium and get an extra one](#)

# The Definitive Guide to Conda Environments

How to manage environments with conda for Python & R.



Matthew Sarmiento May 24, 2019 · 10 min read ★



[Get started](#)[Open in app](#)

Conda environments are like cousins of Python's virtual environments. Both serve to help manage dependencies and isolate projects, and they function in a similar way, with one key distinction: conda environments are **language agnostic**. That is, they support languages other than Python.

 In this guide we'll cover the basics of creating and managing environments with `conda` for Python & R.

 **Note:** We'll be using the latest versions of Conda v4.6.x, Python v3.7.y, and R v3.5.z on macOS Mojave throughout this guide.

## Table of Contents

- [Conda vs. Pip vs. Venv — What's the Difference?](#)
- [Using Conda Environments](#)
- [Installing Packages](#)
- [Managing Environments](#)
- [Environments With R](#)
- [Further Reading](#)

## Conda vs. Pip vs. Venv — What's the Difference?

Before we get started, some of you might be wondering what the difference is between `conda`, `pip`, and `venv`.

I'm glad you asked. We can't put it any better than this: `pip` is a package manager *for Python*. `venv` is an environment manager *for Python*. `conda` is **both a package and environment manager** and is **language agnostic**.

Whereas `venv` creates isolated environments for Python development only, `conda` can create isolated environments for any language (in theory).

Whereas `pip` only installs Python packages from PyPI, `conda` can both



[Get started](#)[Open in app](#)

- Install packages from PyPI by using `pip` in an active Conda environment.

How cool is that?

👉 For a handy, if slightly outdated, chart comparing the three, click [here](#) (don't forget to scroll right!).




[Morning Mist](#) by [Thomas Cole](#).

## Using Conda Environments

### Creating Environments

To create an environment with `conda` for Python development, run:

[Get started](#)[Open in app](#)


 **Important:** Replace “conda-env” with the name of your environment. From here on we’ll always use “conda-env” for the name of our environments.

This environment will use the same version of Python as your current shell’s Python interpreter. To specify a different version of Python, use:

```
% conda create -n conda-env python=3.7
```


You can also install additional packages when creating an environment, like, say, `numpy` and `requests`.

```
% conda create -n conda-env numpy requests
```

 **Note:** Because `conda` ensures dependencies are satisfied when installing packages, Python will be installed alongside `numpy` and `requests` 😊.

You can also specify which versions of packages you’d like to install.

```
% conda create -n conda-env python=3.7 numpy=1.16.1 requests=2.19.1
```

 **Note:** It’s recommended to install all the packages you want to include in an environment at the same time to help avoid dependency conflicts.

Last, you can activate your environment with the invocation:

```
% conda activate conda-env  
(conda-env) % # Fancy new command prompt
```

[Get started](#)[Open in app](#)

```
% conda deactivate  
%
```

```
# Old familiar command prompt
```

## Where Environments Live

When you create an environment with Python's `venv` module, you need to say where it lives by specifying its path.


```
% python3 -m venv /path/to/new/environment
```

Environments created with `conda`, on the other hand, live by default in the `envs/` folder of your Conda directory, whose path will look something like:

```
% /Users/user-name/miniconda3/envs          # Or .../anaconda3/envs
```

I prefer the approach taken by `venv` for two reasons.


**1** It makes it easy to tell if a project utilizes an isolated environment by including the environment as a sub-directory.

```
my-project/  
├── conda-env          # Project uses an isolated env   
├── data  
├── src  
└── tests
```

**2** It allows you to use the same name for all of your environments (I use “conda-env”), meaning you can activate each with the same command.

[Get started](#)[Open in app](#)

 **Bonus:** This allows you to alias the activation command and stick it in your `.bashrc` file, making life a little bit simpler.

 **Note:** If you keep all of your environments in your Conda's `env/` folder, you'll have to give each of them a different name, which can be a pain 😞.

So, how *do* you place environments outside of your Conda's `env/` folder? By using the `--prefix` flag instead of `--name` when creating an environment.

```
% conda create --prefix /path/to/conda-env # Or use -p
```

 **Note:** This makes an environment called “conda-env” in the specified path.

It's as simple as that. *However*, placing environments outside of the default `env/` folder comes with two drawbacks.

**1** `conda` can no longer find your environment with the `--name` flag. Instead, you'll need to pass the `--prefix` flag along with the environment's full path. For example, when installing packages, which we'll cover in the next section.

**2** Your command prompt is no longer prefixed with the active environment's name, but rather its full path.

```
(/path/to/conda-env) %
```

As you can imagine, this gets messy quickly. Like this doozy, for instance.

```
(/Users/user-name/data-science/project-name/conda-env) % # 🤖
```

[Get started](#)[Open in app](#)

```
% conda config --set env_prompt '({name}) '
```

⚠ **Note:** This will edit your `.condarc` file if you already have one and create one if you do not. For more on modifying your `.condarc` file, see [the docs](#).

Now your command prompt will only display the active environment's name.

```
% conda activate /path/to/conda-env  
(conda-env) % # Woohoo! 🎉
```

Last, you can view a list of all your existing environments.

```
% conda env list  
  
# conda environments:  
#  
base * /path/to/conda-env  
r-env /Users/username/miniconda3  
      /Users/username/miniconda3/envs/r-env
```

⚠ **Note:** The `*` points to the current active environment. A bit annoyingly though, it will point to “base” even when no environment is active 🙄.





[Get started](#)[Open in app](#)

An American Lake Scene by Thomas Cole.

## Installing Packages

There are two ways to install packages with `conda`.

**1** From inside an active environment.

**2** From your default shell.

The latter requires you to point to the environment you want to install packages in using the same flag ( `--name` or `--prefix` ) that you used to create your environment with.

The former works equally well regardless of which flag you used.

**☀ Important:** We *strongly* recommend sticking to the former approach, as it removes the danger of unintentionally installing packages system-wide.

**♻ Reminder:** All environments in this guide are named “conda-env”. You can replace “conda-env” with the name of your environment.



[Get started](#)[Open in app](#)

environment, you can install additional packages in two ways.

**1** From inside an active environment.

```
(conda-env) % conda install pandas=0.24.1 # 🐼
```

**2** From your default shell.

```
% conda install -n conda-env pandas=0.24.1 # Or -p /path/to/env
```

Likewise, you can update the packages in an environment in two ways.

**1** From inside the active environment.

```
(conda-env) % conda update pandas
```

**2** From your default shell.

```
% conda update -n conda-env pandas # Or -p /path/to/env
```

You can also list the packages installed in a given environment in — yep, you guessed it — two ways.

**1** From inside the active environment.

```
(conda-env) % conda list
```

**2** From your default shell.

[Get started](#)[Open in app](#)

## From Other Conda Repositories

If a package isn't available from the default [Anaconda Repository](#), you can try searching for it on [Anaconda Cloud](#), which hosts Conda packages provided by third party repositories like [Conda-Forge](#).

To install a package from Anaconda Cloud, you'll need to use the `--channel` flag to specify the repository you want to install from. For example, if you wanted to install `opencv` from Conda-Forge, you'd run:

```
(conda-env) % conda install --channel conda-forge opencv      # Or -c
```

Thankfully, `conda` keeps track of where a package was installed from.

```
(conda-env) % conda list

# packages in environment at /path/to/conda-env:
#
# Name                                Version           Build                Channel
numpy                                1.16.1            py37h926163e_0
opencv                              4.1.0             py37h0cb0d9f_3      conda-forge
pandas                              0.24.2            py37h0a44026_0
```

The blank channel entries for `numpy` and `pandas` represent the `default_channels`, which is set by default to Anaconda Repository.


 **Note:** For brevity we've shown only a selection of packages above.

You can also permanently add a channel as a package source.

[Get started](#)[Open in app](#)

This will modify your `.condarc` file to look something like this:

```
env_prompt: '({name}) '      # Modifies active environment prompt
channels:                    # Lists package sources to install from
- defaults                   # Default Anaconda Repository
- conda-forge
```

 **Caution:** The order of your channels *matters*. If a package is available from multiple channels, `conda` will install it from the channel listed *highest* in your `.condarc` file. For more on managing channels, see [the docs](#).

## From PyPI

If a package isn't available from Anaconda Repository or Anaconda Cloud, you can try installing it with `pip`, which `conda` installs by default in any environment created with Python.

For example, to install `requests` with `pip` you'd run:

```
(conda-env) % pip install requests
```

Note that `conda` correctly lists PyPI as the channel for `requests`, making it easy to identify packages installed with `pip`.

```
(conda-env) % conda list

# packages in environment at /path/to/conda-env:
#
# Name                                Version            Build                Channel
```


[Get started](#)[Open in app](#)

requests

2.21.0

pyp1\_0

pyp1

 **Caution:** As `pip` packages do not possess all the features of `conda` packages, it's strongly recommended to install packages with `conda` whenever possible. For more on `conda` vs. `pip` packages, click [here](#).



[Moonlight](#) by Thomas Cole.

## Managing Environments



[Get started](#)[Open in app](#)

project's root directory listing all the packages, along with their version numbers, that are installed in your project's environment.

Conda calls these environment files. They are the exact analogue of requirements files for Python's virtual environments.

Like with everything else, you can make an environment file in two ways.

**1** From inside an active environment.

```
(conda-env) % conda env export --file environment.yml          # Or -f
```

**2** From your default shell.

```
% conda env export -n conda-env -f /path/to/environment.yml
```

Your `environment.yml` file will look something like this:

```
name: null                                # Our env was made with --prefix
channels:
  - conda-forge                            # We added a third party channel
  - defaults
dependencies:
  - numpy=1.16.3=py37h926163e_0
  - opencv=3.4.2=py37h6fd60c2_1
  - pandas=0.24.2=py37h0a44026_0
  - pip=19.1.1=py37_0                      # Packages installed from PyPI
  - pip:
    - requests==2.21.0
prefix: /Users/user-name/data-science/project-name/conda-env
```

**⚠ Note:** For brevity we've shown only a selection of packages above.

[Get started](#)[Open in app](#)

```
% conda env create -n conda-env -f /path/to/environment.yml
```



**Bonus:** You can also add the packages listed in an `environment.yml` file to an existing environment with:

```
% conda env update -n conda-env -f /path/to/environment.yml
```



[View in the White Mountains](#) by Thomas Cole.

[Get started](#)[Open in app](#)

```
(conda-env) % conda install r-base
```

Of course, you can always do this when first creating an environment.

```
% conda create -n r-env r-base
```

 **Note:** Replace “r-env” with the name of your environment.

Conda’s R packages are available from the [R channel](#) of Anaconda Cloud, which is included by default in Conda’s [default\\_channels](#) list, so you don’t need to specify the R channel when installing R packages like, say, `tidyverse`.

```
% conda activate r-env  
(r-env) % conda install r-tidyverse
```

 **Note:** All packages from the R channel are prefixed with “r-”.

If you want, you can install the `r-essentials` bundle, which includes over 80 of the most popular scientific R packages, like `tidyverse` and `shiny`.

```
(r-env) % conda install r-essentials
```

Last, if you want to install an R package that Conda doesn’t offer, you’ll need to build the package from [CRAN](#), instructions to which you can find [here](#).

[Get started](#)[Open in app](#)

check out [this blurb](#) on how Python's virtual environments do their thing. Conda environments work in exactly the same fashion.

Other than that, that about does it for us. If you'd like to stay up to date with my data science-y postings, feel free to [follow me on twitter](#).

Cheers, and happy reading.

## Update 08/2019: Conda Revisions

You really do learn something new everyday. This morning my friend, Kumar Shishir, told me about yet another **incredibly useful** conda feature: conda revisions.

I couldn't believe my ears. How could I have languished for so long in complete and utter ignorance of such a brilliant feature?

Revisions track changes to your environment over time, allowing you to **easily** remove packages **and** all of their dependencies.

For example, say we created a new conda-env and installed numpy, followed by pandas. Our revision history would look like this:

```
(conda-env) % conda list --revisions
```

```
2019-08-30 16:04:14 (rev 0) # Created our env
```

```
+pip-19.2.2  
+python-3.7.4
```

```
2019-08-30 16:04:30 (rev 1) # Installed numpy
```

```
+numpy-1.16.4  
+numpy-base-1.16.4
```

```
2019-08-30 16:04:39 (rev 2) # Installed pandas
```



[Get started](#)[Open in app](#)

Imagine we no longer wanted to have `pandas` in our environment because it's (somehow) incompatible with our earlier dependencies, or because we simply no longer need it.

Revisions allow us to rollback our environment to a previous incarnation:

```
(conda-env) % conda install --revision 1
(conda-env) % conda list --revisions          # (Showing latest only)

2019-08-30 16:08:05 (rev 3)                  # Uninstalled pandas

-pandas-0.25.1
-python-dateutil-2.8.0
-pytz-2019.2
```

The `-` signs by each package tell us we've successfully removed them from our environment. Now we're ready to get back to some data science 😎.

## Update 02/2020: Clear Your Tarballs!

As you build more projects, each with their own environment, you'll begin to quickly accumulate `tarballs` from packages you've installed.

To get rid of them and free up some disc space, run:

```
% conda clean --all                          # no active env needed
```

---

**Sign up for The Variable**

[Get started](#)[Open in app](#)

and cutting-edge research to original features you don't want to miss. [Take a look.](#)

[Get this newsletter](#)

You'll need to sign in or create an account to receive this newsletter.

[Data Science](#)[Technology](#)[Programming](#)[Software Development](#)[Towards Data Science](#)[About](#) [Help](#) [Legal](#)

Get the Medium app

