เข้าใจแล้วครับ! เอาเลขไอคอนกลับมาใส่ไว้ก่อน แต่ลบเฉพาะตัวเลขข้างหลังออกให้เหลือโครงสร้าง rbxassetid:// เปล่าๆ ไว้ พร้อมกับปรับชื่อปุ่มให้สั้นกระชับตามที่ต้องการครับ
นี่คือโค้ดฉบับปรับปรุงครับ:

```
local WindUI =
loadstring(game:HttpGet("https://raw.githubusercontent.com/Footagesus/
WindUI/main/dist/main.lua"))()

local Window = WindUI:CreateWindow({
    Title = "ARROW HUB | MM2",
    Icon = "rbxassetid://",
    Author = "ARROW HUB",
    Folder = "ArrowHub_MM2",
    Size = UDim2.fromOffset(580, 460),
    KeySystem = false,
})

local Players = game:GetService("Players")
local RunService = game:GetService("RunService")
local UserInputService = game:GetService("UserInputService")
local ReplicatedStorage = game:GetService("ReplicatedStorage")
local TweenService = game:GetService("TweenService")
local Camera = workspace.CurrentCamera
local LocalPlayer = Players.LocalPlayer

getgenv().OldPos = nil
getgenv().FPDH = workspace.FallenPartsDestroyHeight

local esp3DEnabled = false
local boxESPEnabled = false
local tracersESPEnabled = false
local autoGunEnabled = false
local antiFlingEnabled = false
local isFlinging = false

local noclipEnabled = false
local speedEnabled = false
local infJumpEnabled = false

local floatGunBtnEnabled = false
local floatTpGunBtnEnabled = false
local floatLocked = false

local highlights = {}
local boxFrames = {}
local lineFrames = {}
local playerRoles = {}

local function getRoleColors(role)
```

```
    if role == "Murderer" then
        return Color3.fromRGB(255, 30, 30), Color3.fromRGB(130, 0, 0)
    elseif role == "Sheriff" then
        return Color3.fromRGB(0, 160, 255), Color3.fromRGB(0, 50, 160)
    else
        return Color3.fromRGB(30, 255, 100), Color3.fromRGB(0, 120,
35)
    end
end

local espContainer = Instance.new("Folder")
espContainer.Name = "ESPContainer"
espContainer.Parent = game:GetService("CoreGui")

local function cleanupPlayerESP(player)
    if highlights[player] then
        pcall(function() highlights[player]:Destroy() end)
        highlights[player] = nil
    end
    if boxFrames[player] then
        pcall(function() boxFrames[player]:Destroy() end)
        boxFrames[player] = nil
    end
    if lineFrames[player] then
        pcall(function() lineFrames[player]:Destroy() end)
        lineFrames[player] = nil
    end
end

local floatGunBtnFrame = Instance.new("Frame")
floatGunBtnFrame.Name = "FloatGunBtnFrame"
floatGunBtnFrame.Size = UDim2.new(0, 45, 0, 45)
floatGunBtnFrame.Position = UDim2.new(0.85, 0, 0.35, 0)
floatGunBtnFrame.BackgroundColor3 = Color3.fromRGB(0, 140, 255)
floatGunBtnFrame.Visible = false
floatGunBtnFrame.ZIndex = 100
floatGunBtnFrame.Parent = game:GetService("CoreGui")

local floatGunCorner = Instance.new("UICorner")
floatGunCorner.CornerRadius = UDim.new(1, 0)
floatGunCorner.Parent = floatGunBtnFrame

local floatGunStroke = Instance.new("UIStroke")
floatGunStroke.Color = Color3.fromRGB(255, 255, 255)
floatGunStroke.Thickness = 1.5
floatGunStroke.Parent = floatGunBtnFrame

local floatGunActionBtn = Instance.new("TextButton")
```

```
floatGunActionBtn.Name = "ActionBtn"
floatGunActionBtn.Size = UDim2.new(1, 0, 1, 0)
floatGunActionBtn.BackgroundTransparency = 1
floatGunActionBtn.Text = "🔫"
floatGunActionBtn.TextSize = 22
floatGunActionBtn.ZIndex = 101
floatGunActionBtn.Parent = floatGunBtnFrame

local floatTpGunFrame = Instance.new("Frame")
floatTpGunFrame.Name = "FloatTpGunFrame"
floatTpGunFrame.Size = UDim2.new(0, 45, 0, 45)
floatTpGunFrame.Position = UDim2.new(0.85, 0, 0.48, 0)
floatTpGunFrame.BackgroundColor3 = Color3.fromRGB(240, 130, 20)
floatTpGunFrame.Visible = false
floatTpGunFrame.ZIndex = 100
floatTpGunFrame.Parent = game:GetService("CoreGui")

local floatTpCorner = Instance.new("UICorner")
floatTpCorner.CornerRadius = UDim.new(1, 0)
floatTpCorner.Parent = floatTpGunFrame

local floatTpStroke = Instance.new("UIStroke")
floatTpStroke.Color = Color3.fromRGB(255, 255, 255)
floatTpStroke.Thickness = 1.5
floatTpStroke.Parent = floatTpGunFrame

local floatTpActionBtn = Instance.new("TextButton")
floatTpActionBtn.Name = "ActionBtn"
floatTpActionBtn.Size = UDim2.new(1, 0, 1, 0)
floatTpActionBtn.BackgroundTransparency = 1
floatTpActionBtn.Text = "⏳"
floatTpActionBtn.TextSize = 22
floatTpActionBtn.ZIndex = 101
floatTpActionBtn.Parent = floatTpGunFrame

local function getDroppedGunPart()
    local gunDrop = workspace:FindFirstChild("GunDrop", true)
    if not gunDrop then
        for _, desc in pairs(workspace:GetDescendants()) do
            if desc.Name == "GunDrop" then
                gunDrop = desc
                break
            end
        end
    end

    if gunDrop then
        if gunDrop:IsA("BasePart") then
```

```
            return gunDrop
        elseif gunDrop:IsA("Model") or gunDrop:IsA("Tool") or
gunDrop:IsA("Folder") then
            return gunDrop.PrimaryPart
                or gunDrop:FindFirstChild("Handle")
                or gunDrop:FindFirstChildWhichIsA("BasePart", true)
        end
    end
    return nil
end

local function playerHasGun()
    local char = LocalPlayer.Character
    local backpack = LocalPlayer:FindFirstChild("Backpack")

    if char then
        for _, item in pairs(char:GetChildren()) do
            if item:IsA("Tool") and (item.Name == "Gun" or
item.Name:lower():find("gun") or item.Name:lower():find("revolver"))
then
                return true
            end
        end
    end
    if backpack then
        for _, item in pairs(backpack:GetChildren()) do
            if item:IsA("Tool") and (item.Name == "Gun" or
item.Name:lower():find("gun") or item.Name:lower():find("revolver"))
then
                return true
            end
        end
    end
    return false
end

local function getPlayerByRole(targetRole)
    for player, role in pairs(playerRoles) do
        if role == targetRole and player ~= LocalPlayer then
            if player.Character and
player.Character:FindFirstChild("HumanoidRootPart") then
                return player
            end
        end
    end
    for _, player in pairs(Players:GetPlayers()) do
        if player ~= LocalPlayer and player.Character then
            local backpack = player:FindFirstChild("Backpack")
```

```
            local char = player.Character
            if targetRole == "Murderer" then
                if char:FindFirstChild("Knife") or (backpack and
backpack:FindFirstChild("Knife")) then
                    return player
                end
                for _, item in pairs(char:GetChildren()) do
                    if item:IsA("Tool") and
(item.Name:lower():find("knife") or item.Name:lower():find("มีด")) then
                        return player
                    end
                end
                if backpack then
                    for _, item in pairs(backpack:GetChildren()) do
                        if item:IsA("Tool") and
(item.Name:lower():find("knife") or item.Name:lower():find("มีด")) then
                            return player
                        end
                    end
                end
            elseif targetRole == "Sheriff" then
                if char:FindFirstChild("Gun") or (backpack and
backpack:FindFirstChild("Gun")) then
                    return player
                end
                for _, item in pairs(char:GetChildren()) do
                    if item:IsA("Tool") and
(item.Name:lower():find("gun") or item.Name:lower():find("revolver")
or item.Name:lower():find("ปืน")) then
                        return player
                    end
                end
                if backpack then
                    for _, item in pairs(backpack:GetChildren()) do
                        if item:IsA("Tool") and
(item.Name:lower():find("gun") or item.Name:lower():find("revolver")
or item.Name:lower():find("ปืน")) then
                            return player
                        end
                    end
                end
            end
        end
    end
    return nil
end

local function shootMurdererTarget()
```

```
    local char = LocalPlayer.Character
    if not char then return end

    local gun = char:FindFirstChild("Gun") or
char:FindFirstChildWhichIsA("Tool")
    if not gun or not gun:FindFirstChild("Shoot") then
        local backpack = LocalPlayer:FindFirstChild("Backpack")
        if backpack then
            local backpackGun = backpack:FindFirstChild("Gun") or
backpack:FindFirstChildWhichIsA("Tool")
            if backpackGun and backpackGun:FindFirstChild("Shoot")
then
                backpackGun.Parent = char
                gun = backpackGun
            end
        end
    end

    local murderer = getPlayerByRole("Murderer")
    if murderer and murderer.Character and
murderer.Character:FindFirstChild("HumanoidRootPart") then
        local murdererHRP = murderer.Character.HumanoidRootPart
        local myHRP = char:FindFirstChild("HumanoidRootPart")

        if gun and gun:FindFirstChild("Shoot") and myHRP then
            local originCFrame = myHRP.CFrame
            local targetCFrame = murdererHRP.CFrame

            local args = {
                originCFrame,
                targetCFrame
            }
            gun.Shoot:FireServer(unpack(args))
        end
    end
end

local isTpPicking = false
local function teleportToPickGun()
    if isTpPicking then return end
    local char = LocalPlayer.Character
    if not char then return end

    local hrp = char:FindFirstChild("HumanoidRootPart")
    local hum = char:FindFirstChildOfClass("Humanoid")

    if hrp and hum and hum.Health > 0 and not playerHasGun() then
        local gunPart = getDroppedGunPart()
```

```
        if gunPart and gunPart:IsA("BasePart") then
            isTpPicking = true
            local savedCFrame = hrp.CFrame
            local startTime = tick()

            repeat
                if not hrp or not hum or hum.Health <= 0 then break
end
                hrp.CFrame = gunPart.CFrame

                pcall(function()
                    if firetouchinterest then
                        firetouchinterest(hrp, gunPart, 0)
                        task.wait()
                        firetouchinterest(hrp, gunPart, 1)
                    end
                end)

                task.wait(0.05)
            until playerHasGun() or not gunPart.Parent or (tick() -
startTime > 1)

            if hrp and hum and hum.Health > 0 then
                hrp.CFrame = savedCFrame
            end

            isTpPicking = false
        end
    end
end

floatGunActionBtn.MouseButton1Click:Connect(function()
    shootMurdererTarget()
end)

floatTpActionBtn.MouseButton1Click:Connect(function()
    teleportToPickGun()
end)

local function SkidFling(TargetPlayer)
    if not TargetPlayer then return end
    local Character = LocalPlayer.Character
    local Humanoid = Character and
Character:FindFirstChildOfClass("Humanoid")
    local RootPart = Humanoid and Humanoid.RootPart
    local TCharacter = TargetPlayer.Character
    if not TCharacter then return end
```

```
    local THumanoid = TCharacter:FindFirstChildOfClass("Humanoid")
    local TRootPart = THumanoid and THumanoid.RootPart
    local THead = TCharacter:FindFirstChild("Head")
    local Accessory = TCharacter:FindFirstChildOfClass("Accessory")
    local Handle = Accessory and Accessory:FindFirstChild("Handle")

    if Character and Humanoid and RootPart then
        isFlinging = true
        if RootPart.Velocity.Magnitude < 50 then
            getgenv().OldPos = RootPart.CFrame
        end

        if THumanoid and THumanoid.Sit then
            isFlinging = false
            return
        end

        if THead then
            workspace.CurrentCamera.CameraSubject = THead
        elseif Handle then
            workspace.CurrentCamera.CameraSubject = Handle
        elseif THumanoid and TRootPart then
            workspace.CurrentCamera.CameraSubject = THumanoid
        end

        if not TCharacter:FindFirstChildWhichIsA("BasePart") then
            isFlinging = false
            return
        end

        local FPos = function(BasePart, Pos, Ang)
            RootPart.CFrame = CFrame.new(BasePart.Position) * Pos *
Ang

Character:SetPrimaryPartCFrame(CFrame.new(BasePart.Position) * Pos *
Ang)
            RootPart.Velocity = Vector3.new(9e7, 9e7 * 10, 9e7)
            RootPart.RotVelocity = Vector3.new(9e8, 9e8, 9e8)
        end

        local SFBasePart = function(BasePart)
            local TimeToWait = 2
            local Time = tick()
            local Angle = 0
            repeat
                if RootPart and THumanoid then
                    if BasePart.Velocity.Magnitude < 50 then
                        Angle = Angle + 100
```

```
                        FPos(BasePart, CFrame.new(0, 1.5, 0) +
THumanoid.MoveDirection * BasePart.Velocity.Magnitude / 1.25,
CFrame.Angles(math.rad(Angle),0 ,0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0) +
THumanoid.MoveDirection * BasePart.Velocity.Magnitude / 1.25,
CFrame.Angles(math.rad(Angle), 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, 1.5, 0) +
THumanoid.MoveDirection * BasePart.Velocity.Magnitude / 1.25,
CFrame.Angles(math.rad(Angle),0 ,0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0) +
THumanoid.MoveDirection * BasePart.Velocity.Magnitude / 1.25,
CFrame.Angles(math.rad(Angle), 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, 1.5, 0) +
THumanoid.MoveDirection, CFrame.Angles(math.rad(Angle),0 ,0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0) +
THumanoid.MoveDirection, CFrame.Angles(math.rad(Angle), 0, 0))
                        task.wait()
                    else
                        FPos(BasePart, CFrame.new(0, 1.5,
THumanoid.WalkSpeed), CFrame.Angles(math.rad(90), 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5,
-THumanoid.WalkSpeed), CFrame.Angles(0, 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, 1.5,
THumanoid.WalkSpeed), CFrame.Angles(math.rad(90), 0, 0))
                        task.wait()

                        FPos(BasePart, CFrame.new(0, -1.5, 0),
CFrame.Angles(math.rad(90), 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0),
CFrame.Angles(0, 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0),
CFrame.Angles(math.rad(90), 0, 0))
                        task.wait()
                        FPos(BasePart, CFrame.new(0, -1.5, 0),
CFrame.Angles(0, 0, 0))
                        task.wait()
                    end
                end
            until Time + TimeToWait < tick()
```

```
        end

        workspace.FallenPartsDestroyHeight = 0/0

        local BV = Instance.new("BodyVelocity")
        BV.Parent = RootPart
        BV.Velocity = Vector3.new(0, 0, 0)
        BV.MaxForce = Vector3.new(9e9, 9e9, 9e9)

        Humanoid:SetStateEnabled(Enum.HumanoidStateType.Seated, false)

        if TRootPart then
            SFBasePart(TRootPart)
        elseif THead then
            SFBasePart(THead)
        elseif Handle then
            SFBasePart(Handle)
        else
            BV:Destroy()
            Humanoid:SetStateEnabled(Enum.HumanoidStateType.Seated,
true)
            isFlinging = false
            return
        end

        BV:Destroy()
        Humanoid:SetStateEnabled(Enum.HumanoidStateType.Seated, true)
        workspace.CurrentCamera.CameraSubject = Humanoid

        if getgenv().OldPos then
            repeat
                RootPart.CFrame = getgenv().OldPos * CFrame.new(0, .5,
0)
                Character:SetPrimaryPartCFrame(getgenv().OldPos *
CFrame.new(0, .5, 0))
                Humanoid:ChangeState("GettingUp")
                for _, part in pairs(Character:GetChildren()) do
                    if part:IsA("BasePart") then
                        part.Velocity, part.RotVelocity =
Vector3.new(), Vector3.new()
                    end
                end
                task.wait()
            until (RootPart.Position - getgenv().OldPos.p).Magnitude <
25
            workspace.FallenPartsDestroyHeight = getgenv().FPDH or
-500
        end
```

```
        isFlinging = false
    end
end

RunService.Stepped:Connect(function()
    if antiFlingEnabled then
        for _, player in pairs(Players:GetPlayers()) do
            if player ~= LocalPlayer and player.Character then
                for _, part in pairs(player.Character:GetChildren())
do
                    if part:IsA("BasePart") then
                        part.CanCollide = false
                    end
                end
            end
        end

        if not isFlinging then
            local char = LocalPlayer.Character
            if char then
                local hrp = char:FindFirstChild("HumanoidRootPart")
                if hrp then
                    if hrp.Velocity.Magnitude > 100 then
                        hrp.Velocity = Vector3.new(0, 0, 0)
                    end
                    if hrp.RotVelocity.Magnitude > 100 then
                        hrp.RotVelocity = Vector3.new(0, 0, 0)
                    end
                end
            end
        end
    end

    if noclipEnabled then
        local char = LocalPlayer.Character
        if char then
            for _, part in pairs(char:GetDescendants()) do
                if part:IsA("BasePart") then
                    part.CanCollide = false
                end
            end
        end
    end
end)

RunService.RenderStepped:Connect(function()
    if speedEnabled then
        local char = LocalPlayer.Character
```

```
        if char then
            local hum = char:FindFirstChildOfClass("Humanoid")
            if hum then
                hum.WalkSpeed = 35
            end
        end
    end
end)

UserInputService.JumpRequest:Connect(function()
    if infJumpEnabled then
        local char = LocalPlayer.Character
        if char then
            local hum = char:FindFirstChildOfClass("Humanoid")
            if hum then
                hum:ChangeState(Enum.HumanoidStateType.Jumping)
            end
        end
    end
end)

task.spawn(function()
    local isPickingUp = false
    while true do
        task.wait(0.1)
        if autoGunEnabled and not isPickingUp and not isTpPicking then
            local char = LocalPlayer.Character
            if char then
                local hrp = char:FindFirstChild("HumanoidRootPart")
                local hum = char:FindFirstChildOfClass("Humanoid")

                if hrp and hum and hum.Health > 0 and not
playerHasGun() then
                    local gunPart = getDroppedGunPart()
                    if gunPart and gunPart:IsA("BasePart") then
                        isPickingUp = true
                        local savedCFrame = hrp.CFrame
                        local startTime = tick()

                        repeat
                            if not hrp or not hum or hum.Health <= 0
then break end
                            hrp.CFrame = gunPart.CFrame

                            pcall(function()
                                if firetouchinterest then
                                    firetouchinterest(hrp, gunPart, 0)
                                    task.wait()
```

```
                                    firetouchinterest(hrp, gunPart, 1)
                                end
                            end)

                            task.wait(0.05)
                        until playerHasGun() or not gunPart.Parent or
(tick() - startTime > 0.5)

                        if hrp and hum and hum.Health > 0 then
                            hrp.CFrame = savedCFrame
                        end

                        task.wait(0.3)
                        isPickingUp = false
                    end
                end
            end
        end
    end
end)

local function updateRolesFromData()
    pcall(function()
        local getPlayerData =
ReplicatedStorage:FindFirstChild("GetPlayerData", true)
        if getPlayerData and getPlayerData:IsA("RemoteFunction") then
            local data = getPlayerData:InvokeServer()
            if data and type(data) == "table" then
                for playerName, playerData in pairs(data) do
                    local player = Players:FindFirstChild(playerName)
                    if player and playerData.Role then
                        if playerData.Role == "Murderer" then
                            playerRoles[player] = "Murderer"
                        elseif playerData.Role == "Sheriff" or
playerData.Role == "Hero" then
                            playerRoles[player] = "Sheriff"
                        elseif playerData.Role == "Innocent" then
                            playerRoles[player] = "Innocent"
                        end
                    end
                end
            end
        end
    end)
end

local function checkItem(item, player)
    if not item or not item:IsA("Tool") then return end
```

```
    local name = item.Name:lower()

    if name:find("knife") or name:find("มีด") or
item:FindFirstChild("KnifeServer") or
item:FindFirstChild("KnifeLocal") or item:FindFirstChild("Blade") then
        playerRoles[player] = "Murderer"
    elseif name:find("gun") or name:find("revolver") or name:find
("ปืน") or item:FindFirstChild("GunServer") or
item:FindFirstChild("GunLocal") or item:FindFirstChild("Shoot") then
        playerRoles[player] = "Sheriff"
    end
end

local function setupPlayerListener(player)
    local function onCharacterAdded(char)
        playerRoles[player] = "Innocent"
        cleanupPlayerESP(player)

        local backpack = player:WaitForChild("Backpack", 5)
        if backpack then
            for _, item in pairs(backpack:GetChildren()) do
                checkItem(item, player)
            end
            backpack.ChildAdded:Connect(function(item)
                checkItem(item, player)
            end)
        end

        for _, item in pairs(char:GetChildren()) do
            checkItem(item, player)
        end
        char.ChildAdded:Connect(function(item)
            checkItem(item, player)
        end)
    end

    if player.Character then
        task.spawn(onCharacterAdded, player.Character)
    end
    player.CharacterAdded:Connect(onCharacterAdded)
end

for _, p in pairs(Players:GetPlayers()) do
    setupPlayerListener(p)
end
Players.PlayerAdded:Connect(setupPlayerListener)

Players.PlayerRemoving:Connect(function(player)
```

```
    cleanupPlayerESP(player)
    playerRoles[player] = nil
end)

task.spawn(function()
    while true do
        updateRolesFromData()
        task.wait(0.5)
    end
end)

local function update3DESP()
    if not esp3DEnabled then return end

    for _, player in pairs(Players:GetPlayers()) do
        if player ~= LocalPlayer and player.Character and
player.Character:FindFirstChild("HumanoidRootPart") then
            local char = player.Character
            local role = playerRoles[player] or "Innocent"
            local fillColor, outlineColor = getRoleColors(role)

            local highlight = highlights[player]
            if not highlight or highlight.Parent ~= char then
                if highlight then highlight:Destroy() end
                highlight = Instance.new("Highlight")
                highlight.Name = "RoleHighlight3D"
                highlight.FillTransparency = 0.45
                highlight.OutlineTransparency = 0
                highlight.Parent = char
                highlights[player] = highlight
            end

            highlight.FillColor = fillColor
            highlight.OutlineColor = outlineColor
        else
            if highlights[player] then
                highlights[player]:Destroy()
                highlights[player] = nil
            end
        end
    end
end

local function update2DBoxes()
    for _, player in pairs(Players:GetPlayers()) do
        local boxFrame = boxFrames[player]

        if boxESPEnabled and player ~= LocalPlayer and
```

```
player.Character then
            local char = player.Character
            local hrp = char:FindFirstChild("HumanoidRootPart")
            local head = char:FindFirstChild("Head")
            local hum = char:FindFirstChildOfClass("Humanoid")

            if hrp and head and hum and hum.Health > 0 then
                local hrpPos, onScreen =
Camera:WorldToViewportPoint(hrp.Position)

                if onScreen and hrpPos.Z > 0 then
                    local headPos =
Camera:WorldToViewportPoint(head.Position + Vector3.new(0, 0.5, 0))
                    local legPos =
Camera:WorldToViewportPoint(hrp.Position - Vector3.new(0, 3, 0))

                    local height = math.abs(headPos.Y - legPos.Y)
                    local width = height * 0.65

                    if not boxFrame or not boxFrame.Parent then
                        boxFrame = Instance.new("Frame")
                        boxFrame.Name = "Box_" .. player.Name
                        boxFrame.BackgroundTransparency = 1
                        boxFrame.BorderSizePixel = 0
                        boxFrame.Parent = espContainer

                        local stroke = Instance.new("UIStroke")
                        stroke.Name = "BoxStroke"
                        stroke.Thickness = 1.8
                        stroke.LineJoinMode = Enum.LineJoinMode.Miter
                        stroke.Parent = boxFrame

                        boxFrames[player] = boxFrame
                    end

                    local role = playerRoles[player] or "Innocent"
                    local color, _ = getRoleColors(role)

                    boxFrame.Size = UDim2.new(0, width, 0, height)
                    boxFrame.Position = UDim2.new(0, hrpPos.X - width
/ 2, 0, headPos.Y)

                    local stroke =
boxFrame:FindFirstChild("BoxStroke")
                    if stroke then
                        stroke.Color = color
                    end
                    boxFrame.Visible = true
```

```
                else
                    if boxFrame then boxFrame.Visible = false end
                end
            else
                if boxFrame then boxFrame.Visible = false end
            end
        else
            if boxFrame then boxFrame.Visible = false end
        end
    end
end

local function updateTracers()
    local topCenter = Vector2.new(Camera.ViewportSize.X / 2, 0)

    for _, player in pairs(Players:GetPlayers()) do
        local lineFrame = lineFrames[player]

        if tracersESPEnabled and player ~= LocalPlayer and
player.Character then
            local char = player.Character
            local hrp = char:FindFirstChild("HumanoidRootPart")
            local hum = char:FindFirstChildOfClass("Humanoid")

            if hrp and hum and hum.Health > 0 then
                local hrpPos, onScreen =
Camera:WorldToViewportPoint(hrp.Position)

                if onScreen and hrpPos.Z > 0 then
                    if not lineFrame or not lineFrame.Parent then
                        lineFrame = Instance.new("Frame")
                        lineFrame.Name = "Tracer_" .. player.Name
                        lineFrame.BorderSizePixel = 0
                        lineFrame.AnchorPoint = Vector2.new(0.5, 0.5)
                        lineFrame.Parent = espContainer
                        lineFrames[player] = lineFrame
                    end

                    local targetPos = Vector2.new(hrpPos.X, hrpPos.Y)
                    local distance = (targetPos - topCenter).Magnitude
                    local center = (topCenter + targetPos) / 2
                    local angle = math.deg(math.atan2(targetPos.Y -
topCenter.Y, targetPos.X - topCenter.X))

                    local role = playerRoles[player] or "Innocent"
                    local color, _ = getRoleColors(role)

                    lineFrame.Size = UDim2.new(0, distance, 0, 1.5)
```

```
                    lineFrame.Position = UDim2.new(0, center.X, 0,
center.Y)
                    lineFrame.Rotation = angle
                    lineFrame.BackgroundColor3 = color
                    lineFrame.Visible = true
                else
                    if lineFrame then lineFrame.Visible = false end
                end
            else
                if lineFrame then lineFrame.Visible = false end
            end
        else
            if lineFrame then lineFrame.Visible = false end
        end
    end
end

RunService.RenderStepped:Connect(function()
    pcall(function()
        update3DESP()
        update2DBoxes()
        updateTracers()
    end)
end)

local TabMain = Window:Tab({ Title = "หลัก" })
local TabPlayer = Window:Tab({ Title = "ตัวละคร" })
local TabESP = Window:Tab({ Title = "ESP" })
local TabFloat = Window:Tab({ Title = "ปุ่มลอย" })
local TabCredit = Window:Tab({ Title = "เครดิต" })

TabMain:Section({ Title = "ระบบหลัก" })

TabMain:Toggle({
    Title = "เก็บปืนออโต้",
    Default = false,
    Callback = function(val)
        autoGunEnabled = val
    end
})

TabMain:Button({
    Title = "ปลิวฆาตกร",
    Callback = function()
        task.spawn(function()
            local murderer = getPlayerByRole("Murderer")
            if murderer then
                SkidFling(murderer)
```

```
            end
        end)
    end
})

TabMain:Button({
    Title = "ปลิวนายอำเภอ",
    Callback = function()
        task.spawn(function()
            local sheriff = getPlayerByRole("Sheriff")
            if sheriff then
                SkidFling(sheriff)
            end
        end)
    end
})

TabMain:Toggle({
    Title = "กันปลิว",
    Default = false,
    Callback = function(val)
        antiFlingEnabled = val
    end
})

TabPlayer:Section({ Title = "ตัวละคร" })

TabPlayer:Toggle({
    Title = "เดินทะลุ",
    Default = false,
    Callback = function(val)
        noclipEnabled = val
    end
})

TabPlayer:Toggle({
    Title = "สปีด 35",
    Default = false,
    Callback = function(val)
        speedEnabled = val
        local char = LocalPlayer.Character
        if char then
            local hum = char:FindFirstChildOfClass("Humanoid")
            if hum then
                hum.WalkSpeed = val and 35 or 16
            end
        end
    end
```

```
})

TabPlayer:Toggle({
    Title = "โดดไม่จำกัด",
    Default = false,
    Callback = function(val)
        infJumpEnabled = val
    end
})

TabESP:Section({ Title = "ESP" })

TabESP:Toggle({
    Title = "ESP 3D",
    Default = false,
    Callback = function(val)
        esp3DEnabled = val
        if not val then
            for _, h in pairs(highlights) do
                if h then h:Destroy() end
            end
            table.clear(highlights)
        end
    end
})

TabESP:Toggle({
    Title = "ESP 2D",
    Default = false,
    Callback = function(val)
        boxESPEnabled = val
        if not val then
            for _, b in pairs(boxFrames) do
                if b then b.Visible = false end
            end
        end
    end
})

TabESP:Toggle({
    Title = "ESP เส้น",
    Default = false,
    Callback = function(val)
        tracersESPEnabled = val
        if not val then
            for _, l in pairs(lineFrames) do
                if l then l.Visible = false end
            end
```

```
        end
    end
})

TabFloat:Section({ Title = "ปุ่มลอย" })

TabFloat:Toggle({
    Title = "ยิงฆาตกร",
    Default = false,
    Callback = function(val)
        floatGunBtnEnabled = val
        floatGunBtnFrame.Visible = val
    end
})

TabFloat:Toggle({
    Title = "วาร์ปเก็บปืน",
    Default = false,
    Callback = function(val)
        floatTpGunBtnEnabled = val
        floatTpGunFrame.Visible = val
    end
})

TabFloat:Toggle({
    Title = "ล็อกปุ่มลอย",
    Default = false,
    Callback = function(val)
        floatLocked = val
    end
})

TabCredit:Section({ Title = "เครดิต" })

TabCredit:Button({
    Title = "คัดลอกลิงก์ YouTube ARROW HUB",
    Callback = function()

setclipboard("https://youtube.com/@arrow-hub-script?si=PCMGSEA2xj7rfr8
Z")
        WindUI:Notify({
            Title = "คัดลอกสำเร็จ",
            Content = "คัดลอกลิงก์เรียบร้อย!",
            Duration = 3
        })
    end
})
```

```
WindUI:Notify({
    Title = "ARROW HUB Loaded",
    Content = "โหลดสำเร็จ!",
    Duration = 4
})
```