




Computer Processors

Virtual Machines: Overview



This lecture is based on the excellent course *Nand to Tetr**is* by Noam Nisam and Shimon Schocken, and we reuse here many of the slides provided at www.nand2tetris.org



What is a virtual machine (VM)

VM is used in two different contexts but they share a similar idea:

- *OS virtualization* - allows multiple operating systems to be installed and run concurrently on a single physical machine.
- *Abstract virtual machines* - allow for technical details to be abstracted away from an implementation. This is the technology that underpins modern compiler tool chains.

We are interested in Abstract virtual machines

Why VM?



UNIVERSITY OF LEEDS

```
// First example in Programming 101
class Main {
    function void main() {
        do Output.printString("Hello World!");
        do Output.println(); // New line.
        return;
    }
}
```



Why VM?



UNIVERSITY OF LEEDS

```
// First example in Programming 101
class Main {
    function void main() {
        do Output.printString("Hello World!");
        do Output.println(); // New line.
        return;
    }
}
```

Issues:

- Program execution
- Writing on the screen
- Handling class, function ...
- Handling do, while, ...
- function call and return
- operating system
- ...



Why VM?



UNIVERSITY OF LEEDS

```
// First example in Programming 101
class Main {
    function void main() {
        do Output.printString("Hello World!");
        do Output.println(); // New line.
        return;
    }
}
```

abstraction

Q: How can high-level programmers ignore all these issues?

A: They treat the high-level language as an ***abstraction***.



Why VM?



UNIVERSITY OF LEEDS

```
// First example in Programming 101
class Main {
    function void main() {
        do Output.println("Hello World!");
        do Output.println(); // New line.
        return;
    }
}
```

abstraction

Q: What makes the abstraction work?

A:


- Assembler
- Virtual machine
- Compiler
- Operating system



Why VM?



UNIVERSITY OF LEEDS





Why VM? 1-tier compilation:

High-level code

```
// First example in Programming 101
class Main {
    function void main() {
        do Output.printString("Hello World!");
        do Output.println(); // New line.
        return;
    }
}
```


Compiler

Low-level code

```
00000000000010000
1110111111001000
00000000000010001
1110101010001000
00000000000010000
1111110000010000
00000000000000000
1111010011010000
00000000000010010
1110001100000001
00000000000010000
1111110000010000
00000000000010001
00000000000010000
1110111111001000
00000000000010001
1110101010001000
00000000000010000
1111110000010000
00000000000000000
1111010011010000
00000000000010010
1110001100000001
00000000000010000
1111110000010000
00000000000010001
1111110000010000
...
```





Why VM? 1-tier compilation:



- There are many different computer architectures
- Thus, it's not enough to write one compiler only, you have to develop many compilers, one for every different architecture.
- To circumvent this issue VM are used




Why VM: 2-tier compilation:



- Translate with compiler to VM language
- Each target architecture is equipped with a particular compiler that allows to translate the VM-code into the specific ML code
- Every of these single “translation” steps is significantly simpler than 1-tier compilation

Virtual Machine (VM)




Virtual Machine

- Understanding the VM abstraction
- Building a VM implementation

Virtual Machine (VM)




UNIVERSITY OF LEEDS



Stack



UNIVERSITY OF LEEDS



Stack = data structure with two operations to manipulate the stack:


- push: add an element at the stack's top
- pop: remove the top element

Known as: **Last-in-First-out (LiFo)** stack

Stack



UNIVERSITY OF LEEDS



sp = stack pointer which “points” to location where next element will be added (top)



VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*


VM and stack machines



UNIVERSITY OF LEEDS


- The VM we use is **stack** based, will support functions and **memory** (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:



- The VM we use is stack based, will support **functions** and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:




Applying a function f on the stack:

- pops the argument(s) from the stack
- Computes f on the arguments
- Pushes the result onto the stack.

- The VM we use is stack based, will support **functions** and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:



Applying a function f on the stack:


- pops the argument(s) from the stack
- Computes f on the arguments
- Pushes the result onto the stack.



VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:






VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:






VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:






VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:






VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:



Applying a function f on the stack:

- pops the argument(s) from the stack
- Computes f on the arguments
- Pushes the result onto the stack.



VM and stack machines

- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:

high-level
program

compiler

VM code

// 2 - (5+7)

push 2


push 5

push 7

add

sub

pop



Applying a function f on the stack:

- pops the argument(s) from the stack
- Computes f on the arguments
- Pushes the result onto the stack.


2 - (5+7) is “translated to” 2 5 7 + -



VM and stack machines


- The VM we use is stack based, will support functions and memory (=stack machine model) which is a common way to represent VMs
- The elements that we push to / pop from the stack are *operands*

Example:



VM and stack machines


Example:



2 - (5+7) is "translated to" 2 5 7 + -

- Arithmetic or logical expressions are in *infix* notation
- The latter translation is known as *postfix* or *reverse polish notation* and this notation can then be translated to VM-code (done by compiler)
- To compute *reverse polish notation* algorithms exist e.g. Dijkstra's *Shunting-yard-Algorithmus*

Virtual Machine (VM)



Virtual Machine

- Understanding the VM abstraction
- Building a VM implementation