

1 Cluster Methods

- Having selected how we will measure distance, we must now choose the clustering algorithm, i.e. the rules that govern between which points distances are measured to determine cluster membership.
- There are many methods available, the criteria used differ and hence different classifications may be obtained for the same data. This is important since it tells us that, although cluster analysis may provide an objective method for the clustering of cases, there can be subjectivity in the choice of method.
- The linkage distances are calculated by SPSS. The goal of the clustering algorithm is to join objects together into successively larger clusters, using some measure of similarity or distance. SPSS provides seven clustering algorithms, the most commonly used one being *Ward's method*.
- SPSS provides several alternative methods for determining a summary measure of distance when a cluster has multiple cases in the cluster.
- The SPSS options for the clustering method are Between-groups linkage, Within-groups linkage, Nearest neighbor, Furthest neighbor, Centroid clustering, Median clustering, and Ward's method.

1.1 Nearest Neighbour Method

- In this method the distance between two clusters is defined to be the distance between the two closest members, or neighbours.
- For the **nearest neighbor** or **single linkage** method, the dissimilarity between cluster A and cluster B is represented by the minimum of all possible distances between the cases in cluster A and the cases in cluster B.
- The distance between two clusters corresponds to the shortest distance between any two members in the two clusters.




Figure 1: Single linkage (nearest neighbor)

- This method is relatively simple but is often criticised because it doesn't take account of cluster structure and can result in a problem called **chaining** whereby clusters end up being long and straggly.
- However, it is better than the other methods when the natural clusters are not spherical or elliptical in shape.

1.2 Furthest Neighbour Method

- For the **furthest neighbor** or **complete linkage** method, the dissimilarity between cluster A and cluster B is represented by the maximum of all possible distances between the cases in cluster A and the cases in cluster B.
- In this case the distance between two clusters is defined to be the maximum distance between members, i.e. the distance between the two subjects that are furthest apart.
- This method tends to produce compact clusters of similar size but, as for the nearest neighbour method, does not take account of cluster structure. It is also quite sensitive to outliers.




Figure 2: Complete linkage (furthest neighbor)

- This is the oppositional approach to single linkage assumes that the distance between two clusters is based on the longest distance between any two members in the two clusters.

1.3 Average (between groups) Linkage Method

(sometimes referred to as UPGMA).

- For the **between-groups linkage** or average linkage method, the dissimilarity between cluster A and cluster B is represented by the **average of all the possible distances** between the cases in cluster A and the cases in cluster B.
- This is considered to be a fairly robust method.




Figure 3: Average linkage

1.4 Centroid Method

- For the **centroid clustering** method, the dissimilarity between cluster A and cluster B is represented by the *distance between the centroid* for the cases in cluster A and the centroid for the cases in cluster B.
- In this approach, the geometric center (centroid) of each cluster is computed first. Then the distance between the two clusters equals the distance between the two centroids.
- Note that this distance is not mathematically equivalent to the average of the distances used in the average linkage method.

Also note the SPSS warning below about using squared Euclidean distance rather than Euclidean distance for this procedure.




Figure 4: centroid

- This method is also fairly robust.

1.5 Median Clustering


- For the **median clustering** method, the dissimilarity between cluster A and cluster B is represented by the distance between the SPSS determined median for the cases in cluster A and the median for the cases in cluster B. See the message in the note above about using squared Euclidean distance rather than Euclidean distance for this method.

1.6 Wards method: Within-Groups linkage method

- For the **within-groups linkage** method, the dissimilarity between cluster A and cluster B is represented by the average of all the possible distances between the cases within a single new cluster determined by combining cluster A and cluster B.
- **Important:** For a cluster the sum of squares is the sum of squared deviations of each case from the centroid for the cluster. The error sum of squares is the total of these for all clusters.
- **Important:** In this method all possible pairs of clusters are combined and the sum of the squared distances within each cluster is calculated. This is then summed over all clusters. The combination that gives the lowest sum of squares is chosen.
- The dissimilarity between cluster A and cluster B is represented by the loss of information from joining the two clusters with this loss of information being measured by the increase in error sum of squares.
- When selecting clusters to join, the two clusters among all possible combinations that have the minimum increase in error sum of squares are selected.
- This method tends to produce clusters of approximately equal size, which is not always desirable. It is also quite sensitive to outliers. Despite this, it is one of the most popular methods, along with the average linkage method.

• Average Linkage

- Clustering criterion based on the average distance



• Ward's Method

- Based on the loss of information resulting from grouping of the objects into clusters (minimize within cluster variation)



- A commonly used approach in hierarchical clustering is **Wards linkage method**. This approach does not combine the two most similar objects successively. Instead, those objects whose merger increases the overall within-cluster variance to the smallest possible degree, are combined.
- If you expect somewhat equally sized clusters and the data set does not include outliers, you should always use Wards method.
- We will use the Ward's linkage method for laboratory exercises.

1.7 Summary

- Each of these linkage algorithms can yield totally different results when used on the same data set, as each has its specific properties.
- As the single linkage algorithm is based on minimum distances, it tends to form one large cluster with the other clusters containing only one or few objects each. We can make use of this ***chaining effect*** to detect outliers, as these will be merged with the remaining objects usually at very large distances in the last steps of the analysis. Generally, single linkage is considered the most versatile algorithm.
- Conversely, the complete linkage method is strongly affected by outliers, as it is based on maximum distances. Clusters produced by this method are likely to be rather compact and tightly clustered.
- The average linkage and centroid algorithms tend to produce clusters with rather low within-cluster variance and similar sizes. However, both procedures are affected by outliers, though not as much as complete linkage.
- **Important:** An understanding of linkage method's other than than Ward method will be expected in the end of year examination.