

Seeded records

What this run wrote, and what it deliberately did not.

Database	telecom
Tenant	tenant-eu-1
Run at	2026-08-31 02:46:00 UTC
Records written	110

Collections written

“Written” counts this run only. Upsert collections rewrite in place, so a second run reports the same number; insert-only collections (tickets, callbacks, approvals) skip references that already exist and report 0.

Collection	Written this run	Total in database
customers	12	12
services	12	12
orders	12	12
invoices	12	12
Total	110	110

Collection	Written this run	Total in database
network_status	10	10
agent_assignments	10	10
tickets	12	12
callbacks	10	10
approval_requests	10	10
cases	10	10
Total	110	110

Collections left alone

Each of these is written by the service itself. Inserting invented rows would break the audit chain or the event sequence the rest of the design depends on.

Collection	Total in database	Why
audit_records	41	Append-only and hash-chained. An invented row breaks verification.
outbox	0	Written inside the transaction that produces the event it carries.
tenant_sequences	1	One document per tenant, maintained by the service itself.
idempotency_keys	0	Write-deduplication with a TTL; entries expire themselves.

Collection	Total in database	Why
stream_tokens	0	Change-stream resume positions, owned by the running service.

Reference ranges

Collection	References
customers	CX-2001 – CX-2012
services	SVC-B-0001 – SVC-B-0012
orders	ORD-B-0001 – ORD-B-0012
invoices	INV-B-0001 – INV-B-0012
network_status	AREA-BULK-01 – AREA-BULK-10
agent_assignments	auth0 agent-7 → CX-2001 – CX-2010
tickets	TCK-bulk-0001 – TCK-bulk-0012
callbacks	CB-bulk-0001 – CB-bulk-0010
approval_requests	APR-bulk-0001 – APR-bulk-0010
cases	CASE-bulk-0001 – CASE-bulk-0010

Passcode for every seeded customer is 4821, Argon2id-hashed exactly as a real one would be. Demo credential, demo dataset.