

Webserver

Installing httpd in centos using yum




Open default directory and create an index.html page





Its a sample html page . Now copy the ip address of server and paste it on firefox

```
[root@server html]# ifconfig
ens33: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
       inet 192.168.19.134 netmask 255.255.255.0 broadcast 192.168.19.255
       inet6 fe80::ae7f:cdb3:8f07:eac4 prefixlen 64 scopeid 0x20<link>
       ether 00:0c:29:09:19:d1 txqueuelen 1000 (Ethernet)
       RX packets 9403 bytes 11820869 (11.2 MiB)
       RX errors 0 dropped 0 overruns 0 frame 0
       TX packets 2243 bytes 328514 (320.8 KiB)
       TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
lo: flags=73<UP,L00PBACK,RUNNING> mtu 65536
       inet 127.0.0.1 netmask 255.0.0.0
       inet6 ::1 prefixlen 128 scopeid 0x10<host>
       loop txqueuelen 1000 (Local Loopback)
       RX packets 198 bytes 40579 (39.6 KiB)
       RX errors 0 dropped 0 overruns 0 frame 0
       TX packets 198 bytes 40579 (39.6 KiB)
       TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
virbr0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
       inet 192.168.122.1 netmask 255.255.255.0 broadcast 192.168.122.255
       ether 52:54:00:95:7e:ba txqueuelen 1000 (Ethernet)
       RX packets 0 bytes 0 (0.0 B)
       RX errors 0 dropped 0 overruns 0 frame 0
       TX packets 0 bytes 0 (0.0 B)
       TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
[root@server html]#
root@server:/var/www/html
                                [Wipro - Mozilla Firefox]
```



Done!