



# Express

## Serving static files in Express

To serve static files such as images, CSS files, and JavaScript files, use the `express.static` built-in middleware function in Express.

The function signature is:

```
express.static(root, [options])
```

The `root` argument specifies the root directory from which to serve static assets. For more information on the `options` argument, see [express.static](#).

For example, use the following code to serve images, CSS files, and JavaScript files in a directory named `public`:

```
app.use(express.static('public'))
```

Now, you can load the files that are in the `public` directory:

```
http://localhost:3000/images/kitten.jpg  
http://localhost:3000/css/style.css  
http://localhost:3000/js/app.js  
http://localhost:3000/images/bg.png  
http://localhost:3000/hello.html
```

Express looks up the files relative to the static directory, so the name of the static directory is not part of the URL.

To use multiple static assets directories, call the `express.static` middleware function multiple times:

```
app.use(express.static('public'))  
app.use(express.static('files'))
```

Express looks up the files in the order in which you set the static directories with the `express.static` middleware function.



# Express

To create a virtual path prefix (where the path does not actually exist in the file system) for files that are served by the `express.static` function, [specify a mount path](#) for the static directory, as shown below:

```
app.use('/static', express.static('public'))
```

Now, you can load the files that are in the `public` directory from the `/static` path prefix.

```
http://localhost:3000/static/images/kitten.jpg
http://localhost:3000/static/css/style.css
http://localhost:3000/static/js/app.js
http://localhost:3000/static/images/bg.png
http://localhost:3000/static/hello.html
```

However, the path that you provide to the `express.static` function is relative to the directory from where you launch your `node` process. If you run the express app from another directory, it's safer to use the absolute path of the directory that you want to serve:

```
app.use('/static', express.static(path.join(__dirname, 'public')))
```

For more details about the `serve-static` function and its options, see [serve-static](#).

Documentation translations provided by [StrongLoop/IBM](#): [French](#), [German](#), [Spanish](#), [Italian](#), [Japanese](#), [Russian](#), [Chinese](#), [Traditional Chinese](#), [Korean](#), [Portuguese](#).

Community translation available for: [Slovak](#), [Ukrainian](#), [Uzbek](#), [Turkish](#) and [Thai](#).



★ Star

[Express](#) is a project of the Node.js Foundation.

[Edit this page on GitHub](#).

Copyright © 2017 StrongLoop, IBM, and other [expressjs.com](#) contributors.



This work is licensed under a [Creative Commons Attribution-ShareAlike 3.0 United States License](#).