

CS251 - Data Structures and Algorithms

Fall 2024

PSO 6, Week 7

Question 1

(Hashing) Let T be an empty hash table of length $m = 12$ with $h(k) = k \bmod 12$ for $k \in \mathbb{Z}^+$. T uses linear probing as a collision management technique. The following is the content of T after inserting six values.

0	1	2	3	4	5	6	7	8	9	10	11
				16	17	28	18	8	31		

- (a) Write an order of insertion for these six values such that the state of T is the one displayed above.
- (b) Can another insertion order give the same state? Explain your answer.
- (c) What is the load factor of T ? Is there any issue occurring in T ?
- (d) Illustrate T if the collision management technique used was chaining.

Question 2**(Binary search tree)**

- (1) How many different shapes of a binary search tree are possible when 3 elements are inserted into?
- (2) What is the asymptotic performance of inserting n items with keys sorted in a descending order into an initially empty binary search tree?
- (3) Is the operation of deletion “commutative” in the sense that deleting x and then y from a binary search tree leaves the same tree as deleting y and then x ? Argue why it is or give a counterexample.

Question 3

(Binary search tree)

How to find the minimum distance between any two different nodes in a BST efficiently?

Question 4**(2-3 tree)**

- (1) How many 2-3 trees exist storing the keys $\{1, 2, 3, 4, 5\}$?
- (2) Insert $\{15, 21, 7, 24, 0, 26, 3, 28, 29\}$ (in the given order) into an initially empty 2-3 tree.
- (3) Delete element 7 in the final 2-3 tree obtained in question (2).