


PoC

This write-up uses only IDA Free and the participant-deliverable [release/Sudoku.exe](#). No source code or debugger is required.


1. Find the interesting string

After completing the puzzle, the game displays:

Secret reward unavailable.



Open [release/Sudoku.exe](#) in IDA Free, wait for auto-analysis to finish, and search for that string in the Strings window. Follow its DATA XREF. The reference leads to the normal-win branch of the completion-check function.



2. Find the hidden condition

Inspect the nearby control-flow graph. The important instructions are:

```

mov     eax, cs:dword_1400092E8
cmp     eax, 539h
jnz     short normal_win
call    sub_140001D1A
  
```


539h is hexadecimal for decimal 1337. The code is equivalent to:

```

if (secret_score == 1337)
    reveal_flag();
else
    show_normal_win();
  
```

This explains why normal completion produces `Secret reward unavailable.`: normal gameplay does not make the hidden score equal 1337.

3. Decode the flag



Follow `sub_140001D1A`. It uses `0x5A` as the initial value and each ciphertext byte as the next XOR value:

Raw IDA decompilation:

```

__int64 sub_140001D1A()
{
    _BYTE v1[267]; // [rsp+20h] [rbp-60h] BYREF
    char v2; // [rsp+12Bh] [rbp+ABh]

```

```

int i; // [rsp+12Ch] [rbp+ACH]

v2 = 90;
for ( i = 0; i <= 41; ++i )
{
    v1[i] = v2 ^ byte_140006000[i];
    v2 = byte_140006000[i];
}
v1[42] = 0;
return sub_140001975(a1: v1);
}

```

The same logic, rewritten with descriptive names, is:

```

unsigned char previous = 0x5A;

for (int i = 0; i < 42; i++) {
    decoded[i] = encrypted[i] ^ previous;
    previous = encrypted[i];
}

decoded[42] = '\0';
show_flag(decoded);

```

The 42 bytes referenced by `byte_140006000` are:

```

10 53 10 6B 18 6D 09 39 52 27 78 16 25 53 60 12
4D 2A 1B 6D 5E 01 6C 09 56 22 4A 79 26 55 30 53
61 52 26 79 0A 69 59 2B 4E 33

```

The `SUDOKU` bytes after the array belong to unused alternate mode data; they are not used by this chained-XOR loop.

Use this small decoder:

```

encrypted = bytes.fromhex(
    "10 53 10 6B 18 6D 09 39 52 27 78 16 25 53 60 12 "
    "4D 2A 1B 6D 5E 01 6C 09 56 22 4A 79 26 55 30 53 "
    "61 52 26 79 0A 69 59 2B 4E 33"
)

previous = 0x5A
decoded = bytearray()
for value in encrypted:
    decoded.append(value ^ previous)
    previous = value

```

```
print(decoded.decode("ascii"))
```

Output:

```
JCC{sud0ku_n3v3r_g1v3_me_th3_sec23t_sc0re}
```

This static route recovers the flag directly from the executable.