API Specification Doc

(weticketit.com *Winner Approval API*)

Version	Date	Author	Description
1.0	25 Mar 2024	Jeremy Mascarenhas	Initial draft

Overview

The Winner Decision API allows for the random decisioning of a potential winner for a given promotion in ‘gameplay’ mode. The decisioning includes (a) whether they have won or not, (b) what they’ve won and (c) any associated information around that reward. It takes place in a single call.

Index

1. Core API Info
    - Authentication
2. Get Winner Decision
    - Request
    - Response
    - Response library
5. Conventions
6. Status Codes
7. Library
8. IP Whitelist

1. Core API Information

Section : General
SECURITY
DATA IN TRANSIT: HTTPS / 256 BIT
API restricted to PARTNER server IP
Testing Base URL: https://mp-staging.co.uk/master
Live URL: https://www.weticketit.com/<partner>
BLOCK : Request is from an unauthorized IP

Authentication

The Weticketit Winner Decision API uses API user ID and key pairs to authenticate requests. Use your API key by setting your **Userid** and **Apikey** in the **header** of each API call.

All API calls must be over HTTPS and from whitelisted IP addresses only.

Methods

2. Put Winner Status

Identify if this current user is a winner, and if so what they have won and any instructions.

Request

Method	URL
PUT	/api/rewards/<partyID>/<promoID>/<fixtureID>/<token>

Request Input Library

Params	Type	Can it be empty?	Description

partyID	alphanumeric	no	Unique identifier of the user This will be posted to the game when launching
promoID	numeric	no	Primary unique identifier of the related promotion. This will be posted to the game when launching
fixtureID	numeric	no	Unique identifier of the fixture. This will be posted to the game when launching
token	alphanumeric	no	This is a validation hash for the other parameters. This will be posted to the game when launching

Response

Status	Response

200	**An array containing the relevant data sets is given**
	
	Example response:-
	
	{
	"uid": "abc123",
	"promo_id": "613",
	"treat_id": "KON65038",
	"promo_title": "LV= Insurance County Championship",
	"fixture_id": "14486",
	"success": 1,
	"reward_name": "A 3 Days 2 night Holiday",
	"reward_detail": "Click 'continue' for instructions on how to claim your Holiday.",
	"session_token": "67c6e6cde7898d935a78b09f2e47d0dcc4eb718f",
	"expires": "2024-03-25T11:04:37+00:00"
	}

403	{"error":"Error code 1111. Unauthorised."}
500	{"error":"Something went wrong. Please try again later."}

Response Library

Params	Type	Can it be empty?	Description
uid	alphanumeric	no	Unique identifier of the user
promo_id	numeric	no	Primary unique identifier of the related promotion
treat_id	alphanumeric	no	Secondary unique identifier of the related promotion
promo_title	string[100]	no	Title of the promotion
fixture_id	numeric	no	Unique identifier of the related fixture
success	enum(0,1)	no	1=winner 0=not a winner
reward_name	text	no	The top-line name of the reward that has been won.
reward_detail	text	yes	Written description of the reward or the redemption method or next steps.
session_token	alphanumeric	no	This is a unique token which will need to be used with any future calls.

expires	datetime	no	At this point in time, the reward win will expire and is no longer valid. After this point, if not claimed, another game can be played.

5. Conventions

- **Client** - Client application.
- **Status** - HTTP status code of response.
- All the possible responses are listed under 'Responses' for each method. Only one of them is issued per request server.
- All response are in JSON format.
- All request parameters are mandatory unless explicitly marked as `[optional]`

6. Status Codes

All status codes are standard HTTP status codes. The below ones are used in this API.

2XX - Success of some kind
4XX - Error occurred in client's part
5XX - Error occurred in server's part

Status Code	Description
200	OK
400	Bad request
401	Authentication failure
403	Forbidden
404	Resource not found
405	Method Not Allowed
409	Conflict
412	Precondition Failed

413	Request Entity Too Large
500	Internal Server Error
501	Not Implemented
503	Service Unavailable

7. IP Whitelist

Production -
Non-prod -

8. Limits

The API is limited to X requests per minute