

Online Booking API

The Online Booking API allows third-party systems to integrate with Garage Hive's online booking feature and build their own booking experiences. It provides a structured workflow that mirrors the steps a user would normally complete in an online booking form. This API is fully built by Garage Hive and requires a  [Garage Link Advanced Plus](#) subscription.

Using this API, an integration can create booking sessions, identify the vehicle and location, select services and add-ons, retrieve available appointment times, and confirm the booking with customer details.

For authentication overview and general setup, see  [Getting Started with Garage Hive APIs](#) .

TABLE OF CONTENTS

- Base URL
 - Authentication
 - Key Concepts
 - Booking Flow
 - Endpoints
 - 1. Initialise Booking
 - 2. Set Vehicle Information
 - 3. List Services
 - 4. Set Services
 - 5. List Additional Services
 - 6. Add Additional Service
 - 7. Remove Service
 - 8. List Available Timeslots
 - 9. Set Timeslot
 - 10. Set Contact Information
 - Error Handling
 - See Also
-

Base URL

```
1 https://{onlinebooking_url}/api/external-  
   booking/{instance}
```

Example:

```
1 https://api.example.com/api/external-booking/prod
```

Authentication

All endpoints require a Bearer token in the request header:

```
1 Authorisation: Bearer {token}
```

```
2  Accept: application/json
```

Key Concepts

Instance

The `instance` identifies the booking tenant or environment. Please contact support to retrieve your instance details.

Booking Session

Every booking is created and managed through a session. Each session has a unique `session_id`, which is returned by the Initialise Booking endpoint and must be included in all subsequent requests.

Booking Flow

The API follows a sequential workflow. Each step must be completed before moving to the next.

Endpoints

1. Initialise Booking

Creates a new booking session. This is always the first call in the booking flow.

Request

```
1  POST /api/external-booking/{instance}/init
```

Example

```
1  POST /api/external-booking/prod/init
```

Response

```
1  {
2    "status": "success",
3    "booking": {
4      "session_id":
5        "60e059079f86325cded05a63bb8e4b77",
6      "external_booking_provider_id": 1
7    },
8    "locations": [],
9    "reg_no_countries": []
10 }
```

Field	Description
session_id	Unique booking session identifier — include in all subsequent requests
locations	Available booking locations
reg_no_countries	Supported vehicle registration countries

2. Set Vehicle Information

Associates a vehicle and location with the booking session.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-vehicle-info
```

Body

```
1  {  
2    "registration_no": "14VW",  
3    "reg_no_country": "GB",  
4    "location_id": 399  
5  }
```

Field	Description
registration_no	Vehicle registration number
reg_no_country	Country code for the registration (e.g. GB, IE)
location_id	Booking location ID (returned by the Initialise Booking endpoint)

3. List Services

Returns the services available for the current booking session based on the selected vehicle and location.

Request

```
1 GET /api/external-  
   booking/{instance}/{session_id}/list-services
```

Response

```
1  {  
2    "services": [  
3      {  
4        "service_price_id": 11641,  
5        "name": "Brakes",  
6        "description": null,  
7        "price": "60.00",  
8        "from_price": false,  
9        "estimate": false,  
10       "hide_service_prices": false,  
11       "currency_code": "GBP",  
12       "customer_comment": false  
13     },  
14     {  
15       "service_price_id": 11646,  
16       "name": "MOT Class 4 ( car )",  
17       "description": "MOT OB V 1",  
18       "price": ".30",  
19       "from_price": false,  
20       "estimate": false,  
21       "hide_service_prices": false,  
22       "currency_code": "GBP",  
23       "customer_comment": false  
24     }  
25   ]  
26 }
```

Each service object includes identifiers required when selecting services in the next step.

4. Set Services

Adds the selected services to the booking.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-services
```

Body

```
1  {  
2    "servicePriceIDs": [87, 88, 90]  
3  }
```

Field	Description
servicePriceIDs	Array of service price identifiers (returned by List Services)

5. List Additional Services

Returns optional add-on services that can be included with the booking.

Request

```
1 GET /api/external-  
  booking/{instance}/{session_id}/list-additional-  
  services
```

Response

```
1  {  
2    "status": "success",  
3    "additional_services": [  
4      {  
5        "id": 11646,  
6        "name": "MOT Class 4 ( car )",  
7        "description": "MOT OB V 1",  
8        "price": ".30",  
9        "from_price": false,  
10       "estimate": false,  
11       "hide_service_prices": false,  
12       "currency_code": "GBP",  
13       "selected": false  
14     },  
15     {  
16       "id": 11649,  
17       "name": "Wheel allihnment ≥1",  
18       "description": null,  
19       "price": "33.00",  
20       "from_price": false,  
21       "estimate": false,  
22       "hide_service_prices": false,  
23       "currency_code": "GBP",  
24       "selected": false  
25     }  
26   ]
```

27 }

6. Add Additional Service

Adds an optional add-on service to the booking.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-additional-  
    services
```

Body

```
1  {  
2    "addServicePriceID": 93  
3  }
```

7. Remove Service

Removes a previously added service from the booking. Uses the same endpoint as Add Additional Service.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-additional-  
    services
```

Body

```
1  {  
2    "removeServicePriceID": 93  
3  }
```

8. List Available Timeslots

Returns the available appointment times for the configured booking.

Request

```
1 GET /api/external-  
   booking/{instance}/{session_id}/list-timeslots
```

Response

```
1  {  
2    "status": "success",  
3    "timeslots": {  
4      "2026-03-30": [  
5        "13:30"  
6      ],  
7      "2026-03-31": [  
8        "08:30",  
9        "13:30"  
10     ],  
11     "2026-04-01": [  
12       "08:30",  
13       "13:30"  
14     ],  
15     "2026-04-02": [  
16       "08:30",  
17       "13:30"  
18     ]  
19   }  
20 }
```

9. Set Timeslot

Reserves a specific timeslot for the booking.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-timeslot
```

Body

```
1  {  
2    "bookingDate": "2025-09-02",  
3    "bookingTime": "08:30"  
4  }
```

Field	Description
bookingDate	Appointment date in YYYY-MM-DD format
bookingTime	Appointment time in HH:mm format

10. Set Contact Information

The final step in the booking process. Submits the customer's contact details and completes the booking.

Request

```
1  POST /api/external-  
    booking/{instance}/{session_id}/set-contact-info
```

Body

```
1  {  
2    "contact_name": "John",  
3    "contact_last_name": "Doe",  
4    "contact_email": "john@example.com",  
5    "contact_number": "0123456789",  
6    "contact_address": "Some address",  
7    "contact_city": "Nottingham",  
8    "contact_postcode": "NG1 1AA"  
9  }
```

Error Handling

When a request fails, the API returns an error response in the following format:

```
1  {  
2    "status": "error",  
3    "message": "Booking not found"  
4  }
```

Common causes of errors include:

- Invalid or expired `session_id`
- Invalid service identifiers
- Missing required parameters in the request body
- Calling endpoints out of sequence

✓ **Tip:** Always check the `status` field in each response. If the value is `"error"`, read the `message` field for details on what went wrong.

See Also

1.  [Getting Started with Garage Hive APIs](#)
2.  [Garage Hive API Endpoints](#)
3.  [Microsoft Business Central Standard API Endpoints](#)
4.  [Understanding Garage Link Modules](#)

 English (UK, IE, IM and IZ). To find documentation in other regions where Garage Hive operates, click [here](#).