



<http://algs4.cs.princeton.edu>

4.2 DIRECTED GRAPHS

- ▶ *introduction*
- ▶ *digraph API*
- ▶ *digraph search*
- ▶ *topological sort*
- ▶ *strong components*

Digraph API

```
public class Digraph
```

```
    Digraph(int V)
```

create an empty digraph with V vertices

```
    Digraph(In in)
```

create a digraph from input stream

```
    void addEdge(int v, int w)
```

add a directed edge $v \rightarrow w$

```
    Iterable<Integer> adj(int v)
```

vertices pointing from v

```
    int V()
```

number of vertices

```
    int E()
```

number of edges

```
    Digraph reverse()
```

reverse of this digraph

```
    String toString()
```

string representation

```
In in = new In(args[0]);  
Digraph G = new Digraph(in);
```

← read digraph from
input stream


```
for (int v = 0; v < G.V(); v++)  
    for (int w : G.adj(v))  
        StdOut.println(v + "->" + w);
```

← print out each
edge (once)

Digraph API

tinyDG.txt

V → 13
22 ← E
4 2
2 3
3 2
6 0
0 1
2 0
11 12
12 9
9 10
9 11
7 9
10 12
11 4
4 3
3 5
6 8
8 6
⋮



```
% java Digraph tinyDG.txt
```

```
0->5
0->1
2->0
2->3
3->5
3->2
4->3
4->2
5->4
:
11->4
11->12
12-9
```

```
In in = new In(args[0]);
Digraph G = new Digraph(in);
```



```
for (int v = 0; v < G.V(); v++)
    for (int w : G.adj(v))
        StdOut.println(v + "->" + w);
```

← read digraph from
input stream

← print out each
edge (once)

Adjacency-lists digraph representation

Maintain vertex-indexed array of lists.



Adjacency-lists graph representation (review): Java implementation

```
public class Graph
{
```

```
    private final int V;
    private final Bag<Integer>[] adj;
```

← adjacency lists

```
    public Graph(int V)
```

```
    {
        this.V = V;
        adj = (Bag<Integer>[]) new Bag[V];
        for (int v = 0; v < V; v++)
            adj[v] = new Bag<Integer>();
    }
```

← create empty graph
with V vertices

```
    public void addEdge(int v, int w)
```

```
    {
        adj[v].add(w);
        adj[w].add(v);
    }
```

← add edge v-w

```
    public Iterable<Integer> adj(int v)
```

```
    { return adj[v]; }
```

← iterator for vertices
adjacent to v

```
}
```

Adjacency-lists digraph representation: Java implementation

```
public class Digraph  
{
```

```
    private final int V;  
    private final Bag<Integer>[] adj;
```

← adjacency lists

```
    public Digraph(int V)
```

```
    {  
        this.V = V;  
        adj = (Bag<Integer>[]) new Bag[V];  
        for (int v = 0; v < V; v++)  
            adj[v] = new Bag<Integer>();  
    }
```

← create empty digraph
with V vertices

```
    public void addEdge(int v, int w)
```

```
    {  
        adj[v].add(w);  
    }
```

← add edge $v \rightarrow w$

```
    public Iterable<Integer> adj(int v)
```

```
    { return adj[v]; }
```

← iterator for vertices
pointing from v

```
}
```

Digraph representations

In practice. Use adjacency-lists representation.

- Algorithms based on iterating over vertices pointing from v .
- Real-world digraphs tend to be sparse.

↖ huge number of vertices,
small average vertex degree

representation	space	insert edge from v to w	edge from v to w ?	iterate over vertices pointing from v ?
list of edges	E	1	E	E
adjacency matrix	V^2	1 [†]	1	V
adjacency lists	$E + V$	1	$\text{outdegree}(v)$	$\text{outdegree}(v)$

[†] disallows parallel edges



<http://algs4.cs.princeton.edu>

4.2 DIRECTED GRAPHS

- ▶ *introduction*
- ▶ *digraph API*
- ▶ *digraph search*
- ▶ *topological sort*
- ▶ *strong components*




<http://algs4.cs.princeton.edu>

4.2 DIRECTED GRAPHS

- ▶ *introduction*
- ▶ *digraph API*
- ▶ *digraph search*
- ▶ *topological sort*
- ▶ *strong components*

Reachability

Problem. Find all vertices reachable from s along a directed path.



Depth-first search in digraphs

Same method as for undirected graphs.

- Every undirected graph is a digraph (with edges in both directions).
- DFS is a **digraph** algorithm.

DFS (to visit a vertex v)


Mark v as visited.

Recursively visit all unmarked
vertices w pointing from v .

Depth-first search demo

To visit a vertex v :

- Mark vertex v as visited.
- Recursively visit all unmarked vertices pointing from v .




a directed graph

4→2
2→3
3→2
6→0
0→1
2→0
11→12
12→9
9→10
9→11
8→9
10→12
11→4
4→3
3→5
6→8
8→6
5→4
0→5
6→4
6→9
7→6

Depth-first search demo

To visit a vertex v :

- Mark vertex v as visited.
- Recursively visit all unmarked vertices pointing from v .



reachable
from vertex 0

v	marked[]	edgeTo[]
0	T	—
1	T	0
2	T	3
3	T	4
4	T	5
5	T	0
6	F	—
7	F	—
8	F	—
9	F	—
10	F	—
11	F	—
12	F	—

reachable from 0

Depth-first search (in undirected graphs)

Recall code for **undirected** graphs.

```
public class DepthFirstSearch  
{
```

```
    private boolean[] marked;
```

← true if path to s

```
    public DepthFirstSearch(Graph G, int s)  
    {  
        marked = new boolean[G.V()];  
        dfs(G, s);  
    }
```

← constructor marks
vertices connected to s

```
    private void dfs(Graph G, int v)  
    {  
        marked[v] = true;  
        for (int w : G.adj(v))  
            if (!marked[w]) dfs(G, w);  
    }
```

← recursive DFS does the work

```
    public boolean visited(int v)  
    { return marked[v]; }
```

← client can ask whether any
vertex is connected to s

```
}
```

Depth-first search (in directed graphs)

Code for **directed** graphs identical to undirected one.
[substitute Digraph for Graph]

```
public class DirectedDFS
```

```
{
```

```
    private boolean[] marked;
```

← true if path from s

```
    public DirectedDFS(Digraph G, int s)
```

```
    {
```

```
        marked = new boolean[G.V()];
```

← constructor marks
vertices reachable from s

```
        dfs(G, s);
```

```
    }
```

```
    private void dfs(Digraph G, int v)
```

← recursive DFS does the work

```
    {
```

```
        marked[v] = true;
```

```
        for (int w : G.adj(v))
```

```
            if (!marked[w]) dfs(G, w);
```

```
    }
```

```
    public boolean visited(int v)
```

← client can ask whether any
vertex is reachable from s

```
    { return marked[v]; }
```

```
}
```

Reachability application: program control-flow analysis

Every program is a digraph.


- Vertex = basic block of instructions (straight-line program).
- Edge = jump.

Dead-code elimination.

Find (and remove) unreachable code.

Infinite-loop detection.

Determine whether exit is unreachable.




Reachability application: mark-sweep garbage collector

Every data structure is a digraph.

- Vertex = object.
- Edge = reference.

Roots. Objects known to be directly accessible by program (e.g., stack).

Reachable objects. Objects indirectly accessible by program (starting at a root and following a chain of pointers).




Reachability application: mark-sweep garbage collector

Mark-sweep algorithm. [McCarthy, 1960]

- Mark: mark all reachable objects.
- Sweep: if object is unmarked, it is garbage (so add to free list).

Memory cost. Uses 1 extra mark bit per object (plus DFS stack).



Depth-first search in digraphs summary

DFS enables direct solution of simple digraph problems.

- ✓ • Reachability.
- Path finding.
- Topological sort.
- Directed cycle detection.

Basis for solving difficult digraph problems.

- 2-satisfiability.
- Directed Euler path.
- Strongly-connected components.

SIAM J. COMPUT.
Vol. 1, No. 2, June 1972

DEPTH-FIRST SEARCH AND LINEAR GRAPH ALGORITHMS*

ROBERT TARJAN†

Abstract. The value of depth-first search or “backtracking” as a technique for solving problems is illustrated by two examples. An improved version of an algorithm for finding the strongly connected components of a directed graph and an algorithm for finding the biconnected components of an undirect graph are presented. The space and time requirements of both algorithms are bounded by $k_1V + k_2E + k_3$ for some constants k_1, k_2 , and k_3 , where V is the number of vertices and E is the number of edges of the graph being examined.

Breadth-first search in digraphs

Same method as for undirected graphs.

- Every undirected graph is a digraph (with edges in both directions).
- BFS is a **digraph** algorithm.

BFS (from source vertex s)

Put s onto a FIFO queue, and mark s as visited.

Repeat until the queue is empty:


- remove the least recently added vertex v
 - for each unmarked vertex pointing from v :
add to queue and mark as visited.
-

Proposition. BFS computes shortest paths (fewest number of edges) from s to all other vertices in a digraph in time proportional to $E + V$.

Directed breadth-first search demo

Repeat until queue is empty:

- Remove vertex v from queue.
- Add to queue all unmarked vertices pointing from v and mark them.



tinyDG2.txt

V → 6
8 ← E


5 0
2 4
3 2
1 2
0 1
4 3
3 5
0 2

graph G

Directed breadth-first search demo

Repeat until queue is empty:

- Remove vertex v from queue.
- Add to queue all unmarked vertices pointing from v and mark them.



v	edgeTo[]	distTo[]
0	–	0
1	0	1
2	0	1
3	4	3
4	2	2
5	3	4


done

Multiple-source shortest paths

Multiple-source shortest paths. Given a digraph and a **set** of source vertices, find shortest path from any vertex in the set to each other vertex.

Ex. $S = \{ 1, 7, 10 \}$.

- Shortest path to 4 is $7 \rightarrow 6 \rightarrow 4$.
- Shortest path to 5 is $7 \rightarrow 6 \rightarrow 0 \rightarrow 5$.
- Shortest path to 12 is $10 \rightarrow 12$.
- ...



Q. How to implement multi-source shortest paths algorithm?


A. Use BFS, but initialize by enqueueing all source vertices.

Breadth-first search in digraphs application: web crawler

Goal. Crawl web, starting from some root web page, say `www.princeton.edu`.

Solution. [BFS with implicit digraph]

- Choose root web page as source s .
- Maintain a Queue of websites to explore.
- Maintain a SET of discovered websites.
- Dequeue the next website and enqueue websites to which it links (provided you haven't done so before).



Q. Why not use DFS?

Bare-bones web crawler: Java implementation

```
Queue<String> queue = new Queue<String>();  
SET<String> marked = new SET<String>();
```

← queue of websites to crawl
← set of marked websites

```
String root = "http://www.princeton.edu";  
queue.enqueue(root);  
marked.add(root);
```

← start crawling from root website

```
while (!queue.isEmpty())  
{
```

```
    String v = queue.dequeue();  
    StdOut.println(v);  
    In in = new In(v);  
    String input = in.readAll();
```

← read in raw html from next
website in queue

```
    String regexp = "http://(\\w+\\.)*\\w+";  
    Pattern pattern = Pattern.compile(regexp);  
    Matcher matcher = pattern.matcher(input);  
    while (matcher.find())  
    {
```

← use regular expression to find all URLs
in website of form http://xxx.yyy.zzz
[crude pattern misses relative URLs]

```
        String w = matcher.group();  
        if (!marked.contains(w))  
        {  
            marked.add(w);  
            queue.enqueue(w);  
        }  
    }
```

← if unmarked, mark it and put
on the queue

```
    }  
}
```



<http://algs4.cs.princeton.edu>

4.2 DIRECTED GRAPHS

- ▶ *introduction*
- ▶ *digraph API*
- ▶ *digraph search*
- ▶ *topological sort*
- ▶ *strong components*