

# Delivery Problem

---

Alexander S. Kulikov

Steklov Mathematical Institute at St. Petersburg, Russian Academy of Sciences  
and  
University of California, San Diego

# Outline

**Problem Statement**

Brute Force Search

Nearest Neighbor

Branch and Bound


Dynamic Programming

Approximation Algorithm

Local Search


# Traveling Salesman Problem

Given a complete weighted graph, find a cycle (or a path) of minimum total weight (length) visiting each node exactly once



# Traveling Salesman Problem


Given a complete weighted graph, find a cycle (or a path) of minimum total weight (length) visiting each node exactly once



length: 15

# Traveling Salesman Problem


Given a complete weighted graph, find a cycle (or a path) of minimum total weight (length) visiting each node exactly once



length: 11

# Traveling Salesman Problem

Given a complete weighted graph, find a cycle (or a path) of minimum total weight (length) visiting each node exactly once



length: 9

# Status

- Classical optimization problem with countless number of real life applications (we'll see soon)

# Status

- Classical optimization problem with countless number of real life applications (we'll see soon)
- No polynomial time algorithms known



# Status

- Classical optimization problem with countless number of real life applications (we'll see soon)
- No polynomial time algorithms known
- Goal of this project: develop efficient programs for solving TSP problem

# Delivering Goods



Need to visit several points. What is the optimal order of visiting them?

# Traveling




# Traveling



# Traveling



# Traveling





# Drilling a Circuit Board



<https://developers.google.com/optimization/routing/tsp/tsp>



# Drilling a Circuit Board



<https://developers.google.com/optimization/routing/tsp/tsp>



# Drilling a Circuit Board



<https://developers.google.com/optimization/routing/tsp/tsp>

# Euclidean TSP

- **Euclidean TSP:** instead of a complete graph, the input consists of  $n$  points  $p_1 = (x_1, y_1), \dots, p_n = (x_n, y_n)$  on the plane

# Euclidean TSP

- **Euclidean TSP:** instead of a complete graph, the input consists of  $n$  points  $p_1 = (x_1, y_1), \dots, p_n = (x_n, y_n)$  on the plane
- Weights are given implicitly:

$$d(p_i, p_j) = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2}$$

# Euclidean TSP

- **Euclidean TSP:** instead of a complete graph, the input consists of  $n$  points  $p_1 = (x_1, y_1), \dots, p_n = (x_n, y_n)$  on the plane
- Weights are given implicitly:

$$d(p_i, p_j) = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2}$$

- Weights are symmetric:  $d(p_i, p_j) = d(p_j, p_i)$

# Euclidean TSP

- **Euclidean TSP:** instead of a complete graph, the input consists of  $n$  points  $p_1 = (x_1, y_1), \dots, p_n = (x_n, y_n)$  on the plane
- Weights are given implicitly:

$$d(p_i, p_j) = \sqrt{(x_i - x_j)^2 + (y_i - y_j)^2}$$

- Weights are symmetric:  $d(p_i, p_j) = d(p_j, p_i)$
- Weights satisfy the triangle inequality:  
$$d(p_i, p_j) \leq d(p_i, p_k) + d(p_k, p_j)$$

# Processing Components

There are  $n$  mechanical components to be processed on a complex machine. After processing the  $i$ -th component, it takes  $t_{ij}$  units of time to reconfigure the machine so that it is able to process the  $j$ -th component. What is the minimum processing cost?



# Shortest Common Superstring

- The shortest common superstring problem (SCS): given a set  $\{s_1, \dots, s_n\}$  of  $n$  strings find a shortest string containing each  $s_i$  as a substring

# Shortest Common Superstring

- The shortest common superstring problem (SCS): given a set  $\{s_1, \dots, s_n\}$  of  $n$  strings find a shortest string containing each  $s_i$  as a substring
- Practical applications: data storage, data compression, genome assembly



# Shortest Common Superstring

- The shortest common superstring problem (SCS): given a set  $\{s_1, \dots, s_n\}$  of  $n$  strings find a shortest string containing each  $s_i$  as a substring
- Practical applications: data storage, data compression, genome assembly
- At the first look, it is not at all clear how this problem is related to TSP

## SCS: Example

- Consider the following instance:  
ABE, DFA, DAB, CBD, ECA, ACB

## SCS: Example

- Consider the following instance:  
ABE, DFA, DAB, CBD, ECA, ACB
- To get a superstring, just concatenate them:

ABEDFADABCBDECAACB

## SCS: Example

- Consider the following instance:

ABE, DFA, DAB, CBD, ECA, ACB

- To get a superstring, just concatenate them:

ABEDFADABCBDECAACB

- But the strings ECA and ACB have a non-empty **overlap**. One can get a shorter superstring by overlapping them:

ECACB

# SCS: Permutation Problem

ABE

DFA


DAB

ECA


CBD

ACB

# SCS: Permutation Problem



# SCS: Permutation Problem



# Overlap Graph: SCS $\rightarrow$ MAX-ATSP

ABE DFA DAB CBD ECA ACB



# Overlap Graph: SCS $\rightarrow$ MAX-ATSP

ABE DFA DAB CBD ECA ACB

ABE

DAB

CBD

DFA


ECA

ACB




# Overlap Graph: $SCS \rightarrow \text{MAX-ATSP}$

ABE DFA DAB CBD ECA ACB




# Overlap Graph: SCS $\rightarrow$ MAX-ATSP

ABE DFA DAB CBD ECA ACB




# Overlap Graph: SCS $\rightarrow$ MAX-ATSP

ABE DFA DAB CBD ECA ACB



# Overlap Graph: SCS $\rightarrow$ MAX-ATSP

ABE DFA DAB CBD ECA ACB



**DABECACBDFA**

# Outline

Problem Statement

**Brute Force Search**

Nearest Neighbor

Branch and Bound

Dynamic Programming

Approximation Algorithm

Local Search

# Enumerating all Permutations

- Finding the best permutation is easy:  
simply iterate through all of them and  
select the best one



# Enumerating all Permutations

- Finding the best permutation is easy: simply iterate through all of them and select the best one
- But the number of permutations of  $n$  objects is  $n!$

## $n!$ : Growth Rate

---

$n$	$n!$
5	120
8	40320
10	3628800
13	6227020800
20	2432902008176640000
30	2652528598121910586363084800000000

---

# Random Permutation

- OK, in most cases, we cannot afford going through all permutations

# Random Permutation

- OK, in most cases, we cannot afford going through all permutations
- What if we just generate a random permutation?

# Random Permutation

- OK, in most cases, we cannot afford going through all permutations
- What if we just generate a random permutation?
- The length of a random permutation may be much worse than the minimum length, even for Euclidean TSP


# Expected Length

## Lemma


For a complete directed graph  $G$ , the expected length of a random permutation is

$$\frac{1}{n-1} \cdot \sum_{u,v \in V(G)} w(u, v)$$

# Bad Case




# Bad Case





# Bad Case



# Outline

Problem Statement

Brute Force Search

**Nearest Neighbor**

Branch and Bound

Dynamic Programming

Approximation Algorithm

Local Search

# Speculating

- Sampling a random permutation is perhaps too naive

# Speculating

- Sampling a random permutation is perhaps too naive
- What about going to the nearest yet unvisited node at every iteration?

# Speculating

- Sampling a random permutation is perhaps too naive
- What about going to the nearest yet unvisited node at every iteration?
- Efficient, works reasonably well in practice

# Speculating

- Sampling a random permutation is perhaps too naive
- What about going to the nearest yet unvisited node at every iteration?
- Efficient, works reasonably well in practice
- For general graphs, may produce a cycle that is much worse than an optimal one

# Speculating

- Sampling a random permutation is perhaps too naive
- What about going to the nearest yet unvisited node at every iteration?
- Efficient, works reasonably well in practice
- For general graphs, may produce a cycle that is much worse than an optimal one
- For Euclidean instances, the resulting cycle may be about  $\log n$  times worse than an optimal one

## Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?




## Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2


## Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Nearest Neighbors: Bad Case

- How to fool the nearest neighbors heuristic?
- Assume that the weights of almost all the edges in the graph are equal to 2
- And we start to construct a cycle:




# Suboptimal Solution for Euclidean TSP






# Suboptimal Solution for Euclidean TSP




$\text{OPT} \approx 26.42$

# Suboptimal Solution for Euclidean TSP




$\text{OPT} \approx 26.42$

# Suboptimal Solution for Euclidean TSP




$\text{OPT} \approx 26.42$

# Suboptimal Solution for Euclidean TSP




$\text{OPT} \approx 26.42$

# Suboptimal Solution for Euclidean TSP



$\text{OPT} \approx 26.42$

# Suboptimal Solution for Euclidean TSP



OPT  $\approx$  26.42

NN  $\approx$  28.33

# Outline

Problem Statement

Brute Force Search

Nearest Neighbor

**Branch and Bound**

Dynamic Programming

Approximation Algorithm

Local Search

# Main Ideas

- Start with some node




# Main Ideas

- Start with some node
- At every iteration try to extend (recursively) the current path by every yet unvisited node



# Main Ideas

- Start with some node
- At every iteration try to extend (recursively) the current path by every yet unvisited node
- But don't continue extending the path, if it is already clear that it cannot be extended to an optimal cycle


## Example: Brute Force Search




# Example: Brute Force Search




## Example: Pruned Search




## Example: Pruned Search



# Example: Pruned Search




# Example: Pruned Search






# Example: Pruned Search




best so far: 19

# Example: Pruned Search




best so far: 19

# Example: Pruned Search




# Example: Pruned Search





best so far: 7

# Example: Pruned Search





best so far: 7

# Example: Pruned Search





best so far: 7

# Example: Pruned Search



best so far: 7



# Example: Pruned Search



best so far: 7





# Example: Pruned Search





best so far: 7

# Example: Pruned Search



best so far: 7

# Example: Pruned Search



best so far: 7

# Lower Bound

- We used the simplest possible lower bound: any extension of a path has length at least the length of the path

# Lower Bound

- We used the simplest possible lower bound: any extension of a path has length at least the length of the path
- Modern TSP-solvers use smarter lower bounds to solve instances with thousands of vertices

## Example: Lower Bounds (Still Simple)

The length of an optimal TSP cycle is at least

- $\frac{1}{2} \sum_{v \in V} (\text{two min length edges adj to } v)$

## Example: Lower Bounds (Still Simple)

The length of an optimal TSP cycle is at least

- $\frac{1}{2} \sum_{v \in V} (\text{two min length edges adj to } v)$
- the length of a minimum spanning tree (by taking out any edge of a TSP cycle, one gets a spanning tree)

# Branch and Bound: Summary

- Main two heuristics of branch and bound:



# Branch and Bound: Summary

- Main two heuristics of branch and bound:
  - Branch: order of yet unvisited nodes (say, select closer neighbors first)

# Branch and Bound: Summary

- Main two heuristics of branch and bound:
  - Branch: order of yet unvisited nodes (say, select closer neighbors first)
  - Bound: lower bounding the length of a path

# Branch and Bound: Summary

- Main two heuristics of branch and bound:
  - Branch: order of yet unvisited nodes (say, select closer neighbors first)
  - Bound: lower bounding the length of a path
- Finds an optimal solution

# Branch and Bound: Summary

- Main two heuristics of branch and bound:
  - Branch: order of yet unvisited nodes (say, select closer neighbors first)
  - Bound: lower bounding the length of a path
- Finds an optimal solution
- The running time depends on the heuristics used as well as on the instance itself

# Branch and Bound: Summary

- Main two heuristics of branch and bound:
  - Branch: order of yet unvisited nodes (say, select closer neighbors first)
  - Bound: lower bounding the length of a path
- Finds an optimal solution
- The running time depends on the heuristics used as well as on the instance itself
- Used by state-of-the-art TSP-solvers that can handle instances with thousands of nodes!

# Outline

Problem Statement

Brute Force Search

Nearest Neighbor

Branch and Bound

**Dynamic Programming**

Approximation Algorithm

Local Search

# Dynamic Programming

- Dynamic programming is one of the most powerful algorithmic techniques

# Dynamic Programming

- Dynamic programming is one of the most powerful algorithmic techniques
- Rough idea: express a solution for a problem through solutions for smaller subproblems



# Dynamic Programming

- Dynamic programming is one of the most powerful algorithmic techniques
- Rough idea: express a solution for a problem through solutions for smaller subproblems
- Solve subproblems one by one. Store solutions to subproblems in a table to avoid recomputing the same thing again

# Subproblems

- For a subset of nodes  $S \subseteq \{0, \dots, n-1\}$  containing the node 0 and a node  $i \in S$ , let  $C(i, S)$  be the length of the shortest path that starts at 0, ends at  $i$ , and visits all nodes from  $S$  exactly once

# Subproblems

- For a subset of nodes  $S \subseteq \{0, \dots, n-1\}$  containing the node 0 and a node  $i \in S$ , let  $C(i, S)$  be the length of the shortest path that starts at 0, ends at  $i$ , and visits all nodes from  $S$  exactly once
- $C(0, \{0\}) = 0$  and  $C(0, S) = +\infty$  when  $|S| > 1$

## Recurrence Relation

- Consider the second-to-last node  $j$  on the required shortest path from 0 to  $i$  visiting all nodes from  $S$

# Recurrence Relation

- Consider the second-to-last node  $j$  on the required shortest path from 0 to  $i$  visiting all nodes from  $S$
- The subpath from 0 to  $j$  is the shortest one visiting all vertices from  $S - \{i\}$  exactly once

# Recurrence Relation

- Consider the second-to-last node  $j$  on the required shortest path from 0 to  $i$  visiting all nodes from  $S$
- The subpath from 0 to  $j$  is the shortest one visiting all vertices from  $S - \{i\}$  exactly once
- Hence  $C(i, S) = \min\{C(j, S - \{i\}) + w(j, i)\}$ , where the minimum is over all  $j \in S$  such that  $j \neq i$

# Implementation Remark

- How to iterate through all subsets of  $\{0, \dots, n - 1\}$ ?

# Implementation Remark

- How to iterate through all subsets of  $\{0, \dots, n-1\}$ ?
- There is a natural one-to-one correspondence between integers in the range from 0 to  $2^n - 1$  and subsets of  $\{0, \dots, n-1\}$ :

$$k \leftrightarrow \{i: i\text{-th bit of } k \text{ is } 1\}$$



# Example

$k$	$\text{bin}(k)$	$\{i: i\text{-th bit of } k \text{ is } 1\}$
0	000	$\emptyset$
1	001	$\{0\}$
2	010	$\{1\}$
3	011	$\{0,1\}$
4	100	$\{2\}$
5	101	$\{0,2\}$
6	110	$\{1,2\}$
7	111	$\{0,1,2\}$

# Flipping a Particular Bit

- If  $k$  corresponds to  $S$ , how to find out the integer corresponding to  $S - \{j\}$  (for  $j \in S$ )?

# Flipping a Particular Bit

- If  $k$  corresponds to  $S$ , how to find out the integer corresponding to  $S - \{j\}$  (for  $j \in S$ )?
- For this, we need to flip the  $j$ -th bit of  $k$  (from 1 to 0)

# Flipping a Particular Bit

- If  $k$  corresponds to  $S$ , how to find out the integer corresponding to  $S - \{j\}$  (for  $j \in S$ )?
- For this, we need to flip the  $j$ -th bit of  $k$  (from 1 to 0)
- For this, in turn, we compute a bitwise XOR of  $k$  and  $2^j$  (that has 1 only in  $j$ -th position)

# Flipping a Particular Bit

- If  $k$  corresponds to  $S$ , how to find out the integer corresponding to  $S - \{j\}$  (for  $j \in S$ )?
- For this, we need to flip the  $j$ -th bit of  $k$  (from 1 to 0)
- For this, in turn, we compute a bitwise XOR of  $k$  and  $2^j$  (that has 1 only in  $j$ -th position)
- In C/C++, Java, Python:  
 $k \wedge (1 \ll j)$

# Code

```
def dp(G):
    n = G.number_of_nodes()
    T = [[float("inf")] * (1 << n) for _ in range(n)]
    T[0][1] = 0
    for s in range(1 << n):
        if sum(((s >> j) & 1) for j in range(n)) <= 1 or not (s & 1):
            continue

        for i in range(1, n):
            if not ((s >> i) & 1):
                continue
            for j in range(n):
                if j == i or not ((s >> j) & 1):
                    continue

                T[i][s] = min(T[i][s],
                              T[j][s ^ (1 << i)] + G[i][j]['weight'])

    return min(T[i][(1 << n) - 1] + G[0][i]['weight']
               for i in range(1, n))
```

# Dynamic Programming: Summary

- The running time is about  $n^2 2^n$

# Dynamic Programming: Summary

- The running time is about  $n^2 2^n$
- Better than  $n!$ , but still too slow (already for  $n = 20$ )



# Outline

Problem Statement

Brute Force Search

Nearest Neighbor

Branch and Bound

Dynamic Programming

**Approximation Algorithm**

Local Search

# Approximation

- Let's focus on the metric version of TSP:  
 $w(u, v) = w(v, u)$  and  
 $w(u, v) \leq w(u, z) + w(z, v)$  (in particular, Euclidean TSP is metric)
- We will design a 2-approximation algorithm: it quickly finds a cycle that is at most twice longer than an optimal one

# Minimum Spanning Trees

## Lemma

Let  $G$  be an undirected graph with non-negative edge weights. Then  $\text{MST}(G) \leq \text{TSP}(G)$ .

# Minimum Spanning Trees

## Lemma

Let  $G$  be an undirected graph with non-negative edge weights. Then  $\text{MST}(G) \leq \text{TSP}(G)$ .

## Proof

By removing any edge from an optimum TSP cycle one gets a spanning tree of  $G$ . □

# Algorithm

- $T \leftarrow$  minimum spanning tree of  $G$

# Algorithm

- $T \leftarrow$  minimum spanning tree of  $G$
- $D \leftarrow T$  with each edge doubled

# Algorithm


- $T \leftarrow$  minimum spanning tree of  $G$
- $D \leftarrow T$  with each edge doubled
- find an Eulerian cycle  $C$  in  $D$

# Algorithm


- $T \leftarrow$  minimum spanning tree of  $G$
- $D \leftarrow T$  with each edge doubled
- find an Eulerian cycle  $C$  in  $D$
- return a cycle that visits the nodes in the order of their first appearance in  $C$




# Example




# Example




# Example




# Example



# Example



# Example



# Provable Guarantee

## **Lemma**

The algorithm is 2-approximate.

# Provable Guarantee

## Lemma

The algorithm is 2-approximate.

## Proof

- The total length of the MST  $T$  is at most  $2 \cdot \text{OPT}$ .



# Provable Guarantee

## Lemma

The algorithm is 2-approximate.

## Proof

- The total length of the MST  $T$  is at most  $\text{OPT}$ .
- Bypasses can only decrease the total length.



# Final Remarks

- The currently best known approximation algorithm for metric TSP is Christofides' algorithm that achieves a factor of 1.5

# Final Remarks

- The currently best known approximation algorithm for metric TSP is Christofides' algorithm that achieves a factor of 1.5
- If  $P \neq NP$ , then there is no  $\alpha$ -approximation algorithm for the general version of TSP for any constant  $\alpha$

# Outline

Problem Statement

Brute Force Search

Nearest Neighbor

Branch and Bound

Dynamic Programming

Approximation Algorithm

**Local Search**

# Local Search

Local Search with parameter  $d$ :

- $s \leftarrow$  some initial solution

# Local Search

Local Search with parameter  $d$ :

- $s \leftarrow$  some initial solution
- while it is possible to change  $d$  edges in  $s$  to get a better cycle  $s'$ :

# Local Search

Local Search with parameter  $d$ :

- $s \leftarrow$  some initial solution
- while it is possible to change  $d$  edges in  $s$  to get a better cycle  $s'$ :
  - $s \leftarrow s'$

# Local Search

Local Search with parameter  $d$ :

- $s \leftarrow$  some initial solution
- while it is possible to change  $d$  edges in  $s$  to get a better cycle  $s'$ :
  - $s \leftarrow s'$
- return  $s$



# Properties


- Computes a local optimum instead of a global optimum

# Properties

- Computes a local optimum instead of a global optimum
- The larger is  $d$ , the better is the resulting solution and the higher is the running time


# Example

Changing two edges in a suboptimal solution:




# Example

Changing two edges in a suboptimal solution:




# Example

Changing two edges in a suboptimal solution:




# Example

Changing two edges in a suboptimal solution:




# Example

A suboptimal solution that cannot be improved by changing two edges:



## Example

A suboptimal solution that cannot be improved by changing two edges:



Need to allow changing three edges to improve this solution



# Performance

- Trade-off between quality and running time of a single iteration

# Performance

- Trade-off between quality and running time of a single iteration
- Still, the number of iterations may be exponential and the quality of the found cycle may be poor

# Performance

- Trade-off between quality and running time of a single iteration
- Still, the number of iterations may be exponential and the quality of the found cycle may be poor
- But works well in practice

# Summary

- Exact algorithms: brute force, branch and bound, dynamic programming

# Summary

- Exact algorithms: brute force, branch and bound, dynamic programming
- Approximation algorithms: nearest neighbors, MST-based, local search