FRONT VIEW (record side)




SECTION A-A (x=0)

**NOTES:**

1. Centre: 1/4-20 flat head (82 deg) countersunk FLUSH on the back face. Screw goes into a 3/8 in OD x 1 in 1/4-20 F-F aluminum standoff on the FRONT face (the record rests on it).
2. 3x #8 flat-head countersinks on the FRONT face (hidden by the record) fasten the hub from the front.
3. 16 x 13 through cut-out at y=+15 clears the DC jack body in the hub.
4. LED for this variant: 6 x 12 mm top-emitting 12 V COB neon flex laid as a ring on the BACK face, centreline R 61, emitting toward the wall.
5. Laser or waterjet; deburr both faces; no heat-tint on the visible edge. Flatness 0.5 over the face after coating.
6. Countersinks may be done by the cutting vendor (SendCutSend / OSH Cut countersink service) or in-house.

## RECORD SCONCE | BACKPLATE 6.0 in, FLAT ALUMINUM 5 mm (floating record)

PART NO: RS-BP-7-AL5  REV: A  DATE: 2026-11-09

MATERIAL: 5052-H32 aluminum sheet, 5.0 mm [0.197 in]

FINISH: Powder coat matte black (RAL 9005 texture or equal), all over, mask threads not required (no threads)

UNITS: mm [in]  THIRD-ANGLE PROJECTION  SCALE: as shown

GENERAL TOLERANCES: x.x +/-0.3  x.xx +/-0.1  angles +/-0.5 deg  unless noted