



Weekly AI Security Report

2026-09-09 to 2026-09-16

Environment: Demo_env1 (Cloud ID: ryq7a5aiov5z)

Overall Assessment

The most critical risk in this environment is the Windows 11 Home endpoint (agent 002), which carries a large number of unpatched critical-severity vulnerabilities across core OS components enabling remote code execution, compounded by active alerts indicating registry tampering, new service creation, and repeated firewall blocks from a single source – patterns consistent with either active exploitation or post-compromise activity.

Both endpoints exhibit significant security configuration compliance gaps against CIS benchmarks, and the Kali Linux system (agent 001) hosts offensive security tools and vulnerable Python packages that require careful access control. The presence of monitoring disruptions (agent stops/disconnections) and privilege assignment events further elevates the overall risk posture, warranting immediate patching, hardening, and investigation across the environment.

Alert Analysis

Wazuh continuously analyzes log data collected across the monitored infrastructure. Each log entry is evaluated against a robust set of predefined security rules, each tagged with a criticality level to indicate severity and potential impact.

This section presents two perspectives on alert data: analysis by MITRE technique and by alert level, along with a summary of recommended actions.

MITRE ATT&CK TTPs

MITRE ATT&CK is a globally-accessible knowledge base of adversary tactics and techniques based on real-world observations. Wazuh rules are often defined to detect actions that may be related to these attacks.

In this section, you will find an analysis of the top ten attacks that may affect your Wazuh installation, ranked by the activity generated on your endpoints over the reporting period.

ID	Tactic	Technique	Count	Description
T1112	Defense Evasion	Modify Registry	46	Registry modification activity has been detected on the Windows endpoint, including both integrity checksum changes to registry keys and values and outright deletion of registry value entries. This pattern may indicate an attempt to alter system configuration, disable security controls, or cover tracks of malicious activity.
T1565.001	Impact	Stored Data Manipulation	42	Stored data manipulation alerts relate to detected changes in registry key and value integrity checksums, suggesting that persistent data on the Windows system may have been altered. Such changes could reflect legitimate software updates or potentially unauthorized tampering with system configuration data.

ID	Tactic	Technique	Count	Description
T1070.004	Defense Evasion	File Deletion	5	Registry value entry deletions have been flagged, which may be indicative of an attempt to remove evidence of activity or disable system functionality by erasing specific registry entries associated with defense evasion techniques.
T1485	Impact	Data Destruction	5	Alerts associated with data destruction have been triggered by registry value entry deletions, which could indicate an attempt to destroy configuration data or disrupt system operations on the Windows endpoint.
T1543.003	Persistence	Windows Service	4	New Windows services have been created on the Windows endpoint, a technique commonly used by attackers to establish persistence or escalate privileges by registering malicious or unauthorized services that survive reboots.
T1562.001	Defense Evasion	Disable or Modify Tools	4	Wazuh agent stop and disconnection events have been recorded, which map to the technique of disabling or modifying security tools. These events may indicate deliberate attempts to blind the monitoring platform or could reflect legitimate maintenance activity.
T1078	Defense Evasion	Valid Accounts	2	Successful workstation logon events using valid accounts have been detected on the Windows endpoint, which may represent legitimate user activity or could indicate credential misuse if the logon context is unexpected.
T1484	Defense Evasion	Domain Policy Modification	1	A special privileges assignment to a new logon session has been detected, which is associated with domain policy modification and privilege escalation tactics and warrants review to confirm it was an authorized administrative action.

Highest Priority Rules

In this section, you will find an analysis of the ten most critical rules that affected your installation over the reporting period, ranked by the rule level. This information provides a snapshot of your overall activity across multiple endpoints.

ID	Level	Count	Description
4151	10	5	High-severity alerts indicate multiple firewall drop events originating from the same source IP, suggesting a possible port scan, brute-force attempt, or denial-of-service activity targeting the Windows endpoint that the firewall is actively blocking.
19005	9	4	The Windows 11 endpoint has received a CIS benchmark SCA summary score below 30%, indicating a critically poor security configuration posture against the CIS Microsoft Windows 11 Enterprise Benchmark v3.0.0 controls.
19014	9	1	A CIS benchmark check for enforcing password history of 24 or more passwords has transitioned from 'not applicable' to 'failed' on the Windows endpoint, indicating a newly detected password policy compliance gap.
19007	7	448	A large volume of CIS benchmark compliance alerts has been generated across both endpoints, covering Windows Update pause access controls and Linux inactive password lock policy, reflecting systemic configuration drift from security baselines.
19004	7	1	The Linux endpoint's SCA summary score for the CIS Distribution Independent Linux Benchmark v2.0.0 is below 50%, indicating that the system fails to meet the majority of the assessed security configuration requirements.

ID	Level	Count	Description
550	7	1	A file integrity checksum change has been detected on the Linux endpoint, indicating that a monitored file has been modified and should be reviewed to determine whether the change was authorized or potentially malicious.
750	5	27	Registry value integrity checksum changes have been repeatedly detected on the Windows endpoint, indicating ongoing modifications to registry values that may reflect software installation, updates, or unauthorized configuration changes.
594	5	14	Registry key integrity checksum changes have been detected on the Windows endpoint, suggesting that registry keys are being modified, which could be the result of software activity or deliberate tampering.
60646	5	12	Repeated license activation failures for slui.exe have been recorded on the Windows endpoint, which may indicate an unlicensed or improperly activated Windows installation requiring attention.
61102	5	8	Windows System error events have been logged on the Windows endpoint, indicating recurring low-level OS errors that may point to hardware issues, driver problems, or software instability requiring investigation.

Recommended Actions

Alert activity across both endpoints reflects a combination of active security events and systemic configuration compliance failures. The Windows endpoint shows signs of potential adversarial activity including firewall blocking of repeated connection attempts, registry manipulation consistent with defense evasion, and unauthorized service creation. Both endpoints exhibit significant CIS benchmark non-compliance. The Linux endpoint additionally recorded a file integrity change requiring verification.

- Investigate the source of repeated firewall drop events on the Windows endpoint (agent 002) to determine whether an active reconnaissance or attack is in progress, and consider blocking the offending source at the network perimeter. (High urgency)
- Review and remediate the CIS Windows 11 Enterprise Benchmark failures on agent 002, particularly the critically low SCA score below 30% and the failed password history enforcement check, by applying the recommended Group Policy settings. (High urgency)
- Audit all newly created Windows services on agent 002 to verify they are authorized, and remove any unrecognized services that may have been installed for persistence purposes. (High urgency)
- Investigate the registry value and key modifications and deletions detected on agent 002 to determine whether they represent legitimate software activity or unauthorized tampering, correlating with process and user activity logs. (Medium urgency)
- Review the Wazuh agent stop and disconnection events across both agents to confirm they were planned maintenance actions and not deliberate attempts to disable security monitoring. (Medium urgency)
- Address the CIS Linux benchmark compliance failures on agent 001 (linux1), including inactive password lock, /etc/passwd permissions, and password creation requirements, to bring the SCA score above the 50% threshold. (Medium urgency)
- Investigate the file integrity checksum change detected on agent 001 (linux1) to confirm whether the modified file was changed by an authorized process or user. (Low urgency)

Vulnerability Analysis

Software vulnerabilities are weaknesses in code that can allow attackers to gain access to or manipulate the behavior of an application. Vulnerable software applications are commonly targeted by attackers to compromise endpoints and gain a persistent presence on targeted networks.

This section includes three types of analysis—by severity, affected packages, and operating system—as well as a summary of recommended mitigation actions.

Top Vulnerabilities

This summary lists the ten most critical vulnerabilities detected in your wazuh installation across all your endpoints, sorted by their CVSS.

ID	Package	CVSS	Count	Description
CVE-2026-57092	Microsoft Windows 11 Home 10.0.26200.8037	9.8999 996185 30273	1	A use-after-free vulnerability in Windows VMSwitch allows an authorized attacker to elevate privileges over a network, making it exploitable by insiders or already-compromised accounts to gain higher-level access within the system.
CVE-2026-33824	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A double-free memory corruption flaw in the Windows IKE Extension allows an unauthenticated remote attacker to execute arbitrary code over a network, posing a severe risk to VPN and IPsec-dependent infrastructure.
CVE-2026-41096	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A heap-based buffer overflow in Microsoft Windows DNS enables an unauthenticated attacker to remotely execute code, potentially compromising DNS resolution and enabling further lateral movement across the network.
CVE-2026-42990	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A heap-based buffer overflow in the SQL Server ODBC driver allows an unauthenticated remote attacker to execute arbitrary code, threatening data integrity and confidentiality for any system using this driver for database connectivity.
CVE-2026-44815	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A stack-based buffer overflow in the Windows DHCP Client allows an unauthenticated attacker to remotely execute code, which could be triggered by a malicious DHCP server on the same network segment.
CVE-2026-45657	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A use-after-free vulnerability in the Windows Kernel allows an unauthenticated remote attacker to execute arbitrary code, representing one of the most severe classes of kernel-level exploits with potential for full system compromise.
CVE-2026-47291	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	An integer overflow or wraparound in Windows HTTP.sys enables unauthenticated remote code execution, targeting the kernel-mode HTTP request handler used by IIS and other web-facing services.
CVE-2026-49172	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A heap-based buffer overflow in the Windows FTP Service allows an unauthenticated attacker to remotely execute code, posing a direct risk to any system running or exposing FTP services.

ID	Package	CVSS	Count	Description
CVE-2026-50447	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	A heap-based buffer overflow in Windows Message Queuing (MSMQ) allows an unauthenticated remote attacker to execute code, affecting systems that rely on MSMQ for inter-application messaging.
CVE-2026-56190	Microsoft Windows 11 Home 10.0.26200.8037	9.8000 001907 34863	1	Use of an uninitialized resource in Windows RDP allows an unauthenticated attacker to remotely execute code, directly threatening the widely-used Remote Desktop Protocol service and any exposed RDP endpoints.

Vulnerabilities by Packages

This section presents the ten most vulnerable packages, determined by the amount of vulnerabilities detected in your Wazuh installation..

Package	Count	Description
Microsoft Windows 11 Home 10.0.26200.8037	853	The Windows 11 Home OS package carries an extensive set of critical vulnerabilities across core subsystems including the kernel, RDP, DNS, DHCP, HTTP.sys, FTP, IKE, VMSSwitch, Message Queuing, and SQL Server ODBC driver. The top-scoring flaws allow unauthenticated remote code execution or privilege escalation, representing an urgent patching priority for agent 002.
weasyprint	2	The weasyprint Python package (version 62.3) on the Kali Linux agent is affected by an SSRF protection bypass (CVE-2025-68616) that allows redirect-based circumvention of custom URL filters, and a CSS injection vulnerability (CVE-2026-49452) that enables server-side requests via injected CSS when presentational hints are enabled.
mitmproxy	1	The mitmproxy Python package (version 12.2.1) on the Kali Linux agent contains an LDAP authentication bypass (CVE-2026-40606) where unsanitized usernames in LDAP proxy authentication queries allow malicious clients to bypass access controls; a patch is available in version 12.2.2.

OS by Vulnerabilities

This section display the top ten operating systems (OS) ranked by the number of vulnerabilities associated with each one. As mentioned earlier, the number of endpoints with a given OS version installed impacts the number of detected vulnerabilities for that OS, as a larger number of installations represents a greater attack surface.

OS	Count	Description
Microsoft Windows 11 Home 10.0.26200.8037	853	Microsoft Windows 11 Home version 10.0.26200.8037 carries the largest vulnerability burden in the environment, with critical-severity flaws spanning core OS components including VMSSwitch (privilege escalation via use-after-free), FTP Service, HTTP.sys, Windows Kernel, DHCP Client, SQL Server ODBC driver, IKE Extension, Windows DNS, Message Queuing, and RDP – the majority scoring 9.8 or higher on the CVSS scale, enabling unauthenticated remote code execution.

OS	Count	Description
Kali GNU/Linux 2026.1	3	Kali GNU/Linux 2026.1 has a small number of detected vulnerabilities, affecting Python packages weasyprint and mitmproxy. The weasyprint issues include an SSRF protection bypass and a CSS injection flaw, while mitmproxy has an LDAP authentication bypass affecting instances using the proxyauth option.

Recommended Actions

The vulnerability landscape is dominated by a critical concentration of unpatched flaws in the Windows 11 Home OS on agent 002, with the majority enabling unauthenticated remote code execution across widely-used network services. The Kali Linux agent carries a smaller but notable set of vulnerabilities in third-party Python packages that could expose internal network resources or allow authentication bypass. Immediate patching of the Windows system is the highest priority action in the environment.

- Apply the latest Microsoft Windows cumulative security update to agent 002 (win1) immediately to remediate CVE-2026-57092, CVE-2026-49172, CVE-2026-47291, CVE-2026-45657, CVE-2026-44815, CVE-2026-42990, CVE-2026-33824, CVE-2026-41096 (8 highest-scoring; 2 additional critical CVEs remain: CVE-2026-50447, CVE-2026-56190). (High urgency)
- Disable or restrict access to Windows RDP, FTP Service, HTTP.sys, DHCP Client, IKE, VMSwitch, Message Queuing, and DNS services on agent 002 (win1) as compensating controls until the security update is applied, particularly for CVE-2026-56190, CVE-2026-49172, CVE-2026-47291, CVE-2026-44815, CVE-2026-57092, CVE-2026-50447, CVE-2026-33824, CVE-2026-41096. (High urgency)
- Upgrade the weasyprint Python package on agent 001 (linux1) from version 62.3 to the latest patched release to remediate CVE-2025-68616 and CVE-2026-49452, and ensure presentational_hints is disabled in any application using weasyprint with untrusted HTML input. (Medium urgency)
- Upgrade the mitmproxy Python package on agent 001 (linux1) from version 12.2.1 to version 12.2.2 or later to remediate CVE-2026-40606, which allows LDAP authentication bypass when the proxyauth option is in use. (Medium urgency)

Endpoint Analysis

This section highlights the ten most active endpoints in the environment, based on the number of alerts generated. The most active endpoints are those with the highest alert volume, helping to identify areas with elevated security activity or concerns.

Endpoints by Alerts

This section presents the ten endpoints with the most alerts in your Wazuh installation.

ID	Name	OS	Count	Description
002	win1	Microsoft Windows 11 Home 10.0.26200.8037	655	This Windows 11 endpoint is generating a high volume of alerts, predominantly driven by CIS benchmark compliance failures related to Windows Update controls (pause updates and preview builds management) and password policy configuration. Additionally, registry integrity checksum changes and registry value deletions have been detected, suggesting possible configuration tampering or software activity, alongside service startup type changes and repeated license activation failures for slui.exe.
001	linux1	Kali GNU/Linux 2026.1	194	This Kali Linux endpoint is primarily flagging CIS Distribution Independent Linux benchmark compliance issues, including inactive password lock policy, permissions on /etc/passwd, and password creation requirements, with an overall SCA score below 50%. A file integrity checksum change and a PAM login session closure have also been recorded, and the agent experienced a disconnection event, which may indicate monitoring gaps.

Recommended Actions

Alert activity across both endpoints reflects a combination of active security events and systemic configuration compliance failures. The Windows endpoint shows signs of potential adversarial activity including firewall blocking of repeated connection attempts, registry manipulation consistent with defense evasion, and unauthorized service creation. Both endpoints exhibit significant CIS benchmark non-compliance. The Linux endpoint additionally recorded a file integrity change requiring verification.

- Prioritize security hardening of agent 002 (win1, Windows 11 Home) given its high alert volume driven by CIS benchmark failures, registry integrity changes, and firewall drop events indicating possible external probing. (High urgency)
- Investigate the repeated license activation failures (slui.exe) on agent 002 to confirm the Windows installation is properly licensed and activated, as an unlicensed system may not receive security updates. (Medium urgency)
- Review the agent disconnection event on agent 001 (linux1) and ensure continuous monitoring coverage is restored; investigate whether the disconnection coincided with any suspicious activity. (Medium urgency)
- Conduct a full review of the CIS benchmark compliance posture on both agents and implement a remediation plan to address the highest-impact failing controls, starting with password policy and update management settings. (Medium urgency)

IT Hygiene

IT hygiene refers to practices that maintain the security, availability, and efficiency of IT infrastructure. Wazuh maintains a system inventory containing hardware specifications, operating system details, installed software, network interfaces, ports, and others. This data enables identification of unwanted applications, unauthorized services, and malicious artifacts.

This section analyzes system state across processes, open ports, installed packages, services, and users, with recommended actions.

Top 10 Processes

This section lists the ten most common processes ranked by endpoint count, including the command line and a brief description for each.

Name	Command	Count	Description
svchost.exe	C:/WINDOWS/System32/svchost.exe -k LocalSystemNetworkRestricted -p -s TextInputManagementService	75	The Windows Service Host process (svchost.exe) is running multiple instances on agent 002, which is normal for Windows as it hosts many system services. The observed instance is running the TextInputManagementService under the LocalSystemNetworkRestricted group, which manages text input functionality.
kworker/R-scsi_	-	33	A Linux kernel worker thread associated with SCSI device handling on agent 001. Multiple instances are expected on systems with SCSI or virtual disk devices and represent normal kernel activity.
msedgewebview2.exe	"C:/Program Files (x86)/Microsoft/EdgeWebView/Application/153.0.4234.32/msedgewebview2.exe" -embedded-browser-webview=1 -webview-exe-name=SearchHost.exe ...	12	Microsoft Edge WebView2 runtime process running embedded within the Windows Search Host (SearchHost.exe) on agent 002, providing web rendering capabilities for the Windows search interface. The version in use is 153.0.4234.32.
msedge.exe	"C:/Program Files (x86)/Microsoft/Edge/Application/msedge.exe" -no-startup-window	10	Microsoft Edge browser process running on agent 002 without a startup window, likely running background tasks or extensions. Should be kept up to date to avoid browser-based vulnerabilities.
RuntimeBroker.exe	C:/Windows/System32/RuntimeBroker.exe -Embedding	8	The Windows Runtime Broker process manages permissions for Universal Windows Platform (UWP) applications on agent 002. Multiple instances are normal when several UWP apps are running.
wrapper-2.0	/usr/lib/x86_64-linux-gnu/xfce4/panel/wrapper-2.0	8	The XFCE4 panel plugin wrapper process on agent 001, used to host panel plugins in separate processes for stability. Its presence indicates the XFCE desktop environment is in use.
bwrap	bwrap	4	Bubblewrap (bwrap) is a sandboxing tool used on agent 001 to run processes in isolated namespaces, commonly used by Flatpak and other container-like environments on Linux.
psimon	-	3	The psimon process on agent 001 is a process monitoring utility. Its purpose should be verified to confirm it is an authorized monitoring tool and not an unexpected surveillance process.

Name	Command	Count	Description
systemd-userwor	systemd-userwork: waiting...	3	Systemd user worker threads on agent 001 that handle user-session systemd unit management. These are normal background processes in a systemd-based Linux environment.
conhost.exe	/?/?/C:/WINDOWS/system32/conhost.exe 0x4	2	The Windows Console Host process on agent 002, which provides the console window for command-line applications. Its presence is normal but the use of the NT device path prefix (/?/?/) in the command line is worth noting.

Top 10 Open Ports

This section lists the ten most common open ports ranked by endpoint count, including the port number, associated process, and a description.

Port	Process	Count	Description
1900	svchost.exe	4	Port 1900 is used for UPnP (Universal Plug and Play) SSDP discovery, managed by svchost.exe on agent 002. UPnP should be disabled if not required, as it has historically been exploited for network amplification attacks and unauthorized device discovery.
123	svchost.exe	2	Port 123 is the standard NTP (Network Time Protocol) port, used by svchost.exe on agent 002 for time synchronization. This is expected behavior but should be restricted to trusted NTP servers.
135	svchost.exe	2	Port 135 is the Windows RPC endpoint mapper, managed by svchost.exe on agent 002. It is a common target for remote exploitation and should be restricted to trusted internal hosts only.
445	System	2	Port 445 is used for SMB (Server Message Block) file sharing, operated by the Windows System process on agent 002. SMB is a frequent target for lateral movement and ransomware and should not be exposed to untrusted networks.
5353	msedge.exe	2	Port 5353 is used for mDNS (Multicast DNS), here associated with the Microsoft Edge browser process on agent 002. This is used for local network service discovery and is generally low risk on internal networks.

Port	Process	Count	Description
5355	svchost.exe	2	Port 5355 is used for LLMNR (Link-Local Multicast Name Resolution) by svchost.exe on agent 002. LLMNR is known to be vulnerable to poisoning attacks and should be disabled if not required.
7680	svchost.exe	2	Port 7680 is used by the Windows Delivery Optimization service (svchost.exe) on agent 002 for peer-to-peer Windows Update distribution. It should be restricted to the local network and not exposed externally.
49664	lsass.exe	2	A dynamic/ephemeral port associated with the lsass.exe (Local Security Authority Subsystem Service) process on agent 002. lsass.exe listening on a network port is unusual and should be investigated to rule out credential theft or process injection.
49665	wininit.exe	2	A dynamic port associated with wininit.exe (Windows Initialization process) on agent 002, used for RPC communication during system startup. This is generally expected behavior for Windows system initialization.
49666	svchost.exe	2	A dynamic RPC port used by svchost.exe on agent 002 for inter-process communication. Dynamic RPC ports are normal on Windows but should be monitored for unexpected external exposure.

Top 10 Packages

This section lists the ten most common installed packages ranked by endpoint count, including the package name, vendor, version, type, and a description

Package	Vendor	Version	Type	Count	Description
certipy-ad	Kali Developers <devel@kali.org>	5.0.4-0kali3	deb	2	Certipy-ad is an offensive security tool for enumerating and abusing Active Directory Certificate Services (AD CS) misconfigurations. Its presence on agent 001 (Kali Linux) should be confirmed as authorized for security testing purposes.
faraday-agent-dispatcher	Kali Developers <devel@kali.org>	3.2.1-0kali2	deb	2	Faraday Agent Dispatcher is a component of the Faraday vulnerability management platform used to dispatch security agents. Its presence on agent 001 suggests integration with a vulnerability management workflow.

Package	Vendor	Version	Type	Count	Description
faraday-cli	Kali Developers <devel@kali.org>	2.1.8-0kali1	deb	2	Faraday CLI is the command-line interface for the Faraday vulnerability management platform, used to interact with Faraday workspaces and import security findings from various tools.
fierce	-	1.6.0	pypi	2	Fierce is a DNS reconnaissance tool used for locating non-contiguous IP space and hostnames. As an offensive tool on agent 001, its use should be restricted to authorized penetration testing activities.
gcc-16-base	Debian GCC Maintainers <debian-gcc@lists.debian.org>	16.1.0-1	deb	2	GCC 16 base package provides the GNU Compiler Collection runtime libraries on agent 001. It is a standard development dependency on Debian-based Linux systems.
ghp-import	Debian Python Team <team+python@tracker.debian.org>	2.1.0-3	deb	2	ghp-import is a Python utility for importing content into GitHub Pages branches. Its presence on agent 001 may indicate documentation or web publishing workflows.
greenbone-feed-sync	-	25.1.7	pypi	2	Greenbone Feed Sync is a tool for synchronizing vulnerability feed data for the Greenbone/OpenVAS vulnerability scanner. Its presence on agent 001 indicates active vulnerability scanning capabilities.
kali-tweaks	Kali Developers <devel@kali.org>	2025.4.0	deb	2	Kali Tweaks is a configuration utility specific to Kali Linux that allows users to customize the Kali environment, including shell, network, and tool settings.
libabsl20260107	Matthias Klose <doko@debian.org>	20260107.0-5	deb	2	libabsl is the Abseil C++ library, a collection of C++ code from Google used as a dependency by various applications on agent 001. It is a standard system library.
libaom3	Debian Multimedia Maintainers <debian-multimedia@lists.debian.org>	3.13.1-2+b1	deb	2	libaom3 is the AV1 video codec library used for encoding and decoding AV1 video streams on agent 001. It is a multimedia dependency commonly required by browsers and media applications.

Top 10 Users

This section lists the ten most common users ranked by endpoint count, including the username, groups, shell, home directory, and a description.

User	Groups	Shell	Home directory	Count	Description
Administrator	Administrators	C: \Windows\system32\cmd.exe	-	1	The built-in Windows Administrator account on agent 002, a member of the Administrators group with full system privileges. This account should be protected with a strong password and its use should be limited to necessary administrative tasks.
Debian-snmp	Debian-snmp	/bin/false	/var/lib/snmp	1	A service account on agent 001 used by the SNMP daemon. The non-login shell (/bin/false) prevents interactive login, which is appropriate for a service account.
DefaultAccount	System Managed Accounts Group	C: \Windows\system32\cmd.exe	-	1	A built-in Windows account on agent 002 managed by the system, used for running certain Windows Store applications. It is disabled by default and should remain so unless specifically required.
Guest	Guests	C: \Windows\system32\cmd.exe	-	1	The built-in Windows Guest account on agent 002, a member of the Guests group with limited privileges. This account should be disabled to prevent unauthorized access.
LOCAL SERVICE	-	C: \Windows\system32\cmd.exe	%systemroot%\ServiceProfiles\LocalService	1	A built-in Windows service account on agent 002 used by services that require minimal local privileges and anonymous network access. It is a standard system account.
NETWORK SERVICE	-	C: \Windows\system32\cmd.exe	%systemroot%\ServiceProfiles\NetworkService	1	A built-in Windows service account on agent 002 used by services that require network access with limited local privileges. It is a standard system account used by many Windows services.
SYSTEM	-	C: \Windows\system32\cmd.exe	%systemroot%\system32\config\systemprofile	1	The Windows SYSTEM account on agent 002, which has the highest level of privilege on a local Windows system. It is used by the OS and core services and should not be used for interactive logons.
WDAGUtilityAccount	-	C: \Windows\system32\cmd.exe	-	1	A system-managed account on agent 002 used by Windows Defender Application Guard (WDAG) for sandboxed browser sessions. It should remain disabled unless WDAG is actively in use.
_apt	nogroup	/usr/sbin/nologin	/nonexistent	1	A system service account on agent 001 used by the APT package manager for privilege separation during package operations. The nologin shell and nonexistent home directory are appropriate security configurations.

User	Groups	Shell	Home directory	Count	Description
_gophish	_gophish	/usr/sbin/nologin	/var/lib/gophish	1	A service account on agent 001 dedicated to the GoPhish phishing simulation framework. Its presence indicates GoPhish is installed and should be confirmed as authorized for security awareness testing, with access restricted to prevent misuse.

Top 10 Services

This section lists the ten most common services ranked by endpoint count, including the service name and a description.

Service	Count	Description
Intel(R) Serial IO GPIO Driver v2	4	A hardware driver service for Intel Serial IO GPIO (General Purpose Input/Output) controller, providing low-level communication between the OS and Intel platform GPIO hardware on agent 002.
Intel(R) Serial IO I2C Driver v2	4	A hardware driver service for Intel Serial IO I2C (Inter-Integrated Circuit) controller, enabling communication with I2C-connected peripherals such as touchpads and sensors on agent 002.
Microsoft Pluton Service	2	The Microsoft Pluton security processor service on agent 002, which manages the Pluton security chip integrated into modern processors for secure key storage and platform attestation.
Serial UART Support Library	2	A support library service for Serial UART (Universal Asynchronous Receiver-Transmitter) communication on agent 002, used for serial port communication with hardware devices.
1394 OHCI Compliant Host Controller	1	A driver service for IEEE 1394 (FireWire) OHCI-compliant host controllers on agent 002. If FireWire devices are not in use, this service could be disabled to reduce the attack surface.
3ware	1	A driver service for 3ware RAID controllers, used for managing hardware RAID arrays. Its presence on agent 002 should be verified against the actual hardware configuration.
@%SystemRoot%\System32\drivers\tcpipreg.sys,-10110,	1	A Windows TCP/IP registry driver service entry on agent 002, associated with the TCP/IP network stack registration. The unresolved display name may indicate a localization or registry issue.
@todo.dll,-100;Microsoft IPv6 Protocol Driver	1	The Microsoft IPv6 Protocol Driver service on agent 002, responsible for IPv6 network stack support. The '@todo.dll' prefix suggests an unresolved service display name string.
ACPI Audio Compositor Driver	1	An ACPI-based audio compositor driver service on agent 002, used for managing audio hardware through the ACPI interface, typically for integrated audio devices.
ACPI Devices driver	1	The ACPI Devices driver service on agent 002 manages ACPI-compliant hardware devices, enabling power management and hardware enumeration for ACPI-compatible components.

Recommended Actions

- Review and restrict access to SMB port 445 (process: System) on agent 002, as it is a common attack vector for lateral movement and ransomware; ensure it is not exposed to untrusted networks. (High urgency)
- Audit port 135 (RPC endpoint mapper, process: svchost.exe) on agent 002 and restrict access to trusted hosts only, as it is frequently targeted for remote exploitation. (High urgency)
- Review the presence of offensive security tools such as certipy-ad, fierce, and faraday-agent-dispatcher on agent 001 (linux1, Kali) to confirm they are authorized for legitimate security testing and are not accessible to unauthorized users. (High urgency)
- Ensure the Administrator account on agent 002 is protected with a strong password and MFA, and verify it is not used for routine operations, given its membership in the Administrators group. (High urgency)
- Audit the _gophish user account on agent 001 to confirm the GoPhish phishing framework is authorized and its service is not exposed externally, as it could be misused for internal phishing campaigns. (High urgency)
- Review port 49664 (process: lsass.exe) on agent 002; lsass.exe listening on a dynamic port is unusual and should be investigated to rule out credential dumping or process injection activity. (Medium urgency)
- Verify that port 1900 (UPnP, process: svchost.exe) on agent 002 is not exposed to external networks, as UPnP has a history of being exploited for network amplification and unauthorized device discovery. (Medium urgency)
- Confirm that the mitmproxy package on agent 001 is used only for authorized security testing and that the proxyauth LDAP option is not enabled in production contexts given the known authentication bypass vulnerability. (Medium urgency)
- Review the Intel Serial IO GPIO and I2C driver services on agent 002 to confirm they are required for the hardware in use and are running the latest firmware/driver versions. (Low urgency)
- Audit the Debian-snmp user on agent 001 to ensure SNMP is configured with strong community strings or SNMPv3 authentication and is not exposing sensitive system information. (Low urgency)