

# Современные нейросетевые технологии

---

Лекция 2. Линейная  
классификация изображений

- 1) Линейный классификатор изображений
- 2) Преобразование softmax
- 3) Функция потерь Cross Entropy Loss

Материалы курса:

[github.com/balezz/modern\\_dl](https://github.com/balezz/modern_dl)

Срок сдачи А1 – 10.09.2022 г.

Источники:

- [dlcourse.ai](https://dlcourse.ai)
- [cs231n.stanford.edu](https://cs231n.stanford.edu)
- [cs230.stanford.edu](https://cs230.stanford.edu)

## Image Classification: A core task in Computer Vision




This image by Nikita is  
licensed under [CC-BY 2.0](#)

(assume given set of discrete labels)  
{dog, cat, truck, plane, ...}

→ cat

## The Problem: Semantic Gap



This image by Nikita is  
licensed under [CC-BY 2.0](#)


```
[[105 112 108 111 104 99 106 99 96 103 112 119 104 97 93 87]  
[ 91 98 102 106 104 79 98 103 99 105 123 136 110 105 94 85]  
[ 76 85 90 105 128 105 87 96 95 99 115 112 106 103 99 85]  
[ 99 81 81 93 120 131 127 100 95 98 102 99 96 93 101 94]  
[106 91 61 64 69 91 88 85 101 107 109 98 75 84 96 95]  
[114 108 85 55 55 69 64 54 64 87 112 129 98 74 84 91]  
[133 137 147 103 65 81 80 65 52 54 74 84 102 93 85 82]  
[128 137 144 140 109 95 86 70 62 65 63 63 60 73 86 101]  
[125 133 140 137 119 121 117 94 65 79 80 65 54 64 72 98]  
[127 125 131 147 133 127 126 131 111 96 89 75 61 64 72 84]  
[115 114 109 123 150 148 131 118 113 109 100 92 74 65 72 78]  
[ 89 93 98 97 108 147 131 118 113 114 113 109 106 95 77 80]  
[ 63 77 86 81 77 79 102 123 117 115 117 125 125 130 115 87]  
[ 62 65 82 89 78 71 80 101 124 126 119 101 107 114 131 119]  
[ 63 65 75 88 89 71 62 81 120 138 135 105 81 98 110 118]  
[ 87 65 71 87 106 95 69 45 76 130 126 107 92 94 105 112]  
[118 97 82 86 117 123 116 66 41 51 95 93 89 95 102 107]  
[164 146 112 88 82 120 124 104 76 48 45 66 88 101 102 109]  
[157 170 157 120 93 86 114 132 112 97 69 55 70 82 99 94]  
[130 128 134 161 139 100 109 118 121 134 114 87 65 53 69 86]  
[128 112 96 117 150 144 120 115 104 107 102 93 87 81 72 79]  
[123 107 96 86 83 112 153 149 122 109 104 75 80 107 112 99]  
[122 121 102 88 82 86 94 117 145 148 153 102 50 78 92 107]  
[122 164 148 103 71 56 78 83 93 103 119 139 102 61 69 84]]
```

What the computer sees

An image is just a big grid of  
numbers between  $[0, 255]$ :

e.g.  $800 \times 600 \times 3$   
(3 channels RGB)

## Challenges: Viewpoint variation



[105 112 100 111 104 99 106 99 96 103 112 109 104 97 93 87]
[ 91 98 102 106 104 78 98 102 98 105 123 136 150 105 94 85]
[ 78 85 98 105 128 105 87 96 95 99 125 112 105 103 99 85]
[ 99 81 81 93 120 121 127 100 95 98 102 89 96 93 101 94]
[106 91 61 64 69 91 89 85 101 107 109 99 75 84 96 95]
[114 100 85 55 55 68 64 54 64 87 112 129 88 74 84 91]
[133 137 147 103 85 81 88 85 52 54 74 84 102 93 85 82]
[120 137 144 140 100 95 84 79 62 65 63 60 73 86 101]
[125 133 140 137 119 121 117 94 85 79 89 85 54 64 72 90]
[127 126 121 147 133 127 126 101 111 96 89 76 61 64 72 84]
[115 114 109 123 150 148 131 118 113 109 100 82 74 65 72 70]
[ 88 83 88 87 100 147 131 118 113 114 110 100 96 77 80]
[ 63 77 86 81 77 79 102 123 117 115 117 125 125 130 115 87]
[ 62 66 82 88 78 71 88 101 124 126 110 101 107 114 101 110]
[ 63 65 75 88 89 71 62 81 120 130 135 105 81 90 110 110]
[ 87 86 71 87 106 96 88 65 76 130 126 107 82 84 106 112]
[118 97 82 86 117 123 116 66 41 51 85 83 89 95 102 107]
[104 146 112 88 82 120 124 104 76 48 46 86 88 101 102 109]
[157 170 157 120 93 86 114 132 112 97 69 55 70 82 99 94]
[130 128 134 101 138 100 109 118 121 134 114 87 65 83 89 86]
[120 112 96 117 150 144 120 115 104 107 102 83 87 81 72 79]
[129 107 96 88 89 112 103 149 122 109 104 76 80 107 112 99]
[122 121 102 68 82 86 84 117 145 140 153 102 50 70 82 107]
[122 104 140 103 71 96 78 83 83 103 119 119 102 61 60 84]

All pixels change when  
the camera moves!



# Проблемы классификации



This image is CC0 1.0 public domain




This image is CC0 1.0 public domain



This image is CC0 1.0 public domain



This image is CC0 1.0 public domain



This image by Umberto Salvagnin is licensed under CC BY 2.0



This image by Umberto Salvagnin is licensed under CC BY 2.0



This image by jacobloos is licensed under CC BY 2.0



This image by Jona Dine is licensed under CC BY 2.0



This image is CC0 1.0 public domain




This image is CC0 1.0 public domain



This image by jacobloos is licensed under CC BY 2.0



This image is CC0 1.0 public domain



This image is CC0 1.0 public domain



This image is CC0 1.0 public domain

### Naïve image classifier

```
def classify_image(image):  
    # Some magic here?  
    return class_label
```

Unlike sorting, no obvious way to hard-cod the algorithm for recognizing a cat or other classes

### Data driven approach

```
def train(images, labels):  
    # Machine learning!  
    return model
```

```
def predict(model, test_images):  
    # Use model to predict labels  
    return test_labels
```

1. Collect a dataset of images and labels
2. Use Machine Learning to train a classifier
3. Evaluate the classifier on new images



## Example Dataset: CIFAR10

**10** classes

**50,000** training images

**10,000** testing images

airplane



automobile




bird



cat



deer



dog



frog




horse



ship



truck




Test images and nearest neighbors







## Parametric Approach: Linear Classifier



## Линейный классификатор



## Interpreting a Linear Classifier



Plot created using [Wolfram Cloud](#)

$$f(x, W) = Wx + b$$



Array of **32x32x3** numbers  
(3072 numbers total)

[Cat image](#) by [Nikita](#) is licensed under [CC-BY 2.0](#)




# Hard cases for a linear classifier

### Class 1:

number of pixels  $> 0$  odd

### Class 2:

number of pixels  $> 0$  even




### Class 1:

$1 \leq \text{L2 norm} \leq 2$

### Class 2:

Everything else




### Class 1:

Three modes

### Class 2:

Everything else



**So far:** Defined a (linear) score function  $f(x, W) = Wx + b$

Example class  
scores for 3  
images for  
some  $W$ :



How can we tell  
whether this  $W$   
is good or bad?

airplane	-3.45	-0.51	3.42
automobile	-8.87	<b>6.04</b>	4.64
bird	0.09	5.31	2.65
cat	<b>2.9</b>	-4.22	5.1
deer	4.48	-4.19	2.64
dog	8.02	3.58	5.55
frog	3.78	4.49	<b>-4.34</b>
horse	1.06	-4.37	-1.5
ship	-0.36	-2.09	-4.79
truck	-0.72	-2.93	6.14

Suppose: 3 training examples, 3 classes.  
With some  $W$  the scores  $f(x, W) = Wx$  are:



cat	<b>3.2</b>	1.3	2.2
car	5.1	<b>4.9</b>	2.5
frog	-1.7	2.0	<b>-3.1</b>

A **loss function** tells how good our current classifier is

Given a dataset of examples

$$\{(x_i, y_i)\}_{i=1}^N$$

Where  $x_i$  is image and  
 $y_i$  is (integer) label

Loss over the dataset is a  
sum of loss over examples:

$$L = \frac{1}{N} \sum_i L_i(f(x_i, W), y_i)$$



# Softmax Classifier (Multinomial Logistic Regression)



cat **3.2**

car **5.1**

frog **-1.7**

**scores = unnormalized log probabilities of the classes.**

$$P(Y = k | X = x_i) = \frac{e^{s_k}}{\sum_j e^{s_j}} \quad \text{where} \quad s = f(x_i; W)$$


Want to maximize the log likelihood, or (for a loss function) to minimize the negative log likelihood of the correct class:

$$L_i = -\log P(Y = y_i | X = x_i)$$

---

in summary: 
$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

## Функция потерь Cross Entropy



## Функция потерь Cross Entropy

y\_prob

y\_true

0.1
0
0
0.5
0.1
0.2
0
0
0
0.1

0
0
0
1
0
0
0
0
0
0

$$H(p, q) = - \sum_{x \in \mathcal{X}} p(x) \log q(x)$$

$$L_i = - \log \left( \frac{e^{s y_i}}{\sum_j e^{s_j}} \right)$$



## Softmax Classifier (Multinomial Logistic Regression)



$$L_i = -\log\left(\frac{e^{s_{y_i}}}{\sum_j e^{s_j}}\right)$$

unnormalized probabilities

