

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РОССИЙСКОЙ ФЕДЕРАЦИИ
МОСКОВСКИЙ АВИАЦИОННЫЙ ИНСТИТУТ
(НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ)

ЛАБОРАТОРНАЯ РАБОТА №8

по курсу “Объектно-ориентированное программирование”

I семестр, 2021/22 учебный год

Студент: Морозов Артем Борисович, группа М80-208Б-20

Преподаватель: Дорохов Евгений Павлович, каф. 806

Задание:

Используя структуру данных, разработанную для лабораторной работы №7, спроектировать и разработать аллокатор памяти для динамической структуры данных. Целью построения аллокатора является минимизация вызова операции `malloc`.

Аллокатор должен выделять большие блоки памяти для хранения фигур и при создании новых фигур-объектов выделять место под объекты в этой памяти.

Аллокатор должен хранить списки использованных/свободных блоков. Для хранения списка свободных блоков нужно применять динамическую структуру данных (контейнер 2-го уровня, согласно варианту задания).

Для вызова аллокатора должны быть переопределены операторы `new` и `delete` у классов-фигур.

Вариант №14:

- Фигура: Пятиугольник (Pentagon)
- Контейнер первого уровня: Бинарное дерево (TBinaryTree)
- Контейнер второго уровня: Связный список (TLinkedList)

Описание программы:

Исходный код разделён на 16 файлов:

- `figure.h` – описание класса фигуры
- `point.h` – описание класса точки
- `point.cpp` – реализация класса точки
- `pentagon.h` – описание класса пятиугольника
- `pentagon.cpp` – реализация класса пятиугольника
- `TBinaryTreeItem.h` – описание элемента бинарного дерева
- `TBinaryTreeItem.cpp` – реализация элемента бинарного дерева
- `TBinaryTree.h` – описание бинарного дерева
- `TBinaryTree.cpp` – реализация бинарного дерева
- `main.cpp` – основная программа
- `Iterator.h` – реализация итератора по бинарному дереву
- `HListItem.h` – описание класса элемента связного списка
- `HListItem.cpp` – реализация класса элемента связного списка
- `TLinkedList.h` – описание связного списка
- `TLinkedList.cpp` – реализация класса связного списка
- `TAllocatorBlock.h` – реализация аллокатора по заданию

Дневник отладки: При выполнении работы ошибок выявлено не было.

Вывод: В ходе данной лабораторной работы я самостоятельно научился реализовывать аллокатор – очень важную вещь, если мы с вами говорим о низкоуровневых языках программирования типа С или С++. Я считаю, что каждый программист должен уметь реализовывать подобное, ведь работа с памятью – это база С++. Плюс собственноручной реализации аллокатора в том, что мы можем пользоваться другой логикой при выделении памяти, например, в структурах данных. Вполне вероятно, что во многих случаях именно самостоятельно написанное выделение памяти сможет прийти на помощь программисту.

Исходный код:

point.h:

```
#ifndef POINT_H
#define POINT_H

#include <iostream>

class Point {
public:
    Point();
    Point(std::istream &is);
    Point(double x, double y);

    double X();
    double Y();

    friend std::istream& operator>>(std::istream& is, Point& p);
    friend std::ostream& operator<<(std::ostream& os, Point& p);

private:
    double x_;
    double y_;
};
#endif
```

point.cpp:

```
#include "point.h"

#include <cmath>

Point::Point() : x_(0.0), y_(0.0) {}

Point::Point(double x, double y) : x_(x), y_(y) {}

Point::Point(std::istream &is) {
    is >> x_ >> y_;
}

double Point::X() {
    return x_;
};

double Point::Y() {
```

```

    return y_;
};

std::istream& operator>>(std::istream& is, Point& p) {
    is >> p.x_ >> p.y_;
    return is;
}

std::ostream& operator<<(std::ostream& os, Point& p) {
    os << "(" << p.x_ << ", " << p.y_ << ")";
    return os;
}

```

figure.h:

```

#ifndef FIGURE_H
#define FIGURE_H

#include "point.h"

class Figure {
public:
    virtual double Area() = 0;
    virtual void Print(std::ostream &os) = 0;
    virtual size_t VertexesNumber() = 0;
    virtual ~Figure() {};
};

#endif

```

pentagon.h:

```

#ifndef PENTAGON_H
#define PENTAGON_H

#include "figure.h"
#include <iostream>

class Pentagon : public Figure {
public:
    Pentagon(std::istream& InputStream);

    virtual ~Pentagon();

    size_t VertexesNumber();
    double Area();
    void Print(std::ostream &OutputStream);

private:
    Point a;
    Point b;
    Point c;
    Point d;
    Point e;
};

#endif

```

pentagon.cpp:

```

#include "pentagon.h"
#include <cmath>

```

```

Pentagon::Pentagon(std::istream &InputStream)
{
    InputStream >> a;
    InputStream >> b;
    InputStream >> c;
    InputStream >> d;
    InputStream >> e;
    std::cout << "Pentagon that you wanted to create has been created" << std::endl;
}

void Pentagon::Print(std::ostream &OutputStream) {
    OutputStream << "Pentagon: ";
    OutputStream << a << " " << b << " " << c << " " << d << " " << e << std::endl;
}

size_t Pentagon::VertexesNumber() {
    size_t number = 5;
    return number;
}

double Pentagon::Area() {
    double q = abs(a.X() * b.Y() + b.X() * c.Y() + c.X() * d.Y() + d.X() * e.Y() + e.X() * a.Y() - b.X() * a.Y() - c.X() * b.Y() -
d.X() * c.Y() - e.X() * d.Y() - a.X() * e.Y());
    double s = q / 2;
    return s;
}

Pentagon::~Pentagon() {
    std::cout << "My friend, your pentagon has been deleted" << std::endl;
}

```

TBinaryTreeItem.h:

```

#ifndef TBINARYTREE_ITEM_H
#define TBINARYTREE_ITEM_H
#include "pentagon.h"

template <class T>
class TBinaryTreeItem {
public:
    TBinaryTreeItem(const T& pentagon);
    TBinaryTreeItem(const TBinaryTreeItem<T>& other);
    T& GetPentagon();
    void SetPentagon(T& pentagon);
    std::shared_ptr<TBinaryTreeItem<T>> GetLeft();
    std::shared_ptr<TBinaryTreeItem<T>> GetRight();
    void SetLeft(std::shared_ptr<TBinaryTreeItem<T>> item);
    void SetRight(std::shared_ptr<TBinaryTreeItem<T>> item);
    void SetPentagon(const T& pentagon);
    void IncreaseCounter();
    void DecreaseCounter();
    int ReturnCounter();
    virtual ~TBinaryTreeItem();

    template<class A>
    friend std::ostream &operator<<(std::ostream &os, const TBinaryTreeItem<A> &obj);

private:
    T pentagon;
    std::shared_ptr<TBinaryTreeItem<T>> left;
    std::shared_ptr<TBinaryTreeItem<T>> right;
    int counter;
};

```

```
#endif
```

TBinaryTreeItem.cpp:

```
#include "TBinaryTreeItem.h"
```

```
template <class T>
```

```
TBinaryTreeItem<T>::TBinaryTreeItem(const T &pentagon) {  
    this->pentagon = pentagon;  
    this->left = this->right = NULL;  
    this->counter = 1;  
}
```

```
template <class T>
```

```
TBinaryTreeItem<T>::TBinaryTreeItem(const TBinaryTreeItem<T> &other) {  
    this->pentagon = other.pentagon;  
    this->left = other.left;  
    this->right = other.right;  
    this->counter = other.counter;  
}
```

```
template <class T>
```

```
T& TBinaryTreeItem<T>::GetPentagon() {  
    return this->pentagon;  
}
```

```
template <class T>
```

```
void TBinaryTreeItem<T>::SetPentagon(const T& pentagon){  
    this->pentagon = pentagon;  
}
```

```
template <class T>
```

```
std::shared_ptr<TBinaryTreeItem<T>> TBinaryTreeItem<T>::GetLeft(){  
    return this->left;  
}
```

```
template <class T>
```

```
std::shared_ptr<TBinaryTreeItem<T>> TBinaryTreeItem<T>::GetRight(){  
    return this->right;  
}
```

```
template <class T>
```

```
void TBinaryTreeItem<T>::SetLeft(std::shared_ptr<TBinaryTreeItem<T>> item) {  
    if (this != NULL){  
        this->left = item;  
    }  
}
```

```
template <class T>
```

```
void TBinaryTreeItem<T>::SetRight(std::shared_ptr<TBinaryTreeItem<T>> item) {  
    if (this != NULL){  
        this->right = item;  
    }  
}
```

```
template <class T>
```

```
void TBinaryTreeItem<T>::IncreaseCounter() {  
    if (this != NULL){  
        counter++;  
    }  
}
```

```
template <class T>
```

```
void TBinaryTreeItem<T>::DecreaseCounter() {  
    if (this != NULL){  
        counter--;  
    }  
}
```

```

    }
}

template <class T>
int TBinaryTreeItem<T>::ReturnCounter() {
    return this->counter;
}

template <class T>
TBinaryTreeItem<T>::~~TBinaryTreeItem() {
    std::cout << "Destructor TBinaryTreeItem was called\n";
}

template <class T>
std::ostream &operator<<(std::ostream &os, TBinaryTreeItem<T> &obj)
{
    os << "Item: " << obj.GetPentagon() << std::endl;
    return os;
}

#include "pentagon.h"
template class TBinaryTreeItem<Pentagon>;
template std::ostream& operator<<(std::ostream& os, TBinaryTreeItem<Pentagon> &obj);

```

TBinaryTree.h:

```

#ifndef TBINARYTREE_H
#define TBINARYTREE_H
#include "TBinaryTreeItem.h"

template <class T>

class TBinaryTree {
public:
    TBinaryTree();
    TBinaryTree(const TBinaryTree<T> &other);
    void Push(T &pentagon);
    std::shared_ptr<TBinaryTreeItem<T>> Pop(std::shared_ptr<TBinaryTreeItem<T>> root, T &pentagon);
    T& GetItemNotLess(double area, std::shared_ptr<TBinaryTreeItem<T>> root);
    void Clear();
    bool Empty();
    int Count(double minArea, double maxArea);
    template <class A>
    friend std::ostream& operator<<(std::ostream& os, TBinaryTree<A>& tree);
    virtual ~TBinaryTree();
    std::shared_ptr<TBinaryTreeItem<T>> root;
};
#endif

```

TBinaryTree.cpp:

```

#include "TBinaryTree.h"

template <class T>
TBinaryTree<T>::TBinaryTree () {
    root = NULL;
}

template <class T>
std::shared_ptr<TBinaryTreeItem<T>> copy (std::shared_ptr<TBinaryTreeItem<T>> root) {
    if (!root) {
        return NULL;
    }
    std::shared_ptr<TBinaryTreeItem<T>> root_copy(new TBinaryTreeItem<T>(root->GetPentagon()));
    root_copy->SetLeft(copy(root->GetLeft()));
    root_copy->SetRight(copy(root->GetRight()));
}

```

```

    return root_copy;
}

template <class T>
TBinaryTree<T>::TBinaryTree (const TBinaryTree<T> &other) {
    root = copy(other.root);
}

```

```

template <class T>
void Print (std::ostream& os, std::shared_ptr<TBinaryTreeItem<T>> node){
    if (!node){
        return;
    }
    if(node->GetLeft()){
        os << node->GetPentagon().GetArea() << ": [";
        Print (os, node->GetLeft());
        if (node->GetRight()){
            if (node->GetRight()){
                os << ", ";
                Print (os, node->GetRight());
            }
        }
        os << "]";
    } else if (node->GetRight()) {
        os << node->GetPentagon().GetArea() << ": [";
        Print (os, node->GetRight());
        if (node->GetLeft()){
            if (node->GetLeft()){
                os << ", ";
                Print (os, node->GetLeft());
            }
        }
        os << "]";
    }
    else {
        os << node->GetPentagon().GetArea();
    }
}

```

```

template <class T>
std::ostream& operator<< (std::ostream& os, TBinaryTree<T>& tree){
    Print(os, tree.root);
    os << "\n";
    return os;
}

```

```

template <class T>
void TBinaryTree<T>::Push (T &pentagon) {
    if (root == NULL) {
        std::shared_ptr<TBinaryTreeItem<T>> help(new TBinaryTreeItem<T>(pentagon));
        root = help;
    }
    else if (root->GetPentagon() == pentagon) {
        root->IncreaseCounter();
    }
    else {
        std::shared_ptr<TBinaryTreeItem<T>> parent = root;
        std::shared_ptr<TBinaryTreeItem<T>> current;
        bool childInLeft = true;
        if (pentagon.GetArea() < parent->GetPentagon().GetArea()) {
            current = root->GetLeft();
        }
        else if (pentagon.GetArea() > parent->GetPentagon().GetArea()) {
            current = root->GetRight();
            childInLeft = false;
        }
    }
}

```



```

while (current != NULL) {
    if (current->GetPentagon() == pentagon) {
        current->IncreaseCounter();
    }
    else {
        if (pentagon.GetArea() < current->GetPentagon().GetArea()) {
            parent = current;
            current = parent->GetLeft();
            childInLeft = true;
        }
        else if (pentagon.GetArea() > current->GetPentagon().GetArea()) {
            parent = current;
            current = parent->GetRight();
            childInLeft = false;
        }
    }
}

std::shared_ptr<TBinaryTreeItem<T>> item (new TBinaryTreeItem<T>(pentagon));
current = item;
if (childInLeft == true) {
    parent->SetLeft(current);
}
else {
    parent->SetRight(current);
}
}
}

template <class T>
std::shared_ptr<TBinaryTreeItem<T>> FMRST(std::shared_ptr<TBinaryTreeItem<T>> root) {
    if (root->GetLeft() == NULL) {
        return root;
    }
    return FMRST(root->GetLeft());
}

template <class T>
std::shared_ptr<TBinaryTreeItem<T>> TBinaryTree<T>::Pop(std::shared_ptr<TBinaryTreeItem<T>> root, T &pentagon) {
    if (root == NULL) {
        return root;
    }
    else if (pentagon.GetArea() < root->GetPentagon().GetArea()) {
        root->SetLeft(Pop(root->GetLeft(), pentagon));
    }
    else if (pentagon.GetArea() > root->GetPentagon().GetArea()) {
        root->SetRight(Pop(root->GetRight(), pentagon));
    }
    else {
        //first case of deleting - we are deleting a list
        if (root->GetLeft() == NULL && root->GetRight() == NULL) {
            root = NULL;
            return root;
        }
        //second case of deleting - we are deleting a vertex with only one child
        else if (root->GetLeft() == NULL && root->GetRight() != NULL) {
            std::shared_ptr<TBinaryTreeItem<T>> pointer = root;
            root = root->GetRight();
            return root;
        }
        else if (root->GetRight() == NULL && root->GetLeft() != NULL) {
            std::shared_ptr<TBinaryTreeItem<T>> pointer = root;
            root = root->GetLeft();
            return root;
        }
        //third case of deleting
        else {

```

```

        std::shared_ptr<TBinaryTreeItem<T>> pointer = FMRST(root->GetRight());
        root->GetPentagon().area = pointer->GetPentagon().GetArea();
        root->SetRight(Pop(root->GetRight(), pointer->GetPentagon()));
    }
}
return root;
}

template <class T>
void RecursiveCount(double minArea, double maxArea, std::shared_ptr<TBinaryTreeItem<T>> current, int& ans) {
    if (current != NULL) {
        RecursiveCount(minArea, maxArea, current->GetLeft(), ans);
        RecursiveCount(minArea, maxArea, current->GetRight(), ans);
        if (minArea <= current->GetPentagon().GetArea() && current->GetPentagon().GetArea() < maxArea) {
            ans += current->ReturnCounter();
        }
    }
}

template <class T>
int TBinaryTree<T>::Count(double minArea, double maxArea) {
    int ans = 0;
    RecursiveCount(minArea, maxArea, root, ans);
    return ans;
}

template <class T>
T& TBinaryTree<T>::GetItemNotLess(double area, std::shared_ptr<TBinaryTreeItem<T>> root) {
    if (root->GetPentagon().GetArea() >= area) {
        return root->GetPentagon();
    }
    else {
        return GetItemNotLess(area, root->GetRight());
    }
}

template <class T>
void RecursiveClear(std::shared_ptr<TBinaryTreeItem<T>> current){
    if (current!= NULL){
        RecursiveClear(current->GetLeft());
        RecursiveClear(current->GetRight());
        current = NULL;
    }
}

template <class T>
void TBinaryTree<T>::Clear(){
    RecursiveClear(root);
    root = NULL;
}

template <class T>
bool TBinaryTree<T>::Empty() {
    if (root == NULL) {
        return true;
    }
    return false;
}

template <class T>
TBinaryTree<T>::~~TBinaryTree() {
    Clear();
    std::cout << "Your tree has been deleted" << std::endl;
}

#include "pentagon.h"

```

```
template class TBinaryTree<Pentagon>;
```

```
template std::ostream& operator<< (std::ostream& os, TBinaryTree<Pentagon>& stack);
```

TIterator.h:

```
#ifndef TITERATOR_H
```

```
#define TITERATOR_H
```

```
#include <iostream>
```

```
#include <memory>
```

```
template <class T, class A>
```

```
class TIterator {
```

```
public:
```

```
TIterator(std::shared_ptr<T> iter) {
```

```
    node_ptr = iter;
```

```
}
```

```
A& operator*() {
```

```
    return node_ptr->GetPentagon();
```

```
}
```

```
void GoToLeft() { //переход к левому поддереву, если существует
```

```
    if (node_ptr == NULL) {
```

```
        std::cout << "Root does not exist" << std::endl;
```

```
    }
```

```
    else {
```

```
        node_ptr = node_ptr->GetLeft();
```

```
    }
```

```
}
```

```
void GoToRight() { //переход к правому поддереву, если существует
```

```
    if (node_ptr == NULL) {
```

```
        std::cout << "Root does not exist" << std::endl;
```

```
    }
```

```
    else {
```

```
        node_ptr = node_ptr->GetRight();
```

```
    }
```

```
}
```

```
bool operator == (TIterator &iterator) {
```

```
    return node_ptr == iterator.node_ptr;
```

```
}
```

```
bool operator != (TIterator &iterator) {
```

```
    return !(*this == iterator);
```

```
}
```

private:

std::shared_ptr<T> node_ptr;

};

#endif

main.cpp:

#include <iostream>

#include "pentagon.h"

#include "TBinaryTree.h"

#include "TBinaryTreeItem.h"

int main () {

//lab1

Pentagon a (std::cin);

std:: cout << "The area of your figure is : " << a.Area() << std:: endl;

Pentagon b (std::cin);

std:: cout << "The area of your figure is : " << b.Area() << std:: endl;

Pentagon c (std::cin);

std:: cout << "The area of your figure is : " << c.Area() << std:: endl;

Pentagon d (std::cin);

std:: cout << "The area of your figure is : " << d.Area() << std:: endl;

Pentagon e (std::cin);

std:: cout << "The area of your figure is : " << e.Area() << std:: endl;

//lab2

TBinaryTree<Pentagon> tree;

std:: cout << "Is tree empty? " << tree.Empty() << std:: endl;

tree.Push(a);

std:: cout << "And now, is tree empty? " << tree.Empty() << std:: endl;

tree.Push(b);

tree.Push(c);

tree.Push(d);

tree.Push(e);

std:: cout << "The number of figures with area in [minArea, maxArea] is: " << tree.Count(0, 100000) << std:: endl;

std:: cout << "The result of searching the same-figure-counter is: " << tree.root->ReturnCounter() << std:: endl;

std:: cout << "The result of function named GetItemNotLess is: " << tree.GetItemNotLess(0, tree.root) << std:: endl;

//lab5

```

TIterator<TBinaryTreeItem<Pentagon>, Pentagon> iter(tree.root);
std::cout << "The figure that you have put in root is: " << *iter << std::endl;
iter.GoToLeft();
std::cout << "The first result of Left-Iter function is: " << *iter << std::endl;
iter.GoToRight();
std::cout << "The first result of Right-Iter function is: " << *iter << std::endl;
TIterator<TBinaryTreeItem<Pentagon>, Pentagon> first(tree.root->GetLeft());
TIterator<TBinaryTreeItem<Pentagon>, Pentagon> second(tree.root->GetLeft());
if (first == second) {
    std::cout << "YES, YOUR ITERATORS ARE EQUALS" << std::endl;
}
TIterator<TBinaryTreeItem<Pentagon>, Pentagon> third(tree.root->GetRight());
TIterator<TBinaryTreeItem<Pentagon>, Pentagon> fourth(tree.root->GetLeft());
if (third != fourth) {
    std::cout << "NO, YOUR ITERATORS ARE NOT EQUALS" << std::endl;
}
return 0;
}

```

HListItem.h:

```

#ifndef HLISTITEM_H
#define HLISTITEM_H
#include <iostream>
#include "pentagon.h"
#include <memory>

```

```

template <class T> class HListItem {
public:
    HListItem(const std::shared_ptr<Pentagon> &pentagon);
    template <class A> friend std::ostream& operator<<(std::ostream& os, HListItem<A> &obj);
    ~HListItem();
    std::shared_ptr<T> pentagon;
    std::shared_ptr<HListItem<T>> next;
};
#endif

```

HListItem.cpp:

```

#include <iostream>
#include "HListItem.h"

```

```

template <class T> HListItem<T>::HListItem(const std::shared_ptr<Pentagon> &pentagon) {

```

```

    this->pentagon = pentagon;
    this->next = nullptr;
}

template <class A> std::ostream& operator<<(std::ostream& os, HListItem<A> &obj) {
    os << "[" << obj.pentagon << "]" << std::endl;
    return os;
}

template <class T> HListItem<T>::~HListItem() {
}

```

TLinkedList.h:

```

#ifndef HLIST_H
#define HLIST_H

#include <iostream>
#include "HListItem.h"
#include "pentagon.h"
#include <memory>

template <class T> class TLinkedList {
public:
    TLinkedList();
    int size_of_list;
    size_t Length();
    std::shared_ptr<Pentagon>& First();
    std::shared_ptr<Pentagon>& Last();
    std::shared_ptr<Pentagon>& GetItem(size_t idx);
    bool Empty();
    TLinkedList(const std::shared_ptr<TLinkedList> &other);
    void InsertFirst(const std::shared_ptr<Pentagon> &&pentagon);
    void InsertLast(const std::shared_ptr<Pentagon> &&pentagon);
    void RemoveLast();
    void RemoveFirst();
    void Insert(const std::shared_ptr<Pentagon> &&pentagon, size_t position);
    void Remove(size_t position);
    void Clear();

    template <class A> friend std::ostream& operator<<(std::ostream& os, TLinkedList<A>& list);
    ~TLinkedList();

private:
    std::shared_ptr<HListItem<T>> front;
    std::shared_ptr<HListItem<T>> back;
};

#endif

```

TLinkedList.cpp:

```
#include <iostream>

#include "TLinkedList.h"
#include "HListItem.h"

template <class T> TLinkedList<T>::TLinkedList() {
    size_of_list = 0;
    std::shared_ptr<HListItem<T>> front;
    std::shared_ptr<HListItem<T>> back;
    std::cout << "Pentagon List created" << std::endl;
}

template <class T> TLinkedList<T>::TLinkedList(const std::shared_ptr<TLinkedList> &other){
    front = other->front;
    back = other->back;
}

template <class T> size_t TLinkedList<T>::Length() {
    return size_of_list;
}

template <class T> bool TLinkedList<T>::Empty() {
    return size_of_list;
}

template <class T> std::shared_ptr<Pentagon>& TLinkedList<T>::GetItem(size_t idx){
    int k = 0;
    std::shared_ptr<HListItem<T>> obj = front;
    while (k != idx){
        k++;
        obj = obj->next;
    }
    return obj->pentagon;
}

template <class T> std::shared_ptr<Pentagon>& TLinkedList<T>::First() {
    return front->pentagon;
}

template <class T> std::shared_ptr<Pentagon>& TLinkedList<T>::Last() {
    return back->pentagon;
}

template <class T> void TLinkedList<T>::InsertLast(const std::shared_ptr<Pentagon> &&pentagon) {
    std::shared_ptr<HListItem<T>> obj (new HListItem<T>(pentagon));
    if(size_of_list == 0) {
        front = obj;
        back = obj;
    }
}
```

```

    size_of_list++;
    return;
}
back->next = obj;
back = obj;
obj->next = nullptr;
size_of_list++;
}

template <class T> void TLinkedList<T>::RemoveLast() {
    if (size_of_list == 0) {
        std::cout << "Pentagon does not pop_back, because the Pentagon List is empty" << std::endl;
    } else {
        if (front == back) {
            RemoveFirst();
            size_of_list--;
            return;
        }
        std::shared_ptr<HListItem<T>> prev_del = front;
        while (prev_del->next != back) {
            prev_del = prev_del->next;
        }
        prev_del->next = nullptr;
        back = prev_del;
        size_of_list--;
    }
}

template <class T> void TLinkedList<T>::InsertFirst(const std::shared_ptr<Pentagon> &&pentagon) {
    std::shared_ptr<HListItem<T>> obj (new HListItem<T>(pentagon));
    if(size_of_list == 0) {
        front = obj;
        back = obj;
    } else {
        obj->next = front;
        front = obj;
    }
    size_of_list++;
}

template <class T> void TLinkedList<T>::RemoveFirst() {
    if (size_of_list == 0) {
        std::cout << "Pentagon does not pop_front, because the Pentagon List is empty" << std::endl;
    } else {

```



```

std::shared_ptr<HListItem<T>> del = front;
front = del->next;
size_of_list--;
}
}

template <class T> void TLinkedList<T>::Insert(const std::shared_ptr<Pentagon> &&pentagon, size_t position) {
    if (position < 0) {
        std::cout << "Position < zero" << std::endl;
    } else if (position > size_of_list) {
        std::cout << " Position > size_of_list" << std::endl;
    } else {
        std::shared_ptr<HListItem<T>> obj (new HListItem<T>(pentagon));
        if (position == 0) {
            front = obj;
            back = obj;
        } else {
            int k = 0;
            std::shared_ptr<HListItem<T>> prev_insert = front;
            std::shared_ptr<HListItem<T>> next_insert;
            while(k+1 != position) {
                k++;
                prev_insert = prev_insert->next;
            }
            next_insert = prev_insert->next;
            prev_insert->next = obj;
            obj->next = next_insert;
        }
        size_of_list++;
    }
}

template <class T> void TLinkedList<T>::Remove(size_t position) {
    if (position > size_of_list) {
        std::cout << "Position " << position << " > " << "size " << size_of_list << " Not correct erase" << std::endl;
    } else if (position < 0) {
        std::cout << "Position < 0" << std::endl;
    } else {
        if (position == 0) {
            RemoveFirst();
        } else {
            int k = 0;
            std::shared_ptr<HListItem<T>> prev_erase = front;

```

```

    std::shared_ptr<HListItem<T>> next_erase;
    std::shared_ptr<HListItem<T>> del;
    while( k+1 != position) {
        k++;
        prev_erase = prev_erase->next;
    }
    next_erase = prev_erase->next;
    del = prev_erase->next;
    next_erase = del->next;
    prev_erase->next = next_erase;
}
size_of_list--;
}
}

template <class T> void TLinkedList<T>::Clear() {
    std::shared_ptr<HListItem<T>> del = front;
    std::shared_ptr<HListItem<T>> prev_del;
    if(size_of_list !=0 ) {
        while(del->next != nullptr) {
            prev_del = del;
            del = del->next;
        }
        size_of_list = 0;
        //  std::cout << "HListItem deleted" << std::endl;
    }
    size_of_list = 0;
    std::shared_ptr<HListItem<T>> front;
    std::shared_ptr<HListItem<T>> back;
}

template <class T> std::ostream& operator<<(std::ostream& os, TLinkedList<T>& hl) {
    if (hl.size_of_list == 0) {
        os << "The pentagon list is empty, so there is nothing to output" << std::endl;
    } else {
        os << "Print Pentagon List" << std::endl;
        std::shared_ptr<HListItem<T>> obj = hl.front;
        while(obj != nullptr) {
            if (obj->next != nullptr) {
                os << obj->pentagon << " " << "," << " ";
                obj = obj->next;
            } else {
                os << obj->pentagon;
            }
        }
    }
}

```

```

        obj = obj->next;
    }
}
os << std::endl;
}
return os;
}

template <class T> TLinkedList<T>::~TLinkedList() {
    std::shared_ptr<HListItem<T>> del = front;
    std::shared_ptr<HListItem<T>> prev_del;
    if(size_of_list !=0 ) {
        while(del->next != nullptr) {
            prev_del = del;
            del = del->next;
        }
        size_of_list = 0;
        std::cout << "Pentagon List deleted" << std::endl;
    }
}
}

```

TAllocatorBlock.h:

```

#ifndef TALLOCATORBLOCK_H
#define TALLOCATORBLOCK_H

#include "TLinkedList.h"
#include <memory>

class TAllocatorBlock {
public:
    TAllocatorBlock(const size_t& size, const size_t count){
        this->size = size;
        for(int i = 0; i < count; ++i){
            unused_blocks.Insert(malloc(size));
        }
    }

    void* Allocate(const size_t& size){
        if(size != this->size){
            std::cout << "Error during allocation\n";
        }
        if(unused_blocks.Length()){
            for(int i = 0; i < 5; ++i){
                unused_blocks.Insert(malloc(size));
            }
        }
    }
}

```

```

    }
}
void* tmp = unused_blocks.GetItem(1);
used_blocks.Insert(unused_blocks.GetItem(1));
unused_blocks.Remove(0);
return tmp;
}
void Deallocate(void* ptr){
    unused_blocks.Insert(ptr);
}
~TAllocatorBlock(){
    while(used_blocks.size()){
        try{
            free(used_blocks.GetItem(1));
            used_blocks.Remove(0);
        } catch(...){
            used_blocks.Remove(0);
        }
    }
    while(unused_blocks.size()){
        try{
            free(unused_blocks.GetItem(1));
            unused_blocks.Remove(0);
        } catch(...){
            unused_blocks.Remove(0);
        }
    }
}

private:
    size_t size;
    TLinkedList <void*> used_blocks;
    TLinkedList <void*> unused_blocks;
};

#endif

```

Результат работы:

Такой же, как и в лабораторной работе №5.