

Technical Specification

Re-circulating Chiller

1. Cooling capacity: 20 kW @10°C
2. Flow Rate: ≥ 75 LPM Pump (Stainless steel pump 304SS)
3. Pump Head Pressure: ≥ 5 Bar
4. Temperature set range: Ambient to 2°C
5. Refrigerant: Zero ozone depletion potential refrigerant should be used (R404a or equivalent)
6. Mains Power: 415Vac, $\pm 10\%$, three phase, 50 Hz
7. Operating Temperature: $\leq 40^\circ\text{C}$
8. Compressor: Sealed Compressor, Energy efficient
9. Water inlet/outlet coupling: 1/2" BSP
10. Tank Capacity: ≥ 60 Liters
11. Outer Frame M.S & Tank: SS-304 (Corrosion resistant)
12. System cooling: Forced Air cooling
13. Filter: Dust filter mesh
14. Portability: Heavy Duty Castor Wheels (user removable) with locking arrangement
15. Controls, Indication & Safety:
 - a. Mains (Power) On/Off Switch
 - b. Digital Temperature indicator cum Controller
 - c. Water Low Level Trip
 - d. Over Temperature Trip
 - e. Overload alarm
 - f. Trip alarm
16. Mains cable: Heavy duty, 3 core Mains cable 5 meters length
17. Water hose pipes (1/2"), 3 meters each, with appropriate connectors to chiller inlet and outlet (2 nos.), insulated with nitrile rubber all over its length.
18. Quick connect coupling (1/2" to 1/2") for pipe hoses (2 nos.)
19. High insulation tank (25 to 50 mm Nitrile Rubber or PUF sheets)
20. Warranty: 1 year