

## SWING

1. How to display the results of a JDBC Query in a JTable?
  - a. Create an adapter class that extends AbstractTableModel and read the result of the query into a Vector of Vectors, and have the getValueAt(row,col) get the value from the corresponding Vector element.
  - b. Loop through the ResultSet, individually setting the value for one cell at a time in the JTable with DefaultTableModel via the JTable's setValueAt(value,row,column) method.
  - c. Pass a reference to the GUI object via a constructor parameter, and then use public methods of that GUI object(not a constructor) to set or change data.
  - d. Create an adapter class that implements TableCellEditor, which uses a singleton to find the Resultset.
  - e. Extend the JTable class and override the paint() method to open a database connection and loop through the ResultSet, drawing the text for each element in the appropriate cell in the table.
  
2. You add data to a Swing component, such as a JTable, JTree, or JList, via the:
  - a. component's peer.
  - b. component's view.
  - c. component's model.
  - d. component's controller.
  - e. component.

## SWING

```
3. import java.awt.*;
import javax.swing.*;
import javax.swing.border.*;

public class Grid extends JPanel{
private static int ROWS = 7;
private static int COL = 10;

public void Generator() {
    ImageIcon wIcon = new ImageIcon;
    JPanel jPan1 = new JPanel();
    jPan1.setLayout ((LayoutManager) new
    GridLayout(rows,col,1,1));
    jPan1.setSize(350,350);
    TitleBorder bdr =
    javax.swing.BorderFactory.createTitleBorder(null, "Targeting
    Grid");
    Bdr.setTitleColor(java.awt.Color.RED);
    jPan1.setLayout ((LayoutManager) new
    GridLayout(rows,col,1,1));
    jPan1.setBorder(bdr);
    JButton b[] = new JButton[rows*col];
    for (i=0;j=rows*col;i<j; i++){
        b[i] = new JButton(wIcon)
        b[i].setSize(20,20);
        b[i].setMaximumSize(new Dimension(20,20));
        b[i].setPreferredSize(new Dimension(20,20));
        System.out.println("Loop test "+ i);
        jPan1.add(b[i]);
    }
}
}
```

Based on the above sample code, how do you fix the code so the buttons show on the created grid?

- a. Replace all instances of JPanel to jPan1
- b. Change the class JPanel from public to private, and then rebuild.
- c. Remove "jPan1 = JPanel();" and replace all remaining occurrences "jPan1" with "this".
- d. Create the grid prior to adding buttons by inserting Grid = new Grid.
- e. Remove all extra set of { } that are present in the code.

## SWING

### 4. Sample Code:

```
public void setFrame(String example) {  
    JButton button = new JButton ("Example");  
    button.addActionListener (new ActionListener () {  
        public void actionPerformed (ActionEvent e) {  
            System.out.println(example);  
        }  
    } ) ;  
}
```

Which do you add to the declaration of the parameter name example for the sample code above to compile?

- a. private
- b. final
- c. public
- d. volatile
- e. transient

### 5. Sample Code


```
import javax.swing.*;  
import java.util.*;  
public class X {  
    public static void main(String args[]) {  
        List<JButton> list = new ArrayList<JButton>();  
        JLabel label = new JLabel("Example");  
        list.add(label);  
        System.out.println(list);  
    }  
}
```

Referring to the sample code above, what happens when you add a JLabel to a List of JButton objects?

- a. At run time, a ClassCastException is thrown when adding to the list.
- b. At run time, an IllegalArgumentException is thrown when adding to the list.
- c. The contents of the list are printed.
- d. At compile time, the compiler rejects the attempt to add the JLabel.
- e. At run time, an IncorrectCastException is thrown when printing the list.

## SWING

6. How do you perform cleanup when a user is trying to close a window?
- Create an inner class called `WindowListener`, extend `WindowEventHandler`, and put cleanup code in a `processEvent(Event e)` method.
  - Place cleanup code in a try-catch block that catches a `FrameClosingException`.
  - Implement `WindowListener`, and put cleanup code in a `public void windowClosing(WindowEvent method)`.
  - Implement `FrameListener`, and place cleanup code in a `frameClosing(FrameEvent e)` method.
  - Allow for the garbage collector to do automatic cleanup



7. Which layout manager do you use to produce the layout shown in the image above?
- `GridLayout`
  - `BorderLayout`
  - `BoxLayout`
  - `ViewportLayout`
  - `FlowLayout`

## SWING

8. Line 1 static boolean bufferedImageEquals( BufferedImage b1, BufferedImage b2 ) {  
Line 2 if ( b1 == b2 ) {return true;}  
Line 3 if ( b1 == null || b2 == null ) { return false; }  
Line 4 if ( b1.getWidth() != b2.getWidth()){ return false;}  
Line 5 if ( b1.getHeight() != b2.getHeight()){return false;}  
Line 6 for ( int i = 0; i < b1.getWidth(); i++) {  
Line 7 for ( int j = 0; j < b1.getHeight(); i++ ) {  
Line 8 if ( b1.getRGB(i,j) != b2.getRGB(i,j) ) {  
Line 9 return false;  
Line 10 }  
Line 11 }  
Line 12 }  
Line 13 return true;  
Line 14 }

Which do you change in the sample code above to eliminate the error:

"java.lang.ArrayIndexOutOfBoundsException: Coordinate out of bounds!"?

- Remove Line 8 from the code.
- The "i++" needs to be changed to "j++" in the second for loop.
- Add if ( b1 == null || b2 == null ) {return true;} after Line 2.
- The class needs to be changed to "if ( b1.getAlpha() != b2.getAlpha() ) { return false; }".
- Change Line 2 to if ( b1 == b2 ) {return false;}.

## SWING

```
9. import java.awt.EventQueue;
import javax.swing.text.JTextComponent;
public class TestInnerClass {
    public void setTheTextBox(JTextComponent cmp, String a) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                cmp.setText(a);
            }
        });
    }
}
```

Why does the sample code above produce an error?

- The anonymous inner class cannot extend Runnable because Runnable is an interface and cannot be instantiated.
- The setTheTextBox() method needs to be declared static so inner classes can be instantiated without an object of the outer class.
- The run() method needs to have a reference to the parent method to resolve local object references.
- JTextComponent cmp and String a are not accessible from the context of the inner class because they need to be declared final.
- EventQueue.invokeLater() requires a Timer object to determine when the method should be invoked.