



## The *openEHR* Reference Model Support Information Model


*Editors:* {T Beale, S Heard}<sup>a</sup>, {D Kalra, D Lloyd}<sup>b</sup>

<i>Revision:</i> 1.6.1	<i>Pages:</i> 62	<i>Date of issue:</i> 31 Jul 2008
------------------------	------------------	-----------------------------------

a. Ocean Informatics

b. Centre for Health Informatics and Multi-professional Education,  
University College London

*Keywords:* EHR, openehr, reference model



© 2003-2007 The *openEHR* Foundation.

The *openEHR* Foundation is an independent, non-profit community, facilitating the sharing of health records by consumers and clinicians via open-source, standards-based implementations

**Founding Chairman** David Ingram, Professor of Health Informatics,  
CHIME, University College London

**Founding Members** Dr P Schloeffel, Dr S Heard, Dr D Kalra, D Lloyd, T Beale

**email:** [info@openEHR.org](mailto:info@openEHR.org) **web:** <http://www.openEHR.org>

## Copyright Notice

© Copyright openEHR Foundation 2001 – 2008  
All Rights Reserved

1. This document is protected by copyright and/or database right throughout the world and is owned by the openEHR Foundation.
2. You may read and print the document for private, non-commercial use.
3. You may use this document (in whole or in part) for the purposes of making presentations and education, so long as such purposes are non-commercial and are designed to comment on, further the goals of, or inform third parties about, openEHR.
4. You must not alter, modify, add to or delete anything from the document you use (except as is permitted in paragraphs 2 and 3 above).
5. You shall, in any use of this document, include an acknowledgement in the form:  
 www.openEHR.org " © Copyright openEHR Foundation 2001-2008. All rights reserved.
6. This document is being provided as a service to the academic community and on a non-commercial basis. Accordingly, to the fullest extent permitted under applicable law, the openEHR Foundation accepts no liability and offers no warranties in relation to the materials and documentation and their content.
7. If you wish to commercialise, license, sell, distribute, use or otherwise copy the materials and documents on this site other than as provided for in paragraphs 1 to 6 above, you must comply with the terms and conditions of the openEHR Free Commercial Use Licence, or enter into a separate written agreement of with openEHR Foundation covering such activities. The terms and conditions the openEHR Free Commercial Use Licence can be found at [http://www.openehr.org/free\\_commercial\\_use.htm](http://www.openehr.org/free_commercial_use.htm)

## Amendment Record

Issue	Details	Raiser	Completed
RELEASE 1.0.2			
1.6.1	<b>SPEC-260:</b> Correct the regex published for the ARCHETYPE_ID type.	P Gummer	31 Jul 2008
RELEASE 1.0.1			
1.6.0	<p><b>CR-000215:</b> Merge DV_PARTIAL_XX date/time classes and move ISO 8601 semantics to Support IM.</p> <p><b>CR-000209:</b> Minor changes to correctly define AUTHORED_RESOURCE.<i>current_revision</i>. Add minimal definition for List&lt;T&gt; class.</p> <p><b>CR-000200:</b> Correct Release 1.0 typographical errors. Move INTERVAL class definition to correct section. Add two invariants. Improved explanation of identifiers.</p> <p><b>CR-000202:</b> Correct minor errors in VERSION.<i>preceding_version_id</i>. Added <i>is_first</i> function and invariant to VERSION_TREE_ID class. Added invariants for 1-based numbering</p> <p><b>CR-000203:</b> Release 1.0 explanatory text improvements.</p> <p><b>CR-000204:</b> Add generic id subtype of OBJECT_ID.</p> <p><b>CR-000216:</b> Allow mixture of W, D etc in ISO8601 Duration (deviation from standard).</p> <p><b>CR-000219:</b> Use constants instead of literals to refer to terminology in RM.</p> <p><b>CR-000220:</b> Tighten semantics of HISTORY.<i>period</i> and EVENT.<i>time</i>.</p> <p><b>CR-000144:</b> Add new Ratio type: DV_PROPORTION. Add Real.<i>floor</i>.</p> <p><b>CR-000221:</b> Add normal status to DV_ORDERED. Add “normal statuses” code set.</p> <p><b>CR-000228:</b> Add minor deviations from ISO 8601 to assumed date/time types.</p> <p><b>CR-000229:</b> Minor date/time corrections. Allow 2-digit time-zones.</p> <p><b>CR-000236:</b> Change use of Character to Octet in DV_MULTIMEDIA.</p> <p><b>CR-000239:</b> Add common parent type of OBJECT_VERSION_ID and HIER_OBJECT_ID.</p> <p><b>CR-000243:</b> Add <i>template_id</i> to ARCHETYPED class</p> <p><b>CR-000246:</b> Correct <i>openEHR</i> terminology rubrics.</p>	<p>T Beale</p> <p>Y S Lim</p> <p>S Heard G Grieve D Lloyd S Heard, H Frankel Y S Lim</p> <p>A Patterson G Grieve H Frankel S Heard</p> <p>R Chen</p> <p>A Patterson</p> <p>S Heard</p> <p>H Frankel T Beale H Frankel</p> <p>H Frankel</p> <p>G Grieve</p> <p>H Frankel</p> <p>T Beale B Verhees M Forss</p>	08 Apr 2007
RELEASE 1.0			
1.5	<p><b>CR-000162.</b> Allow party identifiers when no demographic data. Relax invariant on PARTY_REF.</p> <p><b>CR-000184.</b> Separate out terminology from Support IM.</p> <p><b>CR-000188:</b> Add <i>generating_type</i> function to ANY for use in invariants</p> <p><b>CR-000161.</b> Support distributed versioning. Move OBJECT_ID.<i>version</i> to subtypes. Add OBJECT_VERSION_ID, VERSION_TREE_ID and LOCATABLE_REF types.</p>	<p>S Heard H Frankel T Beale T Beale</p> <p>T Beale H Frankel</p>	06 Feb 2006

Issue	Details	Raiser	Completed
<b>RELEASE 0.96</b>			
1.3	<b>CR-000135:</b> Minor corrections to rm.support.terminology package. <b>CR-000145:</b> Add class for access to external environment. <b>CR-000137:</b> Add definitions class to support.definition package.	D Lloyd D Lloyd D Lloyd	25 Jun 2005
<b>RELEASE 0.95</b>			
1.2.1	<b>CR-000129.</b> Fix errors in UML & specs of Identification package. Adjust invariants & postcondition of OBJECT_ID, HIER_OBJECT_ID, ARCHETYPE_ID and TERMINOLOGY_ID. Improve text to do with assumed abstract types Any and Ordered_numeric.	D Lloyd	25 Feb 2005
1.2	<b>CR-000128.</b> Update Support assumed types to ISO 11404:2003. <b>CR-000107.</b> Add support for exclusion and inclusion of Interval limits. <b>CR-000116.</b> Add PARTICIPATION.function vocabulary and invariant. <b>CR-000122.</b> Fix UML in Terminology_access classes in Support model. <b>CR-000118.</b> Make package names lower case. <b>CR-000111.</b> Move Identification Package to Support. <b>CR-000064.</b> Re-evaluate COMPOSITION.is_persistent attribute. Add "composition category" vocabulary. Re-ordered vocabularies alphabetically.	T Beale A Goodchild  T Beale  D Lloyd  T Beale DSTC D Kalra	10 Feb 2005
<b>RELEASE 0.9</b>			
1.1	<b>CR-000047.</b> Improve handling of codes for structural attributes. Populated Terminology and code_set codes.	S Heard	11 Mar 2004
1.0	<b>CR-000091.</b> Correct anomalies in use of CODE_PHRASE and DV_CODED_TEXT. Add simple terminology service interface. <b>CR-000095.</b> Remove <i>property</i> attribute from Quantity package. Add simple measurement interface. <b>Formally validated using ISE Eiffel 5.4.</b>	T Beale  DSTC, S Heard	09 Mar 2004
0.9.9	<b>CR-000063.</b> ATTESTATION should have a status attribute.	D Kalra	13 Feb 2004
0.9.8	<b>CR-000068.</b> Correct errors in INTERVAL class.	T Beale	20 Dec 2003
0.9.7	<b>CR-000032.</b> Basic numeric type assumptions need to be stated <b>CR-000041.</b> Visually differentiate primitive types in openEHR documents. <b>CR-000043.</b> Move External package to Common RM and rename to Identification (incorporates CR-000036 - Add HIER_OBJECT_ID class, make OBJECT_ID class abstract.)	DSTC, D Lloyd, T Beale	09 Oct 2003
0.9.6	<b>CR-000013.</b> Rename key classes. Based on CEN ENV13606. <b>CR-000038.</b> Remove <i>archetype_originator</i> from multi-axial archetype id. <b>CR-000039.</b> Change archetype_id section separator from ':' to '- '.	T Beale	18 Sep 2003
0.9.5	<b>CR-000036.</b> Add HIER_OBJECT_ID class, make OBJECT_ID class abstract.	T Beale	16 Aug 2003
0.9.4	<b>CR-000022.</b> Code TERM_MAPPING.purpose.	G Grieve	20 Jun 2003

Issue	Details	Raiser	Completed
0.9.3	<b>CR-000007.</b> Added forgotten terminologies for Subject_relationships and Provider_functions.	T Beale	11 Apr 2003
0.9.2	Detailed review by Ocean, DSTC, Grahame Grieve. Updated valid characters in OBJECT_ID.namespace.	G Grieve	25 Mar 2003
0.9.1	Added specification for BOOLEAN type. Corrected minor error in ISO 639 standard strings - now conformant to TERMINOLOGY_ID. OBJECT_ID.version_id now optional. Improved document structure.	T Beale	18 Mar 2003
0.9	Initial Writing. Taken from Data types and Common Reference Models. <b>Formally validated using ISE Eiffel 5.2.</b>	T Beale	25 Feb 2003

### Acknowledgements

The work reported in this paper has been funded in by a number of organisations, including The University College, London and Ocean Informatics, Australia.

## Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>8</b>
1.1	Purpose .....	8
1.2	Related Documents .....	8
1.3	Status .....	8
1.4	Peer review .....	8
1.5	Conformance .....	8
<b>2</b>	<b>Support Package .....</b>	<b>9</b>
2.1	Overview .....	9
2.2	Class Definitions .....	9
2.2.1	EXTERNAL_ENVIRONMENT_ACCESS Class .....	9
<b>3</b>	<b>Assumed Types .....</b>	<b>11</b>
3.1	Overview .....	11
3.2	Inbuilt Primitive Types .....	12
3.2.1	Any Type .....	13
3.2.2	Ordered Type .....	13
3.2.3	Numeric Type .....	13
3.2.4	Ordered_numeric Type .....	14
3.2.5	Boolean Type .....	14
3.2.6	Real Type .....	16
3.3	Assumed Library Types .....	16
3.3.1	String Type .....	17
3.3.1.1	UNICODE .....	17
3.3.2	Aggregate Type .....	17
3.3.3	List Type .....	18
3.3.4	Set Type .....	18
3.3.5	Array Type .....	18
3.3.6	Hash Type .....	19
3.3.7	Interval Type .....	19
3.4	Date/Time Types .....	20
3.4.1	TIME_DEFINITIONS Class .....	21
3.4.2	ISO8601_DATE Class .....	23
3.4.3	ISO8601_TIME Class .....	24
3.4.4	ISO8601_DATE_TIME Class .....	26
3.4.5	ISO8601_TIMEZONE Class .....	28
3.4.6	ISO8601_DURATION Class .....	29
<b>4</b>	<b>Identification Package .....</b>	<b>31</b>
4.1	Overview .....	31
4.1.1	Requirements .....	31
4.2	Design .....	33
4.2.1	Primitive Identifiers .....	33
4.2.2	Composite Identifiers .....	34
4.2.3	References .....	34
4.3	Class Descriptions .....	35
4.3.1	UID Class .....	35
4.3.2	ISO_OID Class .....	35
4.3.3	UUID Class .....	35

4.3.4	INTERNET_ID Class .....	36
4.3.4.1	Syntax .....	36
4.3.5	OBJECT_ID Class .....	36
4.3.6	UID_BASED_ID Class .....	37
4.3.6.1	Identifier Syntax .....	37
4.3.7	HIER_OBJECT_ID Class.....	37
4.3.8	OBJECT_VERSION_ID Class.....	38
4.3.8.1	Identifier Syntax .....	38
4.3.9	VERSION_TREE_ID Class .....	39
4.3.9.1	Syntax .....	39
4.3.10	ARCHETYPE_ID Class .....	40
4.3.10.1	Archetype ID Syntax .....	41
4.3.11	TEMPLATE_ID Class .....	42
4.3.12	TERMINOLOGY_ID Class .....	42
4.3.12.1	Identifier Syntax .....	42
4.3.13	GENERIC_ID Class .....	43
4.3.14	OBJECT_REF Class.....	43
4.3.15	ACCESS_GROUP_REF Class.....	44
4.3.16	PARTY_REF Class .....	44
4.3.17	LOCATABLE_REF Class .....	45
<b>5</b>	<b>Terminology Package.....</b>	<b>46</b>
5.1	Overview .....	46
5.2	Service Interface .....	46
5.2.1	Code Sets .....	46
5.2.2	Terminologies .....	46
5.2.3	Terms and Codes in the openEHR Reference Model .....	46
5.3	Identifiers .....	48
5.3.1	Code Set Identifiers .....	48
5.3.2	Terminology Identifiers .....	48
5.4	Class Definitions.....	53
5.4.1	TERMINOLOGY_SERVICE Class .....	53
5.4.2	TERMINOLOGY_ACCESS Class .....	54
5.4.3	CODE_SET_ACCESS Class.....	55
5.4.4	OPENEHR_TERMINOLOGY_GROUP_IDENTIFIERS Class .....	55
5.4.5	OPENEHR_CODE_SET_IDENTIFIERS Class .....	56
<b>6</b>	<b>Measurement Package .....</b>	<b>58</b>
6.1	Overview .....	58
6.2	Service Interface .....	58
6.2.1	Class Definitions.....	58
6.2.1.1	MEASUREMENT_SERVICE Class .....	58
<b>7</b>	<b>Definition Package .....</b>	<b>60</b>
7.1	Overview .....	60
7.2	Class Definitions.....	60
7.2.1	OPENEHR_DEFINITIONS Class .....	60
7.2.2	BASIC_DEFINITIONS Class .....	60
<b>A</b>	<b>References .....</b>	<b>61</b>
A.1	General.....	61

# 1 Introduction

---

## 1.1 Purpose

This document describes the *openEHR* Support Reference Model, whose semantics are used by all *openEHR* Reference Models. The intended audience includes:

- Standards bodies producing health informatics standards;
- Software development organisations developing EHR systems;
- Academic groups studying the EHR;
- The open source healthcare community.

## 1.2 Related Documents

Prerequisite documents for reading this document include:

- The *openEHR* Architecture Overview
- The *openEHR* Modelling Guide

## 1.3 Status

This document is under development, and is published as a proposal for input to standards processes and implementation works.

This document is available at [http://svn.openehr.org/specification/TAGS/Release-1.0.1/publishing/architecture/rm/support\\_im.pdf](http://svn.openehr.org/specification/TAGS/Release-1.0.1/publishing/architecture/rm/support_im.pdf).

The latest version of this document can be found at [http://svn.openehr.org/specification/TRUNK/publishing/architecture/rm/support\\_im.pdf](http://svn.openehr.org/specification/TRUNK/publishing/architecture/rm/support_im.pdf).

**Blue text** indicates sections under active development.

## 1.4 Peer review

Areas where more analysis or explanation is required are indicated with “to be continued” paragraphs like the following:

**To Be Continued:**      more work required

Reviewers are encouraged to comment on and/or advise on these paragraphs as well as the main content. Please send requests for information to [info@openEHR.org](mailto:info@openEHR.org). Feedback should preferably be provided on the mailing list [openehr-technical@openehr.org](mailto:openehr-technical@openehr.org), or by private email.

## 1.5 Conformance

Conformance of a data or software artifact to an *openEHR* Reference Model specification is determined by a formal test of that artifact against the relevant *openEHR* Implementation Technology Specification(s) (ITSs), such as an IDL interface or an XML-schema. Since ITSs are formal, automated derivations from the Reference Model, ITS conformance indicates RM conformance.



## 2 Support Package

### 2.1 Overview

The Support Reference Model comprises types used throughout the *openEHR* models, including assumed primitive types defined outside of *openEHR*. The package structure is illustrated in FIGURE 1. The *assumed\_types* ‘pseudo-package’ stands for types assumed by the *openEHR* specifications to exist in an implementation technology, such as a programming language, schema language or database environment. The four Support packages define the semantics respectively for constants, terminology access, access to externally defined scientific units and conversion information. The class `EXTERNAL_ENVIRONMENT_ACCESS` is a mixin class providing access to the service interface classes.




FIGURE 1 `rm.support` and `assumed_types` Packages

### 2.2 Class Definitions

#### 2.2.1 `EXTERNAL_ENVIRONMENT_ACCESS` Class

CLASS	<i><b>EXTERNAL_ENVIRONMENT_ACCESS (abstract)</b></i>	
Purpose	A mixin class providing access to services in the external environment.	
Functions	Signature	Meaning
	<b>eea_terminology_svc:</b> <code>TERMINOLOGY_SERVICE</code>	Return an interface to the terminology service
	<b>eea_measurement_svc:</b> <code>MEASUREMENT_SERVICE</code>	Return an interface to the measurement service

CLASS	<i><b>EXTERNAL_ENVIRONMENT_ACCESS (abstract)</b></i>
Invariants	<i>Terminology_service_exists</i> : eea_terminology_svc /= Void <i>Measurement_service_exists</i> : eea_measurement_svc /= Void

## 3 Assumed Types

### 3.1 Overview

This section describes types assumed by all *openEHR* models. The set of types chosen here is based on a common set from various published sources, including:

- ISO 11404 (2003 revision) general purpose data types;
- ISO 8601 (2004) date/time specification;
- Well-known interoperability formalisms, including OMG IDL, W3C XML-schema;
- Well-known object-oriented programming languages, including Java, C#, C++ and Eiffel.

The intention in *openEHR* is twofold. Firstly, to ensure that *openEHR* software based on the models integrates as easily as possible with existing implementation technologies, and secondly, to make the minimum possible assumptions about types found in implementation formalisms, while making sufficient assumptions to both enable *openEHR* models to be conveniently specified. The ISO 11404 (2003) standard contains basic semantics of “general purpose data types” (GPDs) for information technology, and is used here as a normative basis for describing assumptions about types. The operations and properties described here are compatible with those used in ISO 11404, but not always the same, as 11404 does not use object-oriented functions. For example, the notional function `has(x: T)` (test for presence of a value in a set) defined on the type `Set<T>` below is not defined on the ISO 11404 Set type; instead, the function `IsIn(x: T; s: Set<T>)` is defined. However, in object-oriented formalisms, the function `IsIn` defined on a Set type would usually mean ‘subset of’. In the interests of clarity for developers, an object-oriented style of functions and properties has been used here.

ISO8601:2004 is used as the definitional basis for assumed date/time types, since it is commonly used around the world, and is also the basis for the date/time types in W3C XML-schema. See section 3.4 on page 20 below for details of dates and times.

Two groups of assumed types are identified: primitive types, which are those built in to a formalism’s type system, and library types, which are assumed to be available in a (class) library defined in the formalism. Thus, the type `Boolean` is always assumed to exist in a formalism, while the type `Array<T>` is assumed to be available in a library. For practical purposes, these two categories do not matter that much - whether `String` is really a library class (the usual case) or an inbuilt type doesn’t make much difference to the programmer. They are shown separately here mainly as an explanatory convenience.

The assumptions that *openEHR* makes about existing types are documented below in terms of interface definitions. Each of these definitions contains *only the assumptions required for the given type to be used in the openEHR Reference Model* - **it is not by any means a complete interface definition**. The name and semantics of any function used here for an assumed type **might not be identical** to those found in some implementation technologies. Any mapping required should be stated in the relevant implementation technology specification (ITS). To give a concrete example, where the assumed `Set<T>` type defined below has an operation `has(item: T): Boolean` which is used throughout the *openEHR* specifications, Java has the method `contains()` on its `Set<T>` class. In a Java implementation, the `contains()` method should then be used throughout the *openEHR* classes as expressed in Java, in place of the `has()` method.

## 3.2 Inbuilt Primitive Types

The following types constitute the minimum set of primitive types assumed by *openEHR* of an implementation formalism.

Type name in <i>openEHR</i>	Description	ISO 11404 Type
Octet	represents a type whose value is an 8-bit value.	Octet
Character	represents a type whose value is a member of an 8-bit character-set (ISO: “repertoire”).	Character
Boolean	represents logical True/False values; usually physically represented as an integer, but need not be	Boolean
Integer	represents 32-bit integers	Integer
Real	represents 32-bit real numbers in any interoperable representation, including single-width IEEE floating point	Real
Double	type which represents 64-bit real numbers, in any interoperable representation including double-precision IEEE floating point.	Real

FIGURE 2 illustrates the built-in primitive types. Simple inheritance relationships are shown which facilitate the type descriptions below. A class “Any” is used to stand for the usual top-level class in all object-oriented type systems, typically called something like “Any” or “Object”. Inheritance from or substitutability for an *Any* class is *not* assumed in *openEHR* (hence the dotted lines in the UML). It is used here to enable basic operations like “=” to be described once for the type *Any*, rather than in every subtype. The type *Ordered\_numeric* is on the other hand assumed for purposes of specification in the *openEHR* *data\_types.quantity* package, and is intended to be mapped to an equivalent type in a real type system (e.g. in Java, *java.lang.Number*). Here it is assumed that the operations defined on *Ordered\_numeric* are available on the types *Integer*, *Real* and *Double* in implementation type systems, where relevant. Data-oriented implementation type systems such as XML-schema do not have such operations.




FIGURE 2 Primitive Types Assumed by *openEHR*

### 3.2.1 Any Type

INTERFACE	<i>Any (abstract)</i>	
<b>Description</b>	Abstract supertype. Usually maps to a type like “Any” or “Object” in an object system. Defined here to provide the value and reference equality semantics.	
<b>Abstract</b>	<b>Signature</b>	<b>Meaning</b>
	<b>is_equal</b> (other: Any): Boolean	Value equality
<b>Functions</b>	<b>Signature</b>	<b>Meaning</b>
	<b>infix ‘=’</b> (other: Any): Boolean	Reference equality
	<b>instance_of</b> (a_type: String)	Dynamic type of object as a String. Used for type name matching.
<b>Invariants</b>		

### 3.2.2 Ordered Type

INTERFACE	<i>Ordered (abstract)</i>	
<b>Purpose</b>	Abstract notional parent class of ordered, types i.e. types on which the ‘<’ operator is defined.	
<b>Abstract</b>	<b>Signature</b>	<b>Meaning</b>
	<b>infix ‘&lt;’</b> (other: <i>like</i> Current): Boolean	Arithmetic comparison. In conjunction with ‘=’, enables the definition of the operators ‘>’, ‘>=’, ‘<=’, ‘<’. In real type systems, this operator might be defined on another class for comparability.
<b>Invariants</b>		

### 3.2.3 Numeric Type

INTERFACE	<i>Numeric (abstract)</i>	
<b>Purpose</b>	Abstract notional parent class of numeric types, which are types which have various arithmetic and comparison operators defined.	
<b>Abstract</b>	<b>Signature</b>	<b>Meaning</b>

INTERFACE	<i>Numeric (abstract)</i>	
	<b>infix "*" (other: <i>like</i> Current): <i>like</i> Current</b> <b>require</b> <i>other_exists</i> : other != void <b>ensure</b> <i>result_exists</i> : Result != void	Product by 'other'. Actual type of result depends on arithmetic balancing rules.
	<b>infix "+" (other: <i>like</i> Current): <i>like</i> Current</b> <b>require</b> <i>other_exists</i> : other != void <b>ensure</b> <i>result_exists</i> : Result != void <i>commutative</i> : equal (Result, other + Current)	Sum with 'other' (commutative). Actual type of result depends on arithmetic balancing rules.
	<b>infix "-" (other: <i>like</i> Current): <i>like</i> Current</b> <b>require</b> <i>other_exists</i> : other != void <b>ensure</b> <i>result_exists</i> : Result != void	Result of subtracting 'other'. Actual type of result depends on arithmetic balancing rules.
<b>Invariants</b>		

### 3.2.4 Ordered\_numeric Type

INTERFACE	<i>Ordered_numeric (abstract)</i>	
<b>Purpose</b>	Abstract notional parent class of ordered, numeric types, which are types with '<' and arithmetic operators defined.	
<b>Inherit</b>	ORDERED, NUMERIC	
<b>Function</b>	<b>Signature</b>	<b>Meaning</b>
<b>Invariants</b>		

### 3.2.5 Boolean Type

INTERFACE	<b>Boolean</b>	
<b>Purpose</b>	Boolean type used for two-valued mathematical logic.	
<b>Function</b>	<b>Signature</b>	<b>Meaning</b>

INTERFACE	Boolean	
	<b>infix "and"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>de_morgan</i> : Result = <b>not (not Current or not other)</b> <i>commutative</i> : Result = (other <b>and</b> Current)	Logical conjunction
	<b>infix "and then"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>de_morgan</i> : Result = <b>not (not Current or else not other)</b>	Boolean semi-strict conjunction with <i>other</i>
	<b>infix "or"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>de_morgan</i> : Result = <b>not (not Current and not other)</b> <i>commutative</i> : Result = (other <b>or</b> Current) <i>consistent_with_semi_strict</i> : Result <b>implies</b> (Current <b>or else</b> other)	Boolean disjunction with <i>other</i>
	<b>infix "or else"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>de_morgan</i> : Result = <b>not (not Current and then not other)</b>	Boolean semi-strict disjunction with <i>'other'</i>
	<b>infix "xor"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>definition</i> : Result = ((Current <b>or</b> other) <b>and not</b> (Current <b>and</b> other))	Boolean exclusive or with <i>'other'</i>

INTERFACE	Boolean	
	<b>infix "implies"</b> (other: Boolean): Boolean <i>require</i> <i>other_exists</i> : other != void <i>ensure</i> <i>definition</i> : Result = ( <b>not</b> Current <b>or else</b> other)	Boolean implication of 'other' (semi-strict)
<b>Invariants</b>	<i>involution_negation</i> : is_equal ( <b>not</b> ( <b>not</b> Current)) <i>non_contradiction</i> : <b>not</b> (Current <b>and</b> ( <b>not</b> Current)) <i>completeness</i> : Current <b>or else</b> ( <b>not</b> Current)	

### 3.2.6 Real Type

INTERFACE	Real	
<b>Purpose</b>	Type used to represent decimal numbers. Typically corresponds to a single-precision floating point value in most languages.	
Function	Signature	Meaning
	<b>floor</b> : Integer	Return the greatest integer no greater than the value of this object.
<b>Invariants</b>		

## 3.3 Assumed Library Types

The types described in this section are also assumed to be fairly standard in implementation technologies by *openEHR*, but usually come from type libraries rather than being built into the type system of implementation formalisms.

Type name in <i>openEHR</i>	Description	ISO 11404: 2003 Type
String	represents unicode-enabled strings	Character-String/Sequence
Array<T>	physical container of items indexed by number	Array
List<T>	container of items, implied order, non-unique membership	Sequence
Set<T>	container of items, no order, unique membership	Set
Hash<T, U:Comparable>	a table of values of any type T, keyed by values of any basic comparable type U, typically String or Integer, but may be more complex types, e.g. a coded term type.	Table
Interval<T>	Intervals with open or closed upper and lower bounds.	-



FIGURE 3 illustrates the assumed library types. As with the assumed primitive types, inheritance and abstract classes are used for convenience of the definitions below, but are not formally assumed in *openEHR*.




FIGURE 3 Library Types Assumed by *openEHR*

### 3.3.1 String Type

INTERFACE	String	
Description	Strings of characters, as used to represent textual data in any natural or formal language.	
Functions	Signature	Meaning
	<b>infix</b> '+' (other: String): String	Concatenation operator - causes 'other' to be appended to this string
	<b>is_empty</b> : Boolean	True if string is empty, i.e. equal to "".
	<b>is_integer</b> : Boolean	True if string can be parsed as an integer.
	<b>as_integer</b> : Integer <i>require</i> is_integer	Return the integer corresponding to the integer value represented in this string.
Invariants		

#### 3.3.1.1 UNICODE

It is assumed in the *openEHR* specifications that Unicode is supported by the type *String*. Unicode is needed for all Asian, Arabic and other script languages, for both data values (particularly plain text and coded text) and for many predefined string attributes of the classes in the *openEHR* Reference Model. It encompasses all existing character sets. In *openEHR*, UTF-8 encoding is assumed.

### 3.3.2 Aggregate Type

INTERFACE	Aggregate <T> (abstract)
Description	Abstract parent of the aggregate types <i>List</i> <T>, <i>Set</i> <T>, <i>Array</i> <T> and <i>Hash</i> <T, K>.

INTERFACE	<i>Aggregate &lt;T&gt; (abstract)</i>	
Functions	Signature	Meaning
	<b>has</b> (v: T): Boolean	Test for membership of a value
	<b>count</b> : Integer	Number of items in container
	<b>is_empty</b> : Boolean	True if container is empty.
Invariants		

### 3.3.3 List Type

INTERFACE	<i>List &lt;T&gt; (abstract)</i>	
Description	Ordered container that may contain duplicates.	
Functions	Signature	Meaning
	<b>first</b> : T	Return first element.
	<b>last</b> : T	Return last element.
Invariants	<i>First_validity</i> : not is_empty implies first != Void <i>Last_validity</i> : not is_empty implies last != Void	

### 3.3.4 Set Type

INTERFACE	<i>Set &lt;T&gt; (abstract)</i>	
Description	Unordered container that may not contain duplicates.	
Functions	Signature	Meaning
Invariants		

### 3.3.5 Array Type

INTERFACE	<i>Array &lt;T&gt; (abstract)</i>	
Description	Container whose storage is assumed to be contiguous.	
Functions	Signature	Meaning
Invariants		

### 3.3.6 Hash Type

INTERFACE	Hash <T, U: Comparable>	
<b>Description</b>	Type representing a keyed table of values. T is the value type, and U the type of the keys.	
<b>Functions</b>	<b>Signature</b>	<b>Meaning</b>
	<b>has_key</b> (a_key: U): Boolean	Test for membership of a key
	<b>item</b> (a_key: U): T	Return item for key 'a_key'. Equivalent to ISO 11404 <i>fetch</i> operation.
<b>Invariants</b>		

### 3.3.7 Interval Type

INTERFACE	Interval <T:Ordered>	
<b>Purpose</b>	Interval of ordered items.	
<b>Attributes</b>	<b>Signature</b>	<b>Meaning</b>
	<b>lower</b> : T	lower bound
	<b>upper</b> : T	upper bound
	<b>lower_unbounded</b> : Boolean	lower boundary open (i.e. = -infinity)
	<b>upper_unbounded</b> : Boolean	upper boundary open (i.e. = +infinity)
	<b>lower_included</b> : Boolean	lower boundary value included in range if not <i>lower_unbounded</i>
	<b>upper_included</b> : Boolean	upper boundary value included in range if not <i>upper_unbounded</i>
<b>Functions</b>	<b>Signature</b>	<b>Meaning</b>
	<b>has</b> (e:T): Boolean	True if (lower_unbounded <b>or</b> ((lower_included <b>and</b> v >= lower) <b>or</b> v > lower)) <b>and</b> (upper_unbounded <b>or</b> ((upper_included <b>and</b> v <= upper <b>or</b> v < upper)))

INTERFACE	Interval <T:Ordered>
Invariants	<p><i>Lower_included_valid</i>: lower_unbounded <b>implies not</b> lower_included</p> <p><i>Upper_included_valid</i>: upper_unbounded <b>implies not</b> upper_included</p> <p><i>Limits_consistent</i>: (<b>not</b> upper_unbounded <b>and not</b> lower_unbounded) <b>implies</b> lower ≤ upper</p> <p><i>Limits_comparable</i>: (<b>not</b> upper_unbounded <b>and not</b> lower_unbounded) <b>implies</b> lower.strictly_comparable_to(upper)</p>

### 3.4 Date/Time Types

Although the ISO 11404 (2003) standard defines a date-and-time type generator (section 8.1.6), and a `timeinterval` type (section 10.1.6), a more widely used specification of date/times is given by ISO 8601:2004, which is used as the normative basis for both string literal representation and properties used within *openEHR*. The types are shown in FIGURE 4.




FIGURE 4 Date/Time types assumed by *openEHR*

ISO 8601 semantics not used in *openEHR* include:

- “expanded” dates, which have year numbers of greater than 4 digits, and may be negative; in *openEHR*, only 4-digit year numbers are assumed;
- the YYYY-WW-DD method of expressing dates (since this is imprecise and difficult to compute with due to variable week starting dates, and not required in health);
- partial date/times with fractional minutes or hours, e.g. hh,hhh or mm,mm; in *openEHR*, only fractional seconds are supported;
- the interval syntax. Intervals of date/times are supported in *openEHR*, but their syntax form is defined by ADL, and is standardised across all comparable types, not just dates and times.

**Deviations from the published standard** include the following:

- durations are supposed to take the form of `PnnW` or `PnnYnnMnnDTnnHnnMnnS`, but in *openEHR*, the W (week) designator can be used in combination with the other designators, since it is very common to state durations of pregnancy as some combination of weeks and days.
- partial variants of `ISO8601_DATE_TIME` can include missing hours, days and months, whereas ISO 8601:2004 (section 4.3.3 c) only allows missing seconds and minutes. The reasons for this deviation are:

- the same deviation is used in HL7v2 and HL7v3 TS (timestamp) type, i.e. there are data in existing clinical systems matching this specification;
- in a typed object model, this deviation is more sensible anyway; the ISO 8601 rule is most likely a limitation of the purely syntactic means of expression. In real systems where a timestamp/date-time is specified in a screen form, it makes sense to allow it to be as partial as possible, rather than artificially restricted to only missing seconds and minutes.
- the time 24:00:00 (or 240000) is not allowed anywhere, whereas in ISO8601:2004 it appears to be legal at least for times. This deviation is also appears to be used in HL7v2 and HL7v3 (where midnight is defined as the time 00:00:00), and is preferable to the documented standard, since a date/time with time of 24:00:00 is really the next day, i.e. the date part is then incorrect.

The following class definitions provide an object-oriented expression of the semantics of the subset of ISO 8601:2004 used by *openEHR*.

See <http://www.cl.cam.ac.uk/~mgk25/iso-time.html> and the official ISO standard for ISO 8601 details. Note that in the date, time and date\_time formats shown below, 'Z' and 'T' are literals. In the duration class shown below, 'P', 'Y', 'M', 'W', 'D', 'H', 'S' and 'T' are literals.

### 3.4.1 TIME\_DEFINITIONS Class

INTERFACE	TIME_DEFINITIONS	
<b>Purpose</b>	Definitions for date/time classes. Note that the timezone limits are set by where the international dateline is. Thus, time in New Zealand is quoted using +12:00, not -12:00.	
<b>Constants</b>	<b>Signature</b>	<b>Meaning</b>
1..1	<b>Seconds_in_minute:</b> Integer = 60	
1..1	<b>Minutes_in_hour:</b> Integer = 60	
1..1	<b>Hours_in_day:</b> Integer = 24	
1..1	<b>Nominal_days_in_month:</b> Real = 30.42	Used for conversions of durations containing months to days and / or seconds.
1..1	<b>Max_days_in_month:</b> Integer = 31	Used for validity checking.
1..1	<b>Days_in_year:</b> Integer = 365	
1..1	<b>Days_in_leap_year:</b> Integer = 366	
1..1	<b>Max_days_in_year:</b> Integer = Days_in_leap_year	Used for validity checking.

INTERFACE	TIME_DEFINITIONS	
1..1	<b>Nominal_days_in_year:</b> Real = 365.24	Used for conversions of durations containing years to days and / or seconds.
1..1	<b>Days_in_week:</b> Integer = 7	
1..1	<b>Months_in_year:</b> Integer = 12	
1..1	<b>Min_timezone_hour:</b> Integer <i>ensure</i> Result = 12	Minimum hour value of a timezone (note that the -ve sign is supplied in the ISO8601_TIMEZONE class).
1..1	<b>Max_timezone_hour:</b> Integer <i>ensure</i> Result = 13	Maximum hour value of a timezone.
Functions	Signature	Meaning
	<b>valid_year</b> (y: Integer): Boolean <i>ensure</i> Result = y >= 0	True if y >= 0
	<b>valid_month</b> (m: Integer): Boolean <i>ensure</i> Result = m >= 1 and m <= Months_in_year	True if m >= 1 and m <= Months_in_year
	<b>valid_day</b> (y, m, d: Integer): Boolean <i>ensure</i> Result = d >= 1 and d <= days_in_month(m, y)	True if d >= 1 and d <= days_in_month(m, y)
	<b>valid_hour</b> (h, m, s: Integer): Boolean <i>ensure</i> Result = (h >= 0 and h < Hours_in_day) or (h = Hours_in_day and m = 0 and s = 0)	True if (h >= 0 and h < Hours_in_day) or (h = Hours_in_day and m = 0 and s = 0)
	<b>valid_minute</b> (m: Integer): Boolean <i>ensure</i> Result = m >= 0 and m < Minutes_in_hour	True if m >= 0 and m < Minutes_in_hour

INTERFACE	TIME_DEFINITIONS	
	<b>valid_second</b> (s: Integer): Boolean <i>ensure</i> Result = $s \geq 0$ and $s < \text{Seconds\_in\_minute}$	True if $s \geq 0$ and $s < \text{Seconds\_in\_minute}$
	<b>valid_fractional_second</b> (fs: Double): Boolean <i>ensure</i> Result = $fs \geq 0.0$ and $fs < 1.0$	True if $fs \geq 0.0$ and $fs < 1.0$
Invariants		

### 3.4.2 ISO8601\_DATE Class

INTERFACE	ISO8601_DATE	
<b>Purpose</b>	Represents an absolute point in time, as measured on the Gregorian calendar, and specified only to the day.	
<b>Inherit</b>	ORDERED, TIME_DEFINITIONS	
Function	Signature	Meaning
	<b>as_string</b> : String	ISO8601 string for date, in format <b>YYYYMMDD</b> or <b>YYYY-MM-DD</b> , or a partial invariant. See <i>valid_iso8601_date</i> for validity.
	<b>year</b> : Integer	Year.
	<b>month</b> : Integer <i>require</i> <b>not</b> month_unknown	Month in year.
	<b>day</b> : Integer <i>require</i> <b>not</b> day_unknown	Day in month.
	<b>month_unknown</b> : Boolean	Indicates whether month in year is unknown. If so, the date is of the form “YYYY”.
	<b>day_unknown</b> : Boolean	Indicates whether day in month is unknown. If so, and month is known, the date is of the form “YYYY-MM” or “YYYYMM”.
	<b>is_partial</b> : Boolean	True if this date is partial, i.e. if day or more is missing.

INTERFACE	ISO8601_DATE	
	<b>is_extended</b> : Boolean	True if this date uses '-' separators.
	<b>infix '&lt;'</b> (other: <i>like</i> Current): Boolean	Arithmetic comparison with other date. True if this date is closer to the origin than <i>other</i> .
	<b>valid_iso8601_date</b> (s: String): Boolean	String is a valid ISO 8601 date, i.e. takes the complete form: <ul style="list-style-type: none"> <li>• <b>YYYYMMDD</b></li> </ul> or the extended form: <ul style="list-style-type: none"> <li>• <b>YYYY-MM-DD</b></li> </ul> or one of the partial forms: <ul style="list-style-type: none"> <li>• <b>YYYYMM</b></li> <li>• <b>YYYY</b></li> </ul> or the equivalent extended form: <ul style="list-style-type: none"> <li>• <b>YYYY-MM</b></li> </ul> Where: <ul style="list-style-type: none"> <li>• <b>YYYY</b> is the string form of any positive number in the range "0000" - "9999" (zero-filled to four digits)</li> <li>• <b>MM</b> is "01" - "12" (zero-filled to two digits)</li> <li>• <b>DD</b> is "01" - "31" (zero-filled to two digits)</li> </ul> The combinations of YYYY, MM, DD numbers must be correct with respect to the Gregorian calendar.
<b>Invariants</b>	<i>Year_valid</i> : valid_year(year) <i>Month_valid</i> : not month_unknown <b>implies</b> valid_month(month) <i>Day_valid</i> : not day_unknown <b>implies</b> valid_day(year, month, day) <i>Partial_validity</i> : month_unknown <b>implies</b> day_unknown	

### 3.4.3 ISO8601\_TIME Class

INTERFACE	ISO8601_TIME	
<b>Purpose</b>	Represents an absolute point in time from an origin usually interpreted as meaning the start of the current day, specified to the second.  A small deviation to the ISO 8601:2004 standard in this class is that the time 24:00:00 is not allowed, for consistency with ISO8601_DATE_TIME.	
<b>Inherit</b>	ORDERED, TIME_DEFINITIONS	
<b>Function</b>	<b>Signature</b>	<b>Meaning</b>



INTERFACE	ISO8601_TIME	
	<b>as_string</b> : String	ISO8601 string for time, i.e. in form: <b>hhmmss</b> [,sss][Z ±hh[mm]] or the extended form: <b>hh:mm:ss</b> [,sss][Z ±hh[mm]], or a partial invariant. See <i>valid_iso8601_time</i> for validity.
	<b>hour</b> : Integer	Hour in day, in 24-hour time.
	<b>minute</b> : Integer <i>require</i> <b>not</b> minute_unknown	Minute in hour.
	<b>second</b> : Integer <i>require</i> <b>not</b> second_unknown	Second in minute.
	<b>fractional_second</b> : Double <i>require</i> <b>not</b> second_unknown	Fractional seconds.
	<b>has_fractional_second</b> : Boolean	True if the <i>fractional_second</i> part is significant (i.e. even if = 0.0).
	<b>timezone</b> : ISO8601_TIMEZONE	Time zone; may be Void.
	<b>minute_unknown</b> : Boolean	Indicates whether minute is unknown. If so, the time is of the form “hh”.
	<b>second_unknown</b> : Boolean	Indicates whether second is unknown. If so and month is known, the time is of the form “hh:mm” or “hhmm”.
	<b>is_partial</b> : Boolean	True if this time is partial, i.e. if seconds or more is missing.
	<b>is_extended</b> : Boolean	True if this time uses ‘.’ separators.
	<b>is_decimal_sign_comma</b> : Boolean	True if this time has a decimal part indicated by ‘,’ (comma) rather than ‘.’ (period).
	<b>infix ‘&lt;’</b> (other: <i>like</i> Current): Boolean	Arithmetic comparison with other time. True if this date is closer to previous midnight than <i>other</i> .

INTERFACE	ISO8601_TIME	
	<b>valid_iso8601_time</b> (s: String): Boolean	String is a valid ISO 8601 date, i.e. takes the form: <ul style="list-style-type: none"> <li>• <b>hhmmss[,sss][Z   ±hh[mm]]</b></li> </ul> or the extended form: <ul style="list-style-type: none"> <li>• <b>hh:mm:ss[,sss][Z   ±hh[mm]]</b></li> </ul> or one of the partial forms: <ul style="list-style-type: none"> <li>• <b>hhmm</b> or <b>hh</b></li> </ul> or the extended form: <ul style="list-style-type: none"> <li>• <b>hh:mm</b></li> </ul> with an additional optional timezone indicator of: <ul style="list-style-type: none"> <li>• <b>Z</b> or <b>±hh[mm]</b></li> </ul> Where: <ul style="list-style-type: none"> <li>• <b>hh</b> is “00” - “23” (0-filled to two digits)</li> <li>• <b>mm</b> is “00” - “59” (0-filled to two digits)</li> <li>• <b>ss</b> is “00” - “60” (0-filled to two digits)</li> <li>• <b>sss</b> is any numeric string, representing an optional fractional second</li> <li>• <b>Z</b> is a literal meaning UTC (modern replacement for GMT), i.e. timezone +0000</li> <li>• <b>±hh[mm]</b>, i.e. +hhmm, +hh, -hhmm, -hh indicating the timezone.</li> </ul>
<b>Invariants</b>	<i>Hour_valid</i> : valid_hour(hour, minute, second) <i>Minute_valid</i> : <b>not</b> minute_unknown <b>implies</b> valid_minute(minute) <i>Second_valid</i> : <b>not</b> second_unknown <b>implies</b> valid_second(second) <i>Fractional_second_valid</i> : has_fractional_second <b>implies</b> ( <b>not</b> second_unknown and valid_fractional_second(fractional_second)) <i>Partial_validity</i> : minute_unknown <b>implies</b> second_unknown	

### 3.4.4 ISO8601\_DATE\_TIME Class

INTERFACE	ISO8601_DATE_TIME	
<b>Purpose</b>	Represents an absolute point in time, specified to the second. Note that this class includes 2 deviations from ISO 8601:2004: <ul style="list-style-type: none"> <li>• for partial date/times, any part of the date/time up to the month may be missing, not just seconds and minutes as in the standard;</li> <li>• the time 24:00:00 is not allowed, since it would mean the date was really on the next day.</li> </ul>	
<b>Inherit</b>	ORDERED, TIME_DEFINITIONS	
<b>Function</b>	<b>Signature</b>	<b>Meaning</b>

INTERFACE	ISO8601_DATE_TIME	
	<b>as_string</b> : String <i>ensure</i> valid_iso8601_date_time(Result)	ISO8601 string for date/time, in format <b>YYYYMMDDThhmmss</b> [,sss][Z   ±hh[mm]] or in extended format <b>YYYY-MM-DDThh:mm:ss</b> [,sss][Z   ±hh[mm]] or a partial variant; see <i>valid_iso8601_date_time()</i> below.
	<b>year</b> : Integer	year
	<b>month</b> : Integer <i>require</i> not month_unknown	month in year
	<b>day</b> : Integer <i>require</i> not day_unknown	day in month
	<b>hour</b> : Integer <i>require</i> not hour_unknown	hour in day
	<b>minute</b> : Integer <i>require</i> not minute_unknown	minute in hour
	<b>second</b> : Integer <i>require</i> not second_unknown	second in minute
	<b>fractional_second</b> : Double <i>require</i> has_fractional_second	fractional seconds
	<b>has_fractional_second</b> : Boolean	True if the <i>fractional_second</i> part is significant (i.e. even if = 0.0).
	<b>timezone</b> : ISO8601_TIMEZONE	Timezone; may be Void.
	<b>month_unknown</b> : Boolean	Indicates whether month in year is unknown.
	<b>day_unknown</b> : Boolean	Indicates whether day in month is unknown.
	<b>hour_unknown</b> : Boolean	Indicates whether hour in day is known.
	<b>minute_unknown</b> : Boolean	Indicates whether minute in hour is known.
	<b>second_unknown</b> : Boolean	Indicates whether minute in hour is known.
	<b>is_partial</b> : Boolean	True if this date is partial, i.e. if seconds or more is missing.

INTERFACE	ISO8601_DATE_TIME	
	<b>is_decimal_sign_comma:</b> Boolean	True if this time has a decimal part indicated by ‘,’ (comma) rather than ‘.’ (period).
	<b>infix ‘&lt;’</b> (other: <i>like</i> Current): Boolean	Arithmetic comparison with other date/time. True if this date/time is closer to origin than <i>other</i> .
	<b>is_extended:</b> Boolean	True if this date/time uses ‘-’, ‘.’ separators.
	<b>valid_iso8601_date_time</b> (s: String): Boolean	String is a valid ISO 8601 date-time, i.e. takes the form: <ul style="list-style-type: none"> <li>• <b>YYYYMMDDThhmmss[,sss]</b> [Z   ±hh[mm]]</li> </ul> or the extended form: <ul style="list-style-type: none"> <li>• <b>YYYY-MM-DDThh:mm:ss[,sss]</b> [Z   ±hh[mm]]</li> </ul> or one of the partial forms: <ul style="list-style-type: none"> <li>• <b>YYYYMMDDThhmm</b></li> <li>• <b>YYYYMMDDThh</b></li> </ul> or the equivalent extended forms: <ul style="list-style-type: none"> <li>• <b>YYYY-MM-DDThh:mm</b></li> <li>• <b>YYYY-MM-DDThh</b></li> </ul> (meanings as in DV_DATE, DV_TIME) and the values in each field are valid.
<b>Invariants</b>	<p><b>Year_valid:</b> valid_year(year)  <b>Month_valid:</b> valid_month(month)  <b>Day_valid:</b> valid_day(year, month, day)</p> <p><b>Hour_valid:</b> valid_hour(hour, minute, second)  <b>Minute_valid:</b> <b>not</b> minute_unknown <b>implies</b> valid_minute(minute)  <b>Second_valid:</b> <b>not</b> second_unknown <b>implies</b> valid_second(second)  <b>Fractional_second_valid:</b> has_fractional_second <b>implies</b> (<b>not</b> second_unknown <b>and</b> valid_fractional_second(fractional_second))</p> <p><b>Partial_validity_year:</b> <b>not</b> month_unknown  <b>Partial_validity_month:</b> <b>not</b> month_unknown  <b>Partial_validity_day:</b> <b>not</b> day_unknown  <b>Partial_validity_hour:</b> <b>not</b> hour_unknown  <b>Partial_validity_minute:</b> minute_unknown <b>implies</b> second_unknown</p>	

### 3.4.5 ISO8601\_TIMEZONE Class

INTERFACE	ISO8601_TIMEZONE
<b>Purpose</b>	Represents a timezone as used in ISO 8601.

INTERFACE	ISO8601_TIMEZONE	
Inherit	TIME_DEFINITIONS	
Function	Signature	Meaning
	<b>as_string</b> : String	ISO8601 timezone string, in format <ul style="list-style-type: none"> <li>• <b>Z</b>   <b>±hh[mm]</b></li> </ul> where: <ul style="list-style-type: none"> <li>• <b>hh</b> is “00” - “23” (0-filled to two digits)</li> <li>• <b>mm</b> is “00” - “59” (0-filled to two digits)</li> <li>• <b>Z</b> is a literal meaning UTC (modern replacement for GMT), i.e. timezone +0000</li> </ul>
	<b>hour</b> : Integer	Hour part of timezone - in the range 00 - 13
	<b>minute</b> : Integer <i>require</i> <b>not</b> minute_unknown	Minute part of timezone. Generally 00 or 30.
	<b>sign</b> : Integer	Direction of timezone expressed as +1 or -1.
	<b>is_gmt</b> : Boolean	True if timezone is UTC, i.e. +0000
	<b>minute_unknown</b> : Boolean	Indicates whether minute part known.
Invariants	<i>Min_hour_valid</i> : sign = -1 <b>implies</b> hour > 0 <b>and</b> hour <= Min_timezone_hour <i>Max_hour_valid</i> : sign = 1 <b>implies</b> hour > 0 <b>and</b> hour <= Max_timezone_hour <i>Minute_valid</i> : <b>not</b> minute_unknown <b>implies</b> valid_minute(minute) <i>Sign_valid</i> : sign = 1 or sign = -1	

### 3.4.6 ISO8601\_DURATION Class

INTERFACE	ISO8601_DURATION	
Purpose	Represents a period of time corresponding to a difference between two time-points.	
Inherit	ORDERED, TIME_DEFINITIONS	
Function	Signature	Meaning
	<b>as_string</b> : String	ISO8601 string for duration, in format <ul style="list-style-type: none"> <li>• <b>P[nnY][nnM][nnW][nnD][T[nnH][nnM][nnS]]</b></li> </ul>
	<b>years</b> : Integer	number of years of nominal 365-day length
	<b>months</b> : Integer	number of months of nominal 30 day length
	<b>weeks</b> : Integer	number of 7 day weeks

INTERFACE	ISO8601_DURATION	
	<b>days</b> : Integer	number of 24 hour days
	<b>hours</b> : Integer	number of 60 minute hours
	<b>minutes</b> : Integer	number of 60 second minutes
	<b>seconds</b> : Integer	number of seconds
	<b>fractional_second</b> : Double	fractional seconds
	<b>infix '&lt;'</b> (other: <i>like</i> Current): Boolean	Arithmetic comparison with other duration. True if this duration is smaller than <i>other</i> .
	<b>valid_iso8601_duration</b> (s: String): Boolean	String is a valid ISO 8601 duration, i.e. takes the form: <ul style="list-style-type: none"> <li><b>P[nnY][nnM][nnW][nnD][T[nnH][nnM][nnS]]</b></li> </ul> Where each nn represents a number of years, months, etc. nnW represents a number of 7-day weeks. <b>Note:</b> allowing the W designator in the same expression as other designators is an exception to the published standard, but necessary in clinical information (typically for representing pregnancy duration).
	<b>is_decimal_sign_comma</b> : Boolean	True if this time has a decimal part indicated by ',' (comma) rather than '.' (period).
	<b>to_seconds</b> : Double	Total number of seconds equivalent (including fractional) of entire duration.
<b>Invariants</b>	<b>years_valid</b> : years >= 0 <b>months_valid</b> : months >= 0 <b>weeks_valid</b> : weeks >= 0 <b>days_valid</b> : days >= 0 <b>hours_valid</b> : hours >= 0 <b>minutes_valid</b> : minutes >= 0 <b>seconds_valid</b> : seconds >= 0 <b>fractional_second_valid</b> : fractional_second >= 0.0 and fractional_second < 1.0	

## 4 Identification Package

### 4.1 Overview

The `rm.support.identification` package describes a model of references and identifiers for information entities and is illustrated in FIGURE 5.




FIGURE 5 `rm.support.identification` Package

#### 4.1.1 Requirements

Identification of entities both in the real world and in information systems is a non-trivial problem. The needs for identification across systems in a health information environment include the following:

- real world identifiers such as social security numbers, veterans affairs ids etc can be recorded as required by health care facilities, enterprise policies, or legislation;
- identifiers for informational entities which represent real world entities or processes should be unique;
- it should be possible to determine if two identifiers refer to information entities that represent the same real world entity, even if instances of the information entities are maintained in different systems;
- versions or changes to real-world entity-linked informational entities (which may create new information instances) should be accounted for in two ways:

- it should be possible to tell if two identifiers refer to distinct versions of the same informational entity in the same version tree;
- it should not be possible to confuse same-named versions of informational entities maintained in multiple systems which purport to represent the same real world entity. E.g. there is no guarantee that two systems' "latest" version of the Person "Dr Jones" is the same.

Medico-legal use of information relies on previous states of information being distinguishable from other previous states and the current state.

- It should be possible for an entity in one system or service (such as the EHR) to refer to an entity in another system or service in such a way that:
  - the target of the reference is easily findable within the shared environment, and
  - the reference does is valid regardless of the physical architecture of servers and applications.

The following subsections describe some of the features and challenges of identification.

### Identification of Real World Entities (RWEs)

Real world entities such as people, car engines, invoices, and appointments can all be assigned identifiers. Although many of these are designed to be unique within a jurisdiction, they are often not, due to data entry errors, bad design (ids that are too small or incorporate some non-unique characteristic of the identified entities), bad process (e.g. non-synchronised id issuing points); identity theft (e.g. via theft of documents of proof or hacking). In general, while some real world identifiers (RWIs) are "nearly unique", none can be guaranteed so. It should also be the case that if two RWE identifiers are equal, they refer to the same RWE, but this is often not the case. For practical purposes, RWIs cannot be regarded as computationally safe for making the inferences described here.

### Identification of Informational Entities (IEs)

As soon as information systems are used to record facts about RWEs, the situation becomes more complex because of the intangible nature of information. In particular:

- the same RWE can be represented simultaneously on more than one system ('spatial multiplicity');
- the same RWE may be represented by more than one "version" of the same IE in a system ('temporal multiplicity').

At first sight, it appears that there can also be *purely* informational entities, i.e. IEs which do not refer to any RWE, such as books, online-only documents and software. However, as soon as one considers an example it becomes clear that there is always a notional 'definitive' or 'authoritative' (i.e. trusted) version of every such entity. These entities can better be understood as 'virtual RWEs'. Thus it can still be said that multiple IEs may refer to any given RWE.

The underlying reason for the multiplicity of IEs is that 'reality' - time and space - in computer systems is not continuous but discrete, and each 'entity' is in fact just a snapshot of certain attribute values of a RWE, at a point in time, in a particular system. If identifiers are assigned to IEs without regard to versions or duplicates, then no assertion can be made about the identified RWE when two IE ids are compared.

### Identification of Versions

The notion of 'versioning' applies only to informational entities, i.e. distinct instances of content each representing a snapshot of some logical entity. Where such instances are stored and managed in versioned containers within a versioning system of some kind, explicit identification of the versions is



required. The requirements are discussed in detail in the Common IM, `change_control` package. They can be summarised as follows:

- it must be possible to distinguish two versions of the same logical entity, i.e. know from the identifier if they are the same or different versions of the same thing;
- it must be possible to distinguish two versions of the same logical entity created in two distinct systems;
- it must be possible to tell the relationship between the items in a versioned lineage, from the version identifiers.

## Referencing of Informational Entities

Within a distributed information environment, there is a need for entities not connected by direct references in the same memory space to be able to refer to each other. There are two competing requirements:

- that the separation of objects in a distributed computing environment not compromise the semantics of the model;
- that different types of information can be managed relatively independently; for example EHR and demographic information can be managed by different groups in an organisation or community, each with at least some freedom to change implementation and model details.

## 4.2 Design

This package models only informational identifiers, i.e. transparent identifiers understood by *openEHR* or related computational systems. Real World Entity Identifiers such as driver's license numbers are modelled using the data type `DV_IDENTIFIER`. This is not to imply that such identifiers are any less systematic or well-managed than the system identifiers defined here, only that from the point of view of *openEHR*, they have the same status as other informational attributes such as name, address etc of a Person.

A key design decision has been to choose a string representation for all identifiers, with subparts being made available by appropriate functions which perform simple parsing on the string. This ensures that the data representation of identifiers (e.g. in XML) is as small as possible, while not losing object-oriented typing.

### 4.2.1 Primitive Identifiers

Three kinds of types are defined in this package. The abstract `UID` type and its subtypes correspond to permanent, computationally reliable, primitive identifiers. Such identifiers are regarded as 'primitive' because they are treated as having no further internal structure, in the sense that part of such an identifier is not in general meaningful. The three subtypes `UUID`, `ISO_OID` and `INTERNET_ID` all have these properties, and are commonly accepted ways of uniquely identifying entities in computer systems. In *openEHR* (and generally in health informatics) they are usually used as parts of other identifiers.

A consequence of the string representation approach used in these classes is that to set an attribute of type `UID` from a string value, as would be done when reading from a database, deserialising from XML or another text form, a piece of code that inspects the string structure has to be used in order to decide which of the subtypes of `UID` it is. This is a safe thing to do, since all three subtypes have mutually exclusive string patterns, and can easily be distinguished.

## 4.2.2 Composite Identifiers

The `OBJECT_ID` type and its hierarchy of subtypes correspond to composite identifier types whose structure and semantics are defined by *openEHR* (rather than external organisations), and are the main means of identifying information items in an *openEHR* system. The abstract type `UID_BASED_ID` and its two subtypes `HIER_OBJECT_ID` and `OBJECT_VERSION_ID` provide respectively, UID-based identifiers for non-versioned and versioned items. The design of the latter subtype is explained in the *openEHR* Common IM, `change_control` package.

The other subtypes, `ARCHETYPE_ID` and `TERMINOLOGY_ID` define different kinds of identifier, the former being a multi-axial identifier for archetypes, and the latter being a globally unique single string identifier for terminologies. The `ARCHETYPE_ID` class explicitly includes archetype version as part of the identifier, while terminology identifier values are assumed to include this, either as part of the name (e.g. as is done in the US National Library of Medicine UMLS identifiers - see <http://www.nlm.nih.gov/research/umls/metaal.html>), or according to the syntax defined in section 4.3.12 below.

### Identifying Versions

The `OBJECT_VERSION_ID` defines the semantics of the scheme used in *openEHR* for identifying versions, and uses a three-part identifier, consisting of:

- *object\_id*: the identifier of the version container, in the form of an `UID`;
- *version\_tree\_id*: the location in the version tree, as a 1- or 3-part numeric identifier, where the latter variant expresses branching; this is modelled using the `VERSION_TREE_ID` type;
- *creating\_system\_id*: the identifier of the system in which this version was created, or type `UID`.

Under this scheme, multiple versions in the same container all have the same value for *object\_id*, while their location in the version tree is given by the combination of the version tree identifier and the identifier of the creating system.

The requirements on the third part of the identifier are that it be unique per system, and that it be easy to obtain or generate. It is also helpful if it is a meaningful identifier. The two most practical candidates appear to be GUIDs (which are not meaningful, but are easy to generate) and reverse internet domain identifiers, as recommended in [3] (these are easy to determine if the system has an internet address, and are meaningful and directly processible, however unconnected systems pose a problem). ISO Oids might also be used. All of these identifier types are accommodated via the use of `UID`.

A full explanation of the version identification scheme and its capabilities is given in the `change_control` section of the Common IM.

## 4.2.3 References

All `OBJECT_ID`s are used as identifier attributes *within* the thing they identify, in the same way as a database primary key. To *refer* to an identified object from another object, an instance of the class `OBJECT_REF` should generally be used, in the same way as a database foreign key. The class `OBJECT_REF` is provided as a means of distributed referencing, and includes the object namespace (typically 1:1 with some service, such as “terminology”) and type. The general principle of object references is to be able to refer to an object available in a particular namespace or service. Usually they are used to refer to objects in other services, such as a demographic entity from within an EHR, but they may be used to refer to local objects as well. The type may be the concrete type of the referred-to object (e.g. “GP”) or any proper ancestor (e.g. “PARTY”).

## 4.3 Class Descriptions

### 4.3.1 UID Class

CLASS	UID (abstract)	
Purpose	Abstract parent of classes representing unique identifiers which identify information entities in a durable way. UIDs only ever identify one IE in time or space and are never re-used.	
HL7	The HL7v3 UID Data type.	
Attributes	Signature	Meaning
	value: String	The value of the id.
Invariant	<i>Value_exists</i> : value != Void <i>and then not</i> value.empty	

### 4.3.2 ISO\_OID Class

CLASS	ISO_OID	
Purpose	Model of ISO's Object Identifier (oid) as defined by the standard ISO/IEC 8824 . Oids are formed from integers separated by dots. Each non-leaf node in an Oid starting from the left corresponds to an assigning authority, and identifies that authority's namespace, inside which the remaining part of the identifier is locally unique.	
HL7	The HL7v3 OID Data type.	
Inherit	UID	
Functions	Signature	Meaning
Invariant		

### 4.3.3 UUID Class

CLASS	UUID	
Purpose	Model of the DCE Universal Unique Identifier or UUID which takes the form of hexadecimal integers separated by hyphens, following the pattern 8-4-4-4-12 as defined by the Open Group, CDE 1.1 Remote Procedure Call specification, Appendix A. Also known as a GUID.	
HL7	The HL7v3 UUID Data type.	
Inherit	UID	

CLASS	UUID	
Functions	Signature	Meaning
Invariant		

#### 4.3.4 INTERNET\_ID Class

CLASS	INTERNET_ID	
Purpose	Model of a reverse internet domain, as used to uniquely identify an internet domain. In the form of a dot-separated string in the reverse order of a domain name, specified by IETF RFC 1034 ( <a href="http://www.ietf.org/rfc/rfc1034.txt">http://www.ietf.org/rfc/rfc1034.txt</a> ).	
Inherit	UID	
Functions	Signature	Meaning
Invariant		

##### 4.3.4.1 Syntax

According to IETF RFC1034, the syntax of a domain name follows the BNF grammar:

```

domain: subdomain | ' '
subdomain: label | subdomain '.' label
label: letter [ [ ldh-str ] let-dig ]
ldh-str: let-dig-hyp | let-dig-hyp ldh-str
let-dig-hyp: let-dig | '-'
let-dig: letter | digit

```

**letter:** any one of the 52 alphabetic characters A through Z in upper case and a through z in lower case

**digit:** any one of the ten digits 0 through 9

It can also be expressed using the regular expression:

```
[a-zA-Z]([a-zA-Z0-9-]*[a-zA-Z0-9])?(\.[a-zA-Z]([a-zA-Z0-9-]*[a-zA-Z0-9]))*
```

#### 4.3.5 OBJECT\_ID Class

CLASS	<b>OBJECT_ID (abstract)</b>	
Purpose	Ancestor class of identifiers of informational objects. Ids may be completely meaningless, in which case their only job is to refer to something, or may carry some information to do with the identified object.	
Use	Object ids are used inside an object to identify that object. To identify another object in another service, use an OBJECT_REF, or else use a UID for local objects identified by UID. If none of the subtypes is suitable, direct instances of this class may be used.	

CLASS	<i>OBJECT_ID (abstract)</i>	
Attributes	Signature	Meaning
	<b>value:</b> String	The value of the id in the form defined below.
Invariant	<i>Value_exists:</i> value $\neq$ Void <i>and then not</i> value.empty	

#### 4.3.6 UID\_BASED\_ID Class

CLASS	<i>UID_BASED_ID (abstract)</i>	
Purpose	Abstract model of UID-based identifiers consisting of a root part and an optional extension; lexical form: root '::' extension	
Inherit	<i>OBJECT_ID</i>	
Functions	Signature	Meaning
1..1	<b>root:</b> UID	The identifier of the conceptual namespace in which the object exists, within the identification scheme. Returns the part to the left of the first '::' separator, if any, or else the whole string.
1..1	<b>extension:</b> String	Optional local identifier of the object within the context of the root identifier. Returns the part to the right of the first '::' separator if any, or else any empty String.
	<b>has_extension:</b> Boolean	True if extension $\neq$ Void
Invariant	<i>Root_valid:</i> root $\neq$ Void <i>Extension_validity:</i> extension $\neq$ Void <i>Has_extension_validity:</i> extension.is_empty <b>xor</b> has_extension	

##### 4.3.6.1 Identifier Syntax

The syntax of the *value* attribute by default follows the following production rules (EBNF):

```

value:      root [ '::' extension ]
root:      uid                                -- see UID above
extension: string

```

#### 4.3.7 HIER\_OBJECT\_ID Class

CLASS	<i>HIER_OBJECT_ID</i>
Purpose	Concrete type corresponding to hierarchical identifiers of the form defined by <i>UID_BASED_ID</i> .

CLASS	HIER_OBJECT_ID	
HL7	The HL7v3 II Data type.	
Inherit	UID_BASED_ID	
Functions	Signature	Meaning
Invariant		

### 4.3.8 OBJECT\_VERSION\_ID Class

CLASS	OBJECT_VERSION_ID	
Purpose	Globally unique identifier for one version of a versioned object; lexical form: object_id '::' creating_system_id '::' version_tree_id	
Inherit	UID_BASED_ID	
Functions	Signature	Meaning
1..1	<b>object_id:</b> UID	Unique identifier for logical object of which this identifier identifies one version; normally the <i>object_id</i> will be the unique identifier of the version container containing the version referred to by this OBJECT_VERSION_ID instance.
1..1	<b>version_tree_id:</b> VERSION_TREE_ID	Tree identifier of this version with respect to other versions in the same version tree, as either 1 or 3 part dot-separated numbers, e.g. "1", "2.1.4".
1..1	<b>creating_system_id:</b> UID	Identifier of the system that created the Version corresponding to this Object version id.
	<b>is_branch:</b> Boolean	True if this version identifier represents a branch.
Invariants	<i>Object_valid:</i> object_id != Void <i>Version_tree_id_valid:</i> version_tree_id != Void <i>creating_system_id_valid:</i> creating_system_id != Void	

#### 4.3.8.1 Identifier Syntax

The string form of an OBJECT\_VERSION\_ID stored in its *value* attribute consists of three segments separated by double colons ("::"), i.e. (EBNF):

```

value:                object_id '::' creating_system_id '::' version_tree_id
object_id:            uid                -- see UID below
creating_system_id:  uid                -- see UID below

```

**version\_tree\_id:** -- see VERSION\_TREE\_ID below

An example is as follows:

```
F7C5C7B7-75DB-4b39-9A1E-C0BA9BFDBDEC::87284370-2D4B-
4e3d-A3F3-F303D2F4F34B::2
```

### 4.3.9 VERSION\_TREE\_ID Class

CLASS	VERSION_TREE_ID	
<b>Purpose</b>	Version tree identifier for one version. Lexical form: trunk_version [ '.' branch_number '.' branch_version ]	
<b>Attributes</b>	<b>Signature</b>	<b>Meaning</b>
<b>1..1</b>	<b>value:</b> String	String form of this identifier.
<b>Functions</b>	<b>Signature</b>	<b>Meaning</b>
<b>1..1</b>	<b>trunk_version:</b> String	Trunk version number; numbering starts at 1.
<b>0..1</b>	<b>branch_number:</b> String	Number of branch from the trunk point; numbering starts at 1.
<b>0..1</b>	<b>branch_version:</b> String	Version of the branch; numbering starts at 1.
<b>1..1</b>	<b>is_branch:</b> Boolean	True if this version identifier represents a branch, i.e. has <i>branch_number</i> and <i>branch_version</i> parts.
<b>1..1</b>	<b>is_first:</b> Boolean	True if this version identifier corresponds to the first version, i.e. <i>trunk_version</i> = "1"
<b>Invariants</b>	<p><b>Value_valid:</b> value != Void <b>and then not</b> value.is_empty  <b>Trunk_version_valid:</b> trunk_version != Void <b>and then</b> trunk_version.is_integer <b>and then</b> trunk_version.as_integer &gt;= 1  <b>Branch_number_valid:</b> branch_number != Void <b>implies</b> branch_number.is_integer <b>and then</b> branch_number.as_integer &gt;= 1  <b>Branch_version_valid:</b> branch_version != Void <b>implies</b> branch_version.is_integer <b>and then</b> branch_version.as_integer &gt;= 1  <b>Branch_validity:</b> (branch_number = Void <b>and</b> branch_version = Void ) <b>xor</b> (branch_number != Void <b>and</b> branch_version != Void )  <b>Is_branch_validity:</b> is_branch <b>xor</b> branch_number = Void  <b>Is_first_validity:</b> not is_first <b>xor</b> trunk_version.is_equal("1")</p>	

#### 4.3.9.1 Syntax

The format of the value attribute is (EBNF):

```
value:      trunk_version [ '.' branch_number '.' branch_version ]
trunk_version: { digit }+
branch_number: { digit }+
branch_version: { digit }+
digit:      [0-9]
```

### 4.3.10 ARCHETYPE\_ID Class

CLASS	ARCHETYPE_ID	
<b>Purpose</b>	Identifier for archetypes. Lexical form: <code>rm_terminator '-' rm_name '-' rm_entity '.' concept_name { '-' specialisation }* '.v' number</code>	
<b>Inherit</b>	<i>OBJECT_ID</i>	
Functions	Signature	Meaning
<b>1..1</b>	<b>qualified_rm_entity:</b> String	Globally qualified reference model entity, e.g. "openehr-composition-OBSERVATION".
<b>1..1</b>	<b>domain_concept:</b> String	Name of the concept represented by this archetype, including specialisation, e.g. "biochemistry_result-cholesterol".
<b>1..1</b>	<b>rm_terminator:</b> String	Organisation originating the reference model on which this archetype is based, e.g. "openehr", "cen", "hl7".
<b>1..1</b>	<b>rm_name:</b> String	Name of the reference model, e.g. "rim", "ehr_rm", "en13606".
<b>1..1</b>	<b>rm_entity:</b> String	Name of the ontological level within the reference model to which this archetype is targeted, e.g. for openEHR, "folder", "composition", "section", "entry".
<b>1..1</b>	<b>specialisation:</b> String	Name of specialisation of concept, if this archetype is a specialisation of another archetype, e.g. "cholesterol".
<b>1..1</b>	<b>version_id:</b> String	Version of this archetype.
<b>Invariant</b>	<p><i><b>Qualified_rm_entity_valid:</b></i> qualified_rm_entity != Void <b>and then not</b> qualified_rm_entity.is_empty</p> <p><i><b>Domain_concept_valid:</b></i> domain_concept != Void <b>and then not</b> domain_concept.is_empty</p> <p><i><b>Rm_terminator_valid:</b></i> rm_terminator != Void <b>and then not</b> rm_terminator.is_empty</p> <p><i><b>Rm_name_valid:</b></i> rm_name != Void <b>and then not</b> rm_name.is_empty</p> <p><i><b>Rm_entity_valid:</b></i> rm_entity != Void <b>and then not</b> rm_entity.is_empty</p> <p><i><b>Specialisation_valid:</b></i> specialisation != Void <b>implies not</b> specialisation.is_empty</p> <p><i><b>Version_id_valid:</b></i> version_id != Void <b>and then not</b> version_id.is_empty</p>	



#### 4.3.10.1 Archetype ID Syntax

Archetype identifiers are “multi-axial”, meaning that each identifier instance denotes a single archetype within a multi-dimensional space. In this case, the space is essentially a versioned 3-dimensional space, with the dimensions being:

- reference model entity, i.e. target of archetype
- domain concept
- version

As with any multi-axial identifier, the underlying principle of an archetype id is that all parts of the id must be able to be considered immutable. This means that no variable characteristic of an archetype (e.g. accrediting authority, which might change due to later accreditation by another authority, or may be multiple) can be included in its identifier. The syntax of an `ARCHETYPE_ID` is described by the following production rules:

```
archetype_id: qualified_rm_entity '.' domain_concept '.' version_id
```

```
qualified_rm_entity: rm_originator '-' rm_name '-' rm_entity
```

```
rm_originator: V_NAME
```

```
rm_name: V_NAME
```

```
rm_entity: V_NAME
```

```
domain_concept: concept_name { '-' specialisation }*
```

```
concept_name: V_NAME
```

```
specialisation: V_NAME
```

```
version_id: 'v' V_NATURAL_DIGIT { '.' V_NUMBER }*
```

```
V_NUMBER: [0-9]*
```

```
V_NATURAL_DIGIT: [1-9]
```

```
V_NAME: [a-zA-Z][a-zA-Z0-9_]+
```

The field meanings are as follows:

- rm\_originator*: id of organisation originating the reference model on which this archetype is based;
- rm\_name*: id of the reference model on which the archetype is based;
- rm\_entity*: ontological level in the reference model;
- domain\_concept*: the domain concept name, including any specialisations;
- version\_id*: numeric version identifier.

The PERL regular expression equivalent of the above is as follows:

```
[a-zA-Z]\w+(-[a-zA-Z]\w+){2}\.[a-zA-Z]\w+(-[a-zA-Z]\w+)*\.v[1-9]\d*(\.\d)*
```

The classic regular expression equivalent of this is as follows:

```
[a-zA-Z][a-zA-Z0-9_]+(-[a-zA-Z][a-zA-Z0-9_]+){2}\.[a-zA-Z][a-zA-Z0-9_]+(-[a-zA-Z][a-zA-Z0-9_]+)*\.v[1-9][0-9]*(\.[0-9])*
```

Examples of archetype identifiers include:

- openEHR-EHR-SECTION.physical\_examination.v2
- openEHR-EHR-SECTION.physical\_examination-prenatal.v1
- H17-RIM-Act.progress\_note.v1
- openEHR-EHR-OBSERVATION.progress\_note-naturopathy.v2

### 4.3.11 TEMPLATE\_ID Class

CLASS	TEMPLATE_ID	
Purpose	Identifier for templates. Lexical form to be determined.	
Inherit	OBJECT_ID	
Functions	Signature	Meaning
Invariant		

### 4.3.12 TERMINOLOGY\_ID Class

CLASS	TERMINOLOGY_ID	
Purpose	<p>Identifier for terminologies such accessed via a terminology query service. In this class, the value attribute identifies the Terminology in the terminology service, e.g. "SNOMED-CT". A terminology is assumed to be in a particular language, which must be explicitly specified.</p> <p>The value if the id attribute is the precise terminology id identifier, including actual release (i.e. actual "version"), local modifications etc; e.g. "ICPC2".</p> <p>Lexical form: name [ '(' version ')' ]</p>	
Inherit	OBJECT_ID	
Functions	Signature	Meaning
1..1	<b>name</b> : String	Return the terminology id (which includes the "version" in some cases). Distinct names correspond to distinct (i.e. non-compatible) terminologies. Thus the names "ICD10AM" and "ICD10" refer to distinct terminologies.
1..1	<b>version_id</b> : String	Version of this terminology, if versioning supported, else the empty string.
Invariants	<p><b>Name_valid</b>: name != Void <b>and then not</b> name.is_empty</p> <p><b>Version_id_valid</b>: version_id != Void</p>	

#### 4.3.12.1 Identifier Syntax

The syntax of the *value* attribute is as follows:

name [ '(' version ')' ]

Examples of terminology identifiers include:

- "snomed-ct"
- "ICD9(1999)"

Versions should only be needed for those terminologies which break the rule that the thing being identified with a code loses or changes its meaning over versions of the terminology. This should not be the case for well known modern terminologies and ontologies, particularly those designed since the publication of Cimino's 'desiderata' [1] of which the principle of "concept permanence" is applicable here - "A concept's meaning cannot change and it cannot be deleted from the vocabulary". However, there maybe older terminologies, or specialised terminologies which may not have obeyed these rules, but which are still used; version ids should always be used for these.

#### 4.3.13 GENERIC\_ID Class

CLASS	GENERIC_ID	
<b>Purpose</b>	Generic identifier type for identifiers whose format is otherwise unknown to <i>openEHR</i> . Includes an attribute for naming the identification scheme (which may well be local).	
<b>Inherit</b>	<i>OBJECT_ID</i>	
<b>attributes</b>	<b>Signature</b>	<b>Meaning</b>
<b>1..1</b>	<b>scheme:</b> String	Name of the scheme to which this identifier conforms. Ideally this name will be recognisable globally but realistically it may be a local <i>ad hoc</i> scheme whose name is not controlled or standardised in any way.
<b>Invariants</b>	<i>Scheme_valid</i> : scheme != Void <b>and then not</b> scheme.is_empty	

#### 4.3.14 OBJECT\_REF Class

CLASS	OBJECT_REF	
<b>Purpose</b>	Class describing a reference to another object, which may exist locally or be maintained outside the current namespace, e.g. in another service. Services are usually external, e.g. available in a LAN (including on the same host) or the internet via Corba, SOAP, or some other distributed protocol. However, in small systems they may be part of the same executable as the data containing the Id.	
<b>Attributes</b>	<b>Signature</b>	<b>Meaning</b>
<b>1..1</b>	<b>id:</b> <i>OBJECT_ID</i>	Globally unique id of an object, regardless of where it is stored.

CLASS	OBJECT_REF	
1..1	<b>namespace:</b> String	Namespace to which this identifier belongs in the local system context (and possibly in any other <i>openEHR</i> compliant environment) e.g. “terminology”, “demographic”. These names are not yet standardised. Legal values for the namespace are “local”   “unknown”   “[a-zA-Z][a-zA-Z0-9_~:/&+?]*”
1..1	<b>type:</b> String	Name of the class (concrete or abstract) of object to which this identifier type refers, e.g. “PARTY”, “PERSON”, “GUIDELINE” etc. These class names are from the relevant reference model. The type name “ANY” can be used to indicate that any type is accepted (e.g. if the type is unknown).
Invariant	<i>Id_exists:</i> id != Void <i>Namespace_exists:</i> namespace != Void <b>and then not</b> namespace.is_empty <i>Type_exists:</i> type != Void <b>and then not</b> type.is_empty	

#### 4.3.15 ACCESS\_GROUP\_REF Class

CLASS	ACCESS_GROUP_REF	
Purpose	Reference to access group in an access control service.	
Inherit	OBJECT_REF	
Functions	Signature	Meaning
Invariant	<i>Type_validity:</i> type.is_equal(“ACCESS_GROUP”)	

#### 4.3.16 PARTY\_REF Class

CLASS	PARTY_REF	
Purpose	Identifier for parties in a demographic or identity service. There are typically a number of subtypes of the PARTY class, including PERSON, ORGANISATION, etc. Abstract supertypes are allowed if the referenced object is of a type not known by the current implementation of this class (in other words, if the demographic model is changed by the addition of a new PARTY or ACTOR subtypes, valid PARTY_REFs can still be constructed to them).	
Inherit	OBJECT_REF	
Functions	Signature	Meaning

CLASS	PARTY_REF
Invariant	<i>Type_validity</i> : type.is_equal("PERSON") or type.is_equal("ORGANISATION") or type.is_equal("GROUP") or type.is_equal("AGENT") or type.is_equal("ROLE") or type.is_equal("PARTY") or type.is_equal("ACTOR")

#### 4.3.17 LOCATABLE\_REF Class

CLASS	LOCATABLE_REF	
Purpose	Reference to a LOCATABLE instance inside the top-level content structure inside a VERSION<T>; the <i>path</i> attribute is applied to the object that VERSION.data points to.	
Inherit	OBJECT_REF	
Attributes	Signature	Meaning
1..1 (redefined)	id: OBJECT_VERSION_ID	The identifier of the Version.
0..1	path: String	The path to an instance in question, as an absolute path with respect to the object found at VERSION.data. An empty path means that the object referred to by id being specified.
Functions	Signature	Meaning
1..1	as_uri: String	A URI form of the reference, created by concatenating the following: "ehr://" + id.value + "/" + path
Invariant	<i>Path_valid</i> : path != Void implies not path.is_empty	

## 5 Terminology Package

---

### 5.1 Overview

This section describes the `terminology` package, which contains classes for accessing terminologies and code sets, including the *openEHR* Support Terminology, from within instances of classes defined in the reference model. The classes shown here would normally be inherited via the classes `EXTERNAL_ENVIRONMENT_ACCESS` and `OPENEHR_DEFINITIONS`, although the exact details of how this is done may vary depending on implementation language.

### 5.2 Service Interface

#### 5.2.1 Code Sets

A simple terminology service interface is defined according to FIGURE 6, enabling *openEHR* code sets and terminology to be referenced formally from within the Reference Model. Two types of coded entities are distinguished in *openEHR*, and are accessible via the service interface. The first is codes from ‘code sets’, which are the kind of terminology where the code stands for itself, such as the ISO 639-1 language codes. The identifiers themselves of these code sets do not appear to be standardised, but names such as “ISO\_639-1” are expected to be used (see below).

In any case, code sets needed within the *openEHR* models themselves (e.g. for attributes whose value is a language code) are not referred to directly by an external name such as “ISO\_639-1”, but via an internal constant, in this case, the constant `Code_set_id_languages`, whose value is defined to be “languages”. These constants are defined in the class `OPENEHR_CODE_SET_IDENTIFIERS` in FIGURE 6. The mapping between the internal identifiers and external names should be done in configuration files. The service function `TERMINOLOGY_SERVICE.code_set_for_id()` is used to retrieve code sets on the basis of a constant. The current mapping and external identifiers assumed in *openEHR* is defined in the *openEHR* Support Terminology document. This use of indirection is employed to ensure that the obsoleting and superseding of code-sets does not directly affect *openEHR* software.

For code sets not mapped to internally used constants, i.e. code sets not required in the *openEHR* model itself, but otherwise known in the terminology service, the function `TERMINOLOGY_SERVICE.code_set()` can be used to retrieve these code sets by their external identifier.

#### 5.2.2 Terminologies

Terminologies, including the *openEHR* Support Terminology are accessed via the `TERMINOLOGY_SERVICE` functions `terminology()` and `terminology_identifiers()`, where the argument includes “openehr”, “centc251” (for CEN TC/251 codes) and names from the US NLM terminologies list (see below). The *openEHR* Terminology supports groups, and the set of groups required by the reference model is defined in the class `OPENEHR_TERMINOLOGY_GROUP_IDENTIFIERS`. These groups correspond to coded attributes found in the *openEHR* Reference Model.

#### 5.2.3 Terms and Codes in the *openEHR* Reference Model

True coded attributes in the Reference Model (i.e. attributes of type `DV_CODED_TEXT`), such as `FEEDER_AUDIT.change_type` are defined by an invariant in the enclosing class, such as the following:

OPENEHR_TERMINOLOGY_GROUP_IDENTIFIERS
<pre>const Terminology_id_openehr: String is "openehr" const Group_id_audit_change_type: String is "audit change type" const Group_id_attestation_reason: String is "attestation reason" const Group_id_composition_category: String is "composition category" const Group_id_event_math_function: String is "event math function" const Group_id_instruction_states: String is "instruction states" const Group_id_instruction_transitions: String is "instruction transitions" const Group_id_null_flavours: String is "null flavours" const Group_id_property: String is "property" const Group_id_participation_function: String is "participation function" const Group_id_participation_mode: String is "participation mode" const Group_id_setting: String is "setting" const Group_id_term_mapping_purpose: String is "term mapping purpose" const Group_id_subject_relationship: String is "subject relationship" const Group_id_version_lifecycle_state: String is "version lifecycle state"  valid_group_id(an_id: String): Boolean</pre>

OPENEHR_CODE_SET_IDENTIFIERS
<pre>const Code_set_id_character_sets: String is "character sets" const Code_set_id_compression_algorithms: String is "compression algorithms" const Code_set_id_countries: String is "countries" const Code_set_id_integrity_check_algorithms: String is "integrity check algorithms" const Code_set_id_languages: String is "languages" const Code_set_id_media_types: String is "media types" const Code_set_id_normal_statuses: String is "normal statuses"  valid_code_set_id(an_id: String): Boolean</pre>

CODE_SET_ACCESS
<pre>&lt;&lt;interface&gt;&gt;  id: String all_codes: Set&lt;CODE_PHRASE&gt; has_lang (...): Boolean has_code (...): Boolean</pre>

TERMINOLOGY_SERVICE
<pre>terminology (name: String): TERMINOLOGY_ACCESS code_set (name: String): CODE_SET_ACCESS code_set_for_id (id: String): CODE_SET_ACCESS has_terminology (name: String): Boolean has_code_set (name: String): Boolean terminology_identifiers: List&lt;String&gt; openehr_code_sets: Hash&lt;String, String&gt; code_set_identifiers: List&lt;String&gt;</pre>

TERMINOLOGY_ACCESS
<pre>&lt;&lt;interface&gt;&gt;  id: String all_codes: Set&lt;CODE_PHRASE&gt; codes_for_group_id (...): Set&lt;CODE_PHRASE&gt; codes_for_group_name (...): Set&lt;CODE_PHRASE&gt; has_code_for_group_id (...): Boolean rubric_for_code (...): String</pre>

FIGURE 6 m.support.terminology Package

***Change\_type\_valid***:terminology(Terminology\_id\_openehr).has\_code\_for\_group\_id  
(Group\_id\_audit\_change\_type, change\_type.defining\_code)

This is a formal way of saying that the attribute *change\_type* must have a value such that its *defining\_code* (its CODE\_PHRASE) is in the set of CODE\_PHRASEs in the *openEHR* Terminology which are in the group whose identifier is Group\_id\_audit\_change\_type.

A similar invariant is used for attributes of type CODE\_PHRASE, which come from a code\_set. The following invariant appears in the class ENTRY (rm.composition.content.entry package):

***Language\_valid***: media\_type /= Void **and then**  
code\_set(Code\_set\_languages).has\_code(language)

## 5.3 Identifiers

In *openEHR*, the identifier of a terminology or code set is found in the *terminology\_id* attribute of the class CODE\_PHRASE (Data Types Information Model, text package).

### 5.3.1 Code Set Identifiers

Internal code set identifiers (such as “languages”) used in *openEHR* are defined in the class OPNEHR\_CODE\_SET\_IDENTIFIERS; assumed external identifiers (such as “ISO\_639-1”) for code sets used by the *openEHR* Reference Model are defined in the *openEHR* Support Terminology document.

### 5.3.2 Terminology Identifiers

Valid identifiers that can be used for this attribute for terminologies include but are not limited to the following:

- “openehr”
- “centc251”
- an identifier value from the first column of the US National Library of Medicine (NLM) UMLS terminology identifiers table below, in either of two forms:
  - as is, e.g. “ICD10AM\_2000”, “ICPC93”;
  - with any trailing section starting with an underscore removed, e.g. “ICD10AM”.

Other identification schemes are used in some standards, such as ISO Oids. These are not specified for direct use in *openEHR* for various reasons:

- they are not currently used by the NLM, and no definitive published list of terminology identifiers is available;
- ISO Oids are long identifiers and may significantly increase the size of persisted information due to the ubiquity of coded terms;
- determining the identity of the terminology in data always requires a request to a service containing the Oid / name mapping;
- there is a safety factor in having human readable terminology identifiers in the data.

The use of Oid-based or other terminology identification schemes is not however incompatible with *openEHR*; all that is required is a terminology identifier / name mapping service or table.



The following table is a snapshot of the US National Library of Medicine UMLS terminology identifiers list. A definitive up-to-date list may be found on the NLM website at <http://www.nlm.nih.gov/research/umls/metaa1.html>.

<b>UMLS 2003 Terminology Identifiers</b>	
<b>Identifier</b>	<b>Description</b>
AIR93	AI/RHEUM,1993
ALT2000	Alternative Billing Concepts, 2000
AOD2000	Alcohol and Other Drug Thesaurus, 2000
BI98	Beth Israel Vocabulary, 1.0
BRMP2002	Portuguese translation of the Medical Subject Headings, 2002
BRMS2002	Spanish translation of the Medical Subject Headings, 2002
CCPSS99	Canonical Clinical Problem Statement System, 1999
CCS99	Clinical Classifications Software, 1999
CDT4	Current Dental Terminology(CDT), 4
COSTAR_89-95	COSTAR, 1989-1995
CPM93	Medical Entities Dictionary, 1993
CPT01SP	Physicians' Current Procedural Terminology, Spanish Translation, 2001
CPT2003	Physicians' Current Procedural Terminology, 2003
CSP2002	CRISP Thesaurus, 2002
CST95	COSTART, 1995
DDB00	Diseases Database, 2000
DMD2003	German translation of the Medical Subject Headings, 2003
DMDICD10_1995	German translation of ICD10, 1995
DMDUMD_1996	German translation of UMDNS, 1996
DSM3R_1987	DSM-III-R, 1987
DSM4_1994	DSM-IV, 1994
DUT2001	Dutch Translation of the Medical Subject Headings, 2001
DXP94	DXplain, 1994
FIN2003	Finnish translations of the Medical Subject Headings, 2003
HCDT4	HCPCS Version of Current Dental Terminology(CDT), 4
HCPCS03	Healthcare Common Procedure Coding System, 2003
HCPT03	HCPCS Version of Current Procedural Terminology(CPT), 2003
HHC96	Home Health Care Classification, 1996
HL7_1998-2002	Health Level Seven Vocabulary, 1998-2002
HLREL_1998	ICPC2E-ICD10 relationships from Dr. Henk Lamberts, 1998
HPC99	Health Product Comparison System, 1999
ICD10AE_1998	ICD10, American English Equivalents, 1998
ICD10AMAE_2000	International Statistical Classification of Diseases and Related Health Problems, Australian Modification, Americanized English Equivalents, 2000
ICD10AM_2000	International Statistical Classification of Diseases and Related Health Problems, 10th Revision, Australian Modification, January 2000 Release
ICD10_1998	ICD10, 1998

<b>UMLS 2003 Terminology Identifiers</b>	
<b>Identifier</b>	<b>Description</b>
ICD9CM_2003	ICD-9-CM, 2003
ICPC2AE_1998	International Classification of Primary Care, Americanized English Equivalents, 2E, 1998
ICPC2E_1998	International Classification of Primary Care 2nd Edition, Electronic, 2E, 1998
ICPC2P_2000	International Classification of Primary Care, Version2-Plus, 2000
ICPC93	International Classification of Primary Care, 1993
ICPCBAQ_1993	ICPC, Basque Translation, 1993
ICPCDAN_1993	ICPC, Danish Translation, 1993
ICPCDUT_1993	ICPC, Dutch Translation, 1993
ICPCFIN_1993	ICPC, Finnish Translation, 1993
ICPCFRE_1993	ICPC, French Translation, 1993
ICPCGER_1993	ICPC, German Translation, 1993
ICPCHEB_1993	ICPC, Hebrew Translation, 1993
ICPCHUN_1993	ICPC, Hungarian Translation, 1993
ICPCITA_1993	ICPC, Italian Translation, 1993
ICPCNOR_1993	ICPC, Norwegian Translation, 1993
ICPCPAE_2000	International Classification of Primary Care ,Version2-Plus, Americanized English Equivalents, 2000
ICPCPOR_1993	ICPC, Portuguese Translation, 1993
ICPCSPA_1993	ICPC, Spanish Translation, 1993
ICPCSWE_1993	ICPC, Swedish Translation, 1993
INS2002	French translation of the Medical Subject Headings, 2002
ITA2003	Italian translation of Medical Subject Headings, 2003
JABL99	Online Congenital Multiple Anomaly/ Mental Retardation Syndromes, 1999
LCH90	Library of Congress Subject Headings, 1990
LNC205	LOINC, 2.05
LOINC	LOINC
MCM92	McMaster University Epidemiology Terms, 1992
MDDB99	MasterDrug DataBase, 1999
MDR51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), 5.1
MDRAE51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), American English Equivalents, 5.1
MDREA51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), American English, with expanded abbreviations, 5.1
MDREX51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), with expanded abbreviations, 5.1
MDRPOR51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), 5.1, Portuguese Edition

<b>UMLS 2003 Terminology Identifiers</b>	
<b>Identifier</b>	<b>Description</b>
MDRSPA51	Medical Dictionary for Regulatory Activities Terminology (MedDRA), 5.1, Spanish Edition
MIM93	Online Mendelian Inheritance in Man, 1993
MMSL01	Multum MediSource Lexicon, 2001
MMX01	Micromedex DRUGDEX, 2001-08
MSH2003_2002_10_24	Medical Subject Headings, 2002_10_24
MTH	UMLS Metathesaurus
MTHCH03	Metathesaurus CPT Hierarchical Terms, 2003
MTHHH03	Metathesaurus HCPCS Hierarchical Terms, 2003
MTHICD9_2003	Metathesaurus additional entry terms for ICD-9-CM, 2003
MTHMST2001	Metathesaurus Version of Minimal Standard Terminology Digestive Endoscopy, 2001
MTHMSTFRE_2001	Metathesaurus Version of Minimal Standard Terminology Digestive Endoscopy, French Translation, 2001
MTHMSTITA_2001	Metathesaurus Version of Minimal Standard Terminology Digestive Endoscopy, Italian Translation, 2001
NAN99	Classification of Nursing Diagnoses, 1999
NCBI2001	NCBI Taxonomy, 2001
NCI2001a	NCI Thesaurus, 2001a
NCISEER_1999	NCISEER ICD Neoplasm Code Mappings, 1999
NDDF01	FirstDataBank National Drug DataFile, 2001-07
NEU99	Neuronames Brain Hierarchy, 1999
NIC99	Nursing Interventions Classification, 1999
NOC97	Nursing Outcomes Classification, 1997
OMIM97	OMIM, Online Mendelian Inheritance in Man, 1997
OMS94	Omaha System, 1994
PCDS97	Patient Care Data Set, 1997
PDQ2002	Physician Data Query, 2002
PPAC98	Pharmacy Practice Activity Classification , 1998
PSY2001	Thesaurus of Psychological Index Terms, 2001
QMR96	Quick Medical Reference (QMR), 1996
RAM99	QMR clinically related terms from Randolph A. Miller, 1999
RCD99	Clinical Terms Version 3 (CTV3) (Read Codes), 1999
RCDAE_1999	Read thesaurus, American English Equivalents, 1999
RCDSA_1999	Read thesaurus Americanized Synthesized Terms, 1999
RCDSY_1999	Read thesaurus, Synthesized Terms, 1999
RUS2003	Russian Translation of MeSH, 2003
RXNORM_03AA	RXNORM Project, META2003AA
SNM2	SNOMED-2, 2
SNMI98	SNOMED International, 1998

<b>UMLS 2003 Terminology Identifiers</b>	
<b>Identifier</b>	<b>Description</b>
SNOMED-CT	SNOMED International Clinical Terms, 2002
SPN02	Standard Product Nomenclature, 2002
SRC	Metathesaurus Source Terminology Names
ULT93	UltraSTAR, 1993
UMD2003	UMDNS: product category thesaurus, 2003
UMLS	UMLS: National Library of Medicine, USA
UWDA155	University of Washington Digital Anatomist, 1.5.5
VANDF01	Veterans Health Administration National Drug File, 2001
WHO97	WHO Adverse Reaction Terminology, 1997
WHOFRE_1997	WHOART, French Translation, 1997
WHOGER_1997	WHOART, German Translation, 1997
WHOPOR_1997	WHOART, Portuguese Translation, 1997
WHOSPA_1997	WHOART, Spanish Translation, 1997

## 5.4 Class Definitions

### 5.4.1 TERMINOLOGY\_SERVICE Class

CLASS	TERMINOLOGY_SERVICE	
<b>Purpose</b>	Defines an object providing proxy access to a terminology service.	
<b>Inherit</b>	OPENEHR_CODE_SET_IDENTIFIERS, OPENEHR_TERMINOLOGY_GROUP_IDENTIFIERS	
Functions	Signature	Meaning
	<b>terminology</b> (name: String): TERMINOLOGY_ACCESS <i>require</i> name /= Void <b>and then</b> has_terminology (name) <i>ensure</i> Result /= Void	Return an interface to the terminology named <i>name</i> . Allowable names include <ul style="list-style-type: none"> <li>• “openehr”</li> <li>• “centc251”</li> <li>• any name from are taken from the US NLM UMLS meta-data list at <a href="http://www.nlm.nih.gov/research/umls/metaa1.html">http://www.nlm.nih.gov/research/umls/metaa1.html</a></li> </ul>
	<b>code_set</b> (name: String): CODE_SET_ACCESS <i>require</i> name /= Void <b>and then</b> has_code_set (name) <i>ensure</i> Result /= Void	Return an interface to the code_set identified by the external identifier <i>name</i> (e.g. “ISO_639-1”).
	<b>code_set_for_id</b> (id: String): CODE_SET_ACCESS <i>require</i> id /= Void <b>and then</b> valid_code_set_id (id) <i>ensure</i> Result /= Void	Return an interface to the code_set identified internally in <i>openEHR</i> by <i>id</i> .
	<b>has_terminology</b> (name: String): Boolean <i>require</i> name /= Void <b>and then</b> not name.is_empty	True if terminology named <i>name</i> known by this service. Allowable names include <ul style="list-style-type: none"> <li>• “openehr”</li> <li>• “centc251”</li> <li>• any name from are taken from the US NLM UMLS meta-data list at <a href="http://www.nlm.nih.gov/research/umls/metaa1.html">http://www.nlm.nih.gov/research/umls/metaa1.html</a></li> </ul>

CLASS	TERMINOLOGY_SERVICE	
	<b>has_code_set</b> (name: String): Boolean <i>require</i> name != Void <b>and then not</b> name.is_empty	True if code_set linked to internal <i>name</i> (e.g. "languages") is available.
	<b>terminology_identifiers</b> : List<String>	Set of all terminology identifiers known in the terminology service. Values from the US NLM UMLS meta-data list at <a href="http://www.nlm.nih.gov/research/umls/metaa1.html">http://www.nlm.nih.gov/research/umls/metaa1.html</a>
	<b>code_set_identifiers</b> : List<String>	Set of all code set identifiers known in the terminology service.
	<b>openehr_code_sets</b> : Hash<String, String>	Set of all code sets identifiers for which there is an internal <i>openEHR</i> name; returned as a Hash of ids keyed by internal name.
<b>Invariants</b>		

## 5.4.2 TERMINOLOGY\_ACCESS Class

CLASS	TERMINOLOGY_ACCESS	
<b>Purpose</b>	Defines an object providing proxy access to a terminology.	
Functions	Signature	Meaning
	<b>id</b> : String	Identification of this Terminology
	<b>all_codes</b> : Set<CODE_PHRASE>	Return all codes known in this terminology
	<b>codes_for_group_id</b> (group_id: String): Set<CODE_PHRASE>	Return all codes under grouper 'group_id' from this terminology
	<b>has_code_for_group_id</b> (group_id: String; a_code: CODE_PHRASE): Boolean	True if 'a_code' is known in group 'group_id' in the <i>openEHR</i> terminology.
	<b>codes_for_group_name</b> (name, lang: String): Set<CODE_PHRASE>	Return all codes under grouper whose name in 'lang' is 'name' from this terminology
	<b>rubric_for_code</b> (code, lang: String): String	Return all rubric of code 'code' in language 'lang'.
<b>Invariants</b>	<i>id_exists</i> : id != Void <b>and then not</b> id.is_empty	

**5.4.3 CODE\_SET\_ACCESS Class**

CLASS	CODE_SET_ACCESS	
<b>Purpose</b>	Defines an object providing proxy access to a <code>code_set</code> .	
Functions	Signature	Meaning
	<b>id</b> : String	External identifier of this code set
	<b>all_codes</b> : Set<CODE_PHRASE>	Return all codes known in this code set
	<b>has_lang</b> (a_lang: CODE_PHRASE): Boolean	True if code set knows about ‘a_lang’
	<b>has_code</b> (a_code: CODE_PHRASE): Boolean	True if code set knows about ‘a_code’
<b>Invariants</b>	<i>Id_valid</i> : id != Void and then not id.is_empty	

**5.4.4 OPNEHR\_TERMINOLOGY\_GROUP\_IDENTIFIERS Class**

CLASS	OPNEHR_TERMINOLOGY_GROUP_IDENTIFIERS	
<b>Purpose</b>	List of identifiers for groups in the <i>openEHR</i> terminology.	
Constants	Signature	Meaning
	<b>Terminology_id</b> : String is “openehr”	Name of <i>openEHR</i> ’s own terminology
	<b>Group_id_audit_change_type</b> : String is “audit change type”	
	<b>Group_id_attestation_reason</b> : String is “attestation reason”	
	<b>Group_id_composition_category</b> : String is “composition category”	
	<b>Group_id_event_math_function</b> : String is “event math function”	
	<b>Group_id_instruction_states</b> : String is “instruction states”	
	<b>Group_id_instruction_transitions</b> : String is “instruction transitions”	
	<b>Group_id_null_flavours</b> : String is “null flavours”	

CLASS	OPENEHR_TERMINOLOGY_GROUP_IDENTIFIERS	
	<b>Group_id_property:</b> String is “property”	
	<b>Group_id_participation_function:</b> String is “participation function”	
	<b>Group_id_participation_mode:</b> String is “participation mode”	
	<b>Group_id_subject_relationship:</b> String is “subject relationship”	
	<b>Group_id_setting:</b> String is “setting”	
	<b>Group_id_term_mapping_purpose:</b> String is “term mapping purpose”	
	<b>Group_id_version_lifecycle_state:</b> String is “version lifecycle state”	
Functions	Signature	Meaning
	<b>valid_terminology_group_id</b> (an_id: String): Boolean	Validity function to test if an identifier is in the set defined by this class.
Invariants		

#### 5.4.5 OPENEHR\_CODE\_SET\_IDENTIFIERS Class

CLASS	OPENEHR_CODE_SET_IDENTIFIERS	
Purpose	List of identifiers for code sets in the <i>openEHR</i> terminology.	
Constants	Signature	Meaning
	<b>Code_set_id_character_sets:</b> String is “character sets”	
	<b>Code_set_id_compression_algorithms:</b> String is “compression algorithms”	
	<b>Code_set_id_countries:</b> String is “countries”	
	<b>Code_set_id_integrity_check_algorithms:</b> String is “integrity check algorithms”	
	<b>Code_set_id_languages:</b> String is “languages”	



CLASS	OPENEHR_CODE_SET_IDENTIFIERS	
	<b>Code_set_id_media_types:</b> String is “media types”	
	<b>Code_set_id_normal_statuses:</b> String is “normal statuses”	
Functions	Signature	Meaning
	<b>valid_code_set_id</b> (an_id: String): Boolean	Validity function to test if an identifier is in the set defined by this class.
Invariants		

## 6 Measurement Package

### 6.1 Overview

The Measurement package defines a minimum of semantics relating to quantitative measurement, units, and conversion, enabling the Quantity package of the *openEHR* Data Types Information Model to be correctly expressed. As for the Terminology package, a simple service interface is assumed, which provides useful functions to other parts of the reference model. The definitions underlying measurement and units come from a variety of sources, including:

- CEN ENV 12435, Medical Informatics - Expression of results of measurements in health sciences (see <http://www.centc251.org>);
- the Unified Code for Units of Measure (UCUM), developed by Gunther Schadow and Clement J. McDonald of The Regenstrief Institute (available in HL7v3 ballot materials; <http://www.hl7.org>).

These of course rest in turn upon a vast amount of literature and standards, mainly from ISO on the subject of scientific measurement.

### 6.2 Service Interface

A simple measurement data service interface is defined according to FIGURE 7, enabling quantitative semantics to be used formally from within the Reference Model. Note that this service as currently defined in no way seeks to properly model the semantics of units, conversions etc - it provides only the minimum functions required by the *openEHR* Reference Model.




FIGURE 7 rm.support.measurement Package

#### 6.2.1 Class Definitions

##### 6.2.1.1 MEASUREMENT\_SERVICE Class

CLASS	MEASUREMENT_SERVICE	
Purpose	Defines an object providing proxy access to a measurement information service.	
Functions	Signature	Meaning
	<b>is_valid_units_string</b> (units: String): Boolean <i>require</i> units != Void	True if the units string 'units' is a valid string according to the HL7 UCUM specification.

CLASS	MEASUREMENT_SERVICE	
	<b>units_equivalent</b> (units1, units2: String): Boolean <i>require</i> units1 != Void <i>and then</i> is_valid_units_string(units1) units2 != Void <i>and then</i> is_valid_units_string(units2)	True if two units strings correspond to the same measured property.
Invariants		

## 7 Definition Package

### 7.1 Overview

The `definition` package, illustrated in FIGURE 8, defines symbolic definitions used by the *openEHR* models. Only a small number are currently defined.




FIGURE 8 `rm.support.definition` Package

### 7.2 Class Definitions

#### 7.2.1 OPENEHR\_DEFINITIONS Class

CLASS	OPENEHR_DEFINITIONS	
Purpose	Inheritance class to provide access to constants defined in other packages.	
Inherit	BASIC_DEFINITIONS	
Attributes	Signature	Meaning
Invariants		

#### 7.2.2 BASIC\_DEFINITIONS Class

CLASS	BASIC_DEFINITIONS	
Purpose	Defines globally used constant values.	
Attributes	Signature	Meaning
	CR: Character is '\015'	Carriage return character
	LF: Character is '\012'	Linefeed character
Invariants		

## A References

---

### A.1 General

- 1 Cimino J J. *Desiderata for Controlled Medical vocabularies in the Twenty-First Century*. IMIA WG6 Conference, Jacksonville, Florida, Jan 19-22, 1997.

**END OF DOCUMENT**