

# Learning Neural Representations of Human Cognition across Many fMRI Studies

Arthur Mensch, Julien Mairal,  
Danilo Bzdok, Gaël Varoquaux, Bertrand Thirion

Inria Parietal, Université Paris-Saclay

November 10, 2017



# Learning neural representations accross fMRI studies


1 Introduction

2 Model design

3 Experiments

4 Conclusion

# Introduction



## Functional MRI data:

- **Indirect measure of brain activity**
- 200000 voxels ( $8 \text{ mm}^3$ ), every 2 s.
- Value in each voxel  $\sim$  activity in the area
- **Task fMRI:** timed psychological stimuli
- **Resting-state fMRI:** no stimulation

## Objectives:

- Relate brain images to stimuli
- **Learn models of cognition from data**
- Validated by prediction on *unseen* subjects

# Challenges and trends in fMRI

## Challenges in functional MRI analysis:

- Very indirect measure of brain activity
- Low signal-to-noise ratio
- High inter-subject variability
- Gain statistical power by increasing data size


## Community effort to provide larger datasets:

- From 15 subjects in 1997 to 100000 in 2020
- Costly studies on large cohort: HCP, UKBiobank
- Repositories of many different studies: OpenfMRI

**Adapt algorithms and models** to heavier data and richer labeling

# Canonical learning problem for task fMRI

## Prediction on a single dataset:




Decoding images from *unseen* subjects


What if we have several datasets at hand ?

# Datasets in fMRI

Few big datasets



Many small datasets



UKBiobank 100,000 subjects

OpenfMRI ~150 studies

Using all these datasets jointly to learn richer cognitive models?

# Finding common aspects across fMRI studies

**One of the oldest question in cognitive science:** [Newell, 1973]

- Different cognitive stimuli for each task fMRI study

**Challenges: Many-to-many mapping:**


- Experimental stimulus → several brain regions
- Brain region → several brain functions

**Previous approaches:**

- Meta-analysis      Noisy, coordinate-based
  - [Salimi-Khorshidi et al., 2009, Yarkoni et al., 2011]
- Decoding a cognitive ontology across studies      Not scalable
  - [Schwartz et al., 2013, Wager et al., 2013]

# Our proposal

**Learn a common cognitive base where decoding is easy.**



# Learning neural representations accross fMRI studies

1 Introduction

2 Model design

3 Experiments

4 Conclusion

# Condition prediction for task fMRI

**Common structure from every task fMRI dataset  $d$ :**

- Cognitive stimulus  $\xrightarrow[\text{GLM}]{} \text{contrast map } \mathbf{x} \in \mathbb{R}^p$

**Predictive task:**

- *Input:* contrast  $\mathbf{x} \in \mathbb{R}^p$  from dataset  $d$
- *Output:* condition  $c$  from dataset  $d$ .


Multinomial classification

Parameters for dataset  $d$ :  $(\mathbf{W}_d, \mathbf{b}_d) \in \mathbb{R}^{p \times k}, \mathbb{R}^k$

$$\mathbf{p}_d(\mathbf{x}, \mathbf{W}_d, \mathbf{b}_d) \in \mathbb{R}^c \triangleq \text{softmax}(\mathbf{W}_d^\top \mathbf{x} + \mathbf{b}_d)$$

# Condition prediction for task fMRI

**Baseline:** learn all multinomial regression separately



- **Few samples** per dataset ( $n_d \sim 1000$ )
  - **High dimension**  $W_d \in \mathbb{R}^{p \times k}$
- Aggregate datasets, **reduce the dimension**

# Learning shared representations

## Common structure for classification vectors ( $\mathbf{W}_d$ )<sub>d</sub>:


- Stimuli shares some common aspects
- Vector  $\mathbf{W}_{\text{Archi}}^{\text{Faces}}$  should be close to  $\mathbf{W}_{\text{HCP}}^{\text{Faces}}$
- Enforce *parameter sharing*

### Shared layer model

- $\mathbf{W}_d = \mathbf{W}_e \mathbf{W}'_d$ , where  $\mathbf{W}_e \in \mathbb{R}^{p \times l}$  is shared across datasets.
- Joint minimization objective
- Regularization to enforce parameter sharing

# Shared layer model

**Joint training:** Learn to reduce dimension through  $\mathbf{W}_e$  and to classify through  $(\mathbf{W}'_d)_d$ .



# Dimension reduction using resting-state fMRI

## Initial dimension reduction:

- Compute a dictionary of brain areas
- Represent a brain image from activations in these areas

## How to learn a dictionary with good generic performances:


- Use resting-state data ! [Blumensath et al., 2013]
- Much more available than task data + not biased by stimuli

### Dictionary learning on resting-state data

$$\mathbf{X}_{rs} \in \mathbb{R}^{p \times n} \sim \mathbf{D} \times \mathbf{A}$$

- $\mathbf{D} \in \mathbb{R}^{p \times g}$ ,  $\mathbf{A} \in \mathbb{R}^{g \times n}$  with  $\mathbf{D}$  sparse
- Contrast map  $\mathbf{x} \rightarrow$  brain area loadings  $\mathbf{x}_g$ :

$$\mathbf{x}_g = \mathbf{W}_g^\top \mathbf{x} = (\mathbf{D}^\top \mathbf{D})^{-1} \mathbf{D}^\top \mathbf{x}$$



$$\mathbf{D}_2 \in \mathbb{R}^{p \times 64}$$


# Multi-scale dictionary

## Unsupervised dictionary learning:


- A single  $\mathbf{D}$  captures signal at the scale of its components
- Larger dictionaries  $\rightarrow$  smaller components
- Unknown best number of components

## Solution:

- Dictionaries with different scales
- *Overcomplete* unsupervised dimension reduction



$\mathbf{D}_1$  (16 components)




$\mathbf{D}_2$  (64 components)



$\mathbf{D}_3$  (256 components)

# Unsupervised-learning driven dimension reduction


Concatenate loadings  $x_g(D)$ , from various dictionaries:



# The full model

## Three layer linear network:

- 1<sup>st</sup> layer: Unsupervised learning on resting-state
- 2<sup>nd</sup>/3<sup>rd</sup> layer: Joint training on many datasets



# Training and regularization

## Implementation ingredients:

- Computing  $(\mathbf{D}_j)_j$ : using [Mensch et al., 2017] (a few hours)
- Learn  $\mathbf{W}'_e, (\mathbf{W}'_d)_d$  with stochastic gradient descent
- Use *Dropout* [Srivastava et al., 2014] as a regularizer

### Dropout

- Randomly set coordinates to zero in  $\mathbf{W}_g^\top \mathbf{x}, \mathbf{W}_e^\top \mathbf{W}_g^\top \mathbf{x}$ .
- Prevent co-adaption of coordinates
- Some columns of  $\mathbf{W}_e$  used to classify a single dataset only

# Learning neural representations accross fMRI studies

1 Introduction

2 Model design

3 Experiments

4 Conclusion

# Datasets

## Few big datasets

### HCP

Resting-state

900 subjects

4 million samples

4 TB

Task

900 subjects

23 conditions

40,000 samples

## Many small datasets

### Archi

30 cond.

80 subjects

### Brainomics

18 cond.

100 subjects

### Camcan

5 cond.

600 subjects

### LA5c

10 cond.

200 subjects

UKBiobank

100,000 subjects


OpenfMRI

**~150 studies**

## Datasets

- **HCP**: gambling, working memory, motor, language, social and relational tasks. 800 subjects.
- **Archi** [Pinel et al., 2007]: localizer protocol, motor, social and relational task. 79 subjects.
- **Brainomics** [Papadopoulos Orfanos et al., 2017]: localizer protocol. 100 subjects.
- **Camcan** [Shafto et al., 2014]: audio-video task, with frequency variation. 600 subjects.
- **LA5c consortium** [Poldrack et al., 2016]: task-switching, balloon analog risk taking, stop-signal and spatial working memory capacity tasks — high-level tasks. 200 subjects.

# Model performance




Multi-scale projection, latent space learning are useful.

Dropout is efficient.


Transfer learning occurs

# Model performance



**Multi-scale projection is beneficial**

# Transfer on small datasets




Joint training helps handling **small sample studies**

Better transfer effects using more datasets

# Latent space exploration

Find representative elements of the projected data ( $\mathbf{x}_l$ ) in  $\mathbb{R}^l$ :



- K-means centroids  $\{\mathbf{c}_k\}_k$  of projected data  $(\mathbf{x}_l)_l$



Backward and forward in the model:

- **Forward:** Classification vectors for each dataset  $\{[\mathbf{W}'_{\text{Archi}}, \dots, \mathbf{W}'_{\text{HCP}}]^\top \mathbf{c}\}$
- ← **Backward:** Brain maps (inverse images of  $\{\mathbf{c}_k\}_k$ )

# Latent space exploration



Meaningful template images associated to multi-dataset predictions

# Learning neural representations accross fMRI studies

1 Introduction

2 Model design

3 Experiments

4 Conclusion

# Conclusion

## A new model with better classification performance:

- Efficient use of unsupervised learning on resting-state data
- Good performance of regularization techniques and models from the deep learning (non-convex) world

Learning **representation of brain images** easy to label with **cognitive stimuli**

## Evidence of transfer learning:

- Ongoing extended validation on larger data repositories (OpenfMRI)

# Bibliography I

- [Blumensath et al., 2013] Blumensath, T., Jbabdi, S., Glasser, M. F., Van Essen, D. C., Ugurbil, K., Behrens, T. E., and Smith, S. M. (2013). Spatially constrained hierarchical parcellation of the brain with resting-state fMRI. *NeuroImage*, 76:313–324.
- [Dohmatob et al., 2016] Dohmatob, E., Mensch, A., Varoquaux, G., and Thirion, B. (2016). Learning brain regions via large-scale online structured sparse dictionary-learning. In *30th Conference on Neural Information Processing Systems (NIPS)*.
- [Mensch et al., 2016a] Mensch, A., Mairal, J., Thirion, B., and Varoquaux, G. (2016a). Dictionary learning for massive matrix factorization. In *33rd International Conference on Machine Learning (ICML)*.

## Bibliography II

[Mensch et al., 2016b] Mensch, A., Mairal, J., Thirion, B., and Varoquaux, G. (2016b).

Subsampled online matrix factorization with convergence guarantees.  
In *NIPS Workshop on Optimization for Machine Learning (OPT)*.

[Mensch et al., 2017] Mensch, A., Mairal, J., Thirion, B., and Varoquaux, G. (2017).

Stochastic Subsampling for Factorizing Huge Matrices.  
*arXiv:1701.05363 [cs, math, q-bio, stat]*.

[Mensch et al., 2016c] Mensch, A., Varoquaux, G., and Thirion, B. (2016c).

Compressed Online Dictionary Learning for Fast fMRI Decomposition.  
In *IEEE 13th International Symposium on Biomedical Imaging (ISBI)*.

[Newell, 1973] Newell, A. (1973).

You can't play 20 questions with nature and win: Projective comments on the papers of this symposium.

# Bibliography III

[Papadopoulos Orfanos et al., 2017] Papadopoulos Orfanos, D., Michel, V., Schwartz, Y., Pinel, P., Moreno, A., Le Bihan, D., and Frouin, V. (2017).

The Brainomics/Localizer database.

*NeuroImage*, 144:309–314.

[Pinel et al., 2007] Pinel, P., Thirion, B., Meriaux, S., Jobert, A., Serres, J., Le Bihan, D., Poline, J.-B., and Dehaene, S. (2007).

Fast reproducible identification and large-scale databasing of individual functional cognitive networks.

*BMC neuroscience*, 8(1):91.

[Poldrack et al., 2016] Poldrack, R., Congdon, E., Triplett, W., Gorgolewski, K., Karlsgodt, K., Mumford, J., Sabb, F., Freimer, N., London, E., Cannon, T., and Bilder, R. (2016).

A phenome-wide examination of neural and cognitive function.

*bioRxiv*, page 059733.

# Bibliography IV

[Salimi-Khorshidi et al., 2009] Salimi-Khorshidi, G., Smith, S. M., Keltner, J. R., Wager, T. D., and Nichols, T. E. (2009).

Meta-analysis of neuroimaging data: A comparison of image-based and coordinate-based pooling of studies.

*NeuroImage*, 45(3):810–823.

[Schwartz et al., 2013] Schwartz, Y., Thirion, B., and Varoquaux, G. (2013).

Mapping paradigm ontologies to and from the brain.

In Burges, C. J. C., Bottou, L., Welling, M., Ghahramani, Z., and Weinberger, K. Q., editors, *Advances in Neural Information Processing Systems 26*, pages 1673–1681. Curran Associates, Inc.

[Shafto et al., 2014] Shafto, M. A., Tyler, L. K., Dixon, M., Taylor, J. R., Rowe, J. B., Cusack, R., Calder, A. J., Marslen-Wilson, W. D., Duncan, J., Dalgleish, T., Henson, R. N., Brayne, C., and Matthews, F. E. (2014).

The Cambridge Centre for Ageing and Neuroscience (Cam-CAN) study protocol: A cross-sectional, lifespan, multidisciplinary examination of healthy cognitive ageing.

*BMC Neurology*, 14.

# Bibliography V

- [Srivastava et al., 2014] Srivastava, N., Hinton, G. E., Krizhevsky, A., Sutskever, I., and Salakhutdinov, R. (2014).  
Dropout: A simple way to prevent neural networks from overfitting.  
*Journal of Machine Learning Research*, 15(1):1929–1958.
- [Wager et al., 2013] Wager, T. D., Atlas, L. Y., Lindquist, M. A., Roy, M., Woo, C.-W., and Kross, E. (2013).  
An fMRI-Based Neurologic Signature of Physical Pain.  
*New England Journal of Medicine*, 368(15):1388–1397.
- [Yarkoni et al., 2011] Yarkoni, T., Poldrack, R. A., Nichols, T. E., Van Essen, D. C., and Wager, T. D. (2011).  
Large-scale automated synthesis of human functional neuroimaging data.  
*Nature methods*, 8(8):665–670.