GENE player

```
/******/ (() => { // webpackBootstrap
/******/ 	var __webpack_modules__ = ({

/***/ "./src/App.js"
/*!********************!*\
  !*** ./src/App.js ***!
  \********************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ App)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_router_dom__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-router-dom */ "./node_modules/react-router/dist/development/chunk-
4N6VE7H7.mjs");
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var _App_css__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./App.css */ "./src/App.css");
/* harmony import */ var _components_Layout__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ./components/Layout */ "./src/components/Layout.jsx");
/* harmony import */ var _pages_Home__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ./pages/Home */ "./src/pages/Home.jsx");
/* harmony import */ var _pages_AtlasPage__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ./pages/AtlasPage */ "./src/pages/AtlasPage.jsx");
/* harmony import */ var _pages_ComparePage__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ./pages/ComparePage */ "./src/pages/ComparePage.jsx");
/* harmony import */ var _pages_LibraryPage__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ./pages/LibraryPage */ "./src/pages/LibraryPage.jsx");
/* harmony import */ var _context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ./context/SequenceContext */ "./src/context/SequenceContext.jsx");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/App.js";
```

```
function App() {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)("div", {
    className: "App",
    "x-file-name": "App",
    "x-line-number": "14",
    "x-column": "4",
    "x-component": "div",
    "x-id": "App_14_4",
    "x-dynamic": "false",
    children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__.SequenceProvider, {
      "x-file-name": "App",
      "x-line-number": "15",
      "x-column": "6",
      "x-component": "SequenceProvider",
      "x-id": "App_15_6",
      "x-dynamic": "true",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.BrowserRouter, {
        "x-file-name": "App",
        "x-line-number": "16",
        "x-column": "8",
        "x-component": "BrowserRouter",
        "x-id": "App_16_8",
        "x-dynamic": "false",
        children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_components_Layout__WEBPACK_IMPORTED_MODULE_4__["default"], {
          children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Routes, {
            children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Route, {
              path: "/",
```

```
            element: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_pages_Home__WEBPACK_IMPORTED_MODULE_5__["default"], {}, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 19,
              columnNumber: 40
            }, this)
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 19,
            columnNumber: 15
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Route, {
            path: "/atlas",
            element: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_pages_AtlasPage__WEBPACK_IMPORTED_MODULE_6__["default"], {
              "x-file-name": "App",
              "x-line-number": "20",
              "x-column": "44",
              "x-component": "AtlasPage",
              "x-id": "App_20_44",
              "x-dynamic": "true"
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 20,
              columnNumber: 45
            }, this)
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 20,
            columnNumber: 15
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Route, {
            path: "/compare",
            element: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_pages_ComparePage__WEBPACK_IMPORTED_MODULE_7__["default"], {
              "x-file-name": "App",
              "x-line-number": "21",
              "x-column": "46",
              "x-component": "ComparePage",
              "x-id": "App_21_46",
              "x-dynamic": "true"
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 21,
```

```
            columnNumber: 47
          }, this)
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 21,
          columnNumber: 15
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Route, {
          path: "/library",
          element: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(_pages_LibraryPage__WEBPACK_IMPORTED_MODULE_8__["default"], {
            "x-file-name": "App",
            "x-line-number": "22",
            "x-column": "46",
            "x-component": "LibraryPage",
            "x-id": "App_22_46",
            "x-dynamic": "true"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 22,
            columnNumber: 47
          }, this)
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 22,
          columnNumber: 15
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 18,
        columnNumber: 13
      }, this)
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 17,
      columnNumber: 11
    }, this)
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 16,
    columnNumber: 9
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_10__.jsxDEV)
(sonner__WEBPACK_IMPORTED_MODULE_2__.Toaster, {
    position: "bottom-right",
    theme: "dark",
    toastOptions: {
```

```
          style: {
            background: "#111827",
            color: "#e5e7eb",
            border: "1px solid rgba(255,255,255,0.1)"
          }
        },
        "x-file-name": "App",
        "x-line-number": "26",
        "x-column": "8",
        "x-component": "Toaster",
        "x-id": "App_26_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 26,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 15,
      columnNumber: 7
    }, this)
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 14,
    columnNumber: 5
  }, this);
}
_c = App;
var _c;
__webpack_require__.$Refresh$.register(_c, "App");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
```

```
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/CompareProfile.jsx"
/*!*****************************************!*\
  !*** ./src/components/CompareProfile.jsx ***!
  \*****************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ CompareProfile)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/*
 harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../lib/mirrorGroups */ "./src/lib/mirrorGroups.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/CompareProfile.jsx",
  _s = __webpack_require__.$Refresh$.signature();



function CompareProfile({
  seqA,
```

```
  groupsA,
  seqB,
  groupsB,
  windows = 80,
  metric = "repeatDensity",
  matchedBlocks = [],
  onWindowClick
}) {
  _s();
  const profA = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() =>
(0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__.windowProfile)(seqA, groupsA,
windows, metric), [seqA, groupsA, windows, metric]);
  const profB = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() =>
(0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__.windowProfile)(seqB, groupsB,
windows, metric), [seqB, groupsB, windows, metric]);
  const maxV = Math.max(1e-9, ...profA, ...profB);
  const sizeA = Math.max(1, Math.floor(seqA.length / windows));
  const sizeB = Math.max(1, Math.floor(seqB.length / windows));
  const marksA = matchedBlocks.map(m => Math.min(windows - 1, Math.floor(m.aPos / sizeA)));
  const marksB = matchedBlocks.map(m => Math.min(windows - 1, Math.floor(m.bPos / sizeB)));
  const markSetA = new Set(marksA);
  const markSetB = new Set(marksB);
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "compare-profile",
    "x-file-name": "CompareProfile",
    "x-line-number": "17",
    "x-column": "4",
    "x-component": "div",
    "x-id": "CompareProfile_17_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "CompareProfile",
      "x-line-number": "18",
      "x-column": "6",
      "x-component": "div",
      "x-id": "CompareProfile_18_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        "x-file-name": "CompareProfile",
        "x-line-number": "19",
        "x-column": "8",
        "x-component": "div",
        "x-id": "CompareProfile_19_8",
        "x-dynamic": "false",
```

```
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "CompareProfile",
        "x-line-number": "20",
        "x-column": "10",
        "x-component": "div",
        "x-id": "CompareProfile_20_10",
        "x-dynamic": "false",
        children: "Structural profile"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 20,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("h3", {
        className: "font-heading text-xl font-semibold mt-1",
        "x-file-name": "CompareProfile",
        "x-line-number": "21",
        "x-column": "10",
        "x-component": "h3",
        "x-id": "CompareProfile_21_10",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "metric",
        "x-source-editable": "false",
        children: ["Aligned proportionally \xB7 ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "CompareProfile",
          "x-line-number": "21",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "CompareProfile_21_10_expr1",
          "x-dynamic": "true",
          "x-source-type": "prop",
          "x-source-var": "metric",
          "x-source-editable": "false",
          children: metric
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 21,
        columnNumber: 11
      }, this)]
```

```
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 19,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "text-xs",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "CompareProfile",
        "x-line-number": "23",
        "x-column": "8",
        "x-component": "div",
        "x-id": "CompareProfile_23_8",
        "x-dynamic": "false",
        children: "Click any window to zoom"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 23,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 18,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      "x-file-name": "CompareProfile",
      "x-line-number": "25",
      "x-column": "6",
      "x-component": "div",
      "x-id": "CompareProfile_25_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Row, {
        label: "A",
        prof: profA,
        maxV: maxV,
        marks: markSetA,
        color: "#00f0ff",
        onClick: i => onWindowClick === null || onWindowClick === void 0 ? void 0 :
onWindowClick("A", i),
        testid: "profile-a",
        "x-file-name": "CompareProfile",
        "x-line-number": "26",
        "x-column": "8",
        "x-component": "Row",
        "x-id": "CompareProfile_26_8",
```

```
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 26,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "my-2",
        "x-file-name": "CompareProfile",
        "x-line-number": "27",
        "x-column": "8",
        "x-component": "div",
        "x-id": "CompareProfile_27_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 27,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Row, {
        label: "B",
        prof: profB,
        maxV: maxV,
        marks: markSetB,
        color: "#ffb000",
        onClick: i => onWindowClick === null || onWindowClick === void 0 ? void 0 :
onWindowClick("B", i),
        testid: "profile-b",
        "x-file-name": "CompareProfile",
        "x-line-number": "28",
        "x-column": "8",
        "x-component": "Row",
        "x-id": "CompareProfile_28_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 28,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 25,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 17,
    columnNumber: 5
  }, this);
```

```
}
_s(CompareProfile, "7Aw8kqTLpdZwJSH2agUkL+Jbhiw=");
_c = CompareProfile;
function Row({
  label,
  prof,
  maxV,
  marks,
  color,
  onClick,
  testid
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "flex items-center gap-3",
    "data-testid": testid,
    "x-file-name": "CompareProfile",
    "x-line-number": "36",
    "x-column": "4",
    "x-component": "div",
    "x-id": "CompareProfile_36_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "eyebrow w-6",
      "x-file-name": "CompareProfile",
      "x-line-number": "37",
      "x-column": "6",
      "x-component": "div",
      "x-id": "CompareProfile_37_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "label",
      "x-source-editable": "false",
      children: label
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 37,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex-1 grid",
      style: {
        gridTemplateColumns: `repeat(${prof.length}, 1fr)`,
        height: 60,
        background: "rgba(5,7,13,0.5)",
        borderRadius: 8,
        overflow: "hidden"
      },
```

```
      "x-file-name": "CompareProfile",
      "x-line-number": "38",
      "x-column": "6",
      "x-component": "div",
      "x-id": "CompareProfile_38_6",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: prof.map((v, i) => {
        const h = v / maxV * 100;
        return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("button", {
          onClick: () => onClick === null || onClick === void 0 ? void 0 : onClick(i),
          className: "relative",
          style: {
            background: "transparent",
            border: "none",
            cursor: "pointer",
            padding: 0
          },
          title: `window ${i} · ${v.toFixed(3)}`,
          "data-testid": `${testid}-cell-${i}`,
          "x-file-name":
 "CompareProfile",
          "x-line-number": "42",
          "x-column": "12",
          "x-component": "button",
          "x-id": "CompareProfile_42_12",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
            style: {
              position: "absolute",
              left: 1,
              right: 1,
              bottom: 0,
              height: `${h}%`,
              background: color,
              opacity: 0.75,
              borderRadius: 2
            },
            "x-file-name": "CompareProfile",
            "x-line-number": "50",
            "x-column": "14",
            "x-component": "div",
            "x-id": "CompareProfile_50_14",
            "x-dynamic": "false"
```

```
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 50,
          columnNumber: 15
        }, this), marks.has(i) && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
          style: {
            position: "absolute",
            top: 2,
            left: "50%",
            transform: "translateX(-50%)",
            width: 2,
            height: 8,
            background: "#fff",
            borderRadius: 1
          },
          "x-file-name": "CompareProfile",
          "x-line-number": "52",
          "x-column": "16",
          "x-component": "div",
          "x-id": "CompareProfile_52_16",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 52,
          columnNumber: 17
        }, this)]
      }, i, true, {
        fileName: _jsxFileName,
        lineNumber: 42,
        columnNumber: 13
      }, this);
    })
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 38,
    columnNumber: 7
  }, this)]
 }, void 0, true, {
  fileName: _jsxFileName,
  lineNumber: 36,
  columnNumber: 5
 }, this);
}
_c2 = Row;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "CompareProfile");
__webpack_require__.$Refresh$.register(_c2, "Row");
```

```
const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/FastaInput.jsx"
/*!***************************************!*\
  !*** ./src/components/FastaInput.jsx ***!
  \***************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ FastaInput)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_1__ =
```

```
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/upload.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/zap.js");
/* harmony import */ var _lib_presets__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../lib/presets */ "./src/lib/presets.js");
/* harmony import */ var _lib_fasta__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../lib/fasta */ "./src/lib/fasta.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/FastaInput.jsx",
  _s = __webpack_require__.$Refresh$.signature();




function FastaInput({
  onLoad,
  label = "Load a sequence"
}) {
  _s();
  const [raw, setRaw] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("");
  const [name, setName] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("");
  const fileRef = (0,react__WEBPACK_IMPORTED_MODULE_0__.useRef)(null);
  const submit = () => {
    if (!raw.trim()) {
      sonner__WEBPACK_IMPORTED_MODULE_1__.toast.error("Paste a sequence or pick a preset
first");
      return;
    }
    const parsed = (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_5__.parseFasta)(raw);
    const seq = parsed.sequence || raw;
    const type = (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_5__.detectType)(seq);
    const clean = (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_5__.sanitize)(seq, type);
    if (!clean) {
      sonner__WEBPACK_IMPORTED_MODULE_1__.toast.error("No valid characters found in
input");
      return;
    }
    onLoad({
```

```
      name: name.trim() || parsed.name || "Untitled",
      sequence: clean,
      type,
      source: "user"
    });
    sonner__WEBPACK_IMPORTED_MODULE_1__.toast.success(`Loaded ${clean.length} ${type
=== "digits" ? "digits" : "bases"}`);
  };
  const onFile = async e => {
    var _e$target$files;
    const f = (_e$target$files = e.target.files) === null || _e$target$files === void 0 ? void 0 :
_e$target$files[0];
    if (!f) return;
    const text = await f.text();
    setRaw(text);
    if (!name) setName(f.name.replace(/\.[^.]+$/, ""));
    sonner__WEBPACK_IMPORTED_MODULE_1__.toast.success(`Loaded file: ${f.name}`);
  };
  const applyPreset = p => {
    setRaw(p.sequence);
    setName(p.name);
    onLoad({
      name: p.name,
      sequence: (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_5__.sanitize)(p.sequence, p.type),
      type: p.type,
      source: p.source
    });
    sonner__WEBPACK_IMPORTED_MODULE_1__.toast.success(`Loaded preset: ${p.name}`);
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "fasta-input",
    "x-file-name": "FastaInput",
    "x-line-number": "56",
    "x-column": "4",
    "x-component": "div",
    "x-id": "FastaInput_56_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "flex items-center justify-between mb-3",
      "x-file-name": "FastaInput",
      "x-line-number": "57",
      "x-column": "6",
      "x-component": "div",
      "x-id": "FastaInput_57_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      "x-file-name": "FastaInput",
      "x-line-number": "58",
      "x-column": "8",
      "x-component": "div",
      "x-id": "FastaInput_58_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "FastaInput",
        "x-line-number": "59",
        "x-column": "10",
        "x-component": "div",
        "x-id": "FastaInput_59_10",
        "x-dynamic": "false",
        children: "FASTA Input"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 59,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("h3", {
        className: "font-heading text-xl font-semibold mt-1",
        "x-file-name": "FastaInput",
        "x-line-number": "60",
        "x-column": "10",
        "x-component": "h3",
        "x-id": "FastaInput_60_10",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "label",
        "x-source-editable": "false",
        children: label
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 60,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 58,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
      className: "btn btn-ghost",
      onClick: () => {
        var _fileRef$current;
        return (_fileRef$current = fileRef.current) === null || _fileRef$current === void 0 ? void 0 :
```

```
_fileRef$current.click();
      },
      "data-testid": "fasta-upload-btn",
      "x-file-name": "FastaInput",
      "x-line-number": "62",
      "x-column": "8",
      "x-component": "button",
      "x-id": "FastaInput_62_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_2__["default"],
 {
        size: 14,
        "x-file-name": "FastaInput",
        "x-line-number": "67",
        "x-column": "10",
        "x-component": "Upload",
        "x-id": "FastaInput_67_10",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 67,
        columnNumber: 11
       }, this), " Upload .fasta / .txt"]
     }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 62,
      columnNumber: 9
     }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("input", {
      ref: fileRef,
      type: "file",
      accept: ".fasta,.fa,.txt,.fna",
      className: "hidden",
      onChange: onFile,
      "data-testid": "fasta-file-input",
      "x-file-name": "FastaInput",
      "x-line-number": "69",
      "x-column": "8",
      "x-component": "input",
      "x-id": "FastaInput_69_8",
      "x-dynamic": "false"
     }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 69,
      columnNumber: 9
     }, this)]
    }, void 0, true, {
```

```
      fileName: _jsxFileName,
      lineNumber: 57,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "grid grid-cols-3 gap-3 mb-3",
      "x-file-name": "FastaInput",
      "x-line-number": "79",
      "x-column": "6",
      "x-component": "div",
      "x-id": "FastaInput_79_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("input", {
        className: "input col-span-1",
        placeholder: "Name (optional)",
        value: name,
        onChange: e => setName(e.target.value),
        "data-testid": "fasta-name-input",
        "x-file-name": "FastaInput",
        "x-line-number": "80",
        "x-column": "8",
        "x-component": "input",
        "x-id": "FastaInput_80_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 80,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
        className: "col-span-2 flex flex-wrap gap-2 items-center",
        "x-file-name": "FastaInput",
        "x-line-number": "87",
        "x-column": "8",
        "x-component": "div",
        "x-id": "FastaInput_87_8",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
          className: "eyebrow",
          "x-file-name": "FastaInput",
          "x-line-number": "88",
          "x-column": "10",
          "x-component": "span",
          "x-id": "FastaInput_88_10",
          "x-dynamic": "false",
```

```
        children: "Presets"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 88,
        columnNumber: 11
      }, this), _lib_presets__WEBPACK_IMPORTED_MODULE_4__.PRESETS.map(p =>
/*#__PURE__*/(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
("button", {
        className: "btn btn-ghost",
        style: {
          fontSize: 12,
          padding: "6px 10px"
        },
        onClick: () => applyPreset(p),
        "data-testid": `preset-${p.id}`,
        title: p.description,
        "x-file-name": "FastaInput",
        "x-line-number": "90",
        "x-column": "12",
        "x-component": "button",
        "x-id": "FastaInput_90_12",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_3__["default"], {
          size: 12,
          "x-file-name": "FastaInput",
          "x-line-number": "98",
          "x-column": "14",
          "x-component": "Zap",
          "x-id": "FastaInput_98_14",
          "x-dynamic": "true",
          "x-source-type": "static-imported",
          "x-source-var": "PRESETS",
          "x-source-file": "../lib/presets",
          "x-source-file-abs": "/app/frontend/src/lib/presets.js",
          "x-source-line": "2",
          "x-source-editable": "true",
          "x-array-var": "PRESETS",
          "x-array-file": "../lib/presets",
          "x-array-line": "2",
          "x-array-item-param": "p"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 98,
          columnNumber: 15
        }, this), " ", p.name.split("—")[0].trim()]
```

```
        }, p.id, true, {
          fileName: _jsxFileName,
          lineNumber: 90,
          columnNumber: 13
        }, this))]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 87,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 79,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("textarea", {
      className: "textarea",
      placeholder: ">my_sequence  (optional header)\\nATGCGATCG... or 314159265...",
      value: raw,
      onChange: e => setRaw(e.target.value),
      "data-testid": "fasta-textarea",
      "x-file-name": "FastaInput",
      "x-line-number": "103",
      "x-column": "6",
      "x-component": "textarea",
      "x-id": "FastaInput_103_6",
      "x-dynamic": "false"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 103,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "flex justify-end mt-3",
      "x-file-name": "FastaInput",
      "x-line-number": "110",
      "x-column": "6",
      "x-component": "div",
      "x-id": "FastaInput_110_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
        className: "btn btn-primary",
        onClick: submit,
        "data-testid": "fasta-load-btn",
        "x-file-name": "FastaInput",
        "x-line-number": "111",
        "x-column": "8",
        "x-component": "button",
```

```
        "x-id": "FastaInput_111_8",
        "x-dynamic": "false",
        children: "Load sequence \u2192"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 111,
        columnNumber: 9
      }, this)
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 110,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 56,
    columnNumber: 5
  }, this);
}
_s(FastaInput, "ZCUzbC0FF9NlzY6rsr2bVs3ntP0=");
_c = FastaInput;
var _c;
__webpack_require__.$Refresh$.register(_c, "FastaInput");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}
```

```
if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/InterferenceBuilder.jsx"
/*!************************************************!*\
  !*** ./src/components/InterferenceBuilder.jsx ***!
  \************************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ InterferenceBuilder)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/cog.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/play.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/square.js");
/* harmony import */ var _lib_audio__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../lib/audio */ "./src/lib/audio.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/InterferenceBuilder.jsx",
  _s = __webpack_require__.$Refresh$.signature();




/** Compute interference/resultant rhythm from two integer generators a, b.
 * Every tick of either generator becomes a beat; each beat carries a symbol

 * from generator's group. */
```

```
function resultantRhythm(a, b, totalUnits) {
  const beats = [];
  for (let i = 0; i <= totalUnits; i++) {
    const isA = i % a === 0 && i > 0;
    const isB = i % b === 0 && i > 0;
    if (isA || isB) beats.push({
      unit: i,
      a: isA,
      b: isB
    });
  }
  return beats;
}
function InterferenceBuilder({
  groups,
  type
}) {
  _s();
  const [aIdx, setAIdx] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(0);
  const [bIdx, setBIdx] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(1);
  const [aVal, setAVal] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(3);
  const [bVal, setBVal] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(5);
  const [loop, setLoop] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(false);
  react__WEBPACK_IMPORTED_MODULE_0___default().useEffect(() => {
    if (groups[aIdx]) setAVal(groups[aIdx].length);
    if (groups[bIdx]) setBVal(groups[bIdx].length);
  }, [aIdx, bIdx, groups]);
  const beats = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() =>
resultantRhythm(Math.max(1, aVal), Math.max(1, bVal), Math.max(aVal, bVal) * 6), [aVal, bVal]);
  const play = () => {
    const engine = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_4__.getAudio)();
    engine.stop();
    engine.ensure();
    const step = 1 / 8;
    const t0 = engine.ctx.currentTime + 0.1;
    const ga = groups[aIdx] || "";
    const gb = groups[bIdx] || "";
    const runOnce = startAt => {
      var _beats;
      let posA = 0,
        posB = 0;
      beats.forEach(beat => {
        const t = startAt + beat.unit * step;
        if (beat.a && ga[posA]) {
          const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_4__.symbolToFreq)(ga[posA %
ga.length], type);
          if (f) engine.playNote({
            freq: f,
```

```
          when: t,
          dur: step * 0.9,
          wave: "triangle",
          pan: -0.6
         });
         posA++;
        }
        if (beat.b && gb[posB]) {
         const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_4__.symbolToFreq)(gb[posB %
gb.length], type);
         if (f) engine.playNote({
          freq: (f || 0) * 2,
          when: t,
          dur: step * 0.9,
          wave: "sine",
          pan: 0.6
         });
         posB++;
        }
      });
      return startAt + (((_beats = beats[beats.length - 1]) === null || _beats === void 0 ? void 0 :
_beats.unit) || 0) * step + 0.5;
    };
    let end = runOnce(t0);
    if (loop) end = runOnce(end);
  };
  const stop = () => (0,_lib_audio__WEBPACK_IMPORTED_MODULE_4__.getAudio)().stop();
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "interference-builder",
    "x-file-name": "InterferenceBuilder",
    "x-line-number": "63",
    "x-column": "4",
    "x-component": "div",
    "x-id": "InterferenceBuilder_63_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "64",
      "x-column": "6",
      "x-component": "div",
      "x-id": "InterferenceBuilder_64_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
        "x-file-name": "InterferenceBuilder",
```

```
        "x-line-number": "65",
        "x-column": "8",
        "x-component": "div",
        "x-id": "InterferenceBuilder_65_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "InterferenceBuilder",
          "x-line-number": "66",
          "x-column": "10",
          "x-component": "div",
          "x-id": "InterferenceBuilder_66_10",
          "x-dynamic": "false",
          children: "Interference"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 66,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "InterferenceBuilder",
          "x-line-number": "67",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "InterferenceBuilder_67_10",
          "x-dynamic": "false",
          children: "Two-generator resultant rhythm"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 67,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 65,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_1__["default"], {
        size: 16,
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "69",
        "x-column": "8",
        "x-component": "Cog",
```

```
        "x-id": "InterferenceBuilder_69_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 69,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 64,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
      className: "grid grid-cols-1 md:grid-cols-2 gap-4",
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "72",
      "x-column": "6",
      "x-component": "div",
      "x-id": "InterferenceBuilder_72_6",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: [{
        label: "Generator A",
        idx: aIdx,
        setIdx: setAIdx,
        val: aVal,
        setVal: setAVal,
        testid: "gen-a"
      }, {
        label: "Generator B",
        idx: bIdx,
        setIdx: setBIdx,
        val: bVal,
        setVal: setBVal,
        testid: "gen-b"
      }].map(g => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
        className: "p-3 rounded-lg",
        style: {
          background: "rgba(5,7,13,0.4)"
        },
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "75",
        "x-column": "10",
        "x-component": "div",
        "x-id": "InterferenceBuilder_75_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
        className: "eyebrow mb-2",
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "76",
        "x-column": "12",
        "x-component": "div",
        "x-id": "InterferenceBuilder_76_12",
        "x-dynamic": "true",
        "x-source-type": "static-local",
        "x-source-file": "/app/frontend/src/components/InterferenceBuilder.jsx",
        "x-source-file-abs": "/app/frontend/src/components/InterferenceBuilder.jsx",
        "x-source-line": "73",
        "x-source-path": "label",
        "x-source-editable": "true",
        "x-array-file": "/app/frontend/src/components/InterferenceBuilder.jsx",
        "x-array-line": "73",
        "x-array-item-param": "g",
        "x-array-inline": "true",
        children: g.label
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 76,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("select", {
        className: "select mb-2",
        value: g.idx,
        onChange: e => g.setIdx(parseInt(e.target.value)),
        "data-testid": `${g.testid}-select`,
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "77",
        "x-column": "12",
        "x-component": "select",
        "x-id": "InterferenceBuilder_77_12",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: groups.map((gr, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("option", {
          value: i,
          "x-file-name": "InterferenceBuilder",
          "x-line-number": "79",
          "x-column": "16",
          "x-component": "option",
          "x-id": "InterferenceBuilder_79_16",
          "x-dynamic": "true",
          "x-source-type": "unknown",
          "x-source-var": "i",
          "x-source-editable": "false",
```

```
          children: ["#", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "InterferenceBuilder",
            "x-line-number": "79",
            "x-column": "16",
            "x-component": "option",
            "x-id": "InterferenceBuilder_79_16_expr1",
            "x-dynamic": "true",
            "x-source-type": "unknown",
            "x-source-var": "i",
            "x-source-editable": "false",
            children: i
          }, void 0, false), " \xB7 ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "InterferenceBuilder",
            "x-line-number": "79",
            "x-column": "16",
            "x-component": "option",
            "x-id": "InterferenceBuilder_79_16_expr3",
            "x-dynamic": "true",
            "x-source-type": "computed",
            "x-source-editable":
 "false",
            children: gr.slice(0, 12)
          }, void 0, false), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "InterferenceBuilder",
            "x-line-number": "79",
            "x-column": "16",
            "x-component": "option",
            "x-id": "InterferenceBuilder_79_16_expr4",
            "x-dynamic": "true",
            "x-source-type": "computed",
            "x-source-editable": "false",
```

```
            children: gr.length > 12 ? "…" : ""
          }, void 0, false), " (", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "InterferenceBuilder",
            "x-line-number": "79",
            "x-column": "16",
            "x-component": "option",
            "x-id": "InterferenceBuilder_79_16_expr6",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "groups",
            "x-source-path": "length",
            "x-source-editable": "false",
            "x-array-var": "groups",
            "x-array-item-param": "gr",
            children: gr.length
          }, void 0, false), ")"]
        }, i, true, {
          fileName: _jsxFileName,
          lineNumber: 79,
          columnNumber: 17
        }, this))
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 77,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
        className: "flex items-center gap-2",
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "82",
        "x-column": "12",
        "x-component": "div",
        "x-id": "InterferenceBuilder_82_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
          className: "text-xs",
          style: {
            color: "var(--muted)"
          },
          "x-file-name": "InterferenceBuilder",
          "x-line-number": "83",
          "x-column": "14",
```

```
            "x-component": "span",
            "x-id": "InterferenceBuilder_83_14",
            "x-dynamic": "false",
            children: "Pulse"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 83,
            columnNumber: 15
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("input", {
            type: "number",
            className: "input",
            value: g.val,
            min: 1,
            onChange: e => g.setVal(parseInt(e.target.value) || 1),
            "data-testid": `${g.testid}-value`,
            "x-file-name": "InterferenceBuilder",
            "x-line-number": "84",
            "x-column": "14",
            "x-component": "input",
            "x-id": "InterferenceBuilder_84_14",
            "x-dynamic": "false"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 84,
            columnNumber: 15
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 82,
          columnNumber: 13
        }, this)]
      }, g.label, true, {
        fileName: _jsxFileName,
        lineNumber: 75,
        columnNumber: 11
      }, this))
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 72,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
      className: "mt-4 flex items-center gap-3",
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "90",
      "x-column": "6",
      "x-component": "div",
      "x-id": "InterferenceBuilder_90_6",
```

```
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("input", {
        type: "checkbox",
        id: "int-loop",
        checked: loop,
        onChange: e => setLoop(e.target.checked),
        "data-testid": "interference-loop",
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "91",
        "x-column": "8",
        "x-component": "input",
        "x-id": "InterferenceBuilder_91_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 91,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("label", {
        htmlFor: "int-loop",
        className: "text-sm",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "92",
        "x-column": "8",
        "x-component": "label",
        "x-id": "InterferenceBuilder_92_8",
        "x-dynamic": "false",
        children: "Loop once"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 92,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
        className: "flex-1",
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "93",
        "x-column": "8",
        "x-component": "div",
        "x-id": "InterferenceBuilder_93_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 93,
        columnNumber: 9
```

```
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("button", {
      className: "btn btn-primary",
      onClick: play,
      "data-testid": "interference-play",
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "94",
      "x-column": "8",
      "x-component": "button",
      "x-id": "InterferenceBuilder_94_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_2__["default"], {
        size: 14,
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "94",
        "x-column": "91",
        "x-component": "Play",
        "x-id": "InterferenceBuilder_94_91",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 94,
        columnNumber: 92
      }, this), " Generate & play"]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 94,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("button", {
      className: "btn",
      onClick: stop,
      "data-testid": "interference-stop",
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "95",
      "x-column": "8",
      "x-component": "button",
      "x-id": "InterferenceBuilder_95_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_3__["default"], {
        size: 14,
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "95",
        "x-column": "79",
        "x-component": "Square",
```

```
        "x-id": "InterferenceBuilder_95_79",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 95,
        columnNumber: 80
       }, this), " Stop"]
      }, void 0, true, {
       fileName: _jsxFileName,
       lineNumber: 95,
       columnNumber: 9
      }, this)]
    }, void 0, true, {
     fileName: _jsxFileName,
     lineNumber: 90,
     columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div", {
     className: "mt-3 p-3 rounded-lg font-mono text-xs",
     style: {
      background: "rgba(5,7,13,0.4)",
      color: "var(--teal)"
     },
     "x-file-name": "InterferenceBuilder",
     "x-line-number": "98",
     "x-column": "6",
     "x-component": "div",
     "x-id": "InterferenceBuilder_98_6",
     "x-dynamic": "true",
     "x-source-type": "computed",
     "x-source-editable": "false",
     children: ["beats: ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
       "data-ve-dynamic": "true",
       "x-excluded": "true",
       style: {
        display: "contents"
       },
       "x-file-name": "InterferenceBuilder",
       "x-line-number": "98",
       "x-column": "6",
       "x-component": "div",
       "x-id": "InterferenceBuilder_98_6_expr1",
       "x-dynamic": "true",
       "x-source-type": "computed",
       "x-source-editable": "false",
       children: beats.map(b => `${b.a && b.b ? "✦" : b.a ? "◐" : "◑"}${b.unit}`).slice(0, 40).join("  ")
     }, void 0, false), " ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("span", {
```

```
        "data-ve-dynamic": "true",
        "x-excluded": "true",
        style: {
          display: "contents"
        },
        "x-file-name": "InterferenceBuilder",
        "x-line-number": "98",
        "x-column": "6",
        "x-component": "div",
        "x-id": "InterferenceBuilder_98_6_expr3",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: beats.length > 40 ? "…" : ""
      }, void 0, false)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 98,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_5__.jsxDEV)("div",
 {
      className: "mt-2 text-xs",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "InterferenceBuilder",
      "x-line-number": "101",
      "x-column": "6",
      "x-component": "div",
      "x-id": "InterferenceBuilder_101_6",
      "x-dynamic": "false",
      children: "Two clocks ticking at pulse A and pulse B; every tick becomes a beat. Voice B plays an
octave higher and panned right."
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 101,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 63,
    columnNumber: 5
  }, this);
}
_s(InterferenceBuilder, "Qa4j2pF52OXCz74A4fZvgqanKgE=");
_c = InterferenceBuilder;
var _c;
__webpack_require__.$Refresh$.register(_c, "InterferenceBuilder");
```

```
const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/Layout.jsx"
/*!***********************************!*\
  !*** ./src/components/Layout.jsx ***!
  \***********************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ Layout)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
```

```
/* harmony import */ var react_router_dom__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-router-dom */ "./node_modules/react-router/dist/development/chunk-
4N6VE7H7.mjs");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/house.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/git-compare-
arrows.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/library.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/waves.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/Layout.jsx",
  _s = __webpack_require__.$Refresh$.signature();



function Layout({
  children
}) {
  _s();
  const loc = (0,react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useLocation)();
  const tabs = [{
    to: "/",
    label: "Home",
    icon: lucide_react__WEBPACK_IMPORTED_MODULE_2__["default"],
    testid: "nav-home"
  }, {
    to: "/atlas",
    label: "Atlas",
    icon: lucide_react__WEBPACK_IMPORTED_MODULE_5__["default"],
    testid: "nav-atlas"
  }, {
    to: "/compare",
    label: "Compare",
    icon: lucide_react__WEBPACK_IMPORTED_MODULE_3__["default"],
    testid: "nav-compare"
  }, {
    to: "/library",
    label: "Library",
```

```
    icon: lucide_react__WEBPACK_IMPORTED_MODULE_4__["default"],
    testid: "nav-library"
  }];
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
    className: "min-h-screen",
    "x-file-name": "Layout",
    "x-line-number": "14",
    "x-column": "4",
    "x-component": "div",
    "x-id": "Layout_14_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("header", {
      "data-testid": "app-header",
      className: "sticky top-0 z-30 border-b",
      style: {
        borderColor: "var(--line)",
        background: "rgba(11,15,25,0.85)",
        backdropFilter: "blur(10px)"
      },
      "x-file-name": "Layout",
      "x-line-number": "15",
      "x-column": "6",
      "x-component": "header",
      "x-id": "Layout_15_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
        className: "max-w-[1440px] mx-auto flex items-center justify-between px-6 py-3",
        "x-file-name": "Layout",
        "x-line-number": "24",
        "x-column": "8",
        "x-component": "div",
        "x-id": "Layout_24_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Link, {
          to: "/",
          className: "flex items-center gap-3",
          "data-testid": "brand-logo",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
            className: "w-9 h-9 rounded-lg flex items-center justify-center",
            style: {
              background: "conic-gradient(from 30deg, #00f0ff, #10b981, #fbbf24, #e024a6, #00f0ff)"
            },
            "x-file-name": "Layout",
```

```
          "x-line-number": "26",
          "x-column": "12",
          "x-component": "div",
          "x-id": "Layout_26_12",
          "x-dynamic": "false",
          children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
            className: "w-7 h-7 rounded-md flex items-center justify-center font-heading font-bold",
            style: {
              background: "var(--ink-1)",
              color: "var(--teal)"
            },
            "x-file-name": "Layout",
            "x-line-number": "33",
            "x-column": "14",
            "x-component": "div",
            "x-id": "Layout_33_14",
            "x-dynamic": "false",
            children: "M"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 33,
            columnNumber: 15
          }, this)
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 26,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
          className: "leading-tight",
          "x-file-name": "Layout",
          "x-line-number": "40",
          "x-column": "12",
          "x-component": "div",
          "x-id": "Layout_40_12",
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
            className: "font-heading font-bold text-base",
            "x-file-name": "Layout",
            "x-line-number": "41",
            "x-column": "14",
            "x-component": "div",
            "x-id": "Layout_41_14",
            "x-dynamic": "false",
            children: "Mirror Atlas"
          }, void 0, false, {
            fileName: _jsxFileName,
```

```
            lineNumber: 41,
            columnNumber: 15
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
            className: "eyebrow",
            "x-file-name": "Layout",
            "x-line-number": "42",
            "x-column": "14",
            "x-component": "div",
            "x-id": "Layout_42_14",
            "x-dynamic": "false",
            children: "Sequence Workbench"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 42,
            columnNumber: 15
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 40,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 25,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("nav", {
        className: "flex gap-1",
        "data-testid": "nav-tabs",
        "x-file-name": "Layout",
        "x-line-number": "45",
        "x-column": "10",
        "x-component": "nav",
        "x-id": "Layout_45_10",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: tabs.map(t => {
          const active = t.to === "/" ? loc.pathname === "/" : loc.pathname.startsWith(t.to);
          const Icon = t.icon;
          return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(react_router_dom__WEBPACK_IMPORTED_MODULE_1__.Link, {
            to: t.to,
            "data-testid": t.testid,
            className: `tab ${active ? "active" : ""}`,
            children:
 [/*#__PURE__*/(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
```

```
(Icon, {
              size: 14,
              style: {
                marginRight: 4
              },
              "x-file-name": "Layout",
              "x-line-number": "57",
              "x-column": "18",
              "x-component": "Icon",
              "x-id": "Layout_57_18",
              "x-dynamic": "true",
              "x-source-type": "static-imported",
              "x-source-var": "tabs",
              "x-source-file-abs": "/app/frontend/src/components/Layout.jsx",
              "x-source-line": "7",
              "x-source-editable": "true",
              "x-array-var": "tabs",
              "x-array-line": "7",
              "x-array-item-param": "t"
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 57,
              columnNumber: 19
            }, this), t.label]
          }, t.to, true, {
            fileName: _jsxFileName,
            lineNumber: 51,
            columnNumber: 17
          }, this);
        })
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 45,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 24,
      columnNumber: 9
    }, this)
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 15,
    columnNumber: 7
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("main", {
    className: "max-w-[1440px] mx-auto px-6 py-6",
    "x-file-name": "Layout",
    "x-line-number": "65",
```

```
      "x-column": "6",
      "x-component": "main",
      "x-id": "Layout_65_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "children",
      "x-source-editable": "false",
      children: children
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 65,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("footer", {
      className: "max-w-[1440px] mx-auto px-6 py-8 text-xs",
      style: {
        color: "var(--dim)"
      },
      "x-file-name": "Layout",
      "x-line-number": "66",
      "x-column": "6",
      "x-component": "footer",
      "x-id": "Layout_66_6",
      "x-dynamic": "false",
      children: "Mirror Grouping \xB7 after A. M. Zilkowsky \xB7 Schillinger devices \xB7 432 Hz
drone"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 66,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 14,
    columnNumber: 5
  }, this);
}
_s(Layout, "+fPrPJs5E5K7VLA8vN588fSnNZA=", false, function () {
  return [react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useLocation];
});
_c = Layout;
var _c;
__webpack_require__.$Refresh$.register(_c, "Layout");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);
```

```
function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/LegoBlock.jsx"
/*!**************************************!*\
  !*** ./src/components/LegoBlock.jsx ***!
  \**************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ LegoBlock),
/* harmony export */   depthColors: () => (/* binding */ depthColors)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../lib/mirrorGroups */ "./src/lib/mirrorGroups.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
```

```
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/LegoBlock.jsx";



const DEPTH = {
  0: {
    bg: "#1F2937",
    fg: "#9CA3AF",
    border: "#374151"
  },
  1: {
    bg: "rgba(16,185,129,0.22)",
    fg: "#34D399",
    border: "#10B981"
  },
  2: {
    bg: "rgba(251,191,36,0.22)",
    fg: "#FBBF24",
    border: "#F59E0B"
  },
  3: {
    bg: "rgba(6,182,212,0.22)",
    fg: "#38BDF8",
    border: "#06B6D4"
  }
};
const DEEP = {
  bg: "rgba(224,36,166,0.22)",
  fg: "#F472B6",
  border: "#E024A6"
};
function depthColors(d) {
  return DEPTH[d] || (d >= 4 ? DEEP : DEPTH[0]);
}
function LegoBlock({
  text,
  index,
  onClick,
  selected,
  showDepth = true,
  small = false
}) {
  const depth = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__.palindromeDepth)
(text);
```

```
  const c = depthColors(depth);
  const style = {
    background: c.bg,
    color: c.fg,
    borderColor: c.border,
    fontSize: small ? 10 : 12,
    padding: small ? "3px 6px" : "6px 8px"
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
    className: `lego ${selected ? "selected" : ""}`,
    style: style,
    onClick: () => onClick === null || onClick === void 0 ? void 0 : onClick(index),
    "data-testid": `lego-block-${index}`,
    title: `#${index} · length ${text.length} · depth ${depth}`,
    "x-file-name": "LegoBlock",
    "x-line-number": "34",
    "x-column": "4",
    "x-component": "span",
    "x-id": "LegoBlock_34_4",
    "x-dynamic": "true",
    "x-source-type": "prop",
    "x-source-var": "text",
    "x-source-editable": "false",
    children: [text, showDepth && depth > 0 && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
      className: "depth-ring",
      "x-file-name": "LegoBlock",
      "x-line-number": "42",
      "x-column": "33",
      "x-component": "span",
      "x-id": "LegoBlock_42_33",
      "x-dynamic": "true",
      "x-source-type": "unknown",
      "x-source-var": "depth",
      "x-source-editable": "false",
      children: depth
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 42,
      columnNumber: 34
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 34,
    columnNumber: 5
  }, this);
}
_c = LegoBlock;
```

```
var _c;
__webpack_require__.$Refresh$.register(_c, "LegoBlock");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/MatchedBlocks.jsx"
/*!*****************************************!*\
  !*** ./src/components/MatchedBlocks.jsx ***!
  \*****************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ MatchedBlocks)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
```

```
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _LegoBlock__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./LegoBlock */ "./src/components/LegoBlock.jsx");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/MatchedBlocks.jsx",
  _s = __webpack_require__.$Refresh$.signature();



function
 MatchedBlocks({
  blocks,
  onSelect
}) {
  _s();
  const [sort, setSort] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("size");
  const [minLen, setMinLen] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(6);
  const filtered = blocks.filter(b => b.len >= minLen);
  const sorted = [...filtered].sort((x, y) => sort === "size" ? y.len - x.len : x.aPos - y.aPos);
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "matched-blocks",
    "x-file-name": "MatchedBlocks",
    "x-line-number": "11",
    "x-column": "4",
    "x-component": "div",
    "x-id": "MatchedBlocks_11_4",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "MatchedBlocks",
      "x-line-number": "12",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MatchedBlocks_12_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      "x-file-name": "MatchedBlocks",
      "x-line-number": "13",
      "x-column": "8",
      "x-component": "div",
      "x-id": "MatchedBlocks_13_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "MatchedBlocks",
        "x-line-number": "14",
        "x-column": "10",
        "x-component": "div",
        "x-id": "MatchedBlocks_14_10",
        "x-dynamic": "false",
        children: "Matched blocks"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 14,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("h3", {
        className: "font-heading text-xl font-semibold mt-1",
        "x-file-name": "MatchedBlocks",
        "x-line-number": "15",
        "x-column": "10",
        "x-component": "h3",
        "x-id": "MatchedBlocks_15_10",
        "x-dynamic": "false",
        children: "Shared Lego groups between A and B"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 15,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 13,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex items-center gap-2",
      "x-file-name": "MatchedBlocks",
      "x-line-number": "17",
      "x-column": "8",
      "x-component": "div",
      "x-id": "MatchedBlocks_17_8",
      "x-dynamic": "false",
```

```
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
        className: "text-xs",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MatchedBlocks",
        "x-line-number": "18",
        "x-column": "10",
        "x-component": "span",
        "x-id": "MatchedBlocks_18_10",
        "x-dynamic": "false",
        children: "Min length"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 18,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("input", {
        type: "number",
        className: "input",
        style: {
          width: 80
        },
        value: minLen,
        onChange: e => setMinLen(parseInt(e.target.value) || 1),
        "data-testid": "matched-minlen",
        "x-file-name": "MatchedBlocks",
        "x-line-number": "19",
        "x-column": "10",
        "x-component": "input",
        "x-id": "MatchedBlocks_19_10",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 19,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("select", {
        className: "select",
        style: {
          width: 140
        },
        value: sort,
        onChange: e => setSort(e.target.value),
        "data-testid": "matched-sort",
        "x-file-name": "MatchedBlocks",
        "x-line-number": "20",
        "x-column": "10",
```

```
        "x-component": "select",
        "x-id": "MatchedBlocks_20_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("option", {
          value: "size",
          "x-file-name": "MatchedBlocks",
          "x-line-number": "21",
          "x-column": "12",
          "x-component": "option",
          "x-id": "MatchedBlocks_21_12",
          "x-dynamic": "false",
          children: "Size (largest)"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 21,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("option", {
          value: "position",
          "x-file-name": "MatchedBlocks",
          "x-line-number": "22",
          "x-column": "12",
          "x-component": "option",
          "x-id": "MatchedBlocks_22_12",
          "x-dynamic": "false",
          children: "Position"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 22,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 20,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 17,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 12,
    columnNumber: 7
  }, this), sorted.length === 0 ? /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "text-sm",
```

```
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "MatchedBlocks",
      "x-line-number": "27",
      "x-column": "8",
      "x-component": "div",
      "x-id": "MatchedBlocks_27_8",
      "x-dynamic": "false",
      children: "No shared Lego blocks at this length threshold."
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 27,
      columnNumber: 9
    }, this) : /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "scroll-x flex flex-wrap gap-2",
      "x-file-name": "MatchedBlocks",
      "x-line-number": "29",
      "x-column": "8",
      "x-component": "div",
      "x-id": "MatchedBlocks_29_8",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: sorted.slice(0, 200).map((b, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("button", {
        className: "btn btn-ghost",
        style: {
          padding: "4px 10px"
        },
        onClick: () => onSelect === null || onSelect === void 0 ? void 0 : onSelect(b),
        "data-testid": `matched-block-${i}`,
        "x-file-name": "MatchedBlocks",
        "x-line-number": "31",
        "x-column": "12",
        "x-component": "button",
        "x-id": "MatchedBlocks_31_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)
(_LegoBlock__WEBPACK_IMPORTED_MODULE_1__["default"], {
          text: b.text,
          index: i,
          small: true,
          "x-file-name": "MatchedBlocks",
          "x-line-number": "32",
          "x-column": "14",
          "x-component": "LegoBlock",
```

```
        "x-id": "MatchedBlocks_32_14",
        "x-dynamic": "true",
        "x-source-type": "external",
        "x-source-editable": "false",
        "x-array-item-param": "b"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 32,
        columnNumber: 15
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
        className: "font-mono text-xs",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MatchedBlocks",
        "x-line-number": "33",
        "x-column": "14",
        "x-component": "span",
        "x-id": "MatchedBlocks_33_14",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-path": "len",
        "x-source-editable": "false",
        "x-array-item-param": "b",
        children: ["len ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "MatchedBlocks",
          "x-line-number": "33",
          "x-column": "14",
          "x-component": "span",
          "x-id": "MatchedBlocks_33_14_expr1",
          "x-dynamic": "true",
          "x-source-type": "static-imported",
          "x-source-path": "len",
          "x-source-editable": "false",
          "x-array-item-param": "b",
          children: b.len
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 33,
        columnNumber: 15
      }, this)]
```

```
      }, i, true, {
        fileName: _jsxFileName,
        lineNumber: 31,
        columnNumber: 13
      }, this))
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 29,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName:
 _jsxFileName,
    lineNumber: 11,
    columnNumber: 5
  }, this);
}
_s(MatchedBlocks, "4dC1CWg9TVaadW9xvk+Ak58EYoc=");
_c = MatchedBlocks;
var _c;
__webpack_require__.$Refresh$.register(_c, "MatchedBlocks");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
```

```
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/MirrorGroupsPanel.jsx"
/*!**********************************************!*\
  !*** ./src/components/MirrorGroupsPanel.jsx ***!
  \**********************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ MirrorGroupsPanel)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _LegoBlock__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./LegoBlock */ "./src/components/LegoBlock.jsx");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/MirrorGroupsPanel.jsx";



function MirrorGroupsPanel({
  groups,
  onSelect,
  selectedIndex,
  playhead = -1
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "mirror-groups-panel",
    "x-file-name": "MirrorGroupsPanel",
    "x-line-number": "6",
    "x-column": "4",
    "x-component": "div",
```

```
    "x-id": "MirrorGroupsPanel_6_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "MirrorGroupsPanel",
      "x-line-number": "7",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MirrorGroupsPanel_7_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "8",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MirrorGroupsPanel_8_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "MirrorGroupsPanel",
          "x-line-number": "9",
          "x-column": "10",
          "x-component": "div",
          "x-id": "MirrorGroupsPanel_9_10",
          "x-dynamic": "false",
          children: "Mirror groups"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 9,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "MirrorGroupsPanel",
          "x-line-number": "10",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "MirrorGroupsPanel_10_10",
          "x-dynamic": "false",
          children: "Lego block map"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 10,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
```

```
        fileName: _jsxFileName,
        lineNumber: 8,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "text-xs",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "12",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MirrorGroupsPanel_12_8",
        "x-dynamic": "false",
        children: "Each block ends where a symbol repeats \xB7 ring = palindrome depth"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 12,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 7,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "p-3 rounded-lg",
      style: {
        background: "rgba(5,7,13,0.4)"
      },
      "x-file-name": "MirrorGroupsPanel",
      "x-line-number": "16",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MirrorGroupsPanel_16_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "flex flex-wrap items-center",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "17",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MirrorGroupsPanel_17_8",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: groups.map((g, i) => /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)
((react__WEBPACK_IMPORTED_MODULE_0___default().Fragment), {
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)
(_LegoBlock__WEBPACK_IMPORTED_MODULE_1__["default"], {
          text: g,
          index: i,
          selected: selectedIndex === i,
          onClick: onSelect,
          "x-file-name": "MirrorGroupsPanel",
          "x-line-number": "20",
          "x-column": "14",
          "x-component": "LegoBlock",
          "x-id": "MirrorGroupsPanel_20_14",
          "x-dynamic": "true",
          "x-source-type": "external",
          "x-source-var": "groups",
          "x-source-editable": "false",
          "x-array-var": "groups",
          "x-array-item-param": "g"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 20,
          columnNumber: 15
        }, this), i < groups.length - 1 && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
          className: "mirror-bar",
          "aria-hidden": true,
          "x-file-name": "MirrorGroupsPanel",
          "x-line-number": "26",
          "x-column": "40",
          "x-component": "span",
          "x-id": "MirrorGroupsPanel_26_40",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 26,
          columnNumber: 41
        }, this)]
      }, i, true, {
        fileName: _jsxFileName,
        lineNumber: 19,
        columnNumber: 13
      }, this))
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 17,
      columnNumber: 9
    }, this)
```

```
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 16,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "mt-3 flex gap-4 flex-wrap text-xs",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "MirrorGroupsPanel",
      "x-line-number": "31",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MirrorGroupsPanel_31_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Legend, {
        swatch: "#374151",
        label: "Depth 0",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "32",
        "x-column": "8",
        "x-component": "Legend",
        "x-id": "MirrorGroupsPanel_32_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 32,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Legend, {
        swatch: "#10B981",
        label: "Depth 1",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "33",
        "x-column": "8",
        "x-component": "Legend",
        "x-id": "MirrorGroupsPanel_33_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 33,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Legend, {
        swatch: "#F59E0B",
        label: "Depth 2",
        "x-file-name": "MirrorGroupsPanel",
```

```
        "x-line-number": "34",
        "x-column": "8",
        "x-component": "Legend",
        "x-id": "MirrorGroupsPanel_34_8",
        "x-dynamic": "true"
      }, void 0, false, {

    fileName: _jsxFileName,
        lineNumber: 34,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Legend, {
        swatch: "#06B6D4",
        label: "Depth 3",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "35",
        "x-column": "8",
        "x-component": "Legend",
        "x-id": "MirrorGroupsPanel_35_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 35,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)(Legend, {
        swatch: "#E024A6",
        label: "Depth 4+",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "36",
        "x-column": "8",
        "x-component": "Legend",
        "x-id": "MirrorGroupsPanel_36_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 36,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "flex items-center gap-2",
        "x-file-name": "MirrorGroupsPanel",
        "x-line-number": "37",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MirrorGroupsPanel_37_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
```

```
          className: "mirror-bar",
          style: {
            display: "inline-block"
          },
          "x-file-name": "MirrorGroupsPanel",
          "x-line-number": "38",
          "x-column": "10",
          "x-component": "span",
          "x-id": "MirrorGroupsPanel_38_10",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 38,
          columnNumber: 11
        }, this), " mirror"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 37,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 31,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 6,
    columnNumber: 5
  }, this);
}
_c = MirrorGroupsPanel;
function Legend({
  swatch,
  label
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
    className: "flex items-center gap-2",
    "x-file-name": "MirrorGroupsPanel",
    "x-line-number": "47",
    "x-column": "4",
    "x-component": "span",
    "x-id": "MirrorGroupsPanel_47_4",
    "x-dynamic": "true",
    "x-source-type": "prop",
    "x-source-var": "label",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
      style: {
        display: "inline-block",
        width: 12,
        height: 12,
        background: swatch,
        borderRadius: 3
      },
      "x-file-name": "MirrorGroupsPanel",
      "x-line-number": "48",
      "x-column": "6",
      "x-component": "span",
      "x-id": "MirrorGroupsPanel_48_6",
      "x-dynamic": "false"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 48,
      columnNumber: 7
    }, this), label]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 47,
    columnNumber: 5
  }, this);
}
_c2 = Legend;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "MirrorGroupsPanel");
__webpack_require__.$Refresh$.register(_c2, "Legend");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
```

```
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/MotifScanner.jsx"
/*!*****************************************!*\
  !*** ./src/components/MotifScanner.jsx ***!
  \*****************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ MotifScanner)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var _lib_fasta__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../lib/fasta */ "./src/lib/fasta.js");
/* harmony import */ var _lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../lib/mirrorGroups */ "./src/lib/mirrorGroups.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/MotifScanner.jsx",
  _s = __webpack_require__.$Refresh$.signature();
```

```
function MotifScanner({
  seqA,
  seqB
}) {
  _s();
  const [raw, setRaw] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(">TATA-
box\nTATAAA\n>KOZAK\nGCCACC\n");
  const [hits, setHits] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)({
    A: [],
    B: []
  });
  const scan = () => {
    const motifs = raw.split(/(?=^>)/m).map(block =>
(0,_lib_fasta__WEBPACK_IMPORTED_MODULE_2__.parseFasta)(block)).filter(m => m.sequence);
    if (!motifs.length) {
      sonner__WEBPACK_IMPORTED_MODULE_1__.toast.error("No motifs parsed");
      return;
    }
    const hitFor = seq => {
      const list = [];
      motifs.forEach(m => {
        const fwd = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_3__.findAll)(seq,
m.sequence).map(pos => ({
          name: m.name,
          motif: m.sequence,
          strand: "+",
          pos
        }));
        const rc =
(0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_3__.reverseComplement)(m.sequence);
        const rev = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_3__.findAll)(seq,
rc).map(pos => ({
          name: m.name,
          motif: rc,
          strand: "-",
          pos
        }));
        list.push(...fwd, ...rev);
      });
      return list.sort((a, b) => a.pos - b.pos);
    };
    setHits({
      A: hitFor(seqA),
      B: hitFor(seqB)
    });
    sonner__WEBPACK_IMPORTED_MODULE_1__.toast.success(`Scanned · A:$
{hitFor(seqA).length} B:${hitFor(seqB).length} hits`);
  };
```

```
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "motif-scanner",
    "x-file-name": "MotifScanner",
    "x-line-number": "34",
    "x-column": "4",
    "x-component": "div",
    "x-id": "MotifScanner_34_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "MotifScanner",
      "x-line-number": "35",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MotifScanner_35_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        "x-file-name": "MotifScanner",
        "x-line-number": "36",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MotifScanner_36_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "MotifScanner",
          "x-line-number": "37",
          "x-column": "10",
          "x-component": "div",
          "x-id": "MotifScanner_37_10",
          "x-dynamic": "false",
          children: "Known-function motifs"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 37,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "MotifScanner",
          "x-line-number": "38",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "MotifScanner_38_10",
```

```
          "x-dynamic": "false",
          children: "Scan both strands for exact matches"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 38,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 36,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("button", {
        className: "btn btn-primary",
        onClick: scan,
        "data-testid":
 "motif-scan-btn",
        "x-file-name": "MotifScanner",
        "x-line-number": "40",
        "x-column": "8",
        "x-component": "button",
        "x-id": "MotifScanner_40_8",
        "x-dynamic": "false",
        children: "Scan A & B"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 40,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 35,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("textarea", {
      className: "textarea",
      value: raw,
      onChange: e => setRaw(e.target.value),
      "data-testid": "motif-textarea",
      "x-file-name": "MotifScanner",
      "x-line-number": "42",
      "x-column": "6",
      "x-component": "textarea",
      "x-id": "MotifScanner_42_6",
      "x-dynamic": "false"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 42,
      columnNumber: 7
```

```
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "grid grid-cols-2 gap-4 mt-4",
      "x-file-name": "MotifScanner",
      "x-line-number": "43",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MotifScanner_43_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)(HitPanel, {
        label: "Hits in A",
        hits: hits.A,
        testid: "hits-a",
        "x-file-name": "MotifScanner",
        "x-line-number": "44",
        "x-column": "8",
        "x-component": "HitPanel",
        "x-id": "MotifScanner_44_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 44,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)(HitPanel, {
        label: "Hits in B",
        hits: hits.B,
        testid: "hits-b",
        "x-file-name": "MotifScanner",
        "x-line-number": "45",
        "x-column": "8",
        "x-component": "HitPanel",
        "x-id": "MotifScanner_45_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 45,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 43,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 34,
    columnNumber: 5
```

```
  }, this);
}
_s(MotifScanner, "5OiM8eZJMGyCX5HnDl75ppdqFTw=");
_c = MotifScanner;
function HitPanel({
  label,
  hits,
  testid
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
    className: "p-3 rounded-lg",
    style: {
      background: "rgba(5,7,13,0.4)"
    },
    "data-testid": testid,
    "x-file-name": "MotifScanner",
    "x-line-number": "53",
    "x-column": "4",
    "x-component": "div",
    "x-id": "MotifScanner_53_4",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "eyebrow mb-2",
      "x-file-name": "MotifScanner",
      "x-line-number": "54",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MotifScanner_54_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "label",
      "x-source-editable": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        "data-ve-dynamic": "true",
        "x-excluded": "true",
        style: {
          display: "contents"
        },
        "x-file-name": "MotifScanner",
        "x-line-number": "54",
        "x-column": "6",
        "x-component": "div",
        "x-id": "MotifScanner_54_6_expr0",
        "x-dynamic": "true",
```

```
        "x-source-type": "prop",
        "x-source-var": "label",
        "x-source-editable": "false",
        children: label
      }, void 0, false), " \xB7 ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        "data-ve-dynamic": "true",
        "x-excluded": "true",
        style: {
          display: "contents"
        },
        "x-file-name": "MotifScanner",
        "x-line-number": "54",
        "x-column": "6",
        "x-component": "div",
        "x-id": "MotifScanner_54_6_expr2",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "hits",
        "x-source-path": "length",
        "x-source-editable": "false",
        children: hits.length
      }, void 0, false)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 54,
      columnNumber: 7
    }, this), hits.length === 0 ? /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "text-xs",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "MotifScanner",
      "x-line-number": "56",
      "x-column": "8",
      "x-component": "div",
      "x-id": "MotifScanner_56_8",
      "x-dynamic": "false",
      children: "No hits yet."
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 56,
      columnNumber: 9
    }, this) : /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "scroll-x",
      style: {
        maxHeight: 160,
```

```
      overflowY: "auto"
    },
    "x-file-name": "MotifScanner",
    "x-line-number": "58",
    "x-column": "8",
    "x-component": "div",
    "x-id": "MotifScanner_58_8",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: hits.map((h, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "font-mono text-xs py-1 flex items-center gap-2",
      "x-file-name": "MotifScanner",
      "x-line-number": "60",
      "x-column": "12",
      "x-component": "div",
      "x-id": "MotifScanner_60_12",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        style: {
          color: "var(--teal)"
        },
        "x-file-name": "MotifScanner",
        "x-line-number": "61",
        "x-column": "14",
        "x-component": "span",
        "x-id": "MotifScanner_61_14",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "hits",
        "x-source-path": "name",
        "x-source-editable": "false",
        "x-array-var": "hits",
        "x-array-item-param": "h",
        children: h.name
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 61,
        columnNumber: 15
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MotifScanner",
        "x-line-number": "62",
        "x-column": "14",
```

```
        "x-component": "span",
        "x-id": "MotifScanner_62_14",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "hits",
        "x-source-path": "strand",
        "x-source-editable": "false",
        "x-array-var": "hits",
        "x-array-item-param": "h",
        children: h.strand
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 62,
        columnNumber: 15
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        "x-file-name": "MotifScanner",
        "x-line-number": "63",
        "x-column": "14",
        "x-component": "span",
        "x-id": "MotifScanner_63_14",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "hits",
        "x-source-path": "motif",
        "x-source-editable": "false",
        "x-array-var": "hits",
        "x-array-item-param": "h",
        children: h.motif
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 63,
        columnNumber: 15
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MotifScanner",
        "x-line-number": "64",
        "x-column": "14",
        "x-component": "span",
        "x-id": "MotifScanner_64_14",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "hits",
        "x-source-path": "pos",
        "x-source-editable": "false",
        "x-array-var": "hits",
```

```
          "x-array-item-param": "h",
          children: ["@ ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "MotifScanner",
            "x-line-number": "64",
            "x-column": "14",
            "x-component": "span",
            "x-id": "MotifScanner_64_14_expr1",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "hits",
            "x-source-path": "pos",
            "x-source-editable": "false",
            "x-array-var": "hits",
            "x-array-item-param": "h",
            children: h.pos
          }, void 0, false)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 64,
          columnNumber: 15
        }, this)]
      }, i, true, {
        fileName: _jsxFileName,
        lineNumber: 60,
        columnNumber: 13
      }, this))
    }, void 0, false,
 {
      fileName: _jsxFileName,
      lineNumber: 58,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 53,
    columnNumber: 5
  }, this);
}
_c2 = HitPanel;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "MotifScanner");
__webpack_require__.$Refresh$.register(_c2, "HitPanel");
```

```
const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/MusicalStaff.jsx"
/*!*****************************************!*\
  !*** ./src/components/MusicalStaff.jsx ***!
  \*****************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ MusicalStaff)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _lib_audio__WEBPACK_IMPORTED_MODULE_1__ =
```

```
__webpack_require__(/*! ../lib/audio */ "./src/lib/audio.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/MusicalStaff.jsx";



/**
 * SVG music staff renderer.
 * We use two 5-line staves (treble + bass, purely decorative for our diatonic
 * pentatonic mapping) and place a note head per symbol.
 *
 * Position mapping: we treat semitone steps above C4 and compute a staff
 * position in "diatonic slots" so pentatonic notes land on lines/spaces.
 *   step -> slot :  0(C4)=0, 2(D4)=1, 4(E4)=2, 7(G4)=4, 9(A4)=5
 *   step -> slot : 12(C5)=7, 14(D5)=8, 16(E5)=9, 19(G5)=11, 21(A5)=12
 */

const STEP_TO_SLOT = {
  0: 0,
  2: 1,
  4: 2,
  7: 4,
  9: 5,
  12: 7,
  14: 8,
  16: 9,
  19: 11,
  21: 12
};
function symToStep(sym, type) {
  const freq = type === "digits" ?
_lib_audio__WEBPACK_IMPORTED_MODULE_1__.DIGIT_MAP[sym] :
_lib_audio__WEBPACK_IMPORTED_MODULE_1__.DNA_MAP[sym === null || sym === void 0 ?
void 0 : sym.toUpperCase()];
  if (!freq) return null;
  const step =
Object.entries(_lib_audio__WEBPACK_IMPORTED_MODULE_1__.NOTE_STEPS).find(([_, v]) =>
Math.abs(freqOf(_) - freq) < 0.5);
  return step ? _lib_audio__WEBPACK_IMPORTED_MODULE_1__.NOTE_STEPS[step[0]] : null;
}
function freqOf(name) {
  const table = {
```

```
    C4: 261.63,
    D4: 293.66,
    E4: 329.63,
    G4: 392.0,
    A4: 440.0,
    C5: 523.25,
    D5: 587.33,
    E5: 659.25,
    G5: 783.99,
    A5: 880.0
  };
  return table[name];
}
function MusicalStaff({
  symbols,
  type,
  playhead = -1,
  maxNotes = 96
}) {
  const notes = (symbols || []).slice(0, maxNotes);
  const w = Math.max(560, 40 + notes.length * 22);
  const staffX = 60;
  const usableW = w - staffX - 40;
  const noteSpacing = notes.length > 0 ? Math.min(22, usableW / Math.max(1, notes.length)) : 22;

  // Staff geometry
  const trebleTop = 40; // top line y
  const bassTop = 160; // top line y
  const lineGap = 8; // gap between staff lines
  // slot 0 (C4) sits one ledger line below treble bottom staff for typical placement.
  // Simpler mapping we'll use directly (visual):
  //   Treble: slots 5..12 map to y from bottomStaff line up by (slot-5)*4
  //   Bass:   slots 0..4 map to y from bottomBass line up by slot*4
  const slotToY = slot => {
    if (slot >= 5) {
      // Treble clef region
      const trebleBottom = trebleTop + 4 * lineGap; // e.g., 72
      return trebleBottom + (5 - slot) * (lineGap / 2) * 2; // 4px per slot
    }
    // Bass clef region
    const bassBottom = bassTop + 4 * lineGap;
    return bassBottom + (0 - slot) * (lineGap / 2) * 2; // slot 0 sits on middle-C ledger line
  };
  const staffColor = "rgba(229,231,235,0.35)";
  const noteColor = "#00f0ff";
  const drone = "#ffb000";
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "panel p-5 scroll-x",
```

```
    "data-testid": "musical-staff-container",
    "x-file-name": "MusicalStaff",
    "x-line-number": "61",
    "x-column": "4",
    "x-component": "div",
    "x-id": "MusicalStaff_61_4",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "MusicalStaff",
      "x-line-number": "62",
      "x-column": "6",
      "x-component": "div",
      "x-id": "MusicalStaff_62_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        "x-file-name": "MusicalStaff",
        "x-line-number": "63",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MusicalStaff_63_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "MusicalStaff",
          "x-line-number": "64",
          "x-column": "10",
          "x-component": "div",
          "x-id": "MusicalStaff_64_10",
          "x-dynamic": "false",
          children: "Musical staff"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 64,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "MusicalStaff",
          "x-line-number": "65",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "MusicalStaff_65_10",
          "x-dynamic": "false",
```

```
          children: "Sequence, engraved"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 65,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 63,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
        className: "text-xs",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "MusicalStaff",
        "x-line-number": "67",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MusicalStaff_67_8",
        "x-dynamic": "false",
        children: "Treble + bass \xB7 pentatonic mapping \xB7 amber line = 432 Hz drone"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 67,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 62,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("svg", {
      width: w,
      height: 230,
      style: {
        display: "block",
        minWidth: w
      },
      "x-file-name": "MusicalStaff",
      "x-line-number": "71",
      "x-column": "6",
      "x-component": "svg",
      "x-id": "MusicalStaff_71_6",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: [[0, 1, 2, 3, 4].map(i => /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("line", {
        x1: staffX,
        x2: w - 20,
        y1: trebleTop + i * lineGap,
        y2: trebleTop + i * lineGap,
        stroke: staffColor,
        strokeWidth: 1,
        "x-file-name": "MusicalStaff",
        "x-line-number": "74",
        "x-column": "10",
        "x-component": "line",
        "x-id": "MusicalStaff_74_10",
        "x-dynamic": "false"
      }, `t${i}`, false, {
        fileName: _jsxFileName,
        lineNumber: 74,
        columnNumber: 11
      }, this)), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("text", {
        x: 22,
        y: trebleTop + 3 * lineGap - 2,
        fill: "var(--teal)",
        fontSize: 36,
        fontFamily: "Outfit",
        "x-file-name": "MusicalStaff",
        "x-line-number": "84",
        "x-column": "8",
        "x-component": "text",
        "x-id": "MusicalStaff_84_8",
        "x-dynamic": "false",
        children: "\uD834\uDD1E"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 84,
        columnNumber: 9
      }, this), [0, 1, 2, 3, 4].map(i => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("line", {
        x1: staffX,
        x2: w - 20,
        y1: bassTop + i * lineGap,
        y2: bassTop + i * lineGap,

       stroke: staffColor,
        strokeWidth: 1,
        "x-file-name": "MusicalStaff",
        "x-line-number": "89",
        "x-column": "10",
        "x-component": "line",
        "x-id": "MusicalStaff_89_10",
```

```
        "x-dynamic": "false"
      }, `b${i}`, false, {
        fileName: _jsxFileName,
        lineNumber: 89,
        columnNumber: 11
      }, this)), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("text", {
        x: 22,
        y: bassTop + 2 * lineGap + 5,
        fill: "var(--amber)",
        fontSize: 28,
        fontFamily: "Outfit",
        "x-file-name": "MusicalStaff",
        "x-line-number": "99",
        "x-column": "8",
        "x-component": "text",
        "x-id": "MusicalStaff_99_8",
        "x-dynamic": "false",
        children: "\uD834\uDD22"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 99,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("line", {
        x1: staffX,
        x2: w - 20,
        y1: (trebleTop + 4 * lineGap + bassTop) / 2,
        y2: (trebleTop + 4 * lineGap + bassTop) / 2,
        stroke: drone,
        strokeDasharray: "2 6",
        strokeWidth: 1,
        opacity: 0.6,
        "x-file-name": "MusicalStaff",
        "x-line-number": "104",
        "x-column": "8",
        "x-component": "line",
        "x-id": "MusicalStaff_104_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 104,
        columnNumber: 9
      }, this), notes.map((s, i) => {
        const step = symToStep(s, type);
        if (step == null) return null;
        const slot = STEP_TO_SLOT[step];
        const cx = staffX + 12 + i * noteSpacing;
        const cy = slotToY(slot);
```

```
      const isPlay = i === playhead;
      // stem
      const stemUp = slot < 6;
      return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("g", {
        "x-file-name": "MusicalStaff",
        "x-line-number": "126",
        "x-column": "12",
        "x-component": "g",
        "x-id": "MusicalStaff_126_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("ellipse", {
          cx: cx,
          cy: cy,
          rx: 4.5,
          ry: 3.4,
          fill: isPlay ? "#ffb000" : noteColor,
          opacity: isPlay ? 1 : 0.9,
          stroke: isPlay ? "#fff" : "none",
          strokeWidth: isPlay ? 1 : 0,
          transform: `rotate(-18 ${cx} ${cy})`,
          "x-file-name": "MusicalStaff",
          "x-line-number": "127",
          "x-column": "14",
          "x-component": "ellipse",
          "x-id": "MusicalStaff_127_14",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 127,
          columnNumber: 15
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("line", {
          x1: cx + (stemUp ? 4 : -4),
          y1: cy,
          x2: cx + (stemUp ? 4 : -4),
          y2: cy + (stemUp ? -20 : 20),
          stroke: isPlay ? "#ffb000" : noteColor,
          strokeWidth: 1.2,
          opacity: 0.9,
          "x-file-name": "MusicalStaff",
          "x-line-number": "138",
          "x-column": "14",
          "x-component": "line",
          "x-id": "MusicalStaff_138_14",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
```

```
          lineNumber: 138,
          columnNumber: 15
        }, this)]
      }, i, true, {
        fileName: _jsxFileName,
        lineNumber: 126,
        columnNumber: 13
      }, this);
    }), playhead >= 0 && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("line", {
      x1: staffX + 12 + playhead * noteSpacing,
      x2: staffX + 12 + playhead * noteSpacing,
      y1: trebleTop - 8,
      y2: bassTop + 4 * lineGap + 8,
      stroke: "#ffb000",
      strokeWidth: 1.2,
      opacity: 0.6,
      "x-file-name": "MusicalStaff",
      "x-line-number": "153",
      "x-column": "10",
      "x-component": "line",
      "x-id": "MusicalStaff_153_10",
      "x-dynamic": "false"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 153,
      columnNumber: 11
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 71,
    columnNumber: 7
  }, this), symbols && symbols.length > maxNotes && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("div", {
    className: "mt-2 text-xs",
    style: {
      color: "var(--muted)"
    },
    "x-file-name": "MusicalStaff",
    "x-line-number": "165",
    "x-column": "8",
    "x-component": "div",
    "x-id": "MusicalStaff_165_8",
    "x-dynamic": "true",
    "x-source-type": "prop",
    "x-source-var": "maxNotes",
    "x-source-editable": "false",
    children: ["Showing first ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
```

```
        "data-ve-dynamic": "true",
        "x-excluded": "true",
        style: {
          display: "contents"
        },
        "x-file-name": "MusicalStaff",
        "x-line-number": "165",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MusicalStaff_165_8_expr1",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "maxNotes",
        "x-source-editable": "false",
        children: maxNotes
      }, void 0, false), " of ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_2__.jsxDEV)("span", {
        "data-ve-dynamic": "true",
        "x-excluded": "true",
        style: {
          display: "contents"
        },
        "x-file-name": "MusicalStaff",
        "x-line-number": "165",
        "x-column": "8",
        "x-component": "div",
        "x-id": "MusicalStaff_165_8_expr3",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "symbols",
        "x-source-path": "length",
        "x-source-editable": "false",
        children: symbols.length
      }, void 0, false), " symbols \xB7 playback still uses full length"]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 165,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 61,
    columnNumber: 5
  }, this);
}
_c = MusicalStaff;
var _c;
__webpack_require__.$Refresh$.register(_c, "MusicalStaff");
```

```
const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/Remainders.jsx"
/*!***************************************!*\
  !*** ./src/components/Remainders.jsx ***!
  \***************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ Remainders)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__ =
```

```
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/Remainders.jsx",
  _s = __webpack_require__.$Refresh$.signature();


/** Compute remainders — regions of A / B not covered by matched blocks. */

function remainders(seq, blocks, side) {
  const posKey = side === "A" ? "aPos" : "bPos";
  const sorted = [...blocks].sort((x, y) => x[posKey] - y[posKey]);
  const out = [];
  let cursor = 0;
  for (const b of sorted) {
    if (b[posKey] > cursor) out.push({
      start: cursor,
      end: b[posKey],
      text: seq.slice(cursor, b[posKey])
    });
    cursor = b[posKey] + b.len;
  }
  if (cursor < seq.length) out.push({
    start: cursor,
    end: seq.length,
    text: seq.slice(cursor)
  });
  return out;
}
function Remainders({
  seqA,
  seqB,
  blocks
}) {
  _s();
  const remA = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => remainders(seqA,
blocks, "A"), [seqA, blocks]);
  const remB = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => remainders(seqB,
blocks, "B"), [seqB, blocks]);
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "remainders",

 "x-file-name": "Remainders",
```

```
    "x-line-number": "21",
    "x-column": "4",
    "x-component": "div",
    "x-id": "Remainders_21_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "Remainders",
      "x-line-number": "22",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Remainders_22_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
        "x-file-name": "Remainders",
        "x-line-number": "23",
        "x-column": "8",
        "x-component": "div",
        "x-id": "Remainders_23_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "Remainders",
          "x-line-number": "24",
          "x-column": "10",
          "x-component": "div",
          "x-id": "Remainders_24_10",
          "x-dynamic": "false",
          children: "Remainders"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 24,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "Remainders",
          "x-line-number": "25",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "Remainders_25_10",
          "x-dynamic": "false",
          children: "Regions unaccounted for by matched blocks"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 25,
```

```
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 23,
        columnNumber: 9
      }, this)
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 22,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
      className: "grid grid-cols-1 md:grid-cols-2 gap-4",
      "x-file-name": "Remainders",
      "x-line-number": "28",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Remainders_28_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)(RemPanel, {
        label: "A remainders",
        list: remA,
        testid: "rem-a",
        "x-file-name": "Remainders",
        "x-line-number": "29",
        "x-column": "8",
        "x-component": "RemPanel",
        "x-id": "Remainders_29_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 29,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)(RemPanel, {
        label: "B remainders",
        list: remB,
        testid: "rem-b",
        "x-file-name": "Remainders",
        "x-line-number": "30",
        "x-column": "8",
        "x-component": "RemPanel",
        "x-id": "Remainders_30_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 30,
```

```
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 28,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 21,
    columnNumber: 5
  }, this);
}
_s(Remainders, "CQJYWuW+Teng968aZd8Aslfyc38=");
_c = Remainders;
function RemPanel({
  label,
  list,
  testid
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
    className: "p-3 rounded-lg",
    style: {
      background: "rgba(5,7,13,0.4)"
    },
    "data-testid": testid,
    "x-file-name": "Remainders",
    "x-line-number": "37",
    "x-column": "4",
    "x-component": "div",
    "x-id": "Remainders_37_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
      className: "eyebrow mb-2",
      "x-file-name": "Remainders",
      "x-line-number": "38",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Remainders_38_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "label",
      "x-source-editable": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
        "data-ve-dynamic": "true",
        "x-excluded": "true",
```

```
      style: {
        display: "contents"
      },
      "x-file-name": "Remainders",
      "x-line-number": "38",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Remainders_38_6_expr0",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "label",
      "x-source-editable": "false",
      children: label
    }, void 0, false), " \xB7 ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
      "data-ve-dynamic": "true",
      "x-excluded": "true",
      style: {
        display: "contents"
      },
      "x-file-name": "Remainders",
      "x-line-number": "38",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Remainders_38_6_expr2",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "list",
      "x-source-path": "length",
      "x-source-editable": "false",
      children: list.length
    }, void 0, false)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 38,
    columnNumber: 7
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
    style: {
      maxHeight: 220,
      overflowY: "auto"
    },
    "x-file-name": "Remainders",
    "x-line-number": "39",
    "x-column": "6",
    "x-component": "div",
    "x-id": "Remainders_39_6",
    "x-dynamic": "true",
    "x-source-type": "computed",
```

```
      "x-source-editable": "false",
      children: list.map((r, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
        className: "font-mono text-xs py-1",
        "x-file-name": "Remainders",
        "x-line-number": "41",
        "x-column": "10",
        "x-component": "div",
        "x-id": "Remainders_41_10",
        "x-dynamic": "true",
        "x-source-type": "unknown",
        "x-source-editable": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
          style: {
            color: "var(--teal)"
          },
          "x-file-name": "Remainders",
          "x-line-number": "42",
          "x-column": "12",
          "x-component": "span",
          "x-id": "Remainders_42_12",
          "x-dynamic": "true",
          "x-source-type": "static-imported",
          "x-source-var": "list",
          "x-source-path": "start",
          "x-source-editable": "false",
          "x-array-var": "list",
          "x-array-item-param": "r",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "Remainders",
            "x-line-number": "42",
            "x-column": "12",
            "x-component": "span",
            "x-id": "Remainders_42_12_expr0",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "list",
            "x-source-path": "start",
            "x-source-editable": "false",
            "x-array-var": "list",
            "x-array-item-param": "r",
            children: r.start
```

```
        }, void 0, false), "\u2013", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "Remainders",
          "x-line-number": "42",
          "x-column": "12",
          "x-component": "span",
          "x-id": "Remainders_42_12_expr2",
          "x-dynamic": "true",
          "x-source-type": "static-imported",
          "x-source-var": "list",
          "x-source-path": "end",
          "x-source-editable": "false",
          "x-array-var": "list",
          "x-array-item-param": "r",
          children: r.end
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 42,
        columnNumber: 13
      }, this), " ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "Remainders",
        "x-line-number": "43",
        "x-column": "12",
        "x-component": "span",
        "x-id": "Remainders_43_12",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "list",
        "x-source-path": "text.length",
        "x-source-editable": "false",
        "x-array-var": "list",
        "x-array-item-param": "r",
        children: ["(", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
```

```
          "x-file-name": "Remainders",
          "x-line-number": "43",
          "x-column": "12",
          "x-component": "span",
          "x-id": "Remainders_43_12_expr1",
          "x-dynamic": "true",
          "x-source-type":
 "static-imported",
          "x-source-var": "list",
          "x-source-path": "text.length",
          "x-source-editable": "false",
          "x-array-var": "list",
          "x-array-item-param": "r",
          children: r.text.length
        }, void 0, false), " bp)"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 43,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
        style: {
          color: "var(--text)"
        },
        className: "truncate max-w-full",
        "x-file-name": "Remainders",
        "x-line-number": "44",
        "x-column": "12",
        "x-component": "div",
        "x-id": "Remainders_44_12",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: [r.text.slice(0, 80), r.text.length > 80 ? "…" : ""]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 44,
        columnNumber: 13
      }, this)]
    }, i, true, {
      fileName: _jsxFileName,
      lineNumber: 41,
      columnNumber: 11
    }, this))
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 39,
    columnNumber: 7
  }, this)]
```

```
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 37,
    columnNumber: 5
  }, this);
}
_c2 = RemPanel;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "Remainders");
__webpack_require__.$Refresh$.register(_c2, "RemPanel");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/SchillingerDevices.jsx"
/*!***********************************************!*\
  !*** ./src/components/SchillingerDevices.jsx ***!
  \***********************************************/
(module, __webpack_exports__, __webpack_require__) {
```

```
"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ SchillingerDevices)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _lib_audio__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../lib/audio */ "./src/lib/audio.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/play.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/square.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/SchillingerDevices.jsx",
  _s = __webpack_require__.$Refresh$.signature();




/** Retrograde: reverse the sequence. */

function retrograde(s) {
  return s.split("").reverse().join("");
}
/** Circular permutation by k positions. */
function rotate(s, k) {
  const n = s.length;
  if (!n) return s;
  const kk = (k % n + n) % n;
  return s.slice(kk) + s.slice(0, kk);
}

/** Pitch inversion: reflect each symbol's pitch around the block's centroid.
 * We map to frequency, compute mean, invert around it, then pick the nearest
 * available note within the same scale. */
function pitchInverted(symbols, type) {
  const freqs = symbols.map(s =>
(0,_lib_audio__WEBPACK_IMPORTED_MODULE_1__.symbolToFreq)(s, type)).filter(f => f !=
```

```
null);
  if (!freqs.length) return symbols.slice();
  const mean = freqs.reduce((a, b) => a + b, 0) / freqs.length;
  // Build reverse maps
  const map = type === "digits" ? {
    "0": 261.63,
    "1": 293.66,
    "2": 329.63,
    "3": 392.0,
    "4": 440.0,
    "5": 523.25,
    "6": 587.33,
    "7": 659.25,
    "8": 783.99,
    "9": 880.0
  } : {
    A: 261.63,
    T: 293.66,
    G: 329.63,
    C: 392.0,
    N: 440.0
  };
  const entries = Object.entries(map);
  return symbols.map(s => {
    const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_1__.symbolToFreq)(s, type);
    if (!f) return s;
    const inv = 2 * mean - f;
    let best = entries[0];
    let bestDist = Infinity;
    for (const e of entries) {
      const d = Math.abs(e[1] - inv);
      if (d < bestDist) {
        best = e;
        bestDist = d;
      }
    }
    return best[0];
  });
}
function SchillingerDevices({
  block,
  type,
  index
}) {
  _s();
  const [order, setOrder] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("none");
  const [rot, setRot] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(1);
  const [pitchMode, setPitchMode] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)
("normal");
```

```
  const [duration, setDuration] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(1);
  const [wave, setWave] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("sine");
  const [octave, setOctave] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(0);
  const [loop, setLoop] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(false);
  const transformed = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => {
    if (!block) return "";
    let s = block;
    if (order === "retrograde") s = retrograde(s);else if (order === "circular") s = rotate(s, rot);
    let syms = s.split("");
    if (pitchMode === "inverted") syms = pitchInverted(syms, type);
    return syms;
  }, [block, order, rot, pitchMode, type]);
  const play = () => {
    if (!transformed.length) return;
    const engine = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_1__.getAudio)();
    engine.stop();
    engine.ensure();
    const step = 1 / 6 * duration;
    const octMult = Math.pow(2, octave);
    const runOnce = startAt => {
      for (let i = 0; i < transformed.length; i++) {
        const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_1__.symbolToFreq)
(transformed[i], type);
        if (!f) continue;
        engine.playNote({
          freq: f * octMult,
          when: startAt + i * step,
          dur: step * 0.9,
          wave
        });
      }
      return startAt + transformed.length * step + 0.05;
    };
    const t0 = engine.ctx.currentTime + 0.1;
    let end = runOnce(t0);
    if (loop) end = runOnce(end);
  };
  const stop = () => (0,_lib_audio__WEBPACK_IMPORTED_MODULE_1__.getAudio)().stop();
  if (!block) {
    return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "panel p-5",
      "data-testid": "schillinger-devices",
      "x-file-name": "SchillingerDevices",
      "x-line-number": "78",
      "x-column": "6",
      "x-component": "div",
      "x-id": "SchillingerDevices_78_6",
      "x-dynamic": "false",
```

```
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "79",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_79_8",
        "x-dynamic": "false",
        children: "Schillinger devices"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 79,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "mt-2 text-sm",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "SchillingerDevices",
        "x-line-number": "80",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_80_8",
        "x-dynamic": "false",
        children: "Click a Lego block above to isolate it for transformation."
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 80,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 78,
      columnNumber: 7
    }, this);
  }
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "schillinger-devices",
    "x-file-name": "SchillingerDevices",
    "x-line-number": "88",
    "x-column": "4",
    "x-component": "div",
    "x-id": "SchillingerDevices_88_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
    className: "flex items-baseline justify-between mb-3",
    "x-file-name": "SchillingerDevices",
    "x-line-number": "89",
    "x-column": "6",
    "x-component": "div",

    "x-id": "SchillingerDevices_89_6",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      "x-file-name": "SchillingerDevices",
      "x-line-number": "90",
      "x-column": "8",
      "x-component": "div",
      "x-id": "SchillingerDevices_90_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "91",
        "x-column": "10",
        "x-component": "div",
        "x-id": "SchillingerDevices_91_10",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "index",
        "x-source-editable": "false",
        children: ["Isolated group #", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "SchillingerDevices",
          "x-line-number": "91",
          "x-column": "10",
          "x-component": "div",
          "x-id": "SchillingerDevices_91_10_expr1",
          "x-dynamic": "true",
          "x-source-type": "prop",
          "x-source-var": "index",
          "x-source-editable": "false",
          children: index
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
```

```
          lineNumber: 91,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("h3", {
          className: "font-heading text-xl font-semibold mt-1",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "92",
          "x-column": "10",
          "x-component": "h3",
          "x-id": "SchillingerDevices_92_10",
          "x-dynamic": "false",
          children: "Schillinger devices"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 92,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 90,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "pill",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "94",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_94_8",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "block",
        "x-source-editable": "false",
        children: block
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 94,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 89,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "grid grid-cols-2 lg:grid-cols-4 gap-3",
      "x-file-name": "SchillingerDevices",
      "x-line-number": "97",
      "x-column": "6",
```

```
    "x-component": "div",
    "x-id": "SchillingerDevices_97_6",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      "x-file-name": "SchillingerDevices",
      "x-line-number": "98",
      "x-column": "8",
      "x-component": "div",
      "x-id": "SchillingerDevices_98_8",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "eyebrow mb-1",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "99",
        "x-column": "10",
        "x-component": "div",
        "x-id": "SchillingerDevices_99_10",
        "x-dynamic": "false",
        children: "Order"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 99,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("select", {
        className: "select",
        value: order,
        onChange: e => setOrder(e.target.value),
        "data-testid": "order-select",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "100",
        "x-column": "10",
        "x-component": "select",
        "x-id": "SchillingerDevices_100_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "none",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "101",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_101_12",
          "x-dynamic": "false",
          children: "None"
```

```
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 101,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "retrograde",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "102",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_102_12",
          "x-dynamic": "false",
          children: "Retrograde"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 102,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "circular",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "103",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_103_12",
          "x-dynamic": "false",
          children: "Circular permutation"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 103,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 100,
        columnNumber: 11
      }, this), order === "circular" && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "mt-2 flex items-center gap-2",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "106",
        "x-column": "12",
        "x-component": "div",
        "x-id": "SchillingerDevices_106_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("span", {
          className: "text-xs",
```

```
          style: {
            color: "var(--muted)"
          },
          "x-file-name": "SchillingerDevices",
          "x-line-number": "107",
          "x-column": "14",
          "x-component": "span",
          "x-id": "SchillingerDevices_107_14",
          "x-dynamic": "false",
          children: "Rotate"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 107,
          columnNumber: 15
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("input", {
          type: "number",
          className: "input",
          style: {
            width: 80
          },
          value: rot,
          onChange: e => setRot(parseInt(e.target.value) || 0),
          "data-testid": "rotate-input",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "108",
          "x-column": "14",
          "x-component": "input",
          "x-id": "SchillingerDevices_108_14",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 108,
          columnNumber: 15
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 106,
        columnNumber: 13
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 98,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      "x-file-name": "SchillingerDevices",
      "x-line-number": "113",
      "x-column": "8",
```

```
      "x-component": "div",
      "x-id": "SchillingerDevices_113_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "eyebrow mb-1",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "114",
        "x-column": "10",
        "x-component": "div",
        "x-id": "SchillingerDevices_114_10",
        "x-dynamic": "false",
        children: "Pitch"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 114,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("select", {
        className: "select",
        value: pitchMode,
        onChange: e => setPitchMode(e.target.value),
        "data-testid": "pitch-select",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "115",
        "x-column": "10",
        "x-component": "select",
        "x-id": "SchillingerDevices_115_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "normal",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "116",

  "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_116_12",
          "x-dynamic": "false",
          children: "Normal"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 116,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "inverted",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "117",
```

```
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_117_12",
          "x-dynamic": "false",
          children: "Inverted"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 117,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 115,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 113,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      "x-file-name": "SchillingerDevices",
      "x-line-number": "121",
      "x-column": "8",
      "x-component": "div",
      "x-id": "SchillingerDevices_121_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "eyebrow mb-1",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "122",
        "x-column": "10",
        "x-component": "div",
        "x-id": "SchillingerDevices_122_10",
        "x-dynamic": "false",
        children: "Duration"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 122,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("select", {
        className: "select",
        value: duration,
        onChange: e => setDuration(parseFloat(e.target.value)),
        "data-testid": "duration-select",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "123",
```

```
        "x-column": "10",
        "x-component": "select",
        "x-id": "SchillingerDevices_123_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "0.5",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "124",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_124_12",
          "x-dynamic": "false",
          children: "Diminution 0.5\xD7"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 124,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "1",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "125",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_125_12",
          "x-dynamic": "false",
          children: "Normal 1\xD7"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 125,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "2",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "126",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_126_12",
          "x-dynamic": "false",
          children: "Augmentation 2\xD7"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 126,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
```

```
          lineNumber: 123,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 121,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        "x-file-name": "SchillingerDevices",
        "x-line-number": "130",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_130_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
          className: "eyebrow mb-1",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "131",
          "x-column": "10",
          "x-component": "div",
          "x-id": "SchillingerDevices_131_10",
          "x-dynamic": "false",
          children: "Waveform"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 131,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("select", {
          className: "select",
          value: wave,
          onChange: e => setWave(e.target.value),
          "data-testid": "wave-select-schillinger",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "132",
          "x-column": "10",
          "x-component": "select",
          "x-id": "SchillingerDevices_132_10",
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
            value: "sine",
            "x-file-name": "SchillingerDevices",
            "x-line-number": "133",
            "x-column": "12",
            "x-component": "option",
            "x-id": "SchillingerDevices_133_12",
```

```
          "x-dynamic": "false",
          children: "Sine"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 133,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "triangle",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "134",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_134_12",
          "x-dynamic": "false",
          children: "Triangle"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 134,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "square",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "135",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_135_12",
          "x-dynamic": "false",
          children: "Square"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 135,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("option", {
          value: "sawtooth",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "136",
          "x-column": "12",
          "x-component": "option",
          "x-id": "SchillingerDevices_136_12",
          "x-dynamic": "false",
          children: "Sawtooth"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 136,
          columnNumber: 13
        }, this)]
```

```
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 132,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 130,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        "x-file-name": "SchillingerDevices",
        "x-line-number": "140",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_140_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
          className: "eyebrow mb-1",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "141",
          "x-column": "10",
          "x-component": "div",
          "x-id": "SchillingerDevices_141_10",
          "x-dynamic": "false",
          children: "Octave"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 141,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("input", {
          type: "range",
          min: -2,
          max: 2,
          step: 1,
          value: octave,
          onChange: e => setOctave(parseInt(e.target.value)),
          className: "range w-full",
          "data-testid": "octave-slider",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "142",
          "x-column": "10",
          "x-component": "input",
          "x-id": "SchillingerDevices_142_10",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
```

```
          lineNumber: 142,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
          className: "text-xs mt-1",
          style: {
            color: "var(--teal)"
          },
          "x-file-name": "SchillingerDevices",
          "x-line-number": "143",
          "x-column": "10",
          "x-component": "div",
          "x-id": "SchillingerDevices_143_10",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable":
 "false",
          children: octave >= 0 ? `+${octave}` : octave
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 143,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 140,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
        className: "flex items-center gap-2",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "145",
        "x-column": "8",
        "x-component": "div",
        "x-id": "SchillingerDevices_145_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("input", {
          id: "loop",
          type: "checkbox",
          checked: loop,
          onChange: e => setLoop(e.target.checked),
          "data-testid": "loop-toggle",
          "x-file-name": "SchillingerDevices",
          "x-line-number": "146",
          "x-column": "10",
          "x-component": "input",
          "x-id": "SchillingerDevices_146_10",
          "x-dynamic": "false"
```

```
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 146,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("label", {
        htmlFor: "loop",
        className: "text-sm",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "SchillingerDevices",
        "x-line-number": "147",
        "x-column": "10",
        "x-component": "label",
        "x-id": "SchillingerDevices_147_10",
        "x-dynamic": "false",
        children: "Loop once"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 147,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 145,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "col-span-2 flex justify-end gap-2 items-end",
      "x-file-name": "SchillingerDevices",
      "x-line-number": "149",
      "x-column": "8",
      "x-component": "div",
      "x-id": "SchillingerDevices_149_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("button", {
        className: "btn btn-primary",
        onClick: play,
        "data-testid": "schillinger-play",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "150",
        "x-column": "10",
        "x-component": "button",
        "x-id": "SchillingerDevices_150_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)
```

```
(lucide_react__WEBPACK_IMPORTED_MODULE_2__["default"], {
          size: 14,
          "x-file-name": "SchillingerDevices",
          "x-line-number": "150",
          "x-column": "92",
          "x-component": "Play",
          "x-id": "SchillingerDevices_150_92",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 150,
          columnNumber: 93
        }, this), " Play isolated"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 150,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("button", {
        className: "btn",
        onClick: stop,
        "data-testid": "schillinger-stop",
        "x-file-name": "SchillingerDevices",
        "x-line-number": "151",
        "x-column": "10",
        "x-component": "button",
        "x-id": "SchillingerDevices_151_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_3__["default"], {
          size: 14,
          "x-file-name": "SchillingerDevices",
          "x-line-number": "151",
          "x-column": "80",
          "x-component": "Square",
          "x-id": "SchillingerDevices_151_80",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 151,
          columnNumber: 81
        }, this), " Stop"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 151,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
```

```
        fileName: _jsxFileName,
        lineNumber: 149,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 97,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "mt-4 p-3 rounded-lg font-mono text-sm",
      style: {
        background: "rgba(5,7,13,0.4)",
        color: "var(--teal)"
      },
      "x-file-name": "SchillingerDevices",
      "x-line-number": "155",
      "x-column": "6",
      "x-component": "div",
      "x-id": "SchillingerDevices_155_6",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: transformed.join("")
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 155,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_4__.jsxDEV)("div", {
      className: "mt-2 text-xs",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "SchillingerDevices",
      "x-line-number": "158",
      "x-column": "6",
      "x-component": "div",
      "x-id": "SchillingerDevices_158_6",
      "x-dynamic": "false",
      children: "Circular permutation rotates the cell, retrograde reverses it, inversion mirrors the melodic
contour around the block's centroid, augmentation / diminution stretch or compress durations."
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 158,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
```

```
    lineNumber: 88,
    columnNumber: 5
  }, this);
}
_s(SchillingerDevices, "tVB2n5/mFZNhXYw1NLYVocoDh3c=");
_c = SchillingerDevices;
var _c;
__webpack_require__.$Refresh$.register(_c, "SchillingerDevices");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/StatsBar.jsx"
/*!*************************************!*\
  !*** ./src/components/StatsBar.jsx ***!
  \*************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
```

```
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ StatsBar)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/components/StatsBar.jsx";


function StatsBar({
  stats
}) {
  if (!stats) return null;
  const items = [{
    label: "Length",
    value: stats.length
  }, {
    label: "Groups",
    value: stats.groups,
    teal: true
  }, {
    label: "Repeat sites",
    value: stats.repeatSites
  }, {
    label: "Repeat density",
    value: `${(stats.repeatDensity * 100).toFixed(1)}%`
  }, {
    label: "Longest group",
    value: stats.longestGroup
  }, {
    label: "Max depth",
    value: stats.maxDepth
  }, {
    label: "PAM (NGG)",
    value: stats.pam
  }];
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
    className: "panel-strong flex flex-wrap",
```

```
    "data-testid": "sequence-stats-bar",
    "x-file-name": "StatsBar",
    "x-line-number": "15",
    "x-column": "4",
    "x-component": "div",
    "x-id": "StatsBar_15_4",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: items.map(it => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
      className: "stat flex-1 min-w-[120px]",
      "x-file-name": "StatsBar",
      "x-line-number": "20",
      "x-column": "8",
      "x-component": "div",
      "x-id": "StatsBar_20_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div",
 {
        className: "label",
        "x-file-name": "StatsBar",
        "x-line-number": "21",
        "x-column": "10",
        "x-component": "div",
        "x-id": "StatsBar_21_10",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "items",
        "x-source-file-abs": "/app/frontend/src/components/StatsBar.jsx",
        "x-source-line": "5",
        "x-source-path": "label",
        "x-source-editable": "true",
        "x-array-var": "items",
        "x-array-line": "5",
        "x-array-item-param": "it",
        children: it.label
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 21,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_1__.jsxDEV)("div", {
        className: `value ${it.teal ? "teal" : ""}`,
        "x-file-name": "StatsBar",
        "x-line-number": "22",
        "x-column": "10",
        "x-component": "div",
```

```
        "x-id": "StatsBar_22_10",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "items",
        "x-source-file-abs": "/app/frontend/src/components/StatsBar.jsx",
        "x-source-line": "5",
        "x-source-path": "value",
        "x-source-editable": "true",
        "x-array-var": "items",
        "x-array-line": "5",
        "x-array-item-param": "it",
        children: it.value
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 22,
        columnNumber: 11
      }, this)]
    }, it.label, true, {
      fileName: _jsxFileName,
      lineNumber: 20,
      columnNumber: 9
    }, this))
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 15,
    columnNumber: 5
  }, this);
}
_c = StatsBar;
var _c;
__webpack_require__.$Refresh$.register(_c, "StatsBar");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
```

```
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/components/TransportControls.jsx"
/*!**********************************************!*\
  !*** ./src/components/TransportControls.jsx ***!
  \**********************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ TransportControls)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/download.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/play.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/square.js");
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var _lib_audio__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../lib/audio */ "./src/lib/audio.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");
```

```
var _jsxFileName = "/app/frontend/src/components/TransportControls.jsx",
  _s = __webpack_require__.$Refresh$.signature();



function TransportControls({
  symbols,
  type,
  groupBoundaries = [],
  onTick,
  onDone,
  name = "sequence"
}) {
  _s();
  const [tempo, setTempo] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(6);
  const [tuning, setTuning] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(432);
  const [wave, setWave] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("sine");
  const [restOnMirror, setRestOnMirror] =
(0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("rest");
  const play = () => {
    if (!symbols || !symbols.length) {
      sonner__WEBPACK_IMPORTED_MODULE_4__.toast.error("Load a sequence first");
      return;
    }
    (0,_lib_audio__WEBPACK_IMPORTED_MODULE_5__.getAudio)().playSequence({
      symbols,
      type,
      tempo,
      wave,
      tuning,
      restOnMirror,
      groupBoundaries,
      onTick,
      onDone
    });
  };
  const stop = () => {
    (0,_lib_audio__WEBPACK_IMPORTED_MODULE_5__.getAudio)().stop();
    onDone === null || onDone === void 0 ? void 0 : onDone();
  };
  const download = async () => {
    if (!(symbols !== null && symbols !== void 0 && symbols.length)) {
      sonner__WEBPACK_IMPORTED_MODULE_4__.toast.error("Load a sequence first");
      return;
    }
    sonner__WEBPACK_IMPORTED_MODULE_4__.toast.info("Rendering WAV …");
    try {
```

```
      const blob = await (0,_lib_audio__WEBPACK_IMPORTED_MODULE_5__.renderWav)({
        symbols,
        type,
        tempo,
        wave,
        tuning
      });
      const url = URL.createObjectURL(blob);
      const a = document.createElement("a");
      a.href = url;
      a.download = `${name.replace(/[^a-z0-9]+/gi, "_")}_${tuning}hz.wav`;
      a.click();
      URL.revokeObjectURL(url);
      sonner__WEBPACK_IMPORTED_MODULE_4__.toast.success("WAV downloaded");
    } catch (e) {
      sonner__WEBPACK_IMPORTED_MODULE_4__.toast.error("WAV export failed");
    }
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
    className: "panel p-4 flex flex-wrap items-center gap-4",
    "data-testid": "audio-transport-controls",
    "x-file-name": "TransportControls",
    "x-line-number": "61",
    "x-column": "4",
    "x-component": "div",
    "x-id": "TransportControls_61_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "flex items-center gap-2",
      "x-file-name": "TransportControls",
      "x-line-number": "62",
      "x-column": "6",
      "x-component": "div",
      "x-id": "TransportControls_62_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
        className: "btn btn-primary",
        onClick: play,
        "data-testid": "play-btn",
        "x-file-name": "TransportControls",
        "x-line-number": "63",
        "x-column": "8",
        "x-component": "button",
        "x-id": "TransportControls_63_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_2__["default"], {
        size: 14,
        "x-file-name": "TransportControls",
        "x-line-number": "64",
        "x-column": "10",
        "x-component": "Play",
        "x-id": "TransportControls_64_10",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 64,
        columnNumber: 11
       }, this), " Play"]
     }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 63,
      columnNumber: 9
     }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
      className: "btn",
      onClick: stop,
      "data-testid": "stop-btn",
      "x-file-name": "TransportControls",
      "x-line-number": "66",
      "x-column": "8",
      "x-component": "button",
      "x-id": "TransportControls_66_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_3__["default"], {
        size: 14,
        "x-file-name": "TransportControls",
        "x-line-number": "67",
        "x-column": "10",
        "x-component": "Square",
        "x-id": "TransportControls_67_10",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 67,
        columnNumber: 11
       }, this), " Stop"]
     }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 66,
      columnNumber: 9
     }, this), /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
        className: "btn btn-amber",
        onClick: download,
        "data-testid": "download-wav-btn",
        "x-file-name": "TransportControls",
        "x-line-number": "69",
        "x-column": "8",
        "x-component": "button",
        "x-id": "TransportControls_69_8",
        "x-dynamic":
 "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_1__["default"], {
          size: 14,
          "x-file-name": "TransportControls",
          "x-line-number": "70",
          "x-column": "10",
          "x-component": "Download",
          "x-id": "TransportControls_70_10",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 70,
          columnNumber: 11
        }, this), " WAV"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 69,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 62,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "flex items-center gap-3 min-w-[220px]",
      "x-file-name": "TransportControls",
      "x-line-number": "74",
      "x-column": "6",
      "x-component": "div",
      "x-id": "TransportControls_74_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
        className: "eyebrow",
        "x-file-name": "TransportControls",
        "x-line-number": "75",
```

```
        "x-column": "8",
        "x-component": "span",
        "x-id": "TransportControls_75_8",
        "x-dynamic": "false",
        children: "Tempo"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 75,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("input", {
        type: "range",
        min: 1,
        max: 20,
        value: tempo,
        onChange: e => setTempo(parseInt(e.target.value)),
        className: "range flex-1",
        "data-testid": "tempo-slider",
        "x-file-name": "TransportControls",
        "x-line-number": "76",
        "x-column": "8",
        "x-component": "input",
        "x-id": "TransportControls_76_8",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 76,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
        className: "font-mono text-xs",
        style: {
          color: "var(--teal)"
        },
        "x-file-name": "TransportControls",
        "x-line-number": "85",
        "x-column": "8",
        "x-component": "span",
        "x-id": "TransportControls_85_8",
        "x-dynamic": "true",
        "x-source-type": "state",
        "x-source-var": "tempo",
        "x-source-editable": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
```

```
        },
        "x-file-name": "TransportControls",
        "x-line-number": "85",
        "x-column": "8",
        "x-component": "span",
        "x-id": "TransportControls_85_8_expr1",
        "x-dynamic": "true",
        "x-source-type": "state",
        "x-source-var": "tempo",
        "x-source-editable": "false",
        children: tempo
      }, void 0, false), "/s"]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 85,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 74,
    columnNumber: 7
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
    className: "flex items-center gap-2",
    "x-file-name": "TransportControls",
    "x-line-number": "90",
    "x-column": "6",
    "x-component": "div",
    "x-id": "TransportControls_90_6",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
      className: "eyebrow",
      "x-file-name": "TransportControls",
      "x-line-number": "91",
      "x-column": "8",
      "x-component": "span",
      "x-id": "TransportControls_91_8",
      "x-dynamic": "false",
      children: "Tuning"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 91,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
      className: `tab ${tuning === 432 ? "active" : ""}`,
      onClick: () => setTuning(432),
      "data-testid": "tuning-432",
```

```
        "x-file-name": "TransportControls",
        "x-line-number": "92",
        "x-column": "8",
        "x-component": "button",
        "x-id": "TransportControls_92_8",
        "x-dynamic": "false",
        children: "432 Hz"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 92,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("button", {
        className: `tab ${tuning === 440 ? "active" : ""}`,
        onClick: () => setTuning(440),
        "data-testid": "tuning-440",
        "x-file-name": "TransportControls",
        "x-line-number": "99",
        "x-column": "8",
        "x-component": "button",
        "x-id": "TransportControls_99_8",
        "x-dynamic": "false",
        children: "440 Hz"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 99,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 90,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
      className: "flex items-center gap-2",
      "x-file-name": "TransportControls",
      "x-line-number": "108",
      "x-column": "6",
      "x-component": "div",
      "x-id": "TransportControls_108_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
        className: "eyebrow",
        "x-file-name": "TransportControls",
        "x-line-number": "109",
        "x-column": "8",
        "x-component": "span",
        "x-id": "TransportControls_109_8",
```

```
        "x-dynamic": "false",
        children: "Wave"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 109,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("select", {
        className: "select",
        style: {
          width: 130
        },
        value: wave,
        onChange: e => setWave(e.target.value),
        "data-testid": "wave-select",
        "x-file-name": "TransportControls",
        "x-line-number": "110",
        "x-column": "8",
        "x-component": "select",
        "x-id": "TransportControls_110_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
          value: "sine",
          "x-file-name": "TransportControls",
          "x-line-number": "117",
          "x-column": "10",
          "x-component": "option",
          "x-id": "TransportControls_117_10",
          "x-dynamic": "false",
          children: "Sine"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 117,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
          value: "triangle",
          "x-file-name": "TransportControls",
          "x-line-number": "118",
          "x-column": "10",
          "x-component": "option",
          "x-id": "TransportControls_118_10",
          "x-dynamic": "false",
          children: "Triangle"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 118,
          columnNumber: 11
```

```
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
        value: "square",
        "x-file-name": "TransportControls",
        "x-line-number": "119",
        "x-column": "10",
        "x-component": "option",
        "x-id": "TransportControls_119_10",
        "x-dynamic": "false",
        children: "Square"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 119,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
        value: "sawtooth",
        "x-file-name": "TransportControls",
        "x-line-number": "120",
        "x-column": "10",
        "x-component": "option",
        "x-id": "TransportControls_120_10",
        "x-dynamic": "false",
        children: "Sawtooth"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 120,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 110,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 108,
    columnNumber: 7
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("div", {
    className: "flex items-center gap-2",
    "x-file-name": "TransportControls",
    "x-line-number": "124",
    "x-column": "6",
    "x-component": "div",
    "x-id": "TransportControls_124_6",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("span", {
```

```
        className: "eyebrow",
        "x-file-name": "TransportControls",
        "x-line-number": "125",
        "x-column": "8",
        "x-component": "span",
        "x-id": "TransportControls_125_8",
        "x-dynamic": "false",
        children: "On mirror"
      }, void 0, false, {
        fileName: _jsxFileName,

        lineNumber: 125,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("select", {
        className: "select",
        style: {
          width: 130
        },
        value: restOnMirror,
        onChange: e => setRestOnMirror(e.target.value),
        "data-testid": "mirror-behavior-select",
        "x-file-name": "TransportControls",
        "x-line-number": "126",
        "x-column": "8",
        "x-component": "select",
        "x-id": "TransportControls_126_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
          value: "rest",
          "x-file-name": "TransportControls",
          "x-line-number": "133",
          "x-column": "10",
          "x-component": "option",
          "x-id": "TransportControls_133_10",
          "x-dynamic": "false",
          children: "Rest"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 133,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
          value: "click",
          "x-file-name": "TransportControls",
          "x-line-number": "134",
          "x-column": "10",
          "x-component": "option",
```

```
        "x-id": "TransportControls_134_10",
        "x-dynamic": "false",
        children: "Click"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 134,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)("option", {
        value: "none",
        "x-file-name": "TransportControls",
        "x-line-number": "135",
        "x-column": "10",
        "x-component": "option",
        "x-id": "TransportControls_135_10",
        "x-dynamic": "false",
        children: "Continue"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 135,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 126,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 124,
    columnNumber: 7
  }, this)]
 }, void 0, true, {
  fileName: _jsxFileName,
  lineNumber: 61,
  columnNumber: 5
 }, this);
}
_s(TransportControls, "yaPIhoXyafSg2dPHguAfHkCAhA0=");
_c = TransportControls;
var _c;
__webpack_require__.$Refresh$.register(_c, "TransportControls");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
```

```
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/context/SequenceContext.jsx"
/*!*****************************************!*\
  !*** ./src/context/SequenceContext.jsx ***!
  \*****************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   SequenceProvider: () => (/* binding */ SequenceProvider),
/* harmony export */   useMirror: () => (/* binding */ useMirror),
/* harmony export */   useSequence: () => (/* binding */ useSequence)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../lib/mirrorGroups */ "./src/lib/mirrorGroups.js");
/* harmony import */ var _lib_fasta__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../lib/fasta */ "./src/lib/fasta.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_3__ =
```

```
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/context/SequenceContext.jsx",
  _s = __webpack_require__.$Refresh$.signature(),
  _s2 = __webpack_require__.$Refresh$.signature(),
  _s3 = __webpack_require__.$Refresh$.signature();




const Ctx = /*#__PURE__*/(0,react__WEBPACK_IMPORTED_MODULE_0__.createContext)(null);
function SequenceProvider({
  children
}) {
  _s();
  const [current, setCurrent] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(null); //
{name, type, sequence, source}
  const [sideA, setSideA] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(null);
  const [sideB, setSideB] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(null);
  const loadCurrent = (name, sequence, type, source) => {
    const t = type || (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_2__.detectType)(sequence);
    const clean = (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_2__.sanitize)(sequence, t);
    setCurrent({
      name: name || "Untitled",
      type: t,
      sequence: clean,
      source: source || "user"
    });
  };
  const loadSide = (which, name, sequence, type, source) => {
    const t = type || (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_2__.detectType)(sequence);
    const clean = (0,_lib_fasta__WEBPACK_IMPORTED_MODULE_2__.sanitize)(sequence, t);
    const s = {
      name: name || "Untitled",
      type: t,
      sequence: clean,
      source: source || "user"
    };
    if (which === "A") setSideA(s);else setSideB(s);
  };
  const value = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => ({
    current,
    sideA,
    sideB,
```

```
    setCurrent,
    loadCurrent,
    loadSide,
    setSideA,
    setSideB
  }), [current, sideA, sideB]);
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_3__.jsxDEV)(Ctx.Provider, {
    value: value,
    children: children
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 25,
    columnNumber: 10
  }, this);
}
_s(SequenceProvider, "pdD2qocKDM2MluLp/i710jOA3+M=");
_c = SequenceProvider;
function useSequence() {
  _s2();
  const v = (0,react__WEBPACK_IMPORTED_MODULE_0__.useContext)(Ctx);
  if (!v) throw new Error("useSequence must be used within SequenceProvider");
  return v;
}

// Handy hook: memoized mirror groups + stats for a sequence
_s2(useSequence, "vseRKStixtRCAgA7lJDFgCF8qLI=");
function useMirror(seq) {
  _s3();
  return (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => {
    if (!seq) return {
      groups: [],
      stats: null
    };
    const groups = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__.mirrorGroup)
(seq);
    const stats = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_1__.computeStats)(seq,
groups);
    return {
      groups,
      stats
    };
  }, [seq]);
}
_s3(useMirror, "nwk+m61qLgjDVUp4IGV/072DDN4=");
var _c;
__webpack_require__.$Refresh$.register(_c, "SequenceProvider");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
```

```
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/index.js"
/*!**********************!*\
  !*** ./src/index.js ***!
  \**********************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_dom_client__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-dom/client */ "./node_modules/react-dom/client.js");
/* harmony import */ var _tanstack_react_query__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! @tanstack/react-query */ "./node_modules/@tanstack/query-
core/build/modern/queryClient.js");
```

```
/* harmony import */ var _tanstack_react_query__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! @tanstack/react-query */ "./node_modules/@tanstack/react-
query/build/modern/QueryClientProvider.js");
/* harmony import */ var _index_css__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! @/index.css */ "./src/index.css");
/* harmony import */ var _App__WEBPACK_IMPORTED_MODULE_5__
 = __webpack_require__(/*! @/App */ "./src/App.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/index.js";




const queryClient = new
_tanstack_react_query__WEBPACK_IMPORTED_MODULE_2__.QueryClient({
  defaultOptions: {
    queries: {
      staleTime: 60000,
      refetchOnWindowFocus: false
    }
  }
});
const root =
react_dom_client__WEBPACK_IMPORTED_MODULE_1__.createRoot(document.getElementById("
root"));
root.render(/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
((react__WEBPACK_IMPORTED_MODULE_0___default().StrictMode), {
  children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
(_tanstack_react_query__WEBPACK_IMPORTED_MODULE_3__.QueryClientProvider, {
    client: queryClient,
    "x-file-name": "index",
    "x-line-number": "19",
    "x-column": "4",
    "x-component": "QueryClientProvider",
    "x-id": "index_19_4",
    "x-dynamic": "false",
    children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_6__.jsxDEV)
```

```
(_App__WEBPACK_IMPORTED_MODULE_5__["default"], {
      "x-file-name": "index",
      "x-line-number": "20",
      "x-column": "6",
      "x-component": "App",
      "x-id": "index_20_6",
      "x-dynamic": "true"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 20,
      columnNumber: 7
    }, undefined)
  }, void 0, false, {
    fileName: _jsxFileName,
    lineNumber: 19,
    columnNumber: 5
  }, undefined)
}, void 0, false, {
  fileName: _jsxFileName,
  lineNumber: 18,
  columnNumber: 3
}, undefined));

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
```

```
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/lib/api.js"
/*!*************************!*\
  !*** ./src/lib/api.js ***!
  \*************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   API: () => (/* binding */ API),
/* harmony export */   api: () => (/* binding */ api),
/* harmony export */   deleteSequence: () => (/* binding */ deleteSequence),
/* harmony export */   getSequence: () => (/* binding */ getSequence),
/* harmony export */   listSequences: () => (/* binding */ listSequences),
/* harmony export */   saveSequence: () => (/* binding */ saveSequence)
/* harmony export */ });
/* harmony import */ var axios__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! axios */ "./node_modules/axios/lib/axios.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");


const BACKEND_URL = "https://genetic-music-lab.preview.emergentagent.com";
const API = `${BACKEND_URL}/api`;
const api = axios__WEBPACK_IMPORTED_MODULE_0__["default"].create({
  baseURL: API
});
async function saveSequence(payload) {
  const {
    data
  } = await api.post("/sequences", payload);
  return data;
}
async function listSequences(params = {}) {
  const {
    data
  } = await api.get("/sequences", {
    params
  });
```

```
  return data;
}
async function getSequence(id) {
  const {
    data
  } = await api.get(`/sequences/${id}`);
  return data;
}
async function deleteSequence(id) {
  const {
    data
  } = await api.delete(`/sequences/${id}`);
  return data;
}

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/lib/audio.js"
```

```
/*!**************************!*\
  !*** ./src/lib/audio.js ***!
  \**************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   DIGIT_MAP: () => (/* binding */ DIGIT_MAP),
/* harmony export */   DNA_MAP: () => (/* binding */ DNA_MAP),
/* harmony export */   NOTE_STEPS: () => (/* binding */ NOTE_STEPS),
/* harmony export */   getAudio: () => (/* binding */ getAudio),
/* harmony export */   renderWav: () => (/* binding */ renderWav),
/* harmony export */   symbolToFreq: () => (/* binding */ symbolToFreq),
/* harmony export */   symbolToNoteName: () => (/* binding */ symbolToNoteName)
/* harmony export */ });
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

// WebAudio synthesizer for pentatonic sonification + 432 Hz drone.
// DNA scale (C major pentatonic, octave 4):
//   A -> C4  T -> D4  G -> E4  C -> G4  N -> A4
// Digits (two pentatonic scales, C major pentatonic across two octaves):
//   0..4 -> C4 D4 E4 G4 A4
//   5..9 -> C5 D5 E5 G5 A5

const NOTE = {
  C4: 261.63,
  D4: 293.66,
  E4: 329.63,
  G4: 392.0,
  A4: 440.0,
  C5: 523.25,
  D5: 587.33,
  E5: 659.25,
  G5: 783.99,
  A5: 880.0
};
const DNA_MAP = {
  A: NOTE.C4,
  T: NOTE.D4,
  G: NOTE.E4,
  C: NOTE.G4,
  N: NOTE.A4
};
const DIGIT_MAP = {
```

```
  "0": NOTE.C4,
  "1": NOTE.D4,
  "2": NOTE.E4,
  "3": NOTE.G4,
  "4": NOTE.A4,
  "5": NOTE.C5,
  "6": NOTE.D5,
  "7": NOTE.E5,
  "8": NOTE.G5,
  "9": NOTE.A5
};

// Staff position for note (used by MusicalStaff.jsx). Higher = lower pitch on staff (SVG y+).
// We express as integer semitone steps above C4 (0-indexed). This lets the staff
// place note heads correctly by mapping to line/space indices.
const NOTE_STEPS = {
  C4: 0,
  D4: 2,
  E4: 4,
  G4: 7,
  A4: 9,
  C5: 12,
  D5: 14,
  E5: 16,
  G5: 19,
  A5: 21
};
function symbolToFreq(sym, type) {
  var _DIGIT_MAP$sym, _DNA_MAP$sym$toUpperC;
  if (type === "digits") return (_DIGIT_MAP$sym = DIGIT_MAP[sym]) !== null &&
_DIGIT_MAP$sym !== void 0 ? _DIGIT_MAP$sym : null;
  if (type === "dna") return (_DNA_MAP$sym$toUpperC = DNA_MAP[sym === null || sym === void
0 ? void 0 : sym.toUpperCase()]) !== null && _DNA_MAP$sym$toUpperC !== void 0 ?
_DNA_MAP$sym$toUpperC : null;
  return null;
}
function symbolToNoteName(sym, type) {
  const map = type === "digits" ? DIGIT_MAP : DNA_MAP;
  const target = map[type === "digits" ? sym : sym === null || sym === void 0 ? void 0 :
sym.toUpperCase()];
  if (!target) return null;
  for (const [name, f] of Object.entries(NOTE)) if (f === target) return name;
  return null;
}

// Global-ish audio manager (created lazily)
class AudioEngine {
  constructor() {
    this.ctx = null;
```

```
    this.master = null;
    this.drone = null;
    this.droneGain = null;
    this.playing = false;
    this.timers = [];
  }
  ensure() {
    if (!this.ctx) {
      const Ctx = window.AudioContext || window.webkitAudioContext;
      this.ctx = new Ctx();
      this.master = this.ctx.createGain();
      this.master.gain.value = 0.7;
      this.master.connect(this.ctx.destination);
    }
    if (this.ctx.state === "suspended") this.ctx.resume();
  }
  startDrone(freq = 432, gain = 0.06) {
    this.ensure();
    this.stopDrone();
    const osc = this.ctx.createOscillator();
    osc.type = "sine";
    osc.frequency.value = freq;
    const g = this.ctx.createGain();
    g.gain.value = 0;
    g.gain.linearRampToValueAtTime(gain, this.ctx.currentTime + 0.4);
    osc.connect(g).connect(this.master);
    osc.start();
    this.drone = osc;
    this.droneGain = g;
  }
  stopDrone() {
    if (this.drone) {
      try {
        const now = this.ctx.currentTime;
        this.droneGain.gain.cancelScheduledValues(now);
        this.droneGain.gain.setValueAtTime(this.droneGain.gain.value, now);
        this.droneGain.gain.linearRampToValueAtTime(0,
now + 0.2);
        this.drone.stop(now + 0.25);
      } catch (e) {/* noop */}
      this.drone = null;
      this.droneGain = null;
    }
  }
  playNote({
    freq,
    when,
    dur,
    wave = "sine",
```

```
  gain = 0.18,
  pan = 0
}) {
  this.ensure();
  const t0 = when !== null && when !== void 0 ? when : this.ctx.currentTime;
  const osc = this.ctx.createOscillator();
  osc.type = wave;
  osc.frequency.value = freq;
  const g = this.ctx.createGain();
  g.gain.value = 0;
  g.gain.linearRampToValueAtTime(gain, t0 + 0.01);
  g.gain.exponentialRampToValueAtTime(0.0001, t0 + Math.max(0.04, dur));
  const panNode = this.ctx.createStereoPanner ? this.ctx.createStereoPanner() : null;
  if (panNode) {
    panNode.pan.value = pan;
    osc.connect(g).connect(panNode).connect(this.master);
  } else {
    osc.connect(g).connect(this.master);
  }
  osc.start(t0);
  osc.stop(t0 + Math.max(0.05, dur) + 0.05);
}
playSequence({
  symbols,
  type,
  tempo = 6,
  wave = "sine",
  tuning = 432,
  restOnMirror = "rest",
  onTick,
  onDone,
  groupBoundaries = []
}) {
  this.ensure();
  this.stop();
  this.startDrone(tuning);
  const step = 1 / tempo;
  const t0 = this.ctx.currentTime + 0.15;
  let cursor = 0;
  this.playing = true;
  const boundaries = new Set(groupBoundaries);
  for (let i = 0; i < symbols.length; i++) {
    const sym = symbols[i];
    const isBoundary = boundaries.has(i);
    let t = t0 + cursor * step;
    if (isBoundary && restOnMirror === "rest") {
      cursor += 0.5;
      t = t0 + cursor * step;
    } else if (isBoundary && restOnMirror === "click") {
```

```
        this.playNote({
          freq: 880,
          when: t,
          dur: 0.08,
          wave: "square",
          gain: 0.06
        });
      }
      const freq = symbolToFreq(sym, type);
      if (freq) this.playNote({
        freq,
        when: t,
        dur: step * 0.9,
        wave
      });
      const scheduleAt = (t - this.ctx.currentTime) * 1000;
      this.timers.push(setTimeout(() => onTick === null || onTick === void 0 ? void 0 : onTick(i),
Math.max(0, scheduleAt)));
      cursor += 1;
    }
    const totalMs = (cursor * step + 0.4) * 1000;
    this.timers.push(setTimeout(() => {
      this.stop();
      onDone === null || onDone === void 0 ? void 0 : onDone();
    }, totalMs));
  }
  stop() {
    this.playing = false;
    this.timers.forEach(clearTimeout);
    this.timers = [];
    this.stopDrone();
  }
}
let _engine = null;
function getAudio() {
  if (!_engine) _engine = new AudioEngine();
  return _engine;
}

// ---- Offline render for WAV export ----
async function renderWav({
  symbols,
  type,
  tempo = 6,
  wave = "sine",
  tuning = 432
}) {
  const step = 1 / tempo;
  const durationSec = symbols.length * step + 1.2;
```

```
  const sampleRate = 44100;
  const Offline = window.OfflineAudioContext || window.webkitOfflineAudioContext;
  const ctx = new Offline(1, Math.ceil(durationSec * sampleRate), sampleRate);
  const master = ctx.createGain();
  master.gain.value = 0.8;
  master.connect(ctx.destination);

  // drone
  const drone = ctx.createOscillator();
  drone.type = "sine";
  drone.frequency.value = tuning;
  const dg = ctx.createGain();
  dg.gain.value = 0.05;
  drone.connect(dg).connect(master);
  drone.start(0);
  drone.stop(durationSec);
  for (let i = 0; i < symbols.length; i++) {
    const freq = symbolToFreq(symbols[i], type);
    if (!freq) continue;
    const t = 0.1 + i * step;
    const osc = ctx.createOscillator();
    osc.type = wave;
    osc.frequency.value = freq;
    const g = ctx.createGain();
    g.gain.value = 0;
    g.gain.linearRampToValueAtTime(0.22, t + 0.01);
    g.gain.exponentialRampToValueAtTime(0.0001, t + step * 0.9);
    osc.connect(g).connect(master);
    osc.start(t);
    osc.stop(t + step);
  }
  const buffer = await ctx.startRendering();
  return audioBufferToWav(buffer);
}

// PCM WAV encoder (mono)
function audioBufferToWav(buffer) {
  const numCh = buffer.numberOfChannels;
  const sampleRate = buffer.sampleRate;
  const len = buffer.length * numCh * 2 + 44;
  const buf = new ArrayBuffer(len);
  const view = new DataView(buf);
  const writeStr = (o, s) => {
    for (let i = 0; i < s.length; i++) view.setUint8(o + i, s.charCodeAt(i));
  };
  writeStr(0, "RIFF");
  view.setUint32(4, len - 8, true);
  writeStr(8, "WAVE");
  writeStr(12, "fmt ");
```

```
  view.setUint32(16, 16, true);
  view.setUint16(20, 1, true);
  view.setUint16(22, numCh, true);
  view.setUint32(24, sampleRate, true);
  view.setUint32(28, sampleRate * numCh * 2, true);
  view.setUint16(32, numCh * 2, true);
  view.setUint16(34, 16, true);
  writeStr(36, "data");
  view.setUint32(40, buffer.length * numCh * 2, true);
  const chData = [];
  for (let c = 0; c < numCh; c++) chData.push(buffer.getChannelData(c));
  let offset = 44;
  for (let i = 0; i < buffer.length; i++) {
    for (let c = 0; c < numCh; c++) {
      const s = Math.max(-1, Math.min(1, chData[c][i]));
      view.setInt16(offset, s < 0 ? s * 0x8000 : s * 0x7fff, true);
      offset += 2;
    }
  }
  return new Blob([buf], {
    type: "audio/wav"
  });
}

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}
```

```
if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/lib/fasta.js"
/*!**************************!*\
  !*** ./src/lib/fasta.js ***!
  \**************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   detectType: () => (/* binding */ detectType),
/* harmony export */   parseFasta: () => (/* binding */ parseFasta),
/* harmony export */   sanitize: () => (/* binding */ sanitize)
/* harmony export */ });
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

// Parse FASTA text. Returns { name, sequence } for the first record.
// Also strips non-letters/digits automatically for downstream processing.
function parseFasta(raw) {
  if (!raw) return {
    name: "",
    sequence: ""
  };
  const lines = raw.split(/\r?\n/);
  let name = "";
  const parts = [];
  for (const line of lines) {
    if (line.startsWith(">")) {
      if (!name) name = line.slice(1).trim();
    } else {
      parts.push(line.trim());
    }
  }
  const sequence = parts.join("");
  return {
    name,
    sequence
  };
```

```
}
function detectType(seq) {
  const s = seq.replace(/\s+/g, "");
  if (!s) return "text";
  const digits = /^[0-9.\s]+$/.test(s);
  if (digits) return "digits";
  const dnaish = /^[ATGCNatgcn\s]+$/.test(s);
  if (dnaish) return "dna";
  return "text";
}
function sanitize(seq, type) {
  if (type === "digits") return seq.replace(/[^0-9]/g, "");
  if (type === "dna") return seq.replace(/[^ATGCNatgcn]/g, "").toUpperCase();
  return seq.replace(/\s+/g, "");
}

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
	$ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
	if (true) {
		let errorOverlay;
		if (true) {
			errorOverlay = false;
		}
		let testMode;
		if (typeof __react_refresh_test__ !== 'undefined') {
			testMode = __react_refresh_test__;
		}
		return __react_refresh_utils__.executeRuntime(
			exports,
			$ReactRefreshModuleId$,
			module.hot,
			errorOverlay,
			testMode
		);
	}
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },
```

```
/***/ "./src/lib/mirrorGroups.js"
/*!**********************************!*\
  !*** ./src/lib/mirrorGroups.js ***!
  \**********************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   computeStats: () => (/* binding */ computeStats),
/* harmony export */   countPAM: () => (/* binding */ countPAM),
/* harmony export */   findAll: () => (/* binding */ findAll),
/* harmony export */   matchedLegoBlocks: () => (/* binding */ matchedLegoBlocks),
/* harmony export */   mirrorGroup: () => (/* binding */ mirrorGroup),
/* harmony export */   palindromeDepth: () => (/* binding */ palindromeDepth),
/* harmony export */   reverseComplement: () => (/* binding */ reverseComplement),
/* harmony export */   windowProfile: () => (/* binding */ windowProfile)
/* harmony export */ });
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime
 = __webpack_require__(/*! ./node_modules/react-refresh/runtime.js */ "./node_modules/react-
refresh/runtime.js");

// Mirror Grouping algorithm (Arthur Zilkowsky)
// A mirror `|` is inserted every time a symbol repeats the last symbol of the
// current group. The repeated symbol starts a new group.

function mirrorGroup(seq) {
  const groups = [];
  let current = "";
  for (const ch of seq) {
    if (current.length > 0 && current[current.length - 1] === ch) {
      groups.push(current);
      current = ch;
    } else {
      current += ch;
    }
  }
  if (current.length > 0) groups.push(current);
  return groups;
}

// Palindromic nesting depth of a string:
// count how many outermost pairs match symmetrically, e.g. "ABCBA" -> 2.
function palindromeDepth(s) {
  let l = 0;
  let r = s.length - 1;
```

```
  let d = 0;
  while (l < r && s[l] === s[r]) {
    d++;
    l++;
    r--;
  }
  return d;
}

// Count Cas9 PAM sites (NGG) on forward strand only. `n` may be any base.
function countPAM(seq) {
  const s = seq.toUpperCase();
  let n = 0;
  for (let i = 0; i < s.length - 2; i++) {
    const a = s[i];
    if (a !== "A" && a !== "T" && a !== "G" && a !== "C") continue;
    if (s[i + 1] === "G" && s[i + 2] === "G") n++;
  }
  return n;
}
function computeStats(seq, groups) {
  const repeatSites = Math.max(0, groups.length - 1);
  const longestGroup = groups.reduce((m, g) => Math.max(m, g.length), 0);
  let maxDepth = 0;
  for (const g of groups) maxDepth = Math.max(maxDepth, palindromeDepth(g));
  return {
    length: seq.length,
    groups: groups.length,
    repeatSites,
    repeatDensity: seq.length ? repeatSites / seq.length : 0,
    longestGroup,
    maxDepth,
    pam: countPAM(seq)
  };
}

// Reverse complement for DNA (used for motif scanning)
const COMP = {
  A: "T",
  T: "A",
  G: "C",
  C: "G",
  N: "N"
};
function reverseComplement(s) {
  let out = "";
  for (let i = s.length - 1; i >= 0; i--) {
    const c = s[i].toUpperCase();
    out += COMP[c] || c;
```

```
  }
  return out;
}

// Find all occurrences of `pattern` in `text`
function findAll(text, pattern) {
  if (!pattern) return [];
  const out = [];
  let i = 0;
  const t = text.toUpperCase();
  const p = pattern.toUpperCase();
  while (i <= t.length - p.length) {
    const j = t.indexOf(p, i);
    if (j === -1) break;
    out.push(j);
    i = j + 1;
  }
  return out;
}

// Windowed density chart: divide sequence into `windows` bins and compute a
// metric per bin.
function windowProfile(seq, groups, windows, metric = "repeatDensity") {
  const size = Math.max(1, Math.floor(seq.length / windows));
  const bins = new Array(windows).fill(0);
  // repeat sites index array
  let cursor = 0;
  const repeatIndices = [];
  for (let i = 0; i < groups.length - 1; i++) {
    cursor += groups[i].length;
    repeatIndices.push(cursor);
  }
  for (const idx of repeatIndices) {
    const b = Math.min(windows - 1, Math.floor(idx / size));
    bins[b]++;
  }
  if (metric === "repeatDensity") {
    return bins.map(c => c / size);
  }
  if (metric === "groupCount") return bins.slice();
  if (metric === "longestGroup") {
    const out = new Array(windows).fill(0);
    let pos = 0;
    for (const g of groups) {
      const b = Math.min(windows - 1, Math.floor(pos / size));
      out[b] = Math.max(out[b], g.length);
      pos += g.length;
    }
    return out;
```

```
  }
  return bins;
}

// Find matched Lego blocks (groups that appear in both A and B) then keep a
// consistent, non-crossing chain (LIS by position in B given order in A).
function matchedLegoBlocks(groupsA, groupsB, minLen = 6) {
  const positionsA = {};
  const positionsB = {};
  let pos = 0;
  for (let i = 0; i < groupsA.length; i++) {
    if (groupsA[i].length >= minLen) {
      if (!positionsA[groupsA[i]]) positionsA[groupsA[i]] = [];
      positionsA[groupsA[i]].push({
        index: i,
        pos
      });
    }
    pos += groupsA[i].length;
  }
  pos = 0;
  for (let i = 0; i < groupsB.length; i++) {
    if (groupsB[i].length >= minLen) {
      if (!positionsB[groupsB[i]]) positionsB[groupsB[i]] = [];
      positionsB[groupsB[i]].push({
        index: i,
        pos
      });
    }
    pos += groupsB[i].length;
  }
  // Candidate pairs (only unique groups on both sides - take first occurrence)
  const cands = [];
  for (const key of Object.keys(positionsA)) {
    if (positionsB[key]) {
      cands.push({
        text: key,
        aPos: positionsA[key][0].pos,
        bPos: positionsB[key][0].pos,
        len: key.length
      });
    }
  }
  cands.sort((x, y) => x.aPos - y.aPos);
  // LIS on bPos
  const n = cands.length;
  if (!n) return [];
  const dp = new Array(n).fill(1);
  const prev = new Array(n).fill(-1);
```

```
  for (let i = 1; i < n; i++) {
    for (let j = 0; j < i; j++) {
      if (cands[j].bPos < cands[i].bPos && dp[j] + 1 > dp[i]) {
        dp[i] = dp[j] + 1;
        prev[i] = j;
      }
    }
  }
  let best = 0;
  for (let i = 1; i < n; i++) if (dp[i] > dp[best]) best = i;
  const chain = [];
  for (let k = best; k !== -1; k = prev[k]) chain.push(cands[k]);
  chain.reverse();
  return chain;
}

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },
```

```
/***/ "./src/lib/presets.js"
/*!*****************************!*\
  !*** ./src/lib/presets.js ***!
  \*****************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   PRESETS: () => (/* binding */ PRESETS),
/* harmony export */   getPreset: () => (/* binding */ getPreset)
/* harmony export */ });
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

// Preset sample sequences shown as chips on the FASTA input.
const PRESETS = [{
  id: "pi",
  name: "π — first 1000 digits",
  type: "digits",
  source: "π (Pi)",
  description: "The first 1000 decimal digits of π (starting with 3, decimal removed).",
  sequence:
"31415926535897932384626433832795028841971693993751058209749445923078164062862089986280348253421170679" +
"82148086513282306647093844609550582231725359408128481117450284102701938521105559644622948954930381964" +
"42881097566593344612847564823378678316527120190914564856692346034861045432664821339360726024914127372" +
"45870066063155881748815209209628292540917153643678925903600113305305488204665213841469519415116094330" +
"57270365759591953092186117381932611793105118548074462379962749567351885752724891227938183011949129833" +
"67336244065664308602139494639522473719070217986094370277053921717629317675238467481846766940513200056" +
"81271452635608277857713427577896091736371787214684409012249534301465495853710507922796892589235420199" +
"56112129021960864034418159813629774771309960518707211349999998372978049951059731732816096318595024459" +
"45534690830264252230825334468503526193118817101000313783875288658753320838142061717766914730359825349" +
"04287554687311595628638823537875937519577818577805321712268066130019278766111959092164201989"
}, {
  id: "mtdna",
  name: "Human mtDNA — D-loop excerpt",
```

```
  type: "dna",
  source: "GenBank NC_012920",
  description: "600 bp excerpt from the human mitochondrial D-loop region.",
  sequence:
"GATCACAGGTCTATCACCCTATTAACCACTCACGGGAGCTCTCCATGCATTTGGTATTTTCG
TCTGGGGGGTGTGCACGCGATAGCATTGCGAG" +
"ACGCTGGAGCCGGAGCACCCTATGTCGCAGTATCTGTCTTTGATTCCTGCCTCATCCTATTA
TTTATCGCACCTACGTTCAATATTACAGGCGA" +
"ACATACCTACTAAAGTGTGTTAATTAATTAATGCTTGTAGGACATAATAATAACAATTGAATG
TCTGCACAGCCACTTTCCACACAGACATCAT" +
"AACAAAAAATTTCCACCAAACCCCCCCTCCCCCGCTTCTGGCCACAGCACTTAAACACAT
CTCTGCCAAACCCCAAAAACAAAGAACCCTAACA" +
"CCAGCCTAACCAGATTTCAAAAAAAAGTATAAGGTATAATATTGATGCATTGGGTCCCCCCC
CCCCATTATCCTAACGAATTAACGAGGATATT" +
"GCATTATATTATGTATCATTGCACAACGTATTAAAGCATGTACGTGACATTAGGACAATATCT
TCTAATAT"
}, {
  id: "egfr",
  name: "EGFR — exon 19 region",
  type: "dna",
  source: "EGFR (human)",
  description: "Illustrative excerpt near EGFR exon 19; useful for motif scanning demos.",
  sequence:
"ATGCGACCCTCCGGGACGGCCGGGGCAGCGCTCCTGGCGCTGCTGGCTGCGCTCTGCCCG
GCGAGTCGGGCTCTGGAGGAAAAGAAAGTTTGCC" +
"AAGGCACGAGTAACAAGCTCACGCAGTTGGGCACTTTTGAAGATCATTTTCTCAGCCTCC
AGAGGATGTTCAATAACTGTGAGGTGGTCCTTGG" +
"GAATTTGGAAATTACCTATGTGCAGAGGAATTATGATCTTTCCTTCTTAAAGACCATCCAGG
AGGTGGCTGGTTATGTCCTCATTGCCCTCAAC" +
"ACAGTGGAGCGAATTCCTTTGGAAAACCTGCAGATCATCAGAGGAAATATGTACTACGAA
AATTCCTATGCCTTAGCAGTCTTATCTAACTATG" +
"ATGCAAATAAAACCGGACTGAAGGAGCTGCCCATGAGAAATTTACAGGAAATCCTGCATG
GCGCCGTGCGGTTCAGCAACAACCCT"
}];
const getPreset = id => PRESETS.find(p => p.id === id);

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__
```

```
 !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/pages/AtlasPage.jsx"
/*!*********************************!*\
  !*** ./src/pages/AtlasPage.jsx ***!
  \*********************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ AtlasPage)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var _components_FastaInput__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../components/FastaInput */ "./src/components/FastaInput.jsx");
/* harmony import */ var
_components_MirrorGroupsPanel__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../components/MirrorGroupsPanel */
"./src/components/MirrorGroupsPanel.jsx");
/* harmony import */ var _components_MusicalStaff__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../components/MusicalStaff */ "./src/components/MusicalStaff.jsx");
/* harmony import */ var
_components_TransportControls__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../components/TransportControls */
```

```
"./src/components/TransportControls.jsx");
/* harmony import */ var
_components_SchillingerDevices__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../components/SchillingerDevices */
"./src/components/SchillingerDevices.jsx");
/* harmony import */ var
_components_InterferenceBuilder__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ../components/InterferenceBuilder */
"./src/components/InterferenceBuilder.jsx");
/* harmony import */ var _components_StatsBar__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ../components/StatsBar */ "./src/components/StatsBar.jsx");
/* harmony import */ var _context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ../context/SequenceContext */ "./src/context/SequenceContext.jsx");
/* harmony import */ var _lib_api__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! ../lib/api */ "./src/lib/api.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_11__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/save.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/pages/AtlasPage.jsx",
  _s = __webpack_require__.$Refresh$.signature();









function AtlasPage() {
  _s();
  const {
    current,
    loadCurrent
  } = (0,_context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__.useSequence)();
  const [selectedIdx, setSelectedIdx] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)
(null);
  const [playhead, setPlayhead] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(-1);
```

```
  const {
    groups,
    stats
  } = (0,_context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__.useMirror)((current
=== null || current === void 0 ? void 0 : current.sequence) || "");
  const boundaries = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => {
    const b = [];
    let pos = 0;
    for (let i = 0; i < groups.length - 1; i++) {
      pos += groups[i].length;
      b.push(pos);
    }
    return b;
  }, [groups]);
  const symbols = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => ((current ===
null || current === void 0 ? void 0 : current.sequence) || "").split(""), [current]);
  const save = async () => {
    if (!current) return;
    try {
      await (0,_lib_api__WEBPACK_IMPORTED_MODULE_10__.saveSequence)({
        name: current.name,
        sequence_type: current.type,
        sequence: current.sequence,
        source: current.source || "user",
        group_count: groups.length,
        length: current.sequence.length
      });
      sonner__WEBPACK_IMPORTED_MODULE_1__.toast.success(`Saved to library`);
    } catch (e) {
      sonner__WEBPACK_IMPORTED_MODULE_1__.toast.error("Save failed");
    }
  };
  if (!current) {
    return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
      className: "max-w-2xl mx-auto mt-6",
      "data-testid": "atlas-empty",
      "x-file-name": "AtlasPage",
      "x-line-number": "51",
      "x-column": "6",
      "x-component": "div",
      "x-id": "AtlasPage_51_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_FastaInput__WEBPACK_IMPORTED_MODULE_2__["default"], {
        onLoad: v => loadCurrent(v.name, v.sequence, v.type, v.source),
        label: "Load a sequence to begin",
        "x-file-name": "AtlasPage",
```

```
        "x-line-number": "52",
        "x-column": "8",
        "x-component": "FastaInput",
        "x-id": "AtlasPage_52_8",
        "x-dynamic": "true"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 52,
        columnNumber: 9
       }, this)
     }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 51,
      columnNumber: 7
     }, this);
   }
   return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
     className: "space-y-6",
     "data-testid": "atlas-page",
     "x-file-name": "AtlasPage",
     "x-line-number": "58",
     "x-column": "4",
     "x-component": "div",
     "x-id": "AtlasPage_58_4",
     "x-dynamic": "false",
     children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
       className: "flex flex-wrap items-center justify-between gap-3",
       "x-file-name": "AtlasPage",
       "x-line-number": "59",
       "x-column": "6",
       "x-component": "div",
       "x-id": "AtlasPage_59_6",
       "x-dynamic": "false",
       children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
         "x-file-name": "AtlasPage",
         "x-line-number": "60",
         "x-column": "8",
         "x-component": "div",
         "x-id": "AtlasPage_60_8",
         "x-dynamic": "false",
         children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
           className: "eyebrow",
           "x-file-name": "AtlasPage",
           "x-line-number": "61",
           "x-column": "10",
```

```
        "x-component": "div",
        "x-id": "AtlasPage_61_10",
        "x-dynamic": "false",
        children: "Atlas"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 61,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("h2", {
        className: "font-heading text-2xl sm:text-3xl font-bold mt-1",
        "x-file-name": "AtlasPage",
        "x-line-number": "62",
        "x-column": "10",
        "x-component": "h2",
        "x-id": "AtlasPage_62_10",
        "x-dynamic": "true",
        "x-source-type": "unknown",
        "x-source-var": "current",
        "x-source-path": "name",
        "x-source-editable": "false",
        children: [current.name, /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("span", {
          className: "pill ml-3",
          style: {
            marginLeft: 12
          },
          "x-file-name": "AtlasPage",
          "x-line-number": "64",
          "x-column": "12",
          "x-component": "span",
          "x-id": "AtlasPage_64_12",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: current.type.toUpperCase()
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 64,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("span", {
          className: "pill ml-2",
          "x-file-name": "AtlasPage",
          "x-line-number": "65",
          "x-column": "12",
          "x-component": "span",
          "x-id": "AtlasPage_65_12",
          "x-dynamic": "true",
```

```
          "x-source-type": "unknown",
          "x-source-var": "current",
          "x-source-path": "sequence.length",
          "x-source-editable": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "AtlasPage",
            "x-line-number": "65",
            "x-column": "12",
            "x-component": "span",
            "x-id": "AtlasPage_65_12_expr0",
            "x-dynamic": "true",
            "x-source-type":
 "unknown",
            "x-source-var": "current",
            "x-source-path": "sequence.length",
            "x-source-editable": "false",
            children: current.sequence.length
          }, void 0, false), " symbols"]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 65,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 62,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 60,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
      className: "flex gap-2",
      "x-file-name": "AtlasPage",
      "x-line-number": "68",
      "x-column": "8",
      "x-component": "div",
      "x-id": "AtlasPage_68_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("button", {
```

```
        className: "btn",
        onClick: save,
        "data-testid": "save-sequence-btn",
        "x-file-name": "AtlasPage",
        "x-line-number": "69",
        "x-column": "10",
        "x-component": "button",
        "x-id": "AtlasPage_69_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_11__["default"], {
          size: 14,
          "x-file-name": "AtlasPage",
          "x-line-number": "69",
          "x-column": "81",
          "x-component": "Save",
          "x-id": "AtlasPage_69_81",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 69,
          columnNumber: 82
        }, this), " Save to library"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 69,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("button", {
        className: "btn btn-ghost",
        onClick: () => loadCurrent("", "", "text"),
        "data-testid": "clear-sequence-btn",
        "x-file-name": "AtlasPage",
        "x-line-number": "70",
        "x-column": "10",
        "x-component": "button",
        "x-id": "AtlasPage_70_10",
        "x-dynamic": "false",
        children: "Load another"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 70,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 68,
      columnNumber: 9
```

```
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 59,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_StatsBar__WEBPACK_IMPORTED_MODULE_8__["default"], {
      stats: stats,
      "x-file-name": "AtlasPage",
      "x-line-number": "74",
      "x-column": "6",
      "x-component": "StatsBar",
      "x-id": "AtlasPage_74_6",
      "x-dynamic": "true"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 74,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_TransportControls__WEBPACK_IMPORTED_MODULE_5__["default"], {
      symbols: symbols,
      type: current.type,
      groupBoundaries: boundaries,
      onTick: setPlayhead,
      onDone: () => setPlayhead(-1),
      name: current.name,
      "x-file-name": "AtlasPage",
      "x-line-number": "76",
      "x-column": "6",
      "x-component": "TransportControls",
      "x-id": "AtlasPage_76_6",
      "x-dynamic": "true"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 76,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_MirrorGroupsPanel__WEBPACK_IMPORTED_MODULE_3__["default"], {
      groups: groups,
      onSelect: setSelectedIdx,
      selectedIndex: selectedIdx,
      "x-file-name": "AtlasPage",
      "x-line-number": "85",
      "x-column": "6",
      "x-component": "MirrorGroupsPanel",
      "x-id": "AtlasPage_85_6",
```

```
      "x-dynamic": "true"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 85,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_MusicalStaff__WEBPACK_IMPORTED_MODULE_4__["default"], {
      symbols: symbols,
      type: current.type,
      playhead: playhead,
      "x-file-name": "AtlasPage",
      "x-line-number": "86",
      "x-column": "6",
      "x-component": "MusicalStaff",
      "x-id": "AtlasPage_86_6",
      "x-dynamic": "true"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 86,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)("div", {
      className: "grid grid-cols-1 lg:grid-cols-2 gap-6",
      "x-file-name": "AtlasPage",
      "x-line-number": "88",
      "x-column": "6",
      "x-component": "div",
      "x-id": "AtlasPage_88_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_SchillingerDevices__WEBPACK_IMPORTED_MODULE_6__["default"], {
        block: selectedIdx != null ? groups[selectedIdx] : null,
        type: current.type,
        index: selectedIdx,
        "x-file-name": "AtlasPage",
        "x-line-number": "89",
        "x-column": "8",
        "x-component": "SchillingerDevices",
        "x-id": "AtlasPage_89_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 89,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_12__.jsxDEV)
(_components_InterferenceBuilder__WEBPACK_IMPORTED_MODULE_7__["default"], {
```

```
        groups: groups,
        type: current.type,
        "x-file-name": "AtlasPage",
        "x-line-number": "90",
        "x-column": "8",
        "x-component": "InterferenceBuilder",
        "x-id": "AtlasPage_90_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 90,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 88,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 58,
    columnNumber: 5
  }, this);
}
_s(AtlasPage, "yTdn6+BHdXosHVvOHFl5mqY+ziw=", false, function () {
  return [_context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__.useSequence,
_context_SequenceContext__WEBPACK_IMPORTED_MODULE_9__.useMirror];
});
_c = AtlasPage;
var _c;
__webpack_require__.$Refresh$.register(_c, "AtlasPage");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
```

```
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                    );
                }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/pages/ComparePage.jsx"
/*!**********************************!*\
  !*** ./src/pages/ComparePage.jsx ***!
  \**********************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ ComparePage)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _components_FastaInput__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../components/FastaInput */ "./src/components/FastaInput.jsx");
/* harmony import */ var _components_CompareProfile__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../components/CompareProfile */ "./src/components/CompareProfile.jsx");
/* harmony import */ var _components_MatchedBlocks__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../components/MatchedBlocks */ "./src/components/MatchedBlocks.jsx");
/* harmony import */ var _components_MotifScanner__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../components/MotifScanner */ "./src/components/MotifScanner.jsx");
/* harmony import */ var _components_Remainders__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../components/Remainders */ "./src/components/Remainders.jsx");
/* harmony import */ var _components_LegoBlock__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../components/LegoBlock */ "./src/components/LegoBlock.jsx");
/* harmony import */ var _context_SequenceContext__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ../context/SequenceContext */ "./src/context/SequenceContext.jsx");
/* harmony import */ var _lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ../lib/mirrorGroups */ "./src/lib/mirrorGroups.js");
/* harmony import */ var _lib_audio__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ../lib/audio */ "./src/lib/audio.js");
```

```
/*
 harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/play.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_11__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/square.js");
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_12__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/pages/ComparePage.jsx",
  _s = __webpack_require__.$Refresh$.signature();









function ComparePage() {
  _s();
  const {
    sideA,
    sideB,
    loadSide
  } = (0,_context_SequenceContext__WEBPACK_IMPORTED_MODULE_7__.useSequence)();
  const [windows, setWindows] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(80);
  const [metric, setMetric] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)
("repeatDensity");
  const [minLen, setMinLen] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(6);
  const [zoom, setZoom] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)({
    side: null,
    window: null
  });
  const groupsA = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => sideA ?
(0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__.mirrorGroup)(sideA.sequence) : [],
[sideA]);
  const groupsB = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => sideB ?
```

```
(0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__.mirrorGroup)(sideB.sequence) : [],
[sideB]);
  const matched = (0,react__WEBPACK_IMPORTED_MODULE_0__.useMemo)(() => sideA &&
sideB ? (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__.matchedLegoBlocks)
(groupsA, groupsB, minLen) : [], [groupsA, groupsB, minLen, sideA, sideB]);
  const both = sideA && sideB;
  const playBoth = () => {
    if (!both) return;
    const engine = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_9__.getAudio)();
    engine.stop();
    engine.ensure();
    engine.startDrone(432, 0.04);
    const step = 1 / 6;
    const t0 = engine.ctx.currentTime + 0.1;
    const maxLen = Math.max(sideA.sequence.length, sideB.sequence.length);
    for (let i = 0; i < Math.min(maxLen, 400); i++) {
      const a = sideA.sequence[i];
      const b = sideB.sequence[i];
      if (a) {
        const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_9__.symbolToFreq)(a,
sideA.type);
        if (f) engine.playNote({
          freq: f,
          when: t0 + i * step,
          dur: step * 0.9,
          wave: "sine",
          pan: -0.7
        });
      }
      if (b) {
        const f = (0,_lib_audio__WEBPACK_IMPORTED_MODULE_9__.symbolToFreq)(b,
sideB.type);
        if (f) engine.playNote({
          freq: f,
          when: t0 + i * step,
          dur: step * 0.9,
          wave: "triangle",
          pan: 0.7
        });
      }
    }
    sonner__WEBPACK_IMPORTED_MODULE_12__.toast.success("Playing A left · B right");
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
    className: "space-y-6",
    "data-testid": "compare-page",
    "x-file-name": "ComparePage",
    "x-line-number": "52",
```

```
    "x-column": "4",
    "x-component": "div",
    "x-id": "ComparePage_52_4",
    "x-dynamic": "true",
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
      "x-file-name": "ComparePage",
      "x-line-number": "53",
      "x-column": "6",
      "x-component": "div",
      "x-id": "ComparePage_53_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "ComparePage",
        "x-line-number": "54",
        "x-column": "8",
        "x-component": "div",
        "x-id": "ComparePage_54_8",
        "x-dynamic": "false",
        children: "Compare"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 54,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("h2", {
        className: "font-heading text-2xl sm:text-3xl font-bold mt-1",
        "x-file-name": "ComparePage",
        "x-line-number": "55",
        "x-column": "8",
        "x-component": "h2",
        "x-id": "ComparePage_55_8",
        "x-dynamic": "false",
        children: "Two sequences, side by side"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 55,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 53,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
```

```
      className: "grid grid-cols-1 lg:grid-cols-2 gap-4",
      "x-file-name": "ComparePage",
      "x-line-number": "58",
      "x-column": "6",
      "x-component": "div",
      "x-id": "ComparePage_58_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_FastaInput__WEBPACK_IMPORTED_MODULE_1__["default"], {
        onLoad: v => loadSide("A", v.name, v.sequence, v.type, v.source),
        label: "Sequence A",
        "x-file-name": "ComparePage",
        "x-line-number": "59",
        "x-column": "8",
        "x-component": "FastaInput",
        "x-id": "ComparePage_59_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 59,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_FastaInput__WEBPACK_IMPORTED_MODULE_1__["default"], {
        onLoad: v => loadSide("B", v.name, v.sequence, v.type, v.source),
        label: "Sequence B",
        "x-file-name": "ComparePage",
        "x-line-number": "60",
        "x-column": "8",
        "x-component": "FastaInput",
        "x-id": "ComparePage_60_8",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 60,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 58,
      columnNumber: 7
    }, this), both && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.Fragment, {
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "panel p-4 flex flex-wrap items-center gap-4",
        "data-testid": "compare-controls",
```

```
        "x-file-name": "ComparePage",
        "x-line-number": "65",
        "x-column": "10",
        "x-component": "div",
        "x-id": "ComparePage_65_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
          className: "flex items-center gap-3 min-w-[220px]",
          "x-file-name": "ComparePage",
          "x-line-number": "66",
          "x-column": "12",
          "x-component": "div",
          "x-id": "ComparePage_66_12",
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
            className: "eyebrow",
            "x-file-name": "ComparePage",
            "x-line-number": "67",
            "x-column": "14",
            "x-component": "span",
            "x-id": "ComparePage_67_14",
            "x-dynamic": "false",
            children: "Windows"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 67,
            columnNumber: 15
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("input", {
            type: "range",
            min: 20,
            max: 200,
            value: windows,
            onChange: e => setWindows(parseInt(e.target.value)),
            className: "range flex-1",
            "data-testid": "windows-slider",
            "x-file-name": "ComparePage",
            "x-line-number": "68",
            "x-column": "14",
            "x-component": "input",
            "x-id": "ComparePage_68_14",
            "x-dynamic": "false"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 68,
            columnNumber: 15
          }, this), /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          className: "font-mono text-xs",
          style: {
            color: "var(--teal)"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "69",
          "x-column": "14",
          "x-component": "span",
          "x-id": "ComparePage_69_14",
          "x-dynamic": "true",
          "x-source-type": "state",
          "x-source-var": "windows",
          "x-source-editable": "false",
          children: windows
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 69,
          columnNumber: 15
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 66,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "flex items-center gap-2",

    "x-file-name": "ComparePage",
        "x-line-number": "71",
        "x-column": "12",
        "x-component": "div",
        "x-id": "ComparePage_71_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          className: "eyebrow",
          "x-file-name": "ComparePage",
          "x-line-number": "72",
          "x-column": "14",
          "x-component": "span",
          "x-id": "ComparePage_72_14",
          "x-dynamic": "false",
          children: "Metric"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 72,
          columnNumber: 15
        }, this), /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("select", {
        className: "select",
        style: {
          width: 180
        },
        value: metric,
        onChange: e => setMetric(e.target.value),
        "data-testid": "metric-select",
        "x-file-name": "ComparePage",
        "x-line-number": "73",
        "x-column": "14",
        "x-component": "select",
        "x-id": "ComparePage_73_14",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("option", {
          value: "repeatDensity",
          "x-file-name": "ComparePage",
          "x-line-number": "74",
          "x-column": "16",
          "x-component": "option",
          "x-id": "ComparePage_74_16",
          "x-dynamic": "false",
          children: "Repeat density"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 74,
          columnNumber: 17
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("option", {
          value: "longestGroup",
          "x-file-name": "ComparePage",
          "x-line-number": "75",
          "x-column": "16",
          "x-component": "option",
          "x-id": "ComparePage_75_16",
          "x-dynamic": "false",
          children: "Longest group"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 75,
          columnNumber: 17
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("option", {
          value: "groupCount",
          "x-file-name": "ComparePage",
          "x-line-number": "76",
          "x-column": "16",
          "x-component": "option",
```

```
            "x-id": "ComparePage_76_16",
            "x-dynamic": "false",
            children: "Group count"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 76,
            columnNumber: 17
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 73,
          columnNumber: 15
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 71,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "flex items-center gap-2",
        "x-file-name": "ComparePage",
        "x-line-number": "79",
        "x-column": "12",
        "x-component": "div",
        "x-id": "ComparePage_79_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          className: "eyebrow",
          "x-file-name": "ComparePage",
          "x-line-number": "80",
          "x-column": "14",
          "x-component": "span",
          "x-id": "ComparePage_80_14",
          "x-dynamic": "false",
          children: "Min block"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 80,
          columnNumber: 15
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("input", {
          type: "number",
          className: "input",
          style: {
            width: 80
          },
          value: minLen,
          min: 1,
```

```
          onChange: e => setMinLen(parseInt(e.target.value) || 1),
          "data-testid": "min-block-input",
          "x-file-name": "ComparePage",
          "x-line-number": "81",
          "x-column": "14",
          "x-component": "input",
          "x-id": "ComparePage_81_14",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 81,
          columnNumber: 15
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 79,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "flex-1",
        "x-file-name": "ComparePage",
        "x-line-number": "83",
        "x-column": "12",
        "x-component": "div",
        "x-id": "ComparePage_83_12",
        "x-dynamic": "false"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 83,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("button", {
        className: "btn btn-primary",
        onClick: playBoth,
        "data-testid": "compare-play",
        "x-file-name": "ComparePage",
        "x-line-number": "84",
        "x-column": "12",
        "x-component": "button",
        "x-id": "ComparePage_84_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_10__["default"], {
          size: 14,
          "x-file-name": "ComparePage",
          "x-line-number": "84",
          "x-column": "94",
          "x-component": "Play",
```

```
          "x-id": "ComparePage_84_94",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 84,
          columnNumber: 95
        }, this), " Play A/B"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 84,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("button", {
        className: "btn",
        onClick: () => (0,_lib_audio__WEBPACK_IMPORTED_MODULE_9__.getAudio)().stop(),
        "data-testid": "compare-stop",
        "x-file-name": "ComparePage",
        "x-line-number": "85",
        "x-column": "12",
        "x-component": "button",
        "x-id": "ComparePage_85_12",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_11__["default"], {
          size: 14,
          "x-file-name": "ComparePage",
          "x-line-number": "85",
          "x-column": "97",
          "x-component": "Square",
          "x-id": "ComparePage_85_97",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 85,
          columnNumber: 98
        }, this), " Stop"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 85,
        columnNumber: 13
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 65,
      columnNumber: 11
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_CompareProfile__WEBPACK_IMPORTED_MODULE_2__["default"], {
```

```
        seqA: sideA.sequence,
        groupsA: groupsA,
        seqB: sideB.sequence,
        groupsB: groupsB,
        windows: windows,
        metric: metric,
        matchedBlocks: matched,
        onWindowClick: (side, window) => setZoom({
          side,
          window
        }),
        "x-file-name": "ComparePage",
        "x-line-number": "88",
        "x-column": "10",
        "x-component": "CompareProfile",
        "x-id": "ComparePage_88_10",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 88,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_MatchedBlocks__WEBPACK_IMPORTED_MODULE_3__["default"], {
        blocks: matched,
        onSelect: b => sonner__WEBPACK_IMPORTED_MODULE_12__.toast.info(`Block: $
{b.text.slice(0, 40)} · A@${b.aPos} B@${b.bPos}`),
        "x-file-name": "ComparePage",
        "x-line-number": "99",
        "x-column": "10",
        "x-component": "MatchedBlocks",
        "x-id": "ComparePage_99_10",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 99,
        columnNumber: 11
      }, this), zoom.window != null && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)(ZoomPanel, {
        sideA: sideA,
        sideB: sideB,
        windows: windows,
        window: zoom.window,
        "x-file-name": "ComparePage",
        "x-line-number": "102",
        "x-column": "12",
        "x-component": "ZoomPanel",
        "x-id": "ComparePage_102_12",
        "x-dynamic": "true"
```

```
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 102,
        columnNumber: 13
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_MotifScanner__WEBPACK_IMPORTED_MODULE_4__["default"], {
        seqA: sideA.sequence,
        seqB: sideB.sequence,
        "x-file-name": "ComparePage",
        "x-line-number":
 "105",
        "x-column": "10",
        "x-component": "MotifScanner",
        "x-id": "ComparePage_105_10",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 105,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_Remainders__WEBPACK_IMPORTED_MODULE_5__["default"], {
        seqA: sideA.sequence,
        seqB: sideB.sequence,
        blocks: matched,
        "x-file-name": "ComparePage",
        "x-line-number": "106",
        "x-column": "10",
        "x-component": "Remainders",
        "x-id": "ComparePage_106_10",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 106,
        columnNumber: 11
      }, this)]
    }, void 0, true)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 52,
    columnNumber: 5
  }, this);
}
_s(ComparePage, "NJoKt+zQVtFRUHmd0YxVRq/Knpo=", false, function () {
  return [_context_SequenceContext__WEBPACK_IMPORTED_MODULE_7__.useSequence];
});
_c = ComparePage;
function ZoomPanel({
```

```
  sideA,
  sideB,
  windows,
  window
}) {
  const sizeA = Math.max(1, Math.floor(sideA.sequence.length / windows));
  const sizeB = Math.max(1, Math.floor(sideB.sequence.length / windows));
  const aStart = window * sizeA;
  const bStart = window * sizeB;
  const aSlice = sideA.sequence.slice(aStart, aStart + sizeA);
  const bSlice = sideB.sequence.slice(bStart, bStart + sizeB);
  const gA = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__.mirrorGroup)(aSlice);
  const gB = (0,_lib_mirrorGroups__WEBPACK_IMPORTED_MODULE_8__.mirrorGroup)(bSlice);
  const minLen = Math.min(aSlice.length, bSlice.length);
  let identity = 0;
  for (let i = 0; i < minLen; i++) if (aSlice[i] === bSlice[i]) identity++;
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
    className: "panel p-5",
    "data-testid": "zoom-panel",
    "x-file-name": "ComparePage",
    "x-line-number": "127",
    "x-column": "4",
    "x-component": "div",
    "x-id": "ComparePage_127_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
      className: "flex items-baseline justify-between mb-3",
      "x-file-name": "ComparePage",
      "x-line-number": "128",
      "x-column": "6",
      "x-component": "div",
      "x-id": "ComparePage_128_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        "x-file-name": "ComparePage",
        "x-line-number": "129",
        "x-column": "8",
        "x-component": "div",
        "x-id": "ComparePage_129_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "ComparePage",
          "x-line-number": "130",
          "x-column": "10",
```

```
        "x-component": "div",
        "x-id": "ComparePage_130_10",
        "x-dynamic": "true",
        "x-source-type": "prop",
        "x-source-var": "window",
        "x-source-editable": "false",
        children: ["Zoom \xB7 window ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "130",
          "x-column": "10",
          "x-component": "div",
          "x-id": "ComparePage_130_10_expr1",
          "x-dynamic": "true",
          "x-source-type": "prop",
          "x-source-var": "window",
          "x-source-editable": "false",
          children: window
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 130,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("h3", {
        className: "font-heading text-xl font-semibold mt-1",
        "x-file-name": "ComparePage",
        "x-line-number": "131",
        "x-column": "10",
        "x-component": "h3",
        "x-id": "ComparePage_131_10",
        "x-dynamic": "false",
        children: "Microscope view"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 131,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 129,
      columnNumber: 9
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
```

```
        className: "pill",
        "x-file-name": "ComparePage",
        "x-line-number": "133",
        "x-column": "8",
        "x-component": "div",
        "x-id": "ComparePage_133_8",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: ["identity ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "133",
          "x-column": "8",
          "x-component": "div",
          "x-id": "ComparePage_133_8_expr1",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: minLen ? (identity / minLen * 100).toFixed(1) : 0
        }, void 0, false), "%"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 133,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 128,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
      className: "grid grid-cols-1 md:grid-cols-2 gap-4",
      "x-file-name": "ComparePage",
      "x-line-number": "135",
      "x-column": "6",
      "x-component": "div",
      "x-id": "ComparePage_135_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        "x-file-name": "ComparePage",
        "x-line-number": "136",
        "x-column": "8",
```

```
      "x-component": "div",
      "x-id": "ComparePage_136_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "eyebrow mb-2",
        "x-file-name": "ComparePage",
        "x-line-number": "137",
        "x-column": "10",
        "x-component": "div",
        "x-id": "ComparePage_137_10",
        "x-dynamic": "true",
        "x-source-type": "unknown",
        "x-source-var": "aStart",
        "x-source-editable": "false",
        children: ["A: bases ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "137",
          "x-column": "10",
          "x-component": "div",
          "x-id": "ComparePage_137_10_expr1",
          "x-dynamic": "true",
          "x-source-type": "unknown",
          "x-source-var": "aStart",
          "x-source-editable": "false",
          children: aStart
        }, void 0, false), "\u2013", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
          "data-ve-dynamic": "true",
          "x-excluded": "true",
          style: {
            display: "contents"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "137",
          "x-column": "10",
          "x-component": "div",
          "x-id": "ComparePage_137_10_expr3",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: aStart + aSlice.length
        }, void 0, false)]
```

```
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 137,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
          className: "p-2 rounded",
          style: {
            background: "rgba(5,7,13,0.5)"
          },
          "x-file-name": "ComparePage",
          "x-line-number": "138",
          "x-column": "10",
          "x-component": "div",
          "x-id": "ComparePage_138_10",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: gA.map((g, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_LegoBlock__WEBPACK_IMPORTED_MODULE_6__["default"], {
            text: g,
            index: i,
            small: true,
            "x-file-name": "ComparePage",
            "x-line-number": "139",
            "x-column": "30",
            "x-component": "LegoBlock",
            "x-id": "ComparePage_139_30",
            "x-dynamic": "true",
            "x-source-type": "external",
            "x-source-var": "gA",
            "x-source-editable": "false",
            "x-array-var": "gA",
            "x-array-item-param": "g"
          }, i, false, {
            fileName: _jsxFileName,
            lineNumber: 139,
            columnNumber: 31
          }, this))
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 138,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,

        lineNumber: 136,
```

```
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        "x-file-name": "ComparePage",
        "x-line-number": "142",
        "x-column": "8",
        "x-component": "div",
        "x-id": "ComparePage_142_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
          className: "eyebrow mb-2",
          "x-file-name": "ComparePage",
          "x-line-number": "143",
          "x-column": "10",
          "x-component": "div",
          "x-id": "ComparePage_143_10",
          "x-dynamic": "true",
          "x-source-type": "unknown",
          "x-source-var": "bStart",
          "x-source-editable": "false",
          children: ["B: bases ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "ComparePage",
            "x-line-number": "143",
            "x-column": "10",
            "x-component": "div",
            "x-id": "ComparePage_143_10_expr1",
            "x-dynamic": "true",
            "x-source-type": "unknown",
            "x-source-var": "bStart",
            "x-source-editable": "false",
            children: bStart
          }, void 0, false), "\u2013", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "ComparePage",
            "x-line-number": "143",
            "x-column": "10",
            "x-component": "div",
```

```
          "x-id": "ComparePage_143_10_expr3",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: bStart + bSlice.length
        }, void 0, false)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 143,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)("div", {
        className: "p-2 rounded",
        style: {
          background: "rgba(5,7,13,0.5)"
        },
        "x-file-name": "ComparePage",
        "x-line-number": "144",
        "x-column": "10",
        "x-component": "div",
        "x-id": "ComparePage_144_10",
        "x-dynamic": "true",
        "x-source-type": "computed",
        "x-source-editable": "false",
        children: gB.map((g, i) => /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_13__.jsxDEV)
(_components_LegoBlock__WEBPACK_IMPORTED_MODULE_6__["default"], {
          text: g,
          index: i,
          small: true,
          "x-file-name": "ComparePage",
          "x-line-number": "145",
          "x-column": "30",
          "x-component": "LegoBlock",
          "x-id": "ComparePage_145_30",
          "x-dynamic": "true",
          "x-source-type": "external",
          "x-source-var": "gB",
          "x-source-editable": "false",
          "x-array-var": "gB",
          "x-array-item-param": "g"
        }, i, false, {
          fileName: _jsxFileName,
          lineNumber: 145,
          columnNumber: 31
        }, this))
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 144,
```

```
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 142,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 135,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 127,
    columnNumber: 5
  }, this);
}
_c2 = ZoomPanel;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "ComparePage");
__webpack_require__.$Refresh$.register(_c2, "ZoomPanel");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
```

```
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/pages/Home.jsx"
/*!****************************!*\
  !*** ./src/pages/Home.jsx ***!
  \****************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ Home)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_router_dom__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-router-dom */ "./node_modules/react-router/dist/development/chunk-
4N6VE7H7.mjs");
/* harmony import */ var _components_FastaInput__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../components/FastaInput */ "./src/components/FastaInput.jsx");
/* harmony import */ var _context_SequenceContext__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../context/SequenceContext */ "./src/context/SequenceContext.jsx");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/git-compare-
arrows.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/library.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/waves.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/zap.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/pages/Home.jsx",
  _s = __webpack_require__.$Refresh$.signature();
```

```
function Home() {
  _s();
  const nav = (0,react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useNavigate)();
  const {
    loadCurrent
  } = (0,_context_SequenceContext__WEBPACK_IMPORTED_MODULE_3__.useSequence)();
  const handleLoad = ({
    name,
    sequence,
    type,
    source
  }) => {
    loadCurrent(name, sequence, type, source);
    setTimeout(() => nav("/atlas"), 250);
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
    className: "space-y-8",
    "data-testid": "home-page",
    "x-file-name": "Home",
    "x-line-number": "17",
    "x-column": "4",
    "x-component": "div",
    "x-id": "Home_17_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("section", {
      className: "grid grid-cols-1 lg:grid-cols-12 gap-6",
      "x-file-name": "Home",
      "x-line-number": "18",
      "x-column": "6",
      "x-component": "section",
      "x-id": "Home_18_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
        className: "lg:col-span-7 panel p-8 relative overflow-hidden grid-bg",
        "x-file-name": "Home",
        "x-line-number": "19",
        "x-column": "8",
        "x-component": "div",
        "x-id": "Home_19_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "Home",
        "x-line-number": "20",
        "x-column": "10",
        "x-component": "div",
        "x-id": "Home_20_10",
        "x-dynamic": "false",
        children: "Mirror Grouping Workbench"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 20,
        columnNumber: 11
       }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("h1", {
        className: "font-heading font-extrabold mt-3 text-4xl sm:text-5xl lg:text-6xl leading-tight
tracking-tight",
        "x-file-name": "Home",
        "x-line-number": "21",
        "x-column": "10",
        "x-component": "h1",
        "x-id": "Home_21_10",
        "x-dynamic": "false",
        children: ["Take a sequence apart ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("br", {
          "x-file-name": "Home",
          "x-line-number":
 "22",
          "x-column": "34",
          "x-component": "br",
          "x-id": "Home_22_34",
          "x-dynamic": "false"
         }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 22,
          columnNumber: 35
         }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
          style: {
            color: "var(--teal)"
          },
          "x-file-name": "Home",
          "x-line-number": "23",
          "x-column": "12",
          "x-component": "span",
          "x-id": "Home_23_12",
          "x-dynamic": "false",
          children: "where it repeats itself."
         }, void 0, false, {
```

```
          fileName: _jsxFileName,
          lineNumber: 23,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 21,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("p", {
        className: "mt-4 max-w-xl",
        style: {
          color: "var(--muted)"
        },
        "x-file-name": "Home",
        "x-line-number": "25",
        "x-column": "10",
        "x-component": "p",
        "x-id": "Home_25_10",
        "x-dynamic": "false",
        children: "Load FASTA or numeric strings. See Zilkowsky mirror groups as color-coded Lego blocks. Hear the same sequence on a treble + bass staff with a 432 Hz drone and a pentatonic voice. Compare two genomes structurally. Fold the whole thing through Joseph Schillinger's devices."
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 25,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
        className: "mt-8 grid grid-cols-1 sm:grid-cols-3 gap-3",
        "x-file-name": "Home",
        "x-line-number": "30",
        "x-column": "10",
        "x-component": "div",
        "x-id": "Home_30_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)(FeatureCard, {
          icon: lucide_react__WEBPACK_IMPORTED_MODULE_6__["default"],
          title: "Atlas",
          desc: "Blocks, staff, sonify",
          onClick: () => nav("/atlas"),
          testid: "cta-atlas",
          "x-file-name": "Home",
          "x-line-number": "31",
          "x-column": "12",
          "x-component": "FeatureCard",
          "x-id": "Home_31_12",
          "x-dynamic": "true"
```

```
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 31,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)(FeatureCard, {
          icon: lucide_react__WEBPACK_IMPORTED_MODULE_4__["default"],
          title: "Compare",
          desc: "Two sequences side-by-side",
          onClick: () => nav("/compare"),
          testid: "cta-compare",
          "x-file-name": "Home",
          "x-line-number": "32",
          "x-column": "12",
          "x-component": "FeatureCard",
          "x-id": "Home_32_12",
          "x-dynamic": "true"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 32,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)(FeatureCard, {
          icon: lucide_react__WEBPACK_IMPORTED_MODULE_5__["default"],
          title: "Library",
          desc: "Saved public sequences",
          onClick: () => nav("/library"),
          testid: "cta-library",
          "x-file-name": "Home",
          "x-line-number": "33",
          "x-column": "12",
          "x-component": "FeatureCard",
          "x-id": "Home_33_12",
          "x-dynamic": "true"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 33,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 30,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 19,
      columnNumber: 9
    }, this), /*#__PURE__*/
```

```
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
      className: "lg:col-span-5",
      "x-file-name": "Home",
      "x-line-number": "36",
      "x-column": "8",
      "x-component": "div",
      "x-id": "Home_36_8",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)
(_components_FastaInput__WEBPACK_IMPORTED_MODULE_2__["default"], {
        onLoad: handleLoad,
        label: "Load a sequence",
        "x-file-name": "Home",
        "x-line-number": "37",
        "x-column": "10",
        "x-component": "FastaInput",
        "x-id": "Home_37_10",
        "x-dynamic": "true"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 37,
        columnNumber: 11
      }, this)
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 36,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 18,
    columnNumber: 7
  }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("section", {
    className: "panel p-6 flex flex-wrap items-center gap-5 text-xs",
    style: {
      color: "var(--muted)"
    },
    "x-file-name": "Home",
    "x-line-number": "41",
    "x-column": "6",
    "x-component": "section",
    "x-id": "Home_41_6",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
      className: "pill",
      "x-file-name": "Home",
```

```
        "x-line-number": "42",
        "x-column": "8",
        "x-component": "span",
        "x-id": "Home_42_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_7__["default"], {
          size: 12,
          "x-file-name": "Home",
          "x-line-number": "42",
          "x-column": "31",
          "x-component": "Zap",
          "x-id": "Home_42_31",
          "x-dynamic": "false"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 42,
          columnNumber: 32
        }, this), " 432 Hz drone bass"]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 42,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
        className: "pill",
        "x-file-name": "Home",
        "x-line-number": "43",
        "x-column": "8",
        "x-component": "span",
        "x-id": "Home_43_8",
        "x-dynamic": "false",
        children: "DNA pentatonic (A\u2192C \xB7 T\u2192D \xB7 G\u2192E \xB7 C\u2192G \xB7
N\u2192A)"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 43,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
        className: "pill",
        "x-file-name": "Home",
        "x-line-number": "44",
        "x-column": "8",
        "x-component": "span",
        "x-id": "Home_44_8",
        "x-dynamic": "false",
        children: "Digits pentatonic \xD7 2 octaves (0\u20134 lower \xB7 5\u20139 upper)"
```

```
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 44,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
        className: "pill",
        "x-file-name": "Home",
        "x-line-number": "45",
        "x-column": "8",
        "x-component": "span",
        "x-id": "Home_45_8",
        "x-dynamic": "false",
        children: "Retrograde \xB7 circular permutation \xB7 inversion \xB7 augmentation"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 45,
        columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("span", {
        className: "pill",
        "x-file-name": "Home",
        "x-line-number": "46",
        "x-column": "8",
        "x-component": "span",
        "x-id": "Home_46_8",
        "x-dynamic": "false",
        children: "PAM (NGG) scanner \xB7 palindrome depth \xB7 resultant rhythms"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 46,
        columnNumber: 9
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 41,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 17,
    columnNumber: 5
  }, this);
}
_s(Home, "bT/jBsvd6nIdSQapwhRZ6nrzRZc=", false, function () {
  return [react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useNavigate,
_context_SequenceContext__WEBPACK_IMPORTED_MODULE_3__.useSequence];
});
_c = Home;
```

```
function FeatureCard({
  icon: Icon,
  title,
  desc,
  onClick,
  testid
}) {
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("button", {
    onClick: onClick,
    "data-testid": testid,
    className: "text-left p-4 rounded-xl transition-all",
    style: {
      background: "rgba(17,24,39,0.7)",
      border: "1px solid var(--line)"
    },
    "x-file-name": "Home",
    "x-line-number": "54",
    "x-column": "4",
    "x-component": "button",
    "x-id": "Home_54_4",
    "x-dynamic": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)(Icon, {
      size: 18,
      style: {
        color: "var(--teal)"

      },
      "x-file-name": "Home",
      "x-line-number": "56",
      "x-column": "6",
      "x-component": "Icon",
      "x-id": "Home_56_6",
      "x-dynamic": "false"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 56,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
      className: "font-heading font-semibold mt-2",
      "x-file-name": "Home",
      "x-line-number": "57",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Home_57_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
```

```
      "x-source-var": "title",
      "x-source-editable": "false",
      children: title
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 57,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_8__.jsxDEV)("div", {
      className: "text-xs mt-1",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "Home",
      "x-line-number": "58",
      "x-column": "6",
      "x-component": "div",
      "x-id": "Home_58_6",
      "x-dynamic": "true",
      "x-source-type": "prop",
      "x-source-var": "desc",
      "x-source-editable": "false",
      children: desc
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 58,
      columnNumber: 7
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 54,
    columnNumber: 5
  }, this);
}
_c2 = FeatureCard;
var _c, _c2;
__webpack_require__.$Refresh$.register(_c, "Home");
__webpack_require__.$Refresh$.register(_c2, "FeatureCard");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
```

```
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}

if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
        $ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
        $ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./src/pages/LibraryPage.jsx"
/*!***********************************!*\
  !*** ./src/pages/LibraryPage.jsx ***!
  \***********************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ LibraryPage)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var react_router_dom__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-router-dom */ "./node_modules/react-router/dist/development/chunk-
4N6VE7H7.mjs");
/* harmony import */ var sonner__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! sonner */ "./node_modules/sonner/dist/index.mjs");
/* harmony import */ var _lib_api__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../lib/api */ "./src/lib/api.js");
/* harmony import */ var _context_SequenceContext__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../context/SequenceContext */ "./src/context/SequenceContext.jsx");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/arrow-right.js");
```

```
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/list-filter.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/search.js");
/* harmony import */ var lucide_react__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! lucide-react */ "./node_modules/lucide-react/dist/esm/icons/trash-2.js");
/* harmony import */ var react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! react/jsx-dev-runtime */ "./node_modules/react/jsx-dev-runtime.js");
/* provided dependency */ var __react_refresh_utils__ = __webpack_require__(/*!
./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js */
"./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js");
__webpack_require__.$Refresh$.runtime = __webpack_require__(/*! ./node_modules/react-
refresh/runtime.js */ "./node_modules/react-refresh/runtime.js");

var _jsxFileName = "/app/frontend/src/pages/LibraryPage.jsx",
  _s = __webpack_require__.$Refresh$.signature();




const TYPE_COLORS = {
  dna: {
    bg: "rgba(0,240,255,0.14)",
    fg: "#00f0ff",
    border: "rgba(0,240,255,0.35)"
  },
  digits: {
    bg: "rgba(255,176,0,0.14)",
    fg: "#ffb000",
    border: "rgba(255,176,0,0.35)"
  },
  text: {
    bg: "rgba(224,36,166,0.14)",
    fg: "#f472b6",
    border: "rgba(224,36,166,0.35)"
  }
};
function LibraryPage() {
  _s();
  const nav = (0,react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useNavigate)();
  const {
    loadCurrent,
    loadSide
  } = (0,_context_SequenceContext__WEBPACK_IMPORTED_MODULE_4__.useSequence)();
  const [items, setItems] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)([]);
  const [q, setQ] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("");
```

```
  const [typeFilter, setTypeFilter] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("");
  const [sort, setSort] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)("created_at");
  const [loading, setLoading] = (0,react__WEBPACK_IMPORTED_MODULE_0__.useState)(true);
  const fetch = async () => {
    setLoading(true);
    try {
      const data = await (0,_lib_api__WEBPACK_IMPORTED_MODULE_3__.listSequences)({
        q,
        sequence_type: typeFilter || undefined,
        sort
      });
      setItems(data);
    } catch (e) {
      sonner__WEBPACK_IMPORTED_MODULE_2__.toast.error("Failed to load library");
    } finally {
      setLoading(false);
    }
  };
  (0,react__WEBPACK_IMPORTED_MODULE_0__.useEffect)(() => {
    fetch();
  }, [q, typeFilter, sort]); // eslint-disable-line react-hooks/exhaustive-deps

  const openInAtlas = async id => {
    const doc = await (0,_lib_api__WEBPACK_IMPORTED_MODULE_3__.getSequence)(id);
    loadCurrent(doc.name, doc.sequence, doc.sequence_type, doc.source);
    nav("/atlas");
  };
  const loadAs = async (id, side) => {
    const doc = await (0,_lib_api__WEBPACK_IMPORTED_MODULE_3__.getSequence)(id);
    loadSide(side, doc.name, doc.sequence, doc.sequence_type, doc.source);
    sonner__WEBPACK_IMPORTED_MODULE_2__.toast.success(`Loaded as sequence ${side}`);
    nav("/compare");
  };
  const remove = async id => {
    if (!window.confirm("Delete this sequence from the public library?")) return;
    await (0,_lib_api__WEBPACK_IMPORTED_MODULE_3__.deleteSequence)(id);
    sonner__WEBPACK_IMPORTED_MODULE_2__.toast.success("Deleted");
    fetch();
  };
  return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
    className: "space-y-6",
    "data-testid": "library-page",
    "x-file-name": "LibraryPage",
    "x-line-number": "56",
    "x-column": "4",
    "x-component": "div",
    "x-id": "LibraryPage_56_4",
    "x-dynamic": "true",
```

```
    "x-source-type": "computed",
    "x-source-editable": "false",
    children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
      className: "flex items-baseline justify-between flex-wrap gap-3",
      "x-file-name": "LibraryPage",
      "x-line-number": "57",
      "x-column": "6",
      "x-component": "div",
      "x-id": "LibraryPage_57_6",
      "x-dynamic": "false",
      children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        "x-file-name": "LibraryPage",
        "x-line-number": "58",
        "x-column": "8",
        "x-component": "div",
        "x-id": "LibraryPage_58_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
          className: "eyebrow",
          "x-file-name": "LibraryPage",
          "x-line-number": "59",
          "x-column": "10",
          "x-component": "div",
          "x-id": "LibraryPage_59_10",
          "x-dynamic": "false",
          children: "Library"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 59,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("h2", {
          className: "font-heading text-2xl sm:text-3xl font-bold mt-1",
          "x-file-name": "LibraryPage",
          "x-line-number": "60",
          "x-column": "10",
          "x-component": "h2",
          "x-id": "LibraryPage_60_10",
          "x-dynamic": "false",
          children: "Public sequence repository"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 60,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
```

```
        fileName: _jsxFileName,
        lineNumber: 58,
        columnNumber: 9
      }, this)
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 57,
      columnNumber: 7
    }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
      className: "panel p-4 flex flex-wrap items-center gap-3",
      "data-testid": "library-controls",

      "x-file-name": "LibraryPage",
      "x-line-number": "64",
      "x-column": "6",
      "x-component": "div",
      "x-id": "LibraryPage_64_6",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        className: "flex items-center gap-2 flex-1 min-w-[240px]",
        "x-file-name": "LibraryPage",
        "x-line-number": "65",
        "x-column": "8",
        "x-component": "div",
        "x-id": "LibraryPage_65_8",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_7__["default"], {
          size: 14,
          style: {
            color: "var(--muted)"
          }
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 66,
          columnNumber: 11
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("input", {
          className: "input",
          placeholder: "Search by name\u2026",
          value: q,
          onChange: e => setQ(e.target.value),
          "data-testid": "library-search",
          "x-file-name": "LibraryPage",
          "x-line-number": "67",
          "x-column": "10",
```

```
        "x-component": "input",
        "x-id": "LibraryPage_67_10",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 67,
        columnNumber: 11
       }, this)]
      }, void 0, true, {
       fileName: _jsxFileName,
       lineNumber: 65,
       columnNumber: 9
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
       className: "flex items-center gap-2",
       "x-file-name": "LibraryPage",
       "x-line-number": "69",
       "x-column": "8",
       "x-component": "div",
       "x-id": "LibraryPage_69_8",
       "x-dynamic": "false",
       children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_6__["default"], {
        size: 14,
        style: {
         color: "var(--muted)"
        },
        "x-file-name": "LibraryPage",
        "x-line-number": "70",
        "x-column": "10",
        "x-component": "ListFilter",
        "x-id": "LibraryPage_70_10",
        "x-dynamic": "false"
       }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 70,
        columnNumber: 11
       }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("select", {
        className: "select",
        style: {
         width: 140
        },
        value: typeFilter,
        onChange: e => setTypeFilter(e.target.value),
        "data-testid": "library-type-filter",
        "x-file-name": "LibraryPage",
        "x-line-number": "71",
```

```
        "x-column": "10",
        "x-component": "select",
        "x-id": "LibraryPage_71_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "",
          "x-file-name": "LibraryPage",
          "x-line-number": "72",
          "x-column": "12",
          "x-component": "option",
          "x-id": "LibraryPage_72_12",
          "x-dynamic": "false",
          children: "All types"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 72,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "dna",
          "x-file-name": "LibraryPage",
          "x-line-number": "73",
          "x-column": "12",
          "x-component": "option",
          "x-id": "LibraryPage_73_12",
          "x-dynamic": "false",
          children: "DNA"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 73,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "digits",
          "x-file-name": "LibraryPage",
          "x-line-number": "74",
          "x-column": "12",
          "x-component": "option",
          "x-id": "LibraryPage_74_12",
          "x-dynamic": "false",
          children: "Digits"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 74,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "text",
```

```
          "x-file-name": "LibraryPage",
          "x-line-number": "75",
          "x-column": "12",
          "x-component": "option",
          "x-id": "LibraryPage_75_12",
          "x-dynamic": "false",
          children: "Text"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 75,
          columnNumber: 13
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 71,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("select", {
        className: "select",
        style: {
          width: 180
        },
        value: sort,
        onChange: e => setSort(e.target.value),
        "data-testid": "library-sort",
        "x-file-name": "LibraryPage",
        "x-line-number": "77",
        "x-column": "10",
        "x-component": "select",
        "x-id": "LibraryPage_77_10",
        "x-dynamic": "false",
        children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "created_at",
          "x-file-name": "LibraryPage",
          "x-line-number": "78",
          "x-column": "12",
          "x-component": "option",
          "x-id": "LibraryPage_78_12",
          "x-dynamic": "false",
          children: "Recently added"
        }, void 0, false, {
          fileName: _jsxFileName,
          lineNumber: 78,
          columnNumber: 13
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
          value: "length",
          "x-file-name": "LibraryPage",
```

```
            "x-line-number": "79",
            "x-column": "12",
            "x-component": "option",
            "x-id": "LibraryPage_79_12",
            "x-dynamic": "false",
            children: "Longest"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 79,
            columnNumber: 13
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
            value: "group_count",
            "x-file-name": "LibraryPage",
            "x-line-number": "80",
            "x-column": "12",
            "x-component": "option",
            "x-id": "LibraryPage_80_12",
            "x-dynamic": "false",
            children: "Most groups"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 80,
            columnNumber: 13
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("option", {
            value: "name",
            "x-file-name": "LibraryPage",
            "x-line-number": "81",
            "x-column": "12",
            "x-component": "option",
            "x-id": "LibraryPage_81_12",
            "x-dynamic": "false",
            children: "Name (A-Z)"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 81,
            columnNumber: 13
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 77,
          columnNumber: 11
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 69,
        columnNumber: 9
      }, this)]
```

```
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 64,
      columnNumber: 7
    }, this), loading ? /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
      className: "text-sm",
      style: {
        color: "var(--muted)"
      },
      "x-file-name": "LibraryPage",
      "x-line-number": "87",
      "x-column": "8",
      "x-component": "div",
      "x-id": "LibraryPage_87_8",
      "x-dynamic": "false",
      children: "Loading\u2026"
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 87,
      columnNumber: 9
    }, this) : items.length === 0 ? /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
      className: "panel p-8 text-center",
      "data-testid": "library-empty",
      "x-file-name": "LibraryPage",
      "x-line-number": "89",
      "x-column": "8",
      "x-component": "div",
      "x-id": "LibraryPage_89_8",
      "x-dynamic": "false",
      children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        className: "eyebrow",
        "x-file-name": "LibraryPage",
        "x-line-number": "90",
        "x-column": "10",
        "x-component": "div",
        "x-id": "LibraryPage_90_10",
        "x-dynamic": "false",
        children: "Nothing here yet"
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 90,
        columnNumber: 11
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        className: "mt-2",
        style: {
```

```
          color: "var(--muted)"
        },
        "x-file-name": "LibraryPage",
        "x-line-number": "91",
        "x-column": "10",
        "x-component": "div",
        "x-id": "LibraryPage_91_10",
        "x-dynamic": "false",
        children: "Load a sequence
 in Atlas and press \u201CSave to library\u201D to publish it here."
      }, void 0, false, {
        fileName: _jsxFileName,
        lineNumber: 91,
        columnNumber: 11
      }, this)]
    }, void 0, true, {
      fileName: _jsxFileName,
      lineNumber: 89,
      columnNumber: 9
    }, this) : /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
      className: "grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-4",
      "data-testid": "library-grid",
      "x-file-name": "LibraryPage",
      "x-line-number": "96",
      "x-column": "8",
      "x-component": "div",
      "x-id": "LibraryPage_96_8",
      "x-dynamic": "true",
      "x-source-type": "computed",
      "x-source-editable": "false",
      children: items.map(it => {
        const c = TYPE_COLORS[it.sequence_type] || TYPE_COLORS.text;
        return /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
          className: "panel p-5 flex flex-col",
          "data-testid": `library-card-${it.id}`,
          "x-file-name": "LibraryPage",
          "x-line-number": "100",
          "x-column": "14",
          "x-component": "div",
          "x-id": "LibraryPage_100_14",
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
            className: "flex items-start justify-between",
            "x-file-name": "LibraryPage",
            "x-line-number": "101",
            "x-column": "16",
```

```
          "x-component": "div",
          "x-id": "LibraryPage_101_16",
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
            "x-file-name": "LibraryPage",
            "x-line-number": "102",
            "x-column": "18",
            "x-component": "div",
            "x-id": "LibraryPage_102_18",
            "x-dynamic": "false",
            children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
              className: "font-heading text-lg font-semibold",
              "x-file-name": "LibraryPage",
              "x-line-number": "103",
              "x-column": "20",
              "x-component": "div",
              "x-id": "LibraryPage_103_20",
              "x-dynamic": "true",
              "x-source-type": "static-imported",
              "x-source-var": "items",
              "x-source-path": "name",
              "x-source-editable": "false",
              "x-array-var": "items",
              "x-array-item-param": "it",
              children: it.name
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 103,
              columnNumber: 21
            }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
              className: "text-xs mt-1",
              style: {
                color: "var(--muted)"
              },
              "x-file-name": "LibraryPage",
              "x-line-number": "104",
              "x-column": "20",
              "x-component": "div",
              "x-id": "LibraryPage_104_20",
              "x-dynamic": "true",
              "x-source-type": "computed",
              "x-source-editable": "false",
              children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
                "data-ve-dynamic": "true",
                "x-excluded": "true",
```

```
              style: {
                display: "contents"
              },
              "x-file-name": "LibraryPage",
              "x-line-number": "104",
              "x-column": "20",
              "x-component": "div",
              "x-id": "LibraryPage_104_20_expr1",
              "x-dynamic": "true",
              "x-source-type": "computed",
              "x-source-editable": "false",
              children: new Date(it.created_at).toLocaleDateString()
            }, void 0, false), " \xB7 ", /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
              "data-ve-dynamic": "true",
              "x-excluded": "true",
              style: {
                display: "contents"
              },
              "x-file-name": "LibraryPage",
              "x-line-number": "104",
              "x-column": "20",
              "x-component": "div",
              "x-id": "LibraryPage_104_20_expr3",
              "x-dynamic": "true",
              "x-source-type": "computed",
              "x-source-editable": "false",
              children: it.source || "user"
            }, void 0, false)]
          }, void 0, true, {
            fileName: _jsxFileName,
            lineNumber: 104,
            columnNumber: 21
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 102,
          columnNumber: 19
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
          className: "pill",
          style: {
            background: c.bg,
            color: c.fg,
            borderColor: c.border
          },
          "x-file-name": "LibraryPage",
          "x-line-number": "108",
          "x-column": "18",
```

```
            "x-component": "span",
            "x-id": "LibraryPage_108_18",
            "x-dynamic": "true",
            "x-source-type": "computed",
            "x-source-editable": "false",
            children: it.sequence_type.toUpperCase()
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 108,
            columnNumber: 19
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 101,
          columnNumber: 17
        }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
          className: "mt-3 flex gap-2",
          "x-file-name": "LibraryPage",
          "x-line-number": "112",
          "x-column": "16",
          "x-component": "div",
          "x-id": "LibraryPage_112_16",
          "x-dynamic": "true",
          "x-source-type": "computed",
          "x-source-editable": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
            className: "pill",
            "x-file-name": "LibraryPage",
            "x-line-number": "113",
            "x-column": "18",
            "x-component": "span",
            "x-id": "LibraryPage_113_18",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "items",
            "x-source-path": "length",
            "x-source-editable": "false",
            "x-array-var": "items",
            "x-array-item-param": "it",
            children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
              "data-ve-dynamic": "true",
              "x-excluded": "true",
              style: {
                display: "contents"
              },
              "x-file-name": "LibraryPage",
```

```
            "x-line-number": "113",
            "x-column": "18",
            "x-component": "span",
            "x-id": "LibraryPage_113_18_expr0",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "items",
            "x-source-path": "length",
            "x-source-editable": "false",
            "x-array-var": "items",
            "x-array-item-param": "it",
            children: it.length
          }, void 0, false), " sym"]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 113,
          columnNumber: 19
        }, this), it.group_count != null && /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
          className: "pill",
          "x-file-name": "LibraryPage",
          "x-line-number": "114",
          "x-column": "45",
          "x-component": "span",
          "x-id": "LibraryPage_114_45",
          "x-dynamic": "true",
          "x-source-type": "static-imported",
          "x-source-var": "items",
          "x-source-path": "group_count",
          "x-source-editable": "false",
          "x-array-var": "items",
          "x-array-item-param": "it",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("span", {
            "data-ve-dynamic": "true",
            "x-excluded": "true",
            style: {
              display: "contents"
            },
            "x-file-name": "LibraryPage",
            "x-line-number": "114",
            "x-column": "45",
            "x-component": "span",
            "x-id": "LibraryPage_114_45_expr0",
            "x-dynamic": "true",
            "x-source-type": "static-imported",
            "x-source-var": "items",
            "x-source-path": "group_count",
            "x-source-editable": "false",
```

```
            "x-array-var": "items",
            "x-array-item-param": "it",
            children: it.group_count
          }, void 0, false), " groups"]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 114,
          columnNumber: 46
        }, this)]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber:
 112,
        columnNumber: 17
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        className: "mt-3 font-mono text-xs p-2 rounded",
        style: {
          background: "rgba(5,7,13,0.5)",
          color: "var(--muted)",
          wordBreak: "break-all",
          maxHeight: 64,
          overflow: "hidden"
        },
        "x-file-name": "LibraryPage",
        "x-line-number": "116",
        "x-column": "16",
        "x-component": "div",
        "x-id": "LibraryPage_116_16",
        "x-dynamic": "true",
        "x-source-type": "static-imported",
        "x-source-var": "items",
        "x-source-path": "preview",
        "x-source-editable": "false",
        "x-array-var": "items",
        "x-array-item-param": "it",
        children: [it.preview, it.length > it.preview.length ? "…" : ""]
      }, void 0, true, {
        fileName: _jsxFileName,
        lineNumber: 116,
        columnNumber: 17
      }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("div", {
        className: "mt-4 flex flex-wrap gap-2",
        "x-file-name": "LibraryPage",
        "x-line-number": "119",
        "x-column": "16",
        "x-component": "div",
        "x-id": "LibraryPage_119_16",
```

```
          "x-dynamic": "false",
          children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("button", {
            className: "btn btn-primary",
            onClick: () => openInAtlas(it.id),
            "data-testid": `open-atlas-${it.id}`,
            "x-file-name": "LibraryPage",
            "x-line-number": "120",
            "x-column": "18",
            "x-component": "button",
            "x-id": "LibraryPage_120_18",
            "x-dynamic": "false",
            children: [/*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_5__["default"], {
              size: 14
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 121,
              columnNumber: 21
            }, this), " Open in Atlas"]
          }, void 0, true, {
            fileName: _jsxFileName,
            lineNumber: 120,
            columnNumber: 19
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("button", {
            className: "btn",
            onClick: () => loadAs(it.id, "A"),
            "data-testid": `load-a-${it.id}`,
            "x-file-name": "LibraryPage",
            "x-line-number": "123",
            "x-column": "18",
            "x-component": "button",
            "x-id": "LibraryPage_123_18",
            "x-dynamic": "false",
            children: "As A"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 123,
            columnNumber: 19
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("button", {
            className: "btn",
            onClick: () => loadAs(it.id, "B"),
            "data-testid": `load-b-${it.id}`,
            "x-file-name": "LibraryPage",
            "x-line-number": "124",
            "x-column": "18",
```

```
            "x-component": "button",
            "x-id": "LibraryPage_124_18",
            "x-dynamic": "false",
            children: "As B"
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 124,
            columnNumber: 19
          }, this), /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)("button", {
            className: "btn btn-ghost",
            onClick: () => remove(it.id),
            "data-testid": `delete-${it.id}`,
            "x-file-name": "LibraryPage",
            "x-line-number": "125",
            "x-column": "18",
            "x-component": "button",
            "x-id": "LibraryPage_125_18",
            "x-dynamic": "false",
            children: /*#__PURE__*/
(0,react_jsx_dev_runtime__WEBPACK_IMPORTED_MODULE_9__.jsxDEV)
(lucide_react__WEBPACK_IMPORTED_MODULE_8__["default"], {
              size: 14,
              "x-file-name": "LibraryPage",
              "x-line-number": "126",
              "x-column": "20",
              "x-component": "Trash2",
              "x-id": "LibraryPage_126_20",
              "x-dynamic": "true",
              "x-source-type": "external",
              "x-source-var": "items",
              "x-source-editable": "false",
              "x-array-var": "items",
              "x-array-item-param": "it"
            }, void 0, false, {
              fileName: _jsxFileName,
              lineNumber: 126,
              columnNumber: 21
            }, this)
          }, void 0, false, {
            fileName: _jsxFileName,
            lineNumber: 125,
            columnNumber: 19
          }, this)]
        }, void 0, true, {
          fileName: _jsxFileName,
          lineNumber: 119,
          columnNumber: 17
        }, this)]
```

```
        }, it.id, true, {
          fileName: _jsxFileName,
          lineNumber: 100,
          columnNumber: 15
        }, this);
      })
    }, void 0, false, {
      fileName: _jsxFileName,
      lineNumber: 96,
      columnNumber: 9
    }, this)]
  }, void 0, true, {
    fileName: _jsxFileName,
    lineNumber: 56,
    columnNumber: 5
  }, this);
}
_s(LibraryPage, "4PjwsXvXK3CJ8cghSQGS2D8Yvog=", false, function () {
  return [react_router_dom__WEBPACK_IMPORTED_MODULE_1__.useNavigate,
_context_SequenceContext__WEBPACK_IMPORTED_MODULE_4__.useSequence];
});
_c = LibraryPage;
var _c;
__webpack_require__.$Refresh$.register(_c, "LibraryPage");

const $ReactRefreshModuleId$ = __webpack_require__.$Refresh$.moduleId;
const $ReactRefreshCurrentExports$ = __react_refresh_utils__.getModuleExports(
        $ReactRefreshModuleId$
);

function $ReactRefreshModuleRuntime$(exports) {
        if (true) {
                let errorOverlay;
                if (true) {
                        errorOverlay = false;
                }
                let testMode;
                if (typeof __react_refresh_test__ !== 'undefined') {
                        testMode = __react_refresh_test__;
                }
                return __react_refresh_utils__.executeRuntime(
                        exports,
                        $ReactRefreshModuleId$,
                        module.hot,
                        errorOverlay,
                        testMode
                );
        }
}
```

```
if (typeof Promise !== 'undefined' && $ReactRefreshCurrentExports$ instanceof Promise) {
	$ReactRefreshCurrentExports$.then($ReactRefreshModuleRuntime$);
} else {
	$ReactRefreshModuleRuntime$($ReactRefreshCurrentExports$);
}

/***/ },

/***/ "./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js"
/*!
**********************************************************************************
****!*\
  !*** ./node_modules/@pmmmwh/react-refresh-webpack-plugin/lib/runtime/RefreshUtils.js ***!

\*********************************************************************************
*****/
(module, __unused_webpack_exports, __webpack_require__) {

/* global __webpack_require__ */
var Refresh = __webpack_require__(/*! react-refresh/runtime */ "./node_modules/react-
refresh/runtime.js");

/**
 * Extracts exports from a webpack module object.
 * @param {string} moduleId A Webpack module ID.
 * @returns {*} An exports object from the module.
 */
function getModuleExports(moduleId) {
  if (typeof moduleId === 'undefined') {
    // `moduleId` is unavailable, which indicates that this module is not in the cache,
    // which means we won't be able to capture any exports,
    // and thus they cannot be refreshed safely.
    // These are likely runtime or dynamically generated modules.
    return {};
  }
  var maybeModule = __webpack_require__.c[moduleId];
  if (typeof maybeModule === 'undefined') {
    // `moduleId` is available but the module in cache is unavailable,
    // which indicates the module is somehow corrupted (e.g. broken Webpacak `module` globals).
    // We will warn the user (as this is likely a mistake) and assume they cannot be refreshed.
    console.warn('[React Refresh] Failed to get exports for module: ' + moduleId + '.');
    return {};
  }
  var exportsOrPromise = maybeModule.exports;
  if (typeof Promise !== 'undefined' && exportsOrPromise instanceof Promise) {
    return exportsOrPromise.then(function (exports) {
      return exports;
    });
```

```
  }
  return exportsOrPromise;
}

/**
 * Calculates the signature of a React refresh boundary.
 * If this signature changes, it's unsafe to accept the boundary.
 *
 * This implementation is based on the one in [Metro]
(https://github.com/facebook/metro/blob/907d6af22ac6ebe58572be418e9253a90665ecbd/packages/met
ro/src/lib/polyfills/require.js#L795-L816).
 * @param {*} moduleExports A Webpack module exports object.
 * @returns {string[]} A React refresh boundary signature array.
 */
function getReactRefreshBoundarySignature(moduleExports) {
  var signature = [];
  signature.push(Refresh.getFamilyByType(moduleExports));
  if (moduleExports == null || typeof moduleExports !== 'object') {
    // Exit if we can't iterate over exports.
    return signature;
  }
  for (var key in moduleExports) {
    if (key === '__esModule') {
      continue;
    }
    signature.push(key);
    signature.push(Refresh.getFamilyByType(moduleExports[key]));
  }
  return signature;
}

/**
 * Creates a data object to be retained across refreshes.
 * This object should not transtively reference previous exports,
 * which can form infinite chain of objects across refreshes, which can pressure RAM.
 *
 * @param {*} moduleExports A Webpack module exports object.
 * @returns {*} A React refresh boundary signature array.
 */
function getWebpackHotData(moduleExports) {
  return {
    signature: getReactRefreshBoundarySignature(moduleExports),

    isReactRefreshBoundary: isReactRefreshBoundary(moduleExports)
  };
}

/**
 * Creates a helper that performs a delayed React refresh.
```

```
 * @returns {function(function(): void): void} A debounced React refresh function.
 */
function createDebounceUpdate() {
  /**
   * A cached setTimeout handler.
   * @type {number | undefined}
   */
  var refreshTimeout;

  /**
   * Performs react refresh on a delay and clears the error overlay.
   * @param {function(): void} callback
   * @returns {void}
   */
  function enqueueUpdate(callback) {
    if (typeof refreshTimeout === 'undefined') {
      refreshTimeout = setTimeout(function () {
        refreshTimeout = undefined;
        Refresh.performReactRefresh();
        callback();
      }, 30);
    }
  }
  return enqueueUpdate;
}

/**
 * Checks if all exports are likely a React component.
 *
 * This implementation is based on the one in [Metro]
(https://github.com/facebook/metro/blob/febdba2383113c88296c61e28e4ef6a7f4939fda/packages/metr
o/src/lib/polyfills/require.js#L748-L774).
 * @param {*} moduleExports A Webpack module exports object.
 * @returns {boolean} Whether the exports are React component like.
 */
function isReactRefreshBoundary(moduleExports) {
  if (Refresh.isLikelyComponentType(moduleExports)) {
    return true;
  }
  if (moduleExports === undefined || moduleExports === null || typeof moduleExports !== 'object') {
    // Exit if we can't iterate over exports.
    return false;
  }
  var hasExports = false;
  var areAllExportsComponents = true;
  for (var key in moduleExports) {
    hasExports = true;

    // This is the ES Module indicator flag
```

```
    if (key === '__esModule') {
      continue;
    }

    // We can (and have to) safely execute getters here,
    // as Webpack manually assigns harmony exports to getters,
    // without any side-effects attached.
    // Ref:
https://github.com/webpack/webpack/blob/b93048643fe74de2a6931755911da1212df55897/lib/MainTe
mplate.js#L281
    var exportValue = moduleExports[key];
    if (!Refresh.isLikelyComponentType(exportValue)) {
      areAllExportsComponents = false;
    }
  }
  return hasExports && areAllExportsComponents;
}

/**
 * Checks if exports are likely a React component and registers them.
 *
 * This implementation is based on the one in [Metro]
(https://github.com/facebook/metro/blob/febdba2383113c88296c61e28e4ef6a7f4939fda/packages/metr
o/src/lib/polyfills/require.js#L818-L835).
 * @param {*} moduleExports A Webpack module exports object.
 * @param {string} moduleId A Webpack module ID.
 * @returns {void}
 */
function registerExportsForReactRefresh(moduleExports, moduleId) {
  if (Refresh.isLikelyComponentType(moduleExports)) {
    // Register module.exports if it is likely a component
    Refresh.register(moduleExports, moduleId + ' %exports%');
  }
  if (moduleExports === undefined || moduleExports === null || typeof moduleExports !== 'object') {
    // Exit if we can't iterate over the exports.
    return;
  }
  for (var key in moduleExports) {
    // Skip registering the ES Module indicator
    if (key === '__esModule') {
      continue;
    }
    var exportValue = moduleExports[key];
    if (Refresh.isLikelyComponentType(exportValue)) {
      var typeID = moduleId + ' %exports% ' + key;
      Refresh.register(exportValue, typeID);
    }
  }
}
```

```
/**
 * Compares previous and next module objects to check for mutated boundaries.
 *
 * This implementation is based on the one in [Metro]
(https://github.com/facebook/metro/blob/907d6af22ac6ebe58572be418e9253a90665ecbd/packages/met
ro/src/lib/polyfills/require.js#L776-L792).
 * @param {*} prevSignature The signature of the current Webpack module exports object.
 * @param {*} nextSignature The signature of the next Webpack module exports object.
 * @returns {boolean} Whether the React refresh boundary should be invalidated.
 */
function shouldInvalidateReactRefreshBoundary(prevSignature, nextSignature) {
  if (prevSignature.length !== nextSignature.length) {
    return true;
  }
  for (var i = 0; i < nextSignature.length; i += 1) {
    if (prevSignature[i] !== nextSignature[i]) {
      return true;
    }
  }
  return false;
}
var enqueueUpdate = createDebounceUpdate();
function executeRuntime(moduleExports, moduleId, webpackHot, refreshOverlay, isTest) {
  registerExportsForReactRefresh(moduleExports, moduleId);
  if (webpackHot) {
    var isHotUpdate = !!webpackHot.data;
    var prevData;
    if (isHotUpdate) {
      prevData = webpackHot.data.prevData;
    }
    if (isReactRefreshBoundary(moduleExports)) {
      webpackHot.dispose(
      /**
       * A callback to performs a full refresh if React has unrecoverable errors,
       * and also caches the to-be-disposed module.
       * @param {*} data A hot module data object from Webpack HMR.
       * @returns {void}
       */
      function hotDisposeCallback(data) {
        // We have to mutate the data object to get data registered and cached
        data.prevData = getWebpackHotData(moduleExports);
      });
      webpackHot.accept(
      /**
       * An error handler to allow self-recovering behaviours.
       * @param {Error} error An error occurred during evaluation of a module.
       * @returns {void}
       */
```

```
      function hotErrorHandler(error) {
        if (typeof refreshOverlay !== 'undefined' && refreshOverlay) {
          refreshOverlay.handleRuntimeError(error);
        }
        if (typeof isTest !== 'undefined' && isTest) {
          if (window.onHotAcceptError) {
            window.onHotAcceptError(error.message);
          }
        }
        __webpack_require__.c[moduleId].hot.accept(hotErrorHandler);
      });
      if (isHotUpdate) {
        if (prevData && prevData.isReactRefreshBoundary &&
shouldInvalidateReactRefreshBoundary(prevData.signature,
getReactRefreshBoundarySignature(moduleExports))) {
          webpackHot.invalidate();
        } else {
          enqueueUpdate(
          /**
           * A function to dismiss the error overlay after performing React refresh.
           * @returns {void}
           */
          function updateCallback() {
            if (typeof refreshOverlay !== 'undefined' && refreshOverlay) {
              refreshOverlay.clearRuntimeErrors();
            }
          });
        }
      }
    } else {
      if (isHotUpdate && typeof prevData !== 'undefined') {
        webpackHot.invalidate();
      }
    }
  }
}
module.exports = Object.freeze({
  enqueueUpdate: enqueueUpdate,
  executeRuntime: executeRuntime,
  getModuleExports: getModuleExports,
  isReactRefreshBoundary: isReactRefreshBoundary,
  registerExportsForReactRefresh: registerExportsForReactRefresh
});

/***/ },

/***/ "./node_modules/ansi-html-community/index.js"
/*!***************************************************!*\
  !*** ./node_modules/ansi-html-community/index.js ***!
```

```
  \*************************************************/
(module) {

"use strict";


module.exports = ansiHTML;

// Reference to https://github.com/sindresorhus/ansi-regex
var _regANSI = /(?:(?:\u001b\[)|\u009b)(?:(?:[0-9]{1,3})?(?:(?:;[0-9]{0,3})*)?[A-M|f-m])|\u001b[A-M]/;
var _defColors = {
  reset: ['fff', '000'],
  // [FOREGROUD_COLOR, BACKGROUND_COLOR]
  black: '000',
  red: 'ff0000',
  green: '209805',
  yellow: 'e8bf03',
  blue: '0000ff',
  magenta: 'ff00ff',
  cyan: '00ffee',
  lightgrey: 'f0f0f0',
  darkgrey: '888'
};
var _styles = {
  30: 'black',
  31: 'red',
  32: 'green',
  33: 'yellow',
  34: 'blue',
  35: 'magenta',
  36: 'cyan',
  37: 'lightgrey'
};
var _openTags = {
  '1': 'font-weight:bold',
  // bold
  '2': 'opacity:0.5',
  // dim
  '3': '<i>',
  // italic
  '4': '<u>',
  // underscore
  '8': 'display:none',
  // hidden
  '9': '<del>' // delete
};
var _closeTags = {
  '23': '</i>',
```

```
  // reset italic
  '24': '</u>',
  // reset underscore
  '29': '</del>' // reset delete
};
[0, 21, 22, 27, 28, 39, 49].forEach(function (n) {
  _closeTags[n] = '</span>';
});

/**
 * Converts text with ANSI color codes to HTML markup.
 * @param {String} text
 * @returns {*}
 */
function ansiHTML(text) {
  // Returns the text if the string has no ANSI escape code.
  if (!_regANSI.test(text)) {
    return text;
  }

  // Cache opened sequence.
  var ansiCodes = [];
  // Replace with markup.
  var ret = text.replace(/\033\[(\d+)m/g, function (match, seq) {
    var ot = _openTags[seq];
    if (ot) {
      // If current sequence has been opened, close it.
      if (!!~ansiCodes.indexOf(seq)) {
        // eslint-disable-line no-extra-boolean-cast
        ansiCodes.pop();
        return '</span>';
      }
      // Open tag.
      ansiCodes.push(seq);
      return ot[0] === '<' ? ot : '<span style="' + ot + ';">';
    }
    var ct = _closeTags[seq];
    if (ct) {
      // Pop sequence
      ansiCodes.pop();
      return ct;
    }
    return '';
  });

  // Make sure tags are closed.
  var l = ansiCodes.length;
  l > 0 && (ret += Array(l + 1).join('</span>'));
  return ret;
```

```
}

/**
 * Customize colors.
 * @param {Object} colors reference to _defColors
 */
ansiHTML.setColors = function (colors) {
  if (typeof colors !== 'object') {
    throw new Error('`colors` parameter must be an Object.');
  }
  var _finalColors = {};
  for (var key in _defColors) {
    var hex = colors.hasOwnProperty(key) ? colors[key] : null;
    if (!hex) {
      _finalColors[key] = _defColors[key];
      continue;
    }
    if ('reset' === key) {
      if (typeof hex === 'string') {
        hex = [hex];
      }
      if (!Array.isArray(hex) || hex.length === 0 || hex.some(function (h) {
        return typeof h !== 'string';
      })) {
        throw new Error('The value of `' + key + '` property must be an Array and each item could only be
a hex string, e.g.: FF0000');
      }
      var defHexColor = _defColors[key];
      if (!hex[0]) {
        hex[0] = defHexColor[0];
      }
      if (hex.length === 1 || !hex[1]) {
        hex = [hex[0]];
        hex.push(defHexColor[1]);

      }
      hex = hex.slice(0, 2);
    } else if (typeof hex !== 'string') {
      throw new Error('The value of `' + key + '` property must be a hex string, e.g.: FF0000');
    }
    _finalColors[key] = hex;
  }
  _setTags(_finalColors);
};

/**
 * Reset colors.
 */
ansiHTML.reset = function () {
```

```
  _setTags(_defColors);
};

/**
 * Expose tags, including open and close.
 * @type {Object}
 */
ansiHTML.tags = {};
if (Object.defineProperty) {
  Object.defineProperty(ansiHTML.tags, 'open', {
    get: function () {
      return _openTags;
    }
  });
  Object.defineProperty(ansiHTML.tags, 'close', {
    get: function () {
      return _closeTags;
    }
  });
} else {
  ansiHTML.tags.open = _openTags;
  ansiHTML.tags.close = _closeTags;
}
function _setTags(colors) {
  // reset all
  _openTags['0'] = 'font-weight:normal;opacity:1;color:#' + colors.reset[0] + ';background:#' +
colors.reset[1];
  // inverse
  _openTags['7'] = 'color:#' + colors.reset[1] + ';background:#' + colors.reset[0];
  // dark grey
  _openTags['90'] = 'color:#' + colors.darkgrey;
  for (var code in _styles) {
    var color = _styles[code];
    var oriColor = colors[color] || '000';
    _openTags[code] = 'color:#' + oriColor;
    code = parseInt(code);
    _openTags[(code + 10).toString()] = 'background:#' + oriColor;
  }
}
ansiHTML.reset();

/***/ },

/***/ "./node_modules/css-loader/dist/runtime/api.js"
/*!*****************************************************!*\
  !*** ./node_modules/css-loader/dist/runtime/api.js ***!
  \*****************************************************/
(module) {
```

```
"use strict";


/*
  MIT License http://www.opensource.org/licenses/mit-license.php
  Author Tobias Koppers @sokra
*/
module.exports = function (cssWithMappingToString) {
  var list = [];

  // return the list of modules as css string
  list.toString = function toString() {
    return this.map(function (item) {
      var content = "";
      var needLayer = typeof item[5] !== "undefined";
      if (item[4]) {
        content += "@supports (".concat(item[4], ") {");
      }
      if (item[2]) {
        content += "@media ".concat(item[2], " {");
      }
      if (needLayer) {
        content += "@layer".concat(item[5].length > 0 ? " ".concat(item[5]) : "", " {");
      }
      content += cssWithMappingToString(item);
      if (needLayer) {
        content += "}";
      }
      if (item[2]) {
        content += "}";
      }
      if (item[4]) {
        content += "}";
      }
      return content;
    }).join("");
  };

  // import a list of modules into the list
  list.i = function i(modules, media, dedupe, supports, layer) {
    if (typeof modules === "string") {
      modules = [[null, modules, undefined]];
    }
    var alreadyImportedModules = {};
    if (dedupe) {
      for (var k = 0; k < this.length; k++) {
        var id = this[k][0];
        if (id != null) {
          alreadyImportedModules[id] = true;
```

```
      }
     }
    }
    for (var _k = 0; _k < modules.length; _k++) {
     var item = [].concat(modules[_k]);
     if (dedupe && alreadyImportedModules[item[0]]) {
      continue;
     }
     if (typeof layer !== "undefined") {
      if (typeof item[5] === "undefined") {
       item[5] = layer;
      } else {
       item[1] = "@layer".concat(item[5].length > 0 ? " ".concat(item[5]) : "", " {").concat(item[1],
"}");
       item[5] = layer;
      }
     }
     if (media) {
      if (!item[2]) {
       item[2] = media;
      } else {
       item[1] = "@media ".concat(item[2], " {").concat(item[1], "}");
       item[2] = media;
      }
     }
     if (supports) {
      if (!item[4]) {
       item[4] = "".concat(supports);
      } else {
       item[1] = "@supports (".concat(item[4], ") {").concat(item[1], "}");
       item[4] = supports;
      }
     }
     list.push(item);
    }
   };
   return list;
};

/***/ },

/***/ "./node_modules/css-loader/dist/runtime/sourceMaps.js"
/*!***********************************************************!*\
  !*** ./node_modules/css-loader/dist/runtime/sourceMaps.js ***!
  \***********************************************************/
(module) {

"use strict";
```

```
module.exports = function (item) {
  var content = item[1];
  var cssMapping = item[3];
  if (!cssMapping) {
    return content;
  }
  if (typeof btoa === "function") {
    var base64 = btoa(unescape(encodeURIComponent(JSON.stringify(cssMapping))));
    var data = "sourceMappingURL=data:application/json;charset=utf-8;base64,".concat(base64);
    var sourceMapping = "/*# ".concat(data, " */");
    return [content].concat([sourceMapping]).join("\n");
  }
  return [content].join("\n");
};

/***/ },

/***/ "./node_modules/events/events.js"
/*!*****************************************!*\
  !*** ./node_modules/events/events.js ***!
  \*****************************************/
(module) {

"use strict";
// Copyright Joyent, Inc. and other Node contributors.
//
// Permission is hereby granted, free of charge, to any person obtaining a
// copy of this software and associated documentation files (the
// "Software"), to deal in the Software without restriction, including
// without limitation the rights to use, copy, modify, merge, publish,
// distribute, sublicense, and/or sell copies of the Software, and to permit
// persons to whom the Software is furnished to do so, subject to the
// following conditions:
//
// The above copyright notice and this permission notice shall be included
// in all copies or substantial portions of the Software.
//
// THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
// OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
// MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN
// NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM,
// DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
// OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE
// USE OR OTHER DEALINGS IN THE SOFTWARE.
```

```
var R = typeof Reflect === 'object' ? Reflect : null;
var ReflectApply = R && typeof R.apply === 'function' ? R.apply : function ReflectApply(target,
receiver, args) {
  return Function.prototype.apply.call(target, receiver, args);
};
var ReflectOwnKeys;
if (R && typeof R.ownKeys === 'function') {
  ReflectOwnKeys = R.ownKeys;
} else if (Object.getOwnPropertySymbols) {
  ReflectOwnKeys = function ReflectOwnKeys(target) {
    return Object.getOwnPropertyNames(target).concat(Object.getOwnPropertySymbols(target));
  };
} else {
  ReflectOwnKeys = function ReflectOwnKeys(target) {
    return Object.getOwnPropertyNames(target);
  };
}
function ProcessEmitWarning(warning) {
  if (console && console.warn) console.warn(warning);
}
var NumberIsNaN = Number.isNaN || function NumberIsNaN(value) {
  return value !== value;
};
function EventEmitter() {
  EventEmitter.init.call(this);
}
module.exports = EventEmitter;
module.exports.once = once;

// Backwards-compat with node 0.10.x
EventEmitter.EventEmitter = EventEmitter;
EventEmitter.prototype._events = undefined;
EventEmitter.prototype._eventsCount = 0;
EventEmitter.prototype._maxListeners = undefined;

// By default EventEmitters will print a warning if more than 10 listeners are
// added to it. This is a useful default which helps finding memory leaks.
var defaultMaxListeners = 10;
function checkListener(listener) {
  if (typeof listener !== 'function') {
    throw new TypeError('The "listener" argument must be of type Function. Received type ' + typeof
listener);
  }
}
Object.defineProperty(EventEmitter, 'defaultMaxListeners', {
  enumerable: true,
  get: function () {
```

```
    return defaultMaxListeners;
  },
  set: function (arg) {
    if (typeof arg !== 'number' || arg < 0 || NumberIsNaN(arg)) {
      throw new RangeError('The value of "defaultMaxListeners" is out of range. It must be a non-
negative number. Received ' + arg + '.');
    }
    defaultMaxListeners = arg;
  }
});
EventEmitter.init = function () {
  if (this._events === undefined || this._events === Object.getPrototypeOf(this)._events) {
    this._events = Object.create(null);
    this._eventsCount = 0;
  }
  this._maxListeners = this._maxListeners || undefined;
};

// Obviously not all Emitters should be limited to 10. This function allows
// that to be increased. Set to zero for unlimited.
EventEmitter.prototype.setMaxListeners = function setMaxListeners(n) {
  if (typeof n !== 'number' || n < 0 || NumberIsNaN(n)) {
    throw new RangeError('The value of "n" is out of range. It must be a non-negative number. Received
' + n + '.');
  }
  this._maxListeners = n;
  return this;
};
function _getMaxListeners(that) {
  if (that._maxListeners === undefined) return EventEmitter.defaultMaxListeners;
  return that._maxListeners;
}
EventEmitter.prototype.getMaxListeners = function getMaxListeners() {
  return _getMaxListeners(this);
};
EventEmitter.prototype.emit = function emit(type) {
  var args = [];
  for (var i = 1; i < arguments.length; i++) args.push(arguments[i]);
  var doError = type === 'error';
  var events = this._events;
  if (events !== undefined) doError = doError && events.error === undefined;else if (!doError) return
false;

  // If there is no 'error' event listener then throw.
  if (doError) {
    var er;
    if (args.length > 0) er = args[0];
    if (er instanceof Error) {
      // Note: The comments on the `throw` lines are intentional, they show
```

```
      // up in Node's output if this results in an unhandled exception.
      throw er; // Unhandled 'error' event
    }
    // At least give some kind of context to the user
    var err = new Error('Unhandled error.' + (er ? ' (' + er.message + ')' : ''));
    err.context = er;
    throw err; // Unhandled 'error' event
  }
  var handler = events[type];
  if (handler === undefined) return false;
  if (typeof handler === 'function') {
    ReflectApply(handler,
 this, args);
  } else {
    var len = handler.length;
    var listeners = arrayClone(handler, len);
    for (var i = 0; i < len; ++i) ReflectApply(listeners[i], this, args);
  }
  return true;
};
function _addListener(target, type, listener, prepend) {
  var m;
  var events;
  var existing;
  checkListener(listener);
  events = target._events;
  if (events === undefined) {
    events = target._events = Object.create(null);
    target._eventsCount = 0;
  } else {
    // To avoid recursion in the case that type === "newListener"! Before
    // adding it to the listeners, first emit "newListener".
    if (events.newListener !== undefined) {
      target.emit('newListener', type, listener.listener ? listener.listener : listener);

      // Re-assign `events` because a newListener handler could have caused the
      // this._events to be assigned to a new object
      events = target._events;
    }
    existing = events[type];
  }
  if (existing === undefined) {
    // Optimize the case of one listener. Don't need the extra array object.
    existing = events[type] = listener;
    ++target._eventsCount;
  } else {
    if (typeof existing === 'function') {
      // Adding the second element, need to change to array.
      existing = events[type] = prepend ? [listener, existing] : [existing, listener];
```

```
      // If we've already got an array, just append.
    } else if (prepend) {
      existing.unshift(listener);
    } else {
      existing.push(listener);
    }

    // Check for listener leak
    m = _getMaxListeners(target);
    if (m > 0 && existing.length > m && !existing.warned) {
      existing.warned = true;
      // No error code for this since it is a Warning
      // eslint-disable-next-line no-restricted-syntax
      var w = new Error('Possible EventEmitter memory leak detected. ' + existing.length + ' ' +
String(type) + ' listeners ' + 'added. Use emitter.setMaxListeners() to ' + 'increase limit');
      w.name = 'MaxListenersExceededWarning';
      w.emitter = target;
      w.type = type;
      w.count = existing.length;
      ProcessEmitWarning(w);
    }
  }
  return target;
}
EventEmitter.prototype.addListener = function addListener(type, listener) {
  return _addListener(this, type, listener, false);
};
EventEmitter.prototype.on = EventEmitter.prototype.addListener;
EventEmitter.prototype.prependListener = function prependListener(type, listener) {
  return _addListener(this, type, listener, true);
};
function onceWrapper() {
  if (!this.fired) {
    this.target.removeListener(this.type, this.wrapFn);
    this.fired = true;
    if (arguments.length === 0) return this.listener.call(this.target);
    return this.listener.apply(this.target, arguments);
  }
}
function _onceWrap(target, type, listener) {
  var state = {
    fired: false,
    wrapFn: undefined,
    target: target,
    type: type,
    listener: listener
  };
  var wrapped = onceWrapper.bind(state);
  wrapped.listener = listener;
```

```
  state.wrapFn = wrapped;
  return wrapped;
}
EventEmitter.prototype.once = function once(type, listener) {
  checkListener(listener);
  this.on(type, _onceWrap(this, type, listener));
  return this;
};
EventEmitter.prototype.prependOnceListener = function prependOnceListener(type, listener) {
  checkListener(listener);
  this.prependListener(type, _onceWrap(this, type, listener));
  return this;
};

// Emits a 'removeListener' event if and only if the listener was removed.
EventEmitter.prototype.removeListener = function removeListener(type, listener) {
  var list, events, position, i, originalListener;
  checkListener(listener);
  events = this._events;
  if (events === undefined) return this;
  list = events[type];
  if (list === undefined) return this;
  if (list === listener || list.listener === listener) {
    if (--this._eventsCount === 0) this._events = Object.create(null);else {
      delete events[type];
      if (events.removeListener) this.emit('removeListener', type, list.listener || listener);
    }
  } else if (typeof list !== 'function') {
    position = -1;
    for (i = list.length - 1; i >= 0; i--) {
      if (list[i] === listener || list[i].listener === listener) {
        originalListener = list[i].listener;
        position = i;
        break;
      }
    }
    if (position < 0) return this;
    if (position === 0) list.shift();else {
      spliceOne(list, position);
    }
    if (list.length === 1) events[type] = list[0];
    if (events.removeListener !== undefined) this.emit('removeListener', type, originalListener ||
listener);
  }
  return this;
};
EventEmitter.prototype.off = EventEmitter.prototype.removeListener;
EventEmitter.prototype.removeAllListeners = function removeAllListeners(type) {
  var listeners, events, i;
```

```
  events = this._events;
  if (events === undefined) return this;

  // not listening for removeListener, no need to emit
  if (events.removeListener === undefined) {
    if (arguments.length === 0) {
      this._events = Object.create(null);
      this._eventsCount = 0;
    } else if (events[type] !== undefined) {
      if (--this._eventsCount === 0) this._events = Object.create(null);else delete events[type];
    }
    return this;
  }

  // emit removeListener for all listeners on all events
  if (arguments.length === 0) {
    var keys = Object.keys(events);
    var key;
    for (i = 0; i < keys.length; ++i) {
      key = keys[i];
      if (key === 'removeListener') continue;
      this.removeAllListeners(key);
    }
    this.removeAllListeners('removeListener');
    this._events = Object.create(null);
    this._eventsCount = 0;
    return this;
  }
  listeners = events[type];
  if (typeof listeners === 'function') {
    this.removeListener(type, listeners);
  } else if (listeners !== undefined) {
    // LIFO order
    for (i = listeners.length - 1; i >= 0; i--) {
      this.removeListener(type, listeners[i]);
    }
  }
  return this;
};
function _listeners(target, type, unwrap) {
  var events = target._events;
  if (events === undefined) return [];
  var evlistener = events[type];
  if (evlistener === undefined) return [];
  if (typeof evlistener === 'function') return unwrap ? [evlistener.listener || evlistener] : [evlistener];
  return unwrap ? unwrapListeners(evlistener) : arrayClone(evlistener, evlistener.length);
}
EventEmitter.prototype.listeners = function listeners(type) {
  return _listeners(this, type, true);
```

```
};
EventEmitter.prototype.rawListeners = function rawListeners(type) {
  return _listeners(this, type, false);
};
EventEmitter.listenerCount = function (emitter, type) {
  if (typeof emitter.listenerCount === 'function') {
    return emitter.listenerCount(type);
  } else {
    return listenerCount.call(emitter, type);
  }
};
EventEmitter.prototype.listenerCount = listenerCount;
function listenerCount(type) {
  var events = this._events;
  if (events !== undefined) {
    var evlistener = events[type];
    if (typeof evlistener === 'function') {
      return 1;
    } else if (evlistener !== undefined) {
      return evlistener.length;
    }
  }
  return 0;
}
EventEmitter.prototype.eventNames = function eventNames() {
  return this._eventsCount > 0 ? ReflectOwnKeys(this._events) : [];
};
function arrayClone(arr, n) {
  var copy = new Array(n);
  for (var i = 0; i < n; ++i) copy[i] = arr[i];
  return copy;
}
function spliceOne(list, index) {
  for (; index + 1 < list.length; index++) list[index] = list[index + 1];
  list.pop();
}
function unwrapListeners(arr) {
  var ret = new Array(arr.length);
  for (var i = 0; i < ret.length; ++i) {
    ret[i] = arr[i].listener || arr[i];
  }
  return ret;
}
function once(emitter, name) {
  return new Promise(function (resolve, reject) {
    function errorListener(err) {
      emitter.removeListener(name, resolver);
      reject(err);
    }
```

```
    function resolver() {
      if (typeof emitter.removeListener === 'function') {
        emitter.removeListener('error', errorListener);
      }
      resolve([].slice.call(arguments));
    }
    ;
    eventTargetAgnosticAddListener(emitter, name, resolver, {
      once: true
    });
    if (name !== 'error') {
      addErrorHandlerIfEventEmitter(emitter, errorListener, {
        once: true
      });
    }
  });
}
function addErrorHandlerIfEventEmitter(emitter, handler, flags) {
  if (typeof emitter.on === 'function') {
    eventTargetAgnosticAddListener(emitter, 'error', handler, flags);
  }
}
function eventTargetAgnosticAddListener(emitter, name, listener, flags) {
  if (typeof emitter.on === 'function') {
    if (flags.once) {
      emitter.once(name, listener);
    } else {
      emitter.on(name, listener);
    }
  } else if (typeof emitter.addEventListener === 'function') {
    // EventTarget does not have `error` event semantics like Node
    // EventEmitters, we do not listen for `error` events here.
    emitter.addEventListener(name, function wrapListener(arg) {
      // IE does not have builtin `{ once: true }` support so we
      // have to do it manually.
      if (flags.once) {
        emitter.removeEventListener(name, wrapListener);
      }
      listener(arg);
    });
  } else {
    throw new TypeError('The "emitter" argument must be of type EventEmitter. Received type ' +
typeof emitter);
  }
}

/***/ },

/***/ "./node_modules/lucide-react/dist/esm/Icon.js"
```

```
/*!*****************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/Icon.js ***!
  \*****************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ Icon)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default
 = /*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _defaultAttributes_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./defaultAttributes.js */ "./node_modules/lucide-
react/dist/esm/defaultAttributes.js");
/* harmony import */ var _shared_src_utils_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./shared/src/utils.js */ "./node_modules/lucide-
react/dist/esm/shared/src/utils.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */



const Icon = (0,react__WEBPACK_IMPORTED_MODULE_0__.forwardRef)(({
  color = "currentColor",
  size = 24,
  strokeWidth = 2,
  absoluteStrokeWidth,
  className = "",
  children,
  iconNode,
  ...rest
}, ref) => (0,react__WEBPACK_IMPORTED_MODULE_0__.createElement)("svg", {
  ref,
  ..._defaultAttributes_js__WEBPACK_IMPORTED_MODULE_1__["default"],
  width: size,
  height: size,
  stroke: color,
  strokeWidth: absoluteStrokeWidth ? Number(strokeWidth) * 24 / Number(size) : strokeWidth,
  className: (0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_2__.mergeClasses)
("lucide", className),
  ...(!children && !(0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_2__.hasA11yProp)
```

```
(rest) && {
    "aria-hidden": "true"
  }),
  ...rest
}, [...iconNode.map(([tag, attrs]) =>
(0,react__WEBPACK_IMPORTED_MODULE_0__.createElement)(tag, attrs)), ...
(Array.isArray(children) ? children : [children])]));


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/createLucideIcon.js"
/*!*****************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/createLucideIcon.js ***!
  \*****************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ createLucideIcon)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(react__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var _shared_src_utils_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./shared/src/utils.js */ "./node_modules/lucide-
react/dist/esm/shared/src/utils.js");
/* harmony import */ var _Icon_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./Icon.js */ "./node_modules/lucide-react/dist/esm/Icon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */




const createLucideIcon = (iconName, iconNode) => {
  const Component = (0,react__WEBPACK_IMPORTED_MODULE_0__.forwardRef)(({
    className,
    ...props
  }, ref) => (0,react__WEBPACK_IMPORTED_MODULE_0__.createElement)
(_Icon_js__WEBPACK_IMPORTED_MODULE_2__["default"], {
    ref,
    iconNode,
```

```
    className: (0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_1__.mergeClasses)
(`lucide-${(0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_1__.toKebabCase)
((0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_1__.toPascalCase)(iconName))}`,
`lucide-${iconName}`, className),
    ...props
  }));
  Component.displayName =
(0,_shared_src_utils_js__WEBPACK_IMPORTED_MODULE_1__.toPascalCase)(iconName);
  return Component;
};


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/defaultAttributes.js"
/*!*****************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/defaultAttributes.js ***!
  \*****************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ defaultAttributes)
/* harmony export */ });
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */

var defaultAttributes = {
  xmlns: "http://www.w3.org/2000/svg",
  width: 24,
  height: 24,
  viewBox: "0 0 24 24",
  fill: "none",
  stroke: "currentColor",
  strokeWidth: 2,
  strokeLinecap: "round",
  strokeLinejoin: "round"
};


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/arrow-right.js"
/*!****************************************************************!*\
```

```
  !*** ./node_modules/lucide-react/dist/esm/icons/arrow-right.js ***!
  \*************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ ArrowRight)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M5 12h14",
  key: "1ays0h"
}], ["path", {
  d: "m12 5 7 7-7 7",
  key: "xquz4c"
}]];
const ArrowRight = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("arrow-right", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/cog.js"
/*!*********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/cog.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Cog)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
```

```
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M12 20a8 8 0 1 0 0-16 8 8 0 0 0 0 16Z",
  key: "sobvz5"
}], ["path", {
  d: "M12 14a2 2 0 1 0 0-4 2 2 0 0 0 0 4Z",
  key: "11i496"
}], ["path", {
  d: "M12 2v2",
  key: "tus03m"
}], ["path", {
  d: "M12 22v-2",
  key: "1osdcq"
}], ["path", {
  d: "m17 20.66-1-1.73",
  key: "eq3orb"
}], ["path", {
  d: "M11 10.27 7 3.34",
  key: "16pf9h"
}], ["path", {
  d: "m20.66 17-1.73-1",
  key: "sg0v6f"
}], ["path", {
  d: "m3.34 7 1.73 1",
  key: "1ulond"
}], ["path", {
  d: "M14 12h8",
  key: "4f43i9"
}], ["path", {
  d: "M2 12h2",
  key: "1t8f8n"
}], ["path", {
  d: "m20.66 7-1.73 1",
  key: "1ow05n"
}], ["path", {
  d: "m3.34 17 1.73-1",
  key: "nuk764"
}], ["path", {
  d: "m17 3.34-1 1.73",
  key: "2wel8s"
}], ["path", {
  d: "m11 13.73-4 6.93",
```

```
  key: "794ttg"
}]];
const Cog = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])("cog",
__iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/download.js"
/*!*************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/download.js ***!
  \*************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Download)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M12 15V3",
  key: "m9g1x1"
}], ["path", {
  d: "M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4",
  key: "ih7n3h"
}], ["path", {
  d: "m7 10 5 5 5-5",
  key: "brsn70"
}]];
const Download = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("download", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/git-compare-arrows.js"
/*!***********************************************************************!*\
```

```
  !*** ./node_modules/lucide-react/dist/esm/icons/git-compare-arrows.js ***!
  \*************************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ GitCompareArrows)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react
 v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["circle", {
  cx: "5",
  cy: "6",
  r: "3",
  key: "1qnov2"
}], ["path", {
  d: "M12 6h5a2 2 0 0 1 2 2v7",
  key: "1yj91y"
}], ["path", {
  d: "m15 9-3-3 3-3",
  key: "1lwv8l"
}], ["circle", {
  cx: "19",
  cy: "18",
  r: "3",
  key: "1qljk2"
}], ["path", {
  d: "M12 18H7a2 2 0 0 1-2-2V9",
  key: "16sdep"
}], ["path", {
  d: "m9 15 3 3-3 3",
  key: "1m3kbl"
}]];
const GitCompareArrows =
(0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])("git-compare-
arrows", __iconNode);
```

```
/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/house.js"
/*!**********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/house.js ***!
  \**********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ House)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M15 21v-8a1 1 0 0 0-1-1h-4a1 1 0 0 0-1 1v8",
  key: "5wwlr5"
}], ["path", {
  d: "M3 10a2 2 0 0 1 .709-1.528l7-5.999a2 2 0 0 1 2.582 0l7 5.999A2 2 0 0 1 21 10v9a2 2 0 0 1-2
2H5a2 2 0 0 1-2-2z",
  key: "1d0kgt"
}]];
const House = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("house", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/library.js"
/*!************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/library.js ***!
  \************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
```

```
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Library)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "m16 6 4 14",
  key: "ji33uf"
}], ["path", {
  d: "M12 6v14",
  key: "1n7gus"
}], ["path", {
  d: "M8 8v12",
  key: "1gg7y9"
}], ["path", {
  d: "M4 4v16",
  key: "6qkkli"
}]];
const Library = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("library", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/list-filter.js"
/*!*****************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/list-filter.js ***!
  \*****************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ ListFilter)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
```

```
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M3 6h18",
  key: "d0wm0j"
}], ["path", {
  d: "M7 12h10",
  key: "b7w52i"
}], ["path", {
  d: "M10 18h4",
  key: "1ulq68"
}]];
const ListFilter = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("list-filter", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/play.js"
/*!**********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/play.js ***!
  \**********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Play)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["polygon", {
  points: "6 3 20 12 6 21 6 3",
  key: "1oa8hb"
```

```
}]];
const Play = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])("play",
__iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/save.js"
/*!**********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/save.js ***!
  \**********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Save)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M15.2 3a2 2 0 0 1 1.4.6l3.8 3.8a2 2 0 0 1 .6 1.4V19a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2V5a2 2 0 0 1 2-
2z",
  key: "1c8476"
}], ["path", {
  d: "M17 21v-7a1 1 0 0 0-1-1H8a1 1 0 0 0-1 1v7",
  key: "1ydtos"
}], ["path", {
  d: "M7 3v4a1 1 0 0 0 1 1h7",
  key: "t51u73"
}]];
const Save = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])("save",
__iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/search.js"
/*!************************************************************!*\
```

```
  !*** ./node_modules/lucide-react/dist/esm/icons/search.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Search)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "m21 21-4.34-4.34",
  key: "14j7rj"
}], ["circle", {
  cx: "11",
  cy: "11",
  r: "8",
  key: "4ej97u"
}]];
const Search = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("search", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/square.js"
/*!***********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/square.js ***!
  \***********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Square)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
```

```
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["rect", {
  width: "18",
  height: "18",
  x: "3",
  y: "3",
  rx: "2",
  key: "afitv7"
}]];
const Square = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("square", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/trash-2.js"
/*!*************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/trash-2.js ***!
  \*************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use
 strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Trash2)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
```

```
  d: "M3 6h18",
  key: "d0wm0j"
}], ["path", {
  d: "M19 6v14c0 1-1 2-2 2H7c-1 0-2-1-2-2V6",
  key: "4alrt4"
}], ["path", {
  d: "M8 6V4c0-1 1-2 2-2h4c1 0 2 1 2 2v2",
  key: "v07s0e"
}], ["line", {
  x1: "10",
  x2: "10",
  y1: "11",
  y2: "17",
  key: "1uufr5"
}], ["line", {
  x1: "14",
  x2: "14",
  y1: "11",
  y2: "17",
  key: "xtxkd"
}]];
const Trash2 = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("trash-2", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/upload.js"
/*!*********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/upload.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Upload)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */
```

```
const __iconNode = [["path", {
  d: "M12 3v12",
  key: "1x0j5s"
}], ["path", {
  d: "m17 8-5-5-5 5",
  key: "7q97r8"
}], ["path", {
  d: "M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4",
  key: "ih7n3h"
}]];
const Upload = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("upload", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/waves.js"
/*!*********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/waves.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Waves)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M2 6c.6.5 1.2 1 2.5 1C7 7 7 5 9.5 5c2.6 0 2.4 2 5 2 2.5 0 2.5-2 5-2 1.3 0 1.9.5 2.5 1",
  key: "knzxuh"
}], ["path", {
  d: "M2 12c.6.5 1.2 1 2.5 1 2.5 0 2.5-2 5-2 2.6 0 2.4 2 5 2 2.5 0 2.5-2 5-2 1.3 0 1.9.5 2.5 1",
  key: "2jd2cc"
}], ["path", {
  d: "M2 18c.6.5 1.2 1 2.5 1 2.5 0 2.5-2 5-2 2.6 0 2.4 2 5 2 2.5 0 2.5-2 5-2 1.3 0 1.9.5 2.5 1",
  key: "rd2r6e"
```

```
}]];
const Waves = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])
("waves", __iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/icons/zap.js"
/*!*********************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/icons/zap.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   __iconNode: () => (/* binding */ __iconNode),
/* harmony export */   "default": () => (/* binding */ Zap)
/* harmony export */ });
/* harmony import */ var _createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../createLucideIcon.js */ "./node_modules/lucide-
react/dist/esm/createLucideIcon.js");
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */


const __iconNode = [["path", {
  d: "M4 14a1 1 0 0 1-.78-1.63l9.9-10.2a.5.5 0 0 1 .86.46l-1.92 6.02A1 1 0 0 0 13 10h7a1 1 0 0 1 .78
1.63l-9.9 10.2a.5.5 0 0 1-.86-.46l1.92-6.02A1 1 0 0 0 11 14z",
  key: "1xq2db"
}]];
const Zap = (0,_createLucideIcon_js__WEBPACK_IMPORTED_MODULE_0__["default"])("zap",
__iconNode);


/***/ },

/***/ "./node_modules/lucide-react/dist/esm/shared/src/utils.js"
/*!***************************************************************!*\
  !*** ./node_modules/lucide-react/dist/esm/shared/src/utils.js ***!
  \***************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
```

```
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   hasA11yProp: () => (/* binding */ hasA11yProp),
/* harmony export */   mergeClasses: () => (/* binding */ mergeClasses),
/* harmony export */   toCamelCase: () => (/* binding */ toCamelCase),
/* harmony export */   toKebabCase: () => (/* binding */ toKebabCase),
/* harmony export */   toPascalCase: () => (/* binding */ toPascalCase)
/* harmony export */ });
/**
 * @license lucide-react v0.516.0 - ISC
 *
 * This source code is licensed under the ISC license.
 * See the LICENSE file in the root directory of this source tree.
 */

const toKebabCase = string => string.replace(/([a-z0-9])([A-Z])/g, "$1-$2").toLowerCase();
const toCamelCase = string => string.replace(/^([A-Z])|[\s-_]+(\w)/g, (match, p1, p2) => p2 ?
p2.toUpperCase() : p1.toLowerCase());
const toPascalCase = string => {
  const camelCase = toCamelCase(string);
  return camelCase.charAt(0).toUpperCase() + camelCase.slice(1);
};
const mergeClasses = (...classes) => classes.filter((className, index, array) => {
  return Boolean(className) && className.trim() !== "" && array.indexOf(className) === index;
}).join(" ").trim();
const hasA11yProp = props => {
  for (const prop in props) {
    if (prop.startsWith("aria-") || prop === "role" || prop === "title") {
      return true;
    }
  }
};


/***/ },

/***/ "./node_modules/react-dom/cjs/react-dom-client.development.js"
/*!*****************************************************************!*\
  !*** ./node_modules/react-dom/cjs/react-dom-client.development.js ***!
  \*****************************************************************/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";
/**
 * @license React
 * react-dom-client.development.js
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
```

```
 * LICENSE file in the root directory of this source tree.
 */

/*
 Modernizr 3.0.0pre (Custom Build) | MIT
*/


 true && function () {
  function findHook(fiber, id) {
    for (fiber = fiber.memoizedState; null !== fiber && 0 < id;) fiber = fiber.next, id--;
    return fiber;
  }
  function copyWithSetImpl(obj, path, index, value) {
    if (index >= path.length) return value;
    var key = path[index],
      updated = isArrayImpl(obj) ? obj.slice() : assign({}, obj);
    updated[key] = copyWithSetImpl(obj[key], path, index + 1, value);
    return updated;
  }
  function copyWithRename(obj, oldPath, newPath) {
    if (oldPath.length !== newPath.length) console.warn("copyWithRename() expects paths of the same
length");else {
      for (var i = 0; i < newPath.length - 1; i++) if (oldPath[i] !== newPath[i]) {
        console.warn("copyWithRename() expects paths to be the same except for the deepest key");
        return;
      }
      return copyWithRenameImpl(obj, oldPath, newPath, 0);
    }
  }
  function copyWithRenameImpl(obj, oldPath, newPath, index) {
    var oldKey = oldPath[index],
      updated = isArrayImpl(obj) ? obj.slice() : assign({}, obj);
    index + 1 === oldPath.length ? (updated[newPath[index]] = updated[oldKey],
isArrayImpl(updated) ? updated.splice(oldKey, 1) : delete updated[oldKey]) : updated[oldKey] =
copyWithRenameImpl(obj[oldKey], oldPath, newPath, index + 1);
    return updated;
  }
  function copyWithDeleteImpl(obj, path, index) {
    var key = path[index],
      updated = isArrayImpl(obj) ? obj.slice() : assign({}, obj);
    if (index + 1 === path.length) return isArrayImpl(updated) ? updated.splice(key, 1) : delete
updated[key], updated;
    updated[key] = copyWithDeleteImpl(obj[key], path, index + 1);
    return updated;
  }
  function shouldSuspendImpl() {
    return !1;
  }
```

```
  function shouldErrorImpl() {
    return null;
  }
  function createFiber(tag, pendingProps, key, mode) {
    return new FiberNode(tag, pendingProps, key, mode);
  }
  function warnInvalidHookAccess() {
    console.error("Do not call Hooks inside useEffect(...), useMemo(...), or other built-in Hooks. You
can only call Hooks at the top level of your React function. For more information, see
https://react.dev/link/rules-of-hooks");
  }
  function warnInvalidContextAccess() {
    console.error("Context can only be read while React is rendering. In classes,
 you can read it in the render method or getDerivedStateFromProps. In function components, you can
read it directly in the function body, but not inside Hooks like useReducer() or useMemo().");
  }
  function noop$2() {}
  function warnForMissingKey() {}
  function setToSortedString(set) {
    var array = [];
    set.forEach(function (value) {
      array.push(value);
    });
    return array.sort().join(", ");
  }
  function scheduleRoot(root, element) {
    root.context === emptyContextObject && (updateContainerSync(element, root, null, null),
flushSyncWork$1());
  }
  function scheduleRefresh(root, update) {
    if (null !== resolveFamily) {
      var staleFamilies = update.staleFamilies;
      update = update.updatedFamilies;
      flushPassiveEffects();
      scheduleFibersWithFamiliesRecursively(root.current, update, staleFamilies);
      flushSyncWork$1();
    }
  }
  function setRefreshHandler(handler) {
    resolveFamily = handler;
  }
  function isValidContainer(node) {
    return !(!node || 1 !== node.nodeType && 9 !== node.nodeType && 11 !== node.nodeType);
  }
  function getIteratorFn(maybeIterable) {
    if (null === maybeIterable || "object" !== typeof maybeIterable) return null;
    maybeIterable = MAYBE_ITERATOR_SYMBOL &&
maybeIterable[MAYBE_ITERATOR_SYMBOL] || maybeIterable["@@iterator"];
    return "function" === typeof maybeIterable ? maybeIterable : null;
```

```
  }
  function getComponentNameFromType(type) {
    if (null == type) return null;
    if ("function" === typeof type) return type.$$typeof === REACT_CLIENT_REFERENCE ? null :
type.displayName || type.name || null;
    if ("string" === typeof type) return type;
    switch (type) {
      case REACT_FRAGMENT_TYPE:
        return "Fragment";
      case REACT_PORTAL_TYPE:
        return "Portal";
      case REACT_PROFILER_TYPE:
        return "Profiler";
      case REACT_STRICT_MODE_TYPE:
        return "StrictMode";
      case REACT_SUSPENSE_TYPE:
        return "Suspense";
      case REACT_SUSPENSE_LIST_TYPE:
        return "SuspenseList";
    }
    if ("object" === typeof type) switch ("number" === typeof type.tag && console.error("Received an
unexpected object in getComponentNameFromType(). This is likely a bug in React. Please file an
issue."), type.$$typeof) {
      case REACT_CONTEXT_TYPE:
        return (type.displayName || "Context") + ".Provider";
      case REACT_CONSUMER_TYPE:
        return (type._context.displayName || "Context") + ".Consumer";
      case REACT_FORWARD_REF_TYPE:
        var innerType = type.render;
        type = type.displayName;
        type || (type = innerType.displayName || innerType.name || "", type = "" !== type ? "ForwardRef("
+ type + ")" : "ForwardRef");
        return type;
      case REACT_MEMO_TYPE:
        return innerType = type.displayName || null, null !== innerType ? innerType :
getComponentNameFromType(type.type) || "Memo";
      case REACT_LAZY_TYPE:
        innerType = type._payload;
        type = type._init;
        try {
          return getComponentNameFromType(type(innerType));
        } catch (x) {}
    }
    return null;
  }
  function getComponentNameFromOwner(owner) {
    return "number" === typeof owner.tag ? getComponentNameFromFiber(owner) : "string" ===
typeof owner.name ? owner.name : null;
  }
```

```
  function getComponentNameFromFiber(fiber) {
    var type = fiber.type;
    switch (fiber.tag) {
      case 24:
        return "Cache";
      case 9:
        return (type._context.displayName || "Context") + ".Consumer";
      case 10:
        return (type.displayName || "Context") + ".Provider";
      case 18:
        return "DehydratedFragment";
      case 11:
        return fiber = type.render, fiber = fiber.displayName || fiber.name || "", type.displayName || ("" !==
fiber ? "ForwardRef(" + fiber + ")" : "ForwardRef");
      case 7:
        return "Fragment";
      case 26:
      case 27:
      case 5:
        return type;
      case 4:
        return "Portal";
      case 3:
        return "Root";
      case 6:
        return "Text";
      case 16:
        return getComponentNameFromType(type);
      case 8:
        return type === REACT_STRICT_MODE_TYPE ? "StrictMode" : "Mode";
      case 22:
        return "Offscreen";
      case 12:
        return "Profiler";
      case 21:
        return "Scope";
      case 13:
        return "Suspense";
      case 19:
        return "SuspenseList";
      case 25:
        return "TracingMarker";
      case 1:
      case 0:
      case 14:
      case 15:
        if ("function" === typeof type) return type.displayName || type.name || null;
        if ("string" === typeof type) return type;
        break;
```

```
      case 29:
        type = fiber._debugInfo;
        if (null != type) for (var i = type.length - 1; 0 <= i; i--) if ("string" === typeof type[i].name) return
type[i].name;
        if (null !== fiber.return) return getComponentNameFromFiber(fiber.return);
    }
    return null;
  }
  function disabledLog() {}
  function disableLogs() {
    if (0 === disabledDepth) {
      prevLog = console.log;
      prevInfo = console.info;
      prevWarn = console.warn;
      prevError = console.error;
      prevGroup = console.group;
      prevGroupCollapsed = console.groupCollapsed;
      prevGroupEnd = console.groupEnd;
      var props = {
        configurable: !0,
        enumerable: !0,
        value: disabledLog,
        writable: !0
      };
      Object.defineProperties(console, {
        info: props,
        log: props,
        warn: props,
        error: props,
        group: props,
        groupCollapsed: props,
        groupEnd: props
      });
    }
    disabledDepth++;
  }
  function reenableLogs() {
    disabledDepth--;
    if (0 === disabledDepth) {
      var props = {
        configurable: !0,
        enumerable: !0,
        writable: !0
      };
      Object.defineProperties(console, {
        log: assign({}, props, {
          value: prevLog
        }),
        info: assign({}, props, {
```

```
        value: prevInfo
      }),
      warn: assign({}, props, {
        value: prevWarn
      }),
      error: assign({}, props, {
        value: prevError
      }),
      group: assign({}, props, {
        value: prevGroup
      }),
      groupCollapsed: assign({}, props, {
        value: prevGroupCollapsed
      }),
      groupEnd: assign({}, props, {
        value: prevGroupEnd
      })
    });
  }
  0 > disabledDepth && console.error("disabledDepth fell below zero. This is a bug in React. Please file an issue.");
 }
 function describeBuiltInComponentFrame(name) {
  if (void 0 === prefix) try {
    throw Error();
  } catch (x) {
    var match = x.stack.trim().match(/\n( *(at )?)/);
    prefix = match && match[1] || "";
    suffix = -1 < x.stack.indexOf("\n    at") ? " (<anonymous>)" : -1 < x.stack.indexOf("@") ? "@unknown:0:0" : "";
  }
  return "\n" + prefix + name + suffix;
 }
 function describeNativeComponentFrame(fn, construct) {
  if (!fn || reentry) return "";
  var frame = componentFrameCache.get(fn);
  if (void 0 !== frame) return frame;
  reentry = !0;
  frame = Error.prepareStackTrace;
  Error.prepareStackTrace = void 0;
  var previousDispatcher = null;
  previousDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = null;
  disableLogs();
  try {
    var RunInRootFrame = {
      DetermineComponentFrameRoot: function () {
        try {
          if (construct) {
```

```
          var Fake = function () {
            throw Error();
          };
          Object.defineProperty(Fake.prototype, "props", {
            set: function () {
              throw Error();
            }
          });
          if ("object" === typeof Reflect && Reflect.construct) {
            try {
              Reflect.construct(Fake, []);
            } catch (x) {
              var control = x;
            }
            Reflect.construct(fn, [], Fake);
          } else {
            try {
              Fake.call();
            } catch (x$0) {
              control = x$0;
            }
            fn.call(Fake.prototype);
          }
        } else {
          try {
            throw Error();
          } catch (x$1) {
            control = x$1;
          }
          (Fake = fn()) && "function" === typeof Fake.catch && Fake.catch(function () {});
        }
      } catch (sample) {
        if (sample && control && "string" === typeof sample.stack) return [sample.stack,
control.stack];
      }
      return [null, null];
    }
  };
  RunInRootFrame.DetermineComponentFrameRoot.displayName =
"DetermineComponentFrameRoot";
  var namePropDescriptor =
Object.getOwnPropertyDescriptor(RunInRootFrame.DetermineComponentFrameRoot, "name");
  namePropDescriptor && namePropDescriptor.configurable &&
Object.defineProperty(RunInRootFrame.DetermineComponentFrameRoot, "name", {
    value: "DetermineComponentFrameRoot"
  });
  var _RunInRootFrame$Deter = RunInRootFrame.DetermineComponentFrameRoot(),
    sampleStack = _RunInRootFrame$Deter[0],
    controlStack = _RunInRootFrame$Deter[1];
```

```
    if (sampleStack && controlStack) {
      var sampleLines = sampleStack.split("\n"),
        controlLines = controlStack.split("\n");
      for (_RunInRootFrame$Deter = namePropDescriptor = 0; namePropDescriptor <
sampleLines.length && !
sampleLines[namePropDescriptor].includes("DetermineComponentFrameRoot");)
namePropDescriptor++;
      for (; _RunInRootFrame$Deter < controlLines.length && !
controlLines[_RunInRootFrame$Deter].includes("DetermineComponentFrameRoot");)
_RunInRootFrame$Deter++;
      if (namePropDescriptor === sampleLines.length || _RunInRootFrame$Deter ===
controlLines.length) for (namePropDescriptor = sampleLines.length
 - 1, _RunInRootFrame$Deter = controlLines.length - 1; 1 <= namePropDescriptor && 0 <=
_RunInRootFrame$Deter && sampleLines[namePropDescriptor] !==
controlLines[_RunInRootFrame$Deter];) _RunInRootFrame$Deter--;
      for (; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter; namePropDescriptor--,
_RunInRootFrame$Deter--) if (sampleLines[namePropDescriptor] !==
controlLines[_RunInRootFrame$Deter]) {
        if (1 !== namePropDescriptor || 1 !== _RunInRootFrame$Deter) {
          do if (namePropDescriptor--, _RunInRootFrame$Deter--, 0 > _RunInRootFrame$Deter ||
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter]) {
            var _frame = "\n" + sampleLines[namePropDescriptor].replace(" at new ", " at ");
            fn.displayName && _frame.includes("<anonymous>") && (_frame =
_frame.replace("<anonymous>", fn.displayName));
            "function" === typeof fn && componentFrameCache.set(fn, _frame);
            return _frame;
          } while (1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter);
        }
        break;
      }
    }
  } finally {
    reentry = !1, ReactSharedInternals.H = previousDispatcher, reenableLogs(),
Error.prepareStackTrace = frame;
  }
  sampleLines = (sampleLines = fn ? fn.displayName || fn.name : "") ?
describeBuiltInComponentFrame(sampleLines) : "";
  "function" === typeof fn && componentFrameCache.set(fn, sampleLines);
  return sampleLines;
 }
 function describeFiber(fiber) {
  switch (fiber.tag) {
    case 26:
    case 27:
    case 5:
      return describeBuiltInComponentFrame(fiber.type);
    case 16:
      return describeBuiltInComponentFrame("Lazy");
    case 13:
```

```
      return describeBuiltInComponentFrame("Suspense");
    case 19:
      return describeBuiltInComponentFrame("SuspenseList");
    case 0:
    case 15:
      return fiber = describeNativeComponentFrame(fiber.type, !1), fiber;
    case 11:
      return fiber = describeNativeComponentFrame(fiber.type.render, !1), fiber;
    case 1:
      return fiber = describeNativeComponentFrame(fiber.type, !0), fiber;
    default:
      return "";
  }
}
function getStackByFiberInDevAndProd(workInProgress) {
  try {
    var info = "";
    do {
      info += describeFiber(workInProgress);
      var debugInfo = workInProgress._debugInfo;
      if (debugInfo) for (var i = debugInfo.length - 1; 0 <= i; i--) {
        var entry = debugInfo[i];
        if ("string" === typeof entry.name) {
          var JSCompiler_temp_const = info,
            env = entry.env;
          var JSCompiler_inline_result = describeBuiltInComponentFrame(entry.name + (env ? " [" +
env + "]" : ""));
          info = JSCompiler_temp_const + JSCompiler_inline_result;
        }
      }
      workInProgress = workInProgress.return;
    } while (workInProgress);
    return info;
  } catch (x) {
    return "\nError generating stack: " + x.message + "\n" + x.stack;
  }
}
function getCurrentFiberOwnerNameInDevOrNull() {
  if (null === current) return null;
  var owner = current._debugOwner;
  return null != owner ? getComponentNameFromOwner(owner) : null;
}
function getCurrentFiberStackInDev() {
  return null === current ? "" : getStackByFiberInDevAndProd(current);
}
function runWithFiberInDEV(fiber, callback, arg0, arg1, arg2, arg3, arg4) {
  var previousFiber = current;
  ReactSharedInternals.getCurrentStack = null === fiber ? null : getCurrentFiberStackInDev;
  isRendering = !1;
```

```
    current = fiber;
    try {
      return callback(arg0, arg1, arg2, arg3, arg4);
    } finally {
      current = previousFiber;
    }
    // removed by dead control flow

  }
  function getNearestMountedFiber(fiber) {
    var node = fiber,
      nearestMounted = fiber;
    if (fiber.alternate) for (; node.return;) node = node.return;else {
      fiber = node;
      do node = fiber, 0 !== (node.flags & 4098) && (nearestMounted = node.return), fiber =
node.return; while (fiber);
    }
    return 3 === node.tag ? nearestMounted : null;
  }
  function getSuspenseInstanceFromFiber(fiber) {
    if (13 === fiber.tag) {
      var suspenseState = fiber.memoizedState;
      null === suspenseState && (fiber = fiber.alternate, null !== fiber && (suspenseState =
fiber.memoizedState));
      if (null !== suspenseState) return suspenseState.dehydrated;
    }
    return null;
  }
  function assertIsMounted(fiber) {
    if (getNearestMountedFiber(fiber) !== fiber) throw Error("Unable to find node on an unmounted
component.");
  }
  function findCurrentFiberUsingSlowPath(fiber) {
    var alternate = fiber.alternate;
    if (!alternate) {
      alternate = getNearestMountedFiber(fiber);
      if (null === alternate) throw Error("Unable to find node on an unmounted component.");
      return alternate !== fiber ? null : fiber;
    }
    for (var a = fiber, b = alternate;;) {
      var parentA = a.return;
      if (null === parentA) break;
      var parentB = parentA.alternate;
      if (null === parentB) {
        b = parentA.return;
        if (null !== b) {
          a = b;
          continue;
        }
```

```
      break;
    }
    if (parentA.child === parentB.child) {
      for (parentB = parentA.child; parentB;) {
        if (parentB === a) return assertIsMounted(parentA), fiber;
        if (parentB === b) return assertIsMounted(parentA), alternate;
        parentB = parentB.sibling;
      }
      throw Error("Unable to find node on an unmounted component.");
    }
    if (a.return !== b.return) a = parentA, b = parentB;else {
      for (var didFindChild = !1, _child = parentA.child; _child;) {
        if (_child === a) {
          didFindChild = !0;
          a = parentA;
          b = parentB;
          break;
        }
        if (_child === b) {
          didFindChild = !0;
          b = parentA;
          a = parentB;
          break;
        }
        _child = _child.sibling;
      }
      if (!didFindChild) {
        for (_child = parentB.child; _child;) {
          if (_child === a) {
            didFindChild = !0;
            a = parentB;
            b = parentA;
            break;
          }
          if (_child === b) {
            didFindChild = !0;
            b = parentB;
            a = parentA;
            break;
          }
          _child = _child.sibling;
        }
        if (!didFindChild) throw Error("Child was not found in either parent set. This indicates a bug in
React related to the return pointer. Please file an issue.");
      }
    }
    if (a.alternate !== b) throw Error("Return fibers should always be each others' alternates. This error
is likely caused by a bug in React. Please file an issue.");
  }
```

```
    if (3 !== a.tag) throw Error("Unable to find node on an unmounted component.");
    return a.stateNode.current === a ? fiber : alternate;
  }
  function findCurrentHostFiberImpl(node) {
    var tag = node.tag;
    if (5 === tag || 26 === tag || 27 === tag || 6 === tag) return node;
    for (node = node.child; null !== node;) {
      tag = findCurrentHostFiberImpl(node);
      if (null !== tag) return tag;
      node = node.sibling;
    }
    return null;
  }
  function createCursor(defaultValue) {
    return {
      current: defaultValue
    };
  }
  function pop(cursor, fiber) {
    0 > index$jscomp$0 ? console.error("Unexpected pop.") : (fiber !== fiberStack[index$jscomp$0]
&& console.error("Unexpected Fiber popped."), cursor.current = valueStack[index$jscomp$0],
valueStack[index$jscomp$0] = null, fiberStack[index$jscomp$0] = null, index$jscomp$0--);
  }
  function push(cursor, value, fiber) {
    index$jscomp$0++;
    valueStack[index$jscomp$0] = cursor.current;
    fiberStack[index$jscomp$0] = fiber;
    cursor.current = value;
  }
  function requiredContext(c) {
    null === c && console.error("Expected host context to exist. This error is likely caused by a bug in
React. Please file an issue.");
    return c;
  }
  function pushHostContainer(fiber, nextRootInstance) {
    push(rootInstanceStackCursor, nextRootInstance, fiber);
    push(contextFiberStackCursor, fiber, fiber);
    push(contextStackCursor, null, fiber);
    var nextRootContext = nextRootInstance.nodeType;
    switch (nextRootContext) {
      case 9:
      case 11:
        nextRootContext = 9 === nextRootContext ? "#document" : "#fragment";
        nextRootInstance = (nextRootInstance = nextRootInstance.documentElement) ?
(nextRootInstance = nextRootInstance.namespaceURI) ? getOwnHostContext(nextRootInstance) :
HostContextNamespaceNone : HostContextNamespaceNone;
        break;
      default:
        if (nextRootInstance = 8 === nextRootContext ? nextRootInstance.parentNode :
```

```
nextRootInstance, nextRootContext = nextRootInstance.tagName, nextRootInstance =
nextRootInstance.namespaceURI) nextRootInstance = getOwnHostContext(nextRootInstance),
nextRootInstance = getChildHostContextProd(nextRootInstance, nextRootContext);else switch
(nextRootContext) {
        case "svg":
          nextRootInstance = HostContextNamespaceSvg;
          break;
        case "math":
          nextRootInstance = HostContextNamespaceMath;
          break;
        default:
          nextRootInstance = HostContextNamespaceNone;
      }
    }
    nextRootContext = nextRootContext.toLowerCase();
    nextRootContext = updatedAncestorInfoDev(null, nextRootContext);
    nextRootContext = {
      context: nextRootInstance,
      ancestorInfo: nextRootContext
    };
    pop(contextStackCursor, fiber);
    push(contextStackCursor, nextRootContext, fiber);
  }
  function popHostContainer(fiber) {
    pop(contextStackCursor, fiber);
    pop(contextFiberStackCursor, fiber);
    pop(rootInstanceStackCursor, fiber);
  }
  function getHostContext() {
    return requiredContext(contextStackCursor.current);

  }
  function pushHostContext(fiber) {
    null !== fiber.memoizedState && push(hostTransitionProviderCursor, fiber, fiber);
    var context = requiredContext(contextStackCursor.current);
    var type = fiber.type;
    var nextContext = getChildHostContextProd(context.context, type);
    type = updatedAncestorInfoDev(context.ancestorInfo, type);
    nextContext = {
      context: nextContext,
      ancestorInfo: type
    };
    context !== nextContext && (push(contextFiberStackCursor, fiber, fiber), push(contextStackCursor,
nextContext, fiber));
  }
  function popHostContext(fiber) {
    contextFiberStackCursor.current === fiber && (pop(contextStackCursor, fiber),
pop(contextFiberStackCursor, fiber));
    hostTransitionProviderCursor.current === fiber && (pop(hostTransitionProviderCursor, fiber),
```

```
HostTransitionContext._currentValue = NotPendingTransition);
  }
  function typeName(value) {
    return "function" === typeof Symbol && Symbol.toStringTag && value[Symbol.toStringTag] ||
value.constructor.name || "Object";
  }
  function willCoercionThrow(value) {
    try {
      return testStringCoercion(value), !1;
    } catch (e) {
      return !0;
    }
  }
  function testStringCoercion(value) {
    return "" + value;
  }
  function checkAttributeStringCoercion(value, attributeName) {
    if (willCoercionThrow(value)) return console.error("The provided `%s` attribute is an unsupported
type %s. This value must be coerced to a string before using it here.", attributeName,
typeName(value)), testStringCoercion(value);
  }
  function checkCSSPropertyStringCoercion(value, propName) {
    if (willCoercionThrow(value)) return console.error("The provided `%s` CSS property is an
unsupported type %s. This value must be coerced to a string before using it here.", propName,
typeName(value)), testStringCoercion(value);
  }
  function checkFormFieldValueStringCoercion(value) {
    if (willCoercionThrow(value)) return console.error("Form field values (value, checked, defaultValue,
or defaultChecked props) must be strings, not %s. This value must be coerced to a string before using it
here.", typeName(value)), testStringCoercion(value);
  }
  function injectInternals(internals) {
    if ("undefined" === typeof __REACT_DEVTOOLS_GLOBAL_HOOK__) return !1;
    var hook = __REACT_DEVTOOLS_GLOBAL_HOOK__;
    if (hook.isDisabled) return !0;
    if (!hook.supportsFiber) return console.error("The installed version of React DevTools is too old and
will not work with the current version of React. Please update React DevTools.
https://react.dev/link/react-devtools"), !0;
    try {
      rendererID = hook.inject(internals), injectedHook = hook;
    } catch (err) {
      console.error("React instrumentation encountered an error: %s.", err);
    }
    return hook.checkDCE ? !0 : !1;
  }
  function onCommitRoot$1(root, eventPriority) {
    if (injectedHook && "function" === typeof injectedHook.onCommitFiberRoot) try {
      var didError = 128 === (root.current.flags & 128);
      switch (eventPriority) {
```

```
        case DiscreteEventPriority:
          var schedulerPriority = ImmediatePriority;
          break;
        case ContinuousEventPriority:
          schedulerPriority = UserBlockingPriority;
          break;
        case DefaultEventPriority:
          schedulerPriority = NormalPriority$1;
          break;
        case IdleEventPriority:
          schedulerPriority = IdlePriority;
          break;
        default:
          schedulerPriority = NormalPriority$1;
      }
      injectedHook.onCommitFiberRoot(rendererID, root, schedulerPriority, didError);
    } catch (err) {
      hasLoggedError || (hasLoggedError = !0, console.error("React instrumentation encountered an
error: %s", err));
    }
  }
  function setIsStrictModeForDevtools(newIsStrictMode) {
    "function" === typeof log$1 && unstable_setDisableYieldValue(newIsStrictMode);
    if (injectedHook && "function" === typeof injectedHook.setStrictMode) try {
      injectedHook.setStrictMode(rendererID, newIsStrictMode);
    } catch (err) {
      hasLoggedError || (hasLoggedError = !0, console.error("React instrumentation encountered an
error: %s", err));
    }
  }
  function injectProfilingHooks(profilingHooks) {
    injectedProfilingHooks = profilingHooks;
  }
  function markCommitStopped() {
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markCommitStopped && injectedProfilingHooks.markCommitStopped();
  }
  function markComponentRenderStarted(fiber) {
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentRenderStarted &&
injectedProfilingHooks.markComponentRenderStarted(fiber);
  }
  function markComponentRenderStopped() {
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentRenderStopped &&
injectedProfilingHooks.markComponentRenderStopped();
  }
  function markRenderStarted(lanes) {
    null !== injectedProfilingHooks && "function" === typeof
```

```
injectedProfilingHooks.markRenderStarted && injectedProfilingHooks.markRenderStarted(lanes);
  }
  function markRenderStopped() {
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markRenderStopped && injectedProfilingHooks.markRenderStopped();
  }
  function markStateUpdateScheduled(fiber, lane) {
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markStateUpdateScheduled &&
injectedProfilingHooks.markStateUpdateScheduled(fiber, lane);
  }
  function clz32Fallback(x) {
    x >>>= 0;
    return 0 === x ? 32 : 31 - (log(x) / LN2 | 0) | 0;
  }
  function getLabelForLane(lane) {
    if (lane & 1) return "SyncHydrationLane";
    if (lane & 2) return "Sync";
    if (lane & 4) return "InputContinuousHydration";
    if (lane & 8) return "InputContinuous";
    if (lane & 16) return "DefaultHydration";
    if (lane & 32) return "Default";
    if (lane & 64) return "TransitionHydration";
    if (lane & 4194176) return "Transition";
    if (lane & 62914560) return "Retry";
    if (lane & 67108864) return "SelectiveHydration";
    if (lane & 134217728) return "IdleHydration";
    if (lane & 268435456) return "Idle";
    if (lane & 536870912) return "Offscreen";
    if (lane & 1073741824) return "Deferred";
  }
  function getHighestPriorityLanes(lanes) {
    var pendingSyncLanes = lanes & 42;
    if (0 !== pendingSyncLanes) return pendingSyncLanes;
    switch (lanes & -lanes) {
      case 1:
        return 1;
      case 2:
        return 2;
      case 4:
        return 4;
      case 8:
        return 8;
      case 16:
        return 16;
      case 32:
        return 32;
      case 64:
        return 64;
```

```
      case 128:
      case 256:
      case 512:
      case 1024:
      case 2048:
      case 4096:
      case 8192:
      case 16384:
      case 32768:
      case 65536:
      case 131072:
      case 262144:
      case 524288:
      case 1048576:
      case 2097152:
        return lanes & 4194176;
      case 4194304:
      case 8388608:
      case 16777216:
      case 33554432:
        return lanes & 62914560;
      case 67108864:
        return 67108864;
      case 134217728:
        return 134217728;
      case 268435456:
        return 268435456;
      case 536870912:
        return 536870912;
      case 1073741824:
        return 0;
      default:
        return console.error("Should have found matching lanes. This is a bug in React."), lanes;
    }
  }
  function getNextLanes(root, wipLanes) {
    var pendingLanes = root.pendingLanes;
    if (0 === pendingLanes) return 0;
    var nextLanes = 0,
      suspendedLanes = root.suspendedLanes,
      pingedLanes = root.pingedLanes,
      warmLanes = root.warmLanes;
    root = 0 !== root.finishedLanes;
    var nonIdlePendingLanes = pendingLanes & 134217727;
    0 !== nonIdlePendingLanes ? (pendingLanes = nonIdlePendingLanes & ~suspendedLanes, 0 !==
pendingLanes ? nextLanes = getHighestPriorityLanes(pendingLanes) : (pingedLanes &=
nonIdlePendingLanes, 0 !== pingedLanes ? nextLanes = getHighestPriorityLanes(pingedLanes) : root ||
(warmLanes = nonIdlePendingLanes & ~warmLanes, 0 !== warmLanes && (nextLanes =
getHighestPriorityLanes(warmLanes))))) : (nonIdlePendingLanes = pendingLanes &
```

```
~suspendedLanes, 0 !== nonIdlePendingLanes ? nextLanes =
getHighestPriorityLanes(nonIdlePendingLanes) : 0 !== pingedLanes ? nextLanes =
getHighestPriorityLanes(pingedLanes) : root || (warmLanes = pendingLanes & ~warmLanes, 0 !==
warmLanes && (nextLanes = getHighestPriorityLanes(warmLanes))));
   return 0 === nextLanes ? 0 : 0 !== wipLanes && wipLanes !== nextLanes && 0 === (wipLanes &
suspendedLanes) && (suspendedLanes = nextLanes & -nextLanes, warmLanes = wipLanes &
-wipLanes, suspendedLanes >= warmLanes || 32 === suspendedLanes && 0 !== (warmLanes &
4194176)) ? wipLanes : nextLanes;
 }
 function checkIfRootIsPrerendering(root, renderLanes) {
  return 0 === (root.pendingLanes & ~(root.suspendedLanes & ~root.pingedLanes) & renderLanes);
 }
 function computeExpirationTime(lane, currentTime) {
  switch (lane) {
    case 1:
    case 2:
    case 4:
    case 8:
      return currentTime + 250;
    case 16:
    case 32:
    case 64:
    case 128:
    case 256:
    case 512:
    case 1024:
    case 2048:
    case 4096:
    case 8192:
    case 16384:
    case 32768:
    case 65536:
    case 131072:
    case 262144:
    case 524288:
    case 1048576:
    case 2097152:
      return currentTime + 5e3;
    case 4194304:
    case 8388608:
    case 16777216:
    case 33554432:
      return -1;
    case 67108864:
    case 134217728:
    case 268435456:
    case 536870912:
    case 1073741824:
      return -1;
```

```
      default:
        return console.error("Should have found matching lanes. This is a bug in React."), -1;
    }
  }
  function claimNextTransitionLane() {
    var lane = nextTransitionLane;

    nextTransitionLane <<= 1;
    0 === (nextTransitionLane & 4194176) && (nextTransitionLane = 128);
    return lane;
  }
  function claimNextRetryLane() {
    var lane = nextRetryLane;
    nextRetryLane <<= 1;
    0 === (nextRetryLane & 62914560) && (nextRetryLane = 4194304);
    return lane;
  }
  function createLaneMap(initial) {
    for (var laneMap = [], i = 0; 31 > i; i++) laneMap.push(initial);
    return laneMap;
  }
  function markRootUpdated$1(root, updateLane) {
    root.pendingLanes |= updateLane;
    268435456 !== updateLane && (root.suspendedLanes = 0, root.pingedLanes = 0, root.warmLanes =
0);
  }
  function markRootFinished(root, finishedLanes, remainingLanes, spawnedLane, updatedLanes,
suspendedRetryLanes) {
    var previouslyPendingLanes = root.pendingLanes;
    root.pendingLanes = remainingLanes;
    root.suspendedLanes = 0;
    root.pingedLanes = 0;
    root.warmLanes = 0;
    root.expiredLanes &= remainingLanes;
    root.entangledLanes &= remainingLanes;
    root.errorRecoveryDisabledLanes &= remainingLanes;
    root.shellSuspendCounter = 0;
    var entanglements = root.entanglements,
      expirationTimes = root.expirationTimes,
      hiddenUpdates = root.hiddenUpdates;
    for (remainingLanes = previouslyPendingLanes & ~remainingLanes; 0 < remainingLanes;) {
      var index = 31 - clz32(remainingLanes),
        lane = 1 << index;
      entanglements[index] = 0;
      expirationTimes[index] = -1;
      var hiddenUpdatesForLane = hiddenUpdates[index];
      if (null !== hiddenUpdatesForLane) for (hiddenUpdates[index] = null, index = 0; index <
hiddenUpdatesForLane.length; index++) {
        var update = hiddenUpdatesForLane[index];
```

```
      null !== update && (update.lane &= -536870913);
     }
     remainingLanes &= ~lane;
    }
    0 !== spawnedLane && markSpawnedDeferredLane(root, spawnedLane, 0);
    0 !== suspendedRetryLanes && 0 === updatedLanes && 0 !== root.tag && (root.suspendedLanes |
= suspendedRetryLanes & ~(previouslyPendingLanes & ~finishedLanes));
  }
  function markSpawnedDeferredLane(root, spawnedLane, entangledLanes) {
    root.pendingLanes |= spawnedLane;
    root.suspendedLanes &= ~spawnedLane;
    var spawnedLaneIndex = 31 - clz32(spawnedLane);
    root.entangledLanes |= spawnedLane;
    root.entanglements[spawnedLaneIndex] = root.entanglements[spawnedLaneIndex] | 1073741824 |
entangledLanes & 4194218;
  }
  function markRootEntangled(root, entangledLanes) {
    var rootEntangledLanes = root.entangledLanes |= entangledLanes;
    for (root = root.entanglements; rootEntangledLanes;) {
      var index = 31 - clz32(rootEntangledLanes),
        lane = 1 << index;
      lane & entangledLanes | root[index] & entangledLanes && (root[index] |= entangledLanes);
      rootEntangledLanes &= ~lane;
    }
  }
  function addFiberToLanesMap(root, fiber, lanes) {
    if (isDevToolsPresent) for (root = root.pendingUpdatersLaneMap; 0 < lanes;) {
      var index = 31 - clz32(lanes),
        lane = 1 << index;
      root[index].add(fiber);
      lanes &= ~lane;
    }
  }
  function movePendingFibersToMemoized(root, lanes) {
    if (isDevToolsPresent) for (var pendingUpdatersLaneMap = root.pendingUpdatersLaneMap,
memoizedUpdaters = root.memoizedUpdaters; 0 < lanes;) {
      var index = 31 - clz32(lanes);
      root = 1 << index;
      index = pendingUpdatersLaneMap[index];
      0 < index.size && (index.forEach(function (fiber) {
        var alternate = fiber.alternate;
        null !== alternate && memoizedUpdaters.has(alternate) || memoizedUpdaters.add(fiber);
      }), index.clear());
      lanes &= ~root;
    }
  }
  function lanesToEventPriority(lanes) {
    lanes &= -lanes;
    return 0 !== DiscreteEventPriority && DiscreteEventPriority < lanes ? 0 !==
```

```
ContinuousEventPriority && ContinuousEventPriority < lanes ? 0 !== (lanes & 134217727) ?
DefaultEventPriority : IdleEventPriority : ContinuousEventPriority : DiscreteEventPriority;
  }
  function resolveUpdatePriority() {
    var updatePriority = ReactDOMSharedInternals.p;
    if (0 !== updatePriority) return updatePriority;
    updatePriority = window.event;
    return void 0 === updatePriority ? DefaultEventPriority : getEventPriority(updatePriority.type);
  }
  function runWithPriority(priority, fn) {
    var previousPriority = ReactDOMSharedInternals.p;
    try {
      return ReactDOMSharedInternals.p = priority, fn();
    } finally {
      ReactDOMSharedInternals.p = previousPriority;
    }
  }
  function detachDeletedInstance(node) {
    delete node[internalInstanceKey];
    delete node[internalPropsKey];
    delete node[internalEventHandlersKey];
    delete node[internalEventHandlerListenersKey];
    delete node[internalEventHandlesSetKey];
  }
  function getClosestInstanceFromNode(targetNode) {
    var targetInst = targetNode[internalInstanceKey];
    if (targetInst) return targetInst;
    for (var parentNode = targetNode.parentNode; parentNode;) {
      if (targetInst = parentNode[internalContainerInstanceKey] || parentNode[internalInstanceKey]) {
        parentNode = targetInst.alternate;
        if (null !== targetInst.child || null !== parentNode && null !== parentNode.child) for (targetNode
= getParentSuspenseInstance(targetNode); null !== targetNode;) {
          if (parentNode = targetNode[internalInstanceKey]) return parentNode;
          targetNode = getParentSuspenseInstance(targetNode);
        }
        return targetInst;
      }
      targetNode = parentNode;
      parentNode = targetNode.parentNode;
    }
    return null;
  }
  function getInstanceFromNode(node) {
    if (node = node[internalInstanceKey] || node[internalContainerInstanceKey]) {
      var tag = node.tag;
      if (5 === tag || 6 === tag || 13 === tag || 26 === tag || 27 === tag || 3 === tag) return node;
    }
    return null;
  }
```

```
  function getNodeFromInstance(inst) {
    var tag = inst.tag;
    if (5 === tag || 26 === tag || 27 === tag || 6 === tag) return inst.stateNode;
    throw Error("getNodeFromInstance: Invalid argument.");
  }
  function getResourcesFromRoot(root) {
    var resources = root[internalRootNodeResourcesKey];
    resources || (resources = root[internalRootNodeResourcesKey] = {
      hoistableStyles: new Map(),
      hoistableScripts: new Map()
    });
    return resources;
  }
  function markNodeAsHoistable(node) {
    node[internalHoistableMarker] = !0;
  }
  function registerTwoPhaseEvent(registrationName, dependencies) {
    registerDirectEvent(registrationName, dependencies);
    registerDirectEvent(registrationName + "Capture", dependencies);
  }
  function registerDirectEvent(registrationName, dependencies) {
    registrationNameDependencies[registrationName] && console.error("EventRegistry: More than one
plugin attempted to publish the same registration name, `%s`.", registrationName);
    registrationNameDependencies[registrationName] = dependencies;
    var lowerCasedName = registrationName.toLowerCase();
    possibleRegistrationNames[lowerCasedName] = registrationName;
    "onDoubleClick" === registrationName && (possibleRegistrationNames.ondblclick =
registrationName);
    for (registrationName = 0; registrationName < dependencies.length; registrationName++)
allNativeEvents.add(dependencies[registrationName]);
  }
  function checkControlledValueProps(tagName, props) {
    hasReadOnlyValue[props.type] || props.onChange || props.onInput || props.readOnly || props.disabled
|| null == props.value || ("select" === tagName ? console.error("You provided a `value` prop to a form
field without an `onChange` handler. This will render a read-only field. If the field should be mutable
use `defaultValue`. Otherwise, set `onChange`.") : console.error("You provided a `value` prop to a form
field without an `onChange` handler. This will render a read-only field. If the field should be mutable
use `defaultValue`. Otherwise, set either `onChange` or `readOnly`."));
    props.onChange || props.readOnly || props.disabled || null == props.checked || console.error("You
provided a `checked` prop to a form field without an `onChange` handler. This will render a read-only
field. If the field should be mutable use `defaultChecked`. Otherwise, set either `onChange` or
`readOnly`.");
  }
  function isAttributeNameSafe(attributeName) {
    if (hasOwnProperty.call(validatedAttributeNameCache, attributeName)) return !0;
    if (hasOwnProperty.call(illegalAttributeNameCache, attributeName)) return !1;
    if (VALID_ATTRIBUTE_NAME_REGEX.test(attributeName)) return
validatedAttributeNameCache[attributeName] = !0;
    illegalAttributeNameCache[attributeName] = !0;
```

```
  console.error("Invalid attribute name: `%s`", attributeName);
  return !1;
 }
 function getValueForAttributeOnCustomComponent(node, name, expected) {
  if (isAttributeNameSafe(name)) {
   if (!node.hasAttribute(name)) {
    switch (typeof expected) {
     case "symbol":
     case "object":
      return expected;
     case "function":
      return expected;
     case "boolean":
      if (!1 === expected) return expected;
    }
    return void 0 === expected ? void 0 : null;
   }
   node = node.getAttribute(name);
   if ("" === node && !0 === expected) return !0;
   checkAttributeStringCoercion(expected, name);
   return node === "" + expected ? expected : node;
  }
 }
 function setValueForAttribute(node, name, value) {
  if (isAttributeNameSafe(name)) if (null === value) node.removeAttribute(name);else {
   switch (typeof value) {
    case "undefined":
    case "function":
    case "symbol":
     node.removeAttribute(name);
     return;
    case "boolean":
     var prefix = name.toLowerCase().slice(0, 5);
     if ("data-" !== prefix && "aria-" !== prefix) {
      node.removeAttribute(name);
      return;
     }
   }
   checkAttributeStringCoercion(value,
name);
   node.setAttribute(name, "" + value);
  }
 }
 function setValueForKnownAttribute(node, name, value) {
  if (null === value) node.removeAttribute(name);else {
   switch (typeof value) {
    case "undefined":
    case "function":
    case "symbol":
```

```
        case "boolean":
          node.removeAttribute(name);
          return;
      }
      checkAttributeStringCoercion(value, name);
      node.setAttribute(name, "" + value);
    }
  }
  function setValueForNamespacedAttribute(node, namespace, name, value) {
    if (null === value) node.removeAttribute(name);else {
      switch (typeof value) {
        case "undefined":
        case "function":
        case "symbol":
        case "boolean":
          node.removeAttribute(name);
          return;
      }
      checkAttributeStringCoercion(value, name);
      node.setAttributeNS(namespace, name, "" + value);
    }
  }
  function getToStringValue(value) {
    switch (typeof value) {
      case "bigint":
      case "boolean":
      case "number":
      case "string":
      case "undefined":
        return value;
      case "object":
        return checkFormFieldValueStringCoercion(value), value;
      default:
        return "";
    }
  }
  function isCheckable(elem) {
    var type = elem.type;
    return (elem = elem.nodeName) && "input" === elem.toLowerCase() && ("checkbox" === type ||
"radio" === type);
  }
  function trackValueOnNode(node) {
    var valueField = isCheckable(node) ? "checked" : "value",
      descriptor = Object.getOwnPropertyDescriptor(node.constructor.prototype, valueField);
    checkFormFieldValueStringCoercion(node[valueField]);
    var currentValue = "" + node[valueField];
    if (!node.hasOwnProperty(valueField) && "undefined" !== typeof descriptor && "function" ===
typeof descriptor.get && "function" === typeof descriptor.set) {
      var get = descriptor.get,
```

```
      set = descriptor.set;
    Object.defineProperty(node, valueField, {
      configurable: !0,
      get: function () {
        return get.call(this);
      },
      set: function (value) {
        checkFormFieldValueStringCoercion(value);
        currentValue = "" + value;
        set.call(this, value);
      }
    });
    Object.defineProperty(node, valueField, {
      enumerable: descriptor.enumerable
    });
    return {
      getValue: function () {
        return currentValue;
      },
      setValue: function (value) {
        checkFormFieldValueStringCoercion(value);
        currentValue = "" + value;
      },
      stopTracking: function () {
        node._valueTracker = null;
        delete node[valueField];
      }
    };
  }
}
function track(node) {
  node._valueTracker || (node._valueTracker = trackValueOnNode(node));
}
function updateValueIfChanged(node) {
  if (!node) return !1;
  var tracker = node._valueTracker;
  if (!tracker) return !0;
  var lastValue = tracker.getValue();
  var value = "";
  node && (value = isCheckable(node) ? node.checked ? "true" : "false" : node.value);
  node = value;
  return node !== lastValue ? (tracker.setValue(node), !0) : !1;
}
function getActiveElement(doc) {
  doc = doc || ("undefined" !== typeof document ? document : void 0);
  if ("undefined" === typeof doc) return null;
  try {
    return doc.activeElement || doc.body;
  } catch (e) {
```

```
      return doc.body;
    }
  }
  function escapeSelectorAttributeValueInsideDoubleQuotes(value) {
    return value.replace(escapeSelectorAttributeValueInsideDoubleQuotesRegex, function (ch) {
      return "\\" + ch.charCodeAt(0).toString(16) + " ";
    });
  }
  function validateInputProps(element, props) {
    void 0 === props.checked || void 0 === props.defaultChecked || didWarnCheckedDefaultChecked ||
(console.error("%s contains an input of type %s with both checked and defaultChecked props. Input
elements must be either controlled or uncontrolled (specify either the checked prop, or the
defaultChecked prop, but not both). Decide between using a controlled or uncontrolled input element
and remove one of these props. More info: https://react.dev/link/controlled-components",
getCurrentFiberOwnerNameInDevOrNull() || "A component", props.type),
didWarnCheckedDefaultChecked = !0);
    void 0 === props.value || void 0 === props.defaultValue || didWarnValueDefaultValue$1 ||
(console.error("%s contains an input of type %s with both value and defaultValue props. Input elements
must be either controlled or uncontrolled (specify either the value prop, or the defaultValue prop, but
not both). Decide between using a controlled or uncontrolled input element and remove one of these
props. More info: https://react.dev/link/controlled-components",
getCurrentFiberOwnerNameInDevOrNull() || "A component", props.type),
didWarnValueDefaultValue$1 = !0);
  }
  function updateInput(element, value, defaultValue, lastDefaultValue, checked, defaultChecked, type,
name) {
    element.name = "";
    null != type && "function" !== typeof type && "symbol" !== typeof type && "boolean" !== typeof
type ? (checkAttributeStringCoercion(type, "type"), element.type = type) :
element.removeAttribute("type");
    if (null != value) {
      if ("number" === type) {
        if (0 === value && "" === element.value || element.value != value) element.value = "" +
getToStringValue(value);
      } else element.value !== "" + getToStringValue(value) && (element.value = "" +
getToStringValue(value));
    } else "submit" !== type && "reset" !== type || element.removeAttribute("value");
    null != value ? setDefaultValue(element, type, getToStringValue(value)) : null != defaultValue ?
setDefaultValue(element, type, getToStringValue(defaultValue)) : null != lastDefaultValue &&
element.removeAttribute("value");
    null == checked && null != defaultChecked && (element.defaultChecked = !!defaultChecked);
    null != checked && (element.checked = checked && "function" !== typeof checked && "symbol" !
== typeof checked);
    null != name && "function" !== typeof name && "symbol" !== typeof name && "boolean" !==
typeof name ? (checkAttributeStringCoercion(name, "name"), element.name = "" +
getToStringValue(name)) : element.removeAttribute("name");
  }
  function initInput(element, value, defaultValue, checked, defaultChecked, type, name, isHydrating) {
    null != type && "function" !== typeof type && "symbol" !== typeof type && "boolean" !== typeof
```

```
type && (checkAttributeStringCoercion(type, "type"), element.type = type);
    if (null != value || null != defaultValue) {
      if (!("submit" !== type && "reset" !== type || void 0 !== value && null !== value)) return;
      defaultValue = null != defaultValue ? "" + getToStringValue(defaultValue) : "";
      value = null != value ? "" + getToStringValue(value) : defaultValue;
      isHydrating || value === element.value || (element.value = value);
      element.defaultValue = value;
    }
    checked = null != checked ? checked : defaultChecked;
    checked = "function" !== typeof checked && "symbol" !== typeof checked && !!checked;
    element.checked = isHydrating ? element.checked : !!checked;
    element.defaultChecked = !!checked;
    null != name && "function" !== typeof name && "symbol" !== typeof name && "boolean" !==
typeof name && (checkAttributeStringCoercion(name, "name"), element.name = name);
  }
  function setDefaultValue(node, type, value) {
    "number" === type && getActiveElement(node.ownerDocument) === node || node.defaultValue
=== "" + value || (node.defaultValue = "" + value);
  }
  function validateOptionProps(element, props) {
    null == props.value && ("object" === typeof props.children && null !== props.children ?
React.Children.forEach(props.children, function (child) {
      null == child || "string" === typeof child || "number" === typeof child || "bigint" === typeof child ||
didWarnInvalidChild || (didWarnInvalidChild = !0, console.error("Cannot infer the option value of
complex children. Pass a `value` prop or use a plain string as children to <option>."));
    }) : null == props.dangerouslySetInnerHTML || didWarnInvalidInnerHTML ||
(didWarnInvalidInnerHTML = !0, console.error("Pass a `value` prop if you set dangerouslyInnerHTML
so React knows which value should be selected.")));
    null == props.selected || didWarnSelectedSetOnOption || (console.error("Use the `defaultValue` or
`value` props on <select> instead of setting `selected` on <option>."), didWarnSelectedSetOnOption
= !0);
  }
  function getDeclarationErrorAddendum() {
    var ownerName = getCurrentFiberOwnerNameInDevOrNull();
    return ownerName ? "\n\nCheck the render method of `" + ownerName + "`." : "";
  }
  function updateOptions(node, multiple, propValue, setDefaultSelected) {
    node = node.options;
    if (multiple) {
      multiple = {};
      for (var i = 0; i < propValue.length; i++) multiple["$" + propValue[i]] = !0;
      for (propValue = 0; propValue < node.length; propValue++) i = multiple.hasOwnProperty("$" +
node[propValue].value), node[propValue].selected !== i && (node[propValue].selected = i), i &&
setDefaultSelected && (node[propValue].defaultSelected = !0);
    } else {
      propValue = "" + getToStringValue(propValue);
      multiple = null;
      for (i = 0; i < node.length; i++) {
        if (node[i].value === propValue) {
```

```
          node[i].selected = !0;
          setDefaultSelected && (node[i].defaultSelected = !0);
          return;
        }
        null !== multiple || node[i].disabled || (multiple = node[i]);
      }
      null !== multiple && (multiple.selected = !0);
    }
  }
  function validateSelectProps(element, props) {
    for (element = 0; element < valuePropNames.length; element++) {
      var propName = valuePropNames[element];
      if (null != props[propName]) {
        var propNameIsArray = isArrayImpl(props[propName]);
        props.multiple
 && !propNameIsArray ? console.error("The `%s` prop supplied to <select> must be an array if `multiple` is true.%s", propName, getDeclarationErrorAddendum()) : !props.multiple && propNameIsArray && console.error("The `%s` prop supplied to <select> must be a scalar value if `multiple` is false.%s", propName, getDeclarationErrorAddendum());
      }
    }
    void 0 === props.value || void 0 === props.defaultValue || didWarnValueDefaultValue || (console.error("Select elements must be either controlled or uncontrolled (specify either the value prop, or the defaultValue prop, but not both). Decide between using a controlled or uncontrolled select element and remove one of these props. More info: https://react.dev/link/controlled-components"), didWarnValueDefaultValue = !0);
  }
  function validateTextareaProps(element, props) {
    void 0 === props.value || void 0 === props.defaultValue || didWarnValDefaultVal || (console.error("%s contains a textarea with both value and defaultValue props. Textarea elements must be either controlled or uncontrolled (specify either the value prop, or the defaultValue prop, but not both). Decide between using a controlled or uncontrolled textarea and remove one of these props. More info: https://react.dev/link/controlled-components", getCurrentFiberOwnerNameInDevOrNull() || "A component"), didWarnValDefaultVal = !0);
    null != props.children && null == props.value && console.error("Use the `defaultValue` or `value` props instead of setting children on <textarea>.");
  }
  function updateTextarea(element, value, defaultValue) {
    if (null != value && (value = "" + getToStringValue(value), value !== element.value && (element.value = value), null == defaultValue)) {
      element.defaultValue !== value && (element.defaultValue = value);
      return;
    }
    element.defaultValue = null != defaultValue ? "" + getToStringValue(defaultValue) : "";
  }
  function initTextarea(element, value, defaultValue, children) {
    if (null == value) {
      if (null != children) {
        if (null != defaultValue) throw Error("If you supply `defaultValue` on a <textarea>, do not pass
```

```
children.");
        if (isArrayImpl(children)) {
          if (1 < children.length) throw Error("<textarea> can only have at most one child.");
          children = children[0];
        }
        defaultValue = children;
      }
      null == defaultValue && (defaultValue = "");
      value = defaultValue;
    }
    defaultValue = getToStringValue(value);
    element.defaultValue = defaultValue;
    children = element.textContent;
    children === defaultValue && "" !== children && null !== children && (element.value = children);
  }
  function findNotableNode(node, indent) {
    return void 0 === node.serverProps && 0 === node.serverTail.length && 1 ===
node.children.length && 3 < node.distanceFromLeaf && node.distanceFromLeaf > 15 - indent ?
findNotableNode(node.children[0], indent) : node;
  }
  function indentation(indent) {
    return "  " + "  ".repeat(indent);
  }
  function added(indent) {
    return "+ " + "  ".repeat(indent);
  }
  function removed(indent) {
    return "- " + "  ".repeat(indent);
  }
  function describeFiberType(fiber) {
    switch (fiber.tag) {
      case 26:
      case 27:
      case 5:
        return fiber.type;
      case 16:
        return "Lazy";
      case 13:
        return "Suspense";
      case 19:
        return "SuspenseList";
      case 0:
      case 15:
        return fiber = fiber.type, fiber.displayName || fiber.name || null;
      case 11:
        return fiber = fiber.type.render, fiber.displayName || fiber.name || null;
      case 1:
        return fiber = fiber.type, fiber.displayName || fiber.name || null;
      default:
```

```
      return null;
    }
  }
  function describeTextNode(content, maxLength) {
    return needsEscaping.test(content) ? (content = JSON.stringify(content), content.length >
maxLength - 2 ? 8 > maxLength ? '{"..."}' : "{" + content.slice(0, maxLength - 7) + '..."}' : "{" +
content + "}") : content.length > maxLength ? 5 > maxLength ? '{"..."}' : content.slice(0, maxLength -
3) + "..." : content;
  }
  function describeTextDiff(clientText, serverProps, indent) {
    var maxLength = 120 - 2 * indent;
    if (null === serverProps) return added(indent) + describeTextNode(clientText, maxLength) + "\n";
    if ("string" === typeof serverProps) {
      for (var firstDiff = 0; firstDiff < serverProps.length && firstDiff < clientText.length &&
serverProps.charCodeAt(firstDiff) === clientText.charCodeAt(firstDiff); firstDiff++);
      firstDiff > maxLength - 8 && 10 < firstDiff && (clientText = "..." + clientText.slice(firstDiff - 8),
serverProps = "..." + serverProps.slice(firstDiff - 8));
      return added(indent) + describeTextNode(clientText, maxLength) + "\n" + removed(indent) +
describeTextNode(serverProps, maxLength) + "\n";
    }
    return indentation(indent) + describeTextNode(clientText, maxLength) + "\n";
  }
  function objectName(object) {
    return Object.prototype.toString.call(object).replace(/^\[object (.*)\]$/, function (m, p0) {
      return p0;
    });
  }
  function describeValue(value, maxLength) {
    switch (typeof value) {
      case "string":
        return value = JSON.stringify(value), value.length > maxLength ? 5 > maxLength ? '"..."' :
value.slice(0, maxLength - 4) + '..."' : value;
      case "object":
        if (null === value) return "null";
        if (isArrayImpl(value)) return "[...]";
        if (value.$$typeof === REACT_ELEMENT_TYPE) return (maxLength =
getComponentNameFromType(value.type)) ? "<" + maxLength + ">" : "<...>";
        var name = objectName(value);
        if ("Object" === name) {
          name = "";
          maxLength -= 2;
          for (var propName in value) if (value.hasOwnProperty(propName)) {
            var jsonPropName = JSON.stringify(propName);
            jsonPropName !== '"' + propName + '"' && (propName = jsonPropName);
            maxLength -= propName.length - 2;
            jsonPropName = describeValue(value[propName], 15 > maxLength ? maxLength : 15);
            maxLength -= jsonPropName.length;
            if (0 > maxLength) {
              name += "" === name ? "..." : ", ...";
```

```
            break;
          }
          name += ("" === name ? "" : ",") + propName + ":" + jsonPropName;
        }
        return "{" + name + "}";
      }
      return name;
    case "function":
      return (maxLength = value.displayName || value.name) ? "function " + maxLength : "function";
    default:
      return String(value);
  }
}
function describePropValue(value, maxLength) {
  return "string" !== typeof value || needsEscaping.test(value) ? "{" + describeValue(value, maxLength
- 2) + "}" : value.length > maxLength - 2 ? 5 > maxLength ? '"..."' : '"' + value.slice(0, maxLength - 5)
+ '..."' : '"' + value + '"';
}
function describeExpandedElement(type, props, rowPrefix) {
  var remainingRowLength = 120 - rowPrefix.length - type.length,
    properties = [],
    propName;
  for (propName in props) if (props.hasOwnProperty(propName) && "children" !== propName) {
    var propValue = describePropValue(props[propName], 120 - rowPrefix.length - propName.length -
1);
    remainingRowLength -= propName.length + propValue.length + 2;
    properties.push(propName + "=" + propValue);
  }
  return 0 === properties.length ? rowPrefix + "<" + type + ">\n" : 0 < remainingRowLength ?
rowPrefix + "<" + type + " " + properties.join(" ") + ">\n" : rowPrefix + "<" + type + "\n" + rowPrefix
+ "  " + properties.join("\n" + rowPrefix + "  ") + "\n" + rowPrefix + ">\n";
}
function describePropertiesDiff(clientObject, serverObject, indent) {
  var properties = "",
    remainingServerProperties = assign({}, serverObject),
    propName;
  for (propName in clientObject) if (clientObject.hasOwnProperty(propName)) {
    delete remainingServerProperties[propName];
    var maxLength = 120 - 2 * indent - propName.length - 2,
      clientPropValue = describeValue(clientObject[propName], maxLength);
    serverObject.hasOwnProperty(propName) ? (maxLength = describeValue(serverObject[propName],
maxLength), properties += added(indent) + propName + ": " + clientPropValue + "\n", properties +=
removed(indent) + propName + ": " + maxLength + "\n") : properties += added(indent) + propName +
": " + clientPropValue + "\n";
  }
  for (var _propName in remainingServerProperties)
remainingServerProperties.hasOwnProperty(_propName) && (clientObject =
describeValue(remainingServerProperties[_propName], 120 - 2 * indent - _propName.length - 2),
properties += removed(indent) + _propName + ": " + clientObject + "\n");
```

```
    return properties;
  }
  function describeElementDiff(type, clientProps, serverProps, indent) {
    var content = "",
      serverPropNames = new Map();
    for (propName$jscomp$0 in serverProps) serverProps.hasOwnProperty(propName$jscomp$0) &&
serverPropNames.set(propName$jscomp$0.toLowerCase(), propName$jscomp$0);
    if (1 === serverPropNames.size && serverPropNames.has("children")) content +=
describeExpandedElement(type, clientProps, indentation(indent));else {
      for (var _propName2 in clientProps) if (clientProps.hasOwnProperty(_propName2) &&
"children" !== _propName2) {
        var maxLength$jscomp$0 = 120 - 2 * (indent + 1) - _propName2.length - 1,
          serverPropName = serverPropNames.get(_propName2.toLowerCase());
        if (void 0 !== serverPropName) {
          serverPropNames.delete(_propName2.toLowerCase());
          var propName$jscomp$0 = clientProps[_propName2];
          serverPropName = serverProps[serverPropName];
          var clientPropValue = describePropValue(propName$jscomp$0, maxLength$jscomp$0);
          maxLength$jscomp$0 = describePropValue(serverPropName, maxLength$jscomp$0);
          "object" === typeof propName$jscomp$0
 && null !== propName$jscomp$0 && "object" === typeof serverPropName && null !==
serverPropName && "Object" === objectName(propName$jscomp$0) && "Object" ===
objectName(serverPropName) && (2 < Object.keys(propName$jscomp$0).length || 2 <
Object.keys(serverPropName).length || -1 < clientPropValue.indexOf("...") || -1 <
maxLength$jscomp$0.indexOf("...")) ? content += indentation(indent + 1) + _propName2 + "={{\n" +
describePropertiesDiff(propName$jscomp$0, serverPropName, indent + 2) + indentation(indent + 1) +
"}}\n" : (content += added(indent + 1) + _propName2 + "=" + clientPropValue + "\n", content +=
removed(indent + 1) + _propName2 + "=" + maxLength$jscomp$0 + "\n");
        } else content += indentation(indent + 1) + _propName2 + "=" +
describePropValue(clientProps[_propName2], maxLength$jscomp$0) + "\n";
      }
      serverPropNames.forEach(function (propName) {
        if ("children" !== propName) {
          var maxLength = 120 - 2 * (indent + 1) - propName.length - 1;
          content += removed(indent + 1) + propName + "=" +
describePropValue(serverProps[propName], maxLength) + "\n";
        }
      });
      content = "" === content ? indentation(indent) + "<" + type + ">\n" : indentation(indent) + "<" +
type + "\n" + content + indentation(indent) + ">\n";
    }
    type = serverProps.children;
    clientProps = clientProps.children;
    if ("string" === typeof type || "number" === typeof type || "bigint" === typeof type) {
      serverPropNames = "";
      if ("string" === typeof clientProps || "number" === typeof clientProps || "bigint" === typeof
clientProps) serverPropNames = "" + clientProps;
      content += describeTextDiff(serverPropNames, "" + type, indent + 1);
    } else if ("string" === typeof clientProps || "number" === typeof clientProps || "bigint" === typeof
```

```
clientProps) content = null == type ? content + describeTextDiff("" + clientProps, null, indent + 1) :
content + describeTextDiff("" + clientProps, void 0, indent + 1);
    return content;
  }
  function describeSiblingFiber(fiber, indent) {
    var type = describeFiberType(fiber);
    if (null === type) {
      type = "";
      for (fiber = fiber.child; fiber;) type += describeSiblingFiber(fiber, indent), fiber = fiber.sibling;
      return type;
    }
    return indentation(indent) + "<" + type + ">\n";
  }
  function describeNode(node, indent) {
    var skipToNode = findNotableNode(node, indent);
    if (skipToNode !== node && (1 !== node.children.length || node.children[0] !== skipToNode))
return indentation(indent) + "...\n" + describeNode(skipToNode, indent + 1);
    skipToNode = "";
    var debugInfo = node.fiber._debugInfo;
    if (debugInfo) for (var i = 0; i < debugInfo.length; i++) {
      var serverComponentName = debugInfo[i].name;
      "string" === typeof serverComponentName && (skipToNode += indentation(indent) + "<" +
serverComponentName + ">\n", indent++);
    }
    debugInfo = "";
    i = node.fiber.pendingProps;
    if (6 === node.fiber.tag) debugInfo = describeTextDiff(i, node.serverProps, indent), indent++;else if
(serverComponentName = describeFiberType(node.fiber), null !== serverComponentName) if (void 0
=== node.serverProps) {
      debugInfo = indent;
      var maxLength = 120 - 2 * debugInfo - serverComponentName.length - 2,
        content = "";
      for (propName in i) if (i.hasOwnProperty(propName) && "children" !== propName) {
        var propValue = describePropValue(i[propName], 15);
        maxLength -= propName.length + propValue.length + 2;
        if (0 > maxLength) {
          content += " ...";
          break;
        }
        content += " " + propName + "=" + propValue;
      }
      debugInfo = indentation(debugInfo) + "<" + serverComponentName + content + ">\n";
      indent++;
    } else null === node.serverProps ? (debugInfo = describeExpandedElement(serverComponentName,
i, added(indent)), indent++) : "string" === typeof node.serverProps ? console.error("Should not have
matched a non HostText fiber to a Text node. This is a bug in React.") : (debugInfo =
describeElementDiff(serverComponentName, i, node.serverProps, indent), indent++);
    var propName = "";
    i = node.fiber.child;
```

```
    for (serverComponentName = 0; i && serverComponentName < node.children.length;) maxLength
= node.children[serverComponentName], maxLength.fiber === i ? (propName +=
describeNode(maxLength, indent), serverComponentName++) : propName += describeSiblingFiber(i,
indent), i = i.sibling;
    i && 0 < node.children.length && (propName += indentation(indent) + "...\n");
    i = node.serverTail;
    null === node.serverProps && indent--;
    for (node = 0; node < i.length; node++) serverComponentName = i[node], propName = "string" ===
typeof serverComponentName ? propName + (removed(indent) +
describeTextNode(serverComponentName, 120 - 2 * indent) + "\n") : propName +
describeExpandedElement(serverComponentName.type, serverComponentName.props,
removed(indent));
    return skipToNode + debugInfo + propName;
  }
  function describeDiff(rootNode) {
    try {
      return "\n\n" + describeNode(rootNode, 0);
    } catch (x) {
      return "";
    }
  }
  function describeAncestors(ancestor, child, props) {
    for (var fiber = child, node = null, distanceFromLeaf = 0; fiber;) fiber === ancestor &&
(distanceFromLeaf = 0), node = {
      fiber: fiber,
      children: null !== node ? [node] : [],
      serverProps: fiber === child ? props : fiber === ancestor ? null : void 0,
      serverTail: [],
      distanceFromLeaf: distanceFromLeaf
    }, distanceFromLeaf++, fiber = fiber.return;
    return null !== node ? describeDiff(node).replaceAll(/^[+-]/gm, ">") : "";
  }
  function updatedAncestorInfoDev(oldInfo, tag) {
    oldInfo = assign({}, oldInfo || emptyAncestorInfoDev);
    var info = {
      tag: tag
    };
    -1 !== inScopeTags.indexOf(tag) && (oldInfo.aTagInScope = null, oldInfo.buttonTagInScope =
null, oldInfo.nobrTagInScope = null);
    -1 !== buttonScopeTags.indexOf(tag) && (oldInfo.pTagInButtonScope = null);
    -1 !== specialTags.indexOf(tag) && "address" !== tag && "div" !== tag && "p" !== tag &&
(oldInfo.listItemTagAutoclosing = null, oldInfo.dlItemTagAutoclosing = null);
    oldInfo.current = info;
    "form" === tag && (oldInfo.formTag = info);
    "a" === tag && (oldInfo.aTagInScope = info);
    "button" === tag && (oldInfo.buttonTagInScope = info);
    "nobr" === tag && (oldInfo.nobrTagInScope = info);
    "p" === tag && (oldInfo.pTagInButtonScope = info);
    "li" === tag && (oldInfo.listItemTagAutoclosing = info);
```

```
    if ("dd" === tag || "dt" === tag) oldInfo.dlItemTagAutoclosing = info;
    "#document" === tag || "html" === tag ? oldInfo.containerTagInScope = null :
oldInfo.containerTagInScope || (oldInfo.containerTagInScope = info);
    return oldInfo;
  }
  function isTagValidWithParent(tag, parentTag) {
    switch (parentTag) {
      case "select":
        return "hr" === tag || "option" === tag || "optgroup" === tag || "#text" === tag;
      case "optgroup":
        return "option" === tag || "#text" === tag;
      case "option":
        return "#text" === tag;
      case "tr":
        return "th" === tag || "td" === tag || "style" === tag || "script" === tag || "template" === tag;
      case "tbody":
      case "thead":
      case "tfoot":
        return "tr" === tag || "style" === tag || "script" === tag || "template" === tag;
      case "colgroup":
        return "col" === tag || "template" === tag;
      case "table":
        return "caption" === tag || "colgroup" === tag || "tbody" === tag || "tfoot" === tag || "thead" ===
tag || "style" === tag || "script" === tag || "template" === tag;
      case "head":
        return "base" === tag || "basefont" === tag || "bgsound" === tag || "link" === tag || "meta" === tag
|| "title" === tag || "noscript" === tag || "noframes" === tag || "style" === tag || "script" === tag ||
"template" === tag;
      case "html":
        return "head" === tag || "body" === tag || "frameset" === tag;
      case "frameset":
        return "frame" === tag;
      case "#document":
        return "html" === tag;
    }
    switch (tag) {
      case "h1":
      case "h2":
      case "h3":
      case "h4":
      case "h5":
      case "h6":
        return "h1" !== parentTag && "h2" !== parentTag && "h3" !== parentTag && "h4" !==
parentTag && "h5" !== parentTag && "h6" !== parentTag;
      case "rp":
      case "rt":
        return -1 === impliedEndTags.indexOf(parentTag);
      case "body":
      case "caption":
```

```
    case "col":
    case "colgroup":
    case "frameset":
    case "frame":
    case "head":
    case "html":
    case "tbody":
    case "td":
    case "tfoot":
    case "th":
    case "thead":
    case "tr":
      return null == parentTag;
  }
  return !0;
}
function findInvalidAncestorForTag(tag, ancestorInfo) {
  switch (tag) {
    case "address":
    case "article":
    case "aside":
    case "blockquote":
    case "center":
    case "details":
    case "dialog":
    case "dir":
    case "div":
    case "dl":
    case "fieldset":
    case "figcaption":
    case "figure":
    case "footer":
    case "header":
    case "hgroup":
    case "main":
    case "menu":
    case "nav":
    case "ol":
    case "p":
    case "section":
    case "summary":
    case "ul":
    case "pre":
    case "listing":
    case "table":
    case "hr":
    case "xmp":
    case "h1":
    case "h2":
```

```
      case "h3":
      case "h4":
      case "h5":
      case "h6":
        return ancestorInfo.pTagInButtonScope;
      case "form":
        return ancestorInfo.formTag || ancestorInfo.pTagInButtonScope;
      case "li":
        return ancestorInfo.listItemTagAutoclosing;
      case "dd":
      case "dt":
        return ancestorInfo.dlItemTagAutoclosing;
      case "button":
        return ancestorInfo.buttonTagInScope;

      case "a":
        return ancestorInfo.aTagInScope;
      case "nobr":
        return ancestorInfo.nobrTagInScope;
    }
    return null;
  }
  function findAncestor(parent, tagName) {
    for (; parent;) {
      switch (parent.tag) {
        case 5:
        case 26:
        case 27:
          if (parent.type === tagName) return parent;
      }
      parent = parent.return;
    }
    return null;
  }
  function validateDOMNesting(childTag, ancestorInfo) {
    ancestorInfo = ancestorInfo || emptyAncestorInfoDev;
    var parentInfo = ancestorInfo.current;
    ancestorInfo = (parentInfo = isTagValidWithParent(childTag, parentInfo && parentInfo.tag) ? null :
parentInfo) ? null : findInvalidAncestorForTag(childTag, ancestorInfo);
    ancestorInfo = parentInfo || ancestorInfo;
    if (!ancestorInfo) return !0;
    ancestorInfo = ancestorInfo.tag;
    var warnKey = String(!!parentInfo) + "|" + childTag + "|" + ancestorInfo;
    if (didWarn[warnKey]) return !1;
    didWarn[warnKey] = !0;
    var ancestor = (warnKey = current) ? findAncestor(warnKey.return, ancestorInfo) : null;
    warnKey = null !== warnKey && null !== ancestor ? describeAncestors(ancestor, warnKey, null) :
"";
    ancestor = "<" + childTag + ">";
```

```
    parentInfo ? (parentInfo = "", "table" === ancestorInfo && "tr" === childTag && (parentInfo += "
Add a <tbody>, <thead> or <tfoot> to your code to match the DOM tree generated by the browser."),
console.error("In HTML, %s cannot be a child of <%s>.%s\nThis will cause a hydration error.%s",
ancestor, ancestorInfo, parentInfo, warnKey)) : console.error("In HTML, %s cannot be a descendant of
<%s>.\nThis will cause a hydration error.%s", ancestor, ancestorInfo, warnKey);
    return !1;
  }
  function validateTextNesting(childText, parentTag) {
    if (isTagValidWithParent("#text", parentTag)) return !0;
    var warnKey = "#text|" + parentTag;
    if (didWarn[warnKey]) return !1;
    didWarn[warnKey] = !0;
    var ancestor = (warnKey = current) ? findAncestor(warnKey, parentTag) : null;
    warnKey = null !== warnKey && null !== ancestor ? describeAncestors(ancestor, warnKey, 6 !==
warnKey.tag ? {
      children: null
    } : null) : "";
    /\S/.test(childText) ? console.error("In HTML, text nodes cannot be a child of <%s>.\nThis will
cause a hydration error.%s", parentTag, warnKey) : console.error("In HTML, whitespace text nodes
cannot be a child of <%s>. Make sure you don't have any extra whitespace between tags on each line of
your source code.\nThis will cause a hydration error.%s", parentTag, warnKey);
    return !1;
  }
  function setTextContent(node, text) {
    if (text) {
      var firstChild = node.firstChild;
      if (firstChild && firstChild === node.lastChild && 3 === firstChild.nodeType) {
        firstChild.nodeValue = text;
        return;
      }
    }
    node.textContent = text;
  }
  function camelize(string) {
    return string.replace(hyphenPattern, function (_, character) {
      return character.toUpperCase();
    });
  }
  function setValueForStyle(style, styleName, value) {
    var isCustomProperty = 0 === styleName.indexOf("--");
    isCustomProperty || (-1 < styleName.indexOf("-") ?
warnedStyleNames.hasOwnProperty(styleName) && warnedStyleNames[styleName] ||
(warnedStyleNames[styleName] = !0, console.error("Unsupported style property %s. Did you mean
%s?", styleName, camelize(styleName.replace(msPattern, "ms-")))) :
badVendoredStyleNamePattern.test(styleName) ? warnedStyleNames.hasOwnProperty(styleName)
&& warnedStyleNames[styleName] || (warnedStyleNames[styleName] = !0,
console.error("Unsupported vendor-prefixed style property %s. Did you mean %s?", styleName,
styleName.charAt(0).toUpperCase() + styleName.slice(1))) : !
badStyleValueWithSemicolonPattern.test(value) || warnedStyleValues.hasOwnProperty(value) &&
```

```
warnedStyleValues[value] || (warnedStyleValues[value] = !0, console.error('Style property values shouldn\'t contain a semicolon. Try "%s: %s" instead.', styleName, value.replace(badStyleValueWithSemicolonPattern, ""))), "number" === typeof value && (isNaN(value) ? warnedForNaNValue || (warnedForNaNValue = !0, console.error("`NaN` is an invalid value for the `%s` css style property.", styleName)) : isFinite(value) || warnedForInfinityValue || (warnedForInfinityValue = !0, console.error("`Infinity` is an invalid value for the `%s` css style property.", styleName))));
    null == value || "boolean" === typeof value || "" === value ? isCustomProperty ? style.setProperty(styleName, "") : "float" === styleName ? style.cssFloat = "" : style[styleName] = "" : isCustomProperty ? style.setProperty(styleName, value) : "number" !== typeof value || 0 === value || unitlessNumbers.has(styleName) ? "float" === styleName ? style.cssFloat = value : (checkCSSPropertyStringCoercion(value, styleName), style[styleName] = ("" + value).trim()) : style[styleName] = value + "px";
  }
  function setValueForStyles(node, styles, prevStyles) {
    if (null != styles && "object" !== typeof styles) throw Error("The `style` prop expects a mapping from style properties to values, not a string. For example, style={{marginRight: spacing + 'em'}} when using JSX.");
    styles && Object.freeze(styles);
    node = node.style;
    if (null != prevStyles) {
      if (styles) {
        var expandedUpdates = {};
        if (prevStyles) for (var key in prevStyles) if (prevStyles.hasOwnProperty(key) && !styles.hasOwnProperty(key)) for (var longhands = shorthandToLonghand[key] || [key], i = 0; i < longhands.length; i++) expandedUpdates[longhands[i]] = key;
        for (var _key in styles) if (styles.hasOwnProperty(_key) && (!prevStyles || prevStyles[_key] !== styles[_key])) for (key = shorthandToLonghand[_key] || [_key], longhands = 0; longhands < key.length; longhands++) expandedUpdates[key[longhands]] = _key;
        _key = {};
        for (var key$jscomp$0 in styles) for (key = shorthandToLonghand[key$jscomp$0] || [key$jscomp$0], longhands = 0; longhands < key.length; longhands++) _key[key[longhands]] = key$jscomp$0;
        key$jscomp$0 = {};
        for (var _key2 in expandedUpdates) if (key = expandedUpdates[_key2], (longhands = _key[_key2]) && key !== longhands && (i = key + "," + longhands, !key$jscomp$0[i])) {
          key$jscomp$0[i] = !0;
          i = console;
          var value = styles[key];
          i.error.call(i, "%s a style property during rerender (%s) when a conflicting property is set (%s) can lead to styling bugs. To avoid this, don't mix shorthand and non-shorthand properties for the same value; instead, replace the shorthand with separate values.", null == value || "boolean" === typeof value || "" === value ? "Removing" : "Updating", key, longhands);
        }
      }
      for (var styleName in prevStyles) !prevStyles.hasOwnProperty(styleName) || null != styles && styles.hasOwnProperty(styleName) || (0 === styleName.indexOf("--") ? node.setProperty(styleName, "") : "float" === styleName ? node.cssFloat = "" : node[styleName] = "");
      for (var _styleName in styles) _key2 = styles[_styleName], styles.hasOwnProperty(_styleName)
```

```
&& prevStyles[_styleName] !== _key2 && setValueForStyle(node, _styleName, _key2);
    } else for (expandedUpdates in styles) styles.hasOwnProperty(expandedUpdates) &&
setValueForStyle(node, expandedUpdates, styles[expandedUpdates]);
  }
  function isCustomElement(tagName) {
    if (-1 === tagName.indexOf("-")) return !1;
    switch (tagName) {
      case "annotation-xml":
      case "color-profile":
      case "font-face":
      case "font-face-src":
      case "font-face-uri":
      case "font-face-format":
      case "font-face-name":
      case "missing-glyph":
        return !1;
      default:
        return !0;
    }
  }
  function getAttributeAlias(name) {
    return aliases.get(name) || name;
  }
  function validateProperty$1(tagName, name) {
    if (hasOwnProperty.call(warnedProperties$1, name) && warnedProperties$1[name]) return !0;
    if (rARIACamel$1.test(name)) {
      tagName = "aria-" + name.slice(4).toLowerCase();
      tagName = ariaProperties.hasOwnProperty(tagName) ? tagName : null;
      if (null == tagName) return console.error("Invalid ARIA attribute `%s`. ARIA attributes follow the
pattern aria-* and must be lowercase.", name), warnedProperties$1[name] = !0;
      if (name !== tagName) return console.error("Invalid ARIA attribute `%s`. Did you mean `%s`?",
name, tagName), warnedProperties$1[name] = !0;
    }
    if (rARIA$1.test(name)) {
      tagName = name.toLowerCase();
      tagName = ariaProperties.hasOwnProperty(tagName) ? tagName : null;
      if (null == tagName) return warnedProperties$1[name] = !0, !1;
      name !== tagName && (console.error("Unknown ARIA attribute `%s`. Did you mean `%s`?",
name, tagName), warnedProperties$1[name] = !0);
    }
    return !0;
  }
  function validateProperties$2(type, props) {
    var invalidProps = [],
      key;
    for (key in props) validateProperty$1(type, key) || invalidProps.push(key);
    props = invalidProps.map(function (prop) {
      return "`" + prop + "`";
    }).join(", ");
```

```
    1 === invalidProps.length ? console.error("Invalid aria prop %s on <%s> tag. For details, see
https://react.dev/link/invalid-aria-props", props, type) : 1 < invalidProps.length &&
console.error("Invalid aria props %s on <%s> tag. For details, see https://react.dev/link/invalid-aria-
props", props, type);
  }
  function validateProperty(tagName, name, value, eventRegistry) {
    if (hasOwnProperty.call(warnedProperties, name) && warnedProperties[name]) return !0;
    var lowerCasedName = name.toLowerCase();
    if ("onfocusin" === lowerCasedName || "onfocusout" === lowerCasedName) return
console.error("React uses onFocus and onBlur instead of onFocusIn and onFocusOut. All React events
are normalized to bubble, so onFocusIn and onFocusOut are not needed/supported by React."),
warnedProperties[name] = !0;
    if ("function"
 === typeof value && ("form" === tagName && "action" === name || "input" === tagName &&
"formAction" === name || "button" === tagName && "formAction" === name)) return !0;
    if (null != eventRegistry) {
      tagName = eventRegistry.possibleRegistrationNames;
      if (eventRegistry.registrationNameDependencies.hasOwnProperty(name)) return !0;
      eventRegistry = tagName.hasOwnProperty(lowerCasedName) ? tagName[lowerCasedName] : null;
      if (null != eventRegistry) return console.error("Invalid event handler property `%s`. Did you mean `
%s`?", name, eventRegistry), warnedProperties[name] = !0;
      if (EVENT_NAME_REGEX.test(name)) return console.error("Unknown event handler property `
%s`. It will be ignored.", name), warnedProperties[name] = !0;
    } else if (EVENT_NAME_REGEX.test(name)) return
INVALID_EVENT_NAME_REGEX.test(name) && console.error("Invalid event handler property `
%s`. React events use the camelCase naming convention, for example `onClick`.", name),
warnedProperties[name] = !0;
    if (rARIA.test(name) || rARIACamel.test(name)) return !0;
    if ("innerhtml" === lowerCasedName) return console.error("Directly setting property `innerHTML`
is not permitted. For more information, lookup documentation on `dangerouslySetInnerHTML`."),
warnedProperties[name] = !0;
    if ("aria" === lowerCasedName) return console.error("The `aria` attribute is reserved for future use
in React. Pass individual `aria-` attributes instead."), warnedProperties[name] = !0;
    if ("is" === lowerCasedName && null !== value && void 0 !== value && "string" !== typeof
value) return console.error("Received a `%s` for a string attribute `is`. If this is expected, cast the value
to a string.", typeof value), warnedProperties[name] = !0;
    if ("number" === typeof value && isNaN(value)) return console.error("Received NaN for the `%s`
attribute. If this is expected, cast the value to a string.", name), warnedProperties[name] = !0;
    if (possibleStandardNames.hasOwnProperty(lowerCasedName)) {
      if (lowerCasedName = possibleStandardNames[lowerCasedName], lowerCasedName !== name)
return console.error("Invalid DOM property `%s`. Did you mean `%s`?", name, lowerCasedName),
warnedProperties[name] = !0;
    } else if (name !== lowerCasedName) return console.error("React does not recognize the `%s` prop
on a DOM element. If you intentionally want it to appear in the DOM as a custom attribute, spell it as
lowercase `%s` instead. If you accidentally passed it from a parent component, remove it from the
DOM element.", name, lowerCasedName), warnedProperties[name] = !0;
    switch (name) {
      case "dangerouslySetInnerHTML":
      case "children":
```

```
  case "style":
  case "suppressContentEditableWarning":
  case "suppressHydrationWarning":
  case "defaultValue":
  case "defaultChecked":
  case "innerHTML":
  case "ref":
    return !0;
  case "innerText":
  case "textContent":
    return !0;
}
switch (typeof value) {
  case "boolean":
    switch (name) {
      case "autoFocus":
      case "checked":
      case "multiple":
      case "muted":
      case "selected":
      case "contentEditable":
      case "spellCheck":
      case "draggable":
      case "value":
      case "autoReverse":
      case "externalResourcesRequired":
      case "focusable":
      case "preserveAlpha":
      case "allowFullScreen":
      case "async":
      case "autoPlay":
      case "controls":
      case "default":
      case "defer":
      case "disabled":
      case "disablePictureInPicture":
      case "disableRemotePlayback":
      case "formNoValidate":
      case "hidden":
      case "loop":
      case "noModule":
      case "noValidate":
      case "open":
      case "playsInline":
      case "readOnly":
      case "required":
      case "reversed":
      case "scoped":
      case "seamless":
```

```
        case "itemScope":
        case "capture":
        case "download":
        case "inert":
          return !0;
        default:
          lowerCasedName = name.toLowerCase().slice(0, 5);
          if ("data-" === lowerCasedName || "aria-" === lowerCasedName) return !0;
          value ? console.error('Received `%s` for a non-boolean attribute `%s`.\n\nIf you want to write it to the DOM, pass a string instead: %s="%s" or %s={value.toString()}.', value, name, name, value, name) : console.error('Received `%s` for a non-boolean attribute `%s`.\n\nIf you want to write it to the DOM, pass a string instead: %s="%s" or %s={value.toString()}.\n\nIf you used to conditionally omit it with %s={condition && value}, pass %s={condition ? value : undefined} instead.', value, name, name, value, name, name, name);
          return warnedProperties[name] = !0;
      }
    case "function":
    case "symbol":
      return warnedProperties[name] = !0, !1;
    case "string":
      if ("false" === value || "true" === value) {
        switch (name) {
          case "checked":
          case "selected":
          case "multiple":
          case "muted":
          case "allowFullScreen":
          case "async":
          case "autoPlay":
          case "controls":
          case "default":
          case "defer":
          case "disabled":
          case "disablePictureInPicture":
          case "disableRemotePlayback":
          case "formNoValidate":
          case "hidden":
          case "loop":
          case "noModule":
          case "noValidate":
          case "open":
          case "playsInline":
          case "readOnly":
          case "required":
          case "reversed":
          case "scoped":
          case "seamless":
          case "itemScope":
          case "inert":
```

```
            break;
          default:
            return !0;
        }
        console.error("Received the string `%s` for the boolean attribute `%s`. %s Did you mean
%s={%s}?", value, name, "false" === value ? "The browser will interpret it as a truthy value." :
'Although this works, it will not work as expected if you pass the string "false".', name, value);
        warnedProperties[name] = !0;
      }
    }
    return !0;
  }
  function warnUnknownProperties(type, props, eventRegistry) {
    var unknownProps = [],
      key;
    for (key in props) validateProperty(type, key, props[key], eventRegistry) || unknownProps.push(key);
    props = unknownProps.map(function (prop) {
      return "`" + prop + "`";
    }).join(", ");
    1 === unknownProps.length ? console.error("Invalid value for prop %s on <%s> tag. Either remove
it from the element, or pass a string or number value to keep it in the DOM. For details, see
https://react.dev/link/attribute-behavior ", props, type) : 1 < unknownProps.length &&
console.error("Invalid values for props %s on <%s> tag. Either remove them from the element, or pass
a string or number value to keep them in the DOM. For details, see https://react.dev/link/attribute-
behavior ", props, type);
  }
  function sanitizeURL(url) {
    return isJavaScriptProtocol.test("" + url) ? "javascript:throw new Error('React has blocked a
javascript: URL as a security precaution.')" : url;
  }
  function getEventTarget(nativeEvent) {
    nativeEvent = nativeEvent.target || nativeEvent.srcElement || window;
    nativeEvent.correspondingUseElement && (nativeEvent = nativeEvent.correspondingUseElement);
    return 3 === nativeEvent.nodeType ? nativeEvent.parentNode : nativeEvent;
  }
  function restoreStateOfTarget(target) {
    var internalInstance = getInstanceFromNode(target);
    if (internalInstance && (target = internalInstance.stateNode)) {
      var props = target[internalPropsKey] || null;
      a: switch (target = internalInstance.stateNode, internalInstance.type) {
        case "input":
          updateInput(target, props.value, props.defaultValue, props.defaultValue, props.checked,
props.defaultChecked, props.type, props.name);
          internalInstance = props.name;
          if ("radio" === props.type && null != internalInstance) {
            for (props = target; props.parentNode;) props = props.parentNode;
            checkAttributeStringCoercion(internalInstance, "name");
            props = props.querySelectorAll('input[name="' +
escapeSelectorAttributeValueInsideDoubleQuotes("" + internalInstance) + '"][type="radio"]');
```

```
          for (internalInstance = 0; internalInstance < props.length; internalInstance++) {
            var otherNode = props[internalInstance];
            if (otherNode !== target && otherNode.form === target.form) {
              var otherProps = otherNode[internalPropsKey] || null;
              if (!otherProps) throw Error("ReactDOMInput: Mixing React and non-React radio inputs with the same `name` is not supported.");
              updateInput(otherNode, otherProps.value, otherProps.defaultValue, otherProps.defaultValue, otherProps.checked, otherProps.defaultChecked, otherProps.type, otherProps.name);
            }
          }
          for (internalInstance = 0; internalInstance < props.length; internalInstance++) otherNode = props[internalInstance], otherNode.form === target.form && updateValueIfChanged(otherNode);
        }
        break a;
      case "textarea":
        updateTextarea(target, props.value, props.defaultValue);
        break a;
      case "select":
        internalInstance = props.value, null != internalInstance && updateOptions(target, !! props.multiple, internalInstance, !1);
    }
  }
}
function batchedUpdates$1(fn, a, b) {
  if (isInsideEventHandler) return fn(a, b);
  isInsideEventHandler = !0;
  try {
    var JSCompiler_inline_result = fn(a);
    return JSCompiler_inline_result;

  } finally {
    if (isInsideEventHandler = !1, null !== restoreTarget || null !== restoreQueue) if (flushSyncWork$1(), restoreTarget && (a = restoreTarget, fn = restoreQueue, restoreQueue = restoreTarget = null, restoreStateOfTarget(a), fn)) for (a = 0; a < fn.length; a++) restoreStateOfTarget(fn[a]);
  }
}
function getListener(inst, registrationName) {
  var stateNode = inst.stateNode;
  if (null === stateNode) return null;
  var props = stateNode[internalPropsKey] || null;
  if (null === props) return null;
  stateNode = props[registrationName];
  a: switch (registrationName) {
    case "onClick":
    case "onClickCapture":
    case "onDoubleClick":
    case "onDoubleClickCapture":
    case "onMouseDown":
```

```
      case "onMouseDownCapture":
      case "onMouseMove":
      case "onMouseMoveCapture":
      case "onMouseUp":
      case "onMouseUpCapture":
      case "onMouseEnter":
        (props = !props.disabled) || (inst = inst.type, props = !("button" === inst || "input" === inst ||
"select" === inst || "textarea" === inst));
        inst = !props;
        break a;
      default:
        inst = !1;
    }
    if (inst) return null;
    if (stateNode && "function" !== typeof stateNode) throw Error("Expected `" + registrationName +
"` listener to be a function, instead got a value of `" + typeof stateNode + "` type.");
    return stateNode;
  }
  function getData() {
    if (fallbackText) return fallbackText;
    var start,
      startValue = startText,
      startLength = startValue.length,
      end,
      endValue = "value" in root ? root.value : root.textContent,
      endLength = endValue.length;
    for (start = 0; start < startLength && startValue[start] === endValue[start]; start++);
    var minEnd = startLength - start;
    for (end = 1; end <= minEnd && startValue[startLength - end] === endValue[endLength - end];
end++);
    return fallbackText = endValue.slice(start, 1 < end ? 1 - end : void 0);
  }
  function getEventCharCode(nativeEvent) {
    var keyCode = nativeEvent.keyCode;
    "charCode" in nativeEvent ? (nativeEvent = nativeEvent.charCode, 0 === nativeEvent && 13 ===
keyCode && (nativeEvent = 13)) : nativeEvent = keyCode;
    10 === nativeEvent && (nativeEvent = 13);
    return 32 <= nativeEvent || 13 === nativeEvent ? nativeEvent : 0;
  }
  function functionThatReturnsTrue() {
    return !0;
  }
  function functionThatReturnsFalse() {
    return !1;
  }
  function createSyntheticEvent(Interface) {
    function SyntheticBaseEvent(reactName, reactEventType, targetInst, nativeEvent,
nativeEventTarget) {
      this._reactName = reactName;
```

```
      this._targetInst = targetInst;
      this.type = reactEventType;
      this.nativeEvent = nativeEvent;
      this.target = nativeEventTarget;
      this.currentTarget = null;
      for (var propName in Interface) Interface.hasOwnProperty(propName) && (reactName =
Interface[propName], this[propName] = reactName ? reactName(nativeEvent) :
nativeEvent[propName]);
      this.isDefaultPrevented = (null != nativeEvent.defaultPrevented ? nativeEvent.defaultPrevented : !1
=== nativeEvent.returnValue) ? functionThatReturnsTrue : functionThatReturnsFalse;
      this.isPropagationStopped = functionThatReturnsFalse;
      return this;
    }
    assign(SyntheticBaseEvent.prototype, {
      preventDefault: function () {
        this.defaultPrevented = !0;
        var event = this.nativeEvent;
        event && (event.preventDefault ? event.preventDefault() : "unknown" !== typeof
event.returnValue && (event.returnValue = !1), this.isDefaultPrevented = functionThatReturnsTrue);
      },
      stopPropagation: function () {
        var event = this.nativeEvent;
        event && (event.stopPropagation ? event.stopPropagation() : "unknown" !== typeof
event.cancelBubble && (event.cancelBubble = !0), this.isPropagationStopped =
functionThatReturnsTrue);
      },
      persist: function () {},
      isPersistent: functionThatReturnsTrue
    });
    return SyntheticBaseEvent;
  }
  function modifierStateGetter(keyArg) {
    var nativeEvent = this.nativeEvent;
    return nativeEvent.getModifierState ? nativeEvent.getModifierState(keyArg) : (keyArg =
modifierKeyToProp[keyArg]) ? !!nativeEvent[keyArg] : !1;
  }
  function getEventModifierState() {
    return modifierStateGetter;
  }
  function isFallbackCompositionEnd(domEventName, nativeEvent) {
    switch (domEventName) {
      case "keyup":
        return -1 !== END_KEYCODES.indexOf(nativeEvent.keyCode);
      case "keydown":
        return nativeEvent.keyCode !== START_KEYCODE;
      case "keypress":
      case "mousedown":
      case "focusout":
        return !0;
```

```
      default:
        return !1;
    }
  }
  function getDataFromCustomEvent(nativeEvent) {
    nativeEvent = nativeEvent.detail;
    return "object" === typeof nativeEvent && "data" in nativeEvent ? nativeEvent.data : null;
  }
  function getNativeBeforeInputChars(domEventName, nativeEvent) {
    switch (domEventName) {
      case "compositionend":
        return getDataFromCustomEvent(nativeEvent);
      case "keypress":
        if (nativeEvent.which !== SPACEBAR_CODE) return null;
        hasSpaceKeypress = !0;
        return SPACEBAR_CHAR;
      case "textInput":
        return domEventName = nativeEvent.data, domEventName === SPACEBAR_CHAR &&
hasSpaceKeypress ? null : domEventName;
      default:
        return null;
    }
  }
  function getFallbackBeforeInputChars(domEventName, nativeEvent) {
    if (isComposing) return "compositionend" === domEventName || !canUseCompositionEvent &&
isFallbackCompositionEnd(domEventName, nativeEvent) ? (domEventName = getData(), fallbackText
= startText = root = null, isComposing = !1, domEventName) : null;
    switch (domEventName) {
      case "paste":
        return null;
      case "keypress":
        if (!(nativeEvent.ctrlKey || nativeEvent.altKey || nativeEvent.metaKey) || nativeEvent.ctrlKey &&
nativeEvent.altKey) {
          if (nativeEvent.char && 1 < nativeEvent.char.length) return nativeEvent.char;
          if (nativeEvent.which) return String.fromCharCode(nativeEvent.which);
        }
        return null;
      case "compositionend":
        return useFallbackCompositionData && "ko" !== nativeEvent.locale ? null : nativeEvent.data;
      default:
        return null;
    }
  }
  function isTextInputElement(elem) {
    var nodeName = elem && elem.nodeName && elem.nodeName.toLowerCase();
    return "input" === nodeName ? !!supportedInputTypes[elem.type] : "textarea" === nodeName ? !
0 : !1;
  }
  function isEventSupported(eventNameSuffix) {
```

```
    if (!canUseDOM) return !1;
    eventNameSuffix = "on" + eventNameSuffix;
    var isSupported = eventNameSuffix in document;
    isSupported || (isSupported = document.createElement("div"),
isSupported.setAttribute(eventNameSuffix, "return;"), isSupported = "function" === typeof
isSupported[eventNameSuffix]);
    return isSupported;
  }
  function createAndAccumulateChangeEvent(dispatchQueue, inst, nativeEvent, target) {
    restoreTarget ? restoreQueue ? restoreQueue.push(target) : restoreQueue = [target] : restoreTarget =
target;
    inst = accumulateTwoPhaseListeners(inst, "onChange");
    0 < inst.length && (nativeEvent = new SyntheticEvent("onChange", "change", null, nativeEvent,
target), dispatchQueue.push({
      event: nativeEvent,
      listeners: inst
    }));
  }
  function runEventInBatch(dispatchQueue) {
    processDispatchQueue(dispatchQueue, 0);
  }
  function getInstIfValueChanged(targetInst) {
    var targetNode = getNodeFromInstance(targetInst);
    if (updateValueIfChanged(targetNode)) return targetInst;
  }
  function getTargetInstForChangeEvent(domEventName, targetInst) {
    if ("change" === domEventName) return targetInst;
  }
  function stopWatchingForValueChange() {
    activeElement$1 && (activeElement$1.detachEvent("onpropertychange", handlePropertyChange),
activeElementInst$1 = activeElement$1 = null);
  }
  function handlePropertyChange(nativeEvent) {
    if ("value" === nativeEvent.propertyName && getInstIfValueChanged(activeElementInst$1)) {
      var dispatchQueue = [];
      createAndAccumulateChangeEvent(dispatchQueue, activeElementInst$1, nativeEvent,
getEventTarget(nativeEvent));
      batchedUpdates$1(runEventInBatch, dispatchQueue);
    }
  }
  function handleEventsForInputEventPolyfill(domEventName, target, targetInst) {
    "focusin" === domEventName ? (stopWatchingForValueChange(), activeElement$1 = target,
activeElementInst$1 = targetInst, activeElement$1.attachEvent("onpropertychange",
handlePropertyChange)) : "focusout" === domEventName && stopWatchingForValueChange();
  }
  function getTargetInstForInputEventPolyfill(domEventName) {
    if ("selectionchange" === domEventName || "keyup" === domEventName || "keydown" ===
domEventName) return getInstIfValueChanged(activeElementInst$1);
  }
```

```
  function getTargetInstForClickEvent(domEventName, targetInst) {
    if ("click" === domEventName) return getInstIfValueChanged(targetInst);
  }
  function getTargetInstForInputOrChangeEvent(domEventName, targetInst) {
    if ("input" === domEventName || "change" === domEventName) return
getInstIfValueChanged(targetInst);
  }
  function is(x, y) {
    return x === y && (0 !== x || 1 / x === 1 / y) || x !== x && y !== y;
  }
  function shallowEqual(objA, objB) {
    if (objectIs(objA, objB)) return !0;
    if ("object" !== typeof objA || null === objA || "object" !== typeof objB || null === objB) return !1;
    var keysA = Object.keys(objA),
      keysB = Object.keys(objB);
    if (keysA.length !== keysB.length) return !1;
    for (keysB = 0; keysB < keysA.length; keysB++) {
      var currentKey = keysA[keysB];
      if (!hasOwnProperty.call(objB, currentKey) || !objectIs(objA[currentKey], objB[currentKey]))
return !1;
    }
    return !0;
  }
  function getLeafNode(node) {
    for (; node && node.firstChild;) node = node.firstChild;

    return node;
  }
  function getNodeForCharacterOffset(root, offset) {
    var node = getLeafNode(root);
    root = 0;
    for (var nodeEnd; node;) {
      if (3 === node.nodeType) {
        nodeEnd = root + node.textContent.length;
        if (root <= offset && nodeEnd >= offset) return {
          node: node,
          offset: offset - root
        };
        root = nodeEnd;
      }
      a: {
        for (; node;) {
          if (node.nextSibling) {
            node = node.nextSibling;
            break a;
          }
          node = node.parentNode;
        }
        node = void 0;
```

```
      }
      node = getLeafNode(node);
    }
  }
  function containsNode(outerNode, innerNode) {
    return outerNode && innerNode ? outerNode === innerNode ? !0 : outerNode && 3 ===
outerNode.nodeType ? !1 : innerNode && 3 === innerNode.nodeType ? containsNode(outerNode,
innerNode.parentNode) : "contains" in outerNode ? outerNode.contains(innerNode) :
outerNode.compareDocumentPosition ? !!(outerNode.compareDocumentPosition(innerNode) & 16) : !
1 : !1;
  }
  function getActiveElementDeep(containerInfo) {
    containerInfo = null != containerInfo && null != containerInfo.ownerDocument && null !=
containerInfo.ownerDocument.defaultView ? containerInfo.ownerDocument.defaultView : window;
    for (var element = getActiveElement(containerInfo.document); element instanceof
containerInfo.HTMLIFrameElement;) {
      try {
        var JSCompiler_inline_result = "string" === typeof element.contentWindow.location.href;
      } catch (err) {
        JSCompiler_inline_result = !1;
      }
      if (JSCompiler_inline_result) containerInfo = element.contentWindow;else break;
      element = getActiveElement(containerInfo.document);
    }
    return element;
  }
  function hasSelectionCapabilities(elem) {
    var nodeName = elem && elem.nodeName && elem.nodeName.toLowerCase();
    return nodeName && ("input" === nodeName && ("text" === elem.type || "search" === elem.type
|| "tel" === elem.type || "url" === elem.type || "password" === elem.type) || "textarea" === nodeName ||
"true" === elem.contentEditable);
  }
  function restoreSelection(priorSelectionInformation, containerInfo) {
    var curFocusedElem = getActiveElementDeep(containerInfo);
    containerInfo = priorSelectionInformation.focusedElem;
    var priorSelectionRange = priorSelectionInformation.selectionRange;
    if (curFocusedElem !== containerInfo && containerInfo && containerInfo.ownerDocument &&
containsNode(containerInfo.ownerDocument.documentElement, containerInfo)) {
      if (null !== priorSelectionRange && hasSelectionCapabilities(containerInfo)) if
(priorSelectionInformation = priorSelectionRange.start, curFocusedElem = priorSelectionRange.end,
void 0 === curFocusedElem && (curFocusedElem = priorSelectionInformation), "selectionStart" in
containerInfo) containerInfo.selectionStart = priorSelectionInformation, containerInfo.selectionEnd =
Math.min(curFocusedElem, containerInfo.value.length);else if (curFocusedElem =
(priorSelectionInformation = containerInfo.ownerDocument || document) &&
priorSelectionInformation.defaultView || window, curFocusedElem.getSelection) {
        curFocusedElem = curFocusedElem.getSelection();
        var length = containerInfo.textContent.length,
          start = Math.min(priorSelectionRange.start, length);
        priorSelectionRange = void 0 === priorSelectionRange.end ? start :
```

```
Math.min(priorSelectionRange.end, length);
        !curFocusedElem.extend && start > priorSelectionRange && (length = priorSelectionRange,
priorSelectionRange = start, start = length);
        length = getNodeForCharacterOffset(containerInfo, start);
        var endMarker = getNodeForCharacterOffset(containerInfo, priorSelectionRange);
        length && endMarker && (1 !== curFocusedElem.rangeCount || curFocusedElem.anchorNode !
== length.node || curFocusedElem.anchorOffset !== length.offset || curFocusedElem.focusNode !==
endMarker.node || curFocusedElem.focusOffset !== endMarker.offset) && (priorSelectionInformation
= priorSelectionInformation.createRange(), priorSelectionInformation.setStart(length.node,
length.offset), curFocusedElem.removeAllRanges(), start > priorSelectionRange ?
(curFocusedElem.addRange(priorSelectionInformation), curFocusedElem.extend(endMarker.node,
endMarker.offset)) : (priorSelectionInformation.setEnd(endMarker.node, endMarker.offset),
curFocusedElem.addRange(priorSelectionInformation)));
      }
      priorSelectionInformation = [];
      for (curFocusedElem = containerInfo; curFocusedElem = curFocusedElem.parentNode;) 1 ===
curFocusedElem.nodeType && priorSelectionInformation.push({
        element: curFocusedElem,
        left: curFocusedElem.scrollLeft,
        top: curFocusedElem.scrollTop
      });
      "function" === typeof containerInfo.focus && containerInfo.focus();
      for (containerInfo = 0; containerInfo < priorSelectionInformation.length; containerInfo++)
curFocusedElem = priorSelectionInformation[containerInfo], curFocusedElem.element.scrollLeft =
curFocusedElem.left, curFocusedElem.element.scrollTop = curFocusedElem.top;
    }
  }
  function constructSelectEvent(dispatchQueue, nativeEvent, nativeEventTarget) {
    var doc = nativeEventTarget.window === nativeEventTarget ? nativeEventTarget.document : 9 ===
nativeEventTarget.nodeType ? nativeEventTarget : nativeEventTarget.ownerDocument;
    mouseDown || null == activeElement || activeElement !== getActiveElement(doc) || (doc =
activeElement, "selectionStart" in doc && hasSelectionCapabilities(doc) ? doc = {
      start: doc.selectionStart,
      end: doc.selectionEnd
    } : (doc = (doc.ownerDocument && doc.ownerDocument.defaultView || window).getSelection(),
doc = {
      anchorNode: doc.anchorNode,
      anchorOffset: doc.anchorOffset,
      focusNode: doc.focusNode,
      focusOffset: doc.focusOffset
    }), lastSelection && shallowEqual(lastSelection, doc) || (lastSelection = doc, doc =
accumulateTwoPhaseListeners(activeElementInst, "onSelect"), 0 < doc.length && (nativeEvent = new
SyntheticEvent("onSelect", "select", null, nativeEvent, nativeEventTarget), dispatchQueue.push({
      event: nativeEvent,
      listeners: doc
    }), nativeEvent.target = activeElement)));
  }
  function makePrefixMap(styleProp, eventName) {
    var prefixes = {};
```

```
    prefixes[styleProp.toLowerCase()] = eventName.toLowerCase();
    prefixes["Webkit" + styleProp] = "webkit" + eventName;
    prefixes["Moz" + styleProp] = "moz" + eventName;
    return prefixes;
  }
  function getVendorPrefixedEventName(eventName) {
    if (prefixedEventNames[eventName]) return prefixedEventNames[eventName];
    if (!vendorPrefixes[eventName]) return eventName;
    var prefixMap = vendorPrefixes[eventName],
      styleProp;
    for (styleProp in prefixMap) if (prefixMap.hasOwnProperty(styleProp) && styleProp in style) return
prefixedEventNames[eventName] = prefixMap[styleProp];
    return eventName;
  }
  function registerSimpleEvent(domEventName, reactName) {
    topLevelEventsToReactNames.set(domEventName, reactName);
    registerTwoPhaseEvent(reactName, [domEventName]);
  }
  function finishQueueingConcurrentUpdates() {
    for (var endIndex = concurrentQueuesIndex, i = concurrentlyUpdatedLanes =
concurrentQueuesIndex = 0; i < endIndex;) {
      var fiber = concurrentQueues[i];
      concurrentQueues[i++] = null;
      var queue = concurrentQueues[i];
      concurrentQueues[i++] = null;
      var update = concurrentQueues[i];
      concurrentQueues[i++] = null;
      var lane = concurrentQueues[i];
      concurrentQueues[i++] = null;
      if (null !== queue && null !== update) {
        var pending = queue.pending;
        null === pending ? update.next = update : (update.next = pending.next, pending.next = update);
        queue.pending = update;
      }
      0 !== lane && markUpdateLaneFromFiberToRoot(fiber, update, lane);
    }
  }
  function enqueueUpdate$1(fiber, queue, update, lane) {
    concurrentQueues[concurrentQueuesIndex++] = fiber;
    concurrentQueues[concurrentQueuesIndex++] = queue;
    concurrentQueues[concurrentQueuesIndex++] = update;
    concurrentQueues[concurrentQueuesIndex++] = lane;
    concurrentlyUpdatedLanes |= lane;
    fiber.lanes |= lane;
    fiber = fiber.alternate;
    null !== fiber && (fiber.lanes |= lane);
  }
  function enqueueConcurrentHookUpdate(fiber, queue, update, lane) {
    enqueueUpdate$1(fiber, queue, update, lane);
```

```
    return getRootForUpdatedFiber(fiber);
  }
  function enqueueConcurrentRenderForLane(fiber, lane) {
    enqueueUpdate$1(fiber, null, null, lane);
    return getRootForUpdatedFiber(fiber);
  }
  function markUpdateLaneFromFiberToRoot(sourceFiber, update, lane) {
    sourceFiber.lanes |= lane;
    var alternate = sourceFiber.alternate;
    null !== alternate && (alternate.lanes |= lane);
    for (var isHidden = !1, parent = sourceFiber.return; null !== parent;) parent.childLanes |= lane,
alternate = parent.alternate, null !== alternate && (alternate.childLanes |= lane), 22 === parent.tag &&
(sourceFiber = parent.stateNode, null === sourceFiber || sourceFiber._visibility & OffscreenVisible ||
(isHidden = !0)), sourceFiber = parent, parent = parent.return;
    isHidden && null !== update && 3 === sourceFiber.tag && (parent = sourceFiber.stateNode,
isHidden = 31 - clz32(lane), parent = parent.hiddenUpdates, sourceFiber = parent[isHidden], null ===
sourceFiber ? parent[isHidden] = [update] : sourceFiber.push(update), update.lane = lane | 536870912);
  }
  function getRootForUpdatedFiber(sourceFiber) {
    if (nestedUpdateCount > NESTED_UPDATE_LIMIT) throw nestedPassiveUpdateCount =
nestedUpdateCount = 0, rootWithPassiveNestedUpdates = rootWithNestedUpdates = null,
Error("Maximum update depth exceeded. This can happen when a component repeatedly calls setState
inside componentWillUpdate or componentDidUpdate. React limits the number of nested updates
 to prevent infinite loops.");
    nestedPassiveUpdateCount > NESTED_PASSIVE_UPDATE_LIMIT &&
(nestedPassiveUpdateCount = 0, rootWithPassiveNestedUpdates = null, console.error("Maximum
update depth exceeded. This can happen when a component calls setState inside useEffect, but
useEffect either doesn't have a dependency array, or one of the dependencies changes on every
render."));
    null === sourceFiber.alternate && 0 !== (sourceFiber.flags & 4098) &&
warnAboutUpdateOnNotYetMountedFiberInDEV(sourceFiber);
    for (var node = sourceFiber, parent = node.return; null !== parent;) null === node.alternate && 0 !
== (node.flags & 4098) && warnAboutUpdateOnNotYetMountedFiberInDEV(sourceFiber), node =
parent, parent = node.return;
    return 3 === node.tag ? node.stateNode : null;
  }
  function resolveFunctionForHotReloading(type) {
    if (null === resolveFamily) return type;
    var family = resolveFamily(type);
    return void 0 === family ? type : family.current;
  }
  function resolveForwardRefForHotReloading(type) {
    if (null === resolveFamily) return type;
    var family = resolveFamily(type);
    return void 0 === family ? null !== type && void 0 !== type && "function" === typeof type.render
&& (family = resolveFunctionForHotReloading(type.render), type.render !== family) ? (family = {
      $$typeof: REACT_FORWARD_REF_TYPE,
      render: family
    }, void 0 !== type.displayName && (family.displayName = type.displayName), family) : type :
```

```
family.current;
  }
  function isCompatibleFamilyForHotReloading(fiber, element) {
    if (null === resolveFamily) return !1;
    var prevType = fiber.elementType;
    element = element.type;
    var needsCompareFamilies = !1,
      $$typeofNextType = "object" === typeof element && null !== element ? element.$$typeof : null;
    switch (fiber.tag) {
      case 1:
        "function" === typeof element && (needsCompareFamilies = !0);
        break;
      case 0:
        "function" === typeof element ? needsCompareFamilies = !0 : $$typeofNextType ===
REACT_LAZY_TYPE && (needsCompareFamilies = !0);
        break;
      case 11:
        $$typeofNextType === REACT_FORWARD_REF_TYPE ? needsCompareFamilies = !0 : $
$typeofNextType === REACT_LAZY_TYPE && (needsCompareFamilies = !0);
        break;
      case 14:
      case 15:
        $$typeofNextType === REACT_MEMO_TYPE ? needsCompareFamilies = !0 : $
$typeofNextType === REACT_LAZY_TYPE && (needsCompareFamilies = !0);
        break;
      default:
        return !1;
    }
    return needsCompareFamilies && (fiber = resolveFamily(prevType), void 0 !== fiber && fiber ===
resolveFamily(element)) ? !0 : !1;
  }
  function markFailedErrorBoundaryForHotReloading(fiber) {
    null !== resolveFamily && "function" === typeof WeakSet && (null === failedBoundaries &&
(failedBoundaries = new WeakSet()), failedBoundaries.add(fiber));
  }
  function scheduleFibersWithFamiliesRecursively(fiber, updatedFamilies, staleFamilies) {
    var alternate = fiber.alternate,
      child = fiber.child,
      sibling = fiber.sibling,
      tag = fiber.tag,
      type = fiber.type,
      candidateType = null;
    switch (tag) {
      case 0:
      case 15:
      case 1:
        candidateType = type;
        break;
      case 11:
```

```
      candidateType = type.render;
    }
    if (null === resolveFamily) throw Error("Expected resolveFamily to be set during hot reload.");
    var needsRender = !1;
    type = !1;
    null !== candidateType && (candidateType = resolveFamily(candidateType), void 0 !==
candidateType && (staleFamilies.has(candidateType) ? type = !0 :
updatedFamilies.has(candidateType) && (1 === tag ? type = !0 : needsRender = !0)));
    null !== failedBoundaries && (failedBoundaries.has(fiber) || null !== alternate &&
failedBoundaries.has(alternate)) && (type = !0);
    type && (fiber._debugNeedsRemount = !0);
    if (type || needsRender) alternate = enqueueConcurrentRenderForLane(fiber, 2), null !== alternate
&& scheduleUpdateOnFiber(alternate, fiber, 2);
    null === child || type || scheduleFibersWithFamiliesRecursively(child, updatedFamilies,
staleFamilies);
    null !== sibling && scheduleFibersWithFamiliesRecursively(sibling, updatedFamilies,
staleFamilies);
  }
  function pushNestedEffectDurations() {
    var prevEffectDuration = profilerEffectDuration;
    profilerEffectDuration = 0;
    return prevEffectDuration;
  }
  function popNestedEffectDurations(prevEffectDuration) {
    var elapsedTime = profilerEffectDuration;
    profilerEffectDuration = prevEffectDuration;
    return elapsedTime;
  }
  function bubbleNestedEffectDurations(prevEffectDuration) {
    var elapsedTime = profilerEffectDuration;
    profilerEffectDuration += prevEffectDuration;
    return elapsedTime;
  }
  function startProfilerTimer(fiber) {
    profilerStartTime = now();
    0 > fiber.actualStartTime && (fiber.actualStartTime = profilerStartTime);
  }
  function stopProfilerTimerIfRunningAndRecordDuration(fiber) {
    if (0 <= profilerStartTime) {
      var elapsedTime = now() - profilerStartTime;
      fiber.actualDuration += elapsedTime;
      fiber.selfBaseDuration = elapsedTime;
      profilerStartTime = -1;
    }
  }
  function stopProfilerTimerIfRunningAndRecordIncompleteDuration(fiber) {
    if (0 <= profilerStartTime) {
      var elapsedTime = now() - profilerStartTime;
      fiber.actualDuration += elapsedTime;
```

```
    profilerStartTime = -1;
  }
}
function recordEffectDuration() {
  if (0 <= profilerStartTime) {
    var elapsedTime = now() - profilerStartTime;
    profilerStartTime = -1;
    profilerEffectDuration += elapsedTime;
  }
}
function startEffectTimer() {
  profilerStartTime = now();
}
function transferActualDuration(fiber) {
  for (var child = fiber.child; child;) fiber.actualDuration += child.actualDuration, child = child.sibling;
}
function createCapturedValueAtFiber(value, source) {
  if ("object" === typeof value && null !== value) {
    var existing = CapturedStacks.get(value);
    if (void 0 !== existing) return existing;
    source = {
      value: value,
      source: source,
      stack: getStackByFiberInDevAndProd(source)
    };
    CapturedStacks.set(value, source);
    return source;
  }
  return {
    value: value,
    source: source,
    stack: getStackByFiberInDevAndProd(source)
  };
}
function pushTreeFork(workInProgress, totalChildren) {
  warnIfNotHydrating();
  forkStack[forkStackIndex++] = treeForkCount;
  forkStack[forkStackIndex++] = treeForkProvider;
  treeForkProvider = workInProgress;
  treeForkCount = totalChildren;
}
function pushTreeId(workInProgress, totalChildren, index) {
  warnIfNotHydrating();
  idStack[idStackIndex++] = treeContextId;
  idStack[idStackIndex++] = treeContextOverflow;
  idStack[idStackIndex++] = treeContextProvider;
  treeContextProvider = workInProgress;
  var baseIdWithLeadingBit = treeContextId;
  workInProgress = treeContextOverflow;
```

```
    var baseLength = 32 - clz32(baseIdWithLeadingBit) - 1;
    baseIdWithLeadingBit &= ~(1 << baseLength);
    index += 1;
    var length = 32 - clz32(totalChildren) + baseLength;
    if (30 < length) {
      var numberOfOverflowBits = baseLength - baseLength % 5;
      length = (baseIdWithLeadingBit & (1 << numberOfOverflowBits) - 1).toString(32);
      baseIdWithLeadingBit >>= numberOfOverflowBits;
      baseLength -= numberOfOverflowBits;
      treeContextId = 1 << 32 - clz32(totalChildren) + baseLength | index << baseLength |
baseIdWithLeadingBit;
      treeContextOverflow = length + workInProgress;
    } else treeContextId = 1 << length | index << baseLength | baseIdWithLeadingBit,
treeContextOverflow = workInProgress;
  }
  function pushMaterializedTreeId(workInProgress) {
    warnIfNotHydrating();
    null !== workInProgress.return && (pushTreeFork(workInProgress, 1), pushTreeId(workInProgress,
1, 0));
  }
  function popTreeContext(workInProgress) {
    for (; workInProgress === treeForkProvider;) treeForkProvider = forkStack[--forkStackIndex],
forkStack[forkStackIndex] = null, treeForkCount = forkStack[--forkStackIndex],
forkStack[forkStackIndex] = null;
    for (; workInProgress === treeContextProvider;) treeContextProvider = idStack[--idStackIndex],
idStack[idStackIndex] = null, treeContextOverflow = idStack[--idStackIndex], idStack[idStackIndex] =
null, treeContextId = idStack[--idStackIndex], idStack[idStackIndex] = null;
  }
  function warnIfNotHydrating() {
    isHydrating || console.error("Expected to be hydrating. This is a bug in React. Please file an issue.");
  }
  function buildHydrationDiffNode(fiber, distanceFromLeaf) {
    if (null === fiber.return) {
      if (null === hydrationDiffRootDEV) hydrationDiffRootDEV = {
        fiber: fiber,
        children: [],
        serverProps: void 0,
        serverTail: [],
        distanceFromLeaf: distanceFromLeaf
      };else {
        if (hydrationDiffRootDEV.fiber !== fiber) throw Error("Saw multiple hydration diff roots in a
pass. This is a bug in React.");
        hydrationDiffRootDEV.distanceFromLeaf > distanceFromLeaf &&
(hydrationDiffRootDEV.distanceFromLeaf = distanceFromLeaf);
      }
      return hydrationDiffRootDEV;
    }
    var siblings = buildHydrationDiffNode(fiber.return, distanceFromLeaf + 1).children;
    if (0 < siblings.length && siblings[siblings.length - 1].fiber === fiber) return siblings =
```

```
siblings[siblings.length - 1], siblings.distanceFromLeaf > distanceFromLeaf &&
(siblings.distanceFromLeaf = distanceFromLeaf), siblings;
    distanceFromLeaf = {
      fiber: fiber,
      children: [],
      serverProps: void 0,
      serverTail: [],
      distanceFromLeaf: distanceFromLeaf
    };
    siblings.push(distanceFromLeaf);
    return distanceFromLeaf;
  }
  function warnNonHydratedInstance(fiber, rejectedCandidate) {
    didSuspendOrErrorDEV || (fiber = buildHydrationDiffNode(fiber, 0), fiber.serverProps
 = null, null !== rejectedCandidate && (rejectedCandidate =
describeHydratableInstanceForDevWarnings(rejectedCandidate),
fiber.serverTail.push(rejectedCandidate)));
  }
  function throwOnHydrationMismatch(fiber) {
    var diff = "",
      diffRoot = hydrationDiffRootDEV;
    null !== diffRoot && (hydrationDiffRootDEV = null, diff = describeDiff(diffRoot));
    queueHydrationError(createCapturedValueAtFiber(Error("Hydration failed because the server
rendered HTML didn't match the client. As a result this tree will be regenerated on the client. This can
happen if a SSR-ed Client Component used:\n\n- A server/client branch `if (typeof window !==
'undefined')`.\n- Variable input such as `Date.now()` or `Math.random()` which changes each time it's
called.\n- Date formatting in a user's locale which doesn't match the server.\n- External changing data
without sending a snapshot of it along with the HTML.\n- Invalid HTML tag nesting.\n\nIt can also
happen if the client has a browser extension installed which messes with the HTML before React
loaded.\n\nhttps://react.dev/link/hydration-mismatch" + diff), fiber));
    throw HydrationMismatchException;
  }
  function prepareToHydrateHostInstance(fiber) {
    var didHydrate = fiber.stateNode;
    var type = fiber.type,
      props = fiber.memoizedProps;
    didHydrate[internalInstanceKey] = fiber;
    didHydrate[internalPropsKey] = props;
    validatePropertiesInDevelopment(type, props);
    switch (type) {
      case "dialog":
        listenToNonDelegatedEvent("cancel", didHydrate);
        listenToNonDelegatedEvent("close", didHydrate);
        break;
      case "iframe":
      case "object":
      case "embed":
        listenToNonDelegatedEvent("load", didHydrate);
        break;
```

```
      case "video":
      case "audio":
        for (type = 0; type < mediaEventTypes.length; type++)
listenToNonDelegatedEvent(mediaEventTypes[type], didHydrate);
        break;
      case "source":
        listenToNonDelegatedEvent("error", didHydrate);
        break;
      case "img":
      case "image":
      case "link":
        listenToNonDelegatedEvent("error", didHydrate);
        listenToNonDelegatedEvent("load", didHydrate);
        break;
      case "details":
        listenToNonDelegatedEvent("toggle", didHydrate);
        break;
      case "input":
        checkControlledValueProps("input", props);
        listenToNonDelegatedEvent("invalid", didHydrate);
        validateInputProps(didHydrate, props);
        initInput(didHydrate, props.value, props.defaultValue, props.checked, props.defaultChecked,
props.type, props.name, !0);
        track(didHydrate);
        break;
      case "option":
        validateOptionProps(didHydrate, props);
        break;
      case "select":
        checkControlledValueProps("select", props);
        listenToNonDelegatedEvent("invalid", didHydrate);
        validateSelectProps(didHydrate, props);
        break;
      case "textarea":
        checkControlledValueProps("textarea", props), listenToNonDelegatedEvent("invalid",
didHydrate), validateTextareaProps(didHydrate, props), initTextarea(didHydrate, props.value,
props.defaultValue, props.children), track(didHydrate);
    }
    type = props.children;
    "string" !== typeof type && "number" !== typeof type && "bigint" !== typeof type ||
didHydrate.textContent === "" + type || !0 === props.suppressHydrationWarning ||
checkForUnmatchedText(didHydrate.textContent, type) ? (null != props.popover &&
(listenToNonDelegatedEvent("beforetoggle", didHydrate), listenToNonDelegatedEvent("toggle",
didHydrate)), null != props.onScroll && listenToNonDelegatedEvent("scroll", didHydrate), null !=
props.onScrollEnd && listenToNonDelegatedEvent("scrollend", didHydrate), null != props.onClick
&& (didHydrate.onclick = noop$1), didHydrate = !0) : didHydrate = !1;
    didHydrate || throwOnHydrationMismatch(fiber);
  }
  function popToNextHostParent(fiber) {
```

```
    for (hydrationParentFiber = fiber.return; hydrationParentFiber;) switch (hydrationParentFiber.tag) {
      case 3:
      case 27:
        rootOrSingletonContext = !0;
        return;
      case 5:
      case 13:
        rootOrSingletonContext = !1;
        return;
      default:
        hydrationParentFiber = hydrationParentFiber.return;
    }
  }
  function popHydrationState(fiber) {
    if (fiber !== hydrationParentFiber) return !1;
    if (!isHydrating) return popToNextHostParent(fiber), isHydrating = !0, !1;
    var shouldClear = !1,
      JSCompiler_temp;
    if (JSCompiler_temp = 3 !== fiber.tag && 27 !== fiber.tag) {
      if (JSCompiler_temp = 5 === fiber.tag) JSCompiler_temp = fiber.type, JSCompiler_temp = !
("form" !== JSCompiler_temp && "button" !== JSCompiler_temp) || shouldSetTextContent(fiber.type,
fiber.memoizedProps);
      JSCompiler_temp = !JSCompiler_temp;
    }
    JSCompiler_temp && (shouldClear = !0);
    if (shouldClear && nextHydratableInstance) {
      for (shouldClear = nextHydratableInstance; shouldClear;) {
        JSCompiler_temp = buildHydrationDiffNode(fiber, 0);
        var description = describeHydratableInstanceForDevWarnings(shouldClear);
        JSCompiler_temp.serverTail.push(description);
        shouldClear = "Suspense" === description.type ?
getNextHydratableInstanceAfterSuspenseInstance(shouldClear) :
getNextHydratable(shouldClear.nextSibling);
      }
      throwOnHydrationMismatch(fiber);
    }
    popToNextHostParent(fiber);
    if (13 === fiber.tag) {
      fiber = fiber.memoizedState;
      fiber = null !== fiber ? fiber.dehydrated : null;
      if (!fiber) throw Error("Expected to have a hydrated suspense instance. This error is likely caused
by a bug in React. Please file an issue.");
      nextHydratableInstance = getNextHydratableInstanceAfterSuspenseInstance(fiber);
    } else nextHydratableInstance = hydrationParentFiber ?
getNextHydratable(fiber.stateNode.nextSibling) : null;
    return !0;
  }
  function resetHydrationState() {
    nextHydratableInstance = hydrationParentFiber = null;
```

```
    didSuspendOrErrorDEV = isHydrating = !1;
  }
  function queueHydrationError(error) {
    null === hydrationErrors ? hydrationErrors = [error] : hydrationErrors.push(error);
  }
  function emitPendingHydrationWarnings() {
    var diffRoot = hydrationDiffRootDEV;
    null !== diffRoot && (hydrationDiffRootDEV = null, diffRoot = describeDiff(diffRoot),
console.error("A tree hydrated but some attributes of the server rendered HTML didn't match the client properties. This won't be patched up. This can happen if a SSR-ed Client Component used:\n\n- A server/client branch `if (typeof window !== 'undefined')`.\n- Variable input such as `Date.now()` or `Math.random()` which changes each time it's called.\n- Date formatting in a user's locale which doesn't match the server.\n- External changing data without sending a snapshot of it along with the HTML.\n- Invalid HTML tag nesting.\n\nIt can also happen if the client has a browser extension installed which messes with the HTML before React loaded.\n\n%s%s",
"https://react.dev/link/hydration-mismatch", diffRoot));
  }
  function createThenableState() {
    return {
      didWarnAboutUncachedPromise: !1,
      thenables: []
    };
  }
  function isThenableResolved(thenable) {
    thenable = thenable.status;
    return "fulfilled" === thenable || "rejected" === thenable;
  }
  function noop$3() {}
  function trackUsedThenable(thenableState, thenable, index) {
    null !== ReactSharedInternals.actQueue && (ReactSharedInternals.didUsePromise = !0);
    var trackedThenables = thenableState.thenables;
    index = trackedThenables[index];
    void 0 === index ? trackedThenables.push(thenable) : index !== thenable &&
(thenableState.didWarnAboutUncachedPromise || (thenableState.didWarnAboutUncachedPromise = !0,
console.error("A component was suspended by an uncached promise. Creating promises inside a Client Component or hook is not yet supported, except via a Suspense-compatible library or framework.")),
thenable.then(noop$3, noop$3), thenable = index);
    switch (thenable.status) {
      case "fulfilled":
        return thenable.value;
      case "rejected":
        throw thenableState = thenable.reason, checkIfUseWrappedInAsyncCatch(thenableState),
thenableState;
      default:
        if ("string" === typeof thenable.status) thenable.then(noop$3, noop$3);else {
          thenableState = workInProgressRoot;
          if (null !== thenableState && 100 < thenableState.shellSuspendCounter) throw
Error("async/await is not yet supported in Client Components, only Server Components. This error is often caused by accidentally adding `'use client'` to a module that was originally written for the
```

```
server.");
          thenableState = thenable;
          thenableState.status = "pending";
          thenableState.then(function (fulfilledValue) {
            if ("pending" === thenable.status) {
              var fulfilledThenable = thenable;
              fulfilledThenable.status = "fulfilled";
              fulfilledThenable.value = fulfilledValue;
            }
          }, function (error) {
            if ("pending" === thenable.status) {
              var rejectedThenable = thenable;
              rejectedThenable.status = "rejected";
              rejectedThenable.reason = error;
            }
          });
        }
        switch (thenable.status) {
          case "fulfilled":
            return thenable.value;
          case "rejected":
            throw thenableState = thenable.reason, checkIfUseWrappedInAsyncCatch(thenableState),
thenableState;
        }
        suspendedThenable = thenable;
        needsToResetSuspendedThenableDEV = !0;
        throw SuspenseException;
    }
  }
  function getSuspendedThenable() {
    if (null === suspendedThenable) throw Error("Expected a suspended thenable. This is a bug in
React. Please file an issue.");
    var thenable = suspendedThenable;
    suspendedThenable
 = null;
    needsToResetSuspendedThenableDEV = !1;
    return thenable;
  }
  function checkIfUseWrappedInAsyncCatch(rejectedReason) {
    if (rejectedReason === SuspenseException) throw Error("Hooks are not supported inside an async
component. This error is often caused by accidentally adding `'use client'` to a module that was
originally written for the server.");
  }
  function pushDebugInfo(debugInfo) {
    var previousDebugInfo = currentDebugInfo;
    null != debugInfo && (currentDebugInfo = null === previousDebugInfo ? debugInfo :
previousDebugInfo.concat(debugInfo));
    return previousDebugInfo;
  }
```

```
  function validateFragmentProps(element, fiber, returnFiber) {
    for (var keys = Object.keys(element.props), i = 0; i < keys.length; i++) {
      var key = keys[i];
      if ("children" !== key && "key" !== key) {
        null === fiber && (fiber = createFiberFromElement(element, returnFiber.mode, 0),
fiber._debugInfo = currentDebugInfo, fiber.return = returnFiber);
        runWithFiberInDEV(fiber, function (erroredKey) {
          console.error("Invalid prop `%s` supplied to `React.Fragment`. React.Fragment can only have
`key` and `children` props.", erroredKey);
        }, key);
        break;
      }
    }
  }
  function unwrapThenable(thenable) {
    var index = thenableIndexCounter$1;
    thenableIndexCounter$1 += 1;
    null === thenableState$1 && (thenableState$1 = createThenableState());
    return trackUsedThenable(thenableState$1, thenable, index);
  }
  function coerceRef(workInProgress, element) {
    element = element.props.ref;
    workInProgress.ref = void 0 !== element ? element : null;
  }
  function throwOnInvalidObjectType(returnFiber, newChild) {
    if (newChild.$$typeof === REACT_LEGACY_ELEMENT_TYPE) throw Error('A React Element
from an older version of React was rendered. This is not supported. It can happen if:\n- Multiple copies
of the "react" package is used.\n- A library pre-bundled an old copy of "react" or "react/jsx-runtime".\n-
A compiler tries to "inline" JSX instead of using the runtime.');
    returnFiber = Object.prototype.toString.call(newChild);
    throw Error("Objects are not valid as a React child (found: " + ("[object Object]" === returnFiber ?
"object with keys {" + Object.keys(newChild).join(", ") + "}" : returnFiber) + "). If you meant to render
a collection of children, use an array instead.");
  }
  function warnOnFunctionType(returnFiber, invalidChild) {
    var parentName = getComponentNameFromFiber(returnFiber) || "Component";
    ownerHasFunctionTypeWarning[parentName] || (ownerHasFunctionTypeWarning[parentName] = !0,
invalidChild = invalidChild.displayName || invalidChild.name || "Component", 3 === returnFiber.tag ?
console.error("Functions are not valid as a React child. This may happen if you return %s instead of <
%s /> from render. Or maybe you meant to call this function rather than return it.\n  root.render(%s)",
invalidChild, invalidChild, invalidChild) : console.error("Functions are not valid as a React child. This
may happen if you return %s instead of <%s /> from render. Or maybe you meant to call this function
rather than return it.\n  <%s>{%s}</%s>", invalidChild, invalidChild, parentName, invalidChild,
parentName));
  }
  function warnOnSymbolType(returnFiber, invalidChild) {
    var parentName = getComponentNameFromFiber(returnFiber) || "Component";
    ownerHasSymbolTypeWarning[parentName] || (ownerHasSymbolTypeWarning[parentName] = !0,
invalidChild = String(invalidChild), 3 === returnFiber.tag ? console.error("Symbols are not valid as a
```

```
React child.\n  root.render(%s)", invalidChild) : console.error("Symbols are not valid as a React
child.\n  <%s>%s</%s>", parentName, invalidChild, parentName));
  }
  function createChildReconciler(shouldTrackSideEffects) {
    function deleteChild(returnFiber, childToDelete) {
      if (shouldTrackSideEffects) {
        var deletions = returnFiber.deletions;
        null === deletions ? (returnFiber.deletions = [childToDelete], returnFiber.flags |= 16) :
deletions.push(childToDelete);
      }
    }
    function deleteRemainingChildren(returnFiber, currentFirstChild) {
      if (!shouldTrackSideEffects) return null;
      for (; null !== currentFirstChild;) deleteChild(returnFiber, currentFirstChild), currentFirstChild =
currentFirstChild.sibling;
      return null;
    }
    function mapRemainingChildren(currentFirstChild) {
      for (var existingChildren = new Map(); null !== currentFirstChild;) null !== currentFirstChild.key ?
existingChildren.set(currentFirstChild.key, currentFirstChild) :
existingChildren.set(currentFirstChild.index, currentFirstChild), currentFirstChild =
currentFirstChild.sibling;
      return existingChildren;
    }
    function useFiber(fiber, pendingProps) {
      fiber = createWorkInProgress(fiber, pendingProps);
      fiber.index = 0;
      fiber.sibling = null;
      return fiber;
    }
    function placeChild(newFiber, lastPlacedIndex, newIndex) {
      newFiber.index = newIndex;
      if (!shouldTrackSideEffects) return newFiber.flags |= 1048576, lastPlacedIndex;
      newIndex = newFiber.alternate;
      if (null !== newIndex) return newIndex = newIndex.index, newIndex < lastPlacedIndex ?
(newFiber.flags |= 33554434, lastPlacedIndex) : newIndex;
      newFiber.flags |= 33554434;
      return lastPlacedIndex;
    }
    function placeSingleChild(newFiber) {
      shouldTrackSideEffects && null === newFiber.alternate && (newFiber.flags |= 33554434);
      return newFiber;
    }
    function updateTextNode(returnFiber, current, textContent, lanes) {
      if (null === current || 6 !== current.tag) return current = createFiberFromText(textContent,
returnFiber.mode, lanes), current.return = returnFiber, current._debugOwner = returnFiber,
current._debugInfo = currentDebugInfo, current;
      current = useFiber(current, textContent);
      current.return = returnFiber;
```

```
      current._debugInfo = currentDebugInfo;
      return current;
    }
    function updateElement(returnFiber, current, element, lanes) {
      var elementType = element.type;
      if (elementType === REACT_FRAGMENT_TYPE) return current = updateFragment(returnFiber,
current, element.props.children, lanes, element.key), validateFragmentProps(element, current,
returnFiber), current;
      if (null !== current && (current.elementType === elementType ||
isCompatibleFamilyForHotReloading(current, element) || "object" === typeof elementType && null !
== elementType && elementType.$$typeof === REACT_LAZY_TYPE &&
callLazyInitInDEV(elementType) === current.type)) return current = useFiber(current, element.props),
coerceRef(current, element), current.return = returnFiber, current._debugOwner = element._owner,
current._debugInfo = currentDebugInfo, current;
      current = createFiberFromElement(element, returnFiber.mode, lanes);
      coerceRef(current, element);
      current.return = returnFiber;
      current._debugInfo = currentDebugInfo;
      return current;
    }
    function updatePortal(returnFiber, current, portal, lanes) {
      if (null === current || 4 !== current.tag || current.stateNode.containerInfo !== portal.containerInfo ||
current.stateNode.implementation !== portal.implementation) return current =
createFiberFromPortal(portal, returnFiber.mode, lanes), current.return = returnFiber,
current._debugInfo = currentDebugInfo, current;
      current = useFiber(current, portal.children || []);
      current.return = returnFiber;
      current._debugInfo = currentDebugInfo;
      return current;
    }
    function updateFragment(returnFiber, current, fragment, lanes, key) {
      if (null === current || 7 !== current.tag) return current = createFiberFromFragment(fragment,
returnFiber.mode, lanes, key), current.return = returnFiber, current._debugOwner = returnFiber,
current._debugInfo = currentDebugInfo, current;
      current = useFiber(current, fragment);
      current.return = returnFiber;
      current._debugInfo = currentDebugInfo;
      return current;
    }
    function createChild(returnFiber, newChild, lanes) {
      if ("string" === typeof newChild && "" !== newChild || "number" === typeof newChild || "bigint"
=== typeof newChild) return newChild = createFiberFromText("" + newChild, returnFiber.mode,
lanes), newChild.return = returnFiber, newChild._debugOwner = returnFiber, newChild._debugInfo =
currentDebugInfo, newChild;
      if ("object" === typeof newChild && null !== newChild) {
        switch (newChild.$$typeof) {
          case REACT_ELEMENT_TYPE:
            return lanes = createFiberFromElement(newChild, returnFiber.mode, lanes), coerceRef(lanes,
newChild), lanes.return = returnFiber, returnFiber = pushDebugInfo(newChild._debugInfo),
```

```
lanes._debugInfo = currentDebugInfo, currentDebugInfo = returnFiber, lanes;
        case REACT_PORTAL_TYPE:
          return newChild = createFiberFromPortal(newChild, returnFiber.mode, lanes), newChild.return
= returnFiber, newChild._debugInfo = currentDebugInfo, newChild;
        case REACT_LAZY_TYPE:
          var _prevDebugInfo = pushDebugInfo(newChild._debugInfo);
          newChild = callLazyInitInDEV(newChild);
          returnFiber = createChild(returnFiber, newChild, lanes);
          currentDebugInfo = _prevDebugInfo;
          return returnFiber;
      }
      if (isArrayImpl(newChild) || getIteratorFn(newChild)) return lanes =
createFiberFromFragment(newChild, returnFiber.mode, lanes, null), lanes.return = returnFiber,
lanes._debugOwner = returnFiber, returnFiber = pushDebugInfo(newChild._debugInfo),
lanes._debugInfo = currentDebugInfo, currentDebugInfo = returnFiber, lanes;
      if ("function" === typeof newChild.then) return _prevDebugInfo =
pushDebugInfo(newChild._debugInfo), returnFiber = createChild(returnFiber,
unwrapThenable(newChild), lanes), currentDebugInfo = _prevDebugInfo, returnFiber;
      if (newChild.$$typeof ===
 REACT_CONTEXT_TYPE) return createChild(returnFiber,
readContextDuringReconciliation(returnFiber, newChild), lanes);
      throwOnInvalidObjectType(returnFiber, newChild);
    }
    "function" === typeof newChild && warnOnFunctionType(returnFiber, newChild);
    "symbol" === typeof newChild && warnOnSymbolType(returnFiber, newChild);
    return null;
  }
  function updateSlot(returnFiber, oldFiber, newChild, lanes) {
    var key = null !== oldFiber ? oldFiber.key : null;
    if ("string" === typeof newChild && "" !== newChild || "number" === typeof newChild || "bigint"
=== typeof newChild) return null !== key ? null : updateTextNode(returnFiber, oldFiber, "" +
newChild, lanes);
    if ("object" === typeof newChild && null !== newChild) {
      switch (newChild.$$typeof) {
        case REACT_ELEMENT_TYPE:
          return newChild.key === key ? (key = pushDebugInfo(newChild._debugInfo), returnFiber =
updateElement(returnFiber, oldFiber, newChild, lanes), currentDebugInfo = key, returnFiber) : null;
        case REACT_PORTAL_TYPE:
          return newChild.key === key ? updatePortal(returnFiber, oldFiber, newChild, lanes) : null;
        case REACT_LAZY_TYPE:
          return key = pushDebugInfo(newChild._debugInfo), newChild =
callLazyInitInDEV(newChild), returnFiber = updateSlot(returnFiber, oldFiber, newChild, lanes),
currentDebugInfo = key, returnFiber;
      }
      if (isArrayImpl(newChild) || getIteratorFn(newChild)) {
        if (null !== key) return null;
        key = pushDebugInfo(newChild._debugInfo);
        returnFiber = updateFragment(returnFiber, oldFiber, newChild, lanes, null);
        currentDebugInfo = key;
```

```
        return returnFiber;
      }
      if ("function" === typeof newChild.then) return key = pushDebugInfo(newChild._debugInfo),
returnFiber = updateSlot(returnFiber, oldFiber, unwrapThenable(newChild), lanes), currentDebugInfo
= key, returnFiber;
      if (newChild.$$typeof === REACT_CONTEXT_TYPE) return updateSlot(returnFiber, oldFiber,
readContextDuringReconciliation(returnFiber, newChild), lanes);
      throwOnInvalidObjectType(returnFiber, newChild);
    }
    "function" === typeof newChild && warnOnFunctionType(returnFiber, newChild);
    "symbol" === typeof newChild && warnOnSymbolType(returnFiber, newChild);
    return null;
  }
  function updateFromMap(existingChildren, returnFiber, newIdx, newChild, lanes) {
    if ("string" === typeof newChild && "" !== newChild || "number" === typeof newChild || "bigint"
=== typeof newChild) return existingChildren = existingChildren.get(newIdx) || null,
updateTextNode(returnFiber, existingChildren, "" + newChild, lanes);
    if ("object" === typeof newChild && null !== newChild) {
      switch (newChild.$$typeof) {
        case REACT_ELEMENT_TYPE:
          return newIdx = existingChildren.get(null === newChild.key ? newIdx : newChild.key) || null,
existingChildren = pushDebugInfo(newChild._debugInfo), returnFiber = updateElement(returnFiber,
newIdx, newChild, lanes), currentDebugInfo = existingChildren, returnFiber;
        case REACT_PORTAL_TYPE:
          return existingChildren = existingChildren.get(null === newChild.key ? newIdx :
newChild.key) || null, updatePortal(returnFiber, existingChildren, newChild, lanes);
        case REACT_LAZY_TYPE:
          var _prevDebugInfo7 = pushDebugInfo(newChild._debugInfo);
          newChild = callLazyInitInDEV(newChild);
          returnFiber = updateFromMap(existingChildren, returnFiber, newIdx, newChild, lanes);
          currentDebugInfo = _prevDebugInfo7;
          return returnFiber;
      }
      if (isArrayImpl(newChild) || getIteratorFn(newChild)) return newIdx =
existingChildren.get(newIdx) || null, existingChildren = pushDebugInfo(newChild._debugInfo),
returnFiber = updateFragment(returnFiber, newIdx, newChild, lanes, null), currentDebugInfo =
existingChildren, returnFiber;
      if ("function" === typeof newChild.then) return _prevDebugInfo7 =
pushDebugInfo(newChild._debugInfo), returnFiber = updateFromMap(existingChildren, returnFiber,
newIdx, unwrapThenable(newChild), lanes), currentDebugInfo = _prevDebugInfo7, returnFiber;
      if (newChild.$$typeof === REACT_CONTEXT_TYPE) return
updateFromMap(existingChildren, returnFiber, newIdx, readContextDuringReconciliation(returnFiber,
newChild), lanes);
      throwOnInvalidObjectType(returnFiber, newChild);
    }
    "function" === typeof newChild && warnOnFunctionType(returnFiber, newChild);
    "symbol" === typeof newChild && warnOnSymbolType(returnFiber, newChild);
    return null;
  }
```

```
  function warnOnInvalidKey(returnFiber, workInProgress, child, knownKeys) {
    if ("object" !== typeof child || null === child) return knownKeys;
    switch (child.$$typeof) {
      case REACT_ELEMENT_TYPE:
      case REACT_PORTAL_TYPE:
        warnForMissingKey(returnFiber, workInProgress, child);
        var key = child.key;
        if ("string" !== typeof key) break;
        if (null === knownKeys) {
          knownKeys = new Set();
          knownKeys.add(key);
          break;
        }
        if (!knownKeys.has(key)) {
          knownKeys.add(key);
          break;
        }
        runWithFiberInDEV(workInProgress, function () {
          console.error("Encountered two children with the same key, `%s`. Keys should be unique so that components maintain their identity across updates. Non-unique keys may cause children to be duplicated and/or omitted \u2014 the behavior is unsupported and could change in a future version.", key);
        });
        break;
      case REACT_LAZY_TYPE:
        child = callLazyInitInDEV(child), warnOnInvalidKey(returnFiber, workInProgress, child, knownKeys);
    }
    return knownKeys;
  }
  function reconcileChildrenArray(returnFiber, currentFirstChild, newChildren, lanes) {
    for (var knownKeys = null, resultingFirstChild = null, previousNewFiber = null, oldFiber = currentFirstChild, newIdx = currentFirstChild = 0, nextOldFiber = null; null !== oldFiber && newIdx < newChildren.length; newIdx++) {
      oldFiber.index > newIdx ? (nextOldFiber = oldFiber, oldFiber = null) : nextOldFiber = oldFiber.sibling;
      var newFiber = updateSlot(returnFiber, oldFiber, newChildren[newIdx], lanes);
      if (null === newFiber) {
        null === oldFiber && (oldFiber = nextOldFiber);
        break;
      }
      knownKeys = warnOnInvalidKey(returnFiber, newFiber, newChildren[newIdx], knownKeys);
      shouldTrackSideEffects && oldFiber && null === newFiber.alternate && deleteChild(returnFiber, oldFiber);
      currentFirstChild = placeChild(newFiber, currentFirstChild, newIdx);
      null === previousNewFiber ? resultingFirstChild = newFiber : previousNewFiber.sibling = newFiber;
      previousNewFiber = newFiber;
      oldFiber = nextOldFiber;
```

```
    }
    if (newIdx === newChildren.length) return deleteRemainingChildren(returnFiber, oldFiber),
isHydrating && pushTreeFork(returnFiber, newIdx), resultingFirstChild;
    if (null === oldFiber) {
      for (; newIdx < newChildren.length; newIdx++) oldFiber = createChild(returnFiber,
newChildren[newIdx], lanes), null !== oldFiber && (knownKeys = warnOnInvalidKey(returnFiber,
oldFiber, newChildren[newIdx], knownKeys), currentFirstChild = placeChild(oldFiber,
currentFirstChild, newIdx), null === previousNewFiber ? resultingFirstChild = oldFiber :
previousNewFiber.sibling = oldFiber, previousNewFiber = oldFiber);
      isHydrating && pushTreeFork(returnFiber, newIdx);
      return resultingFirstChild;
    }
    for (oldFiber = mapRemainingChildren(oldFiber); newIdx < newChildren.length; newIdx++)
nextOldFiber = updateFromMap(oldFiber, returnFiber, newIdx, newChildren[newIdx], lanes), null !==
nextOldFiber && (knownKeys = warnOnInvalidKey(returnFiber, nextOldFiber, newChildren[newIdx],
knownKeys), shouldTrackSideEffects && null !== nextOldFiber.alternate && oldFiber.delete(null
=== nextOldFiber.key ? newIdx : nextOldFiber.key), currentFirstChild = placeChild(nextOldFiber,
currentFirstChild, newIdx), null === previousNewFiber ? resultingFirstChild = nextOldFiber :
previousNewFiber.sibling = nextOldFiber, previousNewFiber = nextOldFiber);
    shouldTrackSideEffects && oldFiber.forEach(function (child) {
      return deleteChild(returnFiber, child);
    });
    isHydrating && pushTreeFork(returnFiber, newIdx);
    return resultingFirstChild;
  }
  function reconcileChildrenIterator(returnFiber, currentFirstChild, newChildren, lanes) {
    if (null == newChildren) throw Error("An iterable object provided no iterator.");
    for (var resultingFirstChild = null, previousNewFiber = null, oldFiber = currentFirstChild, newIdx
= currentFirstChild = 0, nextOldFiber = null, knownKeys = null, step = newChildren.next(); null !==
oldFiber && !step.done; newIdx++, step = newChildren.next()) {
      oldFiber.index > newIdx ? (nextOldFiber = oldFiber, oldFiber = null) : nextOldFiber =
oldFiber.sibling;
      var newFiber = updateSlot(returnFiber, oldFiber, step.value, lanes);
      if (null === newFiber) {
        null === oldFiber && (oldFiber = nextOldFiber);
        break;
      }
      knownKeys = warnOnInvalidKey(returnFiber, newFiber, step.value, knownKeys);
      shouldTrackSideEffects && oldFiber && null === newFiber.alternate &&
deleteChild(returnFiber, oldFiber);
      currentFirstChild = placeChild(newFiber, currentFirstChild, newIdx);
      null === previousNewFiber ? resultingFirstChild = newFiber : previousNewFiber.sibling =
newFiber;
      previousNewFiber = newFiber;
      oldFiber = nextOldFiber;
    }
    if (step.done) return deleteRemainingChildren(returnFiber, oldFiber), isHydrating &&
pushTreeFork(returnFiber, newIdx), resultingFirstChild;
```

```
    if (null === oldFiber) {
      for (; !step.done; newIdx++, step = newChildren.next()) oldFiber = createChild(returnFiber,
step.value, lanes), null !== oldFiber && (knownKeys = warnOnInvalidKey(returnFiber, oldFiber,
step.value, knownKeys), currentFirstChild = placeChild(oldFiber, currentFirstChild, newIdx), null ===
previousNewFiber ? resultingFirstChild = oldFiber : previousNewFiber.sibling = oldFiber,
previousNewFiber = oldFiber);
      isHydrating && pushTreeFork(returnFiber, newIdx);
      return resultingFirstChild;
    }
    for (oldFiber = mapRemainingChildren(oldFiber); !step.done; newIdx++, step =
newChildren.next()) nextOldFiber = updateFromMap(oldFiber, returnFiber, newIdx, step.value, lanes),
null !== nextOldFiber && (knownKeys = warnOnInvalidKey(returnFiber, nextOldFiber, step.value,
knownKeys), shouldTrackSideEffects && null !== nextOldFiber.alternate && oldFiber.delete(null
=== nextOldFiber.key ? newIdx : nextOldFiber.key), currentFirstChild = placeChild(nextOldFiber,
currentFirstChild, newIdx), null === previousNewFiber ? resultingFirstChild = nextOldFiber :
previousNewFiber.sibling = nextOldFiber, previousNewFiber = nextOldFiber);
    shouldTrackSideEffects && oldFiber.forEach(function (child) {
      return deleteChild(returnFiber, child);
    });
    isHydrating && pushTreeFork(returnFiber, newIdx);
    return resultingFirstChild;
  }
  function reconcileChildFibersImpl(returnFiber, currentFirstChild, newChild, lanes) {
    "object" === typeof newChild && null !== newChild && newChild.type ===
REACT_FRAGMENT_TYPE && null === newChild.key && (validateFragmentProps(newChild,
null, returnFiber), newChild = newChild.props.children);
    if ("object" === typeof newChild && null !== newChild) {
      switch (newChild.$$typeof) {
        case REACT_ELEMENT_TYPE:
          var prevDebugInfo = pushDebugInfo(newChild._debugInfo);
          a: {
            for (var key = newChild.key; null !== currentFirstChild;) {
              if (currentFirstChild.key === key) {
                key = newChild.type;
                if (key === REACT_FRAGMENT_TYPE) {
                  if (7 === currentFirstChild.tag) {
                    deleteRemainingChildren(returnFiber, currentFirstChild.sibling);
                    lanes = useFiber(currentFirstChild, newChild.props.children);
                    lanes.return = returnFiber;
                    lanes._debugOwner = newChild._owner;
                    lanes._debugInfo = currentDebugInfo;
                    validateFragmentProps(newChild, lanes, returnFiber);
                    returnFiber = lanes;
                    break a;
                  }
                } else if (currentFirstChild.elementType === key ||
isCompatibleFamilyForHotReloading(currentFirstChild, newChild) || "object" === typeof key && null
!== key && key.$$typeof === REACT_LAZY_TYPE && callLazyInitInDEV(key) ===
currentFirstChild.type) {
```

```
                deleteRemainingChildren(returnFiber, currentFirstChild.sibling);
                lanes = useFiber(currentFirstChild, newChild.props);
                coerceRef(lanes, newChild);
                lanes.return = returnFiber;
                lanes._debugOwner = newChild._owner;
                lanes._debugInfo = currentDebugInfo;
                returnFiber = lanes;
                break a;
              }
              deleteRemainingChildren(returnFiber, currentFirstChild);
              break;
            } else deleteChild(returnFiber, currentFirstChild);
            currentFirstChild = currentFirstChild.sibling;
          }
          newChild.type === REACT_FRAGMENT_TYPE ? (lanes =
createFiberFromFragment(newChild.props.children, returnFiber.mode, lanes, newChild.key),
lanes.return = returnFiber, lanes._debugOwner = returnFiber, lanes._debugInfo = currentDebugInfo,
validateFragmentProps(newChild, lanes, returnFiber), returnFiber = lanes) : (lanes =
createFiberFromElement(newChild, returnFiber.mode, lanes), coerceRef(lanes, newChild), lanes.return
= returnFiber, lanes._debugInfo = currentDebugInfo, returnFiber = lanes);
        }
        returnFiber = placeSingleChild(returnFiber);
        currentDebugInfo = prevDebugInfo;
        return returnFiber;
      case REACT_PORTAL_TYPE:
        a: {
          prevDebugInfo = newChild;
          for (newChild = prevDebugInfo.key; null !== currentFirstChild;) {
            if (currentFirstChild.key === newChild) {
              if (4 === currentFirstChild.tag && currentFirstChild.stateNode.containerInfo ===
prevDebugInfo.containerInfo && currentFirstChild.stateNode.implementation ===
prevDebugInfo.implementation) {
                deleteRemainingChildren(returnFiber, currentFirstChild.sibling);
                lanes = useFiber(currentFirstChild, prevDebugInfo.children || []);
                lanes.return = returnFiber;
                returnFiber = lanes;
                break a;
              } else {
                deleteRemainingChildren(returnFiber, currentFirstChild);
                break;
              }
            } else deleteChild(returnFiber, currentFirstChild);
            currentFirstChild = currentFirstChild.sibling;
          }
          lanes = createFiberFromPortal(prevDebugInfo, returnFiber.mode, lanes);
          lanes.return = returnFiber;
          returnFiber = lanes;
        }
        return placeSingleChild(returnFiber);
```

```
        case REACT_LAZY_TYPE:
          return prevDebugInfo = pushDebugInfo(newChild._debugInfo), newChild =
callLazyInitInDEV(newChild), returnFiber = reconcileChildFibersImpl(returnFiber, currentFirstChild,
newChild, lanes), currentDebugInfo = prevDebugInfo, returnFiber;
      }
      if (isArrayImpl(newChild)) return prevDebugInfo = pushDebugInfo(newChild._debugInfo),
returnFiber = reconcileChildrenArray(returnFiber, currentFirstChild, newChild, lanes),
currentDebugInfo = prevDebugInfo, returnFiber;
      if (getIteratorFn(newChild)) {
        prevDebugInfo = pushDebugInfo(newChild._debugInfo);
        key = getIteratorFn(newChild);
        if ("function" !== typeof key) throw Error("An object is not an iterable. This error is likely
caused by a bug in React. Please file an issue.");
        var newChildren = key.call(newChild);
        if (newChildren === newChild) {
          if (0 !== returnFiber.tag || "[object GeneratorFunction]" !==
Object.prototype.toString.call(returnFiber.type) || "[object Generator]" !==
Object.prototype.toString.call(newChildren)) didWarnAboutGenerators || console.error("Using Iterators
as children is unsupported and will likely yield unexpected results because enumerating a generator
mutates it. You may convert it to an array with `Array.from()` or the `[...spread]` operator before
rendering. You can also use an Iterable that can iterate multiple times over the same items."),
didWarnAboutGenerators = !0;
        } else newChild.entries !== key || didWarnAboutMaps || (console.error("Using Maps as children
is not supported. Use an array of keyed ReactElements instead."), didWarnAboutMaps = !0);
        returnFiber = reconcileChildrenIterator(returnFiber, currentFirstChild, newChildren, lanes);
        currentDebugInfo = prevDebugInfo;
        return returnFiber;
      }
      if ("function" === typeof newChild.then) return prevDebugInfo =
pushDebugInfo(newChild._debugInfo), returnFiber = reconcileChildFibersImpl(returnFiber,
currentFirstChild, unwrapThenable(newChild), lanes), currentDebugInfo = prevDebugInfo,
returnFiber;
      if (newChild.$$typeof === REACT_CONTEXT_TYPE) return
reconcileChildFibersImpl(returnFiber, currentFirstChild, readContextDuringReconciliation(returnFiber,
newChild), lanes);
      throwOnInvalidObjectType(returnFiber, newChild);
    }
    if ("string" === typeof newChild && "" !== newChild || "number" === typeof newChild || "bigint"
=== typeof newChild) return prevDebugInfo = "" + newChild, null !== currentFirstChild && 6 ===
currentFirstChild.tag ? (deleteRemainingChildren(returnFiber, currentFirstChild.sibling), lanes =
useFiber(currentFirstChild, prevDebugInfo), lanes.return = returnFiber, returnFiber = lanes) :
(deleteRemainingChildren(returnFiber, currentFirstChild), lanes =
createFiberFromText(prevDebugInfo, returnFiber.mode, lanes), lanes.return = returnFiber,
lanes._debugOwner = returnFiber, lanes._debugInfo = currentDebugInfo, returnFiber = lanes),
placeSingleChild(returnFiber);
    "function" === typeof newChild && warnOnFunctionType(returnFiber, newChild);
    "symbol" === typeof newChild && warnOnSymbolType(returnFiber, newChild);
    return deleteRemainingChildren(returnFiber, currentFirstChild);
  }
```

```
    return function (returnFiber, currentFirstChild, newChild, lanes) {
      var prevDebugInfo = currentDebugInfo;
      currentDebugInfo = null;
      try {
        thenableIndexCounter$1 = 0;
        var firstChildFiber = reconcileChildFibersImpl(returnFiber, currentFirstChild, newChild, lanes);
        thenableState$1 = null;
        return firstChildFiber;
      } catch (x) {
        if (x === SuspenseException) throw x;
        var fiber = createFiber(29, x, null, returnFiber.mode);
        fiber.lanes = lanes;
        fiber.return = returnFiber;
        var debugInfo = fiber._debugInfo = currentDebugInfo;
        fiber._debugOwner = returnFiber._debugOwner;
        if (null != debugInfo) for (var i = debugInfo.length - 1; 0 <= i; i--) if ("string" === typeof
debugInfo[i].stack) {
          fiber._debugOwner = debugInfo[i];
          break;
        }
        return fiber;
      } finally {
        currentDebugInfo = prevDebugInfo;
      }
    };
  }
  function pushHiddenContext(fiber, context) {
    var prevEntangledRenderLanes
 = entangledRenderLanes;
    push(prevEntangledRenderLanesCursor, prevEntangledRenderLanes, fiber);
    push(currentTreeHiddenStackCursor, context, fiber);
    entangledRenderLanes = prevEntangledRenderLanes | context.baseLanes;
  }
  function reuseHiddenContextOnStack(fiber) {
    push(prevEntangledRenderLanesCursor, entangledRenderLanes, fiber);
    push(currentTreeHiddenStackCursor, currentTreeHiddenStackCursor.current, fiber);
  }
  function popHiddenContext(fiber) {
    entangledRenderLanes = prevEntangledRenderLanesCursor.current;
    pop(currentTreeHiddenStackCursor, fiber);
    pop(prevEntangledRenderLanesCursor, fiber);
  }
  function pushPrimaryTreeSuspenseHandler(handler) {
    var current = handler.alternate;
    push(suspenseStackCursor, suspenseStackCursor.current & SubtreeSuspenseContextMask, handler);
    push(suspenseHandlerStackCursor, handler, handler);
    null === shellBoundary && (null === current || null !== currentTreeHiddenStackCursor.current ?
shellBoundary = handler : null !== current.memoizedState && (shellBoundary = handler));
  }
```

```
  function pushOffscreenSuspenseHandler(fiber) {
    if (22 === fiber.tag) {
      if (push(suspenseStackCursor, suspenseStackCursor.current, fiber),
push(suspenseHandlerStackCursor, fiber, fiber), null === shellBoundary) {
        var current = fiber.alternate;
        null !== current && null !== current.memoizedState && (shellBoundary = fiber);
      }
    } else reuseSuspenseHandlerOnStack(fiber);
  }
  function reuseSuspenseHandlerOnStack(fiber) {
    push(suspenseStackCursor, suspenseStackCursor.current, fiber);
    push(suspenseHandlerStackCursor, suspenseHandlerStackCursor.current, fiber);
  }
  function popSuspenseHandler(fiber) {
    pop(suspenseHandlerStackCursor, fiber);
    shellBoundary === fiber && (shellBoundary = null);
    pop(suspenseStackCursor, fiber);
  }
  function findFirstSuspended(row) {
    for (var node = row; null !== node;) {
      if (13 === node.tag) {
        var state = node.memoizedState;
        if (null !== state && (state = state.dehydrated, null === state || state.data ===
SUSPENSE_PENDING_START_DATA || state.data === SUSPENSE_FALLBACK_START_DATA))
return node;
      } else if (19 === node.tag && void 0 !== node.memoizedProps.revealOrder) {
        if (0 !== (node.flags & 128)) return node;
      } else if (null !== node.child) {
        node.child.return = node;
        node = node.child;
        continue;
      }
      if (node === row) break;
      for (; null === node.sibling;) {
        if (null === node.return || node.return === row) return null;
        node = node.return;
      }
      node.sibling.return = node.return;
      node = node.sibling;
    }
    return null;
  }
  function createCache() {
    return {
      controller: new AbortControllerLocal(),
      data: new Map(),
      refCount: 0
    };
  }
```

```
  function retainCache(cache) {
    cache.controller.signal.aborted && console.warn("A cache instance was retained after it was already
freed. This likely indicates a bug in React.");
    cache.refCount++;
  }
  function releaseCache(cache) {
    cache.refCount--;
    0 > cache.refCount && console.warn("A cache instance was released after it was already freed. This
likely indicates a bug in React.");
    0 === cache.refCount && scheduleCallback$2(NormalPriority, function () {
      cache.controller.abort();
    });
  }
  function entangleAsyncAction(transition, thenable) {
    if (null === currentEntangledListeners) {
      var entangledListeners = currentEntangledListeners = [];
      currentEntangledPendingCount = 0;
      currentEntangledLane = requestTransitionLane();
      currentEntangledActionThenable = {
        status: "pending",
        value: void 0,
        then: function (resolve) {
          entangledListeners.push(resolve);
        }
      };
    }
    currentEntangledPendingCount++;
    thenable.then(pingEngtangledActionScope, pingEngtangledActionScope);
    return thenable;
  }
  function pingEngtangledActionScope() {
    if (0 === --currentEntangledPendingCount && null !== currentEntangledListeners) {
      null !== currentEntangledActionThenable && (currentEntangledActionThenable.status =
"fulfilled");
      var listeners = currentEntangledListeners;
      currentEntangledListeners = null;
      currentEntangledLane = 0;
      currentEntangledActionThenable = null;
      for (var i = 0; i < listeners.length; i++) (0, listeners[i])();
    }
  }
  function chainThenableValue(thenable, result) {
    var listeners = [],
      thenableWithOverride = {
        status: "pending",
        value: null,
        reason: null,
        then: function (resolve) {
          listeners.push(resolve);
```

```
      }
    };
  thenable.then(function () {
    thenableWithOverride.status = "fulfilled";
    thenableWithOverride.value = result;
    for (var i = 0; i < listeners.length; i++) (0, listeners[i])(result);
  }, function (error) {
    thenableWithOverride.status = "rejected";
    thenableWithOverride.reason = error;
    for (error = 0; error < listeners.length; error++) (0, listeners[error])(void 0);
  });
  return thenableWithOverride;
}
function peekCacheFromPool() {
  var cacheResumedFromPreviousRender = resumedCache.current;
  return null !== cacheResumedFromPreviousRender ? cacheResumedFromPreviousRender :
workInProgressRoot.pooledCache;
}
function pushTransition(offscreenWorkInProgress, prevCachePool) {
  null === prevCachePool ? push(resumedCache, resumedCache.current, offscreenWorkInProgress) :
push(resumedCache, prevCachePool.pool, offscreenWorkInProgress);
}
function getSuspendedCache() {
  var cacheFromPool = peekCacheFromPool();
  return null === cacheFromPool ? null : {
    parent: CacheContext._currentValue,
    pool: cacheFromPool
  };
}
function mountHookTypesDev() {
  var hookName = currentHookNameInDev;
  null === hookTypesDev ? hookTypesDev = [hookName] : hookTypesDev.push(hookName);
}
function updateHookTypesDev() {
  var hookName = currentHookNameInDev;
  if (null !== hookTypesDev && (hookTypesUpdateIndexDev++,
hookTypesDev[hookTypesUpdateIndexDev] !== hookName)) {
    var componentName = getComponentNameFromFiber(currentlyRenderingFiber$1);
    if (!didWarnAboutMismatchedHooksForComponent.has(componentName) &&
(didWarnAboutMismatchedHooksForComponent.add(componentName), null !== hookTypesDev)) {
      for (var table = "", i = 0; i <= hookTypesUpdateIndexDev; i++) {
        var oldHookName = hookTypesDev[i],
          newHookName = i === hookTypesUpdateIndexDev ? hookName : oldHookName;
        for (oldHookName = i + 1 + ". " + oldHookName; 30 > oldHookName.length;) oldHookName
+= " ";
        oldHookName += newHookName + "\n";
        table += oldHookName;
      }
      console.error("React has detected a change in the order of Hooks called by %s. This will lead to
```

```
bugs and errors if not fixed. For more information, read the Rules of Hooks: https://react.dev/link/rules-of-hooks\n\n   Previous render            Next render\n   ------------------------------------------------------\n%s
^^^
```

```
(didWarnAboutAsyncClientComponent.add(nextRenderLanes), console.error("async/await
 is not yet supported in Client Components, only Server Components. This error is often caused by
accidentally adding `'use client'` to a module that was originally written for the server."));
    workInProgress.memoizedState = null;
    workInProgress.updateQueue = null;
    workInProgress.lanes = 0;
    ReactSharedInternals.H = null !== current && null !== current.memoizedState ?
HooksDispatcherOnUpdateInDEV : null !== hookTypesDev ?
HooksDispatcherOnMountWithHookTypesInDEV : HooksDispatcherOnMountInDEV;
    shouldDoubleInvokeUserFnsInHooksDEV = nextRenderLanes = (workInProgress.mode &
StrictLegacyMode) !== NoMode;
    var children = callComponentInDEV(Component, props, secondArg);
    shouldDoubleInvokeUserFnsInHooksDEV = !1;
    didScheduleRenderPhaseUpdateDuringThisPass && (children =
renderWithHooksAgain(workInProgress, Component, props, secondArg));
    if (nextRenderLanes) {
      setIsStrictModeForDevtools(!0);
      try {
        children = renderWithHooksAgain(workInProgress, Component, props, secondArg);
      } finally {
        setIsStrictModeForDevtools(!1);
      }
    }
    finishRenderingHooks(current, workInProgress);
    return children;
  }
  function finishRenderingHooks(current, workInProgress) {
    workInProgress._debugHookTypes = hookTypesDev;
    null === workInProgress.dependencies ? null !== thenableState && (workInProgress.dependencies
= {
      lanes: 0,
      firstContext: null,
      _debugThenableState: thenableState
    }) : workInProgress.dependencies._debugThenableState = thenableState;
    ReactSharedInternals.H = ContextOnlyDispatcher;
    var didRenderTooFewHooks = null !== currentHook && null !== currentHook.next;
    renderLanes = 0;
    hookTypesDev = currentHookNameInDev = workInProgressHook = currentHook =
currentlyRenderingFiber$1 = null;
    hookTypesUpdateIndexDev = -1;
    null !== current && (current.flags & 31457280) !== (workInProgress.flags & 31457280) &&
console.error("Internal React error: Expected static flag was missing. Please notify the React team.");
    didScheduleRenderPhaseUpdate = !1;
    thenableIndexCounter = 0;
    thenableState = null;
    if (didRenderTooFewHooks) throw Error("Rendered fewer hooks than expected. This may be caused
by an accidental early return statement.");
    null === current || didReceiveUpdate || (current = current.dependencies, null !== current &&
checkIfContextChanged(current) && (didReceiveUpdate = !0));
```

```
    needsToResetSuspendedThenableDEV ? (needsToResetSuspendedThenableDEV = !1, current = !0) :
current = !1;
    current && (workInProgress = getComponentNameFromFiber(workInProgress) || "Unknown",
didWarnAboutUseWrappedInTryCatch.has(workInProgress) ||
didWarnAboutAsyncClientComponent.has(workInProgress) ||
(didWarnAboutUseWrappedInTryCatch.add(workInProgress), console.error("`use` was called from
inside a try/catch block. This is not allowed and can lead to unexpected behavior. To handle errors
triggered by `use`, wrap your component in a error boundary.")));
  }
  function renderWithHooksAgain(workInProgress, Component, props, secondArg) {
    currentlyRenderingFiber$1 = workInProgress;
    var numberOfReRenders = 0;
    do {
      didScheduleRenderPhaseUpdateDuringThisPass && (thenableState = null);
      thenableIndexCounter = 0;
      didScheduleRenderPhaseUpdateDuringThisPass = !1;
      if (numberOfReRenders >= RE_RENDER_LIMIT) throw Error("Too many re-renders. React limits
the number of renders to prevent an infinite loop.");
      numberOfReRenders += 1;
      ignorePreviousDependencies = !1;
      workInProgressHook = currentHook = null;
      if (null != workInProgress.updateQueue) {
        var children = workInProgress.updateQueue;
        children.lastEffect = null;
        children.events = null;
        children.stores = null;
        null != children.memoCache && (children.memoCache.index = 0);
      }
      hookTypesUpdateIndexDev = -1;
      ReactSharedInternals.H = HooksDispatcherOnRerenderInDEV;
      children = callComponentInDEV(Component, props, secondArg);
    } while (didScheduleRenderPhaseUpdateDuringThisPass);
    return children;
  }
  function TransitionAwareHostComponent() {
    var dispatcher = ReactSharedInternals.H,
      maybeThenable = dispatcher.useState()[0];
    maybeThenable = "function" === typeof maybeThenable.then ? useThenable(maybeThenable) :
maybeThenable;
    dispatcher = dispatcher.useState()[0];
    (null !== currentHook ? currentHook.memoizedState : null) !== dispatcher &&
(currentlyRenderingFiber$1.flags |= 1024);
    return maybeThenable;
  }
  function checkDidRenderIdHook() {
    var didRenderIdHook = 0 !== localIdCounter;
    localIdCounter = 0;
    return didRenderIdHook;
  }
```

```
  function bailoutHooks(current, workInProgress, lanes) {
    workInProgress.updateQueue = current.updateQueue;
    workInProgress.flags = (workInProgress.mode & StrictEffectsMode) !== NoMode ?
workInProgress.flags & -201328645 : workInProgress.flags & -2053;
    current.lanes &= ~lanes;
  }
  function resetHooksOnUnwind(workInProgress) {
    if (didScheduleRenderPhaseUpdate) {
      for (workInProgress = workInProgress.memoizedState; null !== workInProgress;) {
        var queue = workInProgress.queue;
        null !== queue && (queue.pending = null);
        workInProgress = workInProgress.next;
      }
      didScheduleRenderPhaseUpdate = !1;
    }
    renderLanes = 0;
    hookTypesDev = workInProgressHook = currentHook = currentlyRenderingFiber$1 = null;
    hookTypesUpdateIndexDev = -1;
    currentHookNameInDev = null;
    didScheduleRenderPhaseUpdateDuringThisPass = !1;
    thenableIndexCounter = localIdCounter = 0;
    thenableState = null;
  }
  function mountWorkInProgressHook() {
    var hook = {
      memoizedState: null,
      baseState: null,
      baseQueue: null,
      queue: null,
      next: null
    };
    null === workInProgressHook ? currentlyRenderingFiber$1.memoizedState = workInProgressHook
= hook : workInProgressHook = workInProgressHook.next = hook;
    return workInProgressHook;
  }
  function updateWorkInProgressHook() {
    if (null === currentHook) {
      var nextCurrentHook = currentlyRenderingFiber$1.alternate;
      nextCurrentHook = null !== nextCurrentHook ? nextCurrentHook.memoizedState : null;
    } else nextCurrentHook = currentHook.next;
    var nextWorkInProgressHook = null === workInProgressHook ?
currentlyRenderingFiber$1.memoizedState : workInProgressHook.next;
    if (null !== nextWorkInProgressHook) workInProgressHook = nextWorkInProgressHook,
currentHook = nextCurrentHook;else {
      if (null === nextCurrentHook) {
        if (null === currentlyRenderingFiber$1.alternate) throw Error("Update hook called on initial
render. This is likely a bug in React. Please file an issue.");
        throw Error("Rendered more hooks than during the previous render.");
      }
```

```
      currentHook = nextCurrentHook;
      nextCurrentHook = {
        memoizedState: currentHook.memoizedState,
        baseState: currentHook.baseState,
        baseQueue: currentHook.baseQueue,
        queue: currentHook.queue,
        next: null
      };
      null === workInProgressHook ? currentlyRenderingFiber$1.memoizedState =
workInProgressHook = nextCurrentHook : workInProgressHook = workInProgressHook.next =
nextCurrentHook;
    }
    return workInProgressHook;
  }
  function useThenable(thenable) {
    var index = thenableIndexCounter;
    thenableIndexCounter += 1;
    null === thenableState && (thenableState = createThenableState());
    thenable = trackUsedThenable(thenableState, thenable, index);
    index = currentlyRenderingFiber$1;
    null === (null === workInProgressHook ? index.memoizedState : workInProgressHook.next) &&
(index = index.alternate, ReactSharedInternals.H = null !== index && null !== index.memoizedState ?
HooksDispatcherOnUpdateInDEV : HooksDispatcherOnMountInDEV);
    return thenable;
  }
  function use(usable) {
    if (null !== usable && "object" === typeof usable) {
      if ("function" === typeof usable.then) return useThenable(usable);
      if (usable.$$typeof === REACT_CONTEXT_TYPE) return readContext(usable);
    }
    throw Error("An unsupported type was passed to use(): " + String(usable));
  }
  function useMemoCache(size) {
    var memoCache = null,
      updateQueue = currentlyRenderingFiber$1.updateQueue;
    null !== updateQueue && (memoCache = updateQueue.memoCache);
    if (null == memoCache) {
      var current = currentlyRenderingFiber$1.alternate;
      null !== current && (current = current.updateQueue, null !== current && (current =
current.memoCache, null != current && (memoCache = {
        data: current.data.map(function (array) {
          return array.slice();
        }),
        index: 0
      })));
    }
    null == memoCache && (memoCache = {
      data: [],
      index: 0
```

```
    });
    null === updateQueue && (updateQueue = createFunctionComponentUpdateQueue(),
currentlyRenderingFiber$1.updateQueue = updateQueue);
    updateQueue.memoCache = memoCache;
    updateQueue = memoCache.data[memoCache.index];
    if (void 0 === updateQueue || ignorePreviousDependencies) for (updateQueue =
memoCache.data[memoCache.index] = Array(size), current = 0; current < size; current++)
updateQueue[current] = REACT_MEMO_CACHE_SENTINEL;else updateQueue.length !== size &&
console.error("Expected a constant size argument for each invocation of useMemoCache. The previous
cache was allocated with size %s but size %s was requested.", updateQueue.length, size);
    memoCache.index++;
    return updateQueue;
  }
  function basicStateReducer(state, action) {
    return "function" === typeof action ? action(state) : action;
  }
  function mountReducer(reducer, initialArg, init) {
    var hook = mountWorkInProgressHook();
    if (void 0 !== init) {
      var initialState = init(initialArg);
      if (shouldDoubleInvokeUserFnsInHooksDEV) {
        setIsStrictModeForDevtools(!0);

        try {
          init(initialArg);
        } finally {
          setIsStrictModeForDevtools(!1);
        }
      }
    } else initialState = initialArg;
    hook.memoizedState = hook.baseState = initialState;
    reducer = {
      pending: null,
      lanes: 0,
      dispatch: null,
      lastRenderedReducer: reducer,
      lastRenderedState: initialState
    };
    hook.queue = reducer;
    reducer = reducer.dispatch = dispatchReducerAction.bind(null, currentlyRenderingFiber$1, reducer);
    return [hook.memoizedState, reducer];
  }
  function updateReducer(reducer) {
    var hook = updateWorkInProgressHook();
    return updateReducerImpl(hook, currentHook, reducer);
  }
  function updateReducerImpl(hook, current, reducer) {
    var queue = hook.queue;
    if (null === queue) throw Error("Should have a queue. You are likely calling Hooks conditionally,
```

```
which is not allowed. (https://react.dev/link/invalid-hook-call)");
    queue.lastRenderedReducer = reducer;
    var baseQueue = hook.baseQueue,
      pendingQueue = queue.pending;
    if (null !== pendingQueue) {
      if (null !== baseQueue) {
        var baseFirst = baseQueue.next;
        baseQueue.next = pendingQueue.next;
        pendingQueue.next = baseFirst;
      }
      current.baseQueue !== baseQueue && console.error("Internal error: Expected work-in-progress
queue to be a clone. This is a bug in React.");
      current.baseQueue = baseQueue = pendingQueue;
      queue.pending = null;
    }
    pendingQueue = hook.baseState;
    if (null === baseQueue) hook.memoizedState = pendingQueue;else {
      current = baseQueue.next;
      var newBaseQueueFirst = baseFirst = null,
        newBaseQueueLast = null,
        update = current,
        didReadFromEntangledAsyncAction = !1;
      do {
        var updateLane = update.lane & -536870913;
        if (updateLane !== update.lane ? (workInProgressRootRenderLanes & updateLane) ===
updateLane : (renderLanes & updateLane) === updateLane) {
          var revertLane = update.revertLane;
          if (0 === revertLane) null !== newBaseQueueLast && (newBaseQueueLast =
newBaseQueueLast.next = {
            lane: 0,
            revertLane: 0,
            action: update.action,
            hasEagerState: update.hasEagerState,
            eagerState: update.eagerState,
            next: null
          }), updateLane === currentEntangledLane && (didReadFromEntangledAsyncAction = !0);else
if ((renderLanes & revertLane) === revertLane) {
            update = update.next;
            revertLane === currentEntangledLane && (didReadFromEntangledAsyncAction = !0);
            continue;
          } else updateLane = {
            lane: 0,
            revertLane: update.revertLane,
            action: update.action,
            hasEagerState: update.hasEagerState,
            eagerState: update.eagerState,
            next: null
          }, null === newBaseQueueLast ? (newBaseQueueFirst = newBaseQueueLast = updateLane,
baseFirst = pendingQueue) : newBaseQueueLast = newBaseQueueLast.next = updateLane,
```

```
currentlyRenderingFiber$1.lanes |= revertLane, workInProgressRootSkippedLanes |= revertLane;
          updateLane = update.action;
          shouldDoubleInvokeUserFnsInHooksDEV && reducer(pendingQueue, updateLane);
          pendingQueue = update.hasEagerState ? update.eagerState : reducer(pendingQueue,
updateLane);
        } else revertLane = {
          lane: updateLane,
          revertLane: update.revertLane,
          action: update.action,
          hasEagerState: update.hasEagerState,
          eagerState: update.eagerState,
          next: null
        }, null === newBaseQueueLast ? (newBaseQueueFirst = newBaseQueueLast = revertLane,
baseFirst = pendingQueue) : newBaseQueueLast = newBaseQueueLast.next = revertLane,
currentlyRenderingFiber$1.lanes |= updateLane, workInProgressRootSkippedLanes |= updateLane;
        update = update.next;
      } while (null !== update && update !== current);
      null === newBaseQueueLast ? baseFirst = pendingQueue : newBaseQueueLast.next =
newBaseQueueFirst;
      if (!objectIs(pendingQueue, hook.memoizedState) && (didReceiveUpdate = !0,
didReadFromEntangledAsyncAction && (reducer = currentEntangledActionThenable, null !==
reducer))) throw reducer;
      hook.memoizedState = pendingQueue;
      hook.baseState = baseFirst;
      hook.baseQueue = newBaseQueueLast;
      queue.lastRenderedState = pendingQueue;
    }
    null === baseQueue && (queue.lanes = 0);
    return [hook.memoizedState, queue.dispatch];
  }
  function rerenderReducer(reducer) {
    var hook = updateWorkInProgressHook(),
      queue = hook.queue;
    if (null === queue) throw Error("Should have a queue. You are likely calling Hooks conditionally,
which is not allowed. (https://react.dev/link/invalid-hook-call)");
    queue.lastRenderedReducer = reducer;
    var dispatch = queue.dispatch,
      lastRenderPhaseUpdate = queue.pending,
      newState = hook.memoizedState;
    if (null !== lastRenderPhaseUpdate) {
      queue.pending = null;
      var update = lastRenderPhaseUpdate = lastRenderPhaseUpdate.next;
      do newState = reducer(newState, update.action), update = update.next; while (update !==
lastRenderPhaseUpdate);
      objectIs(newState, hook.memoizedState) || (didReceiveUpdate = !0);
      hook.memoizedState = newState;
      null === hook.baseQueue && (hook.baseState = newState);
      queue.lastRenderedState = newState;
    }
```

```
    return [newState, dispatch];
  }
  function mountSyncExternalStore(subscribe, getSnapshot, getServerSnapshot) {
    var fiber = currentlyRenderingFiber$1,
      hook = mountWorkInProgressHook();
    if (isHydrating) {
      if (void 0 === getServerSnapshot) throw Error("Missing getServerSnapshot, which is required for server-rendered content. Will revert to client rendering.");
      var nextSnapshot = getServerSnapshot();
      didWarnUncachedGetSnapshot || nextSnapshot === getServerSnapshot() || (console.error("The result of getServerSnapshot should be cached to avoid an infinite loop"), didWarnUncachedGetSnapshot = !0);
    } else {
      nextSnapshot = getSnapshot();
      didWarnUncachedGetSnapshot || (getServerSnapshot = getSnapshot(), objectIs(nextSnapshot, getServerSnapshot) || (console.error("The result of getSnapshot should be cached to avoid an infinite loop"), didWarnUncachedGetSnapshot = !0));
      if (null === workInProgressRoot) throw Error("Expected a work-in-progress root. This is a bug in React. Please file an issue.");
      0 !== (workInProgressRootRenderLanes & 60) || pushStoreConsistencyCheck(fiber, getSnapshot, nextSnapshot);
    }
    hook.memoizedState = nextSnapshot;
    getServerSnapshot = {
      value: nextSnapshot,
      getSnapshot: getSnapshot
    };
    hook.queue = getServerSnapshot;
    mountEffect(subscribeToStore.bind(null, fiber, getServerSnapshot, subscribe), [subscribe]);
    fiber.flags |= 2048;
    pushEffect(HasEffect | Passive, updateStoreInstance.bind(null, fiber, getServerSnapshot, nextSnapshot, getSnapshot), {
      destroy: void 0
    }, null);
    return nextSnapshot;
  }
  function updateSyncExternalStore(subscribe, getSnapshot, getServerSnapshot) {
    var fiber = currentlyRenderingFiber$1,
      hook = updateWorkInProgressHook(),
      isHydrating$jscomp$0 = isHydrating;
    if (isHydrating$jscomp$0) {
      if (void 0 === getServerSnapshot) throw Error("Missing getServerSnapshot, which is required for server-rendered content. Will revert to client rendering.");
      getServerSnapshot = getServerSnapshot();
    } else if (getServerSnapshot = getSnapshot(), !didWarnUncachedGetSnapshot) {
      var cachedSnapshot = getSnapshot();
      objectIs(getServerSnapshot, cachedSnapshot) || (console.error("The result of getSnapshot should be cached to avoid an infinite loop"), didWarnUncachedGetSnapshot = !0);
    }
```

```
    if (cachedSnapshot = !objectIs((currentHook || hook).memoizedState, getServerSnapshot))
hook.memoizedState = getServerSnapshot, didReceiveUpdate = !0;
    hook = hook.queue;
    var create = subscribeToStore.bind(null, fiber, hook, subscribe);
    updateEffectImpl(2048, Passive, create, [subscribe]);
    if (hook.getSnapshot !== getSnapshot || cachedSnapshot || null !== workInProgressHook &&
workInProgressHook.memoizedState.tag & HasEffect) {
      fiber.flags |= 2048;
      pushEffect(HasEffect | Passive, updateStoreInstance.bind(null, fiber, hook, getServerSnapshot,
getSnapshot), {
        destroy: void 0
      }, null);
      if (null === workInProgressRoot) throw Error("Expected a work-in-progress root. This is a bug in
React. Please file an issue.");
      isHydrating$jscomp$0 || 0 !== (renderLanes & 60) || pushStoreConsistencyCheck(fiber,
getSnapshot, getServerSnapshot);
    }
    return getServerSnapshot;
  }
  function pushStoreConsistencyCheck(fiber, getSnapshot, renderedSnapshot) {
    fiber.flags |= 16384;
    fiber = {
      getSnapshot: getSnapshot,
      value: renderedSnapshot
    };
    getSnapshot = currentlyRenderingFiber$1.updateQueue;
    null === getSnapshot ? (getSnapshot = createFunctionComponentUpdateQueue(),
currentlyRenderingFiber$1.updateQueue = getSnapshot, getSnapshot.stores = [fiber]) :
(renderedSnapshot = getSnapshot.stores, null === renderedSnapshot ? getSnapshot.stores = [fiber] :
renderedSnapshot.push(fiber));
  }
  function updateStoreInstance(fiber, inst, nextSnapshot, getSnapshot) {
    inst.value = nextSnapshot;
    inst.getSnapshot = getSnapshot;
    checkIfSnapshotChanged(inst) && forceStoreRerender(fiber);
  }
  function subscribeToStore(fiber, inst, subscribe) {
    return subscribe(function () {
      checkIfSnapshotChanged(inst) && forceStoreRerender(fiber);
    });
  }
  function checkIfSnapshotChanged(inst) {
    var latestGetSnapshot = inst.getSnapshot;
    inst = inst.value;
    try {
      var nextValue = latestGetSnapshot();
      return !objectIs(inst, nextValue);
    }
 catch (error) {
```

```
    return !0;
  }
}
function forceStoreRerender(fiber) {
  var root = enqueueConcurrentRenderForLane(fiber, 2);
  null !== root && scheduleUpdateOnFiber(root, fiber, 2);
}
function mountStateImpl(initialState) {
  var hook = mountWorkInProgressHook();
  if ("function" === typeof initialState) {
    var initialStateInitializer = initialState;
    initialState = initialStateInitializer();
    if (shouldDoubleInvokeUserFnsInHooksDEV) {
      setIsStrictModeForDevtools(!0);
      try {
        initialStateInitializer();
      } finally {
        setIsStrictModeForDevtools(!1);
      }
    }
  }
  hook.memoizedState = hook.baseState = initialState;
  hook.queue = {
    pending: null,
    lanes: 0,
    dispatch: null,
    lastRenderedReducer: basicStateReducer,
    lastRenderedState: initialState
  };
  return hook;
}
function mountState(initialState) {
  initialState = mountStateImpl(initialState);
  var queue = initialState.queue,
    dispatch = dispatchSetState.bind(null, currentlyRenderingFiber$1, queue);
  queue.dispatch = dispatch;
  return [initialState.memoizedState, dispatch];
}
function mountOptimistic(passthrough) {
  var hook = mountWorkInProgressHook();
  hook.memoizedState = hook.baseState = passthrough;
  var queue = {
    pending: null,
    lanes: 0,
    dispatch: null,
    lastRenderedReducer: null,
    lastRenderedState: null
  };
  hook.queue = queue;
```

```
    hook = dispatchOptimisticSetState.bind(null, currentlyRenderingFiber$1, !0, queue);
    queue.dispatch = hook;
    return [passthrough, hook];
  }
  function updateOptimistic(passthrough, reducer) {
    var hook = updateWorkInProgressHook();
    return updateOptimisticImpl(hook, currentHook, passthrough, reducer);
  }
  function updateOptimisticImpl(hook, current, passthrough, reducer) {
    hook.baseState = passthrough;
    return updateReducerImpl(hook, currentHook, "function" === typeof reducer ? reducer :
basicStateReducer);
  }
  function rerenderOptimistic(passthrough, reducer) {
    var hook = updateWorkInProgressHook();
    if (null !== currentHook) return updateOptimisticImpl(hook, currentHook, passthrough, reducer);
    hook.baseState = passthrough;
    return [passthrough, hook.queue.dispatch];
  }
  function dispatchActionState(fiber, actionQueue, setPendingState, setState, payload) {
    if (isRenderPhaseUpdate(fiber)) throw Error("Cannot update form state while rendering.");
    fiber = actionQueue.action;
    if (null !== fiber) {
      var actionNode = {
        payload: payload,
        action: fiber,
        next: null,
        isTransition: !0,
        status: "pending",
        value: null,
        reason: null,
        listeners: [],
        then: function (listener) {
          actionNode.listeners.push(listener);
        }
      };
      null !== ReactSharedInternals.T ? setPendingState(!0) : actionNode.isTransition = !1;
      setState(actionNode);
      setPendingState = actionQueue.pending;
      null === setPendingState ? (actionNode.next = actionQueue.pending = actionNode,
runActionStateAction(actionQueue, actionNode)) : (actionNode.next = setPendingState.next,
actionQueue.pending = setPendingState.next = actionNode);
    }
  }
  function runActionStateAction(actionQueue, node) {
    var action = node.action,
      payload = node.payload,
      prevState = actionQueue.state;
    if (node.isTransition) {
```

```
      var prevTransition = ReactSharedInternals.T,
        currentTransition = {};
      ReactSharedInternals.T = currentTransition;
      ReactSharedInternals.T._updatedFibers = new Set();
      try {
        var returnValue = action(prevState, payload),
          onStartTransitionFinish = ReactSharedInternals.S;
        null !== onStartTransitionFinish && onStartTransitionFinish(currentTransition, returnValue);
        handleActionReturnValue(actionQueue, node, returnValue);
      } catch (error) {
        onActionError(actionQueue, node, error);
      } finally {
        ReactSharedInternals.T = prevTransition, null === prevTransition &&
currentTransition._updatedFibers && (actionQueue = currentTransition._updatedFibers.size,
currentTransition._updatedFibers.clear(), 10 < actionQueue && console.warn("Detected a large
number of updates inside startTransition. If this is due to a subscription please re-write it to use React
provided hooks. Otherwise concurrent mode guarantees are off the table."));
      }
    } else try {
      currentTransition = action(prevState, payload), handleActionReturnValue(actionQueue, node,
currentTransition);
    } catch (error$3) {
      onActionError(actionQueue, node, error$3);
    }
  }
  function handleActionReturnValue(actionQueue, node, returnValue) {
    null !== returnValue && "object" === typeof returnValue && "function" === typeof
returnValue.then ? (returnValue.then(function (nextState) {
      onActionSuccess(actionQueue, node, nextState);
    }, function (error) {
      return onActionError(actionQueue, node, error);
    }), node.isTransition || console.error("An async function was passed to useActionState, but it was
dispatched outside of an action context. This is likely not what you intended. Either pass the dispatch
function to an `action` prop, or dispatch manually inside `startTransition`")) :
onActionSuccess(actionQueue, node, returnValue);
  }
  function onActionSuccess(actionQueue, actionNode, nextState) {
    actionNode.status = "fulfilled";
    actionNode.value = nextState;
    notifyActionListeners(actionNode);
    actionQueue.state = nextState;
    actionNode = actionQueue.pending;
    null !== actionNode && (nextState = actionNode.next, nextState === actionNode ?
actionQueue.pending = null : (nextState = nextState.next, actionNode.next = nextState,
runActionStateAction(actionQueue, nextState)));
  }
  function onActionError(actionQueue, actionNode, error) {
    var last = actionQueue.pending;
    actionQueue.pending = null;
```

```
    if (null !== last) {
      last = last.next;
      do actionNode.status = "rejected", actionNode.reason = error, notifyActionListeners(actionNode),
actionNode = actionNode.next; while (actionNode !== last);
    }
    actionQueue.action = null;
  }
  function notifyActionListeners(actionNode) {
    actionNode = actionNode.listeners;
    for (var i = 0; i < actionNode.length; i++) (0, actionNode[i])();
  }
  function actionStateReducer(oldState, newState) {
    return newState;
  }
  function mountActionState(action, initialStateProp) {
    if (isHydrating) {
      var ssrFormState = workInProgressRoot.formState;
      if (null !== ssrFormState) {
        a: {
          var isMatching = currentlyRenderingFiber$1;
          if (isHydrating) {
            if (nextHydratableInstance) {
              b: {
                var markerInstance = nextHydratableInstance;
                for (var inRootOrSingleton = rootOrSingletonContext; 8 !== markerInstance.nodeType;) {
                  if (!inRootOrSingleton) {
                    markerInstance = null;
                    break b;
                  }
                  markerInstance = getNextHydratable(markerInstance.nextSibling);
                  if (null === markerInstance) {
                    markerInstance = null;
                    break b;
                  }
                }
                inRootOrSingleton = markerInstance.data;
                markerInstance = inRootOrSingleton === FORM_STATE_IS_MATCHING ||
inRootOrSingleton === FORM_STATE_IS_NOT_MATCHING ? markerInstance : null;
              }
              if (markerInstance) {
                nextHydratableInstance = getNextHydratable(markerInstance.nextSibling);
                isMatching = markerInstance.data === FORM_STATE_IS_MATCHING;
                break a;
              }
            }
            throwOnHydrationMismatch(isMatching);
          }
          isMatching = !1;
        }
```

```
      isMatching && (initialStateProp = ssrFormState[0]);
    }
  }
  ssrFormState = mountWorkInProgressHook();
  ssrFormState.memoizedState = ssrFormState.baseState = initialStateProp;
  isMatching = {
    pending: null,
    lanes: 0,
    dispatch: null,
    lastRenderedReducer: actionStateReducer,
    lastRenderedState: initialStateProp
  };
  ssrFormState.queue = isMatching;
  ssrFormState = dispatchSetState.bind(null, currentlyRenderingFiber$1, isMatching);
  isMatching.dispatch = ssrFormState;
  isMatching = mountStateImpl(!1);
  inRootOrSingleton = dispatchOptimisticSetState.bind(null, currentlyRenderingFiber$1, !1,
isMatching.queue);
  isMatching = mountWorkInProgressHook();
  markerInstance = {
    state: initialStateProp,
    dispatch: null,
    action: action,
    pending: null
  };
  isMatching.queue = markerInstance;
  ssrFormState = dispatchActionState.bind(null, currentlyRenderingFiber$1, markerInstance,
inRootOrSingleton, ssrFormState);
  markerInstance.dispatch = ssrFormState;
  isMatching.memoizedState = action;
  return [initialStateProp, ssrFormState, !1];
}
function updateActionState(action) {
  var stateHook = updateWorkInProgressHook();
  return updateActionStateImpl(stateHook, currentHook, action);
}
function updateActionStateImpl(stateHook, currentStateHook, action) {
  currentStateHook = updateReducerImpl(stateHook, currentStateHook, actionStateReducer)[0];
  stateHook = updateReducer(basicStateReducer)[0];
  currentStateHook = "object" === typeof currentStateHook && null !== currentStateHook &&
"function" === typeof currentStateHook.then ? useThenable(currentStateHook) : currentStateHook;
  var actionQueueHook = updateWorkInProgressHook(),
    actionQueue = actionQueueHook.queue,
    dispatch = actionQueue.dispatch;
  action !== actionQueueHook.memoizedState && (currentlyRenderingFiber$1.flags |= 2048,
pushEffect(HasEffect
| Passive, actionStateActionEffect.bind(null, actionQueue, action), {
    destroy: void 0
  }, null));
```

```
    return [currentStateHook, dispatch, stateHook];
  }
  function actionStateActionEffect(actionQueue, action) {
    actionQueue.action = action;
  }
  function rerenderActionState(action) {
    var stateHook = updateWorkInProgressHook(),
      currentStateHook = currentHook;
    if (null !== currentStateHook) return updateActionStateImpl(stateHook, currentStateHook, action);
    updateWorkInProgressHook();
    stateHook = stateHook.memoizedState;
    currentStateHook = updateWorkInProgressHook();
    var dispatch = currentStateHook.queue.dispatch;
    currentStateHook.memoizedState = action;
    return [stateHook, dispatch, !1];
  }
  function pushEffect(tag, create, inst, deps) {
    tag = {
      tag: tag,
      create: create,
      inst: inst,
      deps: deps,
      next: null
    };
    create = currentlyRenderingFiber$1.updateQueue;
    null === create && (create = createFunctionComponentUpdateQueue(),
currentlyRenderingFiber$1.updateQueue = create);
    inst = create.lastEffect;
    null === inst ? create.lastEffect = tag.next = tag : (deps = inst.next, inst.next = tag, tag.next = deps,
create.lastEffect = tag);
    return tag;
  }
  function mountRef(initialValue) {
    var hook = mountWorkInProgressHook();
    initialValue = {
      current: initialValue
    };
    return hook.memoizedState = initialValue;
  }
  function mountEffectImpl(fiberFlags, hookFlags, create, deps) {
    var hook = mountWorkInProgressHook();
    currentlyRenderingFiber$1.flags |= fiberFlags;
    hook.memoizedState = pushEffect(HasEffect | hookFlags, create, {
      destroy: void 0
    }, void 0 === deps ? null : deps);
  }
  function updateEffectImpl(fiberFlags, hookFlags, create, deps) {
    var hook = updateWorkInProgressHook();
    deps = void 0 === deps ? null : deps;
```

```
    var inst = hook.memoizedState.inst;
    null !== currentHook && null !== deps && areHookInputsEqual(deps,
currentHook.memoizedState.deps) ? hook.memoizedState = pushEffect(hookFlags, create, inst, deps) :
(currentlyRenderingFiber$1.flags |= fiberFlags, hook.memoizedState = pushEffect(HasEffect |
hookFlags, create, inst, deps));
  }
  function mountEffect(create, deps) {
    (currentlyRenderingFiber$1.mode & StrictEffectsMode) !== NoMode &&
(currentlyRenderingFiber$1.mode & NoStrictPassiveEffectsMode) === NoMode ?
mountEffectImpl(142608384, Passive, create, deps) : mountEffectImpl(8390656, Passive, create,
deps);
  }
  function mountLayoutEffect(create, deps) {
    var fiberFlags = 4194308;
    (currentlyRenderingFiber$1.mode & StrictEffectsMode) !== NoMode && (fiberFlags |= 67108864);
    return mountEffectImpl(fiberFlags, Layout, create, deps);
  }
  function imperativeHandleEffect(create, ref) {
    if ("function" === typeof ref) {
      create = create();
      var refCleanup = ref(create);
      return function () {
        "function" === typeof refCleanup ? refCleanup() : ref(null);
      };
    }
    if (null !== ref && void 0 !== ref) return ref.hasOwnProperty("current") || console.error("Expected
useImperativeHandle() first argument to either be a ref callback or React.createRef() object. Instead
received: %s.", "an object with keys {" + Object.keys(ref).join(", ") + "}"), create = create(), ref.current
= create, function () {
      ref.current = null;
    };
  }
  function mountImperativeHandle(ref, create, deps) {
    "function" !== typeof create && console.error("Expected useImperativeHandle() second argument
to be a function that creates a handle. Instead received: %s.", null !== create ? typeof create : "null");
    deps = null !== deps && void 0 !== deps ? deps.concat([ref]) : null;
    var fiberFlags = 4194308;
    (currentlyRenderingFiber$1.mode & StrictEffectsMode) !== NoMode && (fiberFlags |= 67108864);
    mountEffectImpl(fiberFlags, Layout, imperativeHandleEffect.bind(null, create, ref), deps);
  }
  function updateImperativeHandle(ref, create, deps) {
    "function" !== typeof create && console.error("Expected useImperativeHandle() second argument
to be a function that creates a handle. Instead received: %s.", null !== create ? typeof create : "null");
    deps = null !== deps && void 0 !== deps ? deps.concat([ref]) : null;
    updateEffectImpl(4, Layout, imperativeHandleEffect.bind(null, create, ref), deps);
  }
  function mountCallback(callback, deps) {
    mountWorkInProgressHook().memoizedState = [callback, void 0 === deps ? null : deps];
    return callback;
```

```
}
function updateCallback(callback, deps) {
  var hook = updateWorkInProgressHook();
  deps = void 0 === deps ? null : deps;
  var prevState = hook.memoizedState;
  if (null !== deps && areHookInputsEqual(deps, prevState[1])) return prevState[0];
  hook.memoizedState = [callback, deps];
  return callback;
}
function mountMemo(nextCreate, deps) {
  var hook = mountWorkInProgressHook();
  deps = void 0 === deps ? null : deps;
  var nextValue = nextCreate();
  if (shouldDoubleInvokeUserFnsInHooksDEV) {
    setIsStrictModeForDevtools(!0);
    try {
      nextCreate();
    } finally {
      setIsStrictModeForDevtools(!1);
    }
  }
  hook.memoizedState = [nextValue, deps];
  return nextValue;
}
function updateMemo(nextCreate, deps) {
  var hook = updateWorkInProgressHook();
  deps = void 0 === deps ? null : deps;
  var prevState = hook.memoizedState;
  if (null !== deps && areHookInputsEqual(deps, prevState[1])) return prevState[0];
  prevState = nextCreate();
  if (shouldDoubleInvokeUserFnsInHooksDEV) {
    setIsStrictModeForDevtools(!0);
    try {
      nextCreate();
    } finally {
      setIsStrictModeForDevtools(!1);
    }
  }
  hook.memoizedState = [prevState, deps];
  return prevState;
}
function mountDeferredValue(value, initialValue) {
  var hook = mountWorkInProgressHook();
  return mountDeferredValueImpl(hook, value, initialValue);
}
function updateDeferredValue(value, initialValue) {
  var hook = updateWorkInProgressHook();
  return updateDeferredValueImpl(hook, currentHook.memoizedState, value, initialValue);
}
```

```
  function rerenderDeferredValue(value, initialValue) {
    var hook = updateWorkInProgressHook();
    return null === currentHook ? mountDeferredValueImpl(hook, value, initialValue) :
updateDeferredValueImpl(hook, currentHook.memoizedState, value, initialValue);
  }
  function mountDeferredValueImpl(hook, value, initialValue) {
    if (void 0 === initialValue || 0 !== (renderLanes & 1073741824)) return hook.memoizedState =
value;
    hook.memoizedState = initialValue;
    hook = requestDeferredLane();
    currentlyRenderingFiber$1.lanes |= hook;
    workInProgressRootSkippedLanes |= hook;
    return initialValue;
  }
  function updateDeferredValueImpl(hook, prevValue, value, initialValue) {
    if (objectIs(value, prevValue)) return value;
    if (null !== currentTreeHiddenStackCursor.current) return hook = mountDeferredValueImpl(hook,
value, initialValue), objectIs(hook, prevValue) || (didReceiveUpdate = !0), hook;
    if (0 === (renderLanes & 42)) return didReceiveUpdate = !0, hook.memoizedState = value;
    hook = requestDeferredLane();
    currentlyRenderingFiber$1.lanes |= hook;
    workInProgressRootSkippedLanes |= hook;
    return prevValue;
  }
  function startTransition(fiber, queue, pendingState, finishedState, callback) {
    var previousPriority = ReactDOMSharedInternals.p;
    ReactDOMSharedInternals.p = 0 !== previousPriority && previousPriority <
ContinuousEventPriority ? previousPriority : ContinuousEventPriority;
    var prevTransition = ReactSharedInternals.T,
      currentTransition = {};
    ReactSharedInternals.T = currentTransition;
    dispatchOptimisticSetState(fiber, !1, queue, pendingState);
    currentTransition._updatedFibers = new Set();
    try {
      var returnValue = callback(),
        onStartTransitionFinish = ReactSharedInternals.S;
      null !== onStartTransitionFinish && onStartTransitionFinish(currentTransition, returnValue);
      if (null !== returnValue && "object" === typeof returnValue && "function" === typeof
returnValue.then) {
        var thenableForFinishedState = chainThenableValue(returnValue, finishedState);
        dispatchSetStateInternal(fiber, queue, thenableForFinishedState, requestUpdateLane(fiber));
      } else dispatchSetStateInternal(fiber, queue, finishedState, requestUpdateLane(fiber));
    } catch (error) {
      dispatchSetStateInternal(fiber, queue, {
        then: function () {},
        status: "rejected",
        reason: error
      }, requestUpdateLane(fiber));
    } finally {
```

```
    ReactDOMSharedInternals.p = previousPriority, ReactSharedInternals.T = prevTransition, null ===
prevTransition && currentTransition._updatedFibers && (fiber =
currentTransition._updatedFibers.size, currentTransition._updatedFibers.clear(), 10 < fiber &&
console.warn("Detected a large number of updates inside startTransition. If this is due to a subscription
please re-write it to use React provided hooks. Otherwise concurrent mode guarantees are off the
table."));
   }
  }
  function startHostTransition(formFiber, pendingState, action, formData) {
   if (5 !== formFiber.tag) throw Error("Expected the form instance to be a HostComponent. This is a
bug in React.");
   var queue = ensureFormComponentIsStateful(formFiber).queue;
   startTransition(formFiber, queue, pendingState, NotPendingTransition, null === action ? noop$2 :
function () {
    requestFormReset$1(formFiber);
    return action(formData);
   });
  }
  function ensureFormComponentIsStateful(formFiber) {
   var existingStateHook = formFiber.memoizedState;
   if (null !== existingStateHook) return existingStateHook;
   existingStateHook = {
    memoizedState: NotPendingTransition,
    baseState: NotPendingTransition,
    baseQueue: null,

    queue: {
     pending: null,
     lanes: 0,
     dispatch: null,
     lastRenderedReducer: basicStateReducer,
     lastRenderedState: NotPendingTransition
    },
    next: null
   };
   var initialResetState = {};
   existingStateHook.next = {
    memoizedState: initialResetState,
    baseState: initialResetState,
    baseQueue: null,
    queue: {
     pending: null,
     lanes: 0,
     dispatch: null,
     lastRenderedReducer: basicStateReducer,
     lastRenderedState: initialResetState
    },
    next: null
   };
```

```
    formFiber.memoizedState = existingStateHook;
    formFiber = formFiber.alternate;
    null !== formFiber && (formFiber.memoizedState = existingStateHook);
    return existingStateHook;
  }
  function requestFormReset$1(formFiber) {
    null === ReactSharedInternals.T && console.error("requestFormReset was called outside a
transition or action. To fix, move to an action, or wrap with startTransition.");
    var resetStateQueue = ensureFormComponentIsStateful(formFiber).next.queue;
    dispatchSetStateInternal(formFiber, resetStateQueue, {}, requestUpdateLane(formFiber));
  }
  function mountTransition() {
    var stateHook = mountStateImpl(!1);
    stateHook = startTransition.bind(null, currentlyRenderingFiber$1, stateHook.queue, !0, !1);
    mountWorkInProgressHook().memoizedState = stateHook;
    return [!1, stateHook];
  }
  function updateTransition() {
    var booleanOrThenable = updateReducer(basicStateReducer)[0],
      start = updateWorkInProgressHook().memoizedState;
    return ["boolean" === typeof booleanOrThenable ? booleanOrThenable :
useThenable(booleanOrThenable), start];
  }
  function rerenderTransition() {
    var booleanOrThenable = rerenderReducer(basicStateReducer)[0],
      start = updateWorkInProgressHook().memoizedState;
    return ["boolean" === typeof booleanOrThenable ? booleanOrThenable :
useThenable(booleanOrThenable), start];
  }
  function useHostTransitionStatus() {
    return readContext(HostTransitionContext);
  }
  function mountId() {
    var hook = mountWorkInProgressHook(),
      identifierPrefix = workInProgressRoot.identifierPrefix;
    if (isHydrating) {
      var treeId = treeContextOverflow;
      var idWithLeadingBit = treeContextId;
      treeId = (idWithLeadingBit & ~(1 << 32 - clz32(idWithLeadingBit) - 1)).toString(32) + treeId;
      identifierPrefix = ":" + identifierPrefix + "R" + treeId;
      treeId = localIdCounter++;
      0 < treeId && (identifierPrefix += "H" + treeId.toString(32));
      identifierPrefix += ":";
    } else treeId = globalClientIdCounter++, identifierPrefix = ":" + identifierPrefix + "r" +
treeId.toString(32) + ":";
    return hook.memoizedState = identifierPrefix;
  }
  function mountRefresh() {
    return mountWorkInProgressHook().memoizedState = refreshCache.bind(null,
```

```
currentlyRenderingFiber$1);
  }
  function refreshCache(fiber, seedKey) {
    for (var provider = fiber.return; null !== provider;) {
      switch (provider.tag) {
        case 24:
        case 3:
          var lane = requestUpdateLane(provider);
          fiber = createUpdate(lane);
          var root = enqueueUpdate(provider, fiber, lane);
          null !== root && (scheduleUpdateOnFiber(root, provider, lane), entangleTransitions(root,
provider, lane));
          provider = createCache();
          null !== seedKey && void 0 !== seedKey && null !== root && console.error("The seed
argument is not enabled outside experimental channels.");
          fiber.payload = {
            cache: provider
          };
          return;
      }
      provider = provider.return;
    }
  }
  function dispatchReducerAction(fiber, queue, action, JSCompiler_OptimizeArgumentsArray_p0) {
    "function" === typeof JSCompiler_OptimizeArgumentsArray_p0 && console.error("State updates
from the useState() and useReducer() Hooks don't support the second callback argument. To execute a
side effect after rendering, declare it in the component body with useEffect().");
    JSCompiler_OptimizeArgumentsArray_p0 = requestUpdateLane(fiber);
    action = {
      lane: JSCompiler_OptimizeArgumentsArray_p0,
      revertLane: 0,
      action: action,
      hasEagerState: !1,
      eagerState: null,
      next: null
    };
    isRenderPhaseUpdate(fiber) ? enqueueRenderPhaseUpdate(queue, action) : (action =
enqueueConcurrentHookUpdate(fiber, queue, action, JSCompiler_OptimizeArgumentsArray_p0),
null !== action && (scheduleUpdateOnFiber(action, fiber, JSCompiler_OptimizeArgumentsArray_p0),
entangleTransitionUpdate(action, queue, JSCompiler_OptimizeArgumentsArray_p0)));
    markStateUpdateScheduled(fiber, JSCompiler_OptimizeArgumentsArray_p0);
  }
  function dispatchSetState(fiber, queue, action, JSCompiler_OptimizeArgumentsArray_p1) {
    "function" === typeof JSCompiler_OptimizeArgumentsArray_p1 && console.error("State updates
from the useState() and useReducer() Hooks don't support the second callback argument. To execute a
side effect after rendering, declare it in the component body with useEffect().");
    JSCompiler_OptimizeArgumentsArray_p1 = requestUpdateLane(fiber);
    dispatchSetStateInternal(fiber, queue, action, JSCompiler_OptimizeArgumentsArray_p1);
    markStateUpdateScheduled(fiber, JSCompiler_OptimizeArgumentsArray_p1);
```

```
  }
  function dispatchSetStateInternal(fiber, queue, action, lane) {
    var update = {
      lane: lane,
      revertLane: 0,
      action: action,
      hasEagerState: !1,
      eagerState: null,
      next: null
    };
    if (isRenderPhaseUpdate(fiber)) enqueueRenderPhaseUpdate(queue, update);else {
      var alternate = fiber.alternate;
      if (0 === fiber.lanes && (null === alternate || 0 === alternate.lanes) && (alternate =
queue.lastRenderedReducer, null !== alternate)) {
        var prevDispatcher = ReactSharedInternals.H;
        ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
        try {
          var currentState = queue.lastRenderedState,
            eagerState = alternate(currentState, action);
          update.hasEagerState = !0;
          update.eagerState = eagerState;
          if (objectIs(eagerState, currentState)) return enqueueUpdate$1(fiber, queue, update, 0), null ===
workInProgressRoot && finishQueueingConcurrentUpdates(), !1;
        } catch (error) {} finally {
          ReactSharedInternals.H = prevDispatcher;
        }
      }
      action = enqueueConcurrentHookUpdate(fiber, queue, update, lane);
      if (null !== action) return scheduleUpdateOnFiber(action, fiber, lane),
entangleTransitionUpdate(action, queue, lane), !0;
    }
    return !1;
  }
  function dispatchOptimisticSetState(fiber, throwIfDuringRender, queue, action) {
    null === ReactSharedInternals.T && 0 === currentEntangledLane && console.error("An optimistic
state update occurred outside a transition or action. To fix, move the update to an action, or wrap with
startTransition.");
    action = {
      lane: 2,
      revertLane: requestTransitionLane(),
      action: action,
      hasEagerState: !1,
      eagerState: null,
      next: null
    };
    if (isRenderPhaseUpdate(fiber)) {
      if (throwIfDuringRender) throw Error("Cannot update optimistic state while rendering.");
      console.error("Cannot call startTransition while rendering.");
    } else throwIfDuringRender = enqueueConcurrentHookUpdate(fiber, queue, action, 2), null !==
```

```
throwIfDuringRender && scheduleUpdateOnFiber(throwIfDuringRender, fiber, 2);
    markStateUpdateScheduled(fiber, 2);
  }
  function isRenderPhaseUpdate(fiber) {
    var alternate = fiber.alternate;
    return fiber === currentlyRenderingFiber$1 || null !== alternate && alternate ===
currentlyRenderingFiber$1;
  }
  function enqueueRenderPhaseUpdate(queue, update) {
    didScheduleRenderPhaseUpdateDuringThisPass = didScheduleRenderPhaseUpdate = !0;
    var pending = queue.pending;
    null === pending ? update.next = update : (update.next = pending.next, pending.next = update);
    queue.pending = update;
  }
  function entangleTransitionUpdate(root, queue, lane) {
    if (0 !== (lane & 4194176)) {
      var queueLanes = queue.lanes;
      queueLanes &= root.pendingLanes;
      lane |= queueLanes;
      queue.lanes = lane;
      markRootEntangled(root, lane);
    }
  }
  function warnOnInvalidCallback(callback) {
    if (null !== callback && "function" !== typeof callback) {
      var key = String(callback);
      didWarnOnInvalidCallback.has(key) || (didWarnOnInvalidCallback.add(key),
console.error("Expected the last optional `callback` argument to be a function. Instead received: %s.",
callback));
    }
  }
  function applyDerivedStateFromProps(workInProgress, ctor, getDerivedStateFromProps, nextProps)
{
    var prevState = workInProgress.memoizedState,
      partialState = getDerivedStateFromProps(nextProps, prevState);
    if (workInProgress.mode & StrictLegacyMode) {
      setIsStrictModeForDevtools(!0);
      try {
        partialState = getDerivedStateFromProps(nextProps, prevState);
      } finally {
        setIsStrictModeForDevtools(!1);
      }
    }
    void 0 === partialState && (ctor = getComponentNameFromType(ctor) || "Component",
didWarnAboutUndefinedDerivedState.has(ctor) || (didWarnAboutUndefinedDerivedState.add(ctor),
console.error("%s.getDerivedStateFromProps(): A valid state object (or null) must be returned. You
have returned undefined.", ctor)));
    prevState = null === partialState || void 0 === partialState ? prevState : assign({}, prevState,
partialState);
```

```
    workInProgress.memoizedState = prevState;
    0 === workInProgress.lanes && (workInProgress.updateQueue.baseState = prevState);
  }
  function checkShouldComponentUpdate(workInProgress, ctor, oldProps, newProps, oldState,
newState, nextContext) {
    var instance = workInProgress.stateNode;
    if ("function" === typeof instance.shouldComponentUpdate) {
      oldProps = instance.shouldComponentUpdate(newProps,
 newState, nextContext);
      if (workInProgress.mode & StrictLegacyMode) {
        setIsStrictModeForDevtools(!0);
        try {
          oldProps = instance.shouldComponentUpdate(newProps, newState, nextContext);
        } finally {
          setIsStrictModeForDevtools(!1);
        }
      }
      void 0 === oldProps && console.error("%s.shouldComponentUpdate(): Returned undefined
instead of a boolean value. Make sure to return true or false.", getComponentNameFromType(ctor) ||
"Component");
      return oldProps;
    }
    return ctor.prototype && ctor.prototype.isPureReactComponent ? !shallowEqual(oldProps,
newProps) || !shallowEqual(oldState, newState) : !0;
  }
  function callComponentWillReceiveProps(workInProgress, instance, newProps, nextContext) {
    var oldState = instance.state;
    "function" === typeof instance.componentWillReceiveProps &&
instance.componentWillReceiveProps(newProps, nextContext);
    "function" === typeof instance.UNSAFE_componentWillReceiveProps &&
instance.UNSAFE_componentWillReceiveProps(newProps, nextContext);
    instance.state !== oldState && (workInProgress = getComponentNameFromFiber(workInProgress)
|| "Component", didWarnAboutStateAssignmentForComponent.has(workInProgress) ||
(didWarnAboutStateAssignmentForComponent.add(workInProgress),
console.error("%s.componentWillReceiveProps(): Assigning directly to this.state is deprecated (except
inside a component's constructor). Use setState instead.", workInProgress)),
classComponentUpdater.enqueueReplaceState(instance, instance.state, null));
  }
  function resolveClassComponentProps(Component, baseProps) {
    var newProps = baseProps;
    if ("ref" in baseProps) {
      newProps = {};
      for (var propName in baseProps) "ref" !== propName && (newProps[propName] =
baseProps[propName]);
    }
    if (Component = Component.defaultProps) {
      newProps === baseProps && (newProps = assign({}, newProps));
      for (var _propName in Component) void 0 === newProps[_propName] &&
(newProps[_propName] = Component[_propName]);
```

```
    }
    return newProps;
  }
  function defaultOnUncaughtError(error, errorInfo) {
    reportGlobalError(error);
    error = componentName ? "An error occurred in the <" + componentName + "> component." : "An
error occurred in one of your React components.";
    var prevGetCurrentStack = ReactSharedInternals.getCurrentStack,
      componentStack = null != errorInfo.componentStack ? errorInfo.componentStack : "";
    ReactSharedInternals.getCurrentStack = function () {
      return componentStack;
    };
    try {
      console.warn("%s\n\n%s\n", error, "Consider adding an error boundary to your tree to customize
error handling behavior.\nVisit https://react.dev/link/error-boundaries to learn more about error
boundaries.");
    } finally {
      ReactSharedInternals.getCurrentStack = prevGetCurrentStack;
    }
  }
  function defaultOnCaughtError(error, errorInfo) {
    var componentNameMessage = componentName ? "The above error occurred in the <" +
componentName + "> component." : "The above error occurred in one of your React components.",
      recreateMessage = "React will try to recreate this component tree from scratch using the error
boundary you provided, " + ((errorBoundaryName || "Anonymous") + "."),
      prevGetCurrentStack = ReactSharedInternals.getCurrentStack,
      componentStack = null != errorInfo.componentStack ? errorInfo.componentStack : "";
    ReactSharedInternals.getCurrentStack = function () {
      return componentStack;
    };
    try {
      "object" === typeof error && null !== error && "string" === typeof error.environmentName ?
bindToConsole("error", ["%o\n\n%s\n\n%s\n", error, componentNameMessage, recreateMessage],
error.environmentName)() : console.error("%o\n\n%s\n\n%s\n", error, componentNameMessage,
recreateMessage);
    } finally {
      ReactSharedInternals.getCurrentStack = prevGetCurrentStack;
    }
  }
  function defaultOnRecoverableError(error) {
    reportGlobalError(error);
  }
  function logUncaughtError(root, errorInfo) {
    try {
      componentName = errorInfo.source ? getComponentNameFromFiber(errorInfo.source) : null;
      errorBoundaryName = null;
      var error = errorInfo.value;
      if (null !== ReactSharedInternals.actQueue) ReactSharedInternals.thrownErrors.push(error);else {
        var onUncaughtError = root.onUncaughtError;
```

```
      onUncaughtError(error, {
        componentStack: errorInfo.stack
      });
    }
  } catch (e$4) {
    setTimeout(function () {
      throw e$4;
    });
  }
}
function logCaughtError(root, boundary, errorInfo) {
  try {
    componentName = errorInfo.source ? getComponentNameFromFiber(errorInfo.source) : null;
    errorBoundaryName = getComponentNameFromFiber(boundary);
    var onCaughtError = root.onCaughtError;
    onCaughtError(errorInfo.value, {
      componentStack: errorInfo.stack,
      errorBoundary: 1 === boundary.tag ? boundary.stateNode : null
    });
  } catch (e$5) {
    setTimeout(function () {
      throw e$5;
    });
  }
}
function createRootErrorUpdate(root, errorInfo, lane) {
  lane = createUpdate(lane);
  lane.tag = CaptureUpdate;
  lane.payload = {
    element: null
  };
  lane.callback = function () {
    runWithFiberInDEV(errorInfo.source, logUncaughtError, root, errorInfo);
  };
  return lane;
}
function createClassErrorUpdate(lane) {
  lane = createUpdate(lane);
  lane.tag = CaptureUpdate;
  return lane;
}
function initializeClassErrorUpdate(update, root, fiber, errorInfo) {
  var getDerivedStateFromError = fiber.type.getDerivedStateFromError;
  if ("function" === typeof getDerivedStateFromError) {
    var error = errorInfo.value;
    update.payload = function () {
      return getDerivedStateFromError(error);
    };
    update.callback = function () {
```

```
        markFailedErrorBoundaryForHotReloading(fiber);
        runWithFiberInDEV(errorInfo.source, logCaughtError, root, fiber, errorInfo);
      };
    }
    var inst = fiber.stateNode;
    null !== inst && "function" === typeof inst.componentDidCatch && (update.callback = function ()
{
      markFailedErrorBoundaryForHotReloading(fiber);
      runWithFiberInDEV(errorInfo.source, logCaughtError, root, fiber, errorInfo);
      "function" !== typeof getDerivedStateFromError && (null ===
legacyErrorBoundariesThatAlreadyFailed ? legacyErrorBoundariesThatAlreadyFailed = new
Set([this]) : legacyErrorBoundariesThatAlreadyFailed.add(this));
      callComponentDidCatchInDEV(this, errorInfo);
      "function" === typeof getDerivedStateFromError || 0 === (fiber.lanes & 2) && console.error("%s:
Error boundaries should implement getDerivedStateFromError(). In that method, return a state update
to display an error message or fallback UI.", getComponentNameFromFiber(fiber) || "Unknown");
    });
  }
  function throwException(root, returnFiber, sourceFiber, value, rootRenderLanes) {
    sourceFiber.flags |= 32768;
    isDevToolsPresent && restorePendingUpdaters(root, rootRenderLanes);
    if (null !== value && "object" === typeof value && "function" === typeof value.then) {
      returnFiber = sourceFiber.alternate;
      null !== returnFiber && propagateParentContextChanges(returnFiber, sourceFiber,
rootRenderLanes, !0);
      isHydrating && (didSuspendOrErrorDEV = !0);
      sourceFiber = suspenseHandlerStackCursor.current;
      if (null !== sourceFiber) {
        switch (sourceFiber.tag) {
          case 13:
            return null === shellBoundary ? renderDidSuspendDelayIfPossible() : null ===
sourceFiber.alternate && workInProgressRootExitStatus === RootInProgress &&
(workInProgressRootExitStatus = RootSuspended), sourceFiber.flags &= -257, sourceFiber.flags |=
65536, sourceFiber.lanes = rootRenderLanes, value === noopSuspenseyCommitThenable ?
sourceFiber.flags |= 16384 : (returnFiber = sourceFiber.updateQueue, null === returnFiber ?
sourceFiber.updateQueue = new Set([value]) : returnFiber.add(value), attachPingListener(root, value,
rootRenderLanes)), !1;
          case 22:
            return sourceFiber.flags |= 65536, value === noopSuspenseyCommitThenable ?
sourceFiber.flags |= 16384 : (returnFiber = sourceFiber.updateQueue, null === returnFiber ?
(returnFiber = {
              transitions: null,
              markerInstances: null,
              retryQueue: new Set([value])
            }, sourceFiber.updateQueue = returnFiber) : (sourceFiber = returnFiber.retryQueue, null ===
sourceFiber ? returnFiber.retryQueue = new Set([value]) : sourceFiber.add(value)),
attachPingListener(root, value, rootRenderLanes)), !1;
        }
        throw Error("Unexpected Suspense handler tag (" + sourceFiber.tag + "). This is a bug in React.");
```

```
      }
      attachPingListener(root, value, rootRenderLanes);
      renderDidSuspendDelayIfPossible();
      return !1;
    }
    if (isHydrating) return didSuspendOrErrorDEV = !0, returnFiber =
suspenseHandlerStackCursor.current, null !== returnFiber ? (0 === (returnFiber.flags & 65536) &&
(returnFiber.flags |= 256), returnFiber.flags |= 65536, returnFiber.lanes = rootRenderLanes, value !==
HydrationMismatchException && queueHydrationError(createCapturedValueAtFiber(Error("There
was an error while hydrating but React was able to recover by instead client rendering from the nearest
Suspense boundary.", {
      cause: value
    }), sourceFiber))) : (value !== HydrationMismatchException &&
queueHydrationError(createCapturedValueAtFiber(Error("There was an error while hydrating but
React was able to recover by instead client rendering the entire root.", {
      cause: value
    }), sourceFiber)), root = root.current.alternate, root.flags |= 65536, rootRenderLanes &=
-rootRenderLanes, root.lanes |= rootRenderLanes, value = createCapturedValueAtFiber(value,
sourceFiber), rootRenderLanes = createRootErrorUpdate(root.stateNode, value, rootRenderLanes),
 enqueueCapturedUpdate(root, rootRenderLanes), workInProgressRootExitStatus !==
RootSuspendedWithDelay && (workInProgressRootExitStatus = RootErrored)), !1;
    var error = createCapturedValueAtFiber(Error("There was an error during concurrent rendering but
React was able to recover by instead synchronously rendering the entire root.", {
      cause: value
    }), sourceFiber);
    null === workInProgressRootConcurrentErrors ? workInProgressRootConcurrentErrors = [error] :
workInProgressRootConcurrentErrors.push(error);
    workInProgressRootExitStatus !== RootSuspendedWithDelay && (workInProgressRootExitStatus
= RootErrored);
    if (null === returnFiber) return !0;
    value = createCapturedValueAtFiber(value, sourceFiber);
    sourceFiber = returnFiber;
    do {
      switch (sourceFiber.tag) {
        case 3:
          return sourceFiber.flags |= 65536, root = rootRenderLanes & -rootRenderLanes,
sourceFiber.lanes |= root, root = createRootErrorUpdate(sourceFiber.stateNode, value, root),
enqueueCapturedUpdate(sourceFiber, root), !1;
        case 1:
          if (returnFiber = sourceFiber.type, error = sourceFiber.stateNode, 0 === (sourceFiber.flags &
128) && ("function" === typeof returnFiber.getDerivedStateFromError || null !== error && "function"
=== typeof error.componentDidCatch && (null === legacyErrorBoundariesThatAlreadyFailed || !
legacyErrorBoundariesThatAlreadyFailed.has(error)))) return sourceFiber.flags |= 65536,
rootRenderLanes &= -rootRenderLanes, sourceFiber.lanes |= rootRenderLanes, rootRenderLanes =
createClassErrorUpdate(rootRenderLanes), initializeClassErrorUpdate(rootRenderLanes, root,
sourceFiber, value), enqueueCapturedUpdate(sourceFiber, rootRenderLanes), !1;
      }
      sourceFiber = sourceFiber.return;
    } while (null !== sourceFiber);
```

```
    return !1;
  }
  function reconcileChildren(current, workInProgress, nextChildren, renderLanes) {
    workInProgress.child = null === current ? mountChildFibers(workInProgress, null, nextChildren,
renderLanes) : reconcileChildFibers(workInProgress, current.child, nextChildren, renderLanes);
  }
  function updateForwardRef(current, workInProgress, Component, nextProps, renderLanes) {
    Component = Component.render;
    var ref = workInProgress.ref;
    if ("ref" in nextProps) {
      var propsWithoutRef = {};
      for (var key in nextProps) "ref" !== key && (propsWithoutRef[key] = nextProps[key]);
    } else propsWithoutRef = nextProps;
    prepareToReadContext(workInProgress);
    markComponentRenderStarted(workInProgress);
    nextProps = renderWithHooks(current, workInProgress, Component, propsWithoutRef, ref,
renderLanes);
    key = checkDidRenderIdHook();
    markComponentRenderStopped();
    if (null !== current && !didReceiveUpdate) return bailoutHooks(current, workInProgress,
renderLanes), bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
    isHydrating && key && pushMaterializedTreeId(workInProgress);
    workInProgress.flags |= 1;
    reconcileChildren(current, workInProgress, nextProps, renderLanes);
    return workInProgress.child;
  }
  function updateMemoComponent(current, workInProgress, Component, nextProps, renderLanes) {
    if (null === current) {
      var type = Component.type;
      if ("function" === typeof type && !shouldConstruct(type) && void 0 === type.defaultProps &&
null === Component.compare) return Component = resolveFunctionForHotReloading(type),
workInProgress.tag = 15, workInProgress.type = Component,
validateFunctionComponentInDev(workInProgress, type), updateSimpleMemoComponent(current,
workInProgress, Component, nextProps, renderLanes);
      current = createFiberFromTypeAndProps(Component.type, null, nextProps, workInProgress,
workInProgress.mode, renderLanes);
      current.ref = workInProgress.ref;
      current.return = workInProgress;
      return workInProgress.child = current;
    }
    type = current.child;
    if (!checkScheduledUpdateOrContext(current, renderLanes)) {
      var prevProps = type.memoizedProps;
      Component = Component.compare;
      Component = null !== Component ? Component : shallowEqual;
      if (Component(prevProps, nextProps) && current.ref === workInProgress.ref) return
bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
    }
    workInProgress.flags |= 1;
```

```
    current = createWorkInProgress(type, nextProps);
    current.ref = workInProgress.ref;
    current.return = workInProgress;
    return workInProgress.child = current;
  }
  function updateSimpleMemoComponent(current, workInProgress, Component, nextProps,
renderLanes) {
    if (null !== current) {
      var prevProps = current.memoizedProps;
      if (shallowEqual(prevProps, nextProps) && current.ref === workInProgress.ref &&
workInProgress.type === current.type) if (didReceiveUpdate = !1, workInProgress.pendingProps =
nextProps = prevProps, checkScheduledUpdateOrContext(current, renderLanes)) 0 !== (current.flags
& 131072) && (didReceiveUpdate = !0);else return workInProgress.lanes = current.lanes,
bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
    }
    return updateFunctionComponent(current, workInProgress, Component, nextProps, renderLanes);
  }
  function updateOffscreenComponent(current, workInProgress, renderLanes) {
    var nextProps = workInProgress.pendingProps,
      nextChildren = nextProps.children,
      nextIsDetached = 0 !== (workInProgress.stateNode._pendingVisibility & OffscreenDetached),
      prevState = null !== current ? current.memoizedState : null;
    markRef(current, workInProgress);
    if ("hidden" === nextProps.mode || nextIsDetached) {
      if (0 !== (workInProgress.flags & 128)) {
        nextProps = null !== prevState ? prevState.baseLanes | renderLanes : renderLanes;
        if (null !== current) {
          nextChildren = workInProgress.child = current.child;
          for (nextIsDetached = 0; null !== nextChildren;) nextIsDetached = nextIsDetached |
nextChildren.lanes | nextChildren.childLanes, nextChildren = nextChildren.sibling;
          workInProgress.childLanes = nextIsDetached & ~nextProps;
        } else workInProgress.childLanes = 0, workInProgress.child = null;
        return deferHiddenOffscreenComponent(current, workInProgress, nextProps, renderLanes);
      }
      if (0 !== (renderLanes & 536870912)) workInProgress.memoizedState = {
        baseLanes: 0,
        cachePool: null
      }, null !== current && pushTransition(workInProgress, null !== prevState ? prevState.cachePool :
null), null !== prevState ? pushHiddenContext(workInProgress, prevState) :
reuseHiddenContextOnStack(workInProgress), pushOffscreenSuspenseHandler(workInProgress);else
return workInProgress.lanes = workInProgress.childLanes = 536870912,
deferHiddenOffscreenComponent(current, workInProgress, null !== prevState ? prevState.baseLanes |
renderLanes : renderLanes, renderLanes);
    } else null !== prevState ? (pushTransition(workInProgress, prevState.cachePool),
pushHiddenContext(workInProgress, prevState), reuseSuspenseHandlerOnStack(workInProgress),
workInProgress.memoizedState = null) : (null !== current && pushTransition(workInProgress, null),
reuseHiddenContextOnStack(workInProgress), reuseSuspenseHandlerOnStack(workInProgress));
    reconcileChildren(current, workInProgress, nextChildren, renderLanes);
    return workInProgress.child;
```

```
  }
  function deferHiddenOffscreenComponent(current, workInProgress, nextBaseLanes, renderLanes) {
    var JSCompiler_inline_result = peekCacheFromPool();
    JSCompiler_inline_result = null === JSCompiler_inline_result ? null : {
      parent: CacheContext._currentValue,
      pool: JSCompiler_inline_result
    };
    workInProgress.memoizedState = {
      baseLanes: nextBaseLanes,
      cachePool: JSCompiler_inline_result
    };
    null !== current && pushTransition(workInProgress, null);
    reuseHiddenContextOnStack(workInProgress);
    pushOffscreenSuspenseHandler(workInProgress);
    null !== current && propagateParentContextChanges(current, workInProgress, renderLanes, !0);
    return null;
  }
  function markRef(current, workInProgress) {
    var ref = workInProgress.ref;
    if (null === ref) null !== current && null !== current.ref && (workInProgress.flags |=
2097664);else {
      if ("function" !== typeof ref && "object" !== typeof ref) throw Error("Expected ref to be a
function, an object returned by React.createRef(), or undefined/null.");
      if (null === current || current.ref !== ref) workInProgress.flags |= 2097664;
    }
  }
  function updateFunctionComponent(current, workInProgress, Component, nextProps, renderLanes) {
    if (Component.prototype && "function" === typeof Component.prototype.render) {
      var componentName = getComponentNameFromType(Component) || "Unknown";
      didWarnAboutBadClass[componentName] || (console.error("The <%s /> component appears to
have a render method, but doesn't extend React.Component. This is likely to cause errors. Change %s
to extend React.Component instead.", componentName, componentName),
didWarnAboutBadClass[componentName] = !0);
    }
    workInProgress.mode & StrictLegacyMode &&
ReactStrictModeWarnings.recordLegacyContextWarning(workInProgress, null);
    null === current && (validateFunctionComponentInDev(workInProgress, workInProgress.type),
Component.contextTypes && (componentName = getComponentNameFromType(Component) ||
"Unknown", didWarnAboutContextTypes[componentName] ||
(didWarnAboutContextTypes[componentName] = !0, console.error("%s uses the legacy contextTypes
API which was removed in React 19. Use React.createContext() with React.useContext() instead.
(https://react.dev/link/legacy-context)", componentName))));
    prepareToReadContext(workInProgress);
    markComponentRenderStarted(workInProgress);
    Component = renderWithHooks(current, workInProgress, Component, nextProps, void 0,
renderLanes);
    nextProps = checkDidRenderIdHook();

    markComponentRenderStopped();
```

```
    if (null !== current && !didReceiveUpdate) return bailoutHooks(current, workInProgress,
renderLanes), bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
    isHydrating && nextProps && pushMaterializedTreeId(workInProgress);
    workInProgress.flags |= 1;
    reconcileChildren(current, workInProgress, Component, renderLanes);
    return workInProgress.child;
  }
  function replayFunctionComponent(current, workInProgress, nextProps, Component, secondArg,
renderLanes) {
    prepareToReadContext(workInProgress);
    markComponentRenderStarted(workInProgress);
    hookTypesUpdateIndexDev = -1;
    ignorePreviousDependencies = null !== current && current.type !== workInProgress.type;
    workInProgress.updateQueue = null;
    nextProps = renderWithHooksAgain(workInProgress, Component, nextProps, secondArg);
    finishRenderingHooks(current, workInProgress);
    Component = checkDidRenderIdHook();
    markComponentRenderStopped();
    if (null !== current && !didReceiveUpdate) return bailoutHooks(current, workInProgress,
renderLanes), bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
    isHydrating && Component && pushMaterializedTreeId(workInProgress);
    workInProgress.flags |= 1;
    reconcileChildren(current, workInProgress, nextProps, renderLanes);
    return workInProgress.child;
  }
  function updateClassComponent(current$jscomp$0, workInProgress, Component, nextProps,
renderLanes) {
    switch (shouldErrorImpl(workInProgress)) {
      case !1:
        var _instance = workInProgress.stateNode,
          state = new workInProgress.type(workInProgress.memoizedProps, _instance.context).state;
        _instance.updater.enqueueSetState(_instance, state, null);
        break;
      case !0:
        workInProgress.flags |= 128;
        workInProgress.flags |= 65536;
        _instance = Error("Simulated error coming from DevTools");
        var lane = renderLanes & -renderLanes;
        workInProgress.lanes |= lane;
        state = workInProgressRoot;
        if (null === state) throw Error("Expected a work-in-progress root. This is a bug in React. Please
file an issue.");
        lane = createClassErrorUpdate(lane);
        initializeClassErrorUpdate(lane, state, workInProgress, createCapturedValueAtFiber(_instance,
workInProgress));
        enqueueCapturedUpdate(workInProgress, lane);
    }
    prepareToReadContext(workInProgress);
    if (null === workInProgress.stateNode) {
```

```
    state = emptyContextObject;
    _instance = Component.contextType;
    "contextType" in Component && null !== _instance && (void 0 === _instance || _instance.$
$typeof !== REACT_CONTEXT_TYPE) && !didWarnAboutInvalidateContextType.has(Component)
&& (didWarnAboutInvalidateContextType.add(Component), lane = void 0 === _instance ? " However,
it is set to undefined. This can be caused by a typo or by mixing up named and default imports. This
can also happen due to a circular dependency, so try moving the createContext() call to a separate
file." : "object" !== typeof _instance ? " However, it is set to a " + typeof _instance + "." : _instance.$
$typeof === REACT_CONSUMER_TYPE ? " Did you accidentally pass the Context.Consumer
instead?" : " However, it is set to an object with keys {" + Object.keys(_instance).join(", ") + "}.",
console.error("%s defines an invalid contextType. contextType should point to the Context object
returned by React.createContext().%s", getComponentNameFromType(Component) || "Component",
lane));
    "object" === typeof _instance && null !== _instance && (state = readContext(_instance));
    _instance = new Component(nextProps, state);
    if (workInProgress.mode & StrictLegacyMode) {
      setIsStrictModeForDevtools(!0);
      try {
        _instance = new Component(nextProps, state);
      } finally {
        setIsStrictModeForDevtools(!1);
      }
    }
    state = workInProgress.memoizedState = null !== _instance.state && void 0 !== _instance.state ?
_instance.state : null;
    _instance.updater = classComponentUpdater;
    workInProgress.stateNode = _instance;
    _instance._reactInternals = workInProgress;
    _instance._reactInternalInstance = fakeInternalInstance;
    "function" === typeof Component.getDerivedStateFromProps && null === state && (state =
getComponentNameFromType(Component) || "Component",
didWarnAboutUninitializedState.has(state) || (didWarnAboutUninitializedState.add(state),
console.error("`%s` uses `getDerivedStateFromProps` but its initial state is %s. This is not
recommended. Instead, define the initial state by assigning an object to `this.state` in the constructor of
`%s`. This ensures that `getDerivedStateFromProps` arguments have a consistent shape.", state, null
=== _instance.state ? "null" : "undefined", state)));
    if ("function" === typeof Component.getDerivedStateFromProps || "function" === typeof
_instance.getSnapshotBeforeUpdate) {
      var foundWillUpdateName = lane = state = null;
      "function" === typeof _instance.componentWillMount && !0 !==
_instance.componentWillMount.__suppressDeprecationWarning ? state = "componentWillMount" :
"function" === typeof _instance.UNSAFE_componentWillMount && (state =
"UNSAFE_componentWillMount");
      "function" === typeof _instance.componentWillReceiveProps && !0 !==
_instance.componentWillReceiveProps.__suppressDeprecationWarning ? lane =
"componentWillReceiveProps" : "function" === typeof
_instance.UNSAFE_componentWillReceiveProps && (lane =
"UNSAFE_componentWillReceiveProps");
      "function" === typeof _instance.componentWillUpdate && !0 !==
```

```
_instance.componentWillUpdate.__suppressDeprecationWarning ? foundWillUpdateName =
"componentWillUpdate" : "function" === typeof _instance.UNSAFE_componentWillUpdate &&
(foundWillUpdateName = "UNSAFE_componentWillUpdate");
        if (null !== state || null !== lane || null !== foundWillUpdateName) {
          _instance = getComponentNameFromType(Component) || "Component";
          var newApiName = "function" === typeof Component.getDerivedStateFromProps ?
"getDerivedStateFromProps()" : "getSnapshotBeforeUpdate()";
          didWarnAboutLegacyLifecyclesAndDerivedState.has(_instance) ||
(didWarnAboutLegacyLifecyclesAndDerivedState.add(_instance), console.error("Unsafe legacy
lifecycles will not be called for components using new component APIs.\n\n%s uses %s but also
contains the following legacy lifecycles:%s%s%s\n\nThe above lifecycles should be removed. Learn
more about this warning here:\nhttps://react.dev/link/unsafe-component-lifecycles", _instance,
newApiName, null !== state ? "\n  " + state : "", null !== lane ? "\n  " + lane : "", null !==
foundWillUpdateName ? "\n  " + foundWillUpdateName : ""));
        }
      }
      _instance = workInProgress.stateNode;
      state = getComponentNameFromType(Component) || "Component";
      _instance.render || (Component.prototype && "function" === typeof Component.prototype.render ?
console.error("No `render` method found on the %s instance: did you accidentally return an object
from the constructor?", state) : console.error("No `render` method found on the %s instance: you may
have forgotten to define `render`.", state));
      !_instance.getInitialState || _instance.getInitialState.isReactClassApproved || _instance.state ||
console.error("getInitialState was defined on %s, a plain JavaScript class. This is only supported for
classes created using React.createClass. Did you mean to define a state property instead?", state);
      _instance.getDefaultProps && !_instance.getDefaultProps.isReactClassApproved &&
console.error("getDefaultProps was defined on %s, a plain JavaScript class. This is only supported for
classes created using React.createClass. Use a static property to define defaultProps instead.", state);
      _instance.contextType && console.error("contextType was defined as an instance property on %s.
Use a static property to define contextType instead.", state);
      Component.childContextTypes && !didWarnAboutChildContextTypes.has(Component) &&
(didWarnAboutChildContextTypes.add(Component), console.error("%s uses the legacy
childContextTypes API which was removed in React 19. Use React.createContext() instead.
(https://react.dev/link/legacy-context)", state));
      Component.contextTypes && !didWarnAboutContextTypes$1.has(Component) &&
(didWarnAboutContextTypes$1.add(Component), console.error("%s uses the legacy contextTypes API
which was removed in React 19. Use React.createContext() with static contextType instead.
(https://react.dev/link/legacy-context)", state));
      "function" === typeof _instance.componentShouldUpdate && console.error("%s has a method
called componentShouldUpdate(). Did you mean shouldComponentUpdate()? The name is phrased as a
question because the function is expected to return a value.", state);
      Component.prototype && Component.prototype.isPureReactComponent && "undefined" !==
typeof _instance.shouldComponentUpdate && console.error("%s has a method called
shouldComponentUpdate(). shouldComponentUpdate should not be used when extending
React.PureComponent. Please extend React.Component if shouldComponentUpdate is used.",
getComponentNameFromType(Component) || "A pure component");
      "function" === typeof _instance.componentDidUnmount && console.error("%s has a method
called componentDidUnmount(). But there is no such lifecycle method. Did you mean
componentWillUnmount()?", state);
```

"function" === typeof _instance.componentDidReceiveProps && console.error("%s has a method called componentDidReceiveProps(). But there is no such lifecycle method. If you meant to update the state in response to changing props, use componentWillReceiveProps(). If you meant to fetch data or run side-effects or mutations after React has updated the UI, use componentDidUpdate().", state);
"function"
=== typeof _instance.componentWillRecieveProps && console.error("%s has a method called componentWillRecieveProps(). Did you mean componentWillReceiveProps()?", state);
"function" === typeof _instance.UNSAFE_componentWillRecieveProps && console.error("%s has a method called UNSAFE_componentWillRecieveProps(). Did you mean UNSAFE_componentWillReceiveProps()?", state);
lane = _instance.props !== nextProps;
void 0 !== _instance.props && lane && console.error("When calling super() in `%s`, make sure to pass up the same props that your component's constructor was passed.", state);
_instance.defaultProps && console.error("Setting defaultProps as an instance property on %s is not supported and will be ignored. Instead, define defaultProps as a static property on %s.", state, state);
"function" !== typeof _instance.getSnapshotBeforeUpdate || "function" === typeof _instance.componentDidUpdate || didWarnAboutGetSnapshotBeforeUpdateWithoutDidUpdate.has(Component) || (didWarnAboutGetSnapshotBeforeUpdateWithoutDidUpdate.add(Component), console.error("%s: getSnapshotBeforeUpdate() should be used with componentDidUpdate(). This component defines getSnapshotBeforeUpdate() only.", getComponentNameFromType(Component)));
"function" === typeof _instance.getDerivedStateFromProps && console.error("%s: getDerivedStateFromProps() is defined as an instance method and will be ignored. Instead, declare it as a static method.", state);
"function" === typeof _instance.getDerivedStateFromError && console.error("%s: getDerivedStateFromError() is defined as an instance method and will be ignored. Instead, declare it as a static method.", state);
"function" === typeof Component.getSnapshotBeforeUpdate && console.error("%s: getSnapshotBeforeUpdate() is defined as a static method and will be ignored. Instead, declare it as an instance method.", state);
(lane = _instance.state) && ("object" !== typeof lane || isArrayImpl(lane)) && console.error("%s.state: must be set to an object or null", state);
"function" === typeof _instance.getChildContext && "object" !== typeof Component.childContextTypes && console.error("%s.getChildContext(): childContextTypes must be defined in order to use getChildContext().", state);
_instance = workInProgress.stateNode;
_instance.props = nextProps;
_instance.state = workInProgress.memoizedState;
_instance.refs = {};
initializeUpdateQueue(workInProgress);
state = Component.contextType;
_instance.context = "object" === typeof state && null !== state ? readContext(state) : emptyContextObject;
_instance.state === nextProps && (state = getComponentNameFromType(Component) || "Component", didWarnAboutDirectlyAssigningPropsToState.has(state) || (didWarnAboutDirectlyAssigningPropsToState.add(state), console.error("%s: It is not recommended to assign props directly to state because updates to props won't be reflected in state. In most cases, it is better to use props directly.", state)));
workInProgress.mode & StrictLegacyMode &&

```
ReactStrictModeWarnings.recordLegacyContextWarning(workInProgress, _instance);
    ReactStrictModeWarnings.recordUnsafeLifecycleWarnings(workInProgress, _instance);
    _instance.state = workInProgress.memoizedState;
    state = Component.getDerivedStateFromProps;
    "function" === typeof state && (applyDerivedStateFromProps(workInProgress, Component, state,
nextProps), _instance.state = workInProgress.memoizedState);
    "function" === typeof Component.getDerivedStateFromProps || "function" === typeof
_instance.getSnapshotBeforeUpdate || "function" !== typeof
_instance.UNSAFE_componentWillMount && "function" !== typeof _instance.componentWillMount
|| (state = _instance.state, "function" === typeof _instance.componentWillMount &&
_instance.componentWillMount(), "function" === typeof _instance.UNSAFE_componentWillMount
&& _instance.UNSAFE_componentWillMount(), state !== _instance.state &&
(console.error("%s.componentWillMount(): Assigning directly to this.state is deprecated (except inside
a component's constructor). Use setState instead.", getComponentNameFromFiber(workInProgress) ||
"Component"), classComponentUpdater.enqueueReplaceState(_instance, _instance.state, null)),
processUpdateQueue(workInProgress, nextProps, _instance, renderLanes),
suspendIfUpdateReadFromEntangledAsyncAction(), _instance.state =
workInProgress.memoizedState);
    "function" === typeof _instance.componentDidMount && (workInProgress.flags |= 4194308);
    (workInProgress.mode & StrictEffectsMode) !== NoMode && (workInProgress.flags |=
67108864);
    _instance = !0;
  } else if (null === current$jscomp$0) {
    _instance = workInProgress.stateNode;
    var unresolvedOldProps = workInProgress.memoizedProps;
    lane = resolveClassComponentProps(Component, unresolvedOldProps);
    _instance.props = lane;
    var oldContext = _instance.context;
    foundWillUpdateName = Component.contextType;
    state = emptyContextObject;
    "object" === typeof foundWillUpdateName && null !== foundWillUpdateName && (state =
readContext(foundWillUpdateName));
    newApiName = Component.getDerivedStateFromProps;
    foundWillUpdateName = "function" === typeof newApiName || "function" === typeof
_instance.getSnapshotBeforeUpdate;
    unresolvedOldProps = workInProgress.pendingProps !== unresolvedOldProps;
    foundWillUpdateName || "function" !== typeof _instance.UNSAFE_componentWillReceiveProps
&& "function" !== typeof _instance.componentWillReceiveProps || (unresolvedOldProps ||
oldContext !== state) && callComponentWillReceiveProps(workInProgress, _instance, nextProps,
state);
    hasForceUpdate = !1;
    var oldState = workInProgress.memoizedState;
    _instance.state = oldState;
    processUpdateQueue(workInProgress, nextProps, _instance, renderLanes);
    suspendIfUpdateReadFromEntangledAsyncAction();
    oldContext = workInProgress.memoizedState;
    unresolvedOldProps || oldState !== oldContext || hasForceUpdate ? ("function" === typeof
newApiName && (applyDerivedStateFromProps(workInProgress, Component, newApiName,
nextProps), oldContext = workInProgress.memoizedState), (lane = hasForceUpdate ||
```

```
checkShouldComponentUpdate(workInProgress, Component, lane, nextProps, oldState, oldContext,
state)) ? (foundWillUpdateName || "function" !== typeof _instance.UNSAFE_componentWillMount
&& "function" !== typeof _instance.componentWillMount || ("function" === typeof
_instance.componentWillMount && _instance.componentWillMount(), "function" === typeof
_instance.UNSAFE_componentWillMount && _instance.UNSAFE_componentWillMount()),
"function" === typeof _instance.componentDidMount && (workInProgress.flags |= 4194308),
(workInProgress.mode & StrictEffectsMode) !== NoMode && (workInProgress.flags |= 67108864)) :
("function" === typeof _instance.componentDidMount && (workInProgress.flags |= 4194308),
(workInProgress.mode & StrictEffectsMode) !== NoMode && (workInProgress.flags |= 67108864),
workInProgress.memoizedProps = nextProps, workInProgress.memoizedState = oldContext),
_instance.props = nextProps, _instance.state = oldContext, _instance.context = state, _instance = lane) :
("function" === typeof _instance.componentDidMount && (workInProgress.flags |= 4194308),
(workInProgress.mode & StrictEffectsMode) !== NoMode && (workInProgress.flags |= 67108864),
_instance = !1);
    } else {
      _instance = workInProgress.stateNode;
      cloneUpdateQueue(current$jscomp$0, workInProgress);
      state = workInProgress.memoizedProps;
      foundWillUpdateName = resolveClassComponentProps(Component, state);
      _instance.props = foundWillUpdateName;
      newApiName = workInProgress.pendingProps;
      oldState = _instance.context;
      oldContext = Component.contextType;
      lane = emptyContextObject;
      "object" === typeof oldContext && null !== oldContext && (lane = readContext(oldContext));
      unresolvedOldProps = Component.getDerivedStateFromProps;
      (oldContext = "function" === typeof unresolvedOldProps || "function" === typeof
_instance.getSnapshotBeforeUpdate) || "function" !== typeof
_instance.UNSAFE_componentWillReceiveProps && "function" !== typeof
_instance.componentWillReceiveProps || (state !== newApiName || oldState !== lane) &&
callComponentWillReceiveProps(workInProgress, _instance, nextProps, lane);
      hasForceUpdate = !1;
      oldState = workInProgress.memoizedState;
      _instance.state = oldState;
      processUpdateQueue(workInProgress, nextProps, _instance, renderLanes);
      suspendIfUpdateReadFromEntangledAsyncAction();
      var newState = workInProgress.memoizedState;
      state !== newApiName || oldState !== newState || hasForceUpdate || null !== current$jscomp$0 &&
null !== current$jscomp$0.dependencies &&
checkIfContextChanged(current$jscomp$0.dependencies) ? ("function" === typeof
unresolvedOldProps && (applyDerivedStateFromProps(workInProgress, Component,
unresolvedOldProps, nextProps), newState = workInProgress.memoizedState), (foundWillUpdateName
= hasForceUpdate || checkShouldComponentUpdate(workInProgress, Component,
foundWillUpdateName, nextProps, oldState, newState, lane) || null !== current$jscomp$0 && null !==
current$jscomp$0.dependencies && checkIfContextChanged(current$jscomp$0.dependencies)) ?
(oldContext || "function" !== typeof _instance.UNSAFE_componentWillUpdate && "function" !==
typeof _instance.componentWillUpdate || ("function" === typeof _instance.componentWillUpdate &&
_instance.componentWillUpdate(nextProps, newState, lane), "function" === typeof
_instance.UNSAFE_componentWillUpdate &&
```

```
_instance.UNSAFE_componentWillUpdate(nextProps, newState, lane)), "function" === typeof
_instance.componentDidUpdate && (workInProgress.flags |= 4), "function" === typeof
_instance.getSnapshotBeforeUpdate && (workInProgress.flags |= 1024))
 : ("function" !== typeof _instance.componentDidUpdate || state ===
current$jscomp$0.memoizedProps && oldState === current$jscomp$0.memoizedState ||
(workInProgress.flags |= 4), "function" !== typeof _instance.getSnapshotBeforeUpdate || state ===
current$jscomp$0.memoizedProps && oldState === current$jscomp$0.memoizedState ||
(workInProgress.flags |= 1024), workInProgress.memoizedProps = nextProps,
workInProgress.memoizedState = newState), _instance.props = nextProps, _instance.state = newState,
_instance.context = lane, _instance = foundWillUpdateName) : ("function" !== typeof
_instance.componentDidUpdate || state === current$jscomp$0.memoizedProps && oldState ===
current$jscomp$0.memoizedState || (workInProgress.flags |= 4), "function" !== typeof
_instance.getSnapshotBeforeUpdate || state === current$jscomp$0.memoizedProps && oldState ===
current$jscomp$0.memoizedState || (workInProgress.flags |= 1024), _instance = !1);
    }
    lane = _instance;
    markRef(current$jscomp$0, workInProgress);
    state = 0 !== (workInProgress.flags & 128);
    if (lane || state) {
      lane = workInProgress.stateNode;
      ReactSharedInternals.getCurrentStack = null === workInProgress ? null :
getCurrentFiberStackInDev;
      isRendering = !1;
      current = workInProgress;
      if (state && "function" !== typeof Component.getDerivedStateFromError) Component = null,
profilerStartTime = -1;else {
        markComponentRenderStarted(workInProgress);
        Component = callRenderInDEV(lane);
        if (workInProgress.mode & StrictLegacyMode) {
          setIsStrictModeForDevtools(!0);
          try {
            callRenderInDEV(lane);
          } finally {
            setIsStrictModeForDevtools(!1);
          }
        }
        markComponentRenderStopped();
      }
      workInProgress.flags |= 1;
      null !== current$jscomp$0 && state ? (workInProgress.child =
reconcileChildFibers(workInProgress, current$jscomp$0.child, null, renderLanes),
workInProgress.child = reconcileChildFibers(workInProgress, null, Component, renderLanes)) :
reconcileChildren(current$jscomp$0, workInProgress, Component, renderLanes);
      workInProgress.memoizedState = lane.state;
      current$jscomp$0 = workInProgress.child;
    } else current$jscomp$0 = bailoutOnAlreadyFinishedWork(current$jscomp$0, workInProgress,
renderLanes);
    renderLanes = workInProgress.stateNode;
    _instance && renderLanes.props !== nextProps && (didWarnAboutReassigningProps ||
```

```
console.error("It looks like %s is reassigning its own `this.props` while rendering. This is not supported and can lead to confusing bugs.", getComponentNameFromFiber(workInProgress) || "a component"), didWarnAboutReassigningProps = !0);
    return current$jscomp$0;
  }
  function mountHostRootWithoutHydrating(current, workInProgress, nextChildren, renderLanes) {
    resetHydrationState();
    workInProgress.flags |= 256;
    reconcileChildren(current, workInProgress, nextChildren, renderLanes);
    return workInProgress.child;
  }
  function validateFunctionComponentInDev(workInProgress, Component) {
    Component && Component.childContextTypes && console.error("childContextTypes cannot be defined on a function component.\n  %s.childContextTypes = ...", Component.displayName || Component.name || "Component");
    "function" === typeof Component.getDerivedStateFromProps && (workInProgress = getComponentNameFromType(Component) || "Unknown", didWarnAboutGetDerivedStateOnFunctionComponent[workInProgress] || (console.error("%s: Function components do not support getDerivedStateFromProps.", workInProgress), didWarnAboutGetDerivedStateOnFunctionComponent[workInProgress] = !0));
    "object" === typeof Component.contextType && null !== Component.contextType && (Component = getComponentNameFromType(Component) || "Unknown", didWarnAboutContextTypeOnFunctionComponent[Component] || (console.error("%s: Function components do not support contextType.", Component), didWarnAboutContextTypeOnFunctionComponent[Component] = !0));
  }
  function mountSuspenseOffscreenState(renderLanes) {
    return {
      baseLanes: renderLanes,
      cachePool: getSuspendedCache()
    };
  }
  function getRemainingWorkInPrimaryTree(current, primaryTreeDidDefer, renderLanes) {
    current = null !== current ? current.childLanes & ~renderLanes : 0;
    primaryTreeDidDefer && (current |= workInProgressDeferredLane);
    return current;
  }
  function updateSuspenseComponent(current, workInProgress, renderLanes) {
    var JSCompiler_object_inline_digest_2317;
    var JSCompiler_object_inline_stack_2318 = workInProgress.pendingProps;
    shouldSuspendImpl(workInProgress) && (workInProgress.flags |= 128);
    var JSCompiler_object_inline_componentStack_2319 = !1;
    var didSuspend = 0 !== (workInProgress.flags & 128);
    (JSCompiler_object_inline_digest_2317 = didSuspend) || (JSCompiler_object_inline_digest_2317 = null !== current && null === current.memoizedState ? !1 : 0 !== (suspenseStackCursor.current & ForceSuspenseFallback));
    JSCompiler_object_inline_digest_2317 && (JSCompiler_object_inline_componentStack_2319 = !0, workInProgress.flags &= -129);
    JSCompiler_object_inline_digest_2317 = 0 !== (workInProgress.flags & 32);
```

```
    workInProgress.flags &= -33;
    if (null === current) {
      if (isHydrating) {
        JSCompiler_object_inline_componentStack_2319 ?
pushPrimaryTreeSuspenseHandler(workInProgress) : reuseSuspenseHandlerOnStack(workInProgress);
        if (isHydrating) {
          var JSCompiler_object_inline_message_2316 = nextHydratableInstance;
          var JSCompiler_temp;
          if (!(JSCompiler_temp = !JSCompiler_object_inline_message_2316)) {
            c: {
              var instance = JSCompiler_object_inline_message_2316;
              for (JSCompiler_temp = rootOrSingletonContext; 8 !== instance.nodeType;) {
                if (!JSCompiler_temp) {
                  JSCompiler_temp = null;
                  break c;
                }
                instance = getNextHydratable(instance.nextSibling);
                if (null === instance) {
                  JSCompiler_temp = null;
                  break c;
                }
              }
              JSCompiler_temp = instance;
            }
            null !== JSCompiler_temp ? (warnIfNotHydrating(), workInProgress.memoizedState = {
              dehydrated: JSCompiler_temp,
              treeContext: null !== treeContextProvider ? {
                id: treeContextId,
                overflow: treeContextOverflow
              } : null,
              retryLane: 536870912
            }, instance = createFiber(18, null, null, NoMode), instance.stateNode = JSCompiler_temp,
instance.return = workInProgress, workInProgress.child = instance, hydrationParentFiber =
workInProgress, nextHydratableInstance = null, JSCompiler_temp = !0) : JSCompiler_temp = !1;
            JSCompiler_temp = !JSCompiler_temp;
          }
          JSCompiler_temp && (warnNonHydratedInstance(workInProgress,
JSCompiler_object_inline_message_2316), throwOnHydrationMismatch(workInProgress));
        }
        JSCompiler_object_inline_message_2316 = workInProgress.memoizedState;
        if (null !== JSCompiler_object_inline_message_2316 &&
(JSCompiler_object_inline_message_2316 = JSCompiler_object_inline_message_2316.dehydrated,
null !== JSCompiler_object_inline_message_2316)) return
JSCompiler_object_inline_message_2316.data === SUSPENSE_FALLBACK_START_DATA ?
workInProgress.lanes = 16 : workInProgress.lanes = 536870912, null;
        popSuspenseHandler(workInProgress);
      }
      JSCompiler_object_inline_message_2316 = JSCompiler_object_inline_stack_2318.children;
      JSCompiler_object_inline_stack_2318 = JSCompiler_object_inline_stack_2318.fallback;
```

```
      if (JSCompiler_object_inline_componentStack_2319) return
reuseSuspenseHandlerOnStack(workInProgress), JSCompiler_object_inline_componentStack_2319 =
workInProgress.mode, JSCompiler_object_inline_message_2316 =
mountWorkInProgressOffscreenFiber({
        mode: "hidden",
        children: JSCompiler_object_inline_message_2316
      }, JSCompiler_object_inline_componentStack_2319), JSCompiler_object_inline_stack_2318 =
createFiberFromFragment(JSCompiler_object_inline_stack_2318,
JSCompiler_object_inline_componentStack_2319, renderLanes, null),
JSCompiler_object_inline_message_2316.return = workInProgress,
JSCompiler_object_inline_stack_2318.return = workInProgress,
JSCompiler_object_inline_message_2316.sibling = JSCompiler_object_inline_stack_2318,
workInProgress.child = JSCompiler_object_inline_message_2316,
JSCompiler_object_inline_componentStack_2319 = workInProgress.child,
JSCompiler_object_inline_componentStack_2319.memoizedState =
mountSuspenseOffscreenState(renderLanes),
JSCompiler_object_inline_componentStack_2319.childLanes =
getRemainingWorkInPrimaryTree(current, JSCompiler_object_inline_digest_2317, renderLanes),
workInProgress.memoizedState = SUSPENDED_MARKER, JSCompiler_object_inline_stack_2318;
      pushPrimaryTreeSuspenseHandler(workInProgress);
      return mountSuspensePrimaryChildren(workInProgress,
JSCompiler_object_inline_message_2316);
    }
    var prevState = current.memoizedState;
    if (null !== prevState && (JSCompiler_object_inline_message_2316 = prevState.dehydrated, null !
== JSCompiler_object_inline_message_2316)) {
      if (didSuspend) workInProgress.flags & 256 ?
(pushPrimaryTreeSuspenseHandler(workInProgress), workInProgress.flags &= -257, workInProgress =
retrySuspenseComponentWithoutHydrating(current, workInProgress, renderLanes)) : null !==
workInProgress.memoizedState ? (reuseSuspenseHandlerOnStack(workInProgress),
workInProgress.child = current.child, workInProgress.flags |= 128, workInProgress = null) :
(reuseSuspenseHandlerOnStack(workInProgress), JSCompiler_object_inline_componentStack_2319 =
JSCompiler_object_inline_stack_2318.fallback, JSCompiler_object_inline_message_2316 =
 workInProgress.mode, JSCompiler_object_inline_stack_2318 =
mountWorkInProgressOffscreenFiber({
        mode: "visible",
        children: JSCompiler_object_inline_stack_2318.children
      }, JSCompiler_object_inline_message_2316), JSCompiler_object_inline_componentStack_2319 =
createFiberFromFragment(JSCompiler_object_inline_componentStack_2319,
JSCompiler_object_inline_message_2316, renderLanes, null),
JSCompiler_object_inline_componentStack_2319.flags |= 2,
JSCompiler_object_inline_stack_2318.return = workInProgress,
JSCompiler_object_inline_componentStack_2319.return = workInProgress,
JSCompiler_object_inline_stack_2318.sibling = JSCompiler_object_inline_componentStack_2319,
workInProgress.child = JSCompiler_object_inline_stack_2318, reconcileChildFibers(workInProgress,
current.child, null, renderLanes), JSCompiler_object_inline_stack_2318 = workInProgress.child,
JSCompiler_object_inline_stack_2318.memoizedState = mountSuspenseOffscreenState(renderLanes),
JSCompiler_object_inline_stack_2318.childLanes = getRemainingWorkInPrimaryTree(current,
JSCompiler_object_inline_digest_2317, renderLanes), workInProgress.memoizedState =
```

```
SUSPENDED_MARKER, workInProgress = JSCompiler_object_inline_componentStack_2319);else if (pushPrimaryTreeSuspenseHandler(workInProgress), isHydrating && console.error("We should not be hydrating here. This is a bug in React. Please file a bug."), JSCompiler_object_inline_message_2316.data === SUSPENSE_FALLBACK_START_DATA) {
      JSCompiler_object_inline_digest_2317 = JSCompiler_object_inline_message_2316.nextSibling && JSCompiler_object_inline_message_2316.nextSibling.dataset;
      if (JSCompiler_object_inline_digest_2317) {
        JSCompiler_temp = JSCompiler_object_inline_digest_2317.dgst;
        var message = JSCompiler_object_inline_digest_2317.msg;
        instance = JSCompiler_object_inline_digest_2317.stck;
        var componentStack = JSCompiler_object_inline_digest_2317.cstck;
      }
      JSCompiler_object_inline_message_2316 = message;
      JSCompiler_object_inline_digest_2317 = JSCompiler_temp;
      JSCompiler_object_inline_stack_2318 = instance;
      JSCompiler_temp = JSCompiler_object_inline_componentStack_2319 = componentStack;
      JSCompiler_object_inline_componentStack_2319 = JSCompiler_object_inline_message_2316 ? Error(JSCompiler_object_inline_message_2316) : Error("The server could not finish this Suspense boundary, likely due to an error during server rendering. Switched to client rendering.");
      JSCompiler_object_inline_componentStack_2319.stack = JSCompiler_object_inline_stack_2318 || "";
      JSCompiler_object_inline_componentStack_2319.digest = JSCompiler_object_inline_digest_2317;
      JSCompiler_object_inline_digest_2317 = void 0 === JSCompiler_temp ? null : JSCompiler_temp;
      JSCompiler_object_inline_stack_2318 = {
        value: JSCompiler_object_inline_componentStack_2319,
        source: null,
        stack: JSCompiler_object_inline_digest_2317
      };
      "string" === typeof JSCompiler_object_inline_digest_2317 && CapturedStacks.set(JSCompiler_object_inline_componentStack_2319, JSCompiler_object_inline_stack_2318);
      queueHydrationError(JSCompiler_object_inline_stack_2318);
      workInProgress = retrySuspenseComponentWithoutHydrating(current, workInProgress, renderLanes);
    } else if (didReceiveUpdate || propagateParentContextChanges(current, workInProgress, renderLanes, !1), JSCompiler_object_inline_digest_2317 = 0 !== (renderLanes & current.childLanes), didReceiveUpdate || JSCompiler_object_inline_digest_2317) {
      JSCompiler_object_inline_digest_2317 = workInProgressRoot;
      if (null !== JSCompiler_object_inline_digest_2317) {
        JSCompiler_object_inline_stack_2318 = renderLanes & -renderLanes;
        if (0 !== (JSCompiler_object_inline_stack_2318 & 42)) JSCompiler_object_inline_stack_2318 = 1;else switch (JSCompiler_object_inline_stack_2318) {
          case 2:
            JSCompiler_object_inline_stack_2318 = 1;
            break;
          case 8:
            JSCompiler_object_inline_stack_2318 = 4;
```

```
            break;
          case 32:
            JSCompiler_object_inline_stack_2318 = 16;
            break;
          case 128:
          case 256:
          case 512:
          case 1024:
          case 2048:
          case 4096:
          case 8192:
          case 16384:
          case 32768:
          case 65536:
          case 131072:
          case 262144:
          case 524288:
          case 1048576:
          case 2097152:
          case 4194304:
          case 8388608:
          case 16777216:
          case 33554432:
            JSCompiler_object_inline_stack_2318 = 64;
            break;
          case 268435456:
            JSCompiler_object_inline_stack_2318 = 134217728;
            break;
          default:
            JSCompiler_object_inline_stack_2318 = 0;
        }
        JSCompiler_object_inline_stack_2318 = 0 !== (JSCompiler_object_inline_stack_2318 &
(JSCompiler_object_inline_digest_2317.suspendedLanes | renderLanes)) ? 0 :
JSCompiler_object_inline_stack_2318;
        if (0 !== JSCompiler_object_inline_stack_2318 && JSCompiler_object_inline_stack_2318 !==
prevState.retryLane) throw prevState.retryLane = JSCompiler_object_inline_stack_2318,
enqueueConcurrentRenderForLane(current, JSCompiler_object_inline_stack_2318),
scheduleUpdateOnFiber(JSCompiler_object_inline_digest_2317, current,
JSCompiler_object_inline_stack_2318), SelectiveHydrationException;
      }
      JSCompiler_object_inline_message_2316.data === SUSPENSE_PENDING_START_DATA ||
renderDidSuspendDelayIfPossible();
      workInProgress = retrySuspenseComponentWithoutHydrating(current, workInProgress,
renderLanes);
    } else JSCompiler_object_inline_message_2316.data === SUSPENSE_PENDING_START_DATA
? (workInProgress.flags |= 128, workInProgress.child = current.child, workInProgress =
retryDehydratedSuspenseBoundary.bind(null, current),
JSCompiler_object_inline_message_2316._reactRetry = workInProgress, workInProgress = null) :
(current = prevState.treeContext, nextHydratableInstance =
```

```
getNextHydratable(JSCompiler_object_inline_message_2316.nextSibling), hydrationParentFiber =
workInProgress, isHydrating = !0, hydrationErrors = null, didSuspendOrErrorDEV = !1,
hydrationDiffRootDEV = null, rootOrSingletonContext = !1, null !== current &&
(warnIfNotHydrating(), idStack[idStackIndex++] = treeContextId, idStack[idStackIndex++] =
treeContextOverflow, idStack[idStackIndex++] = treeContextProvider, treeContextId = current.id,
treeContextOverflow = current.overflow, treeContextProvider = workInProgress), workInProgress =
mountSuspensePrimaryChildren(workInProgress, JSCompiler_object_inline_stack_2318.children),
workInProgress.flags |= 4096);
    return workInProgress;
  }
  if (JSCompiler_object_inline_componentStack_2319) return
reuseSuspenseHandlerOnStack(workInProgress), JSCompiler_object_inline_componentStack_2319 =
JSCompiler_object_inline_stack_2318.fallback, JSCompiler_object_inline_message_2316 =
workInProgress.mode, JSCompiler_temp = current.child, instance = JSCompiler_temp.sibling,
JSCompiler_object_inline_stack_2318 = createWorkInProgress(JSCompiler_temp, {
    mode: "hidden",
    children: JSCompiler_object_inline_stack_2318.children
  }), JSCompiler_object_inline_stack_2318.subtreeFlags = JSCompiler_temp.subtreeFlags &
31457280, null !== instance ? JSCompiler_object_inline_componentStack_2319 =
createWorkInProgress(instance, JSCompiler_object_inline_componentStack_2319) :
(JSCompiler_object_inline_componentStack_2319 =
createFiberFromFragment(JSCompiler_object_inline_componentStack_2319,
JSCompiler_object_inline_message_2316, renderLanes, null),
JSCompiler_object_inline_componentStack_2319.flags |= 2),
JSCompiler_object_inline_componentStack_2319.return = workInProgress,
JSCompiler_object_inline_stack_2318.return = workInProgress,
JSCompiler_object_inline_stack_2318.sibling = JSCompiler_object_inline_componentStack_2319,
workInProgress.child = JSCompiler_object_inline_stack_2318, JSCompiler_object_inline_stack_2318
= JSCompiler_object_inline_componentStack_2319, JSCompiler_object_inline_componentStack_2319
= workInProgress.child, JSCompiler_object_inline_message_2316 = current.child.memoizedState, null
=== JSCompiler_object_inline_message_2316 ? JSCompiler_object_inline_message_2316 =
mountSuspenseOffscreenState(renderLanes) : (JSCompiler_temp =
JSCompiler_object_inline_message_2316.cachePool, null !== JSCompiler_temp ? (instance =
CacheContext._currentValue, JSCompiler_temp = JSCompiler_temp.parent !== instance ? {
    parent: instance,
    pool: instance
  } : JSCompiler_temp) : JSCompiler_temp = getSuspendedCache(),
JSCompiler_object_inline_message_2316 = {
    baseLanes: JSCompiler_object_inline_message_2316.baseLanes | renderLanes,
    cachePool: JSCompiler_temp
  }), JSCompiler_object_inline_componentStack_2319.memoizedState =
JSCompiler_object_inline_message_2316,
JSCompiler_object_inline_componentStack_2319.childLanes =
getRemainingWorkInPrimaryTree(current, JSCompiler_object_inline_digest_2317, renderLanes),
workInProgress.memoizedState = SUSPENDED_MARKER, JSCompiler_object_inline_stack_2318;
  pushPrimaryTreeSuspenseHandler(workInProgress);
  renderLanes = current.child;
  current = renderLanes.sibling;
  renderLanes = createWorkInProgress(renderLanes, {
```

```
      mode: "visible",
      children: JSCompiler_object_inline_stack_2318.children
    });
    renderLanes.return = workInProgress;
    renderLanes.sibling = null;
    null !== current && (JSCompiler_object_inline_digest_2317 = workInProgress.deletions, null ===
JSCompiler_object_inline_digest_2317 ? (workInProgress.deletions = [current], workInProgress.flags |
= 16) : JSCompiler_object_inline_digest_2317.push(current));

    workInProgress.child = renderLanes;
    workInProgress.memoizedState = null;
    return renderLanes;
  }
  function mountSuspensePrimaryChildren(workInProgress, primaryChildren) {
    primaryChildren = mountWorkInProgressOffscreenFiber({
      mode: "visible",
      children: primaryChildren
    }, workInProgress.mode);
    primaryChildren.return = workInProgress;
    return workInProgress.child = primaryChildren;
  }
  function mountWorkInProgressOffscreenFiber(offscreenProps, mode) {
    return createFiberFromOffscreen(offscreenProps, mode, 0, null);
  }
  function retrySuspenseComponentWithoutHydrating(current, workInProgress, renderLanes) {
    reconcileChildFibers(workInProgress, current.child, null, renderLanes);
    current = mountSuspensePrimaryChildren(workInProgress, workInProgress.pendingProps.children);
    current.flags |= 2;
    workInProgress.memoizedState = null;
    return current;
  }
  function scheduleSuspenseWorkOnFiber(fiber, renderLanes, propagationRoot) {
    fiber.lanes |= renderLanes;
    var alternate = fiber.alternate;
    null !== alternate && (alternate.lanes |= renderLanes);
    scheduleContextWorkOnParentPath(fiber.return, renderLanes, propagationRoot);
  }
  function validateSuspenseListNestedChild(childSlot, index) {
    var isAnArray = isArrayImpl(childSlot);
    childSlot = !isAnArray && "function" === typeof getIteratorFn(childSlot);
    return isAnArray || childSlot ? (isAnArray = isAnArray ? "array" : "iterable", console.error("A nested
%s was passed to row #%s in <SuspenseList />. Wrap it in an additional SuspenseList to configure its
revealOrder: <SuspenseList revealOrder=...> ... <SuspenseList
revealOrder=...>{%s}</SuspenseList> ... </SuspenseList>", isAnArray, index, isAnArray), !1) : !0;
  }
  function initSuspenseListRenderState(workInProgress, isBackwards, tail, lastContentRow, tailMode)
{
    var renderState = workInProgress.memoizedState;
    null === renderState ? workInProgress.memoizedState = {
```

```
      isBackwards: isBackwards,
      rendering: null,
      renderingStartTime: 0,
      last: lastContentRow,
      tail: tail,
      tailMode: tailMode
    } : (renderState.isBackwards = isBackwards, renderState.rendering = null,
renderState.renderingStartTime = 0, renderState.last = lastContentRow, renderState.tail = tail,
renderState.tailMode = tailMode);
  }
  function updateSuspenseListComponent(current, workInProgress, renderLanes) {
    var nextProps = workInProgress.pendingProps,
      revealOrder = nextProps.revealOrder,
      tailMode = nextProps.tail;
    nextProps = nextProps.children;
    if (void 0 !== revealOrder && "forwards" !== revealOrder && "backwards" !== revealOrder &&
"together" !== revealOrder && !didWarnAboutRevealOrder[revealOrder]) if
(didWarnAboutRevealOrder[revealOrder] = !0, "string" === typeof revealOrder) switch
(revealOrder.toLowerCase()) {
      case "together":
      case "forwards":
      case "backwards":
        console.error('"%s" is not a valid value for revealOrder on <SuspenseList />. Use lowercase "%s"
instead.', revealOrder, revealOrder.toLowerCase());
        break;
      case "forward":
      case "backward":
        console.error('"%s" is not a valid value for revealOrder on <SuspenseList />. React uses the -s
suffix in the spelling. Use "%ss" instead.', revealOrder, revealOrder.toLowerCase());
        break;
      default:
        console.error('"%s" is not a supported revealOrder on <SuspenseList />. Did you mean "together",
"forwards" or "backwards"?', revealOrder);
    } else console.error('%s is not a supported value for revealOrder on <SuspenseList />. Did you mean
"together", "forwards" or "backwards"?', revealOrder);
    void 0 === tailMode || didWarnAboutTailOptions[tailMode] || ("collapsed" !== tailMode &&
"hidden" !== tailMode ? (didWarnAboutTailOptions[tailMode] = !0, console.error('"%s" is not a
supported value for tail on <SuspenseList />. Did you mean "collapsed" or "hidden"?', tailMode)) :
"forwards" !== revealOrder && "backwards" !== revealOrder &&
(didWarnAboutTailOptions[tailMode] = !0, console.error('<SuspenseList tail="%s" /> is only valid if
revealOrder is "forwards" or "backwards". Did you mean to specify revealOrder="forwards"?',
tailMode)));
    a: if (("forwards" === revealOrder || "backwards" === revealOrder) && void 0 !== nextProps &&
null !== nextProps && !1 !== nextProps) if (isArrayImpl(nextProps)) for (var i = 0; i <
nextProps.length; i++) {
      if (!validateSuspenseListNestedChild(nextProps[i], i)) break a;
    } else if (i = getIteratorFn(nextProps), "function" === typeof i) {
      if (i = i.call(nextProps)) for (var step = i.next(), _i = 0; !step.done; step = i.next()) {
        if (!validateSuspenseListNestedChild(step.value, _i)) break a;
```

```
      _i++;
     }
    } else console.error('A single row was passed to a <SuspenseList revealOrder="%s" />. This is not useful since it needs multiple rows. Did you mean to pass multiple children or an array?', revealOrder);
    reconcileChildren(current, workInProgress, nextProps, renderLanes);
    nextProps = suspenseStackCursor.current;
    if (0 !== (nextProps & ForceSuspenseFallback)) nextProps = nextProps & SubtreeSuspenseContextMask | ForceSuspenseFallback, workInProgress.flags |= 128;else {
     if (null !== current && 0 !== (current.flags & 128)) a: for (current = workInProgress.child; null !== current;) {
       if (13 === current.tag) null !== current.memoizedState && scheduleSuspenseWorkOnFiber(current, renderLanes, workInProgress);else if (19 === current.tag) scheduleSuspenseWorkOnFiber(current, renderLanes, workInProgress);else if (null !== current.child) {
         current.child.return = current;
         current = current.child;
         continue;
        }
        if (current === workInProgress) break a;
        for (; null === current.sibling;) {
         if (null === current.return || current.return === workInProgress) break a;
         current = current.return;
        }
        current.sibling.return = current.return;
        current = current.sibling;
      }
      nextProps &= SubtreeSuspenseContextMask;
    }
    push(suspenseStackCursor, nextProps, workInProgress);
    switch (revealOrder) {
     case "forwards":
       renderLanes = workInProgress.child;
       for (revealOrder = null; null !== renderLanes;) current = renderLanes.alternate, null !== current && null === findFirstSuspended(current) && (revealOrder = renderLanes), renderLanes = renderLanes.sibling;
       renderLanes = revealOrder;
       null === renderLanes ? (revealOrder = workInProgress.child, workInProgress.child = null) : (revealOrder = renderLanes.sibling, renderLanes.sibling = null);
       initSuspenseListRenderState(workInProgress, !1, revealOrder, renderLanes, tailMode);
       break;
     case "backwards":
       renderLanes = null;
       revealOrder = workInProgress.child;
       for (workInProgress.child = null; null !== revealOrder;) {
         current = revealOrder.alternate;
         if (null !== current && null === findFirstSuspended(current)) {
           workInProgress.child = revealOrder;
           break;
         }
         current = revealOrder.sibling;
```

```
          revealOrder.sibling = renderLanes;
          renderLanes = revealOrder;
          revealOrder = current;
        }
        initSuspenseListRenderState(workInProgress, !0, renderLanes, null, tailMode);
        break;
      case "together":
        initSuspenseListRenderState(workInProgress, !1, null, null, void 0);
        break;
      default:
        workInProgress.memoizedState = null;
    }
    return workInProgress.child;
  }
  function bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes) {
    null !== current && (workInProgress.dependencies = current.dependencies);
    profilerStartTime = -1;
    workInProgressRootSkippedLanes |= workInProgress.lanes;
    if (0 === (renderLanes & workInProgress.childLanes)) if (null !== current) {
      if (propagateParentContextChanges(current, workInProgress, renderLanes, !1), 0 === (renderLanes
& workInProgress.childLanes)) return null;
    } else return null;
    if (null !== current && workInProgress.child !== current.child) throw Error("Resuming work not
yet implemented.");
    if (null !== workInProgress.child) {
      current = workInProgress.child;
      renderLanes = createWorkInProgress(current, current.pendingProps);
      workInProgress.child = renderLanes;
      for (renderLanes.return = workInProgress; null !== current.sibling;) current = current.sibling,
renderLanes = renderLanes.sibling = createWorkInProgress(current, current.pendingProps),
renderLanes.return = workInProgress;
      renderLanes.sibling = null;
    }
    return workInProgress.child;
  }
  function checkScheduledUpdateOrContext(current, renderLanes) {
    if (0 !== (current.lanes & renderLanes)) return !0;
    current = current.dependencies;
    return null !== current && checkIfContextChanged(current) ? !0 : !1;
  }
  function attemptEarlyBailoutIfNoScheduledUpdate(current, workInProgress, renderLanes) {
    switch (workInProgress.tag) {
      case 3:
        pushHostContainer(workInProgress, workInProgress.stateNode.containerInfo);
        pushProvider(workInProgress, CacheContext, current.memoizedState.cache);
        resetHydrationState();
        break;
      case 27:
      case 5:
```

```
      pushHostContext(workInProgress);
      break;
    case 4:
      pushHostContainer(workInProgress, workInProgress.stateNode.containerInfo);
      break;
    case 10:
      pushProvider(workInProgress, workInProgress.type, workInProgress.memoizedProps.value);
      break;
    case 12:
      0 !== (renderLanes & workInProgress.childLanes) && (workInProgress.flags |= 4);
      workInProgress.flags |= 2048;
      var stateNode = workInProgress.stateNode;
      stateNode.effectDuration = -0;
      stateNode.passiveEffectDuration
= -0;
      break;
    case 13:
      stateNode = workInProgress.memoizedState;
      if (null !== stateNode) {
        if (null !== stateNode.dehydrated) return pushPrimaryTreeSuspenseHandler(workInProgress),
workInProgress.flags |= 128, null;
        if (0 !== (renderLanes & workInProgress.child.childLanes)) return
updateSuspenseComponent(current, workInProgress, renderLanes);
        pushPrimaryTreeSuspenseHandler(workInProgress);
        current = bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
        return null !== current ? current.sibling : null;
      }
      pushPrimaryTreeSuspenseHandler(workInProgress);
      break;
    case 19:
      var didSuspendBefore = 0 !== (current.flags & 128);
      stateNode = 0 !== (renderLanes & workInProgress.childLanes);
      stateNode || (propagateParentContextChanges(current, workInProgress, renderLanes, !1),
stateNode = 0 !== (renderLanes & workInProgress.childLanes));
      if (didSuspendBefore) {
        if (stateNode) return updateSuspenseListComponent(current, workInProgress, renderLanes);
        workInProgress.flags |= 128;
      }
      didSuspendBefore = workInProgress.memoizedState;
      null !== didSuspendBefore && (didSuspendBefore.rendering = null, didSuspendBefore.tail =
null, didSuspendBefore.lastEffect = null);
      push(suspenseStackCursor, suspenseStackCursor.current, workInProgress);
      if (stateNode) break;else return null;
    case 22:
    case 23:
      return workInProgress.lanes = 0, updateOffscreenComponent(current, workInProgress,
renderLanes);
    case 24:
      pushProvider(workInProgress, CacheContext, current.memoizedState.cache);
```

```
    }
    return bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
  }
  function beginWork(current, workInProgress, renderLanes) {
    if (workInProgress._debugNeedsRemount && null !== current) {
      renderLanes = createFiberFromTypeAndProps(workInProgress.type, workInProgress.key,
workInProgress.pendingProps, workInProgress._debugOwner || null, workInProgress.mode,
workInProgress.lanes);
      var returnFiber = workInProgress.return;
      if (null === returnFiber) throw Error("Cannot swap the root fiber.");
      current.alternate = null;
      workInProgress.alternate = null;
      renderLanes.index = workInProgress.index;
      renderLanes.sibling = workInProgress.sibling;
      renderLanes.return = workInProgress.return;
      renderLanes.ref = workInProgress.ref;
      renderLanes._debugInfo = workInProgress._debugInfo;
      if (workInProgress === returnFiber.child) returnFiber.child = renderLanes;else {
        var prevSibling = returnFiber.child;
        if (null === prevSibling) throw Error("Expected parent to have a child.");
        for (; prevSibling.sibling !== workInProgress;) if (prevSibling = prevSibling.sibling, null ===
prevSibling) throw Error("Expected to find the previous sibling.");
        prevSibling.sibling = renderLanes;
      }
      workInProgress = returnFiber.deletions;
      null === workInProgress ? (returnFiber.deletions = [current], returnFiber.flags |= 16) :
workInProgress.push(current);
      renderLanes.flags |= 2;
      return renderLanes;
    }
    if (null !== current) {
      if (current.memoizedProps !== workInProgress.pendingProps || workInProgress.type !==
current.type) didReceiveUpdate = !0;else {
        if (!checkScheduledUpdateOrContext(current, renderLanes) && 0 === (workInProgress.flags &
128)) return didReceiveUpdate = !1, attemptEarlyBailoutIfNoScheduledUpdate(current,
workInProgress, renderLanes);
        didReceiveUpdate = 0 !== (current.flags & 131072) ? !0 : !1;
      }
    } else {
      didReceiveUpdate = !1;
      if (returnFiber = isHydrating) warnIfNotHydrating(), returnFiber = 0 !== (workInProgress.flags &
1048576);
      returnFiber && (returnFiber = workInProgress.index, warnIfNotHydrating(),
pushTreeId(workInProgress, treeForkCount, returnFiber));
    }
    workInProgress.lanes = 0;
    switch (workInProgress.tag) {
      case 16:
        a: if (returnFiber = workInProgress.pendingProps, current =
```

```
callLazyInitInDEV(workInProgress.elementType), workInProgress.type = current, "function" ===
typeof current) shouldConstruct(current) ? (returnFiber = resolveClassComponentProps(current,
returnFiber), workInProgress.tag = 1, workInProgress.type = current =
resolveFunctionForHotReloading(current), workInProgress = updateClassComponent(null,
workInProgress, current, returnFiber, renderLanes)) : (workInProgress.tag = 0,
validateFunctionComponentInDev(workInProgress, current), workInProgress.type = current =
resolveFunctionForHotReloading(current), workInProgress = updateFunctionComponent(null,
workInProgress, current, returnFiber, renderLanes));else {
        if (void 0 !== current && null !== current) if (prevSibling = current.$$typeof, prevSibling ===
REACT_FORWARD_REF_TYPE) {
          workInProgress.tag = 11;
          workInProgress.type = current = resolveForwardRefForHotReloading(current);
          workInProgress = updateForwardRef(null, workInProgress, current, returnFiber, renderLanes);
          break a;
        } else if (prevSibling === REACT_MEMO_TYPE) {
          workInProgress.tag = 14;
          workInProgress = updateMemoComponent(null, workInProgress, current, returnFiber,
renderLanes);
          break a;
        }
        workInProgress = "";
        null !== current && "object" === typeof current && current.$$typeof ===
REACT_LAZY_TYPE && (workInProgress = " Did you wrap a component in React.lazy() more than
once?");
        current = getComponentNameFromType(current) || current;
        throw Error("Element type is invalid. Received a promise that resolves to: " + current + ". Lazy
element type must resolve to a class or function." + workInProgress);
      }
      return workInProgress;
    case 0:
      return updateFunctionComponent(current, workInProgress, workInProgress.type,
workInProgress.pendingProps, renderLanes);
    case 1:
      return returnFiber = workInProgress.type, prevSibling =
resolveClassComponentProps(returnFiber, workInProgress.pendingProps),
updateClassComponent(current, workInProgress, returnFiber, prevSibling, renderLanes);
    case 3:
      a: {
        pushHostContainer(workInProgress, workInProgress.stateNode.containerInfo);
        if (null === current) throw Error("Should have a current fiber. This is a bug in React.");
        var nextProps = workInProgress.pendingProps;
        prevSibling = workInProgress.memoizedState;
        returnFiber = prevSibling.element;
        cloneUpdateQueue(current, workInProgress);
        processUpdateQueue(workInProgress, nextProps, null, renderLanes);
        var nextState = workInProgress.memoizedState;
        nextProps = nextState.cache;
        pushProvider(workInProgress, CacheContext, nextProps);
        nextProps !== prevSibling.cache && propagateContextChanges(workInProgress,
```

```
[CacheContext], renderLanes, !0);
        suspendIfUpdateReadFromEntangledAsyncAction();
        nextProps = nextState.element;
        if (prevSibling.isDehydrated) {
          if (prevSibling = {
            element: nextProps,
            isDehydrated: !1,
            cache: nextState.cache
          }, workInProgress.updateQueue.baseState = prevSibling, workInProgress.memoizedState =
prevSibling, workInProgress.flags & 256) {
            workInProgress = mountHostRootWithoutHydrating(current, workInProgress, nextProps,
renderLanes);
            break a;
          } else if (nextProps !== returnFiber) {
            returnFiber = createCapturedValueAtFiber(Error("This root received an early update, before
anything was able hydrate. Switched the entire root to client rendering."), workInProgress);
            queueHydrationError(returnFiber);
            workInProgress = mountHostRootWithoutHydrating(current, workInProgress, nextProps,
renderLanes);
            break a;
          } else for (nextHydratableInstance =
getNextHydratable(workInProgress.stateNode.containerInfo.firstChild), hydrationParentFiber =
workInProgress, isHydrating = !0, hydrationErrors = null, didSuspendOrErrorDEV = !1,
hydrationDiffRootDEV = null, rootOrSingletonContext = !0, current =
mountChildFibers(workInProgress, null, nextProps, renderLanes), workInProgress.child = current;
current;) current.flags = current.flags & -3 | 4096, current = current.sibling;
        } else {
          resetHydrationState();
          if (nextProps === returnFiber) {
            workInProgress = bailoutOnAlreadyFinishedWork(current, workInProgress, renderLanes);
            break a;
          }
          reconcileChildren(current, workInProgress, nextProps, renderLanes);
        }
        workInProgress = workInProgress.child;
      }
      return workInProgress;
    case 26:
      return markRef(current, workInProgress), null === current ? (current =
getResource(workInProgress.type, null, workInProgress.pendingProps, null)) ?
workInProgress.memoizedState = current : isHydrating || (current = workInProgress.type, renderLanes
= workInProgress.pendingProps, returnFiber = requiredContext(rootInstanceStackCursor.current),
returnFiber = getOwnerDocumentFromRootContainer(returnFiber).createElement(current),
returnFiber[internalInstanceKey] = workInProgress, returnFiber[internalPropsKey] = renderLanes,
setInitialProperties(returnFiber, current, renderLanes), markNodeAsHoistable(returnFiber),
workInProgress.stateNode = returnFiber) : workInProgress.memoizedState =
getResource(workInProgress.type, current.memoizedProps, workInProgress.pendingProps,
current.memoizedState), null;
    case 27:
```

```
      return pushHostContext(workInProgress), null === current && isHydrating && (prevSibling =
requiredContext(rootInstanceStackCursor.current),
 returnFiber = getHostContext(), prevSibling = workInProgress.stateNode =
resolveSingletonInstance(workInProgress.type, workInProgress.pendingProps, prevSibling,
returnFiber, !1), didSuspendOrErrorDEV || (returnFiber = diffHydratedProperties(prevSibling,
workInProgress.type, workInProgress.pendingProps, returnFiber), null !== returnFiber &&
(buildHydrationDiffNode(workInProgress, 0).serverProps = returnFiber)), hydrationParentFiber =
workInProgress, rootOrSingletonContext = !0, nextHydratableInstance =
getNextHydratable(prevSibling.firstChild)), returnFiber = workInProgress.pendingProps.children,
null !== current || isHydrating ? reconcileChildren(current, workInProgress, returnFiber, renderLanes) :
workInProgress.child = reconcileChildFibers(workInProgress, null, returnFiber, renderLanes),
markRef(current, workInProgress), workInProgress.child;
    case 5:
      return null === current && isHydrating && (nextProps = getHostContext(), returnFiber =
validateDOMNesting(workInProgress.type, nextProps.ancestorInfo), prevSibling =
nextHydratableInstance, (nextState = !prevSibling) || (nextState = canHydrateInstance(prevSibling,
workInProgress.type, workInProgress.pendingProps, rootOrSingletonContext), null !== nextState ?
(workInProgress.stateNode = nextState, didSuspendOrErrorDEV || (nextProps =
diffHydratedProperties(nextState, workInProgress.type, workInProgress.pendingProps, nextProps), null
!== nextProps && (buildHydrationDiffNode(workInProgress, 0).serverProps = nextProps)),
hydrationParentFiber = workInProgress, nextHydratableInstance =
getNextHydratable(nextState.firstChild), rootOrSingletonContext = !1, nextProps = !0) : nextProps = !
1, nextState = !nextProps), nextState && (returnFiber && warnNonHydratedInstance(workInProgress,
prevSibling), throwOnHydrationMismatch(workInProgress))), pushHostContext(workInProgress),
prevSibling = workInProgress.type, nextProps = workInProgress.pendingProps, nextState = null !==
current ? current.memoizedProps : null, returnFiber = nextProps.children,
shouldSetTextContent(prevSibling, nextProps) ? returnFiber = null : null !== nextState &&
shouldSetTextContent(prevSibling, nextState) && (workInProgress.flags |= 32), null !==
workInProgress.memoizedState && (prevSibling = renderWithHooks(current, workInProgress,
TransitionAwareHostComponent, null, null, renderLanes), HostTransitionContext._currentValue =
prevSibling), markRef(current, workInProgress), reconcileChildren(current, workInProgress,
returnFiber, renderLanes), workInProgress.child;
    case 6:
      return null === current && isHydrating && (current = workInProgress.pendingProps,
renderLanes = getHostContext().ancestorInfo.current, current = null != renderLanes ?
validateTextNesting(current, renderLanes.tag) : !0, renderLanes = nextHydratableInstance, (returnFiber
= !renderLanes) || (returnFiber = canHydrateTextInstance(renderLanes, workInProgress.pendingProps,
rootOrSingletonContext), null !== returnFiber ? (workInProgress.stateNode = returnFiber,
hydrationParentFiber = workInProgress, nextHydratableInstance = null, returnFiber = !0) : returnFiber
= !1, returnFiber = !returnFiber), returnFiber && (current &&
warnNonHydratedInstance(workInProgress, renderLanes),
throwOnHydrationMismatch(workInProgress))), null;
    case 13:
      return updateSuspenseComponent(current, workInProgress, renderLanes);
    case 4:
      return pushHostContainer(workInProgress, workInProgress.stateNode.containerInfo), returnFiber
= workInProgress.pendingProps, null === current ? workInProgress.child =
reconcileChildFibers(workInProgress, null, returnFiber, renderLanes) : reconcileChildren(current,
workInProgress, returnFiber, renderLanes), workInProgress.child;
```

```
    case 11:
      return updateForwardRef(current, workInProgress, workInProgress.type,
workInProgress.pendingProps, renderLanes);
    case 7:
      return reconcileChildren(current, workInProgress, workInProgress.pendingProps, renderLanes),
workInProgress.child;
    case 8:
      return reconcileChildren(current, workInProgress, workInProgress.pendingProps.children,
renderLanes), workInProgress.child;
    case 12:
      return workInProgress.flags |= 4, workInProgress.flags |= 2048, returnFiber =
workInProgress.stateNode, returnFiber.effectDuration = -0, returnFiber.passiveEffectDuration = -0,
reconcileChildren(current, workInProgress, workInProgress.pendingProps.children, renderLanes),
workInProgress.child;
    case 10:
      return returnFiber = workInProgress.type, prevSibling = workInProgress.pendingProps, nextProps
= prevSibling.value, "value" in prevSibling || hasWarnedAboutUsingNoValuePropOnContextProvider ||
(hasWarnedAboutUsingNoValuePropOnContextProvider = !0, console.error("The `value` prop is
required for the `<Context.Provider>`. Did you misspell it or forget to pass it?")),
pushProvider(workInProgress, returnFiber, nextProps), reconcileChildren(current, workInProgress,
prevSibling.children, renderLanes), workInProgress.child;
    case 9:
      return prevSibling = workInProgress.type._context, returnFiber =
workInProgress.pendingProps.children, "function" !== typeof returnFiber && console.error("A context
consumer was rendered with multiple children, or a child that isn't a function. A context consumer
expects a single child that is a function. If you did pass a function, make sure there is no trailing or
leading whitespace around it."), prepareToReadContext(workInProgress), prevSibling =
readContext(prevSibling), markComponentRenderStarted(workInProgress), returnFiber =
callComponentInDEV(returnFiber, prevSibling, void 0), markComponentRenderStopped(),
workInProgress.flags |= 1, reconcileChildren(current, workInProgress, returnFiber, renderLanes),
workInProgress.child;
    case 14:
      return updateMemoComponent(current, workInProgress, workInProgress.type,
workInProgress.pendingProps, renderLanes);
    case 15:
      return updateSimpleMemoComponent(current, workInProgress, workInProgress.type,
workInProgress.pendingProps, renderLanes);
    case 19:
      return updateSuspenseListComponent(current, workInProgress, renderLanes);
    case 22:
      return updateOffscreenComponent(current, workInProgress, renderLanes);
    case 24:
      return prepareToReadContext(workInProgress), returnFiber = readContext(CacheContext), null
=== current ? (prevSibling = peekCacheFromPool(), null === prevSibling && (prevSibling =
workInProgressRoot, nextProps = createCache(), prevSibling.pooledCache = nextProps,
retainCache(nextProps), null !== nextProps && (prevSibling.pooledCacheLanes |= renderLanes),
prevSibling = nextProps), workInProgress.memoizedState = {
        parent: returnFiber,
        cache: prevSibling
```

```
        }, initializeUpdateQueue(workInProgress), pushProvider(workInProgress, CacheContext,
prevSibling)) : (0 !== (current.lanes & renderLanes) && (cloneUpdateQueue(current,
workInProgress), processUpdateQueue(workInProgress, null, null, renderLanes),
suspendIfUpdateReadFromEntangledAsyncAction()), prevSibling = current.memoizedState, nextProps
= workInProgress.memoizedState, prevSibling.parent !== returnFiber ? (prevSibling = {
          parent: returnFiber,
          cache: returnFiber
        }, workInProgress.memoizedState = prevSibling, 0 === workInProgress.lanes &&
(workInProgress.memoizedState = workInProgress.updateQueue.baseState = prevSibling),
pushProvider(workInProgress, CacheContext, returnFiber)) : (returnFiber = nextProps.cache,
pushProvider(workInProgress, CacheContext, returnFiber), returnFiber !== prevSibling.cache &&
propagateContextChanges(workInProgress, [CacheContext], renderLanes, !0))),
reconcileChildren(current, workInProgress, workInProgress.pendingProps.children, renderLanes),
workInProgress.child;
      case 29:
        throw workInProgress.pendingProps;
    }
    throw Error("Unknown unit of work tag (" + workInProgress.tag + "). This error is likely caused by a
bug in React. Please file an issue.");
  }
  function resetContextDependencies() {
    lastContextDependency = currentlyRenderingFiber = null;
    isDisallowedContextReadInDEV = !1;
  }
  function pushProvider(providerFiber, context, nextValue) {
    push(valueCursor, context._currentValue, providerFiber);
    context._currentValue = nextValue;
    push(rendererCursorDEV, context._currentRenderer, providerFiber);
    void 0 !== context._currentRenderer && null !== context._currentRenderer &&
context._currentRenderer !== rendererSigil && console.error("Detected multiple renderers
concurrently rendering the same context provider. This is currently unsupported.");
    context._currentRenderer = rendererSigil;
  }
  function popProvider(context, providerFiber) {
    context._currentValue = valueCursor.current;
    var currentRenderer = rendererCursorDEV.current;
    pop(rendererCursorDEV, providerFiber);
    context._currentRenderer = currentRenderer;
    pop(valueCursor, providerFiber);
  }
  function scheduleContextWorkOnParentPath(parent, renderLanes, propagationRoot) {
    for (; null !== parent;) {
      var alternate = parent.alternate;
      (parent.childLanes & renderLanes) !== renderLanes ? (parent.childLanes |= renderLanes, null !==
alternate && (alternate.childLanes |= renderLanes)) : null !== alternate && (alternate.childLanes &
renderLanes) !== renderLanes && (alternate.childLanes |= renderLanes);
      if (parent === propagationRoot) break;
      parent = parent.return;
    }
```

```
    parent !== propagationRoot && console.error("Expected to find the propagation root when
scheduling context work. This error is likely caused by a bug in React. Please file an issue.");
  }
  function propagateContextChanges(workInProgress, contexts, renderLanes,
forcePropagateEntireTree) {
    var fiber = workInProgress.child;
    null !== fiber && (fiber.return = workInProgress);
    for (; null !== fiber;) {
      var list = fiber.dependencies;

      if (null !== list) {
        var nextFiber = fiber.child;
        list = list.firstContext;
        a: for (; null !== list;) {
          var dependency = list;
          list = fiber;
          for (var i = 0; i < contexts.length; i++) if (dependency.context === contexts[i]) {
            list.lanes |= renderLanes;
            dependency = list.alternate;
            null !== dependency && (dependency.lanes |= renderLanes);
            scheduleContextWorkOnParentPath(list.return, renderLanes, workInProgress);
            forcePropagateEntireTree || (nextFiber = null);
            break a;
          }
          list = dependency.next;
        }
      } else if (18 === fiber.tag) {
        nextFiber = fiber.return;
        if (null === nextFiber) throw Error("We just came from a parent so we must have had a parent.
This is a bug in React.");
        nextFiber.lanes |= renderLanes;
        list = nextFiber.alternate;
        null !== list && (list.lanes |= renderLanes);
        scheduleContextWorkOnParentPath(nextFiber, renderLanes, workInProgress);
        nextFiber = null;
      } else nextFiber = fiber.child;
      if (null !== nextFiber) nextFiber.return = fiber;else for (nextFiber = fiber; null !== nextFiber;) {
        if (nextFiber === workInProgress) {
          nextFiber = null;
          break;
        }
        fiber = nextFiber.sibling;
        if (null !== fiber) {
          fiber.return = nextFiber.return;
          nextFiber = fiber;
          break;
        }
        nextFiber = nextFiber.return;
      }
```

```
      fiber = nextFiber;
    }
  }
  function propagateParentContextChanges(current, workInProgress, renderLanes,
forcePropagateEntireTree) {
    current = null;
    for (var parent = workInProgress, isInsidePropagationBailout = !1; null !== parent;) {
      if (!isInsidePropagationBailout) if (0 !== (parent.flags & 524288)) isInsidePropagationBailout = !
0;else if (0 !== (parent.flags & 262144)) break;
      if (10 === parent.tag) {
        var currentParent = parent.alternate;
        if (null === currentParent) throw Error("Should have a current fiber. This is a bug in React.");
        currentParent = currentParent.memoizedProps;
        if (null !== currentParent) {
          var context = parent.type;
          objectIs(parent.pendingProps.value, currentParent.value) || (null !== current ?
current.push(context) : current = [context]);
        }
      } else if (parent === hostTransitionProviderCursor.current) {
        currentParent = parent.alternate;
        if (null === currentParent) throw Error("Should have a current fiber. This is a bug in React.");
        currentParent.memoizedState.memoizedState !== parent.memoizedState.memoizedState && (null
!== current ? current.push(HostTransitionContext) : current = [HostTransitionContext]);
      }
      parent = parent.return;
    }
    null !== current && propagateContextChanges(workInProgress, current, renderLanes,
forcePropagateEntireTree);
    workInProgress.flags |= 262144;
  }
  function checkIfContextChanged(currentDependencies) {
    for (currentDependencies = currentDependencies.firstContext; null !== currentDependencies;) {
      if (!objectIs(currentDependencies.context._currentValue, currentDependencies.memoizedValue))
return !0;
      currentDependencies = currentDependencies.next;
    }
    return !1;
  }
  function prepareToReadContext(workInProgress) {
    currentlyRenderingFiber = workInProgress;
    lastContextDependency = null;
    workInProgress = workInProgress.dependencies;
    null !== workInProgress && (workInProgress.firstContext = null);
  }
  function readContext(context) {
    isDisallowedContextReadInDEV && console.error("Context can only be read while React is
rendering. In classes, you can read it in the render method or getDerivedStateFromProps. In function
components, you can read it directly in the function body, but not inside Hooks like useReducer() or
useMemo().");
```

```
  return readContextForConsumer(currentlyRenderingFiber, context);
}
function readContextDuringReconciliation(consumer, context) {
  null === currentlyRenderingFiber && prepareToReadContext(consumer);
  return readContextForConsumer(consumer, context);
}
function readContextForConsumer(consumer, context) {
  var value = context._currentValue;
  context = {
    context: context,
    memoizedValue: value,
    next: null
  };
  if (null === lastContextDependency) {
    if (null === consumer) throw Error("Context can only be read while React is rendering. In classes, you can read it in the render method or getDerivedStateFromProps. In function components, you can read it directly in the function body, but not inside Hooks like useReducer() or useMemo().");
    lastContextDependency = context;
    consumer.dependencies = {
      lanes: 0,
      firstContext: context,
      _debugThenableState: null
    };
    consumer.flags |= 524288;
  } else lastContextDependency = lastContextDependency.next = context;
  return value;
}
function initializeUpdateQueue(fiber) {
  fiber.updateQueue = {
    baseState: fiber.memoizedState,
    firstBaseUpdate: null,
    lastBaseUpdate: null,
    shared: {
      pending: null,
      lanes: 0,
      hiddenCallbacks: null
    },
    callbacks: null
  };
}
function cloneUpdateQueue(current, workInProgress) {
  current = current.updateQueue;
  workInProgress.updateQueue === current && (workInProgress.updateQueue = {
    baseState: current.baseState,
    firstBaseUpdate: current.firstBaseUpdate,
    lastBaseUpdate: current.lastBaseUpdate,
    shared: current.shared,
    callbacks: null
  });
```

```
  }
  function createUpdate(lane) {
    return {
      lane: lane,
      tag: UpdateState,
      payload: null,
      callback: null,
      next: null
    };
  }
  function enqueueUpdate(fiber, update, lane) {
    var updateQueue = fiber.updateQueue;
    if (null === updateQueue) return null;
    updateQueue = updateQueue.shared;
    if (currentlyProcessingQueue === updateQueue && !didWarnUpdateInsideUpdate) {
      var componentName = getComponentNameFromFiber(fiber);
      console.error("An update (setState, replaceState, or forceUpdate) was scheduled from inside an
update function. Update functions should be pure, with zero side-effects. Consider using
componentDidUpdate or a callback.\n\nPlease update the following component: %s",
componentName);
      didWarnUpdateInsideUpdate = !0;
    }
    if ((executionContext & RenderContext) !== NoContext) return componentName =
updateQueue.pending, null === componentName ? update.next = update : (update.next =
componentName.next, componentName.next = update), updateQueue.pending = update, update =
getRootForUpdatedFiber(fiber), markUpdateLaneFromFiberToRoot(fiber, null, lane), update;
    enqueueUpdate$1(fiber, updateQueue, update, lane);
    return getRootForUpdatedFiber(fiber);
  }
  function entangleTransitions(root, fiber, lane) {
    fiber = fiber.updateQueue;
    if (null !== fiber && (fiber = fiber.shared, 0 !== (lane & 4194176))) {
      var queueLanes = fiber.lanes;
      queueLanes &= root.pendingLanes;
      lane |= queueLanes;
      fiber.lanes = lane;
      markRootEntangled(root, lane);
    }
  }
  function enqueueCapturedUpdate(workInProgress, capturedUpdate) {
    var queue = workInProgress.updateQueue,
      current = workInProgress.alternate;
    if (null !== current && (current = current.updateQueue, queue === current)) {
      var newFirst = null,
        newLast = null;
      queue = queue.firstBaseUpdate;
      if (null !== queue) {
        do {
          var clone = {
```

```
          lane: queue.lane,
          tag: queue.tag,
          payload: queue.payload,
          callback: null,
          next: null
        };
        null === newLast ? newFirst = newLast = clone : newLast = newLast.next = clone;
        queue = queue.next;
      } while (null !== queue);
      null === newLast ? newFirst = newLast = capturedUpdate : newLast = newLast.next =
capturedUpdate;
    } else newFirst = newLast = capturedUpdate;
    queue = {
      baseState: current.baseState,
      firstBaseUpdate: newFirst,
      lastBaseUpdate: newLast,
      shared: current.shared,
      callbacks: current.callbacks
    };
    workInProgress.updateQueue = queue;
    return;
  }
  workInProgress = queue.lastBaseUpdate;
  null === workInProgress ? queue.firstBaseUpdate = capturedUpdate : workInProgress.next =
capturedUpdate;
  queue.lastBaseUpdate = capturedUpdate;
}
function suspendIfUpdateReadFromEntangledAsyncAction() {
  if (didReadFromEntangledAsyncAction) {
    var entangledActionThenable = currentEntangledActionThenable;
    if (null !== entangledActionThenable) throw entangledActionThenable;
  }
}
function processUpdateQueue(workInProgress, props, instance$jscomp$0, renderLanes) {
  didReadFromEntangledAsyncAction = !1;
  var queue = workInProgress.updateQueue;
  hasForceUpdate = !1;
  currentlyProcessingQueue = queue.shared;
  var firstBaseUpdate = queue.firstBaseUpdate,
    lastBaseUpdate = queue.lastBaseUpdate,
    pendingQueue = queue.shared.pending;
  if (null !== pendingQueue) {
    queue.shared.pending = null;
    var lastPendingUpdate = pendingQueue,
      firstPendingUpdate = lastPendingUpdate.next;
    lastPendingUpdate.next = null;
    null === lastBaseUpdate ? firstBaseUpdate = firstPendingUpdate : lastBaseUpdate.next =
firstPendingUpdate;
    lastBaseUpdate = lastPendingUpdate;
```

```
    var current = workInProgress.alternate;
    null !== current && (current = current.updateQueue, pendingQueue = current.lastBaseUpdate,
pendingQueue !== lastBaseUpdate && (null === pendingQueue ? current.firstBaseUpdate =
firstPendingUpdate : pendingQueue.next = firstPendingUpdate, current.lastBaseUpdate =
lastPendingUpdate));

  }
  if (null !== firstBaseUpdate) {
    var newState = queue.baseState;
    lastBaseUpdate = 0;
    current = firstPendingUpdate = lastPendingUpdate = null;
    pendingQueue = firstBaseUpdate;
    do {
      var updateLane = pendingQueue.lane & -536870913,
        isHiddenUpdate = updateLane !== pendingQueue.lane;
      if (isHiddenUpdate ? (workInProgressRootRenderLanes & updateLane) === updateLane :
(renderLanes & updateLane) === updateLane) {
        0 !== updateLane && updateLane === currentEntangledLane &&
(didReadFromEntangledAsyncAction = !0);
        null !== current && (current = current.next = {
          lane: 0,
          tag: pendingQueue.tag,
          payload: pendingQueue.payload,
          callback: null,
          next: null
        });
        a: {
          updateLane = workInProgress;
          var partialState = pendingQueue;
          var nextProps = props,
            instance = instance$jscomp$0;
          switch (partialState.tag) {
            case ReplaceState:
              partialState = partialState.payload;
              if ("function" === typeof partialState) {
                isDisallowedContextReadInDEV = !0;
                var nextState = partialState.call(instance, newState, nextProps);
                if (updateLane.mode & StrictLegacyMode) {
                  setIsStrictModeForDevtools(!0);
                  try {
                    partialState.call(instance, newState, nextProps);
                  } finally {
                    setIsStrictModeForDevtools(!1);
                  }
                }
                isDisallowedContextReadInDEV = !1;
                newState = nextState;
                break a;
              }
```

```
            newState = partialState;
            break a;
          case CaptureUpdate:
            updateLane.flags = updateLane.flags & -65537 | 128;
          case UpdateState:
            nextState = partialState.payload;
            if ("function" === typeof nextState) {
              isDisallowedContextReadInDEV = !0;
              partialState = nextState.call(instance, newState, nextProps);
              if (updateLane.mode & StrictLegacyMode) {
                setIsStrictModeForDevtools(!0);
                try {
                  nextState.call(instance, newState, nextProps);
                } finally {
                  setIsStrictModeForDevtools(!1);
                }
              }
              isDisallowedContextReadInDEV = !1;
            } else partialState = nextState;
            if (null === partialState || void 0 === partialState) break a;
            newState = assign({}, newState, partialState);
            break a;
          case ForceUpdate:
            hasForceUpdate = !0;
        }
      }
      updateLane = pendingQueue.callback;
      null !== updateLane && (workInProgress.flags |= 64, isHiddenUpdate &&
(workInProgress.flags |= 8192), isHiddenUpdate = queue.callbacks, null === isHiddenUpdate ?
queue.callbacks = [updateLane] : isHiddenUpdate.push(updateLane));
    } else isHiddenUpdate = {
      lane: updateLane,
      tag: pendingQueue.tag,
      payload: pendingQueue.payload,
      callback: pendingQueue.callback,
      next: null
    }, null === current ? (firstPendingUpdate = current = isHiddenUpdate, lastPendingUpdate =
newState) : current = current.next = isHiddenUpdate, lastBaseUpdate |= updateLane;
    pendingQueue = pendingQueue.next;
    if (null === pendingQueue) if (pendingQueue = queue.shared.pending, null === pendingQueue)
break;else isHiddenUpdate = pendingQueue, pendingQueue = isHiddenUpdate.next,
isHiddenUpdate.next = null, queue.lastBaseUpdate = isHiddenUpdate, queue.shared.pending = null;
  } while (1);
  null === current && (lastPendingUpdate = newState);
  queue.baseState = lastPendingUpdate;
  queue.firstBaseUpdate = firstPendingUpdate;
  queue.lastBaseUpdate = current;
  null === firstBaseUpdate && (queue.shared.lanes = 0);
  workInProgressRootSkippedLanes |= lastBaseUpdate;
```

```
      workInProgress.lanes = lastBaseUpdate;
      workInProgress.memoizedState = newState;
    }
    currentlyProcessingQueue = null;
  }
  function callCallback(callback, context) {
    if ("function" !== typeof callback) throw Error("Invalid argument passed as callback. Expected a
function. Instead received: " + callback);
    callback.call(context);
  }
  function commitHiddenCallbacks(updateQueue, context) {
    var hiddenCallbacks = updateQueue.shared.hiddenCallbacks;
    if (null !== hiddenCallbacks) for (updateQueue.shared.hiddenCallbacks = null, updateQueue = 0;
updateQueue < hiddenCallbacks.length; updateQueue++) callCallback(hiddenCallbacks[updateQueue],
context);
  }
  function commitCallbacks(updateQueue, context) {
    var callbacks = updateQueue.callbacks;
    if (null !== callbacks) for (updateQueue.callbacks = null, updateQueue = 0; updateQueue <
callbacks.length; updateQueue++) callCallback(callbacks[updateQueue], context);
  }
  function shouldProfile(current) {
    return (current.mode & ProfileMode) !== NoMode;
  }
  function commitHookLayoutEffects(finishedWork, hookFlags) {
    shouldProfile(finishedWork) ? (startEffectTimer(), commitHookEffectListMount(hookFlags,
finishedWork), recordEffectDuration()) : commitHookEffectListMount(hookFlags, finishedWork);
  }
  function commitHookLayoutUnmountEffects(finishedWork, nearestMountedAncestor, hookFlags) {
    shouldProfile(finishedWork) ? (startEffectTimer(), commitHookEffectListUnmount(hookFlags,
finishedWork, nearestMountedAncestor), recordEffectDuration()) :
commitHookEffectListUnmount(hookFlags, finishedWork, nearestMountedAncestor);
  }
  function commitHookEffectListMount(flags, finishedWork) {
    try {
      var updateQueue = finishedWork.updateQueue,
        lastEffect = null !== updateQueue ? updateQueue.lastEffect : null;
      if (null !== lastEffect) {
        var firstEffect = lastEffect.next;
        updateQueue = firstEffect;
        do {
          if ((updateQueue.tag & flags) === flags && ((flags & Passive) !== NoFlags ? null !==
injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentPassiveEffectMountStarted &&
injectedProfilingHooks.markComponentPassiveEffectMountStarted(finishedWork) : (flags & Layout) !
== NoFlags && null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentLayoutEffectMountStarted &&
injectedProfilingHooks.markComponentLayoutEffectMountStarted(finishedWork), lastEffect = void 0,
(flags & Insertion) !== NoFlags && (isRunningInsertionEffect = !0), lastEffect =
```

```
runWithFiberInDEV(finishedWork, callCreateInDEV, updateQueue), (flags & Insertion) !== NoFlags && (isRunningInsertionEffect = !1), (flags & Passive) !== NoFlags ? null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markComponentPassiveEffectMountStopped && injectedProfilingHooks.markComponentPassiveEffectMountStopped() : (flags & Layout) !== NoFlags && null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markComponentLayoutEffectMountStopped && injectedProfilingHooks.markComponentLayoutEffectMountStopped(), void 0 !== lastEffect && "function" !== typeof lastEffect)) {
          var hookName = void 0;
          hookName = 0 !== (updateQueue.tag & Layout) ? "useLayoutEffect" : 0 !== (updateQueue.tag & Insertion) ? "useInsertionEffect" : "useEffect";
          var addendum = void 0;
          addendum = null === lastEffect ? " You returned null. If your effect does not require clean up, return undefined (or nothing)." : "function" === typeof lastEffect.then ? "\n\nIt looks like you wrote " + hookName + "(async () => ...) or returned a Promise. Instead, write the async function inside your effect and call it immediately:\n\n" + hookName + "(() => {\n  async function fetchData() {\n    // You can await here\n    const response = await MyAPI.getData(someId);\n    // ...\n  }\n  fetchData();\n}, [someId]); // Or [] if effect doesn't need props or state\n\nLearn more about data fetching with Hooks: https://react.dev/link/hooks-data-fetching" : " You returned: " + lastEffect;
          runWithFiberInDEV(finishedWork, function (n, a) {
            console.error("%s must not return anything besides a function, which is used for clean-up.%s", n, a);
          }, hookName, addendum);
        }
        updateQueue = updateQueue.next;
      } while (updateQueue !== firstEffect);
    }
  } catch (error) {
    captureCommitPhaseError(finishedWork, finishedWork.return, error);
  }
 }
 function commitHookEffectListUnmount(flags, finishedWork, nearestMountedAncestor) {
  try {
    var updateQueue = finishedWork.updateQueue,
      lastEffect = null !== updateQueue ? updateQueue.lastEffect : null;
    if (null !== lastEffect) {
      var firstEffect = lastEffect.next;
      updateQueue = firstEffect;
      do {
        if ((updateQueue.tag & flags) === flags) {
          var inst = updateQueue.inst,
            destroy = inst.destroy;
          void 0 !== destroy && (inst.destroy = void 0, (flags & Passive) !== NoFlags ? null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markComponentPassiveEffectUnmountStarted && injectedProfilingHooks.markComponentPassiveEffectUnmountStarted(finishedWork) : (flags & Layout) !== NoFlags && null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markComponentLayoutEffectUnmountStarted && injectedProfilingHooks.markComponentLayoutEffectUnmountStarted(finishedWork), (flags &
```

```
Insertion) !== NoFlags && (isRunningInsertionEffect = !0), runWithFiberInDEV(finishedWork,
callDestroyInDEV, finishedWork,
 nearestMountedAncestor, destroy), (flags & Insertion) !== NoFlags && (isRunningInsertionEffect = !
1), (flags & Passive) !== NoFlags ? null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentPassiveEffectUnmountStopped &&
injectedProfilingHooks.markComponentPassiveEffectUnmountStopped() : (flags & Layout) !==
NoFlags && null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentLayoutEffectUnmountStopped &&
injectedProfilingHooks.markComponentLayoutEffectUnmountStopped());
        }
        updateQueue = updateQueue.next;
      } while (updateQueue !== firstEffect);
    }
  } catch (error) {
    captureCommitPhaseError(finishedWork, finishedWork.return, error);
  }
 }
 function commitHookPassiveMountEffects(finishedWork, hookFlags) {
  shouldProfile(finishedWork) ? (startEffectTimer(), commitHookEffectListMount(hookFlags,
finishedWork), recordEffectDuration()) : commitHookEffectListMount(hookFlags, finishedWork);
 }
 function commitHookPassiveUnmountEffects(finishedWork, nearestMountedAncestor, hookFlags) {
  shouldProfile(finishedWork) ? (startEffectTimer(), commitHookEffectListUnmount(hookFlags,
finishedWork, nearestMountedAncestor), recordEffectDuration()) :
commitHookEffectListUnmount(hookFlags, finishedWork, nearestMountedAncestor);
 }
 function commitClassCallbacks(finishedWork) {
  var updateQueue = finishedWork.updateQueue;
  if (null !== updateQueue) {
    var instance = finishedWork.stateNode;
    finishedWork.type.defaultProps || "ref" in finishedWork.memoizedProps ||
didWarnAboutReassigningProps || (instance.props !== finishedWork.memoizedProps &&
console.error("Expected %s props to match memoized props before processing the update queue. This
might either be because of a bug in React, or because a component reassigns its own `this.props`.
Please file an issue.", getComponentNameFromFiber(finishedWork) || "instance"), instance.state !==
finishedWork.memoizedState && console.error("Expected %s state to match memoized state before
processing the update queue. This might either be because of a bug in React, or because a component
reassigns its own `this.state`. Please file an issue.", getComponentNameFromFiber(finishedWork) ||
"instance"));
    try {
      runWithFiberInDEV(finishedWork, commitCallbacks, updateQueue, instance);
    } catch (error) {
      captureCommitPhaseError(finishedWork, finishedWork.return, error);
    }
  }
 }
 function callGetSnapshotBeforeUpdates(instance, prevProps, prevState) {
  return instance.getSnapshotBeforeUpdate(prevProps, prevState);
 }
```

```
  function commitClassSnapshot(finishedWork, current) {
    var prevProps = current.memoizedProps,
      prevState = current.memoizedState;
    current = finishedWork.stateNode;
    finishedWork.type.defaultProps || "ref" in finishedWork.memoizedProps ||
didWarnAboutReassigningProps || (current.props !== finishedWork.memoizedProps &&
console.error("Expected %s props to match memoized props before getSnapshotBeforeUpdate. This
might either be because of a bug in React, or because a component reassigns its own `this.props`.
Please file an issue.", getComponentNameFromFiber(finishedWork) || "instance"), current.state !==
finishedWork.memoizedState && console.error("Expected %s state to match memoized state before
getSnapshotBeforeUpdate. This might either be because of a bug in React, or because a component
reassigns its own `this.state`. Please file an issue.", getComponentNameFromFiber(finishedWork) ||
"instance"));
    try {
      var resolvedPrevProps = resolveClassComponentProps(finishedWork.type, prevProps,
finishedWork.elementType === finishedWork.type);
      var snapshot = runWithFiberInDEV(finishedWork, callGetSnapshotBeforeUpdates, current,
resolvedPrevProps, prevState);
      prevProps = didWarnAboutUndefinedSnapshotBeforeUpdate;
      void 0 !== snapshot || prevProps.has(finishedWork.type) || (prevProps.add(finishedWork.type),
runWithFiberInDEV(finishedWork, function () {
        console.error("%s.getSnapshotBeforeUpdate(): A snapshot value (or null) must be returned. You
have returned undefined.", getComponentNameFromFiber(finishedWork));
      }));
      current.__reactInternalSnapshotBeforeUpdate = snapshot;
    } catch (error) {
      captureCommitPhaseError(finishedWork, finishedWork.return, error);
    }
  }
  function safelyCallComponentWillUnmount(current, nearestMountedAncestor, instance) {
    instance.props = resolveClassComponentProps(current.type, current.memoizedProps);
    instance.state = current.memoizedState;
    shouldProfile(current) ? (startEffectTimer(), runWithFiberInDEV(current,
callComponentWillUnmountInDEV, current, nearestMountedAncestor, instance),
recordEffectDuration()) : runWithFiberInDEV(current, callComponentWillUnmountInDEV, current,
nearestMountedAncestor, instance);
  }
  function commitAttachRef(finishedWork) {
    var ref = finishedWork.ref;
    if (null !== ref) {
      var instance = finishedWork.stateNode;
      if ("function" === typeof ref) {
        if (shouldProfile(finishedWork)) try {
          startEffectTimer(), finishedWork.refCleanup = ref(instance);
        } finally {
          recordEffectDuration();
        } else finishedWork.refCleanup = ref(instance);
      } else "string" === typeof ref ? console.error("String refs are no longer supported.") :
ref.hasOwnProperty("current") || console.error("Unexpected ref object provided for %s. Use either a
```

```
ref-setter function or React.createRef().", getComponentNameFromFiber(finishedWork)), ref.current =
instance;
    }
  }
  function safelyAttachRef(current, nearestMountedAncestor) {
    try {
      runWithFiberInDEV(current, commitAttachRef, current);
    } catch (error) {
      captureCommitPhaseError(current, nearestMountedAncestor, error);
    }
  }
  function safelyDetachRef(current, nearestMountedAncestor) {
    var ref = current.ref,
      refCleanup = current.refCleanup;
    if (null !== ref) if ("function" === typeof refCleanup) try {
      if (shouldProfile(current)) try {
        startEffectTimer(), runWithFiberInDEV(current, refCleanup);
      } finally {
        recordEffectDuration(current);
      } else runWithFiberInDEV(current, refCleanup);
    } catch (error) {
      captureCommitPhaseError(current, nearestMountedAncestor, error);
    } finally {
      current.refCleanup = null, current = current.alternate, null != current && (current.refCleanup =
null);
    } else if ("function" === typeof ref) try {
      if (shouldProfile(current)) try {
        startEffectTimer(), runWithFiberInDEV(current, ref, null);
      } finally {
        recordEffectDuration(current);
      } else runWithFiberInDEV(current, ref, null);
    } catch (error$6) {
      captureCommitPhaseError(current, nearestMountedAncestor, error$6);
    } else ref.current = null;
  }
  function commitProfiler(finishedWork, current, commitStartTime, effectDuration) {
    var _finishedWork$memoize = finishedWork.memoizedProps,
      id = _finishedWork$memoize.id,
      onCommit = _finishedWork$memoize.onCommit;
    _finishedWork$memoize = _finishedWork$memoize.onRender;
    current = null === current ? "mount" : "update";
    currentUpdateIsNested && (current = "nested-update");
    "function" === typeof _finishedWork$memoize && _finishedWork$memoize(id, current,
finishedWork.actualDuration, finishedWork.treeBaseDuration, finishedWork.actualStartTime,
commitStartTime);
    "function" === typeof onCommit && onCommit(finishedWork.memoizedProps.id, current,
effectDuration, commitStartTime);
  }
  function commitProfilerPostCommitImpl(finishedWork, current, commitStartTime,
```

```
passiveEffectDuration) {
    var _finishedWork$memoize2 = finishedWork.memoizedProps;
    finishedWork = _finishedWork$memoize2.id;
    _finishedWork$memoize2 = _finishedWork$memoize2.onPostCommit;
    current = null === current ? "mount" : "update";
    currentUpdateIsNested && (current = "nested-update");
    "function" === typeof _finishedWork$memoize2 && _finishedWork$memoize2(finishedWork,
current, passiveEffectDuration, commitStartTime);
  }
  function commitHostMount(finishedWork) {
    var type = finishedWork.type,
      props = finishedWork.memoizedProps,
      instance = finishedWork.stateNode;
    try {
      runWithFiberInDEV(finishedWork, commitMount, instance, type, props, finishedWork);
    } catch (error) {
      captureCommitPhaseError(finishedWork, finishedWork.return, error);
    }
  }
  function commitHostUpdate(finishedWork, newProps, oldProps) {
    try {
      runWithFiberInDEV(finishedWork, commitUpdate, finishedWork.stateNode, finishedWork.type,
oldProps, newProps, finishedWork);
    } catch (error) {
      captureCommitPhaseError(finishedWork, finishedWork.return, error);
    }
  }
  function isHostParent(fiber) {
    return 5 === fiber.tag || 3 === fiber.tag || 26 === fiber.tag || 27 === fiber.tag || 4 === fiber.tag;
  }
  function getHostSibling(fiber) {
    a: for (;;) {
      for (; null === fiber.sibling;) {
        if (null === fiber.return || isHostParent(fiber.return)) return null;
        fiber = fiber.return;
      }
      fiber.sibling.return = fiber.return;
      for (fiber = fiber.sibling; 5 !== fiber.tag && 6 !== fiber.tag && 27 !== fiber.tag && 18 !==
fiber.tag;) {
        if (fiber.flags & 2) continue a;
        if (null === fiber.child || 4 === fiber.tag) continue a;else fiber.child.return = fiber, fiber =
fiber.child;
      }
      if (!(fiber.flags & 2)) return fiber.stateNode;
    }
  }
  function insertOrAppendPlacementNodeIntoContainer(node, before, parent) {
    var tag = node.tag;
    if (5 === tag || 6 === tag) node = node.stateNode, before ? 8 === parent.nodeType ?
```

```
parent.parentNode.insertBefore(node, before) : parent.insertBefore(node, before) : (8 ===
parent.nodeType ? (before = parent.parentNode, before.insertBefore(node,
 parent)) : (before = parent, before.appendChild(node)), parent = parent._reactRootContainer, null !==
parent && void 0 !== parent || null !== before.onclick || (before.onclick = noop$1));else if (4 !== tag
&& 27 !== tag && (node = node.child, null !== node)) for
(insertOrAppendPlacementNodeIntoContainer(node, before, parent), node = node.sibling; null !==
node;) insertOrAppendPlacementNodeIntoContainer(node, before, parent), node = node.sibling;
  }
  function insertOrAppendPlacementNode(node, before, parent) {
    var tag = node.tag;
    if (5 === tag || 6 === tag) node = node.stateNode, before ? parent.insertBefore(node, before) :
parent.appendChild(node);else if (4 !== tag && 27 !== tag && (node = node.child, null !== node)) for
(insertOrAppendPlacementNode(node, before, parent), node = node.sibling; null !== node;)
insertOrAppendPlacementNode(node, before, parent), node = node.sibling;
  }
  function commitPlacement(finishedWork) {
    if (27 !== finishedWork.tag) {
      a: {
        for (var parent = finishedWork.return; null !== parent;) {
          if (isHostParent(parent)) {
            var parentFiber = parent;
            break a;
          }
          parent = parent.return;
        }
        throw Error("Expected to find a host parent. This error is likely caused by a bug in React. Please
file an issue.");
      }
      switch (parentFiber.tag) {
        case 27:
          parent = parentFiber.stateNode;
          parentFiber = getHostSibling(finishedWork);
          insertOrAppendPlacementNode(finishedWork, parentFiber, parent);
          break;
        case 5:
          parent = parentFiber.stateNode;
          parentFiber.flags & 32 && (resetTextContent(parent), parentFiber.flags &= -33);
          parentFiber = getHostSibling(finishedWork);
          insertOrAppendPlacementNode(finishedWork, parentFiber, parent);
          break;
        case 3:
        case 4:
          parent = parentFiber.stateNode.containerInfo;
          parentFiber = getHostSibling(finishedWork);
          insertOrAppendPlacementNodeIntoContainer(finishedWork, parentFiber, parent);
          break;
        default:
          throw Error("Invalid host parent fiber. This error is likely caused by a bug in React. Please file an
issue.");
```

```
      }
    }
  }
  function commitBeforeMutationEffects(root, firstChild) {
    root = root.containerInfo;
    eventsEnabled = _enabled;
    root = getActiveElementDeep(root);
    if (hasSelectionCapabilities(root)) {
      if ("selectionStart" in root) var JSCompiler_temp = {
        start: root.selectionStart,
        end: root.selectionEnd
      };else a: {
        JSCompiler_temp = (JSCompiler_temp = root.ownerDocument) &&
JSCompiler_temp.defaultView || window;
        var selection = JSCompiler_temp.getSelection && JSCompiler_temp.getSelection();
        if (selection && 0 !== selection.rangeCount) {
          JSCompiler_temp = selection.anchorNode;
          var anchorOffset = selection.anchorOffset,
            focusNode = selection.focusNode;
          selection = selection.focusOffset;
          try {
            JSCompiler_temp.nodeType, focusNode.nodeType;
          } catch (e$2) {
            JSCompiler_temp = null;
            break a;
          }
          var length = 0,
            start = -1,
            end = -1,
            indexWithinAnchor = 0,
            indexWithinFocus = 0,
            node = root,
            parentNode = null;
          b: for (;;) {
            for (var next;;) {
              node !== JSCompiler_temp || 0 !== anchorOffset && 3 !== node.nodeType || (start = length +
anchorOffset);
              node !== focusNode || 0 !== selection && 3 !== node.nodeType || (end = length + selection);
              3 === node.nodeType && (length += node.nodeValue.length);
              if (null === (next = node.firstChild)) break;
              parentNode = node;
              node = next;
            }
            for (;;) {
              if (node === root) break b;
              parentNode === JSCompiler_temp && ++indexWithinAnchor === anchorOffset && (start =
length);
              parentNode === focusNode && ++indexWithinFocus === selection && (end = length);
              if (null !== (next = node.nextSibling)) break;
```

```
            node = parentNode;
            parentNode = node.parentNode;
           }
           node = next;
          }
          JSCompiler_temp = -1 === start || -1 === end ? null : {
           start: start,
           end: end
          };
         } else JSCompiler_temp = null;
        }
        JSCompiler_temp = JSCompiler_temp || {
         start: 0,
         end: 0
        };
       } else JSCompiler_temp = null;
       selectionInformation = {
        focusedElem: root,
        selectionRange: JSCompiler_temp
       };
       _enabled = !1;
       for (nextEffect = firstChild; null !== nextEffect;) if (firstChild = nextEffect, root = firstChild.child, 0
!== (firstChild.subtreeFlags & 1028) && null !== root) root.return = firstChild, nextEffect = root;else
for (; null !== nextEffect;) {
        root = firstChild = nextEffect;
        JSCompiler_temp = root.alternate;
        anchorOffset = root.flags;
        switch (root.tag) {
         case 0:
          break;
         case 11:
         case 15:
          break;
         case 1:
          0 !== (anchorOffset & 1024) && null !== JSCompiler_temp && commitClassSnapshot(root,
JSCompiler_temp);
          break;
         case 3:
          if (0 !== (anchorOffset & 1024)) if (root = root.stateNode.containerInfo, JSCompiler_temp =
root.nodeType, 9 === JSCompiler_temp) clearContainerSparingly(root);else if (1 ===
JSCompiler_temp) switch (root.nodeName) {
           case "HEAD":
           case "HTML":
           case "BODY":
            clearContainerSparingly(root);
            break;
           default:
            root.textContent = "";
          }
```

```
        break;
      case 5:
      case 26:
      case 27:
      case 6:
      case 4:
      case 17:
        break;
      default:
        if (0 !== (anchorOffset & 1024)) throw Error("This unit of work tag should not have side-effects. This error is likely caused by a bug in React. Please file an issue.");
    }
    root = firstChild.sibling;
    if (null !== root) {
      root.return = firstChild.return;
      nextEffect = root;
      break;
    }
    nextEffect = firstChild.return;
  }
  firstChild = shouldFireAfterActiveInstanceBlur;
  shouldFireAfterActiveInstanceBlur = !1;
  return firstChild;
}
function commitLayoutEffectOnFiber(finishedRoot, current, finishedWork) {
  var flags = finishedWork.flags;
  switch (finishedWork.tag) {
    case 0:
    case 11:
    case 15:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      flags & 4 && commitHookLayoutEffects(finishedWork, Layout | HasEffect);
      break;
    case 1:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      if (flags & 4) if (finishedRoot = finishedWork.stateNode, null === current) finishedWork.type.defaultProps || "ref" in finishedWork.memoizedProps || didWarnAboutReassigningProps || (finishedRoot.props !== finishedWork.memoizedProps && console.error("Expected %s props to match memoized props before componentDidMount. This might either be because of a bug in React, or because a component reassigns its own `this.props`. Please file an issue.", getComponentNameFromFiber(finishedWork) || "instance"), finishedRoot.state !== finishedWork.memoizedState && console.error("Expected %s state to match memoized state before componentDidMount. This might either be because of a bug in React, or because a component reassigns its own `this.state`. Please file an issue.", getComponentNameFromFiber(finishedWork) || "instance")), shouldProfile(finishedWork) ? (startEffectTimer(), runWithFiberInDEV(finishedWork, callComponentDidMountInDEV, finishedWork, finishedRoot), recordEffectDuration()) : runWithFiberInDEV(finishedWork, callComponentDidMountInDEV, finishedWork, finishedRoot);else {
        var prevProps = resolveClassComponentProps(finishedWork.type, current.memoizedProps);
```

```
        current = current.memoizedState;
        finishedWork.type.defaultProps || "ref" in finishedWork.memoizedProps ||
didWarnAboutReassigningProps || (finishedRoot.props !== finishedWork.memoizedProps &&
console.error("Expected %s props to match memoized props before componentDidUpdate. This might
either be because of a bug in React, or because a component reassigns its own `this.props`. Please file
an issue.", getComponentNameFromFiber(finishedWork) || "instance"), finishedRoot.state !==
finishedWork.memoizedState && console.error("Expected %s state to match memoized state before
componentDidUpdate. This might either be because of a bug in React, or because a component
reassigns its own `this.state`. Please file an issue.", getComponentNameFromFiber(finishedWork) ||
"instance"));
        shouldProfile(finishedWork) ? (startEffectTimer(), runWithFiberInDEV(finishedWork,
callComponentDidUpdateInDEV, finishedWork, finishedRoot, prevProps, current,
finishedRoot.__reactInternalSnapshotBeforeUpdate), recordEffectDuration()) :
runWithFiberInDEV(finishedWork, callComponentDidUpdateInDEV, finishedWork, finishedRoot,
prevProps, current, finishedRoot.__reactInternalSnapshotBeforeUpdate);
      }
      flags & 64 && commitClassCallbacks(finishedWork);
      flags & 512 && safelyAttachRef(finishedWork, finishedWork.return);
      break;
    case 3:
      current = pushNestedEffectDurations();
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      if (flags & 64 && (flags = finishedWork.updateQueue, null !== flags)) {
        prevProps = null;
        if (null !== finishedWork.child) switch (finishedWork.child.tag) {
          case 27:
          case 5:
            prevProps = finishedWork.child.stateNode;

            break;
          case 1:
            prevProps = finishedWork.child.stateNode;
        }
        try {
          runWithFiberInDEV(finishedWork, commitCallbacks, flags, prevProps);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      }
      finishedRoot.effectDuration += popNestedEffectDurations(current);
      break;
    case 26:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      flags & 512 && safelyAttachRef(finishedWork, finishedWork.return);
      break;
    case 27:
    case 5:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      null === current && flags & 4 && commitHostMount(finishedWork);
```

```
      flags & 512 && safelyAttachRef(finishedWork, finishedWork.return);
      break;
    case 12:
      if (flags & 4) {
        flags = pushNestedEffectDurations();
        recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
        finishedRoot = finishedWork.stateNode;
        finishedRoot.effectDuration += bubbleNestedEffectDurations(flags);
        try {
          runWithFiberInDEV(finishedWork, commitProfiler, finishedWork, current, commitStartTime,
finishedRoot.effectDuration);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      } else recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      break;
    case 13:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
      flags & 4 && commitSuspenseHydrationCallbacks(finishedRoot, finishedWork);
      break;
    case 22:
      prevProps = null !== finishedWork.memoizedState || offscreenSubtreeIsHidden;
      if (!prevProps) {
        current = null !== current && null !== current.memoizedState || offscreenSubtreeWasHidden;
        var prevOffscreenSubtreeIsHidden = offscreenSubtreeIsHidden,
          prevOffscreenSubtreeWasHidden = offscreenSubtreeWasHidden;
        offscreenSubtreeIsHidden = prevProps;
        (offscreenSubtreeWasHidden = current) && !prevOffscreenSubtreeWasHidden ?
recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork, 0 !==
(finishedWork.subtreeFlags & 8772)) : recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
        offscreenSubtreeIsHidden = prevOffscreenSubtreeIsHidden;
        offscreenSubtreeWasHidden = prevOffscreenSubtreeWasHidden;
      }
      flags & 512 && ("manual" === finishedWork.memoizedProps.mode ?
safelyAttachRef(finishedWork, finishedWork.return) : safelyDetachRef(finishedWork,
finishedWork.return));
      break;
    default:
      recursivelyTraverseLayoutEffects(finishedRoot, finishedWork);
  }
}
function detachFiberAfterEffects(fiber) {
  var alternate = fiber.alternate;
  null !== alternate && (fiber.alternate = null, detachFiberAfterEffects(alternate));
  fiber.child = null;
  fiber.deletions = null;
  fiber.sibling = null;
  5 === fiber.tag && (alternate = fiber.stateNode, null !== alternate &&
detachDeletedInstance(alternate));
```

```
    fiber.stateNode = null;
    fiber._debugOwner = null;
    fiber.return = null;
    fiber.dependencies = null;
    fiber.memoizedProps = null;
    fiber.memoizedState = null;
    fiber.pendingProps = null;
    fiber.stateNode = null;
    fiber.updateQueue = null;
  }
  function recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, parent) {
    for (parent = parent.child; null !== parent;) commitDeletionEffectsOnFiber(finishedRoot,
nearestMountedAncestor, parent), parent = parent.sibling;
  }
  function commitDeletionEffectsOnFiber(finishedRoot, nearestMountedAncestor, deletedFiber) {
    if (injectedHook && "function" === typeof injectedHook.onCommitFiberUnmount) try {
      injectedHook.onCommitFiberUnmount(rendererID, deletedFiber);
    } catch (err) {
      hasLoggedError || (hasLoggedError = !0, console.error("React instrumentation encountered an
error: %s", err));
    }
    switch (deletedFiber.tag) {
      case 26:
        offscreenSubtreeWasHidden || safelyDetachRef(deletedFiber, nearestMountedAncestor);
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        deletedFiber.memoizedState ? deletedFiber.memoizedState.count-- : deletedFiber.stateNode &&
(deletedFiber = deletedFiber.stateNode, deletedFiber.parentNode.removeChild(deletedFiber));
        break;
      case 27:
        offscreenSubtreeWasHidden || safelyDetachRef(deletedFiber, nearestMountedAncestor);
        var prevHostParent = hostParent,
          prevHostParentIsContainer = hostParentIsContainer;
        hostParent = deletedFiber.stateNode;
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        deletedFiber = deletedFiber.stateNode;
        for (finishedRoot = deletedFiber.attributes; finishedRoot.length;)
deletedFiber.removeAttributeNode(finishedRoot[0]);
        detachDeletedInstance(deletedFiber);
        hostParent = prevHostParent;
        hostParentIsContainer = prevHostParentIsContainer;
        break;
      case 5:
        offscreenSubtreeWasHidden || safelyDetachRef(deletedFiber, nearestMountedAncestor);
      case 6:
        prevHostParent = hostParent;
        prevHostParentIsContainer = hostParentIsContainer;
        hostParent = null;
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        hostParent = prevHostParent;
```

```
        hostParentIsContainer = prevHostParentIsContainer;
        if (null !== hostParent) if (hostParentIsContainer) try {
          runWithFiberInDEV(deletedFiber, removeChildFromContainer, hostParent,
deletedFiber.stateNode);
        } catch (error) {
          captureCommitPhaseError(deletedFiber, nearestMountedAncestor, error);
        } else try {
          runWithFiberInDEV(deletedFiber, removeChild, hostParent, deletedFiber.stateNode);
        } catch (error) {
          captureCommitPhaseError(deletedFiber, nearestMountedAncestor, error);
        }
        break;
      case 18:
        null !== hostParent && (hostParentIsContainer ? (finishedRoot = hostParent, deletedFiber =
deletedFiber.stateNode, 8 === finishedRoot.nodeType ?
clearSuspenseBoundary(finishedRoot.parentNode, deletedFiber) : 1 === finishedRoot.nodeType &&
clearSuspenseBoundary(finishedRoot, deletedFiber), retryIfBlockedOn(finishedRoot)) :
clearSuspenseBoundary(hostParent, deletedFiber.stateNode));
        break;
      case 4:
        prevHostParent = hostParent;
        prevHostParentIsContainer = hostParentIsContainer;
        hostParent = deletedFiber.stateNode.containerInfo;
        hostParentIsContainer = !0;
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        hostParent = prevHostParent;
        hostParentIsContainer = prevHostParentIsContainer;
        break;
      case 0:
      case 11:
      case 14:
      case 15:
        offscreenSubtreeWasHidden || commitHookEffectListUnmount(Insertion, deletedFiber,
nearestMountedAncestor);
        offscreenSubtreeWasHidden || commitHookLayoutUnmountEffects(deletedFiber,
nearestMountedAncestor, Layout);
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        break;
      case 1:
        offscreenSubtreeWasHidden || (safelyDetachRef(deletedFiber, nearestMountedAncestor),
prevHostParent = deletedFiber.stateNode, "function" === typeof
prevHostParent.componentWillUnmount && safelyCallComponentWillUnmount(deletedFiber,
nearestMountedAncestor, prevHostParent));
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        break;
      case 21:
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        break;
      case 22:
```

```
        offscreenSubtreeWasHidden || safelyDetachRef(deletedFiber, nearestMountedAncestor);
        offscreenSubtreeWasHidden = (prevHostParent = offscreenSubtreeWasHidden) || null !==
deletedFiber.memoizedState;
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
        offscreenSubtreeWasHidden = prevHostParent;
        break;
      default:
        recursivelyTraverseDeletionEffects(finishedRoot, nearestMountedAncestor, deletedFiber);
    }
  }
  function commitSuspenseHydrationCallbacks(finishedRoot, finishedWork) {
    if (null === finishedWork.memoizedState && (finishedRoot = finishedWork.alternate, null !==
finishedRoot && (finishedRoot = finishedRoot.memoizedState, null !== finishedRoot &&
(finishedRoot = finishedRoot.dehydrated, null !== finishedRoot)))) try {
      runWithFiberInDEV(finishedWork, commitHydratedSuspenseInstance, finishedRoot);
    } catch (error) {
      captureCommitPhaseError(finishedWork, finishedWork.return, error);
    }
  }
  function getRetryCache(finishedWork) {
    switch (finishedWork.tag) {
      case 13:
      case 19:
        var retryCache = finishedWork.stateNode;
        null === retryCache && (retryCache = finishedWork.stateNode = new PossiblyWeakSet());
        return retryCache;
      case 22:
        return finishedWork = finishedWork.stateNode, retryCache = finishedWork._retryCache, null ===
retryCache && (retryCache = finishedWork._retryCache = new PossiblyWeakSet()), retryCache;
      default:
        throw Error("Unexpected Suspense handler tag (" + finishedWork.tag + "). This is a bug in
React.");
    }
  }
  function attachSuspenseRetryListeners(finishedWork, wakeables) {
    var retryCache = getRetryCache(finishedWork);
    wakeables.forEach(function (wakeable) {
      var retry = resolveRetryWakeable.bind(null, finishedWork, wakeable);
      if (!retryCache.has(wakeable)) {
        retryCache.add(wakeable);
        if (isDevToolsPresent) if (null !==
 inProgressLanes && null !== inProgressRoot) restorePendingUpdaters(inProgressRoot,
inProgressLanes);else throw Error("Expected finished root and lanes to be set. This is a bug in React.");
        wakeable.then(retry, retry);
      }
    });
  }
  function commitMutationEffects(root, finishedWork, committedLanes) {
    inProgressLanes = committedLanes;
```

```
    inProgressRoot = root;
    commitMutationEffectsOnFiber(finishedWork, root);
    inProgressRoot = inProgressLanes = null;
  }
  function recursivelyTraverseMutationEffects(root$jscomp$0, parentFiber) {
    var deletions = parentFiber.deletions;
    if (null !== deletions) for (var i = 0; i < deletions.length; i++) {
      var root = root$jscomp$0,
        returnFiber = parentFiber,
        deletedFiber = deletions[i],
        parent = returnFiber;
      a: for (; null !== parent;) {
        switch (parent.tag) {
          case 27:
          case 5:
            hostParent = parent.stateNode;
            hostParentIsContainer = !1;
            break a;
          case 3:
            hostParent = parent.stateNode.containerInfo;
            hostParentIsContainer = !0;
            break a;
          case 4:
            hostParent = parent.stateNode.containerInfo;
            hostParentIsContainer = !0;
            break a;
        }
        parent = parent.return;
      }
      if (null === hostParent) throw Error("Expected to find a host parent. This error is likely caused by a bug in React. Please file an issue.");
      commitDeletionEffectsOnFiber(root, returnFiber, deletedFiber);
      hostParent = null;
      hostParentIsContainer = !1;
      root = deletedFiber;
      returnFiber = root.alternate;
      null !== returnFiber && (returnFiber.return = null);
      root.return = null;
    }
    if (parentFiber.subtreeFlags & 13878) for (parentFiber = parentFiber.child; null !== parentFiber;) commitMutationEffectsOnFiber(parentFiber, root$jscomp$0), parentFiber = parentFiber.sibling;
  }
  function commitMutationEffectsOnFiber(finishedWork, root) {
    var current = finishedWork.alternate,
      flags = finishedWork.flags;
    switch (finishedWork.tag) {
      case 0:
      case 11:
      case 14:
```

```
    case 15:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      flags & 4 && (commitHookEffectListUnmount(Insertion | HasEffect, finishedWork,
finishedWork.return), commitHookEffectListMount(Insertion | HasEffect, finishedWork),
commitHookLayoutUnmountEffects(finishedWork, finishedWork.return, Layout | HasEffect));
      break;
    case 1:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      flags & 512 && (offscreenSubtreeWasHidden || null === current || safelyDetachRef(current,
current.return));
      flags & 64 && offscreenSubtreeIsHidden && (finishedWork = finishedWork.updateQueue, null !
== finishedWork && (flags = finishedWork.callbacks, null !== flags && (current =
finishedWork.shared.hiddenCallbacks, finishedWork.shared.hiddenCallbacks = null === current ? flags
: current.concat(flags))));
      break;
    case 26:
      var hoistableRoot = currentHoistableRoot;
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      flags & 512 && (offscreenSubtreeWasHidden || null === current || safelyDetachRef(current,
current.return));
      if (flags & 4) if (root = null !== current ? current.memoizedState : null, flags =
finishedWork.memoizedState, null === current) {
        if (null === flags) {
          if (null === finishedWork.stateNode) {
            a: {
              flags = finishedWork.type;
              current = finishedWork.memoizedProps;
              root = hoistableRoot.ownerDocument || hoistableRoot;
              b: switch (flags) {
                case "title":
                  hoistableRoot = root.getElementsByTagName("title")[0];
                  if (!hoistableRoot || hoistableRoot[internalHoistableMarker] ||
hoistableRoot[internalInstanceKey] || hoistableRoot.namespaceURI === SVG_NAMESPACE ||
hoistableRoot.hasAttribute("itemprop")) hoistableRoot = root.createElement(flags),
root.head.insertBefore(hoistableRoot, root.querySelector("head > title"));
                  setInitialProperties(hoistableRoot, flags, current);
                  hoistableRoot[internalInstanceKey] = finishedWork;
                  markNodeAsHoistable(hoistableRoot);
                  flags = hoistableRoot;
                  break a;
                case "link":
                  var maybeNodes = getHydratableHoistableCache("link", "href", root).get(flags +
(current.href || ""));
                  if (maybeNodes) for (var i = 0; i < maybeNodes.length; i++) if (hoistableRoot =
maybeNodes[i], hoistableRoot.getAttribute("href") === (null == current.href ? null : current.href) &&
hoistableRoot.getAttribute("rel") === (null == current.rel ? null : current.rel) &&
```

```
hoistableRoot.getAttribute("title") === (null == current.title ? null : current.title) &&
hoistableRoot.getAttribute("crossorigin") === (null == current.crossOrigin ? null :
current.crossOrigin)) {
                  maybeNodes.splice(i, 1);
                  break b;
                }
                hoistableRoot = root.createElement(flags);
                setInitialProperties(hoistableRoot, flags, current);
                root.head.appendChild(hoistableRoot);
                break;
              case "meta":
                if (maybeNodes = getHydratableHoistableCache("meta", "content", root).get(flags +
(current.content || ""))) for (i = 0; i < maybeNodes.length; i++) if (hoistableRoot = maybeNodes[i],
checkAttributeStringCoercion(current.content, "content"), hoistableRoot.getAttribute("content") ===
(null == current.content ? null : "" + current.content) && hoistableRoot.getAttribute("name") === (null
== current.name ? null : current.name) && hoistableRoot.getAttribute("property") === (null ==
current.property ? null : current.property) && hoistableRoot.getAttribute("http-equiv") === (null ==
current.httpEquiv ? null : current.httpEquiv) && hoistableRoot.getAttribute("charset") === (null ==
current.charSet ? null : current.charSet)) {
                  maybeNodes.splice(i, 1);
                  break b;
                }
                hoistableRoot = root.createElement(flags);
                setInitialProperties(hoistableRoot, flags, current);
                root.head.appendChild(hoistableRoot);
                break;
              default:
                throw Error('getNodesForType encountered a type it did not expect: "' + flags + '". This is a
bug in React.');
            }
            hoistableRoot[internalInstanceKey] = finishedWork;
            markNodeAsHoistable(hoistableRoot);
            flags = hoistableRoot;
          }
          finishedWork.stateNode = flags;
        } else mountHoistable(hoistableRoot, finishedWork.type, finishedWork.stateNode);
      } else finishedWork.stateNode = acquireResource(hoistableRoot, flags,
finishedWork.memoizedProps);
    } else root !== flags ? (null === root ? null !== current.stateNode && (current =
current.stateNode, current.parentNode.removeChild(current)) : root.count--, null === flags ?
mountHoistable(hoistableRoot, finishedWork.type, finishedWork.stateNode) :
acquireResource(hoistableRoot, flags, finishedWork.memoizedProps)) : null === flags && null !==
finishedWork.stateNode && commitHostUpdate(finishedWork, finishedWork.memoizedProps,
current.memoizedProps);
    break;
  case 27:
    if (flags & 4 && null === finishedWork.alternate) {
      hoistableRoot = finishedWork.stateNode;
      maybeNodes = finishedWork.memoizedProps;
```

```
        try {
          for (i = hoistableRoot.firstChild; i;) {
            var nextNode = i.nextSibling,
              nodeName = i.nodeName;
            i[internalHoistableMarker] || "HEAD" === nodeName || "BODY" === nodeName || "SCRIPT"
=== nodeName || "STYLE" === nodeName || "LINK" === nodeName && "stylesheet" ===
i.rel.toLowerCase() || hoistableRoot.removeChild(i);
            i = nextNode;
          }
          runWithFiberInDEV(finishedWork, acquireSingletonInstance, finishedWork.type, maybeNodes,
hoistableRoot, finishedWork);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      }
    case 5:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      flags & 512 && (offscreenSubtreeWasHidden || null === current || safelyDetachRef(current,
current.return));
      if (finishedWork.flags & 32) {
        root = finishedWork.stateNode;
        try {
          runWithFiberInDEV(finishedWork, resetTextContent, root);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      }
      flags & 4 && null != finishedWork.stateNode && (root = finishedWork.memoizedProps,
commitHostUpdate(finishedWork, root, null !== current ? current.memoizedProps : root));
      flags & 1024 && (needsFormReset = !0, "form" !== finishedWork.type &&
console.error("Unexpected host component type. Expected a form. This is a bug in React."));
      break;
    case 6:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      if (flags & 4) {
        if (null === finishedWork.stateNode) throw Error("This should have a text node initialized. This
error is likely caused by a bug in React. Please file an issue.");
        flags = finishedWork.memoizedProps;
        current = null
 !== current ? current.memoizedProps : flags;
        root = finishedWork.stateNode;
        try {
          runWithFiberInDEV(finishedWork, commitTextUpdate, root, current, flags);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      }
```

```
      break;
    case 3:
      hoistableRoot = pushNestedEffectDurations();
      tagCaches = null;
      maybeNodes = currentHoistableRoot;
      currentHoistableRoot = getHoistableRoot(root.containerInfo);
      recursivelyTraverseMutationEffects(root, finishedWork);
      currentHoistableRoot = maybeNodes;
      commitReconciliationEffects(finishedWork);
      if (flags & 4 && null !== current && current.memoizedState.isDehydrated) try {
        runWithFiberInDEV(finishedWork, commitHydratedContainer, root.containerInfo);
      } catch (error) {
        captureCommitPhaseError(finishedWork, finishedWork.return, error);
      }
      needsFormReset && (needsFormReset = !1, recursivelyResetForms(finishedWork));
      root.effectDuration += popNestedEffectDurations(hoistableRoot);
      break;
    case 4:
      flags = currentHoistableRoot;
      currentHoistableRoot = getHoistableRoot(finishedWork.stateNode.containerInfo);
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      currentHoistableRoot = flags;
      break;
    case 12:
      flags = pushNestedEffectDurations();
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      finishedWork.stateNode.effectDuration += bubbleNestedEffectDurations(flags);
      break;
    case 13:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      finishedWork.child.flags & 8192 && null !== finishedWork.memoizedState !== (null !== current
&& null !== current.memoizedState) && (globalMostRecentFallbackTime = now$1());
      flags & 4 && (flags = finishedWork.updateQueue, null !== flags && (finishedWork.updateQueue
= null, attachSuspenseRetryListeners(finishedWork, flags)));
      break;
    case 22:
      flags & 512 && (offscreenSubtreeWasHidden || null === current || safelyDetachRef(current,
current.return));
      i = null !== finishedWork.memoizedState;
      nextNode = null !== current && null !== current.memoizedState;
      nodeName = offscreenSubtreeIsHidden;
      var prevOffscreenSubtreeWasHidden = offscreenSubtreeWasHidden;
      offscreenSubtreeIsHidden = nodeName || i;
      offscreenSubtreeWasHidden = prevOffscreenSubtreeWasHidden || nextNode;
      recursivelyTraverseMutationEffects(root, finishedWork);
      offscreenSubtreeWasHidden = prevOffscreenSubtreeWasHidden;
```

```
      offscreenSubtreeIsHidden = nodeName;
      commitReconciliationEffects(finishedWork);
      root = finishedWork.stateNode;
      root._current = finishedWork;
      root._visibility &= ~OffscreenDetached;
      root._visibility |= root._pendingVisibility & OffscreenDetached;
      if (flags & 8192 && (root._visibility = i ? root._visibility & ~OffscreenVisible : root._visibility |
OffscreenVisible, i && (root = offscreenSubtreeIsHidden || offscreenSubtreeWasHidden, null ===
current || nextNode || root || recursivelyTraverseDisappearLayoutEffects(finishedWork)), null ===
finishedWork.memoizedProps || "manual" !== finishedWork.memoizedProps.mode)) a: for (current =
null, root = finishedWork;;) {
        if (5 === root.tag || 26 === root.tag || 27 === root.tag) {
          if (null === current) {
            nextNode = current = root;
            try {
              hoistableRoot = nextNode.stateNode, i ? runWithFiberInDEV(nextNode, hideInstance,
hoistableRoot) : runWithFiberInDEV(nextNode, unhideInstance, nextNode.stateNode,
nextNode.memoizedProps);
            } catch (error) {
              captureCommitPhaseError(nextNode, nextNode.return, error);
            }
          }
        } else if (6 === root.tag) {
          if (null === current) {
            nextNode = root;
            try {
              maybeNodes = nextNode.stateNode, i ? runWithFiberInDEV(nextNode, hideTextInstance,
maybeNodes) : runWithFiberInDEV(nextNode, unhideTextInstance, maybeNodes,
nextNode.memoizedProps);
            } catch (error) {
              captureCommitPhaseError(nextNode, nextNode.return, error);
            }
          }
        } else if ((22 !== root.tag && 23 !== root.tag || null === root.memoizedState || root ===
finishedWork) && null !== root.child) {
          root.child.return = root;
          root = root.child;
          continue;
        }
        if (root === finishedWork) break a;
        for (; null === root.sibling;) {
          if (null === root.return || root.return === finishedWork) break a;
          current === root && (current = null);
          root = root.return;
        }
        current === root && (current = null);
        root.sibling.return = root.return;
        root = root.sibling;
      }
```

```
      flags & 4 && (flags = finishedWork.updateQueue, null !== flags && (current = flags.retryQueue,
null !== current && (flags.retryQueue = null, attachSuspenseRetryListeners(finishedWork, current))));
      break;
    case 19:
      recursivelyTraverseMutationEffects(root, finishedWork);
      commitReconciliationEffects(finishedWork);
      flags & 4 && (flags = finishedWork.updateQueue, null !== flags && (finishedWork.updateQueue
= null, attachSuspenseRetryListeners(finishedWork, flags)));
      break;
    case 21:
      break;
    default:
      recursivelyTraverseMutationEffects(root, finishedWork),
commitReconciliationEffects(finishedWork);
  }
 }
 function commitReconciliationEffects(finishedWork) {
  var flags = finishedWork.flags;
  if (flags & 2) {
   try {
    runWithFiberInDEV(finishedWork, commitPlacement, finishedWork);
   } catch (error) {
    captureCommitPhaseError(finishedWork, finishedWork.return, error);
   }
   finishedWork.flags &= -3;
  }
  flags & 4096 && (finishedWork.flags &= -4097);
 }
 function recursivelyResetForms(parentFiber) {
  if (parentFiber.subtreeFlags & 1024) for (parentFiber = parentFiber.child; null !== parentFiber;) {
   var fiber = parentFiber;
   recursivelyResetForms(fiber);
   5 === fiber.tag && fiber.flags & 1024 && fiber.stateNode.reset();
   parentFiber = parentFiber.sibling;
  }
 }
 function commitLayoutEffects(finishedWork, root, committedLanes) {
  inProgressLanes = committedLanes;
  inProgressRoot = root;
  commitLayoutEffectOnFiber(root, finishedWork.alternate, finishedWork);
  inProgressRoot = inProgressLanes = null;
 }
 function recursivelyTraverseLayoutEffects(root, parentFiber) {
  if (parentFiber.subtreeFlags & 8772) for (parentFiber = parentFiber.child; null !== parentFiber;)
commitLayoutEffectOnFiber(root, parentFiber.alternate, parentFiber), parentFiber =
parentFiber.sibling;
 }
 function disappearLayoutEffects(finishedWork) {
  switch (finishedWork.tag) {
```

```
      case 0:
      case 11:
      case 14:
      case 15:
        commitHookLayoutUnmountEffects(finishedWork, finishedWork.return, Layout);
        recursivelyTraverseDisappearLayoutEffects(finishedWork);
        break;
      case 1:
        safelyDetachRef(finishedWork, finishedWork.return);
        var instance = finishedWork.stateNode;
        "function" === typeof instance.componentWillUnmount &&
safelyCallComponentWillUnmount(finishedWork, finishedWork.return, instance);
        recursivelyTraverseDisappearLayoutEffects(finishedWork);
        break;
      case 26:
      case 27:
      case 5:
        safelyDetachRef(finishedWork, finishedWork.return);
        recursivelyTraverseDisappearLayoutEffects(finishedWork);
        break;
      case 22:
        safelyDetachRef(finishedWork, finishedWork.return);
        null === finishedWork.memoizedState &&
recursivelyTraverseDisappearLayoutEffects(finishedWork);
        break;
      default:
        recursivelyTraverseDisappearLayoutEffects(finishedWork);
    }
  }
  function recursivelyTraverseDisappearLayoutEffects(parentFiber) {
    for (parentFiber = parentFiber.child; null !== parentFiber;) disappearLayoutEffects(parentFiber),
parentFiber = parentFiber.sibling;
  }
  function reappearLayoutEffects(finishedRoot, current, finishedWork, includeWorkInProgressEffects)
{
    var flags = finishedWork.flags;
    switch (finishedWork.tag) {
      case 0:
      case 11:
      case 15:
        recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        commitHookLayoutEffects(finishedWork, Layout);
        break;
      case 1:
        recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        current = finishedWork.stateNode;
        "function" === typeof current.componentDidMount && runWithFiberInDEV(finishedWork,
```

```
callComponentDidMountInDEV, finishedWork, current);
        current = finishedWork.updateQueue;
        if (null !== current) {
          finishedRoot = finishedWork.stateNode;
          try {
            runWithFiberInDEV(finishedWork, commitHiddenCallbacks, current, finishedRoot);
          } catch (error) {
            captureCommitPhaseError(finishedWork, finishedWork.return, error);
          }
        }
        includeWorkInProgressEffects && flags & 64 && commitClassCallbacks(finishedWork);
        safelyAttachRef(finishedWork, finishedWork.return);
        break;
      case 26:
      case 27:
      case 5:
        recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        includeWorkInProgressEffects && null === current &&
 flags & 4 && commitHostMount(finishedWork);
        safelyAttachRef(finishedWork, finishedWork.return);
        break;
      case 12:
        if (includeWorkInProgressEffects && flags & 4) {
          flags = pushNestedEffectDurations();
          recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
          includeWorkInProgressEffects = finishedWork.stateNode;
          includeWorkInProgressEffects.effectDuration += bubbleNestedEffectDurations(flags);
          try {
            runWithFiberInDEV(finishedWork, commitProfiler, finishedWork, current, commitStartTime,
includeWorkInProgressEffects.effectDuration);
          } catch (error) {
            captureCommitPhaseError(finishedWork, finishedWork.return, error);
          }
        } else recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        break;
      case 13:
        recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        includeWorkInProgressEffects && flags & 4 &&
commitSuspenseHydrationCallbacks(finishedRoot, finishedWork);
        break;
      case 22:
        null === finishedWork.memoizedState &&
recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
        safelyAttachRef(finishedWork, finishedWork.return);
```

```
      break;
    default:
      recursivelyTraverseReappearLayoutEffects(finishedRoot, finishedWork,
includeWorkInProgressEffects);
  }
}
function recursivelyTraverseReappearLayoutEffects(finishedRoot, parentFiber,
includeWorkInProgressEffects) {
  includeWorkInProgressEffects = includeWorkInProgressEffects && 0 !== (parentFiber.subtreeFlags
& 8772);
  for (parentFiber = parentFiber.child; null !== parentFiber;) reappearLayoutEffects(finishedRoot,
parentFiber.alternate, parentFiber, includeWorkInProgressEffects), parentFiber = parentFiber.sibling;
}
function commitOffscreenPassiveMountEffects(current, finishedWork) {
  var previousCache = null;
  null !== current && null !== current.memoizedState && null !== current.memoizedState.cachePool
&& (previousCache = current.memoizedState.cachePool.pool);
  current = null;
  null !== finishedWork.memoizedState && null !== finishedWork.memoizedState.cachePool &&
(current = finishedWork.memoizedState.cachePool.pool);
  current !== previousCache && (null != current && retainCache(current), null != previousCache &&
releaseCache(previousCache));
}
function commitCachePassiveMountEffect(current, finishedWork) {
  current = null;
  null !== finishedWork.alternate && (current = finishedWork.alternate.memoizedState.cache);
  finishedWork = finishedWork.memoizedState.cache;
  finishedWork !== current && (retainCache(finishedWork), null != current &&
releaseCache(current));
}
function recursivelyTraversePassiveMountEffects(root, parentFiber, committedLanes,
committedTransitions) {
  if (parentFiber.subtreeFlags & 10256) for (parentFiber = parentFiber.child; null !== parentFiber;)
commitPassiveMountOnFiber(root, parentFiber, committedLanes, committedTransitions), parentFiber
= parentFiber.sibling;
}
function commitPassiveMountOnFiber(finishedRoot, finishedWork, committedLanes,
committedTransitions) {
  var flags = finishedWork.flags;
  switch (finishedWork.tag) {
    case 0:
    case 11:
    case 15:
      recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
      flags & 2048 && commitHookPassiveMountEffects(finishedWork, Passive | HasEffect);
      break;
    case 3:
      var prevEffectDuration = pushNestedEffectDurations();
```

```
      recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
      flags & 2048 && (committedLanes = null, null !== finishedWork.alternate && (committedLanes
= finishedWork.alternate.memoizedState.cache), finishedWork = finishedWork.memoizedState.cache,
finishedWork !== committedLanes && (retainCache(finishedWork), null != committedLanes &&
releaseCache(committedLanes)));
      finishedRoot.passiveEffectDuration += popNestedEffectDurations(prevEffectDuration);
      break;
    case 12:
      if (flags & 2048) {
        prevEffectDuration = pushNestedEffectDurations();
        recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
        finishedRoot = finishedWork.stateNode;
        finishedRoot.passiveEffectDuration += bubbleNestedEffectDurations(prevEffectDuration);
        try {
          runWithFiberInDEV(finishedWork, commitProfilerPostCommitImpl, finishedWork,
finishedWork.alternate, commitStartTime, finishedRoot.passiveEffectDuration);
        } catch (error) {
          captureCommitPhaseError(finishedWork, finishedWork.return, error);
        }
      } else recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
      break;
    case 23:
      break;
    case 22:
      prevEffectDuration = finishedWork.stateNode;
      null !== finishedWork.memoizedState ? prevEffectDuration._visibility &
OffscreenPassiveEffectsConnected ? recursivelyTraversePassiveMountEffects(finishedRoot,
finishedWork, committedLanes, committedTransitions) :
recursivelyTraverseAtomicPassiveEffects(finishedRoot, finishedWork) : prevEffectDuration._visibility
& OffscreenPassiveEffectsConnected ? recursivelyTraversePassiveMountEffects(finishedRoot,
finishedWork, committedLanes, committedTransitions) : (prevEffectDuration._visibility |=
OffscreenPassiveEffectsConnected, recursivelyTraverseReconnectPassiveEffects(finishedRoot,
finishedWork, committedLanes, committedTransitions, 0 !== (finishedWork.subtreeFlags & 10256)));
      flags & 2048 && commitOffscreenPassiveMountEffects(finishedWork.alternate, finishedWork);
      break;
    case 24:
      recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
      flags & 2048 && commitCachePassiveMountEffect(finishedWork.alternate, finishedWork);
      break;
    default:
      recursivelyTraversePassiveMountEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions);
  }
 }
 function recursivelyTraverseReconnectPassiveEffects(finishedRoot, parentFiber, committedLanes,
```

```
committedTransitions, includeWorkInProgressEffects) {
    includeWorkInProgressEffects = includeWorkInProgressEffects && 0 !== (parentFiber.subtreeFlags
& 10256);
    for (parentFiber = parentFiber.child; null !== parentFiber;) reconnectPassiveEffects(finishedRoot,
parentFiber, committedLanes, committedTransitions, includeWorkInProgressEffects), parentFiber =
parentFiber.sibling;
  }
  function reconnectPassiveEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions, includeWorkInProgressEffects) {
    var flags = finishedWork.flags;
    switch (finishedWork.tag) {
      case 0:
      case 11:
      case 15:
        recursivelyTraverseReconnectPassiveEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions, includeWorkInProgressEffects);
        commitHookPassiveMountEffects(finishedWork, Passive);
        break;
      case 23:
        break;
      case 22:
        var _instance2 = finishedWork.stateNode;
        null !== finishedWork.memoizedState ? _instance2._visibility &
OffscreenPassiveEffectsConnected ? recursivelyTraverseReconnectPassiveEffects(finishedRoot,
finishedWork, committedLanes, committedTransitions, includeWorkInProgressEffects) :
recursivelyTraverseAtomicPassiveEffects(finishedRoot, finishedWork) : (_instance2._visibility |=
OffscreenPassiveEffectsConnected, recursivelyTraverseReconnectPassiveEffects(finishedRoot,
finishedWork, committedLanes, committedTransitions, includeWorkInProgressEffects));
        includeWorkInProgressEffects && flags & 2048 &&
commitOffscreenPassiveMountEffects(finishedWork.alternate, finishedWork);
        break;
      case 24:
        recursivelyTraverseReconnectPassiveEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions, includeWorkInProgressEffects);
        includeWorkInProgressEffects && flags & 2048 &&
commitCachePassiveMountEffect(finishedWork.alternate, finishedWork);
        break;
      default:
        recursivelyTraverseReconnectPassiveEffects(finishedRoot, finishedWork, committedLanes,
committedTransitions, includeWorkInProgressEffects);
    }
  }
  function recursivelyTraverseAtomicPassiveEffects(finishedRoot$jscomp$0, parentFiber) {
    if (parentFiber.subtreeFlags & 10256) for (parentFiber = parentFiber.child; null !== parentFiber;) {
      var finishedRoot = finishedRoot$jscomp$0,
        finishedWork = parentFiber,
        flags = finishedWork.flags;
      switch (finishedWork.tag) {
        case 22:
```

```
        recursivelyTraverseAtomicPassiveEffects(finishedRoot, finishedWork);
        flags & 2048 && commitOffscreenPassiveMountEffects(finishedWork.alternate, finishedWork);
        break;
      case 24:
        recursivelyTraverseAtomicPassiveEffects(finishedRoot, finishedWork);
        flags & 2048 && commitCachePassiveMountEffect(finishedWork.alternate, finishedWork);
        break;
      default:
        recursivelyTraverseAtomicPassiveEffects(finishedRoot, finishedWork);
    }
    parentFiber = parentFiber.sibling;
  }
 }
 function recursivelyAccumulateSuspenseyCommit(parentFiber) {
  if (parentFiber.subtreeFlags & suspenseyCommitFlag) for (parentFiber = parentFiber.child; null !==
parentFiber;) accumulateSuspenseyCommitOnFiber(parentFiber), parentFiber = parentFiber.sibling;
 }
 function accumulateSuspenseyCommitOnFiber(fiber) {
  switch (fiber.tag) {
    case 26:
      recursivelyAccumulateSuspenseyCommit(fiber);
      fiber.flags & suspenseyCommitFlag && null
 !== fiber.memoizedState && suspendResource(currentHoistableRoot, fiber.memoizedState,
fiber.memoizedProps);
      break;
    case 5:
      recursivelyAccumulateSuspenseyCommit(fiber);
      break;
    case 3:
    case 4:
      var previousHoistableRoot = currentHoistableRoot;
      currentHoistableRoot = getHoistableRoot(fiber.stateNode.containerInfo);
      recursivelyAccumulateSuspenseyCommit(fiber);
      currentHoistableRoot = previousHoistableRoot;
      break;
    case 22:
      null === fiber.memoizedState && (previousHoistableRoot = fiber.alternate, null !==
previousHoistableRoot && null !== previousHoistableRoot.memoizedState ? (previousHoistableRoot
= suspenseyCommitFlag, suspenseyCommitFlag = 16777216,
recursivelyAccumulateSuspenseyCommit(fiber), suspenseyCommitFlag = previousHoistableRoot) :
recursivelyAccumulateSuspenseyCommit(fiber));
      break;
    default:
      recursivelyAccumulateSuspenseyCommit(fiber);
  }
 }
 function detachAlternateSiblings(parentFiber) {
  var previousFiber = parentFiber.alternate;
  if (null !== previousFiber && (parentFiber = previousFiber.child, null !== parentFiber)) {
```

```
      previousFiber.child = null;
      do previousFiber = parentFiber.sibling, parentFiber.sibling = null, parentFiber = previousFiber;
while (null !== parentFiber);
    }
  }
  function recursivelyTraversePassiveUnmountEffects(parentFiber) {
    var deletions = parentFiber.deletions;
    if (0 !== (parentFiber.flags & 16)) {
      if (null !== deletions) for (var i = 0; i < deletions.length; i++) {
        var childToDelete = deletions[i];
        nextEffect = childToDelete;
        commitPassiveUnmountEffectsInsideOfDeletedTree_begin(childToDelete, parentFiber);
      }
      detachAlternateSiblings(parentFiber);
    }
    if (parentFiber.subtreeFlags & 10256) for (parentFiber = parentFiber.child; null !== parentFiber;)
commitPassiveUnmountOnFiber(parentFiber), parentFiber = parentFiber.sibling;
  }
  function commitPassiveUnmountOnFiber(finishedWork) {
    switch (finishedWork.tag) {
      case 0:
      case 11:
      case 15:
        recursivelyTraversePassiveUnmountEffects(finishedWork);
        finishedWork.flags & 2048 && commitHookPassiveUnmountEffects(finishedWork,
finishedWork.return, Passive | HasEffect);
        break;
      case 3:
        var prevEffectDuration = pushNestedEffectDurations();
        recursivelyTraversePassiveUnmountEffects(finishedWork);
        finishedWork.stateNode.passiveEffectDuration +=
popNestedEffectDurations(prevEffectDuration);
        break;
      case 12:
        prevEffectDuration = pushNestedEffectDurations();
        recursivelyTraversePassiveUnmountEffects(finishedWork);
        finishedWork.stateNode.passiveEffectDuration +=
bubbleNestedEffectDurations(prevEffectDuration);
        break;
      case 22:
        prevEffectDuration = finishedWork.stateNode;
        null !== finishedWork.memoizedState && prevEffectDuration._visibility &
OffscreenPassiveEffectsConnected && (null === finishedWork.return || 13 !==
finishedWork.return.tag) ? (prevEffectDuration._visibility &= ~OffscreenPassiveEffectsConnected,
recursivelyTraverseDisconnectPassiveEffects(finishedWork)) :
recursivelyTraversePassiveUnmountEffects(finishedWork);
        break;
      default:
        recursivelyTraversePassiveUnmountEffects(finishedWork);
```

```
    }
  }
  function recursivelyTraverseDisconnectPassiveEffects(parentFiber) {
    var deletions = parentFiber.deletions;
    if (0 !== (parentFiber.flags & 16)) {
      if (null !== deletions) for (var i = 0; i < deletions.length; i++) {
        var childToDelete = deletions[i];
        nextEffect = childToDelete;
        commitPassiveUnmountEffectsInsideOfDeletedTree_begin(childToDelete, parentFiber);
      }
      detachAlternateSiblings(parentFiber);
    }
    for (parentFiber = parentFiber.child; null !== parentFiber;) disconnectPassiveEffect(parentFiber),
parentFiber = parentFiber.sibling;
  }
  function disconnectPassiveEffect(finishedWork) {
    switch (finishedWork.tag) {
      case 0:
      case 11:
      case 15:
        commitHookPassiveUnmountEffects(finishedWork, finishedWork.return, Passive);
        recursivelyTraverseDisconnectPassiveEffects(finishedWork);
        break;
      case 22:
        var instance = finishedWork.stateNode;
        instance._visibility & OffscreenPassiveEffectsConnected && (instance._visibility &=
~OffscreenPassiveEffectsConnected, recursivelyTraverseDisconnectPassiveEffects(finishedWork));
        break;
      default:
        recursivelyTraverseDisconnectPassiveEffects(finishedWork);
    }
  }
  function commitPassiveUnmountEffectsInsideOfDeletedTree_begin(deletedSubtreeRoot,
nearestMountedAncestor) {
    for (; null !== nextEffect;) {
      var fiber = nextEffect,
        current = fiber;
      switch (current.tag) {
        case 0:
        case 11:
        case 15:
          commitHookPassiveUnmountEffects(current, nearestMountedAncestor, Passive);
          break;
        case 23:
        case 22:
          null !== current.memoizedState && null !== current.memoizedState.cachePool && (current =
current.memoizedState.cachePool.pool, null != current && retainCache(current));
          break;
        case 24:
```

```
releaseCache(current.memoizedState.cache);
}
current = fiber.child;
if (null !== current) current.return = fiber, nextEffect = current;else a: for (fiber =
deletedSubtreeRoot; null !== nextEffect;) {
current = nextEffect;
var sibling = current.sibling,
returnFiber = current.return;
detachFiberAfterEffects(current);
if (current === fiber) {
nextEffect = null;
break a;
}
if (null !== sibling) {
sibling.return = returnFiber;
nextEffect = sibling;
break a;
}
nextEffect = returnFiber;
}
}
}
function FiberNode(tag, pendingProps, key, mode) {
this.tag = tag;
this.key = key;
this.sibling = this.child = this.return = this.stateNode = this.type = this.elementType = null;
this.index = 0;
this.refCleanup = this.ref = null;
this.pendingProps = pendingProps;
this.dependencies = this.memoizedState = this.updateQueue = this.memoizedProps = null;
this.mode = mode;
this.subtreeFlags = this.flags = 0;
this.deletions = null;
this.childLanes = this.lanes = 0;
this.alternate = null;
this.actualDuration = -0;
this.actualStartTime = -1.1;
this.treeBaseDuration = this.selfBaseDuration = -0;
this._debugOwner = this._debugInfo = null;
this._debugNeedsRemount = !1;
this._debugHookTypes = null;
hasBadMapPolyfill || "function" !== typeof Object.preventExtensions ||
Object.preventExtensions(this);
}
function shouldConstruct(Component) {
Component = Component.prototype;
return !(!Component || !Component.isReactComponent);
}
function createWorkInProgress(current, pendingProps) {
```

```
    var workInProgress = current.alternate;
    null === workInProgress ? (workInProgress = createFiber(current.tag, pendingProps, current.key,
current.mode), workInProgress.elementType = current.elementType, workInProgress.type =
current.type, workInProgress.stateNode = current.stateNode, workInProgress._debugOwner =
current._debugOwner, workInProgress._debugHookTypes = current._debugHookTypes,
workInProgress.alternate = current, current.alternate = workInProgress) :
(workInProgress.pendingProps = pendingProps, workInProgress.type = current.type,
workInProgress.flags = 0, workInProgress.subtreeFlags = 0, workInProgress.deletions = null,
workInProgress.actualDuration = -0, workInProgress.actualStartTime = -1.1);
    workInProgress.flags = current.flags & 31457280;
    workInProgress.childLanes = current.childLanes;
    workInProgress.lanes = current.lanes;
    workInProgress.child = current.child;
    workInProgress.memoizedProps = current.memoizedProps;
    workInProgress.memoizedState = current.memoizedState;
    workInProgress.updateQueue = current.updateQueue;
    pendingProps = current.dependencies;
    workInProgress.dependencies = null === pendingProps ? null : {
      lanes: pendingProps.lanes,
      firstContext: pendingProps.firstContext,
      _debugThenableState: pendingProps._debugThenableState
    };
    workInProgress.sibling = current.sibling;
    workInProgress.index = current.index;
    workInProgress.ref = current.ref;
    workInProgress.refCleanup = current.refCleanup;
    workInProgress.selfBaseDuration = current.selfBaseDuration;
    workInProgress.treeBaseDuration = current.treeBaseDuration;
    workInProgress._debugInfo = current._debugInfo;
    workInProgress._debugNeedsRemount = current._debugNeedsRemount;
    switch (workInProgress.tag) {
      case 0:
      case 15:
        workInProgress.type = resolveFunctionForHotReloading(current.type);
        break;
      case 1:
        workInProgress.type = resolveFunctionForHotReloading(current.type);
        break;
      case 11:
        workInProgress.type = resolveForwardRefForHotReloading(current.type);
    }
    return workInProgress;
  }
  function resetWorkInProgress(workInProgress, renderLanes) {
    workInProgress.flags &= 31457282;
    var current = workInProgress.alternate;
    null === current ? (workInProgress.childLanes = 0, workInProgress.lanes = renderLanes,
workInProgress.child = null, workInProgress.subtreeFlags = 0, workInProgress.memoizedProps = null,
workInProgress.memoizedState = null, workInProgress.updateQueue = null,
```

```
workInProgress.dependencies = null, workInProgress.stateNode = null,
workInProgress.selfBaseDuration = 0, workInProgress.treeBaseDuration = 0) :
(workInProgress.childLanes = current.childLanes, workInProgress.lanes = current.lanes,
workInProgress.child = current.child, workInProgress.subtreeFlags = 0, workInProgress.deletions =
null, workInProgress.memoizedProps
 = current.memoizedProps, workInProgress.memoizedState = current.memoizedState,
workInProgress.updateQueue = current.updateQueue, workInProgress.type = current.type, renderLanes
= current.dependencies, workInProgress.dependencies = null === renderLanes ? null : {
      lanes: renderLanes.lanes,
      firstContext: renderLanes.firstContext,
      _debugThenableState: renderLanes._debugThenableState
    }, workInProgress.selfBaseDuration = current.selfBaseDuration, workInProgress.treeBaseDuration =
current.treeBaseDuration);
    return workInProgress;
  }
  function createFiberFromTypeAndProps(type, key, pendingProps, owner, mode, lanes) {
    var fiberTag = 0,
      resolvedType = type;
    if ("function" === typeof type) shouldConstruct(type) && (fiberTag = 1), resolvedType =
resolveFunctionForHotReloading(resolvedType);else if ("string" === typeof type) fiberTag =
getHostContext(), fiberTag = isHostHoistableType(type, pendingProps, fiberTag) ? 26 : "html" ===
type || "head" === type || "body" === type ? 27 : 5;else a: switch (type) {
      case REACT_FRAGMENT_TYPE:
        return createFiberFromFragment(pendingProps.children, mode, lanes, key);
      case REACT_STRICT_MODE_TYPE:
        fiberTag = 8;
        mode |= StrictLegacyMode;
        mode |= StrictEffectsMode;
        break;
      case REACT_PROFILER_TYPE:
        return type = pendingProps, owner = mode, "string" !== typeof type.id && console.error('Profiler
must specify an "id" of type `string` as a prop. Received the type `%s` instead.', typeof type.id), key =
createFiber(12, type, key, owner | ProfileMode), key.elementType = REACT_PROFILER_TYPE,
key.lanes = lanes, key.stateNode = {
          effectDuration: 0,
          passiveEffectDuration: 0
        }, key;
      case REACT_SUSPENSE_TYPE:
        return key = createFiber(13, pendingProps, key, mode), key.elementType =
REACT_SUSPENSE_TYPE, key.lanes = lanes, key;
      case REACT_SUSPENSE_LIST_TYPE:
        return key = createFiber(19, pendingProps, key, mode), key.elementType =
REACT_SUSPENSE_LIST_TYPE, key.lanes = lanes, key;
      case REACT_OFFSCREEN_TYPE:
        return createFiberFromOffscreen(pendingProps, mode, lanes, key);
      default:
        if ("object" === typeof type && null !== type) switch (type.$$typeof) {
          case REACT_PROVIDER_TYPE:
          case REACT_CONTEXT_TYPE:
```

```
          fiberTag = 10;
          break a;
        case REACT_CONSUMER_TYPE:
          fiberTag = 9;
          break a;
        case REACT_FORWARD_REF_TYPE:
          fiberTag = 11;
          resolvedType = resolveForwardRefForHotReloading(resolvedType);
          break a;
        case REACT_MEMO_TYPE:
          fiberTag = 14;
          break a;
        case REACT_LAZY_TYPE:
          fiberTag = 16;
          resolvedType = null;
          break a;
      }
      resolvedType = "";
      if (void 0 === type || "object" === typeof type && null !== type && 0 ===
Object.keys(type).length) resolvedType += " You likely forgot to export your component from the file
it's defined in, or you might have mixed up default and named imports.";
      null === type ? pendingProps = "null" : isArrayImpl(type) ? pendingProps = "array" : void 0 !==
type && type.$$typeof === REACT_ELEMENT_TYPE ? (pendingProps = "<" +
(getComponentNameFromType(type.type) || "Unknown") + " />", resolvedType = " Did you
accidentally export a JSX literal instead of a component?") : pendingProps = typeof type;
      (fiberTag = owner ? getComponentNameFromOwner(owner) : null) && (resolvedType +=
"\n\nCheck the render method of `" + fiberTag + "`.");
      fiberTag = 29;
      pendingProps = Error("Element type is invalid: expected a string (for built-in components) or a
class/function (for composite components) but got: " + (pendingProps + "." + resolvedType));
      resolvedType = null;
    }
    key = createFiber(fiberTag, pendingProps, key, mode);
    key.elementType = type;
    key.type = resolvedType;
    key.lanes = lanes;
    key._debugOwner = owner;
    return key;
  }
  function createFiberFromElement(element, mode, lanes) {
    mode = createFiberFromTypeAndProps(element.type, element.key, element.props, element._owner,
mode, lanes);
    mode._debugOwner = element._owner;
    return mode;
  }
  function createFiberFromFragment(elements, mode, lanes, key) {
    elements = createFiber(7, elements, key, mode);
    elements.lanes = lanes;
    return elements;
```

```
  }
  function createFiberFromOffscreen(pendingProps, mode, lanes, key) {
    pendingProps = createFiber(22, pendingProps, key, mode);
    pendingProps.elementType = REACT_OFFSCREEN_TYPE;
    pendingProps.lanes = lanes;
    var primaryChildInstance = {
      _visibility: OffscreenVisible,
      _pendingVisibility: OffscreenVisible,
      _pendingMarkers: null,
      _retryCache: null,
      _transitions: null,
      _current: null,
      detach: function () {
        var instance = primaryChildInstance,
          fiber = instance._current;
        if (null === fiber) throw Error("Calling Offscreen.detach before instance handle has been set.");
        if (0 === (instance._pendingVisibility & OffscreenDetached)) {
          var root = enqueueConcurrentRenderForLane(fiber, 2);
          null !== root && (instance._pendingVisibility |= OffscreenDetached,
scheduleUpdateOnFiber(root, fiber, 2));
        }
      },
      attach: function () {
        var instance = primaryChildInstance,
          fiber = instance._current;
        if (null === fiber) throw Error("Calling Offscreen.detach before instance handle has been set.");
        if (0 !== (instance._pendingVisibility & OffscreenDetached)) {
          var root = enqueueConcurrentRenderForLane(fiber, 2);
          null !== root && (instance._pendingVisibility &= ~OffscreenDetached,
scheduleUpdateOnFiber(root, fiber, 2));
        }
      }
    };
    pendingProps.stateNode = primaryChildInstance;
    return pendingProps;
  }
  function createFiberFromText(content, mode, lanes) {
    content = createFiber(6, content, null, mode);
    content.lanes = lanes;
    return content;
  }
  function createFiberFromPortal(portal, mode, lanes) {
    mode = createFiber(4, null !== portal.children ? portal.children : [], portal.key, mode);
    mode.lanes = lanes;
    mode.stateNode = {
      containerInfo: portal.containerInfo,
      pendingChildren: null,
      implementation: portal.implementation
    };
```

```
    return mode;
  }
  function markUpdate(workInProgress) {
    workInProgress.flags |= 4;
  }
  function preloadResourceAndSuspendIfNeeded(workInProgress, resource) {
    if ("stylesheet" !== resource.type || (resource.state.loading & Inserted) !== NotLoaded)
workInProgress.flags &= -16777217;else if (workInProgress.flags |= 16777216, !
preloadResource(resource)) {
      resource = suspenseHandlerStackCursor.current;
      if (null !== resource && ((workInProgressRootRenderLanes & 4194176) ===
workInProgressRootRenderLanes ? null !== shellBoundary : (workInProgressRootRenderLanes &
62914560) !== workInProgressRootRenderLanes && 0 === (workInProgressRootRenderLanes &
536870912) || resource !== shellBoundary)) throw suspendedThenable =
noopSuspenseyCommitThenable, SuspenseyCommitException;
      workInProgress.flags |= 8192;
    }
  }
  function scheduleRetryEffect(workInProgress, retryQueue) {
    null !== retryQueue && (workInProgress.flags |= 4);
    workInProgress.flags & 16384 && (retryQueue = 22 !== workInProgress.tag ?
claimNextRetryLane() : 536870912, workInProgress.lanes |= retryQueue,
workInProgressSuspendedRetryLanes |= retryQueue);
  }
  function cutOffTailIfNeeded(renderState, hasRenderedATailFallback) {
    if (!isHydrating) switch (renderState.tailMode) {
      case "hidden":
        hasRenderedATailFallback = renderState.tail;
        for (var lastTailNode = null; null !== hasRenderedATailFallback;) null !==
hasRenderedATailFallback.alternate && (lastTailNode = hasRenderedATailFallback),
hasRenderedATailFallback = hasRenderedATailFallback.sibling;
        null === lastTailNode ? renderState.tail = null : lastTailNode.sibling = null;
        break;
      case "collapsed":
        lastTailNode = renderState.tail;
        for (var _lastTailNode = null; null !== lastTailNode;) null !== lastTailNode.alternate &&
(_lastTailNode = lastTailNode), lastTailNode = lastTailNode.sibling;
        null === _lastTailNode ? hasRenderedATailFallback || null === renderState.tail ? renderState.tail
= null : renderState.tail.sibling = null : _lastTailNode.sibling = null;
    }
  }
  function bubbleProperties(completedWork) {
    var didBailout = null !== completedWork.alternate && completedWork.alternate.child ===
completedWork.child,
      newChildLanes = 0,
      subtreeFlags = 0;
    if (didBailout) {
      if ((completedWork.mode & ProfileMode) !== NoMode) {
        for (var _treeBaseDuration = completedWork.selfBaseDuration, _child2 = completedWork.child;
```

```
null !== _child2;) newChildLanes |= _child2.lanes | _child2.childLanes, subtreeFlags |=
_child2.subtreeFlags & 31457280, subtreeFlags |= _child2.flags & 31457280, _treeBaseDuration +=
_child2.treeBaseDuration, _child2 = _child2.sibling;
        completedWork.treeBaseDuration = _treeBaseDuration;
      } else for (_treeBaseDuration = completedWork.child; null !== _treeBaseDuration;)
newChildLanes |= _treeBaseDuration.lanes | _treeBaseDuration.childLanes, subtreeFlags |=
_treeBaseDuration.subtreeFlags & 31457280, subtreeFlags |= _treeBaseDuration.flags & 31457280,
_treeBaseDuration.return = completedWork, _treeBaseDuration = _treeBaseDuration.sibling;
    } else if ((completedWork.mode & ProfileMode) !== NoMode) {
      _treeBaseDuration = completedWork.actualDuration;
      _child2 = completedWork.selfBaseDuration;
      for (var child = completedWork.child; null !== child;) newChildLanes |= child.lanes |
child.childLanes, subtreeFlags |= child.subtreeFlags,
 subtreeFlags |= child.flags, _treeBaseDuration += child.actualDuration, _child2 +=
child.treeBaseDuration, child = child.sibling;
      completedWork.actualDuration = _treeBaseDuration;
      completedWork.treeBaseDuration = _child2;
    } else for (_treeBaseDuration = completedWork.child; null !== _treeBaseDuration;) newChildLanes
|= _treeBaseDuration.lanes | _treeBaseDuration.childLanes, subtreeFlags |=
_treeBaseDuration.subtreeFlags, subtreeFlags |= _treeBaseDuration.flags, _treeBaseDuration.return =
completedWork, _treeBaseDuration = _treeBaseDuration.sibling;
    completedWork.subtreeFlags |= subtreeFlags;
    completedWork.childLanes = newChildLanes;
    return didBailout;
  }
  function completeWork(current, workInProgress, renderLanes) {
    var newProps = workInProgress.pendingProps;
    popTreeContext(workInProgress);
    switch (workInProgress.tag) {
      case 16:
      case 15:
      case 0:
      case 11:
      case 7:
      case 8:
      case 12:
      case 9:
      case 14:
        return bubbleProperties(workInProgress), null;
      case 1:
        return bubbleProperties(workInProgress), null;
      case 3:
        newProps = workInProgress.stateNode;
        renderLanes = null;
        null !== current && (renderLanes = current.memoizedState.cache);
        workInProgress.memoizedState.cache !== renderLanes && (workInProgress.flags |= 2048);
        popProvider(CacheContext, workInProgress);
        popHostContainer(workInProgress);
        newProps.pendingContext && (newProps.context = newProps.pendingContext,
```

```
newProps.pendingContext = null);
      if (null === current || null === current.child) popHydrationState(workInProgress) ?
(emitPendingHydrationWarnings(), markUpdate(workInProgress)) : null === current ||
current.memoizedState.isDehydrated && 0 === (workInProgress.flags & 256) || (workInProgress.flags
|= 1024, null !== hydrationErrors && (queueRecoverableErrors(hydrationErrors), hydrationErrors =
null));
      bubbleProperties(workInProgress);
      return null;
    case 26:
      return renderLanes = workInProgress.memoizedState, null === current ?
(markUpdate(workInProgress), null !== renderLanes ? (bubbleProperties(workInProgress),
preloadResourceAndSuspendIfNeeded(workInProgress, renderLanes)) :
(bubbleProperties(workInProgress), workInProgress.flags &= -16777217)) : renderLanes ?
renderLanes !== current.memoizedState ? (markUpdate(workInProgress),
bubbleProperties(workInProgress), preloadResourceAndSuspendIfNeeded(workInProgress,
renderLanes)) : (bubbleProperties(workInProgress), workInProgress.flags &= -16777217) :
(current.memoizedProps !== newProps && markUpdate(workInProgress),
bubbleProperties(workInProgress), workInProgress.flags &= -16777217), null;
    case 27:
      popHostContext(workInProgress);
      renderLanes = requiredContext(rootInstanceStackCursor.current);
      var _type = workInProgress.type;
      if (null !== current && null != workInProgress.stateNode) current.memoizedProps !== newProps
&& markUpdate(workInProgress);else {
        if (!newProps) {
          if (null === workInProgress.stateNode) throw Error("We must have new props for new mounts.
This error is likely caused by a bug in React. Please file an issue.");
          bubbleProperties(workInProgress);
          return null;
        }
        current = getHostContext();
        popHydrationState(workInProgress) ? prepareToHydrateHostInstance(workInProgress, current) :
(current = resolveSingletonInstance(_type, newProps, renderLanes, current, !0),
workInProgress.stateNode = current, markUpdate(workInProgress));
      }
      bubbleProperties(workInProgress);
      return null;
    case 5:
      popHostContext(workInProgress);
      renderLanes = workInProgress.type;
      if (null !== current && null != workInProgress.stateNode) current.memoizedProps !== newProps
&& markUpdate(workInProgress);else {
        if (!newProps) {
          if (null === workInProgress.stateNode) throw Error("We must have new props for new mounts.
This error is likely caused by a bug in React. Please file an issue.");
          bubbleProperties(workInProgress);
          return null;
        }
        _type = getHostContext();
```

```
        if (popHydrationState(workInProgress)) prepareToHydrateHostInstance(workInProgress,
_type);else {
          current = requiredContext(rootInstanceStackCursor.current);
          validateDOMNesting(renderLanes, _type.ancestorInfo);
          _type = _type.context;
          current = getOwnerDocumentFromRootContainer(current);
          switch (_type) {
            case HostContextNamespaceSvg:
              current = current.createElementNS(SVG_NAMESPACE, renderLanes);
              break;
            case HostContextNamespaceMath:
              current = current.createElementNS(MATH_NAMESPACE, renderLanes);
              break;
            default:
              switch (renderLanes) {
                case "svg":
                  current = current.createElementNS(SVG_NAMESPACE, renderLanes);
                  break;
                case "math":
                  current = current.createElementNS(MATH_NAMESPACE, renderLanes);
                  break;
                case "script":
                  current = current.createElement("div");
                  current.innerHTML = "<script>\x3c/script>";
                  current = current.removeChild(current.firstChild);
                  break;
                case "select":
                  current = "string" === typeof newProps.is ? current.createElement("select", {
                    is: newProps.is
                  }) : current.createElement("select");
                  newProps.multiple ? current.multiple = !0 : newProps.size && (current.size =
newProps.size);
                  break;
                default:
                  current = "string" === typeof newProps.is ? current.createElement(renderLanes, {
                    is: newProps.is
                  }) : current.createElement(renderLanes), -1 === renderLanes.indexOf("-") &&
(renderLanes !== renderLanes.toLowerCase() && console.error("<%s /> is using incorrect casing. Use
PascalCase for React components, or lowercase for HTML elements.", renderLanes), "[object
HTMLUnknownElement]" !== Object.prototype.toString.call(current) ||
hasOwnProperty.call(warnedUnknownTags, renderLanes) || (warnedUnknownTags[renderLanes] = !0,
console.error("The tag <%s> is unrecognized in this browser. If you meant to render a React
component, start its name with an uppercase letter.", renderLanes)));
              }
          }
          current[internalInstanceKey] = workInProgress;
          current[internalPropsKey] = newProps;
          a: for (_type = workInProgress.child; null !== _type;) {
            if (5 === _type.tag || 6 === _type.tag) current.appendChild(_type.stateNode);else if (4 !==
```

```
_type.tag && 27 !== _type.tag && null !== _type.child) {
              _type.child.return = _type;
              _type = _type.child;
              continue;
            }
            if (_type === workInProgress) break a;
            for (; null === _type.sibling;) {
              if (null === _type.return || _type.return === workInProgress) break a;
              _type = _type.return;
            }
            _type.sibling.return = _type.return;
            _type = _type.sibling;
          }
          workInProgress.stateNode = current;
          a: switch (setInitialProperties(current, renderLanes, newProps), renderLanes) {
            case "button":
            case "input":
            case "select":
            case "textarea":
              current = !!newProps.autoFocus;
              break a;
            case "img":
              current = !0;
              break a;
            default:
              current = !1;
          }
          current && markUpdate(workInProgress);
        }
      }
      bubbleProperties(workInProgress);
      workInProgress.flags &= -16777217;
      return null;
    case 6:
      if (current && null != workInProgress.stateNode) current.memoizedProps !== newProps &&
markUpdate(workInProgress);else {
        if ("string" !== typeof newProps && null === workInProgress.stateNode) throw Error("We must
have new props for new mounts. This error is likely caused by a bug in React. Please file an issue.");
        current = requiredContext(rootInstanceStackCursor.current);
        renderLanes = getHostContext();
        if (popHydrationState(workInProgress)) {
          current = workInProgress.stateNode;
          newProps = workInProgress.memoizedProps;
          _type = !didSuspendOrErrorDEV;
          renderLanes = null;
          var returnFiber = hydrationParentFiber;
          if (null !== returnFiber) switch (returnFiber.tag) {
            case 3:
              _type && (_type = diffHydratedTextForDevWarnings(current, newProps, renderLanes),
```

```
null !== _type && (buildHydrationDiffNode(workInProgress, 0).serverProps = _type));
              break;
            case 27:
            case 5:
              renderLanes = returnFiber.memoizedProps, _type && (_type =
diffHydratedTextForDevWarnings(current, newProps, renderLanes), null !== _type &&
(buildHydrationDiffNode(workInProgress, 0).serverProps = _type));
          }
          current[internalInstanceKey] = workInProgress;
          current = current.nodeValue === newProps || null !== renderLanes && !0 ===
renderLanes.suppressHydrationWarning || checkForUnmatchedText(current.nodeValue, newProps) ? !
0 : !1;
          current || throwOnHydrationMismatch(workInProgress);
        } else renderLanes = renderLanes.ancestorInfo.current, null != renderLanes &&
validateTextNesting(newProps,
 renderLanes.tag), current =
getOwnerDocumentFromRootContainer(current).createTextNode(newProps),
current[internalInstanceKey] = workInProgress, workInProgress.stateNode = current;
      }
      bubbleProperties(workInProgress);
      return null;
    case 13:
      newProps = workInProgress.memoizedState;
      if (null === current || null !== current.memoizedState && null !==
current.memoizedState.dehydrated) {
        _type = popHydrationState(workInProgress);
        if (null !== newProps && null !== newProps.dehydrated) {
          if (null === current) {
            if (!_type) throw Error("A dehydrated suspense component was completed without a hydrated
node. This is probably a bug in React.");
            _type = workInProgress.memoizedState;
            _type = null !== _type ? _type.dehydrated : null;
            if (!_type) throw Error("Expected to have a hydrated suspense instance. This error is likely
caused by a bug in React. Please file an issue.");
            _type[internalInstanceKey] = workInProgress;
            bubbleProperties(workInProgress);
            (workInProgress.mode & ProfileMode) !== NoMode && null !== newProps && (_type =
workInProgress.child, null !== _type && (workInProgress.treeBaseDuration -=
_type.treeBaseDuration));
          } else emitPendingHydrationWarnings(), resetHydrationState(), 0 === (workInProgress.flags &
128) && (workInProgress.memoizedState = null), workInProgress.flags |= 4,
bubbleProperties(workInProgress), (workInProgress.mode & ProfileMode) !== NoMode && null !==
newProps && (_type = workInProgress.child, null !== _type && (workInProgress.treeBaseDuration
-= _type.treeBaseDuration));
          _type = !1;
        } else null !== hydrationErrors && (queueRecoverableErrors(hydrationErrors), hydrationErrors
= null), _type = !0;
        if (!_type) {
          if (workInProgress.flags & 256) return popSuspenseHandler(workInProgress), workInProgress;
```

```
          popSuspenseHandler(workInProgress);
          return null;
        }
      }
      popSuspenseHandler(workInProgress);
      if (0 !== (workInProgress.flags & 128)) return workInProgress.lanes = renderLanes,
(workInProgress.mode & ProfileMode) !== NoMode && transferActualDuration(workInProgress),
workInProgress;
      newProps = null !== newProps;
      current = null !== current && null !== current.memoizedState;
      newProps && (renderLanes = workInProgress.child, _type = null, null !== renderLanes.alternate
&& null !== renderLanes.alternate.memoizedState && null !==
renderLanes.alternate.memoizedState.cachePool && (_type =
renderLanes.alternate.memoizedState.cachePool.pool), returnFiber = null, null !==
renderLanes.memoizedState && null !== renderLanes.memoizedState.cachePool && (returnFiber =
renderLanes.memoizedState.cachePool.pool), returnFiber !== _type && (renderLanes.flags |= 2048));
      newProps !== current && newProps && (workInProgress.child.flags |= 8192);
      scheduleRetryEffect(workInProgress, workInProgress.updateQueue);
      bubbleProperties(workInProgress);
      (workInProgress.mode & ProfileMode) !== NoMode && newProps && (current =
workInProgress.child, null !== current && (workInProgress.treeBaseDuration -=
current.treeBaseDuration));
      return null;
    case 4:
      return popHostContainer(workInProgress), null === current &&
listenToAllSupportedEvents(workInProgress.stateNode.containerInfo),
bubbleProperties(workInProgress), null;
    case 10:
      return popProvider(workInProgress.type, workInProgress), bubbleProperties(workInProgress),
null;
    case 19:
      pop(suspenseStackCursor, workInProgress);
      _type = workInProgress.memoizedState;
      if (null === _type) return bubbleProperties(workInProgress), null;
      newProps = 0 !== (workInProgress.flags & 128);
      returnFiber = _type.rendering;
      if (null === returnFiber) {
        if (newProps) cutOffTailIfNeeded(_type, !1);else {
          if (workInProgressRootExitStatus !== RootInProgress || null !== current && 0 !==
(current.flags & 128)) for (current = workInProgress.child; null !== current;) {
            returnFiber = findFirstSuspended(current);
            if (null !== returnFiber) {
              workInProgress.flags |= 128;
              cutOffTailIfNeeded(_type, !1);
              current = returnFiber.updateQueue;
              workInProgress.updateQueue = current;
              scheduleRetryEffect(workInProgress, current);
              workInProgress.subtreeFlags = 0;
              current = renderLanes;
```

```
            for (newProps = workInProgress.child; null !== newProps;) resetWorkInProgress(newProps,
current), newProps = newProps.sibling;
            push(suspenseStackCursor, suspenseStackCursor.current & SubtreeSuspenseContextMask |
ForceSuspenseFallback, workInProgress);
            return workInProgress.child;
          }
          current = current.sibling;
        }
        null !== _type.tail && now$1() > workInProgressRootRenderTargetTime &&
(workInProgress.flags |= 128, newProps = !0, cutOffTailIfNeeded(_type, !1), workInProgress.lanes =
4194304);
      }
    } else {
      if (!newProps) if (current = findFirstSuspended(returnFiber), null !== current) {
        if (workInProgress.flags |= 128, newProps = !0, current = current.updateQueue,
workInProgress.updateQueue = current, scheduleRetryEffect(workInProgress, current),
cutOffTailIfNeeded(_type, !0), null === _type.tail && "hidden" === _type.tailMode && !
returnFiber.alternate && !isHydrating) return bubbleProperties(workInProgress), null;
      } else 2 * now$1() - _type.renderingStartTime > workInProgressRootRenderTargetTime &&
536870912 !== renderLanes && (workInProgress.flags |= 128, newProps = !0,
cutOffTailIfNeeded(_type, !1), workInProgress.lanes = 4194304);
      _type.isBackwards ? (returnFiber.sibling = workInProgress.child, workInProgress.child =
returnFiber) : (current = _type.last, null !== current ? current.sibling = returnFiber :
workInProgress.child = returnFiber, _type.last = returnFiber);
    }
    if (null !== _type.tail) return current = _type.tail, _type.rendering = current, _type.tail =
current.sibling, _type.renderingStartTime = now$1(), current.sibling = null, renderLanes =
suspenseStackCursor.current, renderLanes = newProps ? renderLanes & SubtreeSuspenseContextMask
| ForceSuspenseFallback : renderLanes & SubtreeSuspenseContextMask, push(suspenseStackCursor,
renderLanes, workInProgress), current;
    bubbleProperties(workInProgress);
    return null;
  case 22:
  case 23:
    return popSuspenseHandler(workInProgress), popHiddenContext(workInProgress), newProps =
null !== workInProgress.memoizedState, null !== current ? null !== current.memoizedState !==
newProps && (workInProgress.flags |= 8192) : newProps && (workInProgress.flags |= 8192),
newProps ? 0 !== (renderLanes & 536870912) && 0 === (workInProgress.flags & 128) &&
(bubbleProperties(workInProgress), workInProgress.subtreeFlags & 6 && (workInProgress.flags |=
8192)) : bubbleProperties(workInProgress), newProps = workInProgress.updateQueue, null !==
newProps && scheduleRetryEffect(workInProgress, newProps.retryQueue), newProps = null, null !==
current && null !== current.memoizedState && null !== current.memoizedState.cachePool &&
(newProps = current.memoizedState.cachePool.pool), renderLanes = null, null !==
workInProgress.memoizedState && null !== workInProgress.memoizedState.cachePool &&
(renderLanes = workInProgress.memoizedState.cachePool.pool), renderLanes !== newProps &&
(workInProgress.flags |= 2048), null !== current && pop(resumedCache, workInProgress), null;
  case 24:
    return newProps = null, null !== current && (newProps = current.memoizedState.cache),
workInProgress.memoizedState.cache !== newProps && (workInProgress.flags |= 2048),
```

```
popProvider(CacheContext, workInProgress), bubbleProperties(workInProgress), null;
      case 25:
        return null;
    }
    throw Error("Unknown unit of work tag (" + workInProgress.tag + "). This error is likely caused by a bug in React. Please file an issue.");
  }
  function unwindWork(current, workInProgress) {
    popTreeContext(workInProgress);
    switch (workInProgress.tag) {
      case 1:
        return current = workInProgress.flags, current & 65536 ? (workInProgress.flags = current & -65537 | 128, (workInProgress.mode & ProfileMode) !== NoMode && transferActualDuration(workInProgress), workInProgress) : null;
      case 3:
        return popProvider(CacheContext, workInProgress), popHostContainer(workInProgress), current = workInProgress.flags, 0 !== (current & 65536) && 0 === (current & 128) ? (workInProgress.flags = current & -65537 | 128, workInProgress) : null;
      case 26:
      case 27:
      case 5:
        return popHostContext(workInProgress), null;
      case 13:
        popSuspenseHandler(workInProgress);
        current = workInProgress.memoizedState;
        if (null !== current && null !== current.dehydrated) {
          if (null === workInProgress.alternate) throw Error("Threw in newly mounted dehydrated component. This is likely a bug in React. Please file an issue.");
          resetHydrationState();
        }
        current = workInProgress.flags;
        return current & 65536 ? (workInProgress.flags = current & -65537 | 128, (workInProgress.mode & ProfileMode) !== NoMode && transferActualDuration(workInProgress), workInProgress) : null;
      case 19:
        return pop(suspenseStackCursor, workInProgress), null;
      case 4:
        return popHostContainer(workInProgress), null;
      case 10:
        return popProvider(workInProgress.type, workInProgress), null;
      case 22:
      case 23:
        return popSuspenseHandler(workInProgress), popHiddenContext(workInProgress), null !== current && pop(resumedCache, workInProgress), current = workInProgress.flags, current & 65536 ? (workInProgress.flags = current & -65537 | 128, (workInProgress.mode & ProfileMode) !== NoMode && transferActualDuration(workInProgress), workInProgress) : null;
      case 24:
        return popProvider(CacheContext, workInProgress), null;
      case 25:
        return null;
```

```
      default:
        return null;
    }
  }
  function unwindInterruptedWork(current, interruptedWork) {
    popTreeContext(interruptedWork);
    switch (interruptedWork.tag) {
      case 3:
        popProvider(CacheContext, interruptedWork);
        popHostContainer(interruptedWork);
        break;
      case 26:
      case 27:
      case 5:
        popHostContext(interruptedWork);
        break;
      case 4:
        popHostContainer(interruptedWork);
        break;
      case 13:
        popSuspenseHandler(interruptedWork);
        break;
      case 19:
        pop(suspenseStackCursor, interruptedWork);
        break;
      case 10:
        popProvider(interruptedWork.type, interruptedWork);
        break;
      case 22:
      case 23:
        popSuspenseHandler(interruptedWork);
        popHiddenContext(interruptedWork);
        null !== current && pop(resumedCache, interruptedWork);
        break;
      case 24:
        popProvider(CacheContext, interruptedWork);
    }
  }
  function onCommitRoot() {
    commitHooks.forEach(function (commitHook) {
      return commitHook();
    });
  }
  function isConcurrentActEnvironment() {
    var isReactActEnvironmentGlobal = "undefined" !== typeof IS_REACT_ACT_ENVIRONMENT ?
IS_REACT_ACT_ENVIRONMENT : void 0;
    isReactActEnvironmentGlobal || null === ReactSharedInternals.actQueue || console.error("The
current testing environment is not configured to support act(...)");
    return isReactActEnvironmentGlobal;
```

```
  }
  function requestUpdateLane(fiber) {
    if ((executionContext & RenderContext) !== NoContext && 0 !==
workInProgressRootRenderLanes) return workInProgressRootRenderLanes &
-workInProgressRootRenderLanes;
    var transition = ReactSharedInternals.T;
    return null !== transition ? (transition._updatedFibers || (transition._updatedFibers = new Set()),
transition._updatedFibers.add(fiber), fiber = currentEntangledLane, 0 !== fiber ? fiber :
requestTransitionLane()) : resolveUpdatePriority();
  }
  function requestDeferredLane() {
    0 === workInProgressDeferredLane && (workInProgressDeferredLane = 0 ===
(workInProgressRootRenderLanes & 536870912) || isHydrating ? claimNextTransitionLane() :
536870912);
    var suspenseHandler = suspenseHandlerStackCursor.current;
    null !== suspenseHandler && (suspenseHandler.flags |= 32);
    return workInProgressDeferredLane;
  }
  function scheduleUpdateOnFiber(root, fiber, lane) {
    isRunningInsertionEffect && console.error("useInsertionEffect must not schedule updates.");
    isFlushingPassiveEffects && (didScheduleUpdateDuringPassiveEffects = !0);
    if (root === workInProgressRoot && workInProgressSuspendedReason === SuspendedOnData ||
null !== root.cancelPendingCommit) prepareFreshStack(root, 0), markRootSuspended(root,
workInProgressRootRenderLanes, workInProgressDeferredLane, !1);
    markRootUpdated$1(root, lane);
    if (0 !== (executionContext & RenderContext) && root === workInProgressRoot) {
      if (isRendering) switch (fiber.tag) {
        case 0:
        case 11:
        case 15:
          root = workInProgress && getComponentNameFromFiber(workInProgress) || "Unknown";
          didWarnAboutUpdateInRenderForAnotherComponent.has(root) ||
(didWarnAboutUpdateInRenderForAnotherComponent.add(root), fiber =
getComponentNameFromFiber(fiber) || "Unknown", console.error("Cannot update a component (`%s`)
while rendering a different component (`%s`). To locate the bad setState() call inside `%s`, follow the
stack trace as described in https://react.dev/link/setstate-in-render", fiber, root, root));
          break;
        case 1:
          didWarnAboutUpdateInRender || (console.error("Cannot update during an existing state
transition (such as within `render`). Render methods should be a pure function of props and state."),
didWarnAboutUpdateInRender = !0);
      }
    } else isDevToolsPresent && addFiberToLanesMap(root, fiber, lane),
warnIfUpdatesNotWrappedWithActDEV(fiber), root === workInProgressRoot && ((executionContext
& RenderContext) === NoContext && (workInProgressRootInterleavedUpdatedLanes |= lane),
workInProgressRootExitStatus === RootSuspendedWithDelay && markRootSuspended(root,
workInProgressRootRenderLanes, workInProgressDeferredLane, !1)), ensureRootIsScheduled(root);
  }
  function performWorkOnRoot(root, lanes, forceSync) {
```

```
   if ((executionContext & (RenderContext | CommitContext)) !== NoContext) throw Error("Should
not already be working.");
   var shouldTimeSlice = !forceSync && 0 === (lanes & 60) && 0 === (lanes & root.expiredLanes) ||
checkIfRootIsPrerendering(root, lanes),
     exitStatus = shouldTimeSlice ? renderRootConcurrent(root, lanes) : renderRootSync(root, lanes, !
0),
     renderWasConcurrent = shouldTimeSlice;
   do {
     if (exitStatus === RootInProgress) {
       workInProgressRootIsPrerendering && !shouldTimeSlice && markRootSuspended(root, lanes, 0,
!1);
       break;
     } else if (exitStatus === RootDidNotComplete) markRootSuspended(root, lanes, 0, !
workInProgressRootDidSkipSuspendedSiblings);else {
       forceSync = root.current.alternate;
       if (renderWasConcurrent && !isRenderConsistentWithExternalStores(forceSync)) {
         exitStatus = renderRootSync(root, lanes, !1);
         renderWasConcurrent = !1;
         continue;
       }
       if (exitStatus === RootErrored) {
         renderWasConcurrent = lanes;
         if (root.errorRecoveryDisabledLanes & renderWasConcurrent) var errorRetryLanes = 0;else
errorRetryLanes = root.pendingLanes & -536870913, errorRetryLanes = 0 !== errorRetryLanes ?
errorRetryLanes : errorRetryLanes & 536870912 ? 536870912 : 0;
         if (0 !== errorRetryLanes) {
           lanes = errorRetryLanes;
           a: {
             exitStatus = root;
             var errorRetryLanes$jscomp$0 = errorRetryLanes;
             errorRetryLanes = workInProgressRootConcurrentErrors;
             var wasRootDehydrated = exitStatus.current.memoizedState.isDehydrated;
             wasRootDehydrated && (prepareFreshStack(exitStatus, errorRetryLanes$jscomp$0).flags |=
256);
             errorRetryLanes$jscomp$0 = renderRootSync(exitStatus, errorRetryLanes$jscomp$0, !1);
             if (errorRetryLanes$jscomp$0 !== RootErrored) {
               if (workInProgressRootDidAttachPingListener && !wasRootDehydrated) {
                 exitStatus.errorRecoveryDisabledLanes |= renderWasConcurrent;
                 workInProgressRootInterleavedUpdatedLanes |= renderWasConcurrent;
                 exitStatus = RootSuspendedWithDelay;
                 break a;
               }
               exitStatus = workInProgressRootRecoverableErrors;
               workInProgressRootRecoverableErrors = errorRetryLanes;
               null !== exitStatus && queueRecoverableErrors(exitStatus);
             }
             exitStatus = errorRetryLanes$jscomp$0;
           }
           renderWasConcurrent = !1;
```

```
          if (exitStatus !== RootErrored) continue;
        }
      }
      if (exitStatus === RootFatalErrored) {
        prepareFreshStack(root, 0);
        markRootSuspended(root, lanes, 0, !0);
        break;
      }
      a: {
        shouldTimeSlice = root;
        switch (exitStatus) {
          case RootInProgress:
          case RootFatalErrored:
            throw Error("Root did not complete. This is a bug in React.");
          case RootSuspendedWithDelay:
            if ((lanes & 4194176) === lanes) {
              markRootSuspended(shouldTimeSlice, lanes, workInProgressDeferredLane, !
workInProgressRootDidSkipSuspendedSiblings);
              break a;
            }
            break;
          case RootErrored:
            workInProgressRootRecoverableErrors = null;
            break;
          case RootSuspended:
          case RootCompleted:
            break;
          default:
            throw Error("Unknown root exit status.");
        }
        shouldTimeSlice.finishedWork = forceSync;
        shouldTimeSlice.finishedLanes = lanes;
        if (null !== ReactSharedInternals.actQueue) commitRoot(shouldTimeSlice,
workInProgressRootRecoverableErrors, workInProgressTransitions,
workInProgressRootDidIncludeRecursiveRenderUpdate, workInProgressDeferredLane,
workInProgressRootInterleavedUpdatedLanes, workInProgressSuspendedRetryLanes,
IMMEDIATE_COMMIT, renderStartTime, 0);else {
          if ((lanes & 62914560) === lanes && (exitStatus = globalMostRecentFallbackTime +
FALLBACK_THROTTLE_MS - now$1(), 10 < exitStatus)) {
            markRootSuspended(shouldTimeSlice, lanes, workInProgressDeferredLane, !
workInProgressRootDidSkipSuspendedSiblings);
            if (0 !== getNextLanes(shouldTimeSlice, 0)) break a;
            shouldTimeSlice.timeoutHandle = scheduleTimeout(commitRootWhenReady.bind(null,
shouldTimeSlice, forceSync, workInProgressRootRecoverableErrors, workInProgressTransitions,
workInProgressRootDidIncludeRecursiveRenderUpdate, lanes, workInProgressDeferredLane,
workInProgressRootInterleavedUpdatedLanes, workInProgressSuspendedRetryLanes,
workInProgressRootDidSkipSuspendedSiblings, THROTTLED_COMMIT, renderStartTime, 0),
exitStatus);
            break a;
```

```
          }
          commitRootWhenReady(shouldTimeSlice, forceSync, workInProgressRootRecoverableErrors,
workInProgressTransitions, workInProgressRootDidIncludeRecursiveRenderUpdate, lanes,
workInProgressDeferredLane, workInProgressRootInterleavedUpdatedLanes,
workInProgressSuspendedRetryLanes, workInProgressRootDidSkipSuspendedSiblings,
 IMMEDIATE_COMMIT, renderStartTime, 0);
        }
       }
      }
      break;
    } while (1);
    ensureRootIsScheduled(root);
  }
  function queueRecoverableErrors(errors) {
    null === workInProgressRootRecoverableErrors ? workInProgressRootRecoverableErrors = errors :
workInProgressRootRecoverableErrors.push.apply(workInProgressRootRecoverableErrors, errors);
  }
  function commitRootWhenReady(root, finishedWork, recoverableErrors, transitions,
didIncludeRenderPhaseUpdate, lanes, spawnedLane, updatedLanes, suspendedRetryLanes,
didSkipSuspendedSiblings, suspendedCommitReason, completedRenderStartTime,
completedRenderEndTime) {
    var subtreeFlags = finishedWork.subtreeFlags;
    if (subtreeFlags & 8192 || 16785408 === (subtreeFlags & 16785408)) if (suspendedState = {
      stylesheets: null,
      count: 0,
      unsuspend: noop
    }, accumulateSuspenseyCommitOnFiber(finishedWork), finishedWork =
waitForCommitToBeReady(), null !== finishedWork) {
      root.cancelPendingCommit = finishedWork(commitRoot.bind(null, root, recoverableErrors,
transitions, didIncludeRenderPhaseUpdate, spawnedLane, updatedLanes, suspendedRetryLanes,
SUSPENDED_COMMIT, completedRenderStartTime, completedRenderEndTime));
      markRootSuspended(root, lanes, spawnedLane, !didSkipSuspendedSiblings);
      return;
    }
    commitRoot(root, recoverableErrors, transitions, didIncludeRenderPhaseUpdate, spawnedLane,
updatedLanes, suspendedRetryLanes, suspendedCommitReason, completedRenderStartTime,
completedRenderEndTime);
  }
  function isRenderConsistentWithExternalStores(finishedWork) {
    for (var node = finishedWork;;) {
      var tag = node.tag;
      if ((0 === tag || 11 === tag || 15 === tag) && node.flags & 16384 && (tag = node.updateQueue,
null !== tag && (tag = tag.stores, null !== tag))) for (var i = 0; i < tag.length; i++) {
        var check = tag[i],
          getSnapshot = check.getSnapshot;
        check = check.value;
        try {
          if (!objectIs(getSnapshot(), check)) return !1;
        } catch (error) {
```

```
        return !1;
       }
      }
      tag = node.child;
      if (node.subtreeFlags & 16384 && null !== tag) tag.return = node, node = tag;else {
       if (node === finishedWork) break;
       for (; null === node.sibling;) {
        if (null === node.return || node.return === finishedWork) return !0;
        node = node.return;
       }
       node.sibling.return = node.return;
       node = node.sibling;
      }
     }
     return !0;
    }
    function markRootSuspended(root, suspendedLanes, spawnedLane, didAttemptEntireTree) {
     suspendedLanes &= ~workInProgressRootPingedLanes;
     suspendedLanes &= ~workInProgressRootInterleavedUpdatedLanes;
     root.suspendedLanes |= suspendedLanes;
     root.pingedLanes &= ~suspendedLanes;
     didAttemptEntireTree && (root.warmLanes |= suspendedLanes);
     didAttemptEntireTree = root.expirationTimes;
     for (var lanes = suspendedLanes; 0 < lanes;) {
      var index = 31 - clz32(lanes),
       lane = 1 << index;
      didAttemptEntireTree[index] = -1;
      lanes &= ~lane;
     }
     0 !== spawnedLane && markSpawnedDeferredLane(root, spawnedLane, suspendedLanes);
    }
    function flushSyncWork$1() {
     return (executionContext & (RenderContext | CommitContext)) === NoContext ?
(flushSyncWorkAcrossRoots_impl(0, !1), !1) : !0;
    }
    function resetWorkInProgressStack() {
     if (null !== workInProgress) {
      if (workInProgressSuspendedReason === NotSuspended) var interruptedWork =
workInProgress.return;else interruptedWork = workInProgress, resetContextDependencies(),
resetHooksOnUnwind(interruptedWork), thenableState$1 = null, thenableIndexCounter$1 = 0,
interruptedWork = workInProgress;
      for (; null !== interruptedWork;) unwindInterruptedWork(interruptedWork.alternate,
interruptedWork), interruptedWork = interruptedWork.return;
      workInProgress = null;
     }
    }
    function prepareFreshStack(root, lanes) {
     root.finishedWork = null;
     root.finishedLanes = 0;
```

```
    var timeoutHandle = root.timeoutHandle;
    timeoutHandle !== noTimeout && (root.timeoutHandle = noTimeout,
cancelTimeout(timeoutHandle));
    timeoutHandle = root.cancelPendingCommit;
    null !== timeoutHandle && (root.cancelPendingCommit = null, timeoutHandle());
    resetWorkInProgressStack();
    workInProgressRoot = root;
    workInProgress = timeoutHandle = createWorkInProgress(root.current, null);
    workInProgressRootRenderLanes = lanes;
    workInProgressSuspendedReason = NotSuspended;
    workInProgressThrownValue = null;
    workInProgressRootDidSkipSuspendedSiblings = !1;
    workInProgressRootIsPrerendering = checkIfRootIsPrerendering(root, lanes);
    workInProgressRootDidAttachPingListener = !1;
    workInProgressRootExitStatus = RootInProgress;
    workInProgressSuspendedRetryLanes = workInProgressDeferredLane =
workInProgressRootPingedLanes = workInProgressRootInterleavedUpdatedLanes =
workInProgressRootSkippedLanes = 0;
    workInProgressRootRecoverableErrors = workInProgressRootConcurrentErrors = null;
    workInProgressRootDidIncludeRecursiveRenderUpdate = !1;
    0 !== (lanes & 8) && (lanes |= lanes & 32);
    var allEntangledLanes = root.entangledLanes;
    if (0 !== allEntangledLanes) for (root = root.entanglements, allEntangledLanes &= lanes; 0 <
allEntangledLanes;) {
      var index = 31 - clz32(allEntangledLanes),
        lane = 1 << index;
      lanes |= root[index];
      allEntangledLanes &= ~lane;
    }
    entangledRenderLanes = lanes;
    finishQueueingConcurrentUpdates();
    ReactStrictModeWarnings.discardPendingWarnings();
    return timeoutHandle;
  }
  function handleThrow(root, thrownValue) {
    currentlyRenderingFiber$1 = null;
    ReactSharedInternals.H = ContextOnlyDispatcher;
    ReactSharedInternals.getCurrentStack = null;
    isRendering = !1;
    current = null;
    thrownValue === SuspenseException ? (thrownValue = getSuspendedThenable(),
workInProgressSuspendedReason = SuspendedOnImmediate) : thrownValue ===
SuspenseyCommitException ? (thrownValue = getSuspendedThenable(),
workInProgressSuspendedReason = SuspendedOnInstance) : workInProgressSuspendedReason =
thrownValue === SelectiveHydrationException ? SuspendedOnHydration : null !== thrownValue &&
"object" === typeof thrownValue && "function" === typeof thrownValue.then ?
SuspendedOnDeprecatedThrowPromise : SuspendedOnError;
    workInProgressThrownValue = thrownValue;
    var erroredWork = workInProgress;
```

```
    if (null === erroredWork) workInProgressRootExitStatus = RootFatalErrored,
logUncaughtError(root, createCapturedValueAtFiber(thrownValue, root.current));else switch
(erroredWork.mode & ProfileMode &&
stopProfilerTimerIfRunningAndRecordDuration(erroredWork), markComponentRenderStopped(),
workInProgressSuspendedReason) {
      case SuspendedOnError:
        null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentErrored &&
injectedProfilingHooks.markComponentErrored(erroredWork, thrownValue,
workInProgressRootRenderLanes);
        break;
      case SuspendedOnData:
      case SuspendedOnImmediate:
      case SuspendedOnDeprecatedThrowPromise:
      case SuspendedAndReadyToContinue:
        null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markComponentSuspended &&
injectedProfilingHooks.markComponentSuspended(erroredWork, thrownValue,
workInProgressRootRenderLanes);
    }
  }
  function pushDispatcher() {
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = ContextOnlyDispatcher;
    return null === prevDispatcher ? ContextOnlyDispatcher : prevDispatcher;
  }
  function pushAsyncDispatcher() {
    var prevAsyncDispatcher = ReactSharedInternals.A;
    ReactSharedInternals.A = DefaultAsyncDispatcher;
    return prevAsyncDispatcher;
  }
  function renderDidSuspendDelayIfPossible() {
    workInProgressRootExitStatus = RootSuspendedWithDelay;
    workInProgressRootDidSkipSuspendedSiblings || (workInProgressRootRenderLanes & 4194176) !
== workInProgressRootRenderLanes && null !== suspenseHandlerStackCursor.current ||
(workInProgressRootIsPrerendering = !0);
    0 === (workInProgressRootSkippedLanes & 134217727) && 0 ===
(workInProgressRootInterleavedUpdatedLanes & 134217727) || null === workInProgressRoot ||
markRootSuspended(workInProgressRoot, workInProgressRootRenderLanes,
workInProgressDeferredLane, !1);
  }
  function renderRootSync(root, lanes, shouldYieldForPrerendering) {
    var prevExecutionContext = executionContext;
    executionContext |= RenderContext;
    var prevDispatcher = pushDispatcher(),
      prevAsyncDispatcher = pushAsyncDispatcher();
    if (workInProgressRoot !== root || workInProgressRootRenderLanes !== lanes) {
      if (isDevToolsPresent) {
        var memoizedUpdaters = root.memoizedUpdaters;
```

```
      0 < memoizedUpdaters.size && (restorePendingUpdaters(root,
workInProgressRootRenderLanes), memoizedUpdaters.clear());
       movePendingFibersToMemoized(root, lanes);
     }
     workInProgressTransitions = null;
     prepareFreshStack(root, lanes);
   }
   markRenderStarted(lanes);
   lanes = !1;
   memoizedUpdaters = workInProgressRootExitStatus;
   a: do try {
     if (workInProgressSuspendedReason !== NotSuspended && null !== workInProgress) {
       var unitOfWork = workInProgress,
         thrownValue = workInProgressThrownValue;
       switch (workInProgressSuspendedReason) {
         case SuspendedOnHydration:
           resetWorkInProgressStack();
           memoizedUpdaters = RootDidNotComplete;
           break a;
         case SuspendedOnImmediate:
         case SuspendedOnData:
         case SuspendedOnDeprecatedThrowPromise:
           null === suspenseHandlerStackCursor.current && (lanes = !0);
           var reason = workInProgressSuspendedReason;
           workInProgressSuspendedReason = NotSuspended;
           workInProgressThrownValue
 = null;
           throwAndUnwindWorkLoop(root, unitOfWork, thrownValue, reason);
           if (shouldYieldForPrerendering && workInProgressRootIsPrerendering) {
             memoizedUpdaters = RootInProgress;
             break a;
           }
           break;
         default:
           reason = workInProgressSuspendedReason, workInProgressSuspendedReason = NotSuspended,
workInProgressThrownValue = null, throwAndUnwindWorkLoop(root, unitOfWork, thrownValue,
reason);
       }
     }
     workLoopSync();
     memoizedUpdaters = workInProgressRootExitStatus;
     break;
   } catch (thrownValue$8) {
     handleThrow(root, thrownValue$8);
   } while (1);
   lanes && root.shellSuspendCounter++;
   resetContextDependencies();
   executionContext = prevExecutionContext;
   ReactSharedInternals.H = prevDispatcher;
```

```
    ReactSharedInternals.A = prevAsyncDispatcher;
    markRenderStopped();
    null === workInProgress && (workInProgressRoot = null, workInProgressRootRenderLanes = 0,
finishQueueingConcurrentUpdates());
    return memoizedUpdaters;
  }
  function workLoopSync() {
    for (; null !== workInProgress;) performUnitOfWork(workInProgress);
  }
  function renderRootConcurrent(root, lanes) {
    var prevExecutionContext = executionContext;
    executionContext |= RenderContext;
    var prevDispatcher = pushDispatcher(),
      prevAsyncDispatcher = pushAsyncDispatcher();
    if (workInProgressRoot !== root || workInProgressRootRenderLanes !== lanes) {
      if (isDevToolsPresent) {
        var memoizedUpdaters = root.memoizedUpdaters;
        0 < memoizedUpdaters.size && (restorePendingUpdaters(root,
workInProgressRootRenderLanes), memoizedUpdaters.clear());
        movePendingFibersToMemoized(root, lanes);
      }
      workInProgressTransitions = null;
      workInProgressRootRenderTargetTime = now$1() + RENDER_TIMEOUT_MS;
      prepareFreshStack(root, lanes);
    } else workInProgressRootIsPrerendering = checkIfRootIsPrerendering(root, lanes);
    markRenderStarted(lanes);
    a: do try {
      if (workInProgressSuspendedReason !== NotSuspended && null !== workInProgress) b: switch
(lanes = workInProgress, memoizedUpdaters = workInProgressThrownValue,
workInProgressSuspendedReason) {
        case SuspendedOnError:
          workInProgressSuspendedReason = NotSuspended;
          workInProgressThrownValue = null;
          throwAndUnwindWorkLoop(root, lanes, memoizedUpdaters, SuspendedOnError);
          break;
        case SuspendedOnData:
          if (isThenableResolved(memoizedUpdaters)) {
            workInProgressSuspendedReason = NotSuspended;
            workInProgressThrownValue = null;
            replaySuspendedUnitOfWork(lanes);
            break;
          }
          lanes = function () {
            workInProgressSuspendedReason === SuspendedOnData && workInProgressRoot === root
&& (workInProgressSuspendedReason = SuspendedAndReadyToContinue);
            ensureRootIsScheduled(root);
          };
          memoizedUpdaters.then(lanes, lanes);
          break a;
```

```
      case SuspendedOnImmediate:
        workInProgressSuspendedReason = SuspendedAndReadyToContinue;
        break a;
      case SuspendedOnInstance:
        workInProgressSuspendedReason = SuspendedOnInstanceAndReadyToContinue;
        break a;
      case SuspendedAndReadyToContinue:
        isThenableResolved(memoizedUpdaters) ? (workInProgressSuspendedReason = NotSuspended,
workInProgressThrownValue = null, replaySuspendedUnitOfWork(lanes)) :
(workInProgressSuspendedReason = NotSuspended, workInProgressThrownValue = null,
throwAndUnwindWorkLoop(root, lanes, memoizedUpdaters, SuspendedAndReadyToContinue));
        break;
      case SuspendedOnInstanceAndReadyToContinue:
        var resource = null;
        switch (workInProgress.tag) {
          case 26:
            resource = workInProgress.memoizedState;
          case 5:
          case 27:
            var hostFiber = workInProgress;
            if (resource ? preloadResource(resource) : 1) {
              workInProgressSuspendedReason = NotSuspended;
              workInProgressThrownValue = null;
              var sibling = hostFiber.sibling;
              if (null !== sibling) workInProgress = sibling;else {
                var returnFiber = hostFiber.return;
                null !== returnFiber ? (workInProgress = returnFiber, completeUnitOfWork(returnFiber)) :
workInProgress = null;
              }
              break b;
            }
            break;
          default:
            console.error("Unexpected type of fiber triggered a suspensey commit. This is a bug in
React.");
        }
        workInProgressSuspendedReason = NotSuspended;
        workInProgressThrownValue = null;
        throwAndUnwindWorkLoop(root, lanes, memoizedUpdaters,
SuspendedOnInstanceAndReadyToContinue);
        break;
      case SuspendedOnDeprecatedThrowPromise:
        workInProgressSuspendedReason = NotSuspended;
        workInProgressThrownValue = null;
        throwAndUnwindWorkLoop(root, lanes, memoizedUpdaters,
SuspendedOnDeprecatedThrowPromise);
        break;
      case SuspendedOnHydration:
        resetWorkInProgressStack();
```

```
          workInProgressRootExitStatus = RootDidNotComplete;
          break a;
        default:
          throw Error("Unexpected SuspendedReason. This is a bug in React.");
      }
      null !== ReactSharedInternals.actQueue ? workLoopSync() : workLoopConcurrent();
      break;
    } catch (thrownValue$9) {
      handleThrow(root, thrownValue$9);
    } while (1);
    resetContextDependencies();
    ReactSharedInternals.H = prevDispatcher;
    ReactSharedInternals.A = prevAsyncDispatcher;
    executionContext = prevExecutionContext;
    if (null !== workInProgress) return null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markRenderYielded && injectedProfilingHooks.markRenderYielded(),
RootInProgress;
    markRenderStopped();
    workInProgressRoot = null;
    workInProgressRootRenderLanes = 0;
    finishQueueingConcurrentUpdates();
    return workInProgressRootExitStatus;
  }
  function workLoopConcurrent() {
    for (; null !== workInProgress && !shouldYield();) performUnitOfWork(workInProgress);
  }
  function performUnitOfWork(unitOfWork) {
    var current = unitOfWork.alternate;
    (unitOfWork.mode & ProfileMode) !== NoMode ? (startProfilerTimer(unitOfWork), current =
runWithFiberInDEV(unitOfWork, beginWork, current, unitOfWork, entangledRenderLanes),
stopProfilerTimerIfRunningAndRecordDuration(unitOfWork)) : current =
runWithFiberInDEV(unitOfWork, beginWork, current, unitOfWork, entangledRenderLanes);
    unitOfWork.memoizedProps = unitOfWork.pendingProps;
    null === current ? completeUnitOfWork(unitOfWork) : workInProgress = current;
  }
  function replaySuspendedUnitOfWork(unitOfWork) {
    var next = runWithFiberInDEV(unitOfWork, replayBeginWork, unitOfWork);
    unitOfWork.memoizedProps = unitOfWork.pendingProps;
    null === next ? completeUnitOfWork(unitOfWork) : workInProgress = next;
  }
  function replayBeginWork(unitOfWork) {
    var current = unitOfWork.alternate,
      isProfilingMode = (unitOfWork.mode & ProfileMode) !== NoMode;
    isProfilingMode && startProfilerTimer(unitOfWork);
    switch (unitOfWork.tag) {
      case 15:
      case 0:
        current = replayFunctionComponent(current, unitOfWork, unitOfWork.pendingProps,
unitOfWork.type, void 0, workInProgressRootRenderLanes);
```

```
        break;
      case 11:
        current = replayFunctionComponent(current, unitOfWork, unitOfWork.pendingProps,
unitOfWork.type.render, unitOfWork.ref, workInProgressRootRenderLanes);
        break;
      case 5:
        resetHooksOnUnwind(unitOfWork);
      default:
        unwindInterruptedWork(current, unitOfWork), unitOfWork = workInProgress =
resetWorkInProgress(unitOfWork, entangledRenderLanes), current = beginWork(current, unitOfWork,
entangledRenderLanes);
    }
    isProfilingMode && stopProfilerTimerIfRunningAndRecordDuration(unitOfWork);
    return current;
  }
  function throwAndUnwindWorkLoop(root, unitOfWork, thrownValue, suspendedReason) {
    resetContextDependencies();
    resetHooksOnUnwind(unitOfWork);
    thenableState$1 = null;
    thenableIndexCounter$1 = 0;
    var returnFiber = unitOfWork.return;
    try {
      if (throwException(root, returnFiber, unitOfWork, thrownValue,
workInProgressRootRenderLanes)) {
        workInProgressRootExitStatus = RootFatalErrored;
        logUncaughtError(root, createCapturedValueAtFiber(thrownValue, root.current));
        workInProgress = null;
        return;
      }
    } catch (error) {
      if (null !== returnFiber) throw workInProgress = returnFiber, error;
      workInProgressRootExitStatus = RootFatalErrored;
      logUncaughtError(root, createCapturedValueAtFiber(thrownValue, root.current));
      workInProgress = null;
      return;
    }
    if (unitOfWork.flags & 32768) {
      if (isHydrating || suspendedReason === SuspendedOnError) root = !0;else if
(workInProgressRootIsPrerendering || 0 !== (workInProgressRootRenderLanes & 536870912)) root = !
1;else if (workInProgressRootDidSkipSuspendedSiblings = root = !0, suspendedReason ===
SuspendedOnData || suspendedReason === SuspendedOnImmediate || suspendedReason ===
SuspendedOnDeprecatedThrowPromise) suspendedReason = suspenseHandlerStackCursor.current,
null !== suspendedReason && 13 === suspendedReason.tag && (suspendedReason.flags |= 16384);
      unwindUnitOfWork(unitOfWork, root);
    } else completeUnitOfWork(unitOfWork);
  }
  function completeUnitOfWork(unitOfWork) {
    var completedWork = unitOfWork;
    do {
```

```
    if (0 !== (completedWork.flags & 32768)) {
      unwindUnitOfWork(completedWork, workInProgressRootDidSkipSuspendedSiblings);
      return;
    }
    var current = completedWork.alternate;

    unitOfWork = completedWork.return;
    startProfilerTimer(completedWork);
    current = runWithFiberInDEV(completedWork, completeWork, current, completedWork,
entangledRenderLanes);
    (completedWork.mode & ProfileMode) !== NoMode &&
stopProfilerTimerIfRunningAndRecordIncompleteDuration(completedWork);
    if (null !== current) {
      workInProgress = current;
      return;
    }
    completedWork = completedWork.sibling;
    if (null !== completedWork) {
      workInProgress = completedWork;
      return;
    }
    workInProgress = completedWork = unitOfWork;
  } while (null !== completedWork);
  workInProgressRootExitStatus === RootInProgress && (workInProgressRootExitStatus =
RootCompleted);
 }
 function unwindUnitOfWork(unitOfWork, skipSiblings) {
  do {
    var next = unwindWork(unitOfWork.alternate, unitOfWork);
    if (null !== next) {
      next.flags &= 32767;
      workInProgress = next;
      return;
    }
    if ((unitOfWork.mode & ProfileMode) !== NoMode) {
      stopProfilerTimerIfRunningAndRecordIncompleteDuration(unitOfWork);
      next = unitOfWork.actualDuration;
      for (var child = unitOfWork.child; null !== child;) next += child.actualDuration, child =
child.sibling;
      unitOfWork.actualDuration = next;
    }
    next = unitOfWork.return;
    null !== next && (next.flags |= 32768, next.subtreeFlags = 0, next.deletions = null);
    if (!skipSiblings && (unitOfWork = unitOfWork.sibling, null !== unitOfWork)) {
      workInProgress = unitOfWork;
      return;
    }
    workInProgress = unitOfWork = next;
  } while (null !== unitOfWork);
```

```
    workInProgressRootExitStatus = RootDidNotComplete;
    workInProgress = null;
  }
  function commitRoot(root, recoverableErrors, transitions, didIncludeRenderPhaseUpdate,
spawnedLane, updatedLanes, suspendedRetryLanes, suspendedCommitReason,
completedRenderStartTime, completedRenderEndTime) {
    var prevTransition = ReactSharedInternals.T,
      previousUpdateLanePriority = ReactDOMSharedInternals.p;
    try {
      ReactDOMSharedInternals.p = DiscreteEventPriority, ReactSharedInternals.T = null,
commitRootImpl(root, recoverableErrors, transitions, didIncludeRenderPhaseUpdate,
previousUpdateLanePriority, spawnedLane, updatedLanes, suspendedRetryLanes,
suspendedCommitReason, completedRenderStartTime, completedRenderEndTime);
    } finally {
      ReactSharedInternals.T = prevTransition, ReactDOMSharedInternals.p =
previousUpdateLanePriority;
    }
  }
  function commitRootImpl(root, recoverableErrors, transitions, didIncludeRenderPhaseUpdate,
renderPriorityLevel, spawnedLane, updatedLanes, suspendedRetryLanes) {
    do flushPassiveEffects(); while (null !== rootWithPendingPassiveEffects);
    ReactStrictModeWarnings.flushLegacyContextWarning();
    ReactStrictModeWarnings.flushPendingUnsafeLifecycleWarnings();
    if ((executionContext & (RenderContext | CommitContext)) !== NoContext) throw Error("Should
not already be working.");
    var finishedWork = root.finishedWork;
    didIncludeRenderPhaseUpdate = root.finishedLanes;
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markCommitStarted &&
injectedProfilingHooks.markCommitStarted(didIncludeRenderPhaseUpdate);
    if (null === finishedWork) return markCommitStopped(), null;
    0 === didIncludeRenderPhaseUpdate && console.error("root.finishedLanes should not be empty
during a commit. This is a bug in React.");
    root.finishedWork = null;
    root.finishedLanes = 0;
    if (finishedWork === root.current) throw Error("Cannot commit the same tree as before. This error is
likely caused by a bug in React. Please file an issue.");
    root.callbackNode = null;
    root.callbackPriority = 0;
    root.cancelPendingCommit = null;
    var remainingLanes = finishedWork.lanes | finishedWork.childLanes;
    remainingLanes |= concurrentlyUpdatedLanes;
    markRootFinished(root, didIncludeRenderPhaseUpdate, remainingLanes, spawnedLane,
updatedLanes, suspendedRetryLanes);
    root === workInProgressRoot && (workInProgress = workInProgressRoot = null,
workInProgressRootRenderLanes = 0);
    0 === (finishedWork.subtreeFlags & 10256) && 0 === (finishedWork.flags & 10256) ||
rootDoesHavePassiveEffects || (rootDoesHavePassiveEffects = !0,
pendingPassiveEffectsRemainingLanes = remainingLanes, pendingPassiveTransitions = transitions,
```

```
scheduleCallback$1(NormalPriority$1, function () {
      flushPassiveEffects(!0);
      return null;
    }));
    commitStartTime = now();
    transitions = 0 !== (finishedWork.flags & 15990);
    0 !== (finishedWork.subtreeFlags & 15990) || transitions ? (transitions = ReactSharedInternals.T,
ReactSharedInternals.T = null, spawnedLane = ReactDOMSharedInternals.p,
ReactDOMSharedInternals.p = DiscreteEventPriority, updatedLanes = executionContext,
executionContext |= CommitContext, commitBeforeMutationEffects(root, finishedWork),
commitMutationEffects(root, finishedWork, didIncludeRenderPhaseUpdate),
restoreSelection(selectionInformation, root.containerInfo), _enabled = !!eventsEnabled,
selectionInformation = eventsEnabled = null, root.current = finishedWork, null !==
injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markLayoutEffectsStarted
&& injectedProfilingHooks.markLayoutEffectsStarted(didIncludeRenderPhaseUpdate),
commitLayoutEffects(finishedWork, root, didIncludeRenderPhaseUpdate), null !==
injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markLayoutEffectsStopped
&& injectedProfilingHooks.markLayoutEffectsStopped(), requestPaint(), executionContext =
updatedLanes, ReactDOMSharedInternals.p = spawnedLane, ReactSharedInternals.T = transitions) :
root.current = finishedWork;
    (transitions = rootDoesHavePassiveEffects) ? (rootDoesHavePassiveEffects = !1,
rootWithPendingPassiveEffects = root, pendingPassiveEffectsLanes =
didIncludeRenderPhaseUpdate) : (releaseRootPooledCache(root, remainingLanes),
nestedPassiveUpdateCount = 0, rootWithPassiveNestedUpdates = null);
    remainingLanes = root.pendingLanes;
    0 === remainingLanes && (legacyErrorBoundariesThatAlreadyFailed = null);
    transitions || commitDoubleInvokeEffectsInDEV(root);
    onCommitRoot$1(finishedWork.stateNode, renderPriorityLevel);
    isDevToolsPresent && root.memoizedUpdaters.clear();
    onCommitRoot();
    ensureRootIsScheduled(root);
    if (null !== recoverableErrors) for (renderPriorityLevel = root.onRecoverableError, finishedWork =
0; finishedWork < recoverableErrors.length; finishedWork++) remainingLanes =
recoverableErrors[finishedWork], transitions = makeErrorInfo(remainingLanes.stack),
runWithFiberInDEV(remainingLanes.source, renderPriorityLevel, remainingLanes.value, transitions);
    0 !== (pendingPassiveEffectsLanes & 3) && flushPassiveEffects();
    remainingLanes = root.pendingLanes;
    0 !== (didIncludeRenderPhaseUpdate & 4194218) && 0 !== (remainingLanes & 42) ?
(nestedUpdateScheduled = !0, root === rootWithNestedUpdates ? nestedUpdateCount++ :
(nestedUpdateCount = 0, rootWithNestedUpdates = root)) : nestedUpdateCount = 0;
    flushSyncWorkAcrossRoots_impl(0, !1);
    markCommitStopped();
    return null;
  }
  function makeErrorInfo(componentStack) {
    componentStack = {
      componentStack: componentStack
    };
    Object.defineProperty(componentStack, "digest", {
```

```
      get: function () {
        console.error('You are accessing "digest" from the errorInfo object passed to onRecoverableError. This property is no longer provided as part of errorInfo but can be accessed as a property of the Error instance itself.');
      }
    });
    return componentStack;
  }
  function releaseRootPooledCache(root, remainingLanes) {
    0 === (root.pooledCacheLanes &= remainingLanes) && (remainingLanes = root.pooledCache, null != remainingLanes && (root.pooledCache = null, releaseCache(remainingLanes)));
  }
  function flushPassiveEffects() {
    if (null !== rootWithPendingPassiveEffects) {
      var root = rootWithPendingPassiveEffects,
        remainingLanes = pendingPassiveEffectsRemainingLanes;
      pendingPassiveEffectsRemainingLanes = 0;
      var renderPriority = lanesToEventPriority(pendingPassiveEffectsLanes),
        priority = 0 === DefaultEventPriority || DefaultEventPriority > renderPriority ? DefaultEventPriority : renderPriority;
      renderPriority = ReactSharedInternals.T;
      var previousPriority = ReactDOMSharedInternals.p;
      try {
        ReactDOMSharedInternals.p = priority;
        ReactSharedInternals.T = null;
        if (null === rootWithPendingPassiveEffects) var JSCompiler_inline_result = !1;else {
          priority = pendingPassiveTransitions;
          pendingPassiveTransitions = null;
          var root$jscomp$0 = rootWithPendingPassiveEffects,
            lanes = pendingPassiveEffectsLanes;
          rootWithPendingPassiveEffects = null;
          pendingPassiveEffectsLanes = 0;
          if ((executionContext & (RenderContext | CommitContext)) !== NoContext) throw Error("Cannot flush passive effects while already rendering.");
          isFlushingPassiveEffects = !0;
          didScheduleUpdateDuringPassiveEffects = !1;
          null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markPassiveEffectsStarted && injectedProfilingHooks.markPassiveEffectsStarted(lanes);
          var prevExecutionContext = executionContext;
          executionContext |= CommitContext;
          commitPassiveUnmountOnFiber(root$jscomp$0.current);
          commitPassiveMountOnFiber(root$jscomp$0, root$jscomp$0.current, lanes, priority);
          null !== injectedProfilingHooks && "function" === typeof injectedProfilingHooks.markPassiveEffectsStopped && injectedProfilingHooks.markPassiveEffectsStopped();
          commitDoubleInvokeEffectsInDEV(root$jscomp$0);
          executionContext = prevExecutionContext;
```

```
        flushSyncWorkAcrossRoots_impl(0, !1);
        didScheduleUpdateDuringPassiveEffects ? root$jscomp$0 === rootWithPassiveNestedUpdates ?
nestedPassiveUpdateCount++ : (nestedPassiveUpdateCount = 0, rootWithPassiveNestedUpdates =
root$jscomp$0) : nestedPassiveUpdateCount = 0;
        didScheduleUpdateDuringPassiveEffects = isFlushingPassiveEffects = !1;
        if (injectedHook && "function" === typeof injectedHook.onPostCommitFiberRoot) try {
          injectedHook.onPostCommitFiberRoot(rendererID, root$jscomp$0);
        } catch (err) {
          hasLoggedError || (hasLoggedError = !0, console.error("React instrumentation encountered an
error: %s", err));
        }
        var stateNode = root$jscomp$0.current.stateNode;
        stateNode.effectDuration = 0;
        stateNode.passiveEffectDuration = 0;
        JSCompiler_inline_result = !0;
      }
      return JSCompiler_inline_result;
    } finally {
      ReactDOMSharedInternals.p = previousPriority, ReactSharedInternals.T = renderPriority,
releaseRootPooledCache(root, remainingLanes);
    }
  }
  return !1;
 }
 function captureCommitPhaseErrorOnRoot(rootFiber, sourceFiber, error) {
  sourceFiber = createCapturedValueAtFiber(error, sourceFiber);
  sourceFiber = createRootErrorUpdate(rootFiber.stateNode, sourceFiber, 2);
  rootFiber = enqueueUpdate(rootFiber, sourceFiber, 2);
  null !== rootFiber && (markRootUpdated$1(rootFiber, 2), ensureRootIsScheduled(rootFiber));
 }
 function captureCommitPhaseError(sourceFiber, nearestMountedAncestor, error) {
  isRunningInsertionEffect = !1;
  if (3 === sourceFiber.tag) captureCommitPhaseErrorOnRoot(sourceFiber, sourceFiber, error);else {
    for (; null !== nearestMountedAncestor;) {
      if (3 === nearestMountedAncestor.tag) {
        captureCommitPhaseErrorOnRoot(nearestMountedAncestor, sourceFiber, error);
        return;
      }
      if (1 === nearestMountedAncestor.tag) {
        var instance = nearestMountedAncestor.stateNode;
        if ("function" === typeof nearestMountedAncestor.type.getDerivedStateFromError || "function"
=== typeof instance.componentDidCatch && (null === legacyErrorBoundariesThatAlreadyFailed || !
legacyErrorBoundariesThatAlreadyFailed.has(instance))) {
          sourceFiber = createCapturedValueAtFiber(error, sourceFiber);
          error = createClassErrorUpdate(2);
          instance = enqueueUpdate(nearestMountedAncestor, error, 2);
          null !== instance && (initializeClassErrorUpdate(error, instance, nearestMountedAncestor,
sourceFiber), markRootUpdated$1(instance, 2), ensureRootIsScheduled(instance));
          return;
```

```
          }
        }
        nearestMountedAncestor = nearestMountedAncestor.return;
      }
      console.error("Internal React error: Attempted to capture a commit phase error inside a detached tree. This indicates a bug in React. Potential causes include deleting the same fiber more than once, committing an already-finished tree, or an inconsistent return pointer.\n\nError message:\n\n%s", error);
    }
  }
  function attachPingListener(root, wakeable, lanes) {
    var pingCache = root.pingCache;
    if (null === pingCache) {
      pingCache = root.pingCache = new PossiblyWeakMap();
      var threadIDs = new Set();
      pingCache.set(wakeable, threadIDs);
    } else threadIDs = pingCache.get(wakeable), void 0 === threadIDs && (threadIDs = new Set(), pingCache.set(wakeable, threadIDs));
    threadIDs.has(lanes) || (workInProgressRootDidAttachPingListener = !0, threadIDs.add(lanes), pingCache = pingSuspendedRoot.bind(null, root, wakeable, lanes), isDevToolsPresent && restorePendingUpdaters(root, lanes), wakeable.then(pingCache, pingCache));
  }
  function pingSuspendedRoot(root, wakeable, pingedLanes) {
    var pingCache = root.pingCache;
    null !== pingCache && pingCache.delete(wakeable);
    root.pingedLanes |= root.suspendedLanes & pingedLanes;
    root.warmLanes &= ~pingedLanes;
    isConcurrentActEnvironment() && null === ReactSharedInternals.actQueue && console.error("A suspended resource finished loading inside a test, but the event was not wrapped in act(...).\n\nWhen testing, code that resolves suspended data should be wrapped into act(...):\n\nact(() => {\n  /* finish loading suspended data */\n});\n/* assert on the output */\n\nThis ensures that you're testing the behavior the user would see in the browser. Learn more at https://react.dev/link/wrap-tests-with-act");
    workInProgressRoot === root && (workInProgressRootRenderLanes & pingedLanes) === pingedLanes && (workInProgressRootExitStatus === RootSuspendedWithDelay || workInProgressRootExitStatus === RootSuspended && (workInProgressRootRenderLanes & 62914560) === workInProgressRootRenderLanes && now$1() - globalMostRecentFallbackTime < FALLBACK_THROTTLE_MS ? (executionContext & RenderContext) === NoContext && prepareFreshStack(root, 0) : workInProgressRootPingedLanes |= pingedLanes, workInProgressSuspendedRetryLanes === workInProgressRootRenderLanes && (workInProgressSuspendedRetryLanes = 0));
    ensureRootIsScheduled(root);
  }
  function retryTimedOutBoundary(boundaryFiber, retryLane) {
    0 === retryLane && (retryLane = claimNextRetryLane());
    boundaryFiber = enqueueConcurrentRenderForLane(boundaryFiber, retryLane);
    null !== boundaryFiber && (markRootUpdated$1(boundaryFiber, retryLane), ensureRootIsScheduled(boundaryFiber));
  }
  function retryDehydratedSuspenseBoundary(boundaryFiber) {
```

```
    var suspenseState = boundaryFiber.memoizedState,
      retryLane = 0;
    null !== suspenseState && (retryLane = suspenseState.retryLane);
    retryTimedOutBoundary(boundaryFiber, retryLane);
  }
  function resolveRetryWakeable(boundaryFiber, wakeable) {
    var retryLane = 0;
    switch (boundaryFiber.tag) {
      case 13:
        var retryCache = boundaryFiber.stateNode;
        var suspenseState = boundaryFiber.memoizedState;
        null !== suspenseState && (retryLane = suspenseState.retryLane);
        break;
      case 19:
        retryCache = boundaryFiber.stateNode;
        break;
      case 22:
        retryCache = boundaryFiber.stateNode._retryCache;
        break;
      default:
        throw Error("Pinged unknown suspense boundary type. This is probably a bug in React.");
    }
    null !== retryCache && retryCache.delete(wakeable);
    retryTimedOutBoundary(boundaryFiber, retryLane);
  }
  function recursivelyTraverseAndDoubleInvokeEffectsInDEV(root$jscomp$0, parentFiber,
isInStrictMode) {
    if (0 !== (parentFiber.subtreeFlags & 33562624)) for (parentFiber = parentFiber.child; null !==
parentFiber;) {
      var root = root$jscomp$0,
        fiber = parentFiber,
        isStrictModeFiber = fiber.type === REACT_STRICT_MODE_TYPE;
      isStrictModeFiber = isInStrictMode || isStrictModeFiber;
      22 !== fiber.tag ? fiber.flags & 33554432 ? isStrictModeFiber && runWithFiberInDEV(fiber,
doubleInvokeEffectsOnFiber, root, fiber, (fiber.mode & NoStrictPassiveEffectsMode) === NoMode) :
recursivelyTraverseAndDoubleInvokeEffectsInDEV(root, fiber, isStrictModeFiber) : null ===
fiber.memoizedState && (isStrictModeFiber && fiber.flags & 8192 ? runWithFiberInDEV(fiber,
doubleInvokeEffectsOnFiber, root, fiber) : fiber.subtreeFlags & 33554432 &&
runWithFiberInDEV(fiber, recursivelyTraverseAndDoubleInvokeEffectsInDEV, root, fiber,
isStrictModeFiber));
      parentFiber = parentFiber.sibling;
    }
  }
  function doubleInvokeEffectsOnFiber(root, fiber) {
    var shouldDoubleInvokePassiveEffects = 2 < arguments.length && void 0 !== arguments[2] ?
arguments[2] : !0;
    setIsStrictModeForDevtools(!0);
    try {
      disappearLayoutEffects(fiber), shouldDoubleInvokePassiveEffects &&
```

```
disconnectPassiveEffect(fiber), reappearLayoutEffects(root, fiber.alternate, fiber, !1),
shouldDoubleInvokePassiveEffects && reconnectPassiveEffects(root, fiber, 0, null, !1);
    } finally {
      setIsStrictModeForDevtools(!1);
    }
  }
  function commitDoubleInvokeEffectsInDEV(root) {
    var doubleInvokeEffects = !0;
    root.current.mode & (StrictLegacyMode | StrictEffectsMode) || (doubleInvokeEffects = !1);
    recursivelyTraverseAndDoubleInvokeEffectsInDEV(root, root.current, doubleInvokeEffects);
  }
  function warnAboutUpdateOnNotYetMountedFiberInDEV(fiber) {
    if ((executionContext & RenderContext) === NoContext) {
      var tag = fiber.tag;
      if (3 === tag || 1 === tag || 0 === tag || 11 === tag || 14 === tag || 15 === tag) {
        tag = getComponentNameFromFiber(fiber) || "ReactComponent";
        if (null !== didWarnStateUpdateForNotYetMountedComponent) {
          if (didWarnStateUpdateForNotYetMountedComponent.has(tag)) return;
          didWarnStateUpdateForNotYetMountedComponent.add(tag);
        } else didWarnStateUpdateForNotYetMountedComponent = new Set([tag]);
        runWithFiberInDEV(fiber, function () {
          console.error("Can't perform a React state update on a component that hasn't mounted yet. This
indicates that you have a side-effect in your render function that asynchronously later calls tries to
update the component. Move this work to useEffect instead.");
        });
      }
    }
  }
  function restorePendingUpdaters(root, lanes) {
    isDevToolsPresent && root.memoizedUpdaters.forEach(function (schedulingFiber) {
      addFiberToLanesMap(root, schedulingFiber, lanes);
    });
  }
  function scheduleCallback$1(priorityLevel, callback) {
    var actQueue = ReactSharedInternals.actQueue;
    return null !== actQueue ? (actQueue.push(callback), fakeActCallbackNode$1) :
scheduleCallback$3(priorityLevel, callback);
  }
  function warnIfUpdatesNotWrappedWithActDEV(fiber) {
    isConcurrentActEnvironment() && null === ReactSharedInternals.actQueue &&
runWithFiberInDEV(fiber, function () {
      console.error("An update to %s inside a test was not wrapped in act(...).\n\nWhen testing, code that
causes
 React state updates should be wrapped into act(...):\n\nact(() => {\n  /* fire events that update state
*/\n});\n/* assert on the output */\n\nThis ensures that you're testing the behavior the user would see in
the browser. Learn more at https://react.dev/link/wrap-tests-with-act",
getComponentNameFromFiber(fiber));
    });
  }
```

```
  function ensureRootIsScheduled(root) {
    root !== lastScheduledRoot && null === root.next && (null === lastScheduledRoot ?
firstScheduledRoot = lastScheduledRoot = root : lastScheduledRoot = lastScheduledRoot.next = root);
    mightHavePendingSyncWork = !0;
    null !== ReactSharedInternals.actQueue ? didScheduleMicrotask_act || (didScheduleMicrotask_act =
!0, scheduleImmediateTask(processRootScheduleInMicrotask)) : didScheduleMicrotask ||
(didScheduleMicrotask = !0, scheduleImmediateTask(processRootScheduleInMicrotask));
  }
  function flushSyncWorkAcrossRoots_impl(syncTransitionLanes, onlyLegacy) {
    if (!isFlushingWork && mightHavePendingSyncWork) {
      isFlushingWork = !0;
      do {
        var didPerformSomeWork = !1;
        for (var root = firstScheduledRoot; null !== root;) {
          if (!onlyLegacy) if (0 !== syncTransitionLanes) {
            var pendingLanes = root.pendingLanes;
            if (0 === pendingLanes) var nextLanes = 0;else {
              var suspendedLanes = root.suspendedLanes,
                pingedLanes = root.pingedLanes;
              nextLanes = (1 << 31 - clz32(42 | syncTransitionLanes) + 1) - 1;
              nextLanes &= pendingLanes & ~(suspendedLanes & ~pingedLanes);
              nextLanes = nextLanes & 201326677 ? nextLanes & 201326677 | 1 : nextLanes ? nextLanes |
2 : 0;
            }
            0 !== nextLanes && (didPerformSomeWork = !0, performSyncWorkOnRoot(root, nextLanes));
          } else nextLanes = workInProgressRootRenderLanes, nextLanes = getNextLanes(root, root ===
workInProgressRoot ? nextLanes : 0), 0 === (nextLanes & 3) || checkIfRootIsPrerendering(root,
nextLanes) || (didPerformSomeWork = !0, performSyncWorkOnRoot(root, nextLanes));
          root = root.next;
        }
      } while (didPerformSomeWork);
      isFlushingWork = !1;
    }
  }
  function processRootScheduleInMicrotask() {
    mightHavePendingSyncWork = didScheduleMicrotask_act = didScheduleMicrotask = !1;
    var syncTransitionLanes = 0;
    0 !== currentEventTransitionLane && (shouldAttemptEagerTransition() && (syncTransitionLanes
= currentEventTransitionLane), currentEventTransitionLane = 0);
    for (var currentTime = now$1(), prev = null, root = firstScheduledRoot; null !== root;) {
      var next = root.next,
        nextLanes = scheduleTaskForRootDuringMicrotask(root, currentTime);
      if (0 === nextLanes) root.next = null, null === prev ? firstScheduledRoot = next : prev.next = next,
null === next && (lastScheduledRoot = prev);else if (prev = root, 0 !== syncTransitionLanes || 0 !==
(nextLanes & 3)) mightHavePendingSyncWork = !0;
      root = next;
    }
    flushSyncWorkAcrossRoots_impl(syncTransitionLanes, !1);
  }
```

```
  function scheduleTaskForRootDuringMicrotask(root, currentTime) {
    for (var suspendedLanes = root.suspendedLanes, pingedLanes = root.pingedLanes, expirationTimes
= root.expirationTimes, lanes = root.pendingLanes & -62914561; 0 < lanes;) {
      var index = 31 - clz32(lanes),
        lane = 1 << index,
        expirationTime = expirationTimes[index];
      if (-1 === expirationTime) {
        if (0 === (lane & suspendedLanes) || 0 !== (lane & pingedLanes)) expirationTimes[index] =
computeExpirationTime(lane, currentTime);
      } else expirationTime <= currentTime && (root.expiredLanes |= lane);
      lanes &= ~lane;
    }
    currentTime = workInProgressRoot;
    suspendedLanes = workInProgressRootRenderLanes;
    suspendedLanes = getNextLanes(root, root === currentTime ? suspendedLanes : 0);
    pingedLanes = root.callbackNode;
    if (0 === suspendedLanes || root === currentTime && workInProgressSuspendedReason ===
SuspendedOnData || null !== root.cancelPendingCommit) return null !== pingedLanes &&
cancelCallback(pingedLanes), root.callbackNode = null, root.callbackPriority = 0;
    if (0 === (suspendedLanes & 3) || checkIfRootIsPrerendering(root, suspendedLanes)) {
      currentTime = suspendedLanes & -suspendedLanes;
      if (currentTime !== root.callbackPriority || null !== ReactSharedInternals.actQueue &&
pingedLanes !== fakeActCallbackNode) cancelCallback(pingedLanes);else return currentTime;
      switch (lanesToEventPriority(suspendedLanes)) {
        case DiscreteEventPriority:
        case ContinuousEventPriority:
          suspendedLanes = UserBlockingPriority;
          break;
        case DefaultEventPriority:
          suspendedLanes = NormalPriority$1;
          break;
        case IdleEventPriority:
          suspendedLanes = IdlePriority;
          break;
        default:
          suspendedLanes = NormalPriority$1;
      }
      pingedLanes = performWorkOnRootViaSchedulerTask.bind(null, root);
      null !== ReactSharedInternals.actQueue ? (ReactSharedInternals.actQueue.push(pingedLanes),
suspendedLanes = fakeActCallbackNode) : suspendedLanes = scheduleCallback$3(suspendedLanes,
pingedLanes);
      root.callbackPriority = currentTime;
      root.callbackNode = suspendedLanes;
      return currentTime;
    }
    null !== pingedLanes && cancelCallback(pingedLanes);
    root.callbackPriority = 2;
    root.callbackNode = null;
    return 2;
```

```
  }
  function performWorkOnRootViaSchedulerTask(root, didTimeout) {
    nestedUpdateScheduled = currentUpdateIsNested = !1;
    var originalCallbackNode = root.callbackNode;
    if (flushPassiveEffects() && root.callbackNode !== originalCallbackNode) return null;
    var workInProgressRootRenderLanes$jscomp$0 = workInProgressRootRenderLanes;
    workInProgressRootRenderLanes$jscomp$0 = getNextLanes(root, root === workInProgressRoot ?
workInProgressRootRenderLanes$jscomp$0 : 0);
    if (0 === workInProgressRootRenderLanes$jscomp$0) return null;
    performWorkOnRoot(root, workInProgressRootRenderLanes$jscomp$0, didTimeout);
    scheduleTaskForRootDuringMicrotask(root, now$1());
    return null != root.callbackNode && root.callbackNode === originalCallbackNode ?
performWorkOnRootViaSchedulerTask.bind(null, root) : null;
  }
  function performSyncWorkOnRoot(root, lanes) {
    if (flushPassiveEffects()) return null;
    currentUpdateIsNested = nestedUpdateScheduled;
    nestedUpdateScheduled = !1;
    performWorkOnRoot(root, lanes, !0);
  }
  function cancelCallback(callbackNode) {
    callbackNode !== fakeActCallbackNode && null !== callbackNode &&
cancelCallback$1(callbackNode);
  }
  function scheduleImmediateTask(cb) {
    null !== ReactSharedInternals.actQueue && ReactSharedInternals.actQueue.push(function () {
      cb();
      return null;
    });
    scheduleMicrotask(function () {
      (executionContext & (RenderContext | CommitContext)) !== NoContext ?
scheduleCallback$3(ImmediatePriority, cb) : cb();
    });
  }
  function requestTransitionLane() {
    0 === currentEventTransitionLane && (currentEventTransitionLane = claimNextTransitionLane());
    return currentEventTransitionLane;
  }
  function coerceFormActionProp(actionProp) {
    if (null == actionProp || "symbol" === typeof actionProp || "boolean" === typeof actionProp) return
null;
    if ("function" === typeof actionProp) return actionProp;
    checkAttributeStringCoercion(actionProp, "action");
    return sanitizeURL("" + actionProp);
  }
  function createFormDataWithSubmitter(form, submitter) {
    var temp = submitter.ownerDocument.createElement("input");
    temp.name = submitter.name;
    temp.value = submitter.value;
```

```
    form.id && temp.setAttribute("form", form.id);
    submitter.parentNode.insertBefore(temp, submitter);
    form = new FormData(form);
    temp.parentNode.removeChild(temp);
    return form;
  }
  function extractEvents$1(dispatchQueue, domEventName, maybeTargetInst, nativeEvent,
nativeEventTarget) {
    if ("submit" === domEventName && maybeTargetInst && maybeTargetInst.stateNode ===
nativeEventTarget) {
      var action = coerceFormActionProp((nativeEventTarget[internalPropsKey] || null).action),
        submitter = nativeEvent.submitter;
      submitter && (domEventName = (domEventName = submitter[internalPropsKey] || null) ?
coerceFormActionProp(domEventName.formAction) : submitter.getAttribute("formAction"), null !==
domEventName && (action = domEventName, submitter = null));
      var event = new SyntheticEvent("action", "action", null, nativeEvent, nativeEventTarget);
      dispatchQueue.push({
        event: event,
        listeners: [{
          instance: null,
          listener: function () {
            if (nativeEvent.defaultPrevented) {
              if (0 !== currentEventTransitionLane) {
                var formData = submitter ? createFormDataWithSubmitter(nativeEventTarget, submitter) :
new FormData(nativeEventTarget),
                  pendingState = {
                    pending: !0,
                    data: formData,
                    method: nativeEventTarget.method,
                    action: action
                  };
                Object.freeze(pendingState);
                startHostTransition(maybeTargetInst, pendingState, null, formData);
              }
            } else "function" === typeof action && (event.preventDefault(), formData = submitter ?
createFormDataWithSubmitter(nativeEventTarget, submitter) : new FormData(nativeEventTarget),
pendingState = {
              pending: !0,
              data: formData,
              method: nativeEventTarget.method,
              action: action
            }, Object.freeze(pendingState), startHostTransition(maybeTargetInst, pendingState, action,
formData));
          },
          currentTarget: nativeEventTarget
        }]
      });
    }
  }
```

```
  function processDispatchQueue(dispatchQueue, eventSystemFlags) {

    eventSystemFlags = 0 !== (eventSystemFlags & 4);
    for (var i = 0; i < dispatchQueue.length; i++) {
      var _dispatchQueue$i = dispatchQueue[i];
      a: {
        var previousInstance = void 0,
          event = _dispatchQueue$i.event;
        _dispatchQueue$i = _dispatchQueue$i.listeners;
        if (eventSystemFlags) for (var i$jscomp$0 = _dispatchQueue$i.length - 1; 0 <= i$jscomp$0;
i$jscomp$0--) {
          var _dispatchListeners$i = _dispatchQueue$i[i$jscomp$0],
            instance = _dispatchListeners$i.instance,
            currentTarget = _dispatchListeners$i.currentTarget;
          _dispatchListeners$i = _dispatchListeners$i.listener;
          if (instance !== previousInstance && event.isPropagationStopped()) break a;
          previousInstance = event;
          previousInstance.currentTarget = currentTarget;
          try {
            _dispatchListeners$i(previousInstance);
          } catch (error) {
            reportGlobalError(error);
          }
          previousInstance.currentTarget = null;
          previousInstance = instance;
        } else for (i$jscomp$0 = 0; i$jscomp$0 < _dispatchQueue$i.length; i$jscomp$0++) {
          _dispatchListeners$i = _dispatchQueue$i[i$jscomp$0];
          instance = _dispatchListeners$i.instance;
          currentTarget = _dispatchListeners$i.currentTarget;
          _dispatchListeners$i = _dispatchListeners$i.listener;
          if (instance !== previousInstance && event.isPropagationStopped()) break a;
          previousInstance = event;
          previousInstance.currentTarget = currentTarget;
          try {
            _dispatchListeners$i(previousInstance);
          } catch (error) {
            reportGlobalError(error);
          }
          previousInstance.currentTarget = null;
          previousInstance = instance;
        }
      }
    }
  }
  function listenToNonDelegatedEvent(domEventName, targetElement) {
    nonDelegatedEvents.has(domEventName) || console.error('Did not expect a
listenToNonDelegatedEvent() call for "%s". This is a bug in React. Please file an issue.',
domEventName);
    var listenerSet = targetElement[internalEventHandlersKey];
```

```
    void 0 === listenerSet && (listenerSet = targetElement[internalEventHandlersKey] = new Set());
    var listenerSetKey = domEventName + "__bubble";
    listenerSet.has(listenerSetKey) || (addTrappedEventListener(targetElement, domEventName, 2, !1),
listenerSet.add(listenerSetKey));
  }
  function listenToNativeEvent(domEventName, isCapturePhaseListener, target) {
    nonDelegatedEvents.has(domEventName) && !isCapturePhaseListener && console.error('Did not
expect a listenToNativeEvent() call for "%s" in the bubble phase. This is a bug in React. Please file an
issue.', domEventName);
    var eventSystemFlags = 0;
    isCapturePhaseListener && (eventSystemFlags |= 4);
    addTrappedEventListener(target, domEventName, eventSystemFlags, isCapturePhaseListener);
  }
  function listenToAllSupportedEvents(rootContainerElement) {
    if (!rootContainerElement[listeningMarker]) {
      rootContainerElement[listeningMarker] = !0;
      allNativeEvents.forEach(function (domEventName) {
        "selectionchange" !== domEventName && (nonDelegatedEvents.has(domEventName) ||
listenToNativeEvent(domEventName, !1, rootContainerElement),
listenToNativeEvent(domEventName, !0, rootContainerElement));
      });
      var ownerDocument = 9 === rootContainerElement.nodeType ? rootContainerElement :
rootContainerElement.ownerDocument;
      null === ownerDocument || ownerDocument[listeningMarker] || (ownerDocument[listeningMarker]
= !0, listenToNativeEvent("selectionchange", !1, ownerDocument));
    }
  }
  function addTrappedEventListener(targetContainer, domEventName, eventSystemFlags,
isCapturePhaseListener) {
    switch (getEventPriority(domEventName)) {
      case DiscreteEventPriority:
        var listenerWrapper = dispatchDiscreteEvent;
        break;
      case ContinuousEventPriority:
        listenerWrapper = dispatchContinuousEvent;
        break;
      default:
        listenerWrapper = dispatchEvent;
    }
    eventSystemFlags = listenerWrapper.bind(null, domEventName, eventSystemFlags,
targetContainer);
    listenerWrapper = void 0;
    !passiveBrowserEventsSupported || "touchstart" !== domEventName && "touchmove" !==
domEventName && "wheel" !== domEventName || (listenerWrapper = !0);
    isCapturePhaseListener ? void 0 !== listenerWrapper ?
targetContainer.addEventListener(domEventName, eventSystemFlags, {
      capture: !0,
      passive: listenerWrapper
    }) : targetContainer.addEventListener(domEventName, eventSystemFlags, !0) : void 0 !==
```

```
listenerWrapper ? targetContainer.addEventListener(domEventName, eventSystemFlags, {
      passive: listenerWrapper
    }) : targetContainer.addEventListener(domEventName, eventSystemFlags, !1);
  }
  function dispatchEventForPluginEventSystem(domEventName, eventSystemFlags, nativeEvent,
targetInst$jscomp$0, targetContainer) {
    var ancestorInst = targetInst$jscomp$0;
    if (0 === (eventSystemFlags & 1) && 0 === (eventSystemFlags & 2) && null !==
targetInst$jscomp$0) a: for (;;) {
      if (null === targetInst$jscomp$0) return;
      var nodeTag = targetInst$jscomp$0.tag;
      if (3 === nodeTag || 4 === nodeTag) {
        var container = targetInst$jscomp$0.stateNode.containerInfo;
        if (container === targetContainer || 8 === container.nodeType && container.parentNode ===
targetContainer) break;
        if (4 === nodeTag) for (nodeTag = targetInst$jscomp$0.return; null !== nodeTag;) {
          var grandTag = nodeTag.tag;
          if (3 === grandTag || 4 === grandTag) if (grandTag = nodeTag.stateNode.containerInfo,
grandTag === targetContainer || 8 === grandTag.nodeType && grandTag.parentNode ===
targetContainer) return;
          nodeTag = nodeTag.return;
        }
        for (; null !== container;) {
          nodeTag = getClosestInstanceFromNode(container);
          if (null === nodeTag) return;
          grandTag = nodeTag.tag;
          if (5 === grandTag || 6 === grandTag || 26 === grandTag || 27 === grandTag) {
            targetInst$jscomp$0 = ancestorInst = nodeTag;
            continue a;
          }
          container = container.parentNode;
        }
      }
      targetInst$jscomp$0 = targetInst$jscomp$0.return;
    }
    batchedUpdates$1(function () {
      var targetInst = ancestorInst,
        nativeEventTarget = getEventTarget(nativeEvent),
        dispatchQueue = [];
      a: {
        var reactName = topLevelEventsToReactNames.get(domEventName);
        if (void 0 !== reactName) {
          var SyntheticEventCtor = SyntheticEvent,
            reactEventType = domEventName;
          switch (domEventName) {
            case "keypress":
              if (0 === getEventCharCode(nativeEvent)) break a;
            case "keydown":
            case "keyup":
```

```
  SyntheticEventCtor = SyntheticKeyboardEvent;
  break;
case "focusin":
  reactEventType = "focus";
  SyntheticEventCtor = SyntheticFocusEvent;
  break;
case "focusout":
  reactEventType = "blur";
  SyntheticEventCtor = SyntheticFocusEvent;
  break;
case "beforeblur":
case "afterblur":
  SyntheticEventCtor = SyntheticFocusEvent;
  break;
case "click":
  if (2 === nativeEvent.button) break a;
case "auxclick":
case "dblclick":
case "mousedown":
case "mousemove":
case "mouseup":
case "mouseout":
case "mouseover":
case "contextmenu":
  SyntheticEventCtor = SyntheticMouseEvent;
  break;
case "drag":
case "dragend":
case "dragenter":
case "dragexit":
case "dragleave":
case "dragover":
case "dragstart":
case "drop":
  SyntheticEventCtor = SyntheticDragEvent;
  break;
case "touchcancel":
case "touchend":
case "touchmove":
case "touchstart":
  SyntheticEventCtor = SyntheticTouchEvent;
  break;
case ANIMATION_END:
case ANIMATION_ITERATION:
case ANIMATION_START:
  SyntheticEventCtor = SyntheticAnimationEvent;
  break;
case TRANSITION_END:
  SyntheticEventCtor = SyntheticTransitionEvent;
```

```
            break;
          case "scroll":
          case "scrollend":
            SyntheticEventCtor = SyntheticUIEvent;
            break;
          case "wheel":
            SyntheticEventCtor = SyntheticWheelEvent;
            break;
          case "copy":
          case "cut":
          case "paste":
            SyntheticEventCtor = SyntheticClipboardEvent;
            break;
          case "gotpointercapture":
          case "lostpointercapture":
          case "pointercancel":
          case "pointerdown":
          case "pointermove":
          case "pointerout":
          case "pointerover":
          case "pointerup":
            SyntheticEventCtor = SyntheticPointerEvent;
            break;
          case "toggle":
          case "beforetoggle":
            SyntheticEventCtor = SyntheticToggleEvent;
        }
        var inCapturePhase = 0 !== (eventSystemFlags & 4),
          accumulateTargetOnly = !inCapturePhase && ("scroll" === domEventName || "scrollend" ===
domEventName),
          reactEventName = inCapturePhase ? null !== reactName ? reactName + "Capture" : null :
reactName;
        inCapturePhase = [];
        for (var instance = targetInst, lastHostComponent; null !== instance;) {
          var _instance2 = instance;
          lastHostComponent
 = _instance2.stateNode;
          _instance2 = _instance2.tag;
          5 !== _instance2 && 26 !== _instance2 && 27 !== _instance2 || null === lastHostComponent
|| null === reactEventName || (_instance2 = getListener(instance, reactEventName), null != _instance2
&& inCapturePhase.push(createDispatchListener(instance, _instance2, lastHostComponent)));
          if (accumulateTargetOnly) break;
          instance = instance.return;
        }
        0 < inCapturePhase.length && (reactName = new SyntheticEventCtor(reactName,
reactEventType, null, nativeEvent, nativeEventTarget), dispatchQueue.push({
          event: reactName,
          listeners: inCapturePhase
        }));
```

```
      }
    }
    if (0 === (eventSystemFlags & 7)) {
      a: {
        reactName = "mouseover" === domEventName || "pointerover" === domEventName;
        SyntheticEventCtor = "mouseout" === domEventName || "pointerout" === domEventName;
        if (reactName && nativeEvent !== currentReplayingEvent && (reactEventType =
nativeEvent.relatedTarget || nativeEvent.fromElement) &&
(getClosestInstanceFromNode(reactEventType) || reactEventType[internalContainerInstanceKey]))
break a;
        if (SyntheticEventCtor || reactName) {
          reactName = nativeEventTarget.window === nativeEventTarget ? nativeEventTarget :
(reactName = nativeEventTarget.ownerDocument) ? reactName.defaultView ||
reactName.parentWindow : window;
          if (SyntheticEventCtor) {
            if (reactEventType = nativeEvent.relatedTarget || nativeEvent.toElement, SyntheticEventCtor =
targetInst, reactEventType = reactEventType ? getClosestInstanceFromNode(reactEventType) : null,
null !== reactEventType && (accumulateTargetOnly = getNearestMountedFiber(reactEventType),
inCapturePhase = reactEventType.tag, reactEventType !== accumulateTargetOnly || 5 !==
inCapturePhase && 27 !== inCapturePhase && 6 !== inCapturePhase)) reactEventType = null;
          } else SyntheticEventCtor = null, reactEventType = targetInst;
          if (SyntheticEventCtor !== reactEventType) {
            inCapturePhase = SyntheticMouseEvent;
            _instance2 = "onMouseLeave";
            reactEventName = "onMouseEnter";
            instance = "mouse";
            if ("pointerout" === domEventName || "pointerover" === domEventName) inCapturePhase =
SyntheticPointerEvent, _instance2 = "onPointerLeave", reactEventName = "onPointerEnter", instance
= "pointer";
            accumulateTargetOnly = null == SyntheticEventCtor ? reactName :
getNodeFromInstance(SyntheticEventCtor);
            lastHostComponent = null == reactEventType ? reactName :
getNodeFromInstance(reactEventType);
            reactName = new inCapturePhase(_instance2, instance + "leave", SyntheticEventCtor,
nativeEvent, nativeEventTarget);
            reactName.target = accumulateTargetOnly;
            reactName.relatedTarget = lastHostComponent;
            _instance2 = null;
            getClosestInstanceFromNode(nativeEventTarget) === targetInst && (inCapturePhase = new
inCapturePhase(reactEventName, instance + "enter", reactEventType, nativeEvent, nativeEventTarget),
inCapturePhase.target = lastHostComponent, inCapturePhase.relatedTarget = accumulateTargetOnly,
_instance2 = inCapturePhase);
            accumulateTargetOnly = _instance2;
            if (SyntheticEventCtor && reactEventType) b: {
              inCapturePhase = SyntheticEventCtor;
              reactEventName = reactEventType;
              instance = 0;
              for (lastHostComponent = inCapturePhase; lastHostComponent; lastHostComponent =
getParent(lastHostComponent)) instance++;
```

```
            lastHostComponent = 0;
            for (_instance2 = reactEventName; _instance2; _instance2 = getParent(_instance2))
lastHostComponent++;
            for (; 0 < instance - lastHostComponent;) inCapturePhase = getParent(inCapturePhase),
instance--;
            for (; 0 < lastHostComponent - instance;) reactEventName = getParent(reactEventName),
lastHostComponent--;
            for (; instance--;) {
              if (inCapturePhase === reactEventName || null !== reactEventName && inCapturePhase
=== reactEventName.alternate) break b;
              inCapturePhase = getParent(inCapturePhase);
              reactEventName = getParent(reactEventName);
            }
            inCapturePhase = null;
          } else inCapturePhase = null;
          null !== SyntheticEventCtor && accumulateEnterLeaveListenersForEvent(dispatchQueue,
reactName, SyntheticEventCtor, inCapturePhase, !1);
          null !== reactEventType && null !== accumulateTargetOnly &&
accumulateEnterLeaveListenersForEvent(dispatchQueue, accumulateTargetOnly, reactEventType,
inCapturePhase, !0);
        }
      }
    }
    a: {
      reactName = targetInst ? getNodeFromInstance(targetInst) : window;
      SyntheticEventCtor = reactName.nodeName && reactName.nodeName.toLowerCase();
      if ("select" === SyntheticEventCtor || "input" === SyntheticEventCtor && "file" ===
reactName.type) var getTargetInstFunc = getTargetInstForChangeEvent;else if
(isTextInputElement(reactName)) {
        if (isInputEventSupported) getTargetInstFunc = getTargetInstForInputOrChangeEvent;else {
          getTargetInstFunc = getTargetInstForInputEventPolyfill;
          var handleEventFunc = handleEventsForInputEventPolyfill;
        }
      } else SyntheticEventCtor = reactName.nodeName, !SyntheticEventCtor || "input" !==
SyntheticEventCtor.toLowerCase() || "checkbox" !== reactName.type && "radio" !==
reactName.type ? targetInst && isCustomElement(targetInst.elementType) && (getTargetInstFunc =
getTargetInstForChangeEvent) : getTargetInstFunc = getTargetInstForClickEvent;
      if (getTargetInstFunc && (getTargetInstFunc = getTargetInstFunc(domEventName, targetInst)))
{
        createAndAccumulateChangeEvent(dispatchQueue, getTargetInstFunc, nativeEvent,
nativeEventTarget);
        break a;
      }
      handleEventFunc && handleEventFunc(domEventName, reactName, targetInst);
      "focusout" === domEventName && targetInst && "number" === reactName.type && null !=
targetInst.memoizedProps.value && setDefaultValue(reactName, "number", reactName.value);
    }
    handleEventFunc = targetInst ? getNodeFromInstance(targetInst) : window;
    switch (domEventName) {
```

```
        case "focusin":
          if (isTextInputElement(handleEventFunc) || "true" === handleEventFunc.contentEditable)
activeElement = handleEventFunc, activeElementInst = targetInst, lastSelection = null;
          break;
        case "focusout":
          lastSelection = activeElementInst = activeElement = null;
          break;
        case "mousedown":
          mouseDown = !0;
          break;
        case "contextmenu":
        case "mouseup":
        case "dragend":
          mouseDown = !1;
          constructSelectEvent(dispatchQueue, nativeEvent, nativeEventTarget);
          break;
        case "selectionchange":
          if (skipSelectionChangeEvent) break;
        case "keydown":
        case "keyup":
          constructSelectEvent(dispatchQueue, nativeEvent, nativeEventTarget);
      }
      var fallbackData;
      if (canUseCompositionEvent) b: {
        switch (domEventName) {
          case "compositionstart":
            var eventType = "onCompositionStart";
            break b;
          case "compositionend":
            eventType = "onCompositionEnd";
            break b;
          case "compositionupdate":
            eventType = "onCompositionUpdate";
            break b;
        }
        eventType = void 0;
      } else isComposing ? isFallbackCompositionEnd(domEventName, nativeEvent) && (eventType =
"onCompositionEnd") : "keydown" === domEventName && nativeEvent.keyCode ===
START_KEYCODE && (eventType = "onCompositionStart");
      eventType && (useFallbackCompositionData && "ko" !== nativeEvent.locale && (isComposing
|| "onCompositionStart" !== eventType ? "onCompositionEnd" === eventType && isComposing &&
(fallbackData = getData()) : (root = nativeEventTarget, startText = "value" in root ? root.value :
root.textContent, isComposing = !0)), handleEventFunc = accumulateTwoPhaseListeners(targetInst,
eventType), 0 < handleEventFunc.length && (eventType = new
SyntheticCompositionEvent(eventType, domEventName, null, nativeEvent, nativeEventTarget),
dispatchQueue.push({
        event: eventType,
        listeners: handleEventFunc
      }), fallbackData ? eventType.data = fallbackData : (fallbackData =
```

```
getDataFromCustomEvent(nativeEvent), null !== fallbackData && (eventType.data = fallbackData))));
        if (fallbackData = canUseTextInputEvent ? getNativeBeforeInputChars(domEventName,
nativeEvent) : getFallbackBeforeInputChars(domEventName, nativeEvent)) eventType =
accumulateTwoPhaseListeners(targetInst, "onBeforeInput"), 0 < eventType.length &&
(handleEventFunc = new SyntheticInputEvent("onBeforeInput", "beforeinput", null, nativeEvent,
nativeEventTarget), dispatchQueue.push({
          event: handleEventFunc,
          listeners: eventType
        }), handleEventFunc.data = fallbackData);
        extractEvents$1(dispatchQueue, domEventName, targetInst, nativeEvent, nativeEventTarget);
      }
      processDispatchQueue(dispatchQueue, eventSystemFlags);
    });
  }
  function createDispatchListener(instance, listener, currentTarget) {
    return {
      instance: instance,
      listener: listener,
      currentTarget: currentTarget
    };
  }
  function accumulateTwoPhaseListeners(targetFiber, reactName) {
    for (var captureName = reactName + "Capture", listeners = []; null !== targetFiber;) {
      var _instance3 = targetFiber,
        stateNode = _instance3.stateNode;

      _instance3 = _instance3.tag;
      5 !== _instance3 && 26 !== _instance3 && 27 !== _instance3 || null === stateNode || (_instance3
= getListener(targetFiber, captureName), null != _instance3 &&
listeners.unshift(createDispatchListener(targetFiber, _instance3, stateNode)), _instance3 =
getListener(targetFiber, reactName), null != _instance3 &&
listeners.push(createDispatchListener(targetFiber, _instance3, stateNode)));
      targetFiber = targetFiber.return;
    }
    return listeners;
  }
  function getParent(inst) {
    if (null === inst) return null;
    do inst = inst.return; while (inst && 5 !== inst.tag && 27 !== inst.tag);
    return inst ? inst : null;
  }
  function accumulateEnterLeaveListenersForEvent(dispatchQueue, event, target, common,
inCapturePhase) {
    for (var registrationName = event._reactName, listeners = []; null !== target && target !==
common;) {
      var _instance4 = target,
        alternate = _instance4.alternate,
        stateNode = _instance4.stateNode;
      _instance4 = _instance4.tag;
```

```
      if (null !== alternate && alternate === common) break;
      5 !== _instance4 && 26 !== _instance4 && 27 !== _instance4 || null === stateNode || (alternate =
stateNode, inCapturePhase ? (stateNode = getListener(target, registrationName), null != stateNode &&
listeners.unshift(createDispatchListener(target, stateNode, alternate))) : inCapturePhase || (stateNode =
getListener(target, registrationName), null != stateNode &&
listeners.push(createDispatchListener(target, stateNode, alternate))));
      target = target.return;
    }
    0 !== listeners.length && dispatchQueue.push({
      event: event,
      listeners: listeners
    });
  }
  function validatePropertiesInDevelopment(type, props) {
    validateProperties$2(type, props);
    "input" !== type && "textarea" !== type && "select" !== type || null == props || null !== props.value
|| didWarnValueNull || (didWarnValueNull = !0, "select" === type && props.multiple ?
console.error("`value` prop on `%s` should not be null. Consider using an empty array when `multiple`
is set to `true` to clear the component or `undefined` for uncontrolled components.", type) :
console.error("`value` prop on `%s` should not be null. Consider using an empty string to clear the
component or `undefined` for uncontrolled components.", type));
    var eventRegistry = {
      registrationNameDependencies: registrationNameDependencies,
      possibleRegistrationNames: possibleRegistrationNames
    };
    isCustomElement(type) || "string" === typeof props.is || warnUnknownProperties(type, props,
eventRegistry);
    props.contentEditable && !props.suppressContentEditableWarning && null != props.children &&
console.error("A component is `contentEditable` and contains `children` managed by React. It is now
your responsibility to guarantee that none of those nodes are unexpectedly modified or duplicated. This
is probably not intentional.");
  }
  function warnForPropDifference(propName, serverValue, clientValue, serverDifferences) {
    serverValue !== clientValue && (clientValue = normalizeMarkupForTextOrAttribute(clientValue),
normalizeMarkupForTextOrAttribute(serverValue) !== clientValue && (serverDifferences[propName]
= serverValue));
  }
  function warnForExtraAttributes(domElement, attributeNames, serverDifferences) {
    attributeNames.forEach(function (attributeName) {
      serverDifferences[getPropNameFromAttributeName(attributeName)] = "style" ===
attributeName ? getStylesObjectFromElement(domElement) :
domElement.getAttribute(attributeName);
    });
  }
  function warnForInvalidEventListener(registrationName, listener) {
    !1 === listener ? console.error("Expected `%s` listener to be a function, instead got `false`.\n\nIf you
used to conditionally omit it with %s={condition && value}, pass %s={condition ? value : undefined}
instead.", registrationName, registrationName, registrationName) : console.error("Expected `%s`
listener to be a function, instead got a value of `%s` type.", registrationName, typeof listener);
```

```
  }
  function normalizeHTML(parent, html) {
    parent = parent.namespaceURI === MATH_NAMESPACE || parent.namespaceURI ===
SVG_NAMESPACE ? parent.ownerDocument.createElementNS(parent.namespaceURI,
parent.tagName) : parent.ownerDocument.createElement(parent.tagName);
    parent.innerHTML = html;
    return parent.innerHTML;
  }
  function normalizeMarkupForTextOrAttribute(markup) {
    willCoercionThrow(markup) && (console.error("The provided HTML markup uses a value of
unsupported type %s. This value must be coerced to a string before using it here.",
typeName(markup)), testStringCoercion(markup));
    return ("string" === typeof markup ? markup : "" +
markup).replace(NORMALIZE_NEWLINES_REGEX,
"\n").replace(NORMALIZE_NULL_AND_REPLACEMENT_REGEX, "");
  }
  function checkForUnmatchedText(serverText, clientText) {
    clientText = normalizeMarkupForTextOrAttribute(clientText);
    return normalizeMarkupForTextOrAttribute(serverText) === clientText ? !0 : !1;
  }
  function noop$1() {}
  function setProp(domElement, tag, key, value, props, prevValue) {
    switch (key) {
      case "children":
        if ("string" === typeof value) validateTextNesting(value, tag), "body" === tag || "textarea" ===
tag && "" === value || setTextContent(domElement, value);else if ("number" === typeof value ||
"bigint" === typeof value) validateTextNesting("" + value, tag), "body" !== tag &&
setTextContent(domElement, "" + value);
        break;
      case "className":
        setValueForKnownAttribute(domElement, "class", value);
        break;
      case "tabIndex":
        setValueForKnownAttribute(domElement, "tabindex", value);
        break;
      case "dir":
      case "role":
      case "viewBox":
      case "width":
      case "height":
        setValueForKnownAttribute(domElement, key, value);
        break;
      case "style":
        setValueForStyles(domElement, value, prevValue);
        break;
      case "data":
        if ("object" !== tag) {
          setValueForKnownAttribute(domElement, "data", value);
          break;
```

```
      }
    case "src":
    case "href":
      if ("" === value && ("a" !== tag || "href" !== key)) {
        "src" === key ? console.error('An empty string ("") was passed to the %s attribute. This may cause the browser to download the whole page again over the network. To fix this, either do not render the element at all or pass null to %s instead of an empty string.', key, key) : console.error('An empty string ("") was passed to the %s attribute. To fix this, either do not render the element at all or pass null to %s instead of an empty string.', key, key);
        domElement.removeAttribute(key);
        break;
      }
      if (null == value || "function" === typeof value || "symbol" === typeof value || "boolean" === typeof value) {
        domElement.removeAttribute(key);
        break;
      }
      checkAttributeStringCoercion(value, key);
      value = sanitizeURL("" + value);
      domElement.setAttribute(key, value);
      break;
    case "action":
    case "formAction":
      null != value && ("form" === tag ? "formAction" === key ? console.error("You can only pass the formAction prop to <input> or <button>. Use the action prop on <form>.") : "function" === typeof value && (null == props.encType && null == props.method || didWarnFormActionMethod || (didWarnFormActionMethod = !0, console.error("Cannot specify a encType or method for a form that specifies a function as the action. React provides those automatically. They will get overridden.")), null == props.target || didWarnFormActionTarget || (didWarnFormActionTarget = !0, console.error("Cannot specify a target for a form that specifies a function as the action. The function will always be executed in the same window."))) : "input" === tag || "button" === tag ? "action" === key ? console.error("You can only pass the action prop to <form>. Use the formAction prop on <input> or <button>.") : "input" !== tag || "submit" === props.type || "image" === props.type || didWarnFormActionType ? "button" !== tag || null == props.type || "submit" === props.type || didWarnFormActionType ? "function" === typeof value && (null == props.name || didWarnFormActionName || (didWarnFormActionName = !0, console.error('Cannot specify a "name" prop for a button that specifies a function as a formAction. React needs it to encode which action should be invoked. It will get overridden.')), null == props.formEncType && null == props.formMethod || didWarnFormActionMethod || (didWarnFormActionMethod = !0, console.error("Cannot specify a formEncType or formMethod for a button that specifies a function as a formAction. React provides those automatically. They will get overridden.")), null == props.formTarget || didWarnFormActionTarget || (didWarnFormActionTarget = !0, console.error("Cannot specify a formTarget for a button that specifies a function as a formAction. The function will always be executed in the same window."))) : (didWarnFormActionType = !0, console.error('A button can only specify a formAction along with type="submit" or no type.')) : (didWarnFormActionType = !0, console.error('An input can only specify a formAction along with type="submit" or type="image".')) : "action" === key ? console.error("You can only pass the action prop to <form>.") : console.error("You can only pass the formAction prop to <input> or <button>."));
      if ("function" === typeof value) {
        domElement.setAttribute(key, "javascript:throw new Error('A React form was unexpectedly
```

```
submitted. If you called form.submit() manually, consider using form.requestSubmit() instead. If
you\\'re trying to use event.stopPropagation() in a submit event handler, consider also calling
event.preventDefault().')");
          break;
        } else "function" === typeof prevValue && ("formAction"
 === key ? ("input" !== tag && setProp(domElement, tag, "name", props.name, props, null),
setProp(domElement, tag, "formEncType", props.formEncType, props, null), setProp(domElement, tag,
"formMethod", props.formMethod, props, null), setProp(domElement, tag, "formTarget",
props.formTarget, props, null)) : (setProp(domElement, tag, "encType", props.encType, props, null),
setProp(domElement, tag, "method", props.method, props, null), setProp(domElement, tag, "target",
props.target, props, null)));
        if (null == value || "symbol" === typeof value || "boolean" === typeof value) {
          domElement.removeAttribute(key);
          break;
        }
        checkAttributeStringCoercion(value, key);
        value = sanitizeURL("" + value);
        domElement.setAttribute(key, value);
        break;
      case "onClick":
        null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
domElement.onclick = noop$1);
        break;
      case "onScroll":
        null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
listenToNonDelegatedEvent("scroll", domElement));
        break;
      case "onScrollEnd":
        null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
listenToNonDelegatedEvent("scrollend", domElement));
        break;
      case "dangerouslySetInnerHTML":
        if (null != value) {
          if ("object" !== typeof value || !("__html" in value)) throw
Error("`props.dangerouslySetInnerHTML` must be in the form `{__html: ...}`. Please visit
https://react.dev/link/dangerously-set-inner-html for more information.");
          key = value.__html;
          if (null != key) {
            if (null != props.children) throw Error("Can only set one of `children` or
`props.dangerouslySetInnerHTML`.");
            domElement.innerHTML = key;
          }
        }
        break;
      case "multiple":
        domElement.multiple = value && "function" !== typeof value && "symbol" !== typeof value;
        break;
      case "muted":
        domElement.muted = value && "function" !== typeof value && "symbol" !== typeof value;
```

```
      break;
    case "suppressContentEditableWarning":
    case "suppressHydrationWarning":
    case "defaultValue":
    case "defaultChecked":
    case "innerHTML":
    case "ref":
      break;
    case "autoFocus":
      break;
    case "xlinkHref":
      if (null == value || "function" === typeof value || "boolean" === typeof value || "symbol" ===
typeof value) {
        domElement.removeAttribute("xlink:href");
        break;
      }
      checkAttributeStringCoercion(value, key);
      key = sanitizeURL("" + value);
      domElement.setAttributeNS(xlinkNamespace, "xlink:href", key);
      break;
    case "contentEditable":
    case "spellCheck":
    case "draggable":
    case "value":
    case "autoReverse":
    case "externalResourcesRequired":
    case "focusable":
    case "preserveAlpha":
      null != value && "function" !== typeof value && "symbol" !== typeof value ?
(checkAttributeStringCoercion(value, key), domElement.setAttribute(key, "" + value)) :
domElement.removeAttribute(key);
      break;
    case "inert":
      "" !== value || didWarnForNewBooleanPropsWithEmptyValue[key] ||
(didWarnForNewBooleanPropsWithEmptyValue[key] = !0, console.error("Received an empty string
for a boolean attribute `%s`. This will treat the attribute as if it were false. Either pass `false` to silence
this warning, or pass `true` if you used an empty string in earlier versions of React to indicate this
attribute is true.", key));
    case "allowFullScreen":
    case "async":
    case "autoPlay":
    case "controls":
    case "default":
    case "defer":
    case "disabled":
    case "disablePictureInPicture":
    case "disableRemotePlayback":
    case "formNoValidate":
    case "hidden":
```

```
      case "loop":
      case "noModule":
      case "noValidate":
      case "open":
      case "playsInline":
      case "readOnly":
      case "required":
      case "reversed":
      case "scoped":
      case "seamless":
      case "itemScope":
        value && "function" !== typeof value && "symbol" !== typeof value ?
domElement.setAttribute(key, "") : domElement.removeAttribute(key);
        break;
      case "capture":
      case "download":
        !0 === value ? domElement.setAttribute(key, "") : !1 !== value && null != value && "function" !
== typeof value && "symbol" !== typeof value ? (checkAttributeStringCoercion(value, key),
domElement.setAttribute(key, value)) : domElement.removeAttribute(key);
        break;
      case "cols":
      case "rows":
      case "size":
      case "span":
        null != value && "function" !== typeof value && "symbol" !== typeof value && !isNaN(value)
&& 1 <= value ? (checkAttributeStringCoercion(value, key), domElement.setAttribute(key, value)) :
domElement.removeAttribute(key);
        break;
      case "rowSpan":
      case "start":
        null == value || "function" === typeof value || "symbol" === typeof value || isNaN(value) ?
domElement.removeAttribute(key) : (checkAttributeStringCoercion(value, key),
domElement.setAttribute(key, value));
        break;
      case "popover":
        listenToNonDelegatedEvent("beforetoggle", domElement);
        listenToNonDelegatedEvent("toggle", domElement);
        setValueForAttribute(domElement, "popover", value);
        break;
      case "xlinkActuate":
        setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:actuate", value);
        break;
      case "xlinkArcrole":
        setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:arcrole", value);
        break;
      case "xlinkRole":
        setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:role", value);
        break;
      case "xlinkShow":
```

```
      setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:show", value);
      break;
    case "xlinkTitle":
      setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:title", value);
      break;
    case "xlinkType":
      setValueForNamespacedAttribute(domElement, xlinkNamespace, "xlink:type", value);
      break;
    case "xmlBase":
      setValueForNamespacedAttribute(domElement, xmlNamespace, "xml:base", value);
      break;
    case "xmlLang":
      setValueForNamespacedAttribute(domElement, xmlNamespace, "xml:lang", value);
      break;
    case "xmlSpace":
      setValueForNamespacedAttribute(domElement, xmlNamespace, "xml:space", value);
      break;
    case "is":
      null != prevValue && console.error('Cannot update the "is" prop after it has been initialized.');
      setValueForAttribute(domElement, "is", value);
      break;
    case "innerText":
    case "textContent":
      break;
    case "popoverTarget":
      didWarnPopoverTargetObject || null == value || "object" !== typeof value ||
(didWarnPopoverTargetObject = !0, console.error("The `popoverTarget` prop expects the ID of an
Element as a string. Received %s instead.", value));
    default:
      !(2 < key.length) || "o" !== key[0] && "O" !== key[0] || "n" !== key[1] && "N" !== key[1] ? (key
= getAttributeAlias(key), setValueForAttribute(domElement, key, value)) :
registrationNameDependencies.hasOwnProperty(key) && null != value && "function" !== typeof
value && warnForInvalidEventListener(key, value);
  }
 }
 function setPropOnCustomElement(domElement, tag, key, value, props, prevValue) {
  switch (key) {
    case "style":
      setValueForStyles(domElement, value, prevValue);
      break;
    case "dangerouslySetInnerHTML":
      if (null != value) {
        if ("object" !== typeof value || !("__html" in value)) throw
Error("`props.dangerouslySetInnerHTML` must be in the form `{__html: ...}`. Please visit
https://react.dev/link/dangerously-set-inner-html for more information.");
        key = value.__html;
        if (null != key) {
          if (null != props.children) throw Error("Can only set one of `children` or
`props.dangerouslySetInnerHTML`.");
```

```
          domElement.innerHTML = key;
        }
      }
      break;
    case "children":
      "string" === typeof value ? setTextContent(domElement, value) : ("number" === typeof value ||
"bigint" === typeof value) && setTextContent(domElement, "" + value);
      break;
    case "onScroll":
      null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
listenToNonDelegatedEvent("scroll", domElement));
      break;
    case "onScrollEnd":
      null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
listenToNonDelegatedEvent("scrollend", domElement));
      break;
    case "onClick":
      null != value && ("function" !== typeof value && warnForInvalidEventListener(key, value),
domElement.onclick = noop$1);
      break;
    case "suppressContentEditableWarning":
    case "suppressHydrationWarning":
    case "innerHTML":
    case "ref":
      break;
    case "innerText":
    case "textContent":
      break;
    default:
      if (registrationNameDependencies.hasOwnProperty(key)) null != value && "function" !== typeof
value && warnForInvalidEventListener(key, value);else a: {
        if ("o" === key[0] && "n" === key[1] && (props = key.endsWith("Capture"), tag = key.slice(2,
props ? key.length - 7 : void 0), prevValue = domElement[internalPropsKey] || null, prevValue = null !=
prevValue ? prevValue[key] : null, "function" === typeof prevValue &&
domElement.removeEventListener(tag, prevValue, props), "function" === typeof value)) {
          "function" !== typeof prevValue && null !== prevValue && (key in domElement ?
domElement[key] = null : domElement.hasAttribute(key)
 && domElement.removeAttribute(key));
          domElement.addEventListener(tag, value, props);
          break a;
        }
        key in domElement ? domElement[key] = value : !0 === value ? domElement.setAttribute(key,
"") : setValueForAttribute(domElement, key, value);
      }
  }
 }
 function setInitialProperties(domElement, tag, props) {
  validatePropertiesInDevelopment(tag, props);
  switch (tag) {
```

```
      case "div":
      case "span":
      case "svg":
      case "path":
      case "a":
      case "g":
      case "p":
      case "li":
        break;
      case "img":
        listenToNonDelegatedEvent("error", domElement);
        listenToNonDelegatedEvent("load", domElement);
        var hasSrc = !1,
          hasSrcSet = !1,
          propKey;
        for (propKey in props) if (props.hasOwnProperty(propKey)) {
          var propValue = props[propKey];
          if (null != propValue) switch (propKey) {
            case "src":
              hasSrc = !0;
              break;
            case "srcSet":
              hasSrcSet = !0;
              break;
            case "children":
            case "dangerouslySetInnerHTML":
              throw Error(tag + " is a void element tag and must neither have `children` nor use
`dangerouslySetInnerHTML`.");
            default:
              setProp(domElement, tag, propKey, propValue, props, null);
          }
        }
        hasSrcSet && setProp(domElement, tag, "srcSet", props.srcSet, props, null);
        hasSrc && setProp(domElement, tag, "src", props.src, props, null);
        return;
      case "input":
        checkControlledValueProps("input", props);
        listenToNonDelegatedEvent("invalid", domElement);
        var defaultValue = propKey = propValue = hasSrcSet = null,
          checked = null,
          defaultChecked = null;
        for (hasSrc in props) if (props.hasOwnProperty(hasSrc)) {
          var _propValue = props[hasSrc];
          if (null != _propValue) switch (hasSrc) {
            case "name":
              hasSrcSet = _propValue;
              break;
            case "type":
              propValue = _propValue;
```

```
            break;
          case "checked":
            checked = _propValue;
            break;
          case "defaultChecked":
            defaultChecked = _propValue;
            break;
          case "value":
            propKey = _propValue;
            break;
          case "defaultValue":
            defaultValue = _propValue;
            break;
          case "children":
          case "dangerouslySetInnerHTML":
            if (null != _propValue) throw Error(tag + " is a void element tag and must neither have
`children` nor use `dangerouslySetInnerHTML`.");
            break;
          default:
            setProp(domElement, tag, hasSrc, _propValue, props, null);
        }
      }
      validateInputProps(domElement, props);
      initInput(domElement, propKey, defaultValue, checked, defaultChecked, propValue, hasSrcSet, !
1);
      track(domElement);
      return;
    case "select":
      checkControlledValueProps("select", props);
      listenToNonDelegatedEvent("invalid", domElement);
      hasSrc = propValue = propKey = null;
      for (hasSrcSet in props) if (props.hasOwnProperty(hasSrcSet) && (defaultValue =
props[hasSrcSet], null != defaultValue)) switch (hasSrcSet) {
        case "value":
          propKey = defaultValue;
          break;
        case "defaultValue":
          propValue = defaultValue;
          break;
        case "multiple":
          hasSrc = defaultValue;
        default:
          setProp(domElement, tag, hasSrcSet, defaultValue, props, null);
      }
      validateSelectProps(domElement, props);
      tag = propKey;
      props = propValue;
      domElement.multiple = !!hasSrc;
      null != tag ? updateOptions(domElement, !!hasSrc, tag, !1) : null != props &&
```

```
updateOptions(domElement, !!hasSrc, props, !0);
        return;
      case "textarea":
        checkControlledValueProps("textarea", props);
        listenToNonDelegatedEvent("invalid", domElement);
        propKey = hasSrcSet = hasSrc = null;
        for (propValue in props) if (props.hasOwnProperty(propValue) && (defaultValue =
props[propValue], null != defaultValue)) switch (propValue) {
          case "value":
            hasSrc = defaultValue;
            break;
          case "defaultValue":
            hasSrcSet = defaultValue;
            break;
          case "children":
            propKey = defaultValue;
            break;
          case "dangerouslySetInnerHTML":
            if (null != defaultValue) throw Error("`dangerouslySetInnerHTML` does not make sense on
<textarea>.");
            break;
          default:
            setProp(domElement, tag, propValue, defaultValue, props, null);
        }
        validateTextareaProps(domElement, props);
        initTextarea(domElement, hasSrc, hasSrcSet, propKey);
        track(domElement);
        return;
      case "option":
        validateOptionProps(domElement, props);
        for (checked in props) if (props.hasOwnProperty(checked) && (hasSrc = props[checked], null !=
hasSrc)) switch (checked) {
          case "selected":
            domElement.selected = hasSrc && "function" !== typeof hasSrc && "symbol" !== typeof
hasSrc;
            break;
          default:
            setProp(domElement, tag, checked, hasSrc, props, null);
        }
        return;
      case "dialog":
        listenToNonDelegatedEvent("cancel", domElement);
        listenToNonDelegatedEvent("close", domElement);
        break;
      case "iframe":
      case "object":
        listenToNonDelegatedEvent("load", domElement);
        break;
      case "video":
```

```
      case "audio":
        for (hasSrc = 0; hasSrc < mediaEventTypes.length; hasSrc++)
listenToNonDelegatedEvent(mediaEventTypes[hasSrc], domElement);
        break;
      case "image":
        listenToNonDelegatedEvent("error", domElement);
        listenToNonDelegatedEvent("load", domElement);
        break;
      case "details":
        listenToNonDelegatedEvent("toggle", domElement);
        break;
      case "embed":
      case "source":
      case "link":
        listenToNonDelegatedEvent("error", domElement), listenToNonDelegatedEvent("load",
domElement);
      case "area":
      case "base":
      case "br":
      case "col":
      case "hr":
      case "keygen":
      case "meta":
      case "param":
      case "track":
      case "wbr":
      case "menuitem":
        for (defaultChecked in props) if (props.hasOwnProperty(defaultChecked) && (hasSrc =
props[defaultChecked], null != hasSrc)) switch (defaultChecked) {
          case "children":
          case "dangerouslySetInnerHTML":
            throw Error(tag + " is a void element tag and must neither have `children` nor use
`dangerouslySetInnerHTML`.");
          default:
            setProp(domElement, tag, defaultChecked, hasSrc, props, null);
        }
        return;
      default:
        if (isCustomElement(tag)) {
          for (_propValue in props) props.hasOwnProperty(_propValue) && (hasSrc = props[_propValue],
void 0 !== hasSrc && setPropOnCustomElement(domElement, tag, _propValue, hasSrc, props, void
0));
          return;
        }
    }
    for (defaultValue in props) props.hasOwnProperty(defaultValue) && (hasSrc = props[defaultValue],
null != hasSrc && setProp(domElement, tag, defaultValue, hasSrc, props, null));
  }
  function updateProperties(domElement, tag, lastProps, nextProps) {
```

```
    validatePropertiesInDevelopment(tag, nextProps);
    switch (tag) {
      case "div":
      case "span":
      case "svg":
      case "path":
      case "a":
      case "g":
      case "p":
      case "li":
        break;
      case "input":
        var name = null,
          type = null,
          value = null,
          defaultValue = null,
          lastDefaultValue = null,
          checked = null,
          defaultChecked = null;
        for (propKey in lastProps) {
          var lastProp = lastProps[propKey];
          if (lastProps.hasOwnProperty(propKey) && null != lastProp) switch (propKey) {
            case "checked":
              break;
            case "value":
              break;
            case "defaultValue":
              lastDefaultValue = lastProp;
            default:
              nextProps.hasOwnProperty(propKey) || setProp(domElement, tag, propKey, null, nextProps,
lastProp);
          }
        }
        for (var _propKey8 in nextProps) {
          var propKey = nextProps[_propKey8];
          lastProp = lastProps[_propKey8];
          if (nextProps.hasOwnProperty(_propKey8) && (null != propKey || null != lastProp)) switch
(_propKey8) {
            case "type":
              type = propKey;
              break;
            case "name":
              name = propKey;
              break;
            case "checked":
              checked = propKey;
              break;
            case "defaultChecked":
              defaultChecked = propKey;
```

```
            break;
          case "value":
            value = propKey;
            break;
          case "defaultValue":
            defaultValue = propKey;
            break;
          case "children":
          case "dangerouslySetInnerHTML":
            if (null != propKey) throw Error(tag + " is a void element tag and must neither have `children` nor use `dangerouslySetInnerHTML`.");
            break;
          default:
            propKey !== lastProp && setProp(domElement, tag, _propKey8, propKey, nextProps, lastProp);
        }
      }
      tag = "checkbox" === lastProps.type || "radio" === lastProps.type ? null != lastProps.checked : null != lastProps.value;
      nextProps = "checkbox" === nextProps.type || "radio" === nextProps.type ? null != nextProps.checked : null
 != nextProps.value;
      tag || !nextProps || didWarnUncontrolledToControlled || (console.error("A component is changing an uncontrolled input to be controlled. This is likely caused by the value changing from undefined to a defined value, which should not happen. Decide between using a controlled or uncontrolled input element for the lifetime of the component. More info: https://react.dev/link/controlled-components"), didWarnUncontrolledToControlled = !0);
      !tag || nextProps || didWarnControlledToUncontrolled || (console.error("A component is changing a controlled input to be uncontrolled. This is likely caused by the value changing from a defined to undefined, which should not happen. Decide between using a controlled or uncontrolled input element for the lifetime of the component. More info: https://react.dev/link/controlled-components"), didWarnControlledToUncontrolled = !0);
      updateInput(domElement, value, defaultValue, lastDefaultValue, checked, defaultChecked, type, name);
      return;
    case "select":
      propKey = value = defaultValue = _propKey8 = null;
      for (type in lastProps) if (lastDefaultValue = lastProps[type], lastProps.hasOwnProperty(type) && null != lastDefaultValue) switch (type) {
        case "value":
          break;
        case "multiple":
          propKey = lastDefaultValue;
        default:
          nextProps.hasOwnProperty(type) || setProp(domElement, tag, type, null, nextProps, lastDefaultValue);
      }
      for (name in nextProps) if (type = nextProps[name], lastDefaultValue = lastProps[name], nextProps.hasOwnProperty(name) && (null != type || null != lastDefaultValue)) switch (name) {
```

```
        case "value":
          _propKey8 = type;
          break;
        case "defaultValue":
          defaultValue = type;
          break;
        case "multiple":
          value = type;
        default:
          type !== lastDefaultValue && setProp(domElement, tag, name, type, nextProps,
lastDefaultValue);
      }
      nextProps = defaultValue;
      tag = value;
      lastProps = propKey;
      null != _propKey8 ? updateOptions(domElement, !!tag, _propKey8, !1) : !!lastProps !== !!tag &&
(null != nextProps ? updateOptions(domElement, !!tag, nextProps, !0) : updateOptions(domElement, !!
tag, tag ? [] : "", !1));
      return;
    case "textarea":
      propKey = _propKey8 = null;
      for (defaultValue in lastProps) if (name = lastProps[defaultValue],
lastProps.hasOwnProperty(defaultValue) && null != name && !
nextProps.hasOwnProperty(defaultValue)) switch (defaultValue) {
        case "value":
          break;
        case "children":
          break;
        default:
          setProp(domElement, tag, defaultValue, null, nextProps, name);
      }
      for (value in nextProps) if (name = nextProps[value], type = lastProps[value],
nextProps.hasOwnProperty(value) && (null != name || null != type)) switch (value) {
        case "value":
          _propKey8 = name;
          break;
        case "defaultValue":
          propKey = name;
          break;
        case "children":
          break;
        case "dangerouslySetInnerHTML":
          if (null != name) throw Error("`dangerouslySetInnerHTML` does not make sense on
<textarea>.");
          break;
        default:
          name !== type && setProp(domElement, tag, value, name, nextProps, type);
      }
      updateTextarea(domElement, _propKey8, propKey);
```

```
      return;
    case "option":
      for (var _propKey13 in lastProps) if (_propKey8 = lastProps[_propKey13],
lastProps.hasOwnProperty(_propKey13) && null != _propKey8 && !
nextProps.hasOwnProperty(_propKey13)) switch (_propKey13) {
        case "selected":
          domElement.selected = !1;
          break;
        default:
          setProp(domElement, tag, _propKey13, null, nextProps, _propKey8);
      }
      for (lastDefaultValue in nextProps) if (_propKey8 = nextProps[lastDefaultValue], propKey =
lastProps[lastDefaultValue], nextProps.hasOwnProperty(lastDefaultValue) && _propKey8 !==
propKey && (null != _propKey8 || null != propKey)) switch (lastDefaultValue) {
        case "selected":
          domElement.selected = _propKey8 && "function" !== typeof _propKey8 && "symbol" !==
typeof _propKey8;
          break;
        default:
          setProp(domElement, tag, lastDefaultValue, _propKey8, nextProps, propKey);
      }
      return;
    case "img":
    case "link":
    case "area":
    case "base":
    case "br":
    case "col":
    case "embed":
    case "hr":
    case "keygen":
    case "meta":
    case "param":
    case "source":
    case "track":
    case "wbr":
    case "menuitem":
      for (var _propKey15 in lastProps) _propKey8 = lastProps[_propKey15],
lastProps.hasOwnProperty(_propKey15) && null != _propKey8 && !
nextProps.hasOwnProperty(_propKey15) && setProp(domElement, tag, _propKey15, null, nextProps,
_propKey8);
      for (checked in nextProps) if (_propKey8 = nextProps[checked], propKey = lastProps[checked],
nextProps.hasOwnProperty(checked) && _propKey8 !== propKey && (null != _propKey8 || null !=
propKey)) switch (checked) {
        case "children":
        case "dangerouslySetInnerHTML":
          if (null != _propKey8) throw Error(tag + " is a void element tag and must neither have
`children` nor use `dangerouslySetInnerHTML`.");
          break;
```

```
        default:
          setProp(domElement, tag, checked, _propKey8, nextProps, propKey);
      }
      return;
    default:
      if (isCustomElement(tag)) {
        for (var _propKey17 in lastProps) _propKey8 = lastProps[_propKey17],
lastProps.hasOwnProperty(_propKey17) && void 0 !== _propKey8 && !
nextProps.hasOwnProperty(_propKey17) && setPropOnCustomElement(domElement, tag,
_propKey17, void 0, nextProps, _propKey8);
        for (defaultChecked in nextProps) _propKey8 = nextProps[defaultChecked], propKey =
lastProps[defaultChecked], !nextProps.hasOwnProperty(defaultChecked) || _propKey8 === propKey ||
void 0 === _propKey8 && void 0 === propKey || setPropOnCustomElement(domElement, tag,
defaultChecked, _propKey8, nextProps, propKey);
        return;
      }
  }
  for (var _propKey19 in lastProps) _propKey8 = lastProps[_propKey19],
lastProps.hasOwnProperty(_propKey19) && null != _propKey8 && !
nextProps.hasOwnProperty(_propKey19) && setProp(domElement, tag, _propKey19, null, nextProps,
_propKey8);
  for (lastProp in nextProps) _propKey8 = nextProps[lastProp], propKey = lastProps[lastProp], !
nextProps.hasOwnProperty(lastProp) || _propKey8 === propKey || null == _propKey8 && null ==
propKey || setProp(domElement, tag, lastProp, _propKey8, nextProps, propKey);
}
function getPropNameFromAttributeName(attrName) {
  switch (attrName) {
    case "class":
      return "className";
    case "for":
      return "htmlFor";
    default:
      return attrName;
  }
}
function getStylesObjectFromElement(domElement) {
  var serverValueInObjectForm = {};
  domElement = domElement.style;
  for (var i = 0; i < domElement.length; i++) {
    var styleName = domElement[i];
    serverValueInObjectForm[styleName] = domElement.getPropertyValue(styleName);
  }
  return serverValueInObjectForm;
}
function diffHydratedStyles(domElement, value$jscomp$0, serverDifferences) {
  if (null != value$jscomp$0 && "object" !== typeof value$jscomp$0) console.error("The `style` prop
expects a mapping from style properties to values, not a string. For example, style={{marginRight:
spacing + 'em'}} when using JSX.");else if (canDiffStyleForHydrationWarning) {
    var clientValue;
```

```
      var delimiter = clientValue = "",
        styleName;
      for (styleName in value$jscomp$0) if (value$jscomp$0.hasOwnProperty(styleName)) {
        var value = value$jscomp$0[styleName];
        null != value && "boolean" !== typeof value && "" !== value && (0 ===
styleName.indexOf("--") ? (checkCSSPropertyStringCoercion(value, styleName), clientValue +=
delimiter + styleName + ":" + ("" + value).trim()) : "number" !== typeof value || 0 === value ||
unitlessNumbers.has(styleName) ? (checkCSSPropertyStringCoercion(value, styleName), clientValue
+= delimiter + styleName.replace(uppercasePattern, "-$1").toLowerCase().replace(msPattern$1, "-
ms-") + ":" + ("" + value).trim()) : clientValue += delimiter + styleName.replace(uppercasePattern, "-
$1").toLowerCase().replace(msPattern$1, "-ms-") + ":" + value + "px", delimiter = ";");
      }
      clientValue = clientValue || null;
      value$jscomp$0 = domElement.getAttribute("style");
      value$jscomp$0 !== clientValue && (clientValue =
normalizeMarkupForTextOrAttribute(clientValue),
normalizeMarkupForTextOrAttribute(value$jscomp$0) !== clientValue && (serverDifferences.style =
getStylesObjectFromElement(domElement)));
    }
  }
  function hydrateAttribute(domElement, propKey, attributeName, value, extraAttributes,
serverDifferences) {
    extraAttributes.delete(attributeName);
    domElement = domElement.getAttribute(attributeName);
    if (null === domElement) switch (typeof value) {
      case "undefined":
      case "function":
      case "symbol":
      case "boolean":
        return;
    } else if (null != value) switch (typeof value) {
      case "function":
      case "symbol":
      case "boolean":
        break;
      default:
        if (checkAttributeStringCoercion(value, propKey), domElement === "" + value) return;
    }
    warnForPropDifference(propKey, domElement, value, serverDifferences);
  }
  function hydrateBooleanAttribute(domElement, propKey, attributeName, value, extraAttributes,
serverDifferences) {
    extraAttributes.delete(attributeName);
    domElement = domElement.getAttribute(attributeName);
    if (null === domElement)
 {
      switch (typeof value) {
        case "function":
        case "symbol":
```

```
          return;
        }
        if (!value) return;
      } else switch (typeof value) {
        case "function":
        case "symbol":
          break;
        default:
          if (value) return;
      }
      warnForPropDifference(propKey, domElement, value, serverDifferences);
    }
    function hydrateBooleanishAttribute(domElement, propKey, attributeName, value, extraAttributes,
serverDifferences) {
      extraAttributes.delete(attributeName);
      domElement = domElement.getAttribute(attributeName);
      if (null === domElement) switch (typeof value) {
        case "undefined":
        case "function":
        case "symbol":
          return;
      } else if (null != value) switch (typeof value) {
        case "function":
        case "symbol":
          break;
        default:
          if (checkAttributeStringCoercion(value, attributeName), domElement === "" + value) return;
      }
      warnForPropDifference(propKey, domElement, value, serverDifferences);
    }
    function hydrateNumericAttribute(domElement, propKey, attributeName, value, extraAttributes,
serverDifferences) {
      extraAttributes.delete(attributeName);
      domElement = domElement.getAttribute(attributeName);
      if (null === domElement) switch (typeof value) {
        case "undefined":
        case "function":
        case "symbol":
        case "boolean":
          return;
        default:
          if (isNaN(value)) return;
      } else if (null != value) switch (typeof value) {
        case "function":
        case "symbol":
        case "boolean":
          break;
        default:
          if (!isNaN(value) && (checkAttributeStringCoercion(value, propKey), domElement === "" +
```

```
value)) return;
    }
    warnForPropDifference(propKey, domElement, value, serverDifferences);
  }
  function hydrateSanitizedAttribute(domElement, propKey, attributeName, value, extraAttributes,
serverDifferences) {
    extraAttributes.delete(attributeName);
    domElement = domElement.getAttribute(attributeName);
    if (null === domElement) switch (typeof value) {
      case "undefined":
      case "function":
      case "symbol":
      case "boolean":
        return;
    } else if (null != value) switch (typeof value) {
      case "function":
      case "symbol":
      case "boolean":
        break;
      default:
        if (checkAttributeStringCoercion(value, propKey), attributeName = sanitizeURL("" + value),
domElement === attributeName) return;
    }
    warnForPropDifference(propKey, domElement, value, serverDifferences);
  }
  function diffHydratedProperties(domElement, tag, props, hostContext) {
    for (var serverDifferences = {}, extraAttributes = new Set(), attributes = domElement.attributes, i =
0; i < attributes.length; i++) switch (attributes[i].name.toLowerCase()) {
      case "value":
        break;
      case "checked":
        break;
      case "selected":
        break;
      default:
        extraAttributes.add(attributes[i].name);
    }
    if (isCustomElement(tag)) for (var propKey in props) {
      if (props.hasOwnProperty(propKey)) {
        var value = props[propKey];
        if (null != value) if (registrationNameDependencies.hasOwnProperty(propKey)) "function" !==
typeof value && warnForInvalidEventListener(propKey, value);else if (!0 !==
props.suppressHydrationWarning) switch (propKey) {
          case "children":
            "string" !== typeof value && "number" !== typeof value || warnForPropDifference("children",
domElement.textContent, value, serverDifferences);
            continue;
          case "suppressContentEditableWarning":
          case "suppressHydrationWarning":
```

```
        case "defaultValue":
        case "defaultChecked":
        case "innerHTML":
        case "ref":
          continue;
        case "dangerouslySetInnerHTML":
          attributes = domElement.innerHTML;
          value = value ? value.__html : void 0;
          null != value && (value = normalizeHTML(domElement, value),
warnForPropDifference(propKey, attributes, value, serverDifferences));
          continue;
        case "style":
          extraAttributes.delete(propKey);
          diffHydratedStyles(domElement, value, serverDifferences);
          continue;
        case "offsetParent":
        case "offsetTop":
        case "offsetLeft":
        case "offsetWidth":
        case "offsetHeight":
        case "isContentEditable":
        case "outerText":
        case "outerHTML":
          extraAttributes.delete(propKey.toLowerCase());
          console.error("Assignment to read-only property will result in a no-op: `%s`", propKey);
          continue;
        case "className":
          extraAttributes.delete("class");
          attributes = getValueForAttributeOnCustomComponent(domElement, "class", value);
          warnForPropDifference("className", attributes, value, serverDifferences);
          continue;
        default:
          hostContext.context === HostContextNamespaceNone && "svg" !== tag && "math" !== tag ?
extraAttributes.delete(propKey.toLowerCase()) : extraAttributes.delete(propKey), attributes =
getValueForAttributeOnCustomComponent(domElement, propKey, value),
warnForPropDifference(propKey, attributes, value, serverDifferences);
      }
    }
  } else for (value in props) if (props.hasOwnProperty(value) && (propKey = props[value], null !=
propKey)) if (registrationNameDependencies.hasOwnProperty(value)) "function" !== typeof propKey
&& warnForInvalidEventListener(value, propKey);else if (!0 !== props.suppressHydrationWarning)
switch (value) {
    case "children":
      "string" !== typeof propKey && "number" !== typeof propKey ||
warnForPropDifference("children", domElement.textContent, propKey, serverDifferences);
      continue;
    case "suppressContentEditableWarning":
    case "suppressHydrationWarning":
    case "value":
```

```
      case "checked":
      case "selected":
      case "defaultValue":
      case "defaultChecked":
      case "innerHTML":
      case "ref":
        continue;
      case "dangerouslySetInnerHTML":
        attributes = domElement.innerHTML;
        propKey = propKey ? propKey.__html : void 0;
        null != propKey && (propKey = normalizeHTML(domElement, propKey), attributes !==
propKey && (serverDifferences[value] = {
          __html: attributes
        }));
        continue;
      case "className":
        hydrateAttribute(domElement, value, "class", propKey, extraAttributes, serverDifferences);
        continue;
      case "tabIndex":
        hydrateAttribute(domElement, value, "tabindex", propKey, extraAttributes, serverDifferences);
        continue;
      case "style":
        extraAttributes.delete(value);
        diffHydratedStyles(domElement, propKey, serverDifferences);
        continue;
      case "multiple":
        extraAttributes.delete(value);
        warnForPropDifference(value, domElement.multiple, propKey, serverDifferences);
        continue;
      case "muted":
        extraAttributes.delete(value);
        warnForPropDifference(value, domElement.muted, propKey, serverDifferences);
        continue;
      case "autoFocus":
        extraAttributes.delete("autofocus");
        warnForPropDifference(value, domElement.autofocus, propKey, serverDifferences);
        continue;
      case "data":
        if ("object" !== tag) {
          extraAttributes.delete(value);
          attributes = domElement.getAttribute("data");
          warnForPropDifference(value, attributes, propKey, serverDifferences);
          continue;
        }
      case "src":
      case "href":
        if (!("" !== propKey || "a" === tag && "href" === value || "object" === tag && "data" ===
value)) {
          "src" === value ? console.error('An empty string ("") was passed to the %s attribute. This may
```

```
cause the browser to download the whole page again over the network. To fix this, either do not render the element at all or pass null to %s instead of an empty string.', value, value) : console.error('An empty string ("") was passed to the %s attribute. To fix this, either do not render the element at all or pass null to %s instead of an empty string.', value, value);
          hydrateSanitizedAttribute(domElement, value, value, null, extraAttributes, serverDifferences);
          continue;
        }
        hydrateSanitizedAttribute(domElement, value, value, propKey, extraAttributes,
serverDifferences);
        continue;
      case "action":
      case "formAction":
        attributes = domElement.getAttribute(value);
        if ("function" === typeof propKey) {
          extraAttributes.delete(value.toLowerCase());
          "formAction" === value ? (extraAttributes.delete("name"),
extraAttributes.delete("formenctype"), extraAttributes.delete("formmethod"),
extraAttributes.delete("formtarget")) : (extraAttributes.delete("enctype"),
extraAttributes.delete("method"), extraAttributes.delete("target"));
          continue;
        } else if (attributes === EXPECTED_FORM_ACTION_URL) {
          extraAttributes.delete(value.toLowerCase());
          warnForPropDifference(value, "function", propKey, serverDifferences);
          continue;
        }
        hydrateSanitizedAttribute(domElement, value, value.toLowerCase(), propKey, extraAttributes,
serverDifferences);
        continue;
      case "xlinkHref":
        hydrateSanitizedAttribute(domElement, value, "xlink:href", propKey, extraAttributes,
serverDifferences);
        continue;
      case "contentEditable":
        hydrateBooleanishAttribute(domElement, value, "contenteditable", propKey, extraAttributes,
serverDifferences);
        continue;
      case "spellCheck":
        hydrateBooleanishAttribute(domElement, value, "spellcheck", propKey, extraAttributes,
serverDifferences);
        continue;
      case "draggable":
      case "autoReverse":
      case "externalResourcesRequired":

      case "focusable":
      case "preserveAlpha":
        hydrateBooleanishAttribute(domElement, value, value, propKey, extraAttributes,
serverDifferences);
        continue;
```

```
      case "allowFullScreen":
      case "async":
      case "autoPlay":
      case "controls":
      case "default":
      case "defer":
      case "disabled":
      case "disablePictureInPicture":
      case "disableRemotePlayback":
      case "formNoValidate":
      case "hidden":
      case "loop":
      case "noModule":
      case "noValidate":
      case "open":
      case "playsInline":
      case "readOnly":
      case "required":
      case "reversed":
      case "scoped":
      case "seamless":
      case "itemScope":
        hydrateBooleanAttribute(domElement, value, value.toLowerCase(), propKey, extraAttributes,
serverDifferences);
        continue;
      case "capture":
      case "download":
        a: {
          i = domElement;
          var attributeName = attributes = value,
            serverDifferences$jscomp$0 = serverDifferences;
          extraAttributes.delete(attributeName);
          i = i.getAttribute(attributeName);
          if (null === i) switch (typeof propKey) {
            case "undefined":
            case "function":
            case "symbol":
              break a;
            default:
              if (!1 === propKey) break a;
          } else if (null != propKey) switch (typeof propKey) {
            case "function":
            case "symbol":
              break;
            case "boolean":
              if (!0 === propKey && "" === i) break a;
              break;
            default:
              if (checkAttributeStringCoercion(propKey, attributes), i === "" + propKey) break a;
```

```
        }
        warnForPropDifference(attributes, i, propKey, serverDifferences$jscomp$0);
      }
      continue;
    case "cols":
    case "rows":
    case "size":
    case "span":
      a: {
        i = domElement;
        attributeName = attributes = value;
        serverDifferences$jscomp$0 = serverDifferences;
        extraAttributes.delete(attributeName);
        i = i.getAttribute(attributeName);
        if (null === i) switch (typeof propKey) {
          case "undefined":
          case "function":
          case "symbol":
          case "boolean":
            break a;
          default:
            if (isNaN(propKey) || 1 > propKey) break a;
        } else if (null != propKey) switch (typeof propKey) {
          case "function":
          case "symbol":
          case "boolean":
            break;
          default:
            if (!(isNaN(propKey) || 1 > propKey) && (checkAttributeStringCoercion(propKey, attributes),
i === "" + propKey)) break a;
        }
        warnForPropDifference(attributes, i, propKey, serverDifferences$jscomp$0);
      }
      continue;
    case "rowSpan":
      hydrateNumericAttribute(domElement, value, "rowspan", propKey, extraAttributes,
serverDifferences);
      continue;
    case "start":
      hydrateNumericAttribute(domElement, value, value, propKey, extraAttributes, serverDifferences);
      continue;
    case "xHeight":
      hydrateAttribute(domElement, value, "x-height", propKey, extraAttributes, serverDifferences);
      continue;
    case "xlinkActuate":
      hydrateAttribute(domElement, value, "xlink:actuate", propKey, extraAttributes,
serverDifferences);
      continue;
    case "xlinkArcrole":
```

```
      hydrateAttribute(domElement, value, "xlink:arcrole", propKey, extraAttributes,
serverDifferences);
      continue;
    case "xlinkRole":
      hydrateAttribute(domElement, value, "xlink:role", propKey, extraAttributes, serverDifferences);
      continue;
    case "xlinkShow":
      hydrateAttribute(domElement, value, "xlink:show", propKey, extraAttributes, serverDifferences);
      continue;
    case "xlinkTitle":
      hydrateAttribute(domElement, value, "xlink:title", propKey, extraAttributes, serverDifferences);
      continue;
    case "xlinkType":
      hydrateAttribute(domElement, value, "xlink:type", propKey, extraAttributes, serverDifferences);
      continue;
    case "xmlBase":
      hydrateAttribute(domElement, value, "xml:base", propKey, extraAttributes, serverDifferences);
      continue;
    case "xmlLang":
      hydrateAttribute(domElement, value, "xml:lang", propKey, extraAttributes, serverDifferences);
      continue;
    case "xmlSpace":
      hydrateAttribute(domElement, value, "xml:space", propKey, extraAttributes, serverDifferences);
      continue;
    case "inert":
      "" !== propKey || didWarnForNewBooleanPropsWithEmptyValue[value] ||
(didWarnForNewBooleanPropsWithEmptyValue[value] = !0, console.error("Received an empty string
for a boolean attribute `%s`. This will treat the attribute as if it were false. Either pass `false` to silence
this warning, or pass `true` if you used an empty string in earlier versions of React to indicate this
attribute is true.", value));
      hydrateBooleanAttribute(domElement, value, value, propKey, extraAttributes, serverDifferences);
      continue;
    default:
      if (!(2 < value.length) || "o" !== value[0] && "O" !== value[0] || "n" !== value[1] && "N" !==
value[1]) {
        i = getAttributeAlias(value);
        attributes = !1;
        hostContext.context === HostContextNamespaceNone && "svg" !== tag && "math" !== tag ?
extraAttributes.delete(i.toLowerCase()) : (attributeName = value.toLowerCase(), attributeName =
possibleStandardNames.hasOwnProperty(attributeName) ? possibleStandardNames[attributeName] ||
null : null, null !== attributeName && attributeName !== value && (attributes = !0,
extraAttributes.delete(attributeName)), extraAttributes.delete(i));
        a: if (attributeName = domElement, serverDifferences$jscomp$0 = i, i = propKey,
isAttributeNameSafe(serverDifferences$jscomp$0)) {
          if (attributeName.hasAttribute(serverDifferences$jscomp$0)) attributeName =
attributeName.getAttribute(serverDifferences$jscomp$0), checkAttributeStringCoercion(i,
serverDifferences$jscomp$0), i = attributeName === "" + i ? i : attributeName;else {
            switch (typeof i) {
              case "function":
```

```
            case "symbol":
              break a;
            case "boolean":
              if (attributeName = serverDifferences$jscomp$0.toLowerCase().slice(0, 5), "data-" !==
attributeName && "aria-" !== attributeName) break a;
            }
            i = void 0 === i ? void 0 : null;
          }
        } else i = void 0;
        attributes || warnForPropDifference(value, i, propKey, serverDifferences);
      }
    }
    0 < extraAttributes.size && !0 !== props.suppressHydrationWarning &&
warnForExtraAttributes(domElement, extraAttributes, serverDifferences);
    return 0 === Object.keys(serverDifferences).length ? null : serverDifferences;
  }
  function propNamesListJoin(list, combinator) {
    switch (list.length) {
      case 0:
        return "";
      case 1:
        return list[0];
      case 2:
        return list[0] + " " + combinator + " " + list[1];
      default:
        return list.slice(0, -1).join(", ") + ", " + combinator + " " + list[list.length - 1];
    }
  }
  function getOwnerDocumentFromRootContainer(rootContainerElement) {
    return 9 === rootContainerElement.nodeType ? rootContainerElement :
rootContainerElement.ownerDocument;
  }
  function getOwnHostContext(namespaceURI) {
    switch (namespaceURI) {
      case SVG_NAMESPACE:
        return HostContextNamespaceSvg;
      case MATH_NAMESPACE:
        return HostContextNamespaceMath;
      default:
        return HostContextNamespaceNone;
    }
  }
  function getChildHostContextProd(parentNamespace, type) {
    if (parentNamespace === HostContextNamespaceNone) switch (type) {
      case "svg":
        return HostContextNamespaceSvg;
      case "math":
        return HostContextNamespaceMath;
      default:
```

```
      return HostContextNamespaceNone;
    }
    return parentNamespace === HostContextNamespaceSvg && "foreignObject" === type ?
HostContextNamespaceNone : parentNamespace;
  }
  function shouldSetTextContent(type, props) {
    return "textarea" === type || "noscript" === type || "string" === typeof props.children || "number"
=== typeof props.children || "bigint" === typeof props.children || "object" === typeof
props.dangerouslySetInnerHTML && null !== props.dangerouslySetInnerHTML && null !=
props.dangerouslySetInnerHTML.__html;
  }
  function shouldAttemptEagerTransition() {
    var event = window.event;
    if (event && "popstate" === event.type) {
      if (event === currentPopstateTransitionEvent) return !1;
      currentPopstateTransitionEvent = event;
      return !0;
    }
    currentPopstateTransitionEvent = null;
    return !1;
  }
  function handleErrorInNextTick(error) {
    setTimeout(function () {
      throw error;
    });
  }
  function commitMount(domElement, type, newProps) {
    switch (type) {
      case "button":
      case "input":
      case "select":
      case "textarea":
        newProps.autoFocus && domElement.focus();
        break;
      case "img":
        newProps.src ? domElement.src = newProps.src : newProps.srcSet && (domElement.srcset =
newProps.srcSet);
    }
  }
  function commitUpdate(domElement, type, oldProps, newProps) {
    updateProperties(domElement, type, oldProps, newProps);
    domElement[internalPropsKey] = newProps;
  }
  function resetTextContent(domElement) {
    setTextContent(domElement, "");
  }
  function commitTextUpdate(textInstance, oldText, newText) {
    textInstance.nodeValue = newText;
  }
```

```
  function removeChild(parentInstance, child) {
    parentInstance.removeChild(child);
  }
  function removeChildFromContainer(container, child) {
    8 === container.nodeType ? container.parentNode.removeChild(child)
 : container.removeChild(child);
  }
  function clearSuspenseBoundary(parentInstance, suspenseInstance) {
    var node = suspenseInstance,
      depth = 0;
    do {
      var nextNode = node.nextSibling;
      parentInstance.removeChild(node);
      if (nextNode && 8 === nextNode.nodeType) if (node = nextNode.data, node ===
SUSPENSE_END_DATA) {
        if (0 === depth) {
          parentInstance.removeChild(nextNode);
          retryIfBlockedOn(suspenseInstance);
          return;
        }
        depth--;
      } else node !== SUSPENSE_START_DATA && node !==
SUSPENSE_PENDING_START_DATA && node !== SUSPENSE_FALLBACK_START_DATA ||
depth++;
      node = nextNode;
    } while (node);
    retryIfBlockedOn(suspenseInstance);
  }
  function hideInstance(instance) {
    instance = instance.style;
    "function" === typeof instance.setProperty ? instance.setProperty("display", "none", "important") :
instance.display = "none";
  }
  function hideTextInstance(textInstance) {
    textInstance.nodeValue = "";
  }
  function unhideInstance(instance, props) {
    props = props[STYLE];
    props = void 0 !== props && null !== props && props.hasOwnProperty("display") ? props.display :
null;
    instance.style.display = null == props || "boolean" === typeof props ? "" : ("" + props).trim();
  }
  function unhideTextInstance(textInstance, text) {
    textInstance.nodeValue = text;
  }
  function clearContainerSparingly(container) {
    var nextNode = container.firstChild;
    nextNode && 10 === nextNode.nodeType && (nextNode = nextNode.nextSibling);
    for (; nextNode;) {
```

```
    var node = nextNode;
    nextNode = nextNode.nextSibling;
    switch (node.nodeName) {
      case "HTML":
      case "HEAD":
      case "BODY":
        clearContainerSparingly(node);
        detachDeletedInstance(node);
        continue;
      case "SCRIPT":
      case "STYLE":
        continue;
      case "LINK":
        if ("stylesheet" === node.rel.toLowerCase()) continue;
    }
    container.removeChild(node);
  }
 }
 function canHydrateInstance(instance, type, props, inRootOrSingleton) {
  for (; 1 === instance.nodeType;) {
    var anyProps = props;
    if (instance.nodeName.toLowerCase() !== type.toLowerCase()) {
      if (!inRootOrSingleton && ("INPUT" !== instance.nodeName || "hidden" !== instance.type))
break;
    } else if (!inRootOrSingleton) {
      if ("input" === type && "hidden" === instance.type) {
        checkAttributeStringCoercion(anyProps.name, "name");
        var name = null == anyProps.name ? null : "" + anyProps.name;
        if ("hidden" === anyProps.type && instance.getAttribute("name") === name) return instance;
      } else return instance;
    } else if (!instance[internalHoistableMarker]) switch (type) {
      case "meta":
        if (!instance.hasAttribute("itemprop")) break;
        return instance;
      case "link":
        name = instance.getAttribute("rel");
        if ("stylesheet" === name && instance.hasAttribute("data-precedence")) break;else if (name !==
anyProps.rel || instance.getAttribute("href") !== (null == anyProps.href ? null : anyProps.href) ||
instance.getAttribute("crossorigin") !== (null == anyProps.crossOrigin ? null : anyProps.crossOrigin) ||
instance.getAttribute("title") !== (null == anyProps.title ? null : anyProps.title)) break;
        return instance;
      case "style":
        if (instance.hasAttribute("data-precedence")) break;
        return instance;
      case "script":
        name = instance.getAttribute("src");
        if ((name !== (null == anyProps.src ? null : anyProps.src) || instance.getAttribute("type") !==
(null == anyProps.type ? null : anyProps.type) || instance.getAttribute("crossorigin") !== (null ==
anyProps.crossOrigin ? null : anyProps.crossOrigin)) && name && instance.hasAttribute("async") &&
```

```
!instance.hasAttribute("itemprop")) break;
          return instance;
        default:
          return instance;
      }
      instance = getNextHydratable(instance.nextSibling);
      if (null === instance) break;
    }
    return null;
  }
  function canHydrateTextInstance(instance, text, inRootOrSingleton) {
    if ("" === text) return null;
    for (; 3 !== instance.nodeType;) {
      if ((1 !== instance.nodeType || "INPUT" !== instance.nodeName || "hidden" !== instance.type)
&& !inRootOrSingleton) return null;
      instance = getNextHydratable(instance.nextSibling);
      if (null === instance) return null;
    }
    return instance;
  }
  function getNextHydratable(node) {
    for (; null != node; node = node.nextSibling) {
      var nodeType = node.nodeType;
      if (1 === nodeType || 3 === nodeType) break;
      if (8 === nodeType) {
        nodeType = node.data;
        if (nodeType === SUSPENSE_START_DATA || nodeType ===
SUSPENSE_FALLBACK_START_DATA || nodeType === SUSPENSE_PENDING_START_DATA ||
nodeType === FORM_STATE_IS_MATCHING || nodeType ===
FORM_STATE_IS_NOT_MATCHING) break;
        if (nodeType === SUSPENSE_END_DATA) return null;
      }
    }
    return node;
  }
  function describeHydratableInstanceForDevWarnings(instance) {
    if (1 === instance.nodeType) {
      for (var JSCompiler_temp_const = instance.nodeName.toLowerCase(), serverDifferences = {},
attributes = instance.attributes, i = 0; i < attributes.length; i++) {
        var attr = attributes[i];
        serverDifferences[getPropNameFromAttributeName(attr.name)] = "style" ===
attr.name.toLowerCase() ? getStylesObjectFromElement(instance) : attr.value;
      }
      return {
        type: JSCompiler_temp_const,
        props: serverDifferences
      };
    }
    return 8 === instance.nodeType ? {
```

```
      type: "Suspense",
      props: {}
    } : instance.nodeValue;
  }
  function diffHydratedTextForDevWarnings(textInstance, text, parentProps) {
    return null === parentProps || !0 !== parentProps[SUPPRESS_HYDRATION_WARNING] ?
(textInstance.nodeValue === text ? textInstance = null : (text =
normalizeMarkupForTextOrAttribute(text), textInstance =
normalizeMarkupForTextOrAttribute(textInstance.nodeValue) === text ? null :
textInstance.nodeValue), textInstance) : null;
  }
  function getNextHydratableInstanceAfterSuspenseInstance(suspenseInstance) {
    suspenseInstance = suspenseInstance.nextSibling;
    for (var depth = 0; suspenseInstance;) {
      if (8 === suspenseInstance.nodeType) {
        var data = suspenseInstance.data;
        if (data === SUSPENSE_END_DATA) {
          if (0 === depth) return getNextHydratable(suspenseInstance.nextSibling);
          depth--;
        } else data !== SUSPENSE_START_DATA && data !==
SUSPENSE_FALLBACK_START_DATA && data !== SUSPENSE_PENDING_START_DATA ||
depth++;
      }
      suspenseInstance = suspenseInstance.nextSibling;
    }
    return null;
  }
  function getParentSuspenseInstance(targetInstance) {
    targetInstance = targetInstance.previousSibling;
    for (var depth = 0; targetInstance;) {
      if (8 === targetInstance.nodeType) {
        var data = targetInstance.data;
        if (data === SUSPENSE_START_DATA || data === SUSPENSE_FALLBACK_START_DATA ||
data === SUSPENSE_PENDING_START_DATA) {
          if (0 === depth) return targetInstance;
          depth--;
        } else data === SUSPENSE_END_DATA && depth++;
      }
      targetInstance = targetInstance.previousSibling;
    }
    return null;
  }
  function commitHydratedContainer(container) {
    retryIfBlockedOn(container);
  }
  function commitHydratedSuspenseInstance(suspenseInstance) {
    retryIfBlockedOn(suspenseInstance);
  }
  function resolveSingletonInstance(type, props, rootContainerInstance, hostContext,
```

```
validateDOMNestingDev) {
    validateDOMNestingDev && validateDOMNesting(type, hostContext.ancestorInfo);
    props = getOwnerDocumentFromRootContainer(rootContainerInstance);
    switch (type) {
      case "html":
        type = props.documentElement;
        if (!type) throw Error("React expected an <html> element (document.documentElement) to exist
in the Document but one was not found. React never removes the documentElement for any Document
it renders into so the cause is likely in some other script running on this page.");
        return type;
      case "head":
        type = props.head;
        if (!type) throw Error("React expected a <head> element (document.head) to exist in the
Document but one was not found. React never removes the head for any Document it renders into so
the cause is likely in some other script running on this page.");
        return type;
      case "body":
        type = props.body;
        if (!type) throw Error("React expected a <body> element (document.body) to exist in the
Document but one was not found. React never removes the body for any Document it renders into so
the cause is likely in some other script running on this page.");
        return type;
      default:
        throw Error("resolveSingletonInstance was called with an element type that is not supported. This
is a bug in React.");
    }
  }
  function acquireSingletonInstance(type, props, instance, internalInstanceHandle) {
    if (getInstanceFromNode(instance)) {
      var tagName = instance.tagName.toLowerCase();
      console.error("You are mounting a new %s component when a previous one has not first
unmounted. It is an error to render more than one %s component at a time and attributes and children of
these components will likely fail in unpredictable ways. Please only render a single instance of <%s>
and if you need to mount a new one, ensure any previous ones have unmounted first.", tagName,
tagName, tagName);
    }
    switch (type) {
      case "html":
      case "head":
      case "body":
        break;
      default:
        console.error("acquireSingletonInstance was called with an element type that is not supported.
This is a bug in React.");
    }
    for (tagName = instance.attributes; tagName.length;)
 instance.removeAttributeNode(tagName[0]);
    setInitialProperties(instance, type, props);
    instance[internalInstanceKey] = internalInstanceHandle;
```

```
    instance[internalPropsKey] = props;
  }
  function getHoistableRoot(container) {
    return "function" === typeof container.getRootNode ? container.getRootNode() :
container.ownerDocument;
  }
  function preconnectAs(rel, href, crossOrigin) {
    var ownerDocument = globalDocument;
    if (ownerDocument && "string" === typeof href && href) {
      var limitedEscapedHref = escapeSelectorAttributeValueInsideDoubleQuotes(href);
      limitedEscapedHref = 'link[rel="' + rel + '"][href="' + limitedEscapedHref + '"]';
      "string" === typeof crossOrigin && (limitedEscapedHref += '[crossorigin="' + crossOrigin + '"]');
      preconnectsSet.has(limitedEscapedHref) || (preconnectsSet.add(limitedEscapedHref), rel = {
        rel: rel,
        crossOrigin: crossOrigin,
        href: href
      }, null === ownerDocument.querySelector(limitedEscapedHref) && (href =
ownerDocument.createElement("link"), setInitialProperties(href, "link", rel),
markNodeAsHoistable(href), ownerDocument.head.appendChild(href)));
    }
  }
  function getResource(type, currentProps, pendingProps, currentResource) {
    var resourceRoot = (resourceRoot = rootInstanceStackCursor.current) ?
getHoistableRoot(resourceRoot) : null;
    if (!resourceRoot) throw Error('"resourceRoot" was expected to exist. This is a bug in React.');
    switch (type) {
      case "meta":
      case "title":
        return null;
      case "style":
        return "string" === typeof pendingProps.precedence && "string" === typeof pendingProps.href ?
(pendingProps = getStyleKey(pendingProps.href), currentProps =
getResourcesFromRoot(resourceRoot).hoistableStyles, currentResource =
currentProps.get(pendingProps), currentResource || (currentResource = {
          type: "style",
          instance: null,
          count: 0,
          state: null
        }, currentProps.set(pendingProps, currentResource)), currentResource) : {
          type: "void",
          instance: null,
          count: 0,
          state: null
        };
      case "link":
        if ("stylesheet" === pendingProps.rel && "string" === typeof pendingProps.href && "string" ===
typeof pendingProps.precedence) {
          type = getStyleKey(pendingProps.href);
          var _styles = getResourcesFromRoot(resourceRoot).hoistableStyles,
```

```
          _resource = _styles.get(type);
        if (!_resource && (resourceRoot = resourceRoot.ownerDocument || resourceRoot, _resource = {
          type: "stylesheet",
          instance: null,
          count: 0,
          state: {
            loading: NotLoaded,
            preload: null
          }
        }, _styles.set(type, _resource), (_styles =
resourceRoot.querySelector(getStylesheetSelectorFromKey(type))) && !_styles._p &&
(_resource.instance = _styles, _resource.state.loading = Loaded | Inserted), !
preloadPropsMap.has(type))) {
          var preloadProps = {
            rel: "preload",
            as: "style",
            href: pendingProps.href,
            crossOrigin: pendingProps.crossOrigin,
            integrity: pendingProps.integrity,
            media: pendingProps.media,
            hrefLang: pendingProps.hrefLang,
            referrerPolicy: pendingProps.referrerPolicy
          };
          preloadPropsMap.set(type, preloadProps);
          _styles || preloadStylesheet(resourceRoot, type, preloadProps, _resource.state);
        }
        if (currentProps && null === currentResource) throw pendingProps = "\n\n  - " +
describeLinkForResourceErrorDEV(currentProps) + "\n  + " +
describeLinkForResourceErrorDEV(pendingProps), Error("Expected <link> not to update to be
updated to a stylesheet with precedence. Check the `rel`, `href`, and `precedence` props of this
component. Alternatively, check whether two different <link> components render in the same slot or
share the same key." + pendingProps);
        return _resource;
      }
      if (currentProps && null !== currentResource) throw pendingProps = "\n\n  - " +
describeLinkForResourceErrorDEV(currentProps) + "\n  + " +
describeLinkForResourceErrorDEV(pendingProps), Error("Expected stylesheet with precedence to not
be updated to a different kind of <link>. Check the `rel`, `href`, and `precedence` props of this
component. Alternatively, check whether two different <link> components render in the same slot or
share the same key." + pendingProps);
      return null;
    case "script":
      return currentProps = pendingProps.async, pendingProps = pendingProps.src, "string" === typeof
pendingProps && currentProps && "function" !== typeof currentProps && "symbol" !== typeof
currentProps ? (pendingProps = getScriptKey(pendingProps), currentProps =
getResourcesFromRoot(resourceRoot).hoistableScripts, currentResource =
currentProps.get(pendingProps), currentResource || (currentResource = {
        type: "script",
        instance: null,
```

```
          count: 0,
          state: null
        }, currentProps.set(pendingProps, currentResource)), currentResource) : {
          type: "void",
          instance: null,
          count: 0,
          state: null
        };
      default:
        throw Error('getResource encountered a type it did not expect: "' + type + '". this is a bug in
React.');
    }
  }
  function describeLinkForResourceErrorDEV(props) {
    var describedProps = 0,
      description = "<link";
    "string" === typeof props.rel ? (describedProps++, description += ' rel="' + props.rel + '"') :
hasOwnProperty.call(props, "rel") && (describedProps++, description += ' rel="' + (null ===
props.rel ? "null" : "invalid type " + typeof props.rel) + '"');
    "string" === typeof props.href ? (describedProps++, description += ' href="' + props.href + '"') :
hasOwnProperty.call(props, "href") && (describedProps++, description += ' href="' + (null ===
props.href ? "null" : "invalid type " + typeof props.href) + '"');
    "string" === typeof props.precedence ? (describedProps++, description += ' precedence="' +
props.precedence + '"') : hasOwnProperty.call(props, "precedence") && (describedProps++, description
+= " precedence={" + (null === props.precedence ? "null" : "invalid type " + typeof props.precedence)
+ "}");
    Object.getOwnPropertyNames(props).length > describedProps && (description += " ...");
    return description + " />";
  }
  function getStyleKey(href) {
    return 'href="' + escapeSelectorAttributeValueInsideDoubleQuotes(href) + '"';
  }
  function getStylesheetSelectorFromKey(key) {
    return 'link[rel="stylesheet"][' + key + "]";
  }
  function stylesheetPropsFromRawProps(rawProps) {
    return assign({}, rawProps, {
      "data-precedence": rawProps.precedence,
      precedence: null
    });
  }
  function preloadStylesheet(ownerDocument, key, preloadProps, state) {
    ownerDocument.querySelector('link[rel="preload"][as="style"][' + key + "]") ? state.loading =
Loaded : (key = ownerDocument.createElement("link"), state.preload = key,
key.addEventListener("load", function () {
      return state.loading |= Loaded;
    }), key.addEventListener("error", function () {
      return state.loading |= Errored;
    }), setInitialProperties(key, "link", preloadProps), markNodeAsHoistable(key),
```

```
ownerDocument.head.appendChild(key));
  }
  function getScriptKey(src) {
    return '[src="' + escapeSelectorAttributeValueInsideDoubleQuotes(src) + '"]';
  }
  function getScriptSelectorFromKey(key) {
    return "script[async]" + key;
  }
  function acquireResource(hoistableRoot, resource, props) {
    resource.count++;
    if (null === resource.instance) switch (resource.type) {
      case "style":
        var instance = hoistableRoot.querySelector('style[data-href~="' +
escapeSelectorAttributeValueInsideDoubleQuotes(props.href) + '"]');
        if (instance) return resource.instance = instance, markNodeAsHoistable(instance), instance;
        var styleProps = assign({}, props, {
          "data-href": props.href,
          "data-precedence": props.precedence,
          href: null,
          precedence: null
        });
        instance = (hoistableRoot.ownerDocument || hoistableRoot).createElement("style");
        markNodeAsHoistable(instance);
        setInitialProperties(instance, "style", styleProps);
        insertStylesheet(instance, props.precedence, hoistableRoot);
        return resource.instance = instance;
      case "stylesheet":
        styleProps = getStyleKey(props.href);
        var _instance = hoistableRoot.querySelector(getStylesheetSelectorFromKey(styleProps));
        if (_instance) return resource.state.loading |= Inserted, resource.instance = _instance,
markNodeAsHoistable(_instance), _instance;
        instance = stylesheetPropsFromRawProps(props);
        (styleProps = preloadPropsMap.get(styleProps)) && adoptPreloadPropsForStylesheet(instance,
styleProps);
        _instance = (hoistableRoot.ownerDocument || hoistableRoot).createElement("link");
        markNodeAsHoistable(_instance);
        var linkInstance = _instance;
        linkInstance._p = new Promise(function (resolve, reject) {
          linkInstance.onload = resolve;
          linkInstance.onerror = reject;
        });
        setInitialProperties(_instance, "link", instance);
        resource.state.loading |= Inserted;
        insertStylesheet(_instance, props.precedence, hoistableRoot);
        return resource.instance = _instance;
      case "script":
        _instance = getScriptKey(props.src);
        if (styleProps = hoistableRoot.querySelector(getScriptSelectorFromKey(_instance))) return
resource.instance = styleProps, markNodeAsHoistable(styleProps), styleProps;
```

```
        instance = props;
        if (styleProps = preloadPropsMap.get(_instance)) instance = assign({}, props),
adoptPreloadPropsForScript(instance,
 styleProps);
        hoistableRoot = hoistableRoot.ownerDocument || hoistableRoot;
        styleProps = hoistableRoot.createElement("script");
        markNodeAsHoistable(styleProps);
        setInitialProperties(styleProps, "link", instance);
        hoistableRoot.head.appendChild(styleProps);
        return resource.instance = styleProps;
      case "void":
        return null;
      default:
        throw Error('acquireResource encountered a resource type it did not expect: "' + resource.type + '".
this is a bug in React.');
    } else "stylesheet" === resource.type && (resource.state.loading & Inserted) === NotLoaded &&
(instance = resource.instance, resource.state.loading |= Inserted, insertStylesheet(instance,
props.precedence, hoistableRoot));
    return resource.instance;
  }
  function insertStylesheet(instance, precedence, root) {
    for (var nodes = root.querySelectorAll('link[rel="stylesheet"][data-precedence],style[data-
precedence]'), last = nodes.length ? nodes[nodes.length - 1] : null, prior = last, i = 0; i < nodes.length;
i++) {
      var node = nodes[i];
      if (node.dataset.precedence === precedence) prior = node;else if (prior !== last) break;
    }
    prior ? prior.parentNode.insertBefore(instance, prior.nextSibling) : (precedence = 9 ===
root.nodeType ? root.head : root, precedence.insertBefore(instance, precedence.firstChild));
  }
  function adoptPreloadPropsForStylesheet(stylesheetProps, preloadProps) {
    null == stylesheetProps.crossOrigin && (stylesheetProps.crossOrigin = preloadProps.crossOrigin);
    null == stylesheetProps.referrerPolicy && (stylesheetProps.referrerPolicy =
preloadProps.referrerPolicy);
    null == stylesheetProps.title && (stylesheetProps.title = preloadProps.title);
  }
  function adoptPreloadPropsForScript(scriptProps, preloadProps) {
    null == scriptProps.crossOrigin && (scriptProps.crossOrigin = preloadProps.crossOrigin);
    null == scriptProps.referrerPolicy && (scriptProps.referrerPolicy = preloadProps.referrerPolicy);
    null == scriptProps.integrity && (scriptProps.integrity = preloadProps.integrity);
  }
  function getHydratableHoistableCache(type, keyAttribute, ownerDocument) {
    if (null === tagCaches) {
      var cache = new Map();
      var caches = tagCaches = new Map();
      caches.set(ownerDocument, cache);
    } else caches = tagCaches, cache = caches.get(ownerDocument), cache || (cache = new Map(),
caches.set(ownerDocument, cache));
    if (cache.has(type)) return cache;
```

```
    cache.set(type, null);
    ownerDocument = ownerDocument.getElementsByTagName(type);
    for (caches = 0; caches < ownerDocument.length; caches++) {
      var node = ownerDocument[caches];
      if (!(node[internalHoistableMarker] || node[internalInstanceKey] || "link" === type && "stylesheet"
=== node.getAttribute("rel")) && node.namespaceURI !== SVG_NAMESPACE) {
        var nodeKey = node.getAttribute(keyAttribute) || "";
        nodeKey = type + nodeKey;
        var existing = cache.get(nodeKey);
        existing ? existing.push(node) : cache.set(nodeKey, [node]);
      }
    }
    return cache;
  }
  function mountHoistable(hoistableRoot, type, instance) {
    hoistableRoot = hoistableRoot.ownerDocument || hoistableRoot;
    hoistableRoot.head.insertBefore(instance, "title" === type ? hoistableRoot.querySelector("head >
title") : null);
  }
  function isHostHoistableType(type, props, hostContext) {
    var outsideHostContainerContext = !hostContext.ancestorInfo.containerTagInScope;
    if (hostContext.context === HostContextNamespaceSvg || null != props.itemProp) return !
outsideHostContainerContext || null == props.itemProp || "meta" !== type && "title" !== type &&
"style" !== type && "link" !== type && "script" !== type || console.error("Cannot render a <%s>
outside the main document if it has an `itemProp` prop. `itemProp` suggests the tag belongs to an
`itemScope` which can appear anywhere in the DOM. If you were intending for React to hoist this <
%s> remove the `itemProp` prop. Otherwise, try moving this tag into the <head> or <body> of the
Document.", type, type), !1;
    switch (type) {
      case "meta":
      case "title":
        return !0;
      case "style":
        if ("string" !== typeof props.precedence || "string" !== typeof props.href || "" === props.href) {
          outsideHostContainerContext && console.error('Cannot render a <style> outside the main
document without knowing its precedence and a unique href key. React can hoist and deduplicate
<style> tags if you provide a `precedence` prop along with an `href` prop that does not conflic with the
`href` values used in any other hoisted <style> or <link rel="stylesheet" ...> tags.  Note that hoisting
<style> tags is considered an advanced feature that most will not use directly. Consider moving the
<style> tag to the <head> or consider adding a `precedence="default"` and `href="some unique
resource identifier"`, or move the <style> to the <style> tag.');
          break;
        }
        return !0;
      case "link":
        if ("string" !== typeof props.rel || "string" !== typeof props.href || "" === props.href ||
props.onLoad || props.onError) {
          if ("stylesheet" === props.rel && "string" === typeof props.precedence) {
            type = props.href;
```

```
          var onError = props.onError,
            disabled = props.disabled;
          hostContext = [];
          props.onLoad && hostContext.push("`onLoad`");
          onError && hostContext.push("`onError`");
          null != disabled && hostContext.push("`disabled`");
          onError = propNamesListJoin(hostContext, "and");
          onError += 1 === hostContext.length ? " prop" : " props";
          disabled = 1 === hostContext.length ? "an " + onError : "the " + onError;
          hostContext.length && console.error('React encountered a <link rel="stylesheet"
href="%s" ... /> with a `precedence` prop that also included %s. The presence of loading and error
handlers indicates an intent to manage the stylesheet loading state from your from your Component
code and React will not hoist or deduplicate this stylesheet. If your intent was to have React hoist and
deduplciate this stylesheet using the `precedence` prop remove the %s, otherwise remove the
`precedence` prop.', type, disabled, onError);
        }
        outsideHostContainerContext && ("string" !== typeof props.rel || "string" !== typeof props.href
|| "" === props.href ? console.error("Cannot render a <link> outside the main document without a `rel`
and `href` prop. Try adding a `rel` and/or `href` prop to this <link> or moving the link into the <head>
tag") : (props.onError || props.onLoad) && console.error("Cannot render a <link> with onLoad or
onError listeners outside the main document. Try removing onLoad={...} and onError={...} or moving
it into the root <head> tag or somewhere in the <body>."));
        break;
      }
      switch (props.rel) {
        case "stylesheet":
          return type = props.precedence, props = props.disabled, "string" !== typeof type &&
outsideHostContainerContext && console.error('Cannot render a <link rel="stylesheet" /> outside the
main document without knowing its precedence. Consider adding precedence="default" or moving it
into the root <head> tag.'), "string" === typeof type && null == props;
        default:
          return !0;
      }
    case "script":
      type = props.async && "function" !== typeof props.async && "symbol" !== typeof props.async;
      if (!type || props.onLoad || props.onError || !props.src || "string" !== typeof props.src) {
        outsideHostContainerContext && (type ? props.onLoad || props.onError ? console.error("Cannot
render a <script> with onLoad or onError listeners outside the main document. Try removing
onLoad={...} and onError={...} or moving it into the root <head> tag or somewhere in the <body>.") :
console.error("Cannot render a <script> outside the main document without `async={true}` and a non-
empty `src` prop. Ensure there is a valid `src` and either make the script async or move it into the root
<head> tag or somewhere in the <body>.") : console.error('Cannot render a sync or defer <script>
outside the main document without knowing its order. Try adding async="" or moving it into the root
<head> tag.'));
        break;
      }
      return !0;
    case "noscript":
    case "template":
```

```
      outsideHostContainerContext && console.error("Cannot render <%s> outside the main document. Try moving it into the root <head> tag.", type);
    }
    return !1;
  }
  function preloadResource(resource) {
    return "stylesheet" === resource.type && (resource.state.loading & Settled) === NotLoaded ? !1 : !0;
  }
  function noop() {}
  function suspendResource(hoistableRoot, resource, props) {
    if (null === suspendedState) throw Error("Internal React Error: suspendedState null when it was expected to exists. Please report this as a React bug.");
    var state = suspendedState;
    if ("stylesheet" === resource.type && ("string" !== typeof props.media || !1 !== matchMedia(props.media).matches) && (resource.state.loading & Inserted) === NotLoaded) {
      if (null === resource.instance) {
        var key = getStyleKey(props.href),
          instance = hoistableRoot.querySelector(getStylesheetSelectorFromKey(key));
        if (instance) {
          hoistableRoot = instance._p;
          null !== hoistableRoot && "object" === typeof hoistableRoot && "function" === typeof hoistableRoot.then && (state.count++, state = onUnsuspend.bind(state), hoistableRoot.then(state, state));
          resource.state.loading |= Inserted;
          resource.instance = instance;
          markNodeAsHoistable(instance);
          return;
        }
        instance = hoistableRoot.ownerDocument || hoistableRoot;
        props = stylesheetPropsFromRawProps(props);

        (key = preloadPropsMap.get(key)) && adoptPreloadPropsForStylesheet(props, key);
        instance = instance.createElement("link");
        markNodeAsHoistable(instance);
        var linkInstance = instance;
        linkInstance._p = new Promise(function (resolve, reject) {
          linkInstance.onload = resolve;
          linkInstance.onerror = reject;
        });
        setInitialProperties(instance, "link", props);
        resource.instance = instance;
      }
      null === state.stylesheets && (state.stylesheets = new Map());
      state.stylesheets.set(resource, hoistableRoot);
      (hoistableRoot = resource.state.preload) && (resource.state.loading & Settled) === NotLoaded && (state.count++, resource = onUnsuspend.bind(state), hoistableRoot.addEventListener("load", resource), hoistableRoot.addEventListener("error", resource));
    }
```

```
  }
  function waitForCommitToBeReady() {
    if (null === suspendedState) throw Error("Internal React Error: suspendedState null when it was
expected to exists. Please report this as a React bug.");
    var state = suspendedState;
    state.stylesheets && 0 === state.count && insertSuspendedStylesheets(state, state.stylesheets);
    return 0 < state.count ? function (commit) {
      var stylesheetTimer = setTimeout(function () {
        state.stylesheets && insertSuspendedStylesheets(state, state.stylesheets);
        if (state.unsuspend) {
          var unsuspend = state.unsuspend;
          state.unsuspend = null;
          unsuspend();
        }
      }, 6e4);
      state.unsuspend = commit;
      return function () {
        state.unsuspend = null;
        clearTimeout(stylesheetTimer);
      };
    } : null;
  }
  function onUnsuspend() {
    this.count--;
    if (0 === this.count) if (this.stylesheets) insertSuspendedStylesheets(this, this.stylesheets);else if
(this.unsuspend) {
      var unsuspend = this.unsuspend;
      this.unsuspend = null;
      unsuspend();
    }
  }
  function insertSuspendedStylesheets(state, resources) {
    state.stylesheets = null;
    null !== state.unsuspend && (state.count++, precedencesByRoot = new Map(),
resources.forEach(insertStylesheetIntoRoot, state), precedencesByRoot = null,
onUnsuspend.call(state));
  }
  function insertStylesheetIntoRoot(root, resource) {
    if (!(resource.state.loading & Inserted)) {
      var precedences = precedencesByRoot.get(root);
      if (precedences) var last = precedences.get(LAST_PRECEDENCE);else {
        precedences = new Map();
        precedencesByRoot.set(root, precedences);
        for (var nodes = root.querySelectorAll("link[data-precedence],style[data-precedence]"), i = 0; i <
nodes.length; i++) {
          var node = nodes[i];
          if ("LINK" === node.nodeName || "not all" !== node.getAttribute("media"))
precedences.set(node.dataset.precedence, node), last = node;
        }
```

```
      last && precedences.set(LAST_PRECEDENCE, last);
    }
    nodes = resource.instance;
    node = nodes.getAttribute("data-precedence");
    i = precedences.get(node) || last;
    i === last && precedences.set(LAST_PRECEDENCE, nodes);
    precedences.set(node, nodes);
    this.count++;
    last = onUnsuspend.bind(this);
    nodes.addEventListener("load", last);
    nodes.addEventListener("error", last);
    i ? i.parentNode.insertBefore(nodes, i.nextSibling) : (root = 9 === root.nodeType ? root.head : root,
root.insertBefore(nodes, root.firstChild));
    resource.state.loading |= Inserted;
  }
 }
 function bindToConsole(methodName, args, badgeName) {
  var offset = 0;
  switch (methodName) {
    case "dir":
    case "dirxml":
    case "groupEnd":
    case "table":
      return bind.apply(console[methodName], [console].concat(args));
    case "assert":
      offset = 1;
  }
  args = args.slice(0);
  "string" === typeof args[offset] ? args.splice(offset, 1, badgeFormat + args[offset], badgeStyle, pad +
badgeName + pad, resetStyle) : args.splice(offset, 0, badgeFormat, badgeStyle, pad + badgeName +
pad, resetStyle);
  args.unshift(console);
  return bind.apply(console[methodName], args);
 }
 function FiberRootNode(containerInfo, tag, hydrate, identifierPrefix, onUncaughtError,
onCaughtError, onRecoverableError, formState) {
  this.tag = 1;
  this.containerInfo = containerInfo;
  this.finishedWork = this.pingCache = this.current = this.pendingChildren = null;
  this.timeoutHandle = noTimeout;
  this.callbackNode = this.next = this.pendingContext = this.context = this.cancelPendingCommit =
null;
  this.callbackPriority = 0;
  this.expirationTimes = createLaneMap(-1);
  this.entangledLanes = this.shellSuspendCounter = this.errorRecoveryDisabledLanes =
this.finishedLanes = this.expiredLanes = this.warmLanes = this.pingedLanes = this.suspendedLanes =
this.pendingLanes = 0;
  this.entanglements = createLaneMap(0);
  this.hiddenUpdates = createLaneMap(null);
```

```
    this.identifierPrefix = identifierPrefix;
    this.onUncaughtError = onUncaughtError;
    this.onCaughtError = onCaughtError;
    this.onRecoverableError = onRecoverableError;
    this.pooledCache = null;
    this.pooledCacheLanes = 0;
    this.formState = formState;
    this.incompleteTransitions = new Map();
    this.passiveEffectDuration = this.effectDuration = -0;
    this.memoizedUpdaters = new Set();
    containerInfo = this.pendingUpdatersLaneMap = [];
    for (tag = 0; 31 > tag; tag++) containerInfo.push(new Set());
    this._debugRootType = hydrate ? "hydrateRoot()" : "createRoot()";
  }
  function createFiberRoot(containerInfo, tag, hydrate, initialChildren, hydrationCallbacks,
isStrictMode, identifierPrefix, onUncaughtError, onCaughtError, onRecoverableError,
transitionCallbacks, formState) {
    containerInfo = new FiberRootNode(containerInfo, tag, hydrate, identifierPrefix, onUncaughtError,
onCaughtError, onRecoverableError, formState);
    tag = ConcurrentMode;
    !0 === isStrictMode && (tag |= StrictLegacyMode | StrictEffectsMode);
    isDevToolsPresent && (tag |= ProfileMode);
    isStrictMode = createFiber(3, null, null, tag);
    containerInfo.current = isStrictMode;
    isStrictMode.stateNode = containerInfo;
    tag = createCache();
    retainCache(tag);
    containerInfo.pooledCache = tag;
    retainCache(tag);
    isStrictMode.memoizedState = {
      element: initialChildren,
      isDehydrated: hydrate,
      cache: tag
    };
    initializeUpdateQueue(isStrictMode);
    return containerInfo;
  }
  function getContextForSubtree(parentComponent) {
    if (!parentComponent) return emptyContextObject;
    parentComponent = emptyContextObject;
    return parentComponent;
  }
  function updateContainerSync(element, container, parentComponent, callback) {
    0 === container.tag && flushPassiveEffects();
    updateContainerImpl(container.current, 2, element, container, parentComponent, callback);
    return 2;
  }
  function updateContainerImpl(rootFiber, lane, element, container, parentComponent, callback) {
    if (injectedHook && "function" === typeof injectedHook.onScheduleFiberRoot) try {
```

```
      injectedHook.onScheduleFiberRoot(rendererID, container, element);
    } catch (err) {
      hasLoggedError || (hasLoggedError = !0, console.error("React instrumentation encountered an
error: %s", err));
    }
    null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markRenderScheduled &&
injectedProfilingHooks.markRenderScheduled(lane);
    parentComponent = getContextForSubtree(parentComponent);
    null === container.context ? container.context = parentComponent : container.pendingContext =
parentComponent;
    isRendering && null !== current && !didWarnAboutNestedUpdates &&
(didWarnAboutNestedUpdates = !0, console.error("Render methods should be a pure function of props
and state; triggering nested component updates from render is not allowed. If necessary, trigger nested
updates in componentDidUpdate.\n\nCheck the render method of %s.",
getComponentNameFromFiber(current) || "Unknown"));
    container = createUpdate(lane);
    container.payload = {
      element: element
    };
    callback = void 0 === callback ? null : callback;
    null !== callback && ("function" !== typeof callback && console.error("Expected the last optional
`callback` argument to be a function. Instead received: %s.", callback), container.callback = callback);
    element = enqueueUpdate(rootFiber, container, lane);
    null !== element && (scheduleUpdateOnFiber(element, rootFiber, lane),
entangleTransitions(element, rootFiber, lane));
  }
  function markRetryLaneImpl(fiber, retryLane) {
    fiber = fiber.memoizedState;
    if (null !== fiber && null !== fiber.dehydrated) {
      var a = fiber.retryLane;
      fiber.retryLane = 0 !== a && a < retryLane ? a : retryLane;
    }
  }
  function markRetryLaneIfNotHydrated(fiber, retryLane) {
    markRetryLaneImpl(fiber, retryLane);
    (fiber = fiber.alternate) && markRetryLaneImpl(fiber, retryLane);
  }
  function attemptContinuousHydration(fiber) {
    if (13 === fiber.tag) {
      var root = enqueueConcurrentRenderForLane(fiber, 67108864);
      null !== root && scheduleUpdateOnFiber(root, fiber, 67108864);
      markRetryLaneIfNotHydrated(fiber, 67108864);
    }
  }
  function getCurrentFiberForDevTools() {
    return current;
  }
  function getLaneLabelMap() {
```

```
    for (var map = new Map(), lane = 1, index = 0; 31 > index; index++) {
      var label = getLabelForLane(lane);
      map.set(lane, label);
      lane *= 2;
    }
    return map;
  }
  function dispatchDiscreteEvent(domEventName, eventSystemFlags, container, nativeEvent) {
    var prevTransition = ReactSharedInternals.T;
    ReactSharedInternals.T = null;
    var previousPriority = ReactDOMSharedInternals.p;
    try {
      ReactDOMSharedInternals.p = DiscreteEventPriority, dispatchEvent(domEventName,
eventSystemFlags, container, nativeEvent);
    } finally
 {
      ReactDOMSharedInternals.p = previousPriority, ReactSharedInternals.T = prevTransition;
    }
  }
  function dispatchContinuousEvent(domEventName, eventSystemFlags, container, nativeEvent) {
    var prevTransition = ReactSharedInternals.T;
    ReactSharedInternals.T = null;
    var previousPriority = ReactDOMSharedInternals.p;
    try {
      ReactDOMSharedInternals.p = ContinuousEventPriority, dispatchEvent(domEventName,
eventSystemFlags, container, nativeEvent);
    } finally {
      ReactDOMSharedInternals.p = previousPriority, ReactSharedInternals.T = prevTransition;
    }
  }
  function dispatchEvent(domEventName, eventSystemFlags, targetContainer, nativeEvent) {
    if (_enabled) {
      var blockedOn = findInstanceBlockingEvent(nativeEvent);
      if (null === blockedOn) dispatchEventForPluginEventSystem(domEventName, eventSystemFlags,
nativeEvent, return_targetInst, targetContainer), clearIfContinuousEvent(domEventName,
nativeEvent);else if (queueIfContinuousEvent(blockedOn, domEventName, eventSystemFlags,
targetContainer, nativeEvent)) nativeEvent.stopPropagation();else if
(clearIfContinuousEvent(domEventName, nativeEvent), eventSystemFlags & 4 && -1 <
discreteReplayableEvents.indexOf(domEventName)) {
        for (; null !== blockedOn;) {
          var fiber = getInstanceFromNode(blockedOn);
          if (null !== fiber) switch (fiber.tag) {
            case 3:
              fiber = fiber.stateNode;
              if (fiber.current.memoizedState.isDehydrated) {
                var lanes = getHighestPriorityLanes(fiber.pendingLanes);
                if (0 !== lanes) {
                  var root = fiber;
                  root.pendingLanes |= 2;
```

```
              for (root.entangledLanes |= 2; lanes;) {
                var lane = 1 << 31 - clz32(lanes);
                root.entanglements[1] |= lane;
                lanes &= ~lane;
              }
              ensureRootIsScheduled(fiber);
              (executionContext & (RenderContext | CommitContext)) === NoContext &&
(workInProgressRootRenderTargetTime = now$1() + RENDER_TIMEOUT_MS,
flushSyncWorkAcrossRoots_impl(0, !1));
            }
          }
          break;
        case 13:
          root = enqueueConcurrentRenderForLane(fiber, 2), null !== root &&
scheduleUpdateOnFiber(root, fiber, 2), flushSyncWork$1(), markRetryLaneIfNotHydrated(fiber, 2);
      }
      fiber = findInstanceBlockingEvent(nativeEvent);
      null === fiber && dispatchEventForPluginEventSystem(domEventName, eventSystemFlags,
nativeEvent, return_targetInst, targetContainer);
      if (fiber === blockedOn) break;
      blockedOn = fiber;
    }
    null !== blockedOn && nativeEvent.stopPropagation();
  } else dispatchEventForPluginEventSystem(domEventName, eventSystemFlags, nativeEvent, null,
targetContainer);
 }
}
function findInstanceBlockingEvent(nativeEvent) {
 nativeEvent = getEventTarget(nativeEvent);
 return findInstanceBlockingTarget(nativeEvent);
}
function findInstanceBlockingTarget(targetNode) {
 return_targetInst = null;
 targetNode = getClosestInstanceFromNode(targetNode);
 if (null !== targetNode) {
  var nearestMounted = getNearestMountedFiber(targetNode);
  if (null === nearestMounted) targetNode = null;else {
   var tag = nearestMounted.tag;
   if (13 === tag) {
    targetNode = getSuspenseInstanceFromFiber(nearestMounted);
    if (null !== targetNode) return targetNode;
    targetNode = null;
   } else if (3 === tag) {
    if (nearestMounted.stateNode.current.memoizedState.isDehydrated) return 3 ===
nearestMounted.tag ? nearestMounted.stateNode.containerInfo : null;
    targetNode = null;
   } else nearestMounted !== targetNode && (targetNode = null);
  }
 }
```

```
  return_targetInst = targetNode;
  return null;
}
function getEventPriority(domEventName) {
  switch (domEventName) {
    case "beforetoggle":
    case "cancel":
    case "click":
    case "close":
    case "contextmenu":
    case "copy":
    case "cut":
    case "auxclick":
    case "dblclick":
    case "dragend":
    case "dragstart":
    case "drop":
    case "focusin":
    case "focusout":
    case "input":
    case "invalid":
    case "keydown":
    case "keypress":
    case "keyup":
    case "mousedown":
    case "mouseup":
    case "paste":
    case "pause":
    case "play":
    case "pointercancel":
    case "pointerdown":
    case "pointerup":
    case "ratechange":
    case "reset":
    case "resize":
    case "seeked":
    case "submit":
    case "toggle":
    case "touchcancel":
    case "touchend":
    case "touchstart":
    case "volumechange":
    case "change":
    case "selectionchange":
    case "textInput":
    case "compositionstart":
    case "compositionend":
    case "compositionupdate":
    case "beforeblur":
```

```
    case "afterblur":
    case "beforeinput":
    case "blur":
    case "fullscreenchange":
    case "focus":
    case "hashchange":
    case "popstate":
    case "select":
    case "selectstart":
      return DiscreteEventPriority;
    case "drag":
    case "dragenter":
    case "dragexit":
    case "dragleave":
    case "dragover":
    case "mousemove":
    case "mouseout":
    case "mouseover":
    case "pointermove":
    case "pointerout":
    case "pointerover":
    case "scroll":
    case "touchmove":
    case "wheel":
    case "mouseenter":
    case "mouseleave":
    case "pointerenter":
    case "pointerleave":
      return ContinuousEventPriority;
    case "message":
      switch (getCurrentPriorityLevel()) {
        case ImmediatePriority:
          return DiscreteEventPriority;
        case UserBlockingPriority:
          return ContinuousEventPriority;
        case NormalPriority$1:
        case LowPriority:
          return DefaultEventPriority;
        case IdlePriority:
          return IdleEventPriority;
        default:
          return DefaultEventPriority;
      }
    default:
      return DefaultEventPriority;
  }
}
function clearIfContinuousEvent(domEventName, nativeEvent) {
  switch (domEventName) {
```

```
      case "focusin":
      case "focusout":
        queuedFocus = null;
        break;
      case "dragenter":
      case "dragleave":
        queuedDrag = null;
        break;
      case "mouseover":
      case "mouseout":
        queuedMouse = null;
        break;
      case "pointerover":
      case "pointerout":
        queuedPointers.delete(nativeEvent.pointerId);
        break;
      case "gotpointercapture":
      case "lostpointercapture":
        queuedPointerCaptures.delete(nativeEvent.pointerId);
    }
  }
  function accumulateOrCreateContinuousQueuedReplayableEvent(existingQueuedEvent, blockedOn,
domEventName, eventSystemFlags, targetContainer, nativeEvent) {
    if (null === existingQueuedEvent || existingQueuedEvent.nativeEvent !== nativeEvent) return
existingQueuedEvent = {
      blockedOn: blockedOn,
      domEventName: domEventName,
      eventSystemFlags: eventSystemFlags,
      nativeEvent: nativeEvent,
      targetContainers: [targetContainer]
    }, null !== blockedOn && (blockedOn = getInstanceFromNode(blockedOn), null !== blockedOn
&& attemptContinuousHydration(blockedOn)), existingQueuedEvent;
    existingQueuedEvent.eventSystemFlags |= eventSystemFlags;
    blockedOn = existingQueuedEvent.targetContainers;
    null !== targetContainer && -1 === blockedOn.indexOf(targetContainer) &&
blockedOn.push(targetContainer);
    return existingQueuedEvent;
  }
  function queueIfContinuousEvent(blockedOn, domEventName, eventSystemFlags, targetContainer,
nativeEvent) {
    switch (domEventName) {
      case "focusin":
        return queuedFocus = accumulateOrCreateContinuousQueuedReplayableEvent(queuedFocus,
blockedOn, domEventName, eventSystemFlags, targetContainer, nativeEvent), !0;
      case "dragenter":
        return queuedDrag = accumulateOrCreateContinuousQueuedReplayableEvent(queuedDrag,
blockedOn, domEventName, eventSystemFlags, targetContainer, nativeEvent), !0;
      case "mouseover":
        return queuedMouse = accumulateOrCreateContinuousQueuedReplayableEvent(queuedMouse,
```

```
blockedOn, domEventName, eventSystemFlags, targetContainer, nativeEvent), !0;
      case "pointerover":
       var pointerId = nativeEvent.pointerId;
       queuedPointers.set(pointerId,
accumulateOrCreateContinuousQueuedReplayableEvent(queuedPointers.get(pointerId) || null,
blockedOn, domEventName, eventSystemFlags, targetContainer, nativeEvent));
       return !0;
      case "gotpointercapture":
       return pointerId = nativeEvent.pointerId, queuedPointerCaptures.set(pointerId,
accumulateOrCreateContinuousQueuedReplayableEvent(queuedPointerCaptures.get(pointerId) || null,
blockedOn, domEventName, eventSystemFlags, targetContainer, nativeEvent)), !0;
    }
    return !1;
  }
  function attemptExplicitHydrationTarget(queuedTarget) {
    var targetInst = getClosestInstanceFromNode(queuedTarget.target);
    if (null !== targetInst) {
      var nearestMounted = getNearestMountedFiber(targetInst);
      if (null !== nearestMounted) if (targetInst = nearestMounted.tag, 13 === targetInst) {
        if (targetInst = getSuspenseInstanceFromFiber(nearestMounted), null !== targetInst) {
          queuedTarget.blockedOn = targetInst;
          runWithPriority(queuedTarget.priority, function () {
            if (13 === nearestMounted.tag) {
              var lane = requestUpdateLane(nearestMounted),
                root = enqueueConcurrentRenderForLane(nearestMounted, lane);
              null !== root && scheduleUpdateOnFiber(root, nearestMounted, lane);
              markRetryLaneIfNotHydrated(nearestMounted,
 lane);
            }
          });
          return;
        }
      } else if (3 === targetInst && nearestMounted.stateNode.current.memoizedState.isDehydrated) {
        queuedTarget.blockedOn = 3 === nearestMounted.tag ? nearestMounted.stateNode.containerInfo :
null;
        return;
      }
    }
    queuedTarget.blockedOn = null;
  }
  function attemptReplayContinuousQueuedEvent(queuedEvent) {
    if (null !== queuedEvent.blockedOn) return !1;
    for (var targetContainers = queuedEvent.targetContainers; 0 < targetContainers.length;) {
      var nextBlockedOn = findInstanceBlockingEvent(queuedEvent.nativeEvent);
      if (null === nextBlockedOn) {
        nextBlockedOn = queuedEvent.nativeEvent;
        var nativeEventClone = new nextBlockedOn.constructor(nextBlockedOn.type, nextBlockedOn),
          event = nativeEventClone;
        null !== currentReplayingEvent && console.error("Expected currently replaying event to be null.
```

```
This error is likely caused by a bug in React. Please file an issue.");
        currentReplayingEvent = event;
        nextBlockedOn.target.dispatchEvent(nativeEventClone);
        null === currentReplayingEvent && console.error("Expected currently replaying event to not be
null. This error is likely caused by a bug in React. Please file an issue.");
        currentReplayingEvent = null;
      } else return targetContainers = getInstanceFromNode(nextBlockedOn), null !== targetContainers
&& attemptContinuousHydration(targetContainers), queuedEvent.blockedOn = nextBlockedOn, !1;
      targetContainers.shift();
    }
    return !0;
  }
  function attemptReplayContinuousQueuedEventInMap(queuedEvent, key, map) {
    attemptReplayContinuousQueuedEvent(queuedEvent) && map.delete(key);
  }
  function replayUnblockedEvents() {
    hasScheduledReplayAttempt = !1;
    null !== queuedFocus && attemptReplayContinuousQueuedEvent(queuedFocus) && (queuedFocus
= null);
    null !== queuedDrag && attemptReplayContinuousQueuedEvent(queuedDrag) && (queuedDrag =
null);
    null !== queuedMouse && attemptReplayContinuousQueuedEvent(queuedMouse) &&
(queuedMouse = null);
    queuedPointers.forEach(attemptReplayContinuousQueuedEventInMap);
    queuedPointerCaptures.forEach(attemptReplayContinuousQueuedEventInMap);
  }
  function scheduleCallbackIfUnblocked(queuedEvent, unblocked) {
    queuedEvent.blockedOn === unblocked && (queuedEvent.blockedOn = null,
hasScheduledReplayAttempt || (hasScheduledReplayAttempt = !0,
Scheduler.unstable_scheduleCallback(Scheduler.unstable_NormalPriority, replayUnblockedEvents)));
  }
  function scheduleReplayQueueIfNeeded(formReplayingQueue) {
    lastScheduledReplayQueue !== formReplayingQueue && (lastScheduledReplayQueue =
formReplayingQueue, Scheduler.unstable_scheduleCallback(Scheduler.unstable_NormalPriority,
function () {
      lastScheduledReplayQueue === formReplayingQueue && (lastScheduledReplayQueue = null);
      for (var i = 0; i < formReplayingQueue.length; i += 3) {
        var form = formReplayingQueue[i],
          submitterOrAction = formReplayingQueue[i + 1],
          formData = formReplayingQueue[i + 2];
        if ("function" !== typeof submitterOrAction) if (null ===
findInstanceBlockingTarget(submitterOrAction || form)) continue;else break;
        var formInst = getInstanceFromNode(form);
        null !== formInst && (formReplayingQueue.splice(i, 3), i -= 3, form = {
          pending: !0,
          data: formData,
          method: form.method,
          action: submitterOrAction
        }, Object.freeze(form), startHostTransition(formInst, form, submitterOrAction, formData));
```

```
      }
    }));
  }
  function retryIfBlockedOn(unblocked) {
    function unblock(queuedEvent) {
      return scheduleCallbackIfUnblocked(queuedEvent, unblocked);
    }
    null !== queuedFocus && scheduleCallbackIfUnblocked(queuedFocus, unblocked);
    null !== queuedDrag && scheduleCallbackIfUnblocked(queuedDrag, unblocked);
    null !== queuedMouse && scheduleCallbackIfUnblocked(queuedMouse, unblocked);
    queuedPointers.forEach(unblock);
    queuedPointerCaptures.forEach(unblock);
    for (var i = 0; i < queuedExplicitHydrationTargets.length; i++) {
      var queuedTarget = queuedExplicitHydrationTargets[i];
      queuedTarget.blockedOn === unblocked && (queuedTarget.blockedOn = null);
    }
    for (; 0 < queuedExplicitHydrationTargets.length && (i = queuedExplicitHydrationTargets[0], null
=== i.blockedOn);) attemptExplicitHydrationTarget(i), null === i.blockedOn &&
queuedExplicitHydrationTargets.shift();
    i = (unblocked.ownerDocument || unblocked).$$reactFormReplay;
    if (null != i) for (queuedTarget = 0; queuedTarget < i.length; queuedTarget += 3) {
      var form = i[queuedTarget],
        submitterOrAction = i[queuedTarget + 1],
        formProps = form[internalPropsKey] || null;
      if ("function" === typeof submitterOrAction) formProps || scheduleReplayQueueIfNeeded(i);else if
(formProps) {
        var action = null;
        if (submitterOrAction && submitterOrAction.hasAttribute("formAction")) {
          if (form = submitterOrAction, formProps = submitterOrAction[internalPropsKey] || null) action
= formProps.formAction;else {
            if (null !== findInstanceBlockingTarget(form)) continue;
          }
        } else action = formProps.action;
        "function" === typeof action ? i[queuedTarget + 1] = action : (i.splice(queuedTarget, 3),
queuedTarget -= 3);
        scheduleReplayQueueIfNeeded(i);
      }
    }
  }
  function ReactDOMRoot(internalRoot) {
    this._internalRoot = internalRoot;
  }
  function ReactDOMHydrationRoot(internalRoot) {
    this._internalRoot = internalRoot;
  }
  function warnIfReactDOMContainerInDEV(container) {
    container[internalContainerInstanceKey] && (container._reactRootContainer ? console.error("You
are calling ReactDOMClient.createRoot() on a container that was previously passed to
ReactDOM.render(). This is not supported.") : console.error("You are calling
```

```
ReactDOMClient.createRoot() on a container that has already been passed to createRoot() before.
Instead, call root.render() on the existing root instead if you want to update it."));
  }
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart(Error());
  var Scheduler = __webpack_require__(/*! scheduler */ "./node_modules/scheduler/index.js"),
    React = __webpack_require__(/*! react */ "./node_modules/react/index.js"),
    ReactDOM = __webpack_require__(/*! react-dom */ "./node_modules/react-dom/index.js"),
    REACT_LEGACY_ELEMENT_TYPE = Symbol.for("react.element"),
    REACT_ELEMENT_TYPE = Symbol.for("react.transitional.element"),
    REACT_PORTAL_TYPE = Symbol.for("react.portal"),
    REACT_FRAGMENT_TYPE = Symbol.for("react.fragment"),
    REACT_STRICT_MODE_TYPE = Symbol.for("react.strict_mode"),
    REACT_PROFILER_TYPE = Symbol.for("react.profiler"),
    REACT_PROVIDER_TYPE = Symbol.for("react.provider"),
    REACT_CONSUMER_TYPE = Symbol.for("react.consumer"),
    REACT_CONTEXT_TYPE = Symbol.for("react.context"),
    REACT_FORWARD_REF_TYPE = Symbol.for("react.forward_ref"),
    REACT_SUSPENSE_TYPE = Symbol.for("react.suspense"),
    REACT_SUSPENSE_LIST_TYPE = Symbol.for("react.suspense_list"),
    REACT_MEMO_TYPE = Symbol.for("react.memo"),
    REACT_LAZY_TYPE = Symbol.for("react.lazy");
  Symbol.for("react.scope");
  Symbol.for("react.debug_trace_mode");
  var REACT_OFFSCREEN_TYPE = Symbol.for("react.offscreen");
  Symbol.for("react.legacy_hidden");
  Symbol.for("react.tracing_marker");
  var REACT_MEMO_CACHE_SENTINEL = Symbol.for("react.memo_cache_sentinel"),
    MAYBE_ITERATOR_SYMBOL = Symbol.iterator,
    REACT_CLIENT_REFERENCE = Symbol.for("react.client.reference"),
    ReactSharedInternals =
React.__CLIENT_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRAD
E,
    assign = Object.assign,
    disabledDepth = 0,
    prevLog,
    prevInfo,
    prevWarn,
    prevError,
    prevGroup,
    prevGroupCollapsed,
    prevGroupEnd;
  disabledLog.__reactDisabledLog = !0;
  var prefix,
    suffix,
    reentry = !1;
  var componentFrameCache = new ("function" === typeof WeakMap ? WeakMap : Map)();
  var current = null,
```

```
    isRendering = !1,
    isArrayImpl = Array.isArray,
    ReactDOMSharedInternals =
ReactDOM.__DOM_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGR
ADE,
    NotPending = Object.freeze({
      pending: !1,
      data: null,
      method: null,
      action: null
    }),
    valueStack = [];
  var fiberStack = [];
  var index$jscomp$0 = -1,
    contextStackCursor = createCursor(null),
    contextFiberStackCursor = createCursor(null),
    rootInstanceStackCursor = createCursor(null),
    hostTransitionProviderCursor = createCursor(null),
    hasOwnProperty = Object.prototype.hasOwnProperty,
    scheduleCallback$3 = Scheduler.unstable_scheduleCallback,
    cancelCallback$1 = Scheduler.unstable_cancelCallback,
    shouldYield = Scheduler.unstable_shouldYield,
    requestPaint = Scheduler.unstable_requestPaint,
    now$1 = Scheduler.unstable_now,
    getCurrentPriorityLevel = Scheduler.unstable_getCurrentPriorityLevel,
    ImmediatePriority = Scheduler.unstable_ImmediatePriority,
    UserBlockingPriority = Scheduler.unstable_UserBlockingPriority,
    NormalPriority$1 = Scheduler.unstable_NormalPriority,
    LowPriority = Scheduler.unstable_LowPriority,
    IdlePriority = Scheduler.unstable_IdlePriority,
    log$1 = Scheduler.log,
    unstable_setDisableYieldValue = Scheduler.unstable_setDisableYieldValue,
    rendererID = null,
    injectedHook = null,
    injectedProfilingHooks = null,
    hasLoggedError = !1,
    isDevToolsPresent = "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__,
    clz32 = Math.clz32 ? Math.clz32 : clz32Fallback,
    log = Math.log,
    LN2 = Math.LN2,
    nextTransitionLane = 128,

   nextRetryLane = 4194304,
    DiscreteEventPriority = 2,
    ContinuousEventPriority = 8,
    DefaultEventPriority = 32,
    IdleEventPriority = 268435456,
    randomKey = Math.random().toString(36).slice(2),
    internalInstanceKey = "__reactFiber$" + randomKey,
```

```
    internalPropsKey = "__reactProps$" + randomKey,
    internalContainerInstanceKey = "__reactContainer$" + randomKey,
    internalEventHandlersKey = "__reactEvents$" + randomKey,
    internalEventHandlerListenersKey = "__reactListeners$" + randomKey,
    internalEventHandlesSetKey = "__reactHandles$" + randomKey,
    internalRootNodeResourcesKey = "__reactResources$" + randomKey,
    internalHoistableMarker = "__reactMarker$" + randomKey,
    allNativeEvents = new Set(),
    registrationNameDependencies = {},
    possibleRegistrationNames = {},
    canUseDOM = !("undefined" === typeof window || "undefined" === typeof window.document ||
"undefined" === typeof window.document.createElement),
    hasReadOnlyValue = {
      button: !0,
      checkbox: !0,
      image: !0,
      hidden: !0,
      radio: !0,
      reset: !0,
      submit: !0
    },
    VALID_ATTRIBUTE_NAME_REGEX = RegExp("^[:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD][:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD\\-.0-
9\\u00B7\\u0300-\\u036F\\u203F-\\u2040]*$"),
    illegalAttributeNameCache = {},
    validatedAttributeNameCache = {},
    escapeSelectorAttributeValueInsideDoubleQuotesRegex = /[\n"\\]/g,
    didWarnValueDefaultValue$1 = !1,
    didWarnCheckedDefaultChecked = !1,
    didWarnSelectedSetOnOption = !1,
    didWarnInvalidChild = !1,
    didWarnInvalidInnerHTML = !1;
  var didWarnValueDefaultValue = !1;
  var valuePropNames = ["value", "defaultValue"],
    didWarnValDefaultVal = !1,
    needsEscaping = /["'&<>\n\t]|^\s|\s$/,
    specialTags = "address applet area article aside base basefont bgsound blockquote body br button
caption center col colgroup dd details dir div dl dt embed fieldset figcaption figure footer form frame
frameset h1 h2 h3 h4 h5 h6 head header hgroup hr html iframe img input isindex li link listing main
marquee menu menuitem meta nav noembed noframes noscript object ol p param plaintext pre script
section select source style summary table tbody td template textarea tfoot th thead title tr track ul wbr
xmp".split(" "),
    inScopeTags = "applet caption html table td th marquee object template foreignObject desc
title".split(" "),
    buttonScopeTags = inScopeTags.concat(["button"]),
    impliedEndTags = "dd dt li option optgroup p rp rt".split(" "),
```

```
    emptyAncestorInfoDev = {
      current: null,
      formTag: null,
      aTagInScope: null,
      buttonTagInScope: null,
      nobrTagInScope: null,
      pTagInButtonScope: null,
      listItemTagAutoclosing: null,
      dlItemTagAutoclosing: null,
      containerTagInScope: null
    },
    didWarn = {},
    MATH_NAMESPACE = "http://www.w3.org/1998/Math/MathML",
    SVG_NAMESPACE = "http://www.w3.org/2000/svg",
    shorthandToLonghand = {
      animation: "animationDelay animationDirection animationDuration animationFillMode
animationIterationCount animationName animationPlayState animationTimingFunction".split(" "),
      background: "backgroundAttachment backgroundClip backgroundColor backgroundImage
backgroundOrigin backgroundPositionX backgroundPositionY backgroundRepeat
backgroundSize".split(" "),
      backgroundPosition: ["backgroundPositionX", "backgroundPositionY"],
      border: "borderBottomColor borderBottomStyle borderBottomWidth borderImageOutset
borderImageRepeat borderImageSlice borderImageSource borderImageWidth borderLeftColor
borderLeftStyle borderLeftWidth borderRightColor borderRightStyle borderRightWidth
borderTopColor borderTopStyle borderTopWidth".split(" "),
      borderBlockEnd: ["borderBlockEndColor", "borderBlockEndStyle", "borderBlockEndWidth"],
      borderBlockStart: ["borderBlockStartColor", "borderBlockStartStyle", "borderBlockStartWidth"],
      borderBottom: ["borderBottomColor", "borderBottomStyle", "borderBottomWidth"],
      borderColor: ["borderBottomColor", "borderLeftColor", "borderRightColor", "borderTopColor"],
      borderImage: ["borderImageOutset", "borderImageRepeat", "borderImageSlice",
"borderImageSource", "borderImageWidth"],
      borderInlineEnd: ["borderInlineEndColor", "borderInlineEndStyle", "borderInlineEndWidth"],
      borderInlineStart: ["borderInlineStartColor", "borderInlineStartStyle", "borderInlineStartWidth"],
      borderLeft: ["borderLeftColor", "borderLeftStyle", "borderLeftWidth"],
      borderRadius: ["borderBottomLeftRadius", "borderBottomRightRadius", "borderTopLeftRadius",
"borderTopRightRadius"],
      borderRight: ["borderRightColor", "borderRightStyle", "borderRightWidth"],
      borderStyle: ["borderBottomStyle", "borderLeftStyle", "borderRightStyle", "borderTopStyle"],
      borderTop: ["borderTopColor", "borderTopStyle", "borderTopWidth"],
      borderWidth: ["borderBottomWidth", "borderLeftWidth", "borderRightWidth", "borderTopWidth"],
      columnRule: ["columnRuleColor", "columnRuleStyle", "columnRuleWidth"],
      columns: ["columnCount", "columnWidth"],
      flex: ["flexBasis", "flexGrow", "flexShrink"],
      flexFlow: ["flexDirection", "flexWrap"],
      font: "fontFamily fontFeatureSettings fontKerning fontLanguageOverride fontSize fontSizeAdjust
fontStretch fontStyle fontVariant fontVariantAlternates fontVariantCaps fontVariantEastAsian
fontVariantLigatures fontVariantNumeric fontVariantPosition fontWeight lineHeight".split(" "),
      fontVariant: "fontVariantAlternates fontVariantCaps fontVariantEastAsian fontVariantLigatures
fontVariantNumeric fontVariantPosition".split(" "),
```

```
    gap: ["columnGap", "rowGap"],
    grid: "gridAutoColumns gridAutoFlow gridAutoRows gridTemplateAreas gridTemplateColumns
gridTemplateRows".split(" "),
    gridArea: ["gridColumnEnd", "gridColumnStart", "gridRowEnd", "gridRowStart"],
    gridColumn: ["gridColumnEnd", "gridColumnStart"],
    gridColumnGap: ["columnGap"],
    gridGap: ["columnGap", "rowGap"],
    gridRow: ["gridRowEnd", "gridRowStart"],
    gridRowGap: ["rowGap"],
    gridTemplate: ["gridTemplateAreas", "gridTemplateColumns", "gridTemplateRows"],
    listStyle: ["listStyleImage", "listStylePosition", "listStyleType"],
    margin: ["marginBottom", "marginLeft", "marginRight", "marginTop"],
    marker: ["markerEnd", "markerMid", "markerStart"],
    mask: "maskClip maskComposite maskImage maskMode maskOrigin maskPositionX
maskPositionY maskRepeat maskSize".split(" "),
    maskPosition: ["maskPositionX", "maskPositionY"],
    outline: ["outlineColor", "outlineStyle", "outlineWidth"],
    overflow: ["overflowX", "overflowY"],
    padding: ["paddingBottom", "paddingLeft", "paddingRight", "paddingTop"],
    placeContent: ["alignContent", "justifyContent"],
    placeItems: ["alignItems", "justifyItems"],
    placeSelf: ["alignSelf", "justifySelf"],
    textDecoration: ["textDecorationColor", "textDecorationLine", "textDecorationStyle"],
    textEmphasis: ["textEmphasisColor", "textEmphasisStyle"],
    transition: ["transitionDelay", "transitionDuration", "transitionProperty",
"transitionTimingFunction"],
    wordWrap: ["overflowWrap"]
  },
  uppercasePattern = /([A-Z])/g,
  msPattern$1 = /^ms-/,
  badVendoredStyleNamePattern = /^(?:webkit|moz|o)[A-Z]/,
  msPattern = /^-ms-/,
  hyphenPattern = /-(.)/g,
  badStyleValueWithSemicolonPattern = /;\s*$/,
  warnedStyleNames = {},
  warnedStyleValues = {},
  warnedForNaNValue = !1,
  warnedForInfinityValue = !1,
  unitlessNumbers = new Set("animationIterationCount aspectRatio borderImageOutset
borderImageSlice borderImageWidth boxFlex boxFlexGroup boxOrdinalGroup columnCount columns
flex flexGrow flexPositive flexShrink flexNegative flexOrder gridArea gridRow gridRowEnd
gridRowSpan gridRowStart gridColumn gridColumnEnd gridColumnSpan gridColumnStart
fontWeight lineClamp lineHeight opacity order orphans scale tabSize widows zIndex zoom fillOpacity
floodOpacity stopOpacity strokeDasharray strokeDashoffset strokeMiterlimit strokeOpacity
strokeWidth MozAnimationIterationCount MozBoxFlex MozBoxFlexGroup MozLineClamp
msAnimationIterationCount msFlex msZoom msFlexGrow msFlexNegative msFlexOrder
msFlexPositive msFlexShrink msGridColumn msGridColumnSpan msGridRow msGridRowSpan
WebkitAnimationIterationCount WebkitBoxFlex WebKitBoxFlexGroup WebkitBoxOrdinalGroup
WebkitColumnCount WebkitColumns WebkitFlex WebkitFlexGrow WebkitFlexPositive
```

```
WebkitFlexShrink WebkitLineClamp".split(" ")),
    aliases = new Map([["acceptCharset", "accept-charset"], ["htmlFor", "for"], ["httpEquiv", "http-
equiv"], ["crossOrigin", "crossorigin"], ["accentHeight", "accent-height"], ["alignmentBaseline",
"alignment-baseline"], ["arabicForm", "arabic-form"], ["baselineShift", "baseline-shift"], ["capHeight",
"cap-height"], ["clipPath", "clip-path"], ["clipRule", "clip-rule"], ["colorInterpolation", "color-
interpolation"], ["colorInterpolationFilters", "color-interpolation-filters"], ["colorProfile", "color-
profile"], ["colorRendering", "color-rendering"], ["dominantBaseline", "dominant-baseline"],
["enableBackground", "enable-background"], ["fillOpacity", "fill-opacity"], ["fillRule", "fill-rule"],
["floodColor", "flood-color"], ["floodOpacity", "flood-opacity"], ["fontFamily", "font-family"],
["fontSize", "font-size"], ["fontSizeAdjust", "font-size-adjust"], ["fontStretch", "font-stretch"],
["fontStyle", "font-style"], ["fontVariant", "font-variant"], ["fontWeight", "font-weight"],
["glyphName", "glyph-name"], ["glyphOrientationHorizontal", "glyph-orientation-horizontal"],
 ["glyphOrientationVertical", "glyph-orientation-vertical"], ["horizAdvX", "horiz-adv-x"],
["horizOriginX", "horiz-origin-x"], ["imageRendering", "image-rendering"], ["letterSpacing", "letter-
spacing"], ["lightingColor", "lighting-color"], ["markerEnd", "marker-end"], ["markerMid", "marker-
mid"], ["markerStart", "marker-start"], ["overlinePosition", "overline-position"], ["overlineThickness",
"overline-thickness"], ["paintOrder", "paint-order"], ["panose-1", "panose-1"], ["pointerEvents",
"pointer-events"], ["renderingIntent", "rendering-intent"], ["shapeRendering", "shape-rendering"],
["stopColor", "stop-color"], ["stopOpacity", "stop-opacity"], ["strikethroughPosition", "strikethrough-
position"], ["strikethroughThickness", "strikethrough-thickness"], ["strokeDasharray", "stroke-
dasharray"], ["strokeDashoffset", "stroke-dashoffset"], ["strokeLinecap", "stroke-linecap"],
["strokeLinejoin", "stroke-linejoin"], ["strokeMiterlimit", "stroke-miterlimit"], ["strokeOpacity",
"stroke-opacity"], ["strokeWidth", "stroke-width"], ["textAnchor", "text-anchor"], ["textDecoration",
"text-decoration"], ["textRendering", "text-rendering"], ["transformOrigin", "transform-origin"],
["underlinePosition", "underline-position"], ["underlineThickness", "underline-thickness"],
["unicodeBidi", "unicode-bidi"], ["unicodeRange", "unicode-range"], ["unitsPerEm", "units-per-em"],
["vAlphabetic", "v-alphabetic"], ["vHanging", "v-hanging"], ["vIdeographic", "v-ideographic"],
["vMathematical", "v-mathematical"], ["vectorEffect", "vector-effect"], ["vertAdvY", "vert-adv-y"],
["vertOriginX", "vert-origin-x"], ["vertOriginY", "vert-origin-y"], ["wordSpacing", "word-spacing"],
["writingMode", "writing-mode"], ["xmlnsXlink", "xmlns:xlink"], ["xHeight", "x-height"]]),
    possibleStandardNames = {
      accept: "accept",
      acceptcharset: "acceptCharset",
      "accept-charset": "acceptCharset",
      accesskey: "accessKey",
      action: "action",
      allowfullscreen: "allowFullScreen",
      alt: "alt",
      as: "as",
      async: "async",
      autocapitalize: "autoCapitalize",
      autocomplete: "autoComplete",
      autocorrect: "autoCorrect",
      autofocus: "autoFocus",
      autoplay: "autoPlay",
      autosave: "autoSave",
      capture: "capture",
      cellpadding: "cellPadding",
      cellspacing: "cellSpacing",
```

challenge: "challenge",
charset: "charSet",
checked: "checked",
children: "children",
cite: "cite",
class: "className",
classid: "classID",
classname: "className",
cols: "cols",
colspan: "colSpan",
content: "content",
contenteditable: "contentEditable",
contextmenu: "contextMenu",
controls: "controls",
controlslist: "controlsList",
coords: "coords",
crossorigin: "crossOrigin",
dangerouslysetinnerhtml: "dangerouslySetInnerHTML",
data: "data",
datetime: "dateTime",
default: "default",
defaultchecked: "defaultChecked",
defaultvalue: "defaultValue",
defer: "defer",
dir: "dir",
disabled: "disabled",
disablepictureinpicture: "disablePictureInPicture",
disableremoteplayback: "disableRemotePlayback",
download: "download",
draggable: "draggable",
enctype: "encType",
enterkeyhint: "enterKeyHint",
fetchpriority: "fetchPriority",
for: "htmlFor",
form: "form",
formmethod: "formMethod",
formaction: "formAction",
formenctype: "formEncType",
formnovalidate: "formNoValidate",
formtarget: "formTarget",
frameborder: "frameBorder",
headers: "headers",
height: "height",
hidden: "hidden",
high: "high",
href: "href",
hreflang: "hrefLang",
htmlfor: "htmlFor",
httpequiv: "httpEquiv",

"http-equiv": "httpEquiv",
icon: "icon",
id: "id",
imagesizes: "imageSizes",
imagesrcset: "imageSrcSet",
inert: "inert",
innerhtml: "innerHTML",
inputmode: "inputMode",
integrity: "integrity",
is: "is",
itemid: "itemID",
itemprop: "itemProp",
itemref: "itemRef",
itemscope: "itemScope",
itemtype: "itemType",
keyparams: "keyParams",
keytype: "keyType",
kind: "kind",
label: "label",
lang: "lang",
list: "list",
loop: "loop",
low: "low",
manifest: "manifest",
marginwidth: "marginWidth",
marginheight: "marginHeight",
max: "max",
maxlength: "maxLength",
media: "media",
mediagroup: "mediaGroup",
method: "method",
min: "min",
minlength: "minLength",
multiple: "multiple",
muted: "muted",
name: "name",
nomodule: "noModule",
nonce: "nonce",
novalidate: "noValidate",
open: "open",
optimum: "optimum",
pattern: "pattern",
placeholder: "placeholder",
playsinline: "playsInline",
poster: "poster",
preload: "preload",
profile: "profile",
radiogroup: "radioGroup",
readonly: "readOnly",

referrerpolicy: "referrerPolicy",
rel: "rel",
required: "required",
reversed: "reversed",
role: "role",
rows: "rows",
rowspan: "rowSpan",
sandbox: "sandbox",
scope: "scope",
scoped: "scoped",
scrolling: "scrolling",
seamless: "seamless",
selected: "selected",
shape: "shape",
size: "size",
sizes: "sizes",
span: "span",
spellcheck: "spellCheck",
src: "src",
srcdoc: "srcDoc",
srclang: "srcLang",
srcset: "srcSet",
start: "start",
step: "step",
style: "style",
summary: "summary",
tabindex: "tabIndex",
target: "target",
title: "title",
type: "type",
usemap: "useMap",
value: "value",
width: "width",
wmode: "wmode",
wrap: "wrap",
about: "about",
accentheight: "accentHeight",
"accent-height": "accentHeight",
accumulate: "accumulate",
additive: "additive",
alignmentbaseline: "alignmentBaseline",
"alignment-baseline": "alignmentBaseline",
allowreorder: "allowReorder",
alphabetic: "alphabetic",
amplitude: "amplitude",
arabicform: "arabicForm",
"arabic-form": "arabicForm",
ascent: "ascent",
attributename: "attributeName",

attributetype: "attributeType",
autoreverse: "autoReverse",
azimuth: "azimuth",
basefrequency: "baseFrequency",
baselineshift: "baselineShift",
"baseline-shift": "baselineShift",
baseprofile: "baseProfile",
bbox: "bbox",
begin: "begin",
bias: "bias",
by: "by",
calcmode: "calcMode",
capheight: "capHeight",
"cap-height": "capHeight",
clip: "clip",
clippath: "clipPath",
"clip-path": "clipPath",
clippathunits: "clipPathUnits",
cliprule: "clipRule",
"clip-rule": "clipRule",
color: "color",
colorinterpolation: "colorInterpolation",
"color-interpolation": "colorInterpolation",
colorinterpolationfilters: "colorInterpolationFilters",
"color-interpolation-filters": "colorInterpolationFilters",
colorprofile: "colorProfile",
"color-profile": "colorProfile",
colorrendering: "colorRendering",
"color-rendering": "colorRendering",
contentscripttype: "contentScriptType",
contentstyletype: "contentStyleType",
cursor: "cursor",
cx: "cx",
cy: "cy",
d: "d",
datatype: "datatype",
decelerate: "decelerate",
descent: "descent",
diffuseconstant: "diffuseConstant",
direction: "direction",
display: "display",
divisor: "divisor",
dominantbaseline: "dominantBaseline",
"dominant-baseline": "dominantBaseline",
dur: "dur",
dx: "dx",
dy: "dy",
edgemode: "edgeMode",
elevation: "elevation",

enablebackground: "enableBackground",
"enable-background": "enableBackground",
end: "end",
exponent: "exponent",
externalresourcesrequired: "externalResourcesRequired",
fill: "fill",
fillopacity: "fillOpacity",
"fill-opacity": "fillOpacity",
fillrule: "fillRule",
"fill-rule": "fillRule",
filter: "filter",
filterres: "filterRes",
filterunits: "filterUnits",
floodopacity: "floodOpacity",
"flood-opacity": "floodOpacity",
floodcolor: "floodColor",
"flood-color": "floodColor",
focusable: "focusable",
fontfamily: "fontFamily",
"font-family": "fontFamily",
fontsize: "fontSize",
"font-size": "fontSize",
fontsizeadjust: "fontSizeAdjust",
"font-size-adjust": "fontSizeAdjust",
fontstretch: "fontStretch",
"font-stretch": "fontStretch",
fontstyle: "fontStyle",
"font-style": "fontStyle",
fontvariant: "fontVariant",
"font-variant": "fontVariant",
fontweight: "fontWeight",
"font-weight": "fontWeight",
format: "format",
from: "from",
fx: "fx",
fy: "fy",
g1: "g1",
g2: "g2",
glyphname: "glyphName",
"glyph-name": "glyphName",
glyphorientationhorizontal: "glyphOrientationHorizontal",
"glyph-orientation-horizontal": "glyphOrientationHorizontal",
glyphorientationvertical: "glyphOrientationVertical",
"glyph-orientation-vertical": "glyphOrientationVertical",
glyphref: "glyphRef",
gradienttransform: "gradientTransform",
gradientunits: "gradientUnits",
hanging: "hanging",
horizadvx: "horizAdvX",

"horiz-adv-x": "horizAdvX",
horizoriginx: "horizOriginX",
"horiz-origin-x": "horizOriginX",
ideographic: "ideographic",
imagerendering: "imageRendering",
"image-rendering": "imageRendering",
in2: "in2",

in: "in",
inlist: "inlist",
intercept: "intercept",
k1: "k1",
k2: "k2",
k3: "k3",
k4: "k4",
k: "k",
kernelmatrix: "kernelMatrix",
kernelunitlength: "kernelUnitLength",
kerning: "kerning",
keypoints: "keyPoints",
keysplines: "keySplines",
keytimes: "keyTimes",
lengthadjust: "lengthAdjust",
letterspacing: "letterSpacing",
"letter-spacing": "letterSpacing",
lightingcolor: "lightingColor",
"lighting-color": "lightingColor",
limitingconeangle: "limitingConeAngle",
local: "local",
markerend: "markerEnd",
"marker-end": "markerEnd",
markerheight: "markerHeight",
markermid: "markerMid",
"marker-mid": "markerMid",
markerstart: "markerStart",
"marker-start": "markerStart",
markerunits: "markerUnits",
markerwidth: "markerWidth",
mask: "mask",
maskcontentunits: "maskContentUnits",
maskunits: "maskUnits",
mathematical: "mathematical",
mode: "mode",
numoctaves: "numOctaves",
offset: "offset",
opacity: "opacity",
operator: "operator",
order: "order",
orient: "orient",

orientation: "orientation",
origin: "origin",
overflow: "overflow",
overlineposition: "overlinePosition",
"overline-position": "overlinePosition",
overlinethickness: "overlineThickness",
"overline-thickness": "overlineThickness",
paintorder: "paintOrder",
"paint-order": "paintOrder",
panose1: "panose1",
"panose-1": "panose1",
pathlength: "pathLength",
patterncontentunits: "patternContentUnits",
patterntransform: "patternTransform",
patternunits: "patternUnits",
pointerevents: "pointerEvents",
"pointer-events": "pointerEvents",
points: "points",
pointsatx: "pointsAtX",
pointsaty: "pointsAtY",
pointsatz: "pointsAtZ",
popover: "popover",
popovertarget: "popoverTarget",
popovertargetaction: "popoverTargetAction",
prefix: "prefix",
preservealpha: "preserveAlpha",
preserveaspectratio: "preserveAspectRatio",
primitiveunits: "primitiveUnits",
property: "property",
r: "r",
radius: "radius",
refx: "refX",
refy: "refY",
renderingintent: "renderingIntent",
"rendering-intent": "renderingIntent",
repeatcount: "repeatCount",
repeatdur: "repeatDur",
requiredextensions: "requiredExtensions",
requiredfeatures: "requiredFeatures",
resource: "resource",
restart: "restart",
result: "result",
results: "results",
rotate: "rotate",
rx: "rx",
ry: "ry",
scale: "scale",
security: "security",
seed: "seed",

shaperendering: "shapeRendering",
"shape-rendering": "shapeRendering",
slope: "slope",
spacing: "spacing",
specularconstant: "specularConstant",
specularexponent: "specularExponent",
speed: "speed",
spreadmethod: "spreadMethod",
startoffset: "startOffset",
stddeviation: "stdDeviation",
stemh: "stemh",
stemv: "stemv",
stitchtiles: "stitchTiles",
stopcolor: "stopColor",
"stop-color": "stopColor",
stopopacity: "stopOpacity",
"stop-opacity": "stopOpacity",
strikethroughposition: "strikethroughPosition",
"strikethrough-position": "strikethroughPosition",
strikethroughthickness: "strikethroughThickness",
"strikethrough-thickness": "strikethroughThickness",
string: "string",
stroke: "stroke",
strokedasharray: "strokeDasharray",
"stroke-dasharray": "strokeDasharray",
strokedashoffset: "strokeDashoffset",
"stroke-dashoffset": "strokeDashoffset",
strokelinecap: "strokeLinecap",
"stroke-linecap": "strokeLinecap",
strokelinejoin: "strokeLinejoin",
"stroke-linejoin": "strokeLinejoin",
strokemiterlimit: "strokeMiterlimit",
"stroke-miterlimit": "strokeMiterlimit",
strokewidth: "strokeWidth",
"stroke-width": "strokeWidth",
strokeopacity: "strokeOpacity",
"stroke-opacity": "strokeOpacity",
suppresscontenteditablewarning: "suppressContentEditableWarning",
suppresshydrationwarning: "suppressHydrationWarning",
surfacescale: "surfaceScale",
systemlanguage: "systemLanguage",
tablevalues: "tableValues",
targetx: "targetX",
targety: "targetY",
textanchor: "textAnchor",
"text-anchor": "textAnchor",
textdecoration: "textDecoration",
"text-decoration": "textDecoration",
textlength: "textLength",

textrendering: "textRendering",
"text-rendering": "textRendering",
to: "to",
transform: "transform",
transformorigin: "transformOrigin",
"transform-origin": "transformOrigin",
typeof: "typeof",
u1: "u1",
u2: "u2",
underlineposition: "underlinePosition",
"underline-position": "underlinePosition",
underlinethickness: "underlineThickness",
"underline-thickness": "underlineThickness",
unicode: "unicode",
unicodebidi: "unicodeBidi",
"unicode-bidi": "unicodeBidi",
unicoderange: "unicodeRange",
"unicode-range": "unicodeRange",
unitsperem: "unitsPerEm",
"units-per-em": "unitsPerEm",
unselectable: "unselectable",
valphabetic: "vAlphabetic",
"v-alphabetic": "vAlphabetic",
values: "values",
vectoreffect: "vectorEffect",
"vector-effect": "vectorEffect",
version: "version",
vertadvy: "vertAdvY",
"vert-adv-y": "vertAdvY",
vertoriginx: "vertOriginX",
"vert-origin-x": "vertOriginX",
vertoriginy: "vertOriginY",
"vert-origin-y": "vertOriginY",
vhanging: "vHanging",
"v-hanging": "vHanging",
videographic: "vIdeographic",
"v-ideographic": "vIdeographic",
viewbox: "viewBox",
viewtarget: "viewTarget",
visibility: "visibility",
vmathematical: "vMathematical",
"v-mathematical": "vMathematical",
vocab: "vocab",
widths: "widths",
wordspacing: "wordSpacing",
"word-spacing": "wordSpacing",
writingmode: "writingMode",
"writing-mode": "writingMode",
x1: "x1",

```
  x2: "x2",
  x: "x",
  xchannelselector: "xChannelSelector",
  xheight: "xHeight",
  "x-height": "xHeight",
  xlinkactuate: "xlinkActuate",
  "xlink:actuate": "xlinkActuate",
  xlinkarcrole: "xlinkArcrole",
  "xlink:arcrole": "xlinkArcrole",
  xlinkhref: "xlinkHref",
  "xlink:href": "xlinkHref",
  xlinkrole: "xlinkRole",
  "xlink:role": "xlinkRole",
  xlinkshow: "xlinkShow",
  "xlink:show": "xlinkShow",
  xlinktitle: "xlinkTitle",
  "xlink:title": "xlinkTitle",
  xlinktype: "xlinkType",
  "xlink:type": "xlinkType",
  xmlbase: "xmlBase",
  "xml:base": "xmlBase",
  xmllang: "xmlLang",
  "xml:lang": "xmlLang",
  xmlns: "xmlns",
  "xml:space": "xmlSpace",
  xmlnsxlink: "xmlnsXlink",
  "xmlns:xlink": "xmlnsXlink",
  xmlspace: "xmlSpace",
  y1: "y1",
  y2: "y2",
  y: "y",
  ychannelselector: "yChannelSelector",
  z: "z",
  zoomandpan: "zoomAndPan"
},
ariaProperties = {
  "aria-current": 0,
  "aria-description": 0,
  "aria-details": 0,
  "aria-disabled": 0,
  "aria-hidden": 0,
  "aria-invalid": 0,
  "aria-keyshortcuts": 0,
  "aria-label": 0,
  "aria-roledescription": 0,
  "aria-autocomplete": 0,
  "aria-checked": 0,
  "aria-expanded": 0,
  "aria-haspopup": 0,
```

```
    "aria-level": 0,
    "aria-modal": 0,
    "aria-multiline": 0,
    "aria-multiselectable": 0,
    "aria-orientation": 0,
    "aria-placeholder": 0,
    "aria-pressed": 0,
    "aria-readonly": 0,
    "aria-required": 0,
    "aria-selected": 0,
    "aria-sort": 0,
    "aria-valuemax": 0,
    "aria-valuemin": 0,
    "aria-valuenow": 0,
    "aria-valuetext": 0,
    "aria-atomic": 0,
    "aria-busy": 0,
    "aria-live": 0,
    "aria-relevant": 0,
    "aria-dropeffect": 0,
    "aria-grabbed": 0,
    "aria-activedescendant": 0,
    "aria-colcount": 0,
    "aria-colindex": 0,
    "aria-colspan": 0,
    "aria-controls": 0,
    "aria-describedby": 0,
    "aria-errormessage": 0,
    "aria-flowto": 0,
    "aria-labelledby": 0,
    "aria-owns": 0,
    "aria-posinset": 0,
    "aria-rowcount": 0,
    "aria-rowindex": 0,
    "aria-rowspan": 0,
    "aria-setsize": 0
  },
  warnedProperties$1 = {},
  rARIA$1 = RegExp("^(aria)-[:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD\\-.0-
9\\u00B7\\u0300-\\u036F\\u203F-\\u2040]*$"),
  rARIACamel$1 = RegExp("^(aria)[A-Z][:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD\\-.0-
9\\u00B7\\u0300-\\u036F\\u203F-\\u2040]*$"),
  didWarnValueNull = !1,
  warnedProperties = {},
  EVENT_NAME_REGEX = /^on./,
```

```
  INVALID_EVENT_NAME_REGEX = /^on[^A-Z]/,
  rARIA = RegExp("^(aria)-[:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD\\-.0-
9\\u00B7\\u0300-\\u036F\\u203F-\\u2040]*$"),
  rARIACamel = RegExp("^(aria)[A-Z][:A-Z_a-
z\\u00C0-\\u00D6\\u00D8-\\u00F6\\u00F8-\\u02FF\\u0370-\\u037D\\u037F-\\u1FFF\\u200C-\\u200D\\
u2070-\\u218F\\u2C00-\\u2FEF\\u3001-\\uD7FF\\uF900-\\uFDCF\\uFDF0-\\uFFFD\\-.0-
9\\u00B7\\u0300-\\u036F\\u203F-\\u2040]*$"),
  isJavaScriptProtocol = /^[\u0000-\u001F ]
*j[\r\n\t]*a[\r\n\t]*v[\r\n\t]*a[\r\n\t]*s[\r\n\t]*c[\r\n\t]*r[\r\n\t]*i[\r\n\t]*p[\r\n\t]*t[\r\n\t]*:/i,

  currentReplayingEvent = null,
  restoreTarget = null,
  restoreQueue = null,
  isInsideEventHandler = !1,
  passiveBrowserEventsSupported = !1;
 if (canUseDOM) try {
  var options$jscomp$0 = {};
  Object.defineProperty(options$jscomp$0, "passive", {
   get: function () {
    passiveBrowserEventsSupported = !0;
   }
  });
  window.addEventListener("test", options$jscomp$0, options$jscomp$0);
  window.removeEventListener("test", options$jscomp$0, options$jscomp$0);
 } catch (e) {
  passiveBrowserEventsSupported = !1;
 }
 var root = null,
  startText = null,
  fallbackText = null,
  EventInterface = {
   eventPhase: 0,
   bubbles: 0,
   cancelable: 0,
   timeStamp: function (event) {
    return event.timeStamp || Date.now();
   },
   defaultPrevented: 0,
   isTrusted: 0
  },
  SyntheticEvent = createSyntheticEvent(EventInterface),
  UIEventInterface = assign({}, EventInterface, {
   view: 0,
   detail: 0
  }),
  SyntheticUIEvent = createSyntheticEvent(UIEventInterface),
  lastMovementX,
```

```
    lastMovementY,
    lastMouseEvent,
    MouseEventInterface = assign({}, UIEventInterface, {
      screenX: 0,
      screenY: 0,
      clientX: 0,
      clientY: 0,
      pageX: 0,
      pageY: 0,
      ctrlKey: 0,
      shiftKey: 0,
      altKey: 0,
      metaKey: 0,
      getModifierState: getEventModifierState,
      button: 0,
      buttons: 0,
      relatedTarget: function (event) {
        return void 0 === event.relatedTarget ? event.fromElement === event.srcElement ?
event.toElement : event.fromElement : event.relatedTarget;
      },
      movementX: function (event) {
        if ("movementX" in event) return event.movementX;
        event !== lastMouseEvent && (lastMouseEvent && "mousemove" === event.type ?
(lastMovementX = event.screenX - lastMouseEvent.screenX, lastMovementY = event.screenY -
lastMouseEvent.screenY) : lastMovementY = lastMovementX = 0, lastMouseEvent = event);
        return lastMovementX;
      },
      movementY: function (event) {
        return "movementY" in event ? event.movementY : lastMovementY;
      }
    }),
    SyntheticMouseEvent = createSyntheticEvent(MouseEventInterface),
    DragEventInterface = assign({}, MouseEventInterface, {
      dataTransfer: 0
    }),
    SyntheticDragEvent = createSyntheticEvent(DragEventInterface),
    FocusEventInterface = assign({}, UIEventInterface, {
      relatedTarget: 0
    }),
    SyntheticFocusEvent = createSyntheticEvent(FocusEventInterface),
    AnimationEventInterface = assign({}, EventInterface, {
      animationName: 0,
      elapsedTime: 0,
      pseudoElement: 0
    }),
    SyntheticAnimationEvent = createSyntheticEvent(AnimationEventInterface),
    ClipboardEventInterface = assign({}, EventInterface, {
      clipboardData: function (event) {
        return "clipboardData" in event ? event.clipboardData : window.clipboardData;
```

```
  }
}),
SyntheticClipboardEvent = createSyntheticEvent(ClipboardEventInterface),
CompositionEventInterface = assign({}, EventInterface, {
  data: 0
}),
SyntheticCompositionEvent = createSyntheticEvent(CompositionEventInterface),
SyntheticInputEvent = SyntheticCompositionEvent,
normalizeKey = {
  Esc: "Escape",
  Spacebar: " ",
  Left: "ArrowLeft",
  Up: "ArrowUp",
  Right: "ArrowRight",
  Down: "ArrowDown",
  Del: "Delete",
  Win: "OS",
  Menu: "ContextMenu",
  Apps: "ContextMenu",
  Scroll: "ScrollLock",
  MozPrintableKey: "Unidentified"
},
translateToKey = {
  8: "Backspace",
  9: "Tab",
  12: "Clear",
  13: "Enter",
  16: "Shift",
  17: "Control",
  18: "Alt",
  19: "Pause",
  20: "CapsLock",
  27: "Escape",
  32: " ",
  33: "PageUp",
  34: "PageDown",
  35: "End",
  36: "Home",
  37: "ArrowLeft",
  38: "ArrowUp",
  39: "ArrowRight",
  40: "ArrowDown",
  45: "Insert",
  46: "Delete",
  112: "F1",
  113: "F2",
  114: "F3",
  115: "F4",
  116: "F5",
```

```
    117: "F6",
    118: "F7",
    119: "F8",
    120: "F9",
    121: "F10",
    122: "F11",
    123: "F12",
    144: "NumLock",
    145: "ScrollLock",
    224: "Meta"
  },
  modifierKeyToProp = {
    Alt: "altKey",
    Control: "ctrlKey",
    Meta: "metaKey",
    Shift: "shiftKey"
  },
  KeyboardEventInterface = assign({}, UIEventInterface, {
    key: function (nativeEvent) {
      if (nativeEvent.key) {
        var key = normalizeKey[nativeEvent.key] || nativeEvent.key;
        if ("Unidentified" !== key) return key;
      }
      return "keypress" === nativeEvent.type ? (nativeEvent = getEventCharCode(nativeEvent), 13 ===
nativeEvent ? "Enter" : String.fromCharCode(nativeEvent)) : "keydown" === nativeEvent.type ||
"keyup" === nativeEvent.type ? translateToKey[nativeEvent.keyCode] || "Unidentified" : "";
    },
    code: 0,
    location: 0,
    ctrlKey: 0,
    shiftKey: 0,
    altKey: 0,
    metaKey: 0,
    repeat: 0,
    locale: 0,
    getModifierState: getEventModifierState,
    charCode: function (event) {
      return "keypress" === event.type ? getEventCharCode(event) : 0;
    },
    keyCode: function (event) {
      return "keydown" === event.type || "keyup" === event.type ? event.keyCode : 0;
    },
    which: function (event) {
      return "keypress" === event.type ? getEventCharCode(event) : "keydown" === event.type ||
"keyup" === event.type ? event.keyCode : 0;
    }
  }),
  SyntheticKeyboardEvent = createSyntheticEvent(KeyboardEventInterface),
  PointerEventInterface = assign({}, MouseEventInterface, {
```

```
    pointerId: 0,
    width: 0,
    height: 0,
    pressure: 0,
    tangentialPressure: 0,
    tiltX: 0,
    tiltY: 0,
    twist: 0,
    pointerType: 0,
    isPrimary: 0
  }),
  SyntheticPointerEvent = createSyntheticEvent(PointerEventInterface),
  TouchEventInterface = assign({}, UIEventInterface, {
    touches: 0,
    targetTouches: 0,
    changedTouches: 0,
    altKey: 0,
    metaKey: 0,
    ctrlKey: 0,
    shiftKey: 0,
    getModifierState: getEventModifierState
  }),
  SyntheticTouchEvent = createSyntheticEvent(TouchEventInterface),
  TransitionEventInterface = assign({}, EventInterface, {
    propertyName: 0,
    elapsedTime: 0,
    pseudoElement: 0
  }),
  SyntheticTransitionEvent = createSyntheticEvent(TransitionEventInterface),
  WheelEventInterface = assign({}, MouseEventInterface, {
    deltaX: function (event) {
      return "deltaX" in event ? event.deltaX : "wheelDeltaX" in event ? -event.wheelDeltaX : 0;
    },
    deltaY: function (event) {
      return "deltaY" in event ? event.deltaY : "wheelDeltaY" in event ? -event.wheelDeltaY :
"wheelDelta" in event ? -event.wheelDelta : 0;
    },
    deltaZ: 0,
    deltaMode: 0
  }),
  SyntheticWheelEvent = createSyntheticEvent(WheelEventInterface),
  ToggleEventInterface = assign({}, EventInterface, {
    newState: 0,
    oldState: 0
  }),
  SyntheticToggleEvent = createSyntheticEvent(ToggleEventInterface),
  END_KEYCODES = [9, 13, 27, 32],
  START_KEYCODE = 229,
  canUseCompositionEvent = canUseDOM && "CompositionEvent" in window,
```

```
    documentMode = null;
  canUseDOM && "documentMode" in document && (documentMode = document.documentMode);
  var canUseTextInputEvent = canUseDOM && "TextEvent" in window && !documentMode,
    useFallbackCompositionData = canUseDOM && (!canUseCompositionEvent || documentMode &&
8 < documentMode && 11 >= documentMode),
    SPACEBAR_CODE = 32,
    SPACEBAR_CHAR = String.fromCharCode(SPACEBAR_CODE),
    hasSpaceKeypress = !1,
    isComposing = !1,
    supportedInputTypes = {
      color: !0,
      date: !0,
      datetime: !0,
      "datetime-local": !0,
      email: !0,
      month: !0,
      number: !0,
      password: !0,
      range: !0,
      search: !0,
      tel: !0,
      text: !0,
      time: !0,
      url: !0,
      week: !0
    },
    activeElement$1 = null,
    activeElementInst$1 = null,
    isInputEventSupported = !1;
  canUseDOM && (isInputEventSupported = isEventSupported("input") && (!
document.documentMode || 9 < document.documentMode));
  var objectIs = "function" === typeof Object.is ? Object.is : is,
    skipSelectionChangeEvent = canUseDOM && "documentMode" in document && 11 >=
document.documentMode,
    activeElement = null,
    activeElementInst = null,
    lastSelection = null,
    mouseDown = !1,
    vendorPrefixes = {
      animationend: makePrefixMap("Animation", "AnimationEnd"),
      animationiteration: makePrefixMap("Animation", "AnimationIteration"),
      animationstart: makePrefixMap("Animation", "AnimationStart"),
      transitionrun: makePrefixMap("Transition", "TransitionRun"),
      transitionstart: makePrefixMap("Transition", "TransitionStart"),
      transitioncancel: makePrefixMap("Transition", "TransitionCancel"),
      transitionend: makePrefixMap("Transition", "TransitionEnd")
    },
    prefixedEventNames = {},
    style = {};
```

```
  canUseDOM && (style = document.createElement("div").style, "AnimationEvent" in window ||
(delete vendorPrefixes.animationend.animation, delete vendorPrefixes.animationiteration.animation,
delete vendorPrefixes.animationstart.animation), "TransitionEvent" in window || delete
vendorPrefixes.transitionend.transition);
  var ANIMATION_END = getVendorPrefixedEventName("animationend"),
    ANIMATION_ITERATION = getVendorPrefixedEventName("animationiteration"),
    ANIMATION_START = getVendorPrefixedEventName("animationstart"),
    TRANSITION_RUN = getVendorPrefixedEventName("transitionrun"),
    TRANSITION_START = getVendorPrefixedEventName("transitionstart"),
    TRANSITION_CANCEL = getVendorPrefixedEventName("transitioncancel"),
    TRANSITION_END = getVendorPrefixedEventName("transitionend"),

    topLevelEventsToReactNames = new Map(),
    simpleEventPluginEvents = "abort auxClick beforeToggle cancel canPlay canPlayThrough click
close contextMenu copy cut drag dragEnd dragEnter dragExit dragLeave dragOver dragStart drop
durationChange emptied encrypted ended error gotPointerCapture input invalid keyDown keyPress
keyUp load loadedData loadedMetadata loadStart lostPointerCapture mouseDown mouseMove
mouseOut mouseOver mouseUp paste pause play playing pointerCancel pointerDown pointerMove
pointerOut pointerOver pointerUp progress rateChange reset resize seeked seeking stalled submit
suspend timeUpdate touchCancel touchEnd touchStart volumeChange scroll scrollEnd toggle
touchMove waiting wheel".split(" "),
    OffscreenVisible = 1,
    OffscreenDetached = 2,
    OffscreenPassiveEffectsConnected = 4,
    concurrentQueues = [],
    concurrentQueuesIndex = 0,
    concurrentlyUpdatedLanes = 0,
    emptyContextObject = {};
  Object.freeze(emptyContextObject);
  var resolveFamily = null,
    failedBoundaries = null,
    NoMode = 0,
    ConcurrentMode = 1,
    ProfileMode = 2,
    StrictLegacyMode = 8,
    StrictEffectsMode = 16,
    NoStrictPassiveEffectsMode = 64,
    now = Scheduler.unstable_now,
    renderStartTime = -0,
    commitStartTime = -0,
    profilerStartTime = -1.1,
    profilerEffectDuration = -0,
    currentUpdateIsNested = !1,
    nestedUpdateScheduled = !1,
    ReactStrictModeWarnings = {
      recordUnsafeLifecycleWarnings: function () {},
      flushPendingUnsafeLifecycleWarnings: function () {},
      recordLegacyContextWarning: function () {},
      flushLegacyContextWarning: function () {},
```

```
    discardPendingWarnings: function () {}
  },
  pendingComponentWillMountWarnings = [],
  pendingUNSAFE_ComponentWillMountWarnings = [],
  pendingComponentWillReceivePropsWarnings = [],
  pendingUNSAFE_ComponentWillReceivePropsWarnings = [],
  pendingComponentWillUpdateWarnings = [],
  pendingUNSAFE_ComponentWillUpdateWarnings = [],
  didWarnAboutUnsafeLifecycles = new Set();
ReactStrictModeWarnings.recordUnsafeLifecycleWarnings = function (fiber, instance) {
  didWarnAboutUnsafeLifecycles.has(fiber.type) || ("function" === typeof
instance.componentWillMount && !0 !==
instance.componentWillMount.__suppressDeprecationWarning &&
pendingComponentWillMountWarnings.push(fiber), fiber.mode & StrictLegacyMode && "function"
=== typeof instance.UNSAFE_componentWillMount &&
pendingUNSAFE_ComponentWillMountWarnings.push(fiber), "function" === typeof
instance.componentWillReceiveProps && !0 !==
instance.componentWillReceiveProps.__suppressDeprecationWarning &&
pendingComponentWillReceivePropsWarnings.push(fiber), fiber.mode & StrictLegacyMode &&
"function" === typeof instance.UNSAFE_componentWillReceiveProps &&
pendingUNSAFE_ComponentWillReceivePropsWarnings.push(fiber), "function" === typeof
instance.componentWillUpdate && !0 !==
instance.componentWillUpdate.__suppressDeprecationWarning &&
pendingComponentWillUpdateWarnings.push(fiber), fiber.mode & StrictLegacyMode && "function"
=== typeof instance.UNSAFE_componentWillUpdate &&
pendingUNSAFE_ComponentWillUpdateWarnings.push(fiber));
};
ReactStrictModeWarnings.flushPendingUnsafeLifecycleWarnings = function () {
  var componentWillMountUniqueNames = new Set();
  0 < pendingComponentWillMountWarnings.length &&
(pendingComponentWillMountWarnings.forEach(function (fiber) {
    componentWillMountUniqueNames.add(getComponentNameFromFiber(fiber) || "Component");
    didWarnAboutUnsafeLifecycles.add(fiber.type);
  }), pendingComponentWillMountWarnings = []);
  var UNSAFE_componentWillMountUniqueNames = new Set();
  0 < pendingUNSAFE_ComponentWillMountWarnings.length &&
(pendingUNSAFE_ComponentWillMountWarnings.forEach(function (fiber) {
    UNSAFE_componentWillMountUniqueNames.add(getComponentNameFromFiber(fiber) ||
"Component");
    didWarnAboutUnsafeLifecycles.add(fiber.type);
  }), pendingUNSAFE_ComponentWillMountWarnings = []);
  var componentWillReceivePropsUniqueNames = new Set();
  0 < pendingComponentWillReceivePropsWarnings.length &&
(pendingComponentWillReceivePropsWarnings.forEach(function (fiber) {
    componentWillReceivePropsUniqueNames.add(getComponentNameFromFiber(fiber) ||
"Component");
    didWarnAboutUnsafeLifecycles.add(fiber.type);
  }), pendingComponentWillReceivePropsWarnings = []);
  var UNSAFE_componentWillReceivePropsUniqueNames = new Set();
```

```
    0 < pendingUNSAFE_ComponentWillReceivePropsWarnings.length &&
(pendingUNSAFE_ComponentWillReceivePropsWarnings.forEach(function (fiber) {
      UNSAFE_componentWillReceivePropsUniqueNames.add(getComponentNameFromFiber(fiber) ||
"Component");
      didWarnAboutUnsafeLifecycles.add(fiber.type);
    }), pendingUNSAFE_ComponentWillReceivePropsWarnings = []);
    var componentWillUpdateUniqueNames = new Set();
    0 < pendingComponentWillUpdateWarnings.length &&
(pendingComponentWillUpdateWarnings.forEach(function (fiber) {
      componentWillUpdateUniqueNames.add(getComponentNameFromFiber(fiber) || "Component");
      didWarnAboutUnsafeLifecycles.add(fiber.type);
    }), pendingComponentWillUpdateWarnings = []);
    var UNSAFE_componentWillUpdateUniqueNames = new Set();
    0 < pendingUNSAFE_ComponentWillUpdateWarnings.length &&
(pendingUNSAFE_ComponentWillUpdateWarnings.forEach(function (fiber) {
      UNSAFE_componentWillUpdateUniqueNames.add(getComponentNameFromFiber(fiber) ||
"Component");
      didWarnAboutUnsafeLifecycles.add(fiber.type);
    }), pendingUNSAFE_ComponentWillUpdateWarnings = []);
    if (0 < UNSAFE_componentWillMountUniqueNames.size) {
      var sortedNames = setToSortedString(UNSAFE_componentWillMountUniqueNames);
      console.error("Using UNSAFE_componentWillMount in strict mode is not recommended and may
indicate bugs in your code. See https://react.dev/link/unsafe-component-lifecycles for details.\n\n*
Move code with side effects to componentDidMount, and set initial state in the constructor.\n\nPlease
update the following components: %s", sortedNames);
    }
    0 < UNSAFE_componentWillReceivePropsUniqueNames.size && (sortedNames =
setToSortedString(UNSAFE_componentWillReceivePropsUniqueNames), console.error("Using
UNSAFE_componentWillReceiveProps in strict mode is not recommended and may indicate bugs in
your code. See https://react.dev/link/unsafe-component-lifecycles for details.\n\n* Move data fetching
code or side effects to componentDidUpdate.\n* If you're updating state whenever props change,
refactor your code to use memoization techniques or move it to static getDerivedStateFromProps.
Learn more at: https://react.dev/link/derived-state\n\nPlease update the following components: %s",
sortedNames));
    0 < UNSAFE_componentWillUpdateUniqueNames.size && (sortedNames =
setToSortedString(UNSAFE_componentWillUpdateUniqueNames), console.error("Using
UNSAFE_componentWillUpdate in strict mode is not recommended and may indicate bugs in your
code. See https://react.dev/link/unsafe-component-lifecycles for details.\n\n* Move data fetching code
or side effects to componentDidUpdate.\n\nPlease update the following components: %s",
sortedNames));
    0 < componentWillMountUniqueNames.size && (sortedNames =
setToSortedString(componentWillMountUniqueNames), console.warn("componentWillMount has
been renamed, and is not recommended for use. See https://react.dev/link/unsafe-component-lifecycles
for details.\n\n* Move code with side effects to componentDidMount, and set initial state in the
constructor.\n* Rename componentWillMount to UNSAFE_componentWillMount to suppress this
warning in non-strict mode. In React 18.x, only the UNSAFE_ name will work. To rename all
deprecated lifecycles to their new names, you can run `npx react-codemod rename-unsafe-lifecycles` in
your project source folder.\n\nPlease update the following components: %s", sortedNames));
    0 < componentWillReceivePropsUniqueNames.size && (sortedNames =
```

```
setToSortedString(componentWillReceivePropsUniqueNames),
console.warn("componentWillReceiveProps has been renamed, and is not recommended for use. See https://react.dev/link/unsafe-component-lifecycles for details.\n\n* Move data fetching code or side effects to componentDidUpdate.\n* If you're updating state whenever props change, refactor your code to use memoization techniques or move it to static getDerivedStateFromProps. Learn more at: https://react.dev/link/derived-state\n* Rename componentWillReceiveProps to UNSAFE_componentWillReceiveProps to suppress this warning in non-strict mode. In React 18.x, only the UNSAFE_ name will work. To rename all deprecated lifecycles to their new names, you can run `npx react-codemod rename-unsafe-lifecycles` in your project source folder.\n\nPlease update the following components: %s", sortedNames));
    0 < componentWillUpdateUniqueNames.size && (sortedNames =
setToSortedString(componentWillUpdateUniqueNames), console.warn("componentWillUpdate has been renamed, and is not recommended for use. See https://react.dev/link/unsafe-component-lifecycles for details.\n\n* Move data fetching code or side effects to componentDidUpdate.\n* Rename componentWillUpdate to UNSAFE_componentWillUpdate to suppress this warning in non-strict mode. In React 18.x, only the UNSAFE_ name will work. To rename all deprecated lifecycles to their new names, you can run `npx react-codemod rename-unsafe-lifecycles` in your project source folder.\n\nPlease update the following components: %s", sortedNames));
  };
  var pendingLegacyContextWarning = new Map(),
    didWarnAboutLegacyContext = new Set();
  ReactStrictModeWarnings.recordLegacyContextWarning = function (fiber, instance) {
    var strictRoot = null;
    for (var node = fiber; null !== node;) node.mode & StrictLegacyMode && (strictRoot = node), node
= node.return;
    null === strictRoot ? console.error("Expected to find a StrictMode component
 in a strict mode tree. This error is likely caused by a bug in React. Please file an issue.") : !
didWarnAboutLegacyContext.has(fiber.type) && (node =
pendingLegacyContextWarning.get(strictRoot), null != fiber.type.contextTypes || null !=
fiber.type.childContextTypes || null !== instance && "function" === typeof instance.getChildContext)
&& (void 0 === node && (node = [], pendingLegacyContextWarning.set(strictRoot, node)),
node.push(fiber));
  };
  ReactStrictModeWarnings.flushLegacyContextWarning = function () {
    pendingLegacyContextWarning.forEach(function (fiberArray) {
      if (0 !== fiberArray.length) {
        var firstFiber = fiberArray[0],
          uniqueNames = new Set();
        fiberArray.forEach(function (fiber) {
          uniqueNames.add(getComponentNameFromFiber(fiber) || "Component");
          didWarnAboutLegacyContext.add(fiber.type);
        });
        var sortedNames = setToSortedString(uniqueNames);
        runWithFiberInDEV(firstFiber, function () {
          console.error("Legacy context API has been detected within a strict-mode tree.\n\nThe old API
will be supported in all 16.x releases, but applications using it should migrate to the new
version.\n\nPlease update the following components: %s\n\nLearn more about this warning here:
https://react.dev/link/legacy-context", sortedNames);
        });
```

```
    }
  });
};
ReactStrictModeWarnings.discardPendingWarnings = function () {
  pendingComponentWillMountWarnings = [];
  pendingUNSAFE_ComponentWillMountWarnings = [];
  pendingComponentWillReceivePropsWarnings = [];
  pendingUNSAFE_ComponentWillReceivePropsWarnings = [];
  pendingComponentWillUpdateWarnings = [];
  pendingUNSAFE_ComponentWillUpdateWarnings = [];
  pendingLegacyContextWarning = new Map();
};
var CapturedStacks = new WeakMap(),
  forkStack = [],
  forkStackIndex = 0,
  treeForkProvider = null,
  treeForkCount = 0,
  idStack = [],
  idStackIndex = 0,
  treeContextProvider = null,
  treeContextId = 1,
  treeContextOverflow = "",
  hydrationParentFiber = null,
  nextHydratableInstance = null,
  isHydrating = !1,
  didSuspendOrErrorDEV = !1,
  hydrationDiffRootDEV = null,
  hydrationErrors = null,
  rootOrSingletonContext = !1,
  HydrationMismatchException = Error("Hydration Mismatch Exception: This is not a real error, and should not leak into userspace. If you're seeing this, it's likely a bug in React."),
  SuspenseException = Error("Suspense Exception: This is not a real error! It's an implementation detail of `use` to interrupt the current render. You must either rethrow it immediately, or move the `use` call outside of the `try/catch` block. Capturing without rethrowing will lead to unexpected behavior.\n\nTo handle async errors, wrap your component in an error boundary, or call the promise's `.catch` method and pass the result to `use`"),
  SuspenseyCommitException = Error("Suspense Exception: This is not a real error, and should not leak into userspace. If you're seeing this, it's likely a bug in React."),
  noopSuspenseyCommitThenable = {
    then: function () {
      console.error('Internal React error: A listener was unexpectedly attached to a "noop" thenable. This is a bug in React. Please file an issue.');
    }
  },
  suspendedThenable = null,
  needsToResetSuspendedThenableDEV = !1,
  callComponent = {
    "react-stack-bottom-frame": function (Component, props, secondArg) {
      var wasRendering = isRendering;
```

```
      isRendering = !0;
      try {
        return Component(props, secondArg);
      } finally {
        isRendering = wasRendering;
      }
    }
  },
  callComponentInDEV = callComponent["react-stack-bottom-frame"].bind(callComponent),
  callRender = {
    "react-stack-bottom-frame": function (instance) {
      var wasRendering = isRendering;
      isRendering = !0;
      try {
        return instance.render();
      } finally {
        isRendering = wasRendering;
      }
    }
  },
  callRenderInDEV = callRender["react-stack-bottom-frame"].bind(callRender),
  callComponentDidMount = {
    "react-stack-bottom-frame": function (finishedWork, instance) {
      try {
        instance.componentDidMount();
      } catch (error) {
        captureCommitPhaseError(finishedWork, finishedWork.return, error);
      }
    }
  },
  callComponentDidMountInDEV = callComponentDidMount["react-stack-bottom-
frame"].bind(callComponentDidMount),
  callComponentDidUpdate = {
    "react-stack-bottom-frame": function (finishedWork, instance, prevProps, prevState, snapshot) {
      try {
        instance.componentDidUpdate(prevProps, prevState, snapshot);
      } catch (error) {
        captureCommitPhaseError(finishedWork, finishedWork.return, error);
      }
    }
  },
  callComponentDidUpdateInDEV = callComponentDidUpdate["react-stack-bottom-
frame"].bind(callComponentDidUpdate),
  callComponentDidCatch = {
    "react-stack-bottom-frame": function (instance, errorInfo) {
      var stack = errorInfo.stack;
      instance.componentDidCatch(errorInfo.value, {
        componentStack: null !== stack ? stack : ""
      });
```

```
    }
  },
  callComponentDidCatchInDEV = callComponentDidCatch["react-stack-bottom-
frame"].bind(callComponentDidCatch),
  callComponentWillUnmount = {
    "react-stack-bottom-frame": function (current, nearestMountedAncestor, instance) {
      try {
        instance.componentWillUnmount();
      } catch (error) {
        captureCommitPhaseError(current, nearestMountedAncestor, error);
      }
    }
  },
  callComponentWillUnmountInDEV = callComponentWillUnmount["react-stack-bottom-
frame"].bind(callComponentWillUnmount),
  callCreate = {
    "react-stack-bottom-frame": function (effect) {
      var create = effect.create;
      effect = effect.inst;
      create = create();
      return effect.destroy = create;
    }
  },
  callCreateInDEV = callCreate["react-stack-bottom-frame"].bind(callCreate),
  callDestroy = {
    "react-stack-bottom-frame": function (current, nearestMountedAncestor, destroy) {
      try {
        destroy();
      } catch (error) {
        captureCommitPhaseError(current, nearestMountedAncestor, error);
      }
    }
  },
  callDestroyInDEV = callDestroy["react-stack-bottom-frame"].bind(callDestroy),
  callLazyInit = {
    "react-stack-bottom-frame": function (lazy) {
      var init = lazy._init;
      return init(lazy._payload);
    }
  },
  callLazyInitInDEV = callLazyInit["react-stack-bottom-frame"].bind(callLazyInit),
  thenableState$1 = null,
  thenableIndexCounter$1 = 0,
  currentDebugInfo = null,
  didWarnAboutMaps;
var didWarnAboutGenerators = didWarnAboutMaps = !1;
var ownerHasKeyUseWarning = {};
var ownerHasFunctionTypeWarning = {};
var ownerHasSymbolTypeWarning = {};
```

```
  warnForMissingKey = function (returnFiber, workInProgress, child) {
    if (null !== child && "object" === typeof child && child._store && (!child._store.validated &&
null == child.key || 2 === child._store.validated)) {
      if ("object" !== typeof child._store) throw Error("React Component in warnForMissingKey should
have a _store. This error is likely caused by a bug in React. Please file an issue.");
      child._store.validated = 1;
      var componentName = getComponentNameFromFiber(returnFiber),
        componentKey = componentName || "null";
      if (!ownerHasKeyUseWarning[componentKey]) {
        ownerHasKeyUseWarning[componentKey] = !0;
        child = child._owner;
        returnFiber = returnFiber._debugOwner;
        var currentComponentErrorInfo = "";
        returnFiber && "number" === typeof returnFiber.tag && (componentKey =
getComponentNameFromFiber(returnFiber)) && (currentComponentErrorInfo = "\n\nCheck the
render method of `" + componentKey + "`.");
        currentComponentErrorInfo || componentName && (currentComponentErrorInfo = "\n\nCheck
the top-level render call using <" + componentName + ">.");
        var childOwnerAppendix = "";
        null != child && returnFiber !== child && (componentName = null, "number" === typeof
child.tag ? componentName = getComponentNameFromFiber(child) : "string" === typeof child.name
&& (componentName = child.name), componentName && (childOwnerAppendix = " It was passed a
child from " + componentName + "."));
        runWithFiberInDEV(workInProgress, function () {
          console.error('Each child in a list should have a unique "key" prop.%s%s See
https://react.dev/link/warning-keys for more information.', currentComponentErrorInfo,
childOwnerAppendix);
        });
      }
    }
  };
  var reconcileChildFibers = createChildReconciler(!0),
    mountChildFibers = createChildReconciler(!1),
    currentTreeHiddenStackCursor = createCursor(null),
    prevEntangledRenderLanesCursor = createCursor(0),
    suspenseHandlerStackCursor = createCursor(null),
    shellBoundary = null,
    SubtreeSuspenseContextMask = 1,
    ForceSuspenseFallback = 2,
    suspenseStackCursor = createCursor(0),
    NoFlags = 0,
    HasEffect = 1,
    Insertion = 2,
    Layout = 4,
    Passive = 8,
    AbortControllerLocal = "undefined" !== typeof AbortController ? AbortController : function () {
      var listeners = [],
        signal = this.signal = {
          aborted: !1,
```

```
        addEventListener: function (type, listener) {
          listeners.push(listener);
        }
      };
      this.abort = function () {
        signal.aborted = !0;
        listeners.forEach(function (listener) {
          return listener();
        });
      };
    },
    scheduleCallback$2 = Scheduler.unstable_scheduleCallback,
    NormalPriority = Scheduler.unstable_NormalPriority,
    CacheContext = {
      $$typeof: REACT_CONTEXT_TYPE,
      Consumer: null,
      Provider: null,

      _currentValue: null,
      _currentValue2: null,
      _threadCount: 0,
      _currentRenderer: null,
      _currentRenderer2: null
    },
    currentEntangledListeners = null,
    currentEntangledPendingCount = 0,
    currentEntangledLane = 0,
    currentEntangledActionThenable = null,
    prevOnStartTransitionFinish = ReactSharedInternals.S;
  ReactSharedInternals.S = function (transition, returnValue) {
    "object" === typeof returnValue && null !== returnValue && "function" === typeof
returnValue.then && entangleAsyncAction(transition, returnValue);
    null !== prevOnStartTransitionFinish && prevOnStartTransitionFinish(transition, returnValue);
  };
  var resumedCache = createCursor(null),
    didWarnUncachedGetSnapshot;
  var didWarnAboutMismatchedHooksForComponent = new Set();
  var didWarnAboutUseWrappedInTryCatch = new Set();
  var didWarnAboutAsyncClientComponent = new Set();
  var didWarnAboutUseFormState = new Set();
  var renderLanes = 0,
    currentlyRenderingFiber$1 = null,
    currentHook = null,
    workInProgressHook = null,
    didScheduleRenderPhaseUpdate = !1,
    didScheduleRenderPhaseUpdateDuringThisPass = !1,
    shouldDoubleInvokeUserFnsInHooksDEV = !1,
    localIdCounter = 0,
    thenableIndexCounter = 0,
```

```
  thenableState = null,
  globalClientIdCounter = 0,
  RE_RENDER_LIMIT = 25,
  currentHookNameInDev = null,
  hookTypesDev = null,
  hookTypesUpdateIndexDev = -1,
  ignorePreviousDependencies = !1;
var createFunctionComponentUpdateQueue = function () {
  return {
    lastEffect: null,
    events: null,
    stores: null,
    memoCache: null
  };
};
var ContextOnlyDispatcher = {
  readContext: readContext,
  use: use,
  useCallback: throwInvalidHookError,
  useContext: throwInvalidHookError,
  useEffect: throwInvalidHookError,
  useImperativeHandle: throwInvalidHookError,
  useLayoutEffect: throwInvalidHookError,
  useInsertionEffect: throwInvalidHookError,
  useMemo: throwInvalidHookError,
  useReducer: throwInvalidHookError,
  useRef: throwInvalidHookError,
  useState: throwInvalidHookError,
  useDebugValue: throwInvalidHookError,
  useDeferredValue: throwInvalidHookError,
  useTransition: throwInvalidHookError,
  useSyncExternalStore: throwInvalidHookError,
  useId: throwInvalidHookError
};
ContextOnlyDispatcher.useCacheRefresh = throwInvalidHookError;
ContextOnlyDispatcher.useMemoCache = throwInvalidHookError;
ContextOnlyDispatcher.useHostTransitionStatus = throwInvalidHookError;
ContextOnlyDispatcher.useFormState = throwInvalidHookError;
ContextOnlyDispatcher.useActionState = throwInvalidHookError;
ContextOnlyDispatcher.useOptimistic = throwInvalidHookError;
var HooksDispatcherOnMountInDEV = null,
  HooksDispatcherOnMountWithHookTypesInDEV = null,
  HooksDispatcherOnUpdateInDEV = null,
  HooksDispatcherOnRerenderInDEV = null,
  InvalidNestedHooksDispatcherOnMountInDEV = null,
  InvalidNestedHooksDispatcherOnUpdateInDEV = null,
  InvalidNestedHooksDispatcherOnRerenderInDEV = null;
HooksDispatcherOnMountInDEV = {
  readContext: function (context) {
```

```
  return readContext(context);
},
use: use,
useCallback: function (callback, deps) {
  currentHookNameInDev = "useCallback";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  return mountCallback(callback, deps);
},
useContext: function (context) {
  currentHookNameInDev = "useContext";
  mountHookTypesDev();
  return readContext(context);
},
useEffect: function (create, deps) {
  currentHookNameInDev = "useEffect";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  return mountEffect(create, deps);
},
useImperativeHandle: function (ref, create, deps) {
  currentHookNameInDev = "useImperativeHandle";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  return mountImperativeHandle(ref, create, deps);
},
useInsertionEffect: function (create, deps) {
  currentHookNameInDev = "useInsertionEffect";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  mountEffectImpl(4, Insertion, create, deps);
},
useLayoutEffect: function (create, deps) {
  currentHookNameInDev = "useLayoutEffect";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  return mountLayoutEffect(create, deps);
},
useMemo: function (create, deps) {
  currentHookNameInDev = "useMemo";
  mountHookTypesDev();
  checkDepsAreArrayDev(deps);
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountMemo(create, deps);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
```

```
},
useReducer: function (reducer, initialArg, init) {
  currentHookNameInDev = "useReducer";
  mountHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountReducer(reducer, initialArg, init);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useRef: function (initialValue) {
  currentHookNameInDev = "useRef";
  mountHookTypesDev();
  return mountRef(initialValue);
},
useState: function (initialState) {
  currentHookNameInDev = "useState";
  mountHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountState(initialState);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useDebugValue: function () {
  currentHookNameInDev = "useDebugValue";
  mountHookTypesDev();
},
useDeferredValue: function (value, initialValue) {
  currentHookNameInDev = "useDeferredValue";
  mountHookTypesDev();
  return mountDeferredValue(value, initialValue);
},
useTransition: function () {
  currentHookNameInDev = "useTransition";
  mountHookTypesDev();
  return mountTransition();
},
useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
  currentHookNameInDev = "useSyncExternalStore";
  mountHookTypesDev();
  return mountSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
},
useId: function () {
  currentHookNameInDev = "useId";
```

```
    mountHookTypesDev();
    return mountId();
  },
  useCacheRefresh: function () {
    currentHookNameInDev = "useCacheRefresh";
    mountHookTypesDev();
    return mountRefresh();
  }
};
HooksDispatcherOnMountInDEV.useMemoCache = useMemoCache;
HooksDispatcherOnMountInDEV.useHostTransitionStatus = useHostTransitionStatus;
HooksDispatcherOnMountInDEV.useFormState = function (action, initialState) {
  currentHookNameInDev = "useFormState";
  mountHookTypesDev();
  warnOnUseFormStateInDev();
  return mountActionState(action, initialState);
};
HooksDispatcherOnMountInDEV.useActionState = function (action, initialState) {
  currentHookNameInDev = "useActionState";
  mountHookTypesDev();
  return mountActionState(action, initialState);
};
HooksDispatcherOnMountInDEV.useOptimistic = function (passthrough) {
  currentHookNameInDev = "useOptimistic";
  mountHookTypesDev();
  return mountOptimistic(passthrough);
};
HooksDispatcherOnMountWithHookTypesInDEV = {
  readContext: function (context) {
    return readContext(context);
  },
  use: use,
  useCallback: function (callback, deps) {
    currentHookNameInDev = "useCallback";
    updateHookTypesDev();
    return mountCallback(callback, deps);
  },
  useContext: function (context) {
    currentHookNameInDev = "useContext";
    updateHookTypesDev();
    return readContext(context);
  },
  useEffect: function (create, deps) {
    currentHookNameInDev = "useEffect";
    updateHookTypesDev();
    return mountEffect(create, deps);
  },
  useImperativeHandle: function (ref, create, deps) {
    currentHookNameInDev = "useImperativeHandle";
```

```
  updateHookTypesDev();
  return mountImperativeHandle(ref, create, deps);
},
useInsertionEffect: function (create, deps) {
  currentHookNameInDev = "useInsertionEffect";
  updateHookTypesDev();
  mountEffectImpl(4, Insertion, create, deps);
},
useLayoutEffect: function (create, deps) {
  currentHookNameInDev = "useLayoutEffect";
  updateHookTypesDev();
  return mountLayoutEffect(create, deps);
},
useMemo: function (create, deps) {
  currentHookNameInDev = "useMemo";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountMemo(create, deps);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useReducer: function (reducer, initialArg, init) {
  currentHookNameInDev = "useReducer";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountReducer(reducer, initialArg, init);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useRef: function (initialValue) {
  currentHookNameInDev = "useRef";
  updateHookTypesDev();
  return mountRef(initialValue);
},
useState: function (initialState) {
  currentHookNameInDev = "useState";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
  try {
    return mountState(initialState);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
```

```
      }
    },

    useDebugValue: function () {
      currentHookNameInDev = "useDebugValue";
      updateHookTypesDev();
    },
    useDeferredValue: function (value, initialValue) {
      currentHookNameInDev = "useDeferredValue";
      updateHookTypesDev();
      return mountDeferredValue(value, initialValue);
    },
    useTransition: function () {
      currentHookNameInDev = "useTransition";
      updateHookTypesDev();
      return mountTransition();
    },
    useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
      currentHookNameInDev = "useSyncExternalStore";
      updateHookTypesDev();
      return mountSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
    },
    useId: function () {
      currentHookNameInDev = "useId";
      updateHookTypesDev();
      return mountId();
    },
    useCacheRefresh: function () {
      currentHookNameInDev = "useCacheRefresh";
      updateHookTypesDev();
      return mountRefresh();
    }
  };
  HooksDispatcherOnMountWithHookTypesInDEV.useMemoCache = useMemoCache;
  HooksDispatcherOnMountWithHookTypesInDEV.useHostTransitionStatus =
useHostTransitionStatus;
  HooksDispatcherOnMountWithHookTypesInDEV.useFormState = function (action, initialState) {
    currentHookNameInDev = "useFormState";
    updateHookTypesDev();
    warnOnUseFormStateInDev();
    return mountActionState(action, initialState);
  };
  HooksDispatcherOnMountWithHookTypesInDEV.useActionState = function (action, initialState) {
    currentHookNameInDev = "useActionState";
    updateHookTypesDev();
    return mountActionState(action, initialState);
  };
  HooksDispatcherOnMountWithHookTypesInDEV.useOptimistic = function (passthrough) {
    currentHookNameInDev = "useOptimistic";
```

```
  updateHookTypesDev();
  return mountOptimistic(passthrough);
};
HooksDispatcherOnUpdateInDEV = {
  readContext: function (context) {
    return readContext(context);
  },
  use: use,
  useCallback: function (callback, deps) {
    currentHookNameInDev = "useCallback";
    updateHookTypesDev();
    return updateCallback(callback, deps);
  },
  useContext: function (context) {
    currentHookNameInDev = "useContext";
    updateHookTypesDev();
    return readContext(context);
  },
  useEffect: function (create, deps) {
    currentHookNameInDev = "useEffect";
    updateHookTypesDev();
    updateEffectImpl(2048, Passive, create, deps);
  },
  useImperativeHandle: function (ref, create, deps) {
    currentHookNameInDev = "useImperativeHandle";
    updateHookTypesDev();
    return updateImperativeHandle(ref, create, deps);
  },
  useInsertionEffect: function (create, deps) {
    currentHookNameInDev = "useInsertionEffect";
    updateHookTypesDev();
    return updateEffectImpl(4, Insertion, create, deps);
  },
  useLayoutEffect: function (create, deps) {
    currentHookNameInDev = "useLayoutEffect";
    updateHookTypesDev();
    return updateEffectImpl(4, Layout, create, deps);
  },
  useMemo: function (create, deps) {
    currentHookNameInDev = "useMemo";
    updateHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
    try {
      return updateMemo(create, deps);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
```

```
useReducer: function (reducer, initialArg, init) {
  currentHookNameInDev = "useReducer";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
  try {
    return updateReducer(reducer, initialArg, init);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useRef: function () {
  currentHookNameInDev = "useRef";
  updateHookTypesDev();
  return updateWorkInProgressHook().memoizedState;
},
useState: function () {
  currentHookNameInDev = "useState";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
  try {
    return updateReducer(basicStateReducer);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useDebugValue: function () {
  currentHookNameInDev = "useDebugValue";
  updateHookTypesDev();
},
useDeferredValue: function (value, initialValue) {
  currentHookNameInDev = "useDeferredValue";
  updateHookTypesDev();
  return updateDeferredValue(value, initialValue);
},
useTransition: function () {
  currentHookNameInDev = "useTransition";
  updateHookTypesDev();
  return updateTransition();
},
useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
  currentHookNameInDev = "useSyncExternalStore";
  updateHookTypesDev();
  return updateSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
},
useId: function () {
  currentHookNameInDev = "useId";
  updateHookTypesDev();
```

```
    return updateWorkInProgressHook().memoizedState;
  },
  useCacheRefresh: function () {
    currentHookNameInDev = "useCacheRefresh";
    updateHookTypesDev();
    return updateWorkInProgressHook().memoizedState;
  }
};
HooksDispatcherOnUpdateInDEV.useMemoCache = useMemoCache;
HooksDispatcherOnUpdateInDEV.useHostTransitionStatus = useHostTransitionStatus;
HooksDispatcherOnUpdateInDEV.useFormState = function (action) {
  currentHookNameInDev = "useFormState";
  updateHookTypesDev();
  warnOnUseFormStateInDev();
  return updateActionState(action);
};
HooksDispatcherOnUpdateInDEV.useActionState = function (action) {
  currentHookNameInDev = "useActionState";
  updateHookTypesDev();
  return updateActionState(action);
};
HooksDispatcherOnUpdateInDEV.useOptimistic = function (passthrough, reducer) {
  currentHookNameInDev = "useOptimistic";
  updateHookTypesDev();
  return updateOptimistic(passthrough, reducer);
};
HooksDispatcherOnRerenderInDEV = {
  readContext: function (context) {
    return readContext(context);
  },
  use: use,
  useCallback: function (callback, deps) {
    currentHookNameInDev = "useCallback";
    updateHookTypesDev();
    return updateCallback(callback, deps);
  },
  useContext: function (context) {
    currentHookNameInDev = "useContext";
    updateHookTypesDev();
    return readContext(context);
  },
  useEffect: function (create, deps) {
    currentHookNameInDev = "useEffect";
    updateHookTypesDev();
    updateEffectImpl(2048, Passive, create, deps);
  },
  useImperativeHandle: function (ref, create, deps) {
    currentHookNameInDev = "useImperativeHandle";
    updateHookTypesDev();
```

```
  return updateImperativeHandle(ref, create, deps);
},
useInsertionEffect: function (create, deps) {
  currentHookNameInDev = "useInsertionEffect";
  updateHookTypesDev();
  return updateEffectImpl(4, Insertion, create, deps);
},
useLayoutEffect: function (create, deps) {
  currentHookNameInDev = "useLayoutEffect";
  updateHookTypesDev();
  return updateEffectImpl(4, Layout, create, deps);
},
useMemo: function (create, deps) {
  currentHookNameInDev = "useMemo";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnRerenderInDEV;
  try {
    return updateMemo(create, deps);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useReducer: function (reducer, initialArg, init) {
  currentHookNameInDev = "useReducer";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnRerenderInDEV;
  try {
    return rerenderReducer(reducer, initialArg, init);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useRef: function () {
  currentHookNameInDev = "useRef";
  updateHookTypesDev();
  return updateWorkInProgressHook().memoizedState;
},
useState: function () {
  currentHookNameInDev = "useState";
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnRerenderInDEV;
  try {
    return rerenderReducer(basicStateReducer);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
```

```
  },
  useDebugValue: function () {
    currentHookNameInDev = "useDebugValue";
    updateHookTypesDev();
  },
  useDeferredValue: function (value, initialValue) {
    currentHookNameInDev = "useDeferredValue";
    updateHookTypesDev();
    return rerenderDeferredValue(value, initialValue);
  },
  useTransition: function () {
    currentHookNameInDev = "useTransition";
    updateHookTypesDev();
    return rerenderTransition();
  },
  useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
    currentHookNameInDev = "useSyncExternalStore";
    updateHookTypesDev();
    return updateSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
  },
  useId: function () {
    currentHookNameInDev = "useId";
    updateHookTypesDev();
    return updateWorkInProgressHook().memoizedState;
  },
  useCacheRefresh: function () {
    currentHookNameInDev = "useCacheRefresh";
    updateHookTypesDev();
    return updateWorkInProgressHook().memoizedState;
  }
};
HooksDispatcherOnRerenderInDEV.useMemoCache = useMemoCache;
HooksDispatcherOnRerenderInDEV.useHostTransitionStatus = useHostTransitionStatus;
HooksDispatcherOnRerenderInDEV.useFormState = function (action) {
  currentHookNameInDev = "useFormState";
  updateHookTypesDev();
  warnOnUseFormStateInDev();

  return rerenderActionState(action);
};
HooksDispatcherOnRerenderInDEV.useActionState = function (action) {
  currentHookNameInDev = "useActionState";
  updateHookTypesDev();
  return rerenderActionState(action);
};
HooksDispatcherOnRerenderInDEV.useOptimistic = function (passthrough, reducer) {
  currentHookNameInDev = "useOptimistic";
  updateHookTypesDev();
  return rerenderOptimistic(passthrough, reducer);
```

```
};
InvalidNestedHooksDispatcherOnMountInDEV = {
  readContext: function (context) {
    warnInvalidContextAccess();
    return readContext(context);
  },
  use: function (usable) {
    warnInvalidHookAccess();
    return use(usable);
  },
  useCallback: function (callback, deps) {
    currentHookNameInDev = "useCallback";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountCallback(callback, deps);
  },
  useContext: function (context) {
    currentHookNameInDev = "useContext";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return readContext(context);
  },
  useEffect: function (create, deps) {
    currentHookNameInDev = "useEffect";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountEffect(create, deps);
  },
  useImperativeHandle: function (ref, create, deps) {
    currentHookNameInDev = "useImperativeHandle";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountImperativeHandle(ref, create, deps);
  },
  useInsertionEffect: function (create, deps) {
    currentHookNameInDev = "useInsertionEffect";
    warnInvalidHookAccess();
    mountHookTypesDev();
    mountEffectImpl(4, Insertion, create, deps);
  },
  useLayoutEffect: function (create, deps) {
    currentHookNameInDev = "useLayoutEffect";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountLayoutEffect(create, deps);
  },
  useMemo: function (create, deps) {
    currentHookNameInDev = "useMemo";
    warnInvalidHookAccess();
```

```
    mountHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
    try {
      return mountMemo(create, deps);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useReducer: function (reducer, initialArg, init) {
    currentHookNameInDev = "useReducer";
    warnInvalidHookAccess();
    mountHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
    try {
      return mountReducer(reducer, initialArg, init);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useRef: function (initialValue) {
    currentHookNameInDev = "useRef";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountRef(initialValue);
  },
  useState: function (initialState) {
    currentHookNameInDev = "useState";
    warnInvalidHookAccess();
    mountHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnMountInDEV;
    try {
      return mountState(initialState);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useDebugValue: function () {
    currentHookNameInDev = "useDebugValue";
    warnInvalidHookAccess();
    mountHookTypesDev();
  },
  useDeferredValue: function (value, initialValue) {
    currentHookNameInDev = "useDeferredValue";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountDeferredValue(value, initialValue);
```

```
  },
  useTransition: function () {
    currentHookNameInDev = "useTransition";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountTransition();
  },
  useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
    currentHookNameInDev = "useSyncExternalStore";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
  },
  useId: function () {
    currentHookNameInDev = "useId";
    warnInvalidHookAccess();
    mountHookTypesDev();
    return mountId();
  },
  useCacheRefresh: function () {
    currentHookNameInDev = "useCacheRefresh";
    mountHookTypesDev();
    return mountRefresh();
  },
  useMemoCache: function (size) {
    warnInvalidHookAccess();
    return useMemoCache(size);
  }
};
InvalidNestedHooksDispatcherOnMountInDEV.useHostTransitionStatus = useHostTransitionStatus;
InvalidNestedHooksDispatcherOnMountInDEV.useFormState = function (action, initialState) {
  currentHookNameInDev = "useFormState";
  warnInvalidHookAccess();
  mountHookTypesDev();
  return mountActionState(action, initialState);
};
InvalidNestedHooksDispatcherOnMountInDEV.useActionState = function (action, initialState) {
  currentHookNameInDev = "useActionState";
  warnInvalidHookAccess();
  mountHookTypesDev();
  return mountActionState(action, initialState);
};
InvalidNestedHooksDispatcherOnMountInDEV.useOptimistic = function (passthrough) {
  currentHookNameInDev = "useOptimistic";
  warnInvalidHookAccess();
  mountHookTypesDev();
  return mountOptimistic(passthrough);
};
InvalidNestedHooksDispatcherOnUpdateInDEV = {
```

```
readContext: function (context) {
  warnInvalidContextAccess();
  return readContext(context);
},
use: function (usable) {
  warnInvalidHookAccess();
  return use(usable);
},
useCallback: function (callback, deps) {
  currentHookNameInDev = "useCallback";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateCallback(callback, deps);
},
useContext: function (context) {
  currentHookNameInDev = "useContext";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return readContext(context);
},
useEffect: function (create, deps) {
  currentHookNameInDev = "useEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  updateEffectImpl(2048, Passive, create, deps);
},
useImperativeHandle: function (ref, create, deps) {
  currentHookNameInDev = "useImperativeHandle";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateImperativeHandle(ref, create, deps);
},
useInsertionEffect: function (create, deps) {
  currentHookNameInDev = "useInsertionEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateEffectImpl(4, Insertion, create, deps);
},
useLayoutEffect: function (create, deps) {
  currentHookNameInDev = "useLayoutEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateEffectImpl(4, Layout, create, deps);
},
useMemo: function (create, deps) {
  currentHookNameInDev = "useMemo";
  warnInvalidHookAccess();
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
```

```
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
  try {
    return updateMemo(create, deps);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useReducer: function (reducer, initialArg, init) {
  currentHookNameInDev = "useReducer";
  warnInvalidHookAccess();
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
  try {
    return updateReducer(reducer, initialArg, init);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useRef: function () {
  currentHookNameInDev = "useRef";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateWorkInProgressHook().memoizedState;
},
useState: function () {
  currentHookNameInDev = "useState";
  warnInvalidHookAccess();
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
  try {
    return updateReducer(basicStateReducer);
  } finally {
    ReactSharedInternals.H = prevDispatcher;
  }
},
useDebugValue: function () {
  currentHookNameInDev = "useDebugValue";
  warnInvalidHookAccess();
  updateHookTypesDev();
},
useDeferredValue: function (value, initialValue) {
  currentHookNameInDev = "useDeferredValue";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateDeferredValue(value, initialValue);
},
useTransition: function () {
```

```
      currentHookNameInDev = "useTransition";
      warnInvalidHookAccess();
      updateHookTypesDev();
      return updateTransition();
    },
    useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
      currentHookNameInDev = "useSyncExternalStore";
      warnInvalidHookAccess();
      updateHookTypesDev();
      return updateSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
    },
    useId: function () {
      currentHookNameInDev = "useId";
      warnInvalidHookAccess();
      updateHookTypesDev();
      return updateWorkInProgressHook().memoizedState;
    },
    useCacheRefresh: function () {
      currentHookNameInDev = "useCacheRefresh";
      updateHookTypesDev();
      return updateWorkInProgressHook().memoizedState;
    },
    useMemoCache: function (size) {
      warnInvalidHookAccess();
      return useMemoCache(size);
    }
  };
  InvalidNestedHooksDispatcherOnUpdateInDEV.useHostTransitionStatus = useHostTransitionStatus;
  InvalidNestedHooksDispatcherOnUpdateInDEV.useFormState = function (action) {
    currentHookNameInDev = "useFormState";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return updateActionState(action);
  };
  InvalidNestedHooksDispatcherOnUpdateInDEV.useActionState
= function (action) {
    currentHookNameInDev = "useActionState";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return updateActionState(action);
  };
  InvalidNestedHooksDispatcherOnUpdateInDEV.useOptimistic = function (passthrough, reducer) {
    currentHookNameInDev = "useOptimistic";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return updateOptimistic(passthrough, reducer);
  };
  InvalidNestedHooksDispatcherOnRerenderInDEV = {
    readContext: function (context) {
```

```
  warnInvalidContextAccess();
  return readContext(context);
},
use: function (usable) {
  warnInvalidHookAccess();
  return use(usable);
},
useCallback: function (callback, deps) {
  currentHookNameInDev = "useCallback";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateCallback(callback, deps);
},
useContext: function (context) {
  currentHookNameInDev = "useContext";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return readContext(context);
},
useEffect: function (create, deps) {
  currentHookNameInDev = "useEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  updateEffectImpl(2048, Passive, create, deps);
},
useImperativeHandle: function (ref, create, deps) {
  currentHookNameInDev = "useImperativeHandle";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateImperativeHandle(ref, create, deps);
},
useInsertionEffect: function (create, deps) {
  currentHookNameInDev = "useInsertionEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateEffectImpl(4, Insertion, create, deps);
},
useLayoutEffect: function (create, deps) {
  currentHookNameInDev = "useLayoutEffect";
  warnInvalidHookAccess();
  updateHookTypesDev();
  return updateEffectImpl(4, Layout, create, deps);
},
useMemo: function (create, deps) {
  currentHookNameInDev = "useMemo";
  warnInvalidHookAccess();
  updateHookTypesDev();
  var prevDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
```

```
    try {
      return updateMemo(create, deps);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useReducer: function (reducer, initialArg, init) {
    currentHookNameInDev = "useReducer";
    warnInvalidHookAccess();
    updateHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
    try {
      return rerenderReducer(reducer, initialArg, init);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useRef: function () {
    currentHookNameInDev = "useRef";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return updateWorkInProgressHook().memoizedState;
  },
  useState: function () {
    currentHookNameInDev = "useState";
    warnInvalidHookAccess();
    updateHookTypesDev();
    var prevDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = InvalidNestedHooksDispatcherOnUpdateInDEV;
    try {
      return rerenderReducer(basicStateReducer);
    } finally {
      ReactSharedInternals.H = prevDispatcher;
    }
  },
  useDebugValue: function () {
    currentHookNameInDev = "useDebugValue";
    warnInvalidHookAccess();
    updateHookTypesDev();
  },
  useDeferredValue: function (value, initialValue) {
    currentHookNameInDev = "useDeferredValue";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return rerenderDeferredValue(value, initialValue);
  },
  useTransition: function () {
    currentHookNameInDev = "useTransition";
```

```
      warnInvalidHookAccess();
      updateHookTypesDev();
      return rerenderTransition();
    },
    useSyncExternalStore: function (subscribe, getSnapshot, getServerSnapshot) {
      currentHookNameInDev = "useSyncExternalStore";
      warnInvalidHookAccess();
      updateHookTypesDev();
      return updateSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
    },
    useId: function () {
      currentHookNameInDev = "useId";
      warnInvalidHookAccess();
      updateHookTypesDev();
      return updateWorkInProgressHook().memoizedState;
    },
    useCacheRefresh: function () {
      currentHookNameInDev = "useCacheRefresh";
      updateHookTypesDev();
      return updateWorkInProgressHook().memoizedState;
    },
    useMemoCache: function (size) {
      warnInvalidHookAccess();
      return useMemoCache(size);
    }
  };
  InvalidNestedHooksDispatcherOnRerenderInDEV.useHostTransitionStatus =
useHostTransitionStatus;
  InvalidNestedHooksDispatcherOnRerenderInDEV.useFormState = function (action) {
    currentHookNameInDev = "useFormState";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return rerenderActionState(action);
  };
  InvalidNestedHooksDispatcherOnRerenderInDEV.useActionState = function (action) {
    currentHookNameInDev = "useActionState";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return rerenderActionState(action);
  };
  InvalidNestedHooksDispatcherOnRerenderInDEV.useOptimistic = function (passthrough, reducer) {
    currentHookNameInDev = "useOptimistic";
    warnInvalidHookAccess();
    updateHookTypesDev();
    return rerenderOptimistic(passthrough, reducer);
  };
  var fakeInternalInstance = {};
  var didWarnAboutStateAssignmentForComponent = new Set();
  var didWarnAboutUninitializedState = new Set();
```

```
  var didWarnAboutGetSnapshotBeforeUpdateWithoutDidUpdate = new Set();
  var didWarnAboutLegacyLifecyclesAndDerivedState = new Set();
  var didWarnAboutDirectlyAssigningPropsToState = new Set();
  var didWarnAboutUndefinedDerivedState = new Set();
  var didWarnAboutContextTypes$1 = new Set();
  var didWarnAboutChildContextTypes = new Set();
  var didWarnAboutInvalidateContextType = new Set();
  var didWarnOnInvalidCallback = new Set();
  Object.freeze(fakeInternalInstance);
  var classComponentUpdater = {
      isMounted: function (component) {
        var owner = current;
        if (null !== owner && isRendering && 1 === owner.tag) {
          var instance = owner.stateNode;
          instance._warnedAboutRefsInRender || console.error("%s is accessing isMounted inside its
render() function. render() should be a pure function of props and state. It should never access
something that requires stale data from the previous render, such as refs. Move this logic to
componentDidMount and componentDidUpdate instead.", getComponentNameFromFiber(owner) || "A
component");
          instance._warnedAboutRefsInRender = !0;
        }
        return (component = component._reactInternals) ? getNearestMountedFiber(component) ===
component : !1;
      },
      enqueueSetState: function (inst, payload, callback) {
        inst = inst._reactInternals;
        var lane = requestUpdateLane(inst),
          update = createUpdate(lane);
        update.payload = payload;
        void 0 !== callback && null !== callback && (warnOnInvalidCallback(callback), update.callback
= callback);
        payload = enqueueUpdate(inst, update, lane);
        null !== payload && (scheduleUpdateOnFiber(payload, inst, lane), entangleTransitions(payload,
inst, lane));
        markStateUpdateScheduled(inst, lane);
      },
      enqueueReplaceState: function (inst, payload, callback) {
        inst = inst._reactInternals;
        var lane = requestUpdateLane(inst),
          update = createUpdate(lane);
        update.tag = ReplaceState;
        update.payload = payload;
        void 0 !== callback && null !== callback && (warnOnInvalidCallback(callback), update.callback
= callback);
        payload = enqueueUpdate(inst, update, lane);
        null !== payload && (scheduleUpdateOnFiber(payload, inst, lane), entangleTransitions(payload,
inst, lane));
        markStateUpdateScheduled(inst, lane);
      },
```

```
    enqueueForceUpdate: function (inst, callback) {
      inst = inst._reactInternals;
      var lane = requestUpdateLane(inst),
        update = createUpdate(lane);
      update.tag = ForceUpdate;
      void 0 !== callback && null !== callback && (warnOnInvalidCallback(callback), update.callback
= callback);
      callback = enqueueUpdate(inst, update, lane);
      null !== callback && (scheduleUpdateOnFiber(callback, inst, lane), entangleTransitions(callback,
inst, lane));
      null !== injectedProfilingHooks && "function" === typeof
injectedProfilingHooks.markForceUpdateScheduled &&
injectedProfilingHooks.markForceUpdateScheduled(inst, lane);
    }
  },
  reportGlobalError = "function" === typeof reportError ? reportError : function (error) {
    if ("object" === typeof window && "function" === typeof window.ErrorEvent) {
      var event = new window.ErrorEvent("error", {
        bubbles: !0,
        cancelable: !0,
        message: "object" === typeof error && null !== error && "string" === typeof error.message ?
String(error.message) : String(error),
        error: error
      });
      if (!window.dispatchEvent(event)) return;
    } else if ("object" === typeof process && "function" === typeof process.emit) {
      process.emit("uncaughtException", error);
      return;
    }
    console.error(error);
  },
  componentName = null,
  errorBoundaryName = null,
  SelectiveHydrationException = Error("This is not a real error. It's an implementation detail of React's
selective hydration feature. If this leaks into userspace, it's a bug in React. Please file an issue."),
  didReceiveUpdate = !1;
var didWarnAboutBadClass = {};
var didWarnAboutContextTypeOnFunctionComponent = {};
var didWarnAboutContextTypes = {};
var didWarnAboutGetDerivedStateOnFunctionComponent = {};
var didWarnAboutReassigningProps = !1;

var didWarnAboutRevealOrder = {};
var didWarnAboutTailOptions = {};
var SUSPENDED_MARKER = {
  dehydrated: null,
  treeContext: null,
  retryLane: 0
},
```

```
    hasWarnedAboutUsingNoValuePropOnContextProvider = !1,
    valueCursor = createCursor(null);
  var rendererCursorDEV = createCursor(null);
  var rendererSigil = {};
  var currentlyRenderingFiber = null,
    lastContextDependency = null,
    isDisallowedContextReadInDEV = !1,
    UpdateState = 0,
    ReplaceState = 1,
    ForceUpdate = 2,
    CaptureUpdate = 3,
    hasForceUpdate = !1;
  var didWarnUpdateInsideUpdate = !1;
  var currentlyProcessingQueue = null;
  var didReadFromEntangledAsyncAction = !1,
    didWarnAboutUndefinedSnapshotBeforeUpdate = null;
  didWarnAboutUndefinedSnapshotBeforeUpdate = new Set();
  var offscreenSubtreeIsHidden = !1,
    offscreenSubtreeWasHidden = !1,
    needsFormReset = !1,
    PossiblyWeakSet = "function" === typeof WeakSet ? WeakSet : Set,
    nextEffect = null,
    inProgressLanes = null,
    inProgressRoot = null,
    shouldFireAfterActiveInstanceBlur = !1,
    hostParent = null,
    hostParentIsContainer = !1,
    currentHoistableRoot = null,
    suspenseyCommitFlag = 8192;
  var hasBadMapPolyfill = !1;
  try {
    var nonExtensibleObject = Object.preventExtensions({});
    new Map([[nonExtensibleObject, null]]);
    new Set([nonExtensibleObject]);
  } catch (e$7) {
    hasBadMapPolyfill = !0;
  }
  var DefaultAsyncDispatcher = {
    getCacheForType: function (resourceType) {
      var cache = readContext(CacheContext),
        cacheForType = cache.data.get(resourceType);
      void 0 === cacheForType && (cacheForType = resourceType(), cache.data.set(resourceType,
cacheForType));
      return cacheForType;
    },
    getOwner: function () {
      return current;
    }
  };
```

```
if ("function" === typeof Symbol && Symbol.for) {
  var symbolFor = Symbol.for;
  symbolFor("selector.component");
  symbolFor("selector.has_pseudo_class");
  symbolFor("selector.role");
  symbolFor("selector.test_id");
  symbolFor("selector.text");
}
var commitHooks = [],
  PossiblyWeakMap = "function" === typeof WeakMap ? WeakMap : Map,
  NoContext = 0,
  RenderContext = 2,
  CommitContext = 4,
  RootInProgress = 0,
  RootFatalErrored = 1,
  RootErrored = 2,
  RootSuspended = 3,
  RootSuspendedWithDelay = 4,
  RootCompleted = 5,
  RootDidNotComplete = 6,
  executionContext = NoContext,
  workInProgressRoot = null,
  workInProgress = null,
  workInProgressRootRenderLanes = 0,
  NotSuspended = 0,
  SuspendedOnError = 1,
  SuspendedOnData = 2,
  SuspendedOnImmediate = 3,
  SuspendedOnInstance = 4,
  SuspendedOnInstanceAndReadyToContinue = 5,
  SuspendedOnDeprecatedThrowPromise = 6,
  SuspendedAndReadyToContinue = 7,
  SuspendedOnHydration = 8,
  workInProgressSuspendedReason = NotSuspended,
  workInProgressThrownValue = null,
  workInProgressRootDidSkipSuspendedSiblings = !1,
  workInProgressRootIsPrerendering = !1,
  workInProgressRootDidAttachPingListener = !1,
  entangledRenderLanes = 0,
  workInProgressRootExitStatus = RootInProgress,
  workInProgressRootSkippedLanes = 0,
  workInProgressRootInterleavedUpdatedLanes = 0,
  workInProgressRootPingedLanes = 0,
  workInProgressDeferredLane = 0,
  workInProgressSuspendedRetryLanes = 0,
  workInProgressRootConcurrentErrors = null,
  workInProgressRootRecoverableErrors = null,
  workInProgressRootDidIncludeRecursiveRenderUpdate = !1,
  globalMostRecentFallbackTime = 0,
```

```
  FALLBACK_THROTTLE_MS = 300,
  workInProgressRootRenderTargetTime = Infinity,
  RENDER_TIMEOUT_MS = 500,
  workInProgressTransitions = null,
  legacyErrorBoundariesThatAlreadyFailed = null,
  rootDoesHavePassiveEffects = !1,
  rootWithPendingPassiveEffects = null,
  pendingPassiveEffectsLanes = 0,
  pendingPassiveEffectsRemainingLanes = 0,
  pendingPassiveTransitions = null,
  NESTED_UPDATE_LIMIT = 50,
  nestedUpdateCount = 0,
  rootWithNestedUpdates = null,
  isFlushingPassiveEffects = !1,
  didScheduleUpdateDuringPassiveEffects = !1,
  NESTED_PASSIVE_UPDATE_LIMIT = 50,
  nestedPassiveUpdateCount = 0,
  rootWithPassiveNestedUpdates = null,
  isRunningInsertionEffect = !1,
  IMMEDIATE_COMMIT = 0,
  SUSPENDED_COMMIT = 1,
  THROTTLED_COMMIT = 2,
  didWarnStateUpdateForNotYetMountedComponent = null,
  didWarnAboutUpdateInRender = !1;
var didWarnAboutUpdateInRenderForAnotherComponent = new Set();
var fakeActCallbackNode$1 = {},
  firstScheduledRoot = null,
  lastScheduledRoot = null,
  didScheduleMicrotask = !1,
  didScheduleMicrotask_act = !1,
  mightHavePendingSyncWork = !1,
  isFlushingWork = !1,
  currentEventTransitionLane = 0,
  fakeActCallbackNode = {};
(function () {
  for (var i = 0; i < simpleEventPluginEvents.length; i++) {
    var eventName = simpleEventPluginEvents[i],
      domEventName = eventName.toLowerCase();
    eventName = eventName[0].toUpperCase() + eventName.slice(1);
    registerSimpleEvent(domEventName, "on" + eventName);
  }
  registerSimpleEvent(ANIMATION_END, "onAnimationEnd");
  registerSimpleEvent(ANIMATION_ITERATION, "onAnimationIteration");
  registerSimpleEvent(ANIMATION_START, "onAnimationStart");
  registerSimpleEvent("dblclick", "onDoubleClick");
  registerSimpleEvent("focusin", "onFocus");
  registerSimpleEvent("focusout", "onBlur");
  registerSimpleEvent(TRANSITION_RUN, "onTransitionRun");
  registerSimpleEvent(TRANSITION_START, "onTransitionStart");
```

```
    registerSimpleEvent(TRANSITION_CANCEL, "onTransitionCancel");
    registerSimpleEvent(TRANSITION_END, "onTransitionEnd");
  })();
  registerDirectEvent("onMouseEnter", ["mouseout", "mouseover"]);
  registerDirectEvent("onMouseLeave", ["mouseout", "mouseover"]);
  registerDirectEvent("onPointerEnter", ["pointerout", "pointerover"]);
  registerDirectEvent("onPointerLeave", ["pointerout", "pointerover"]);
  registerTwoPhaseEvent("onChange", "change click focusin focusout input keydown keyup
selectionchange".split(" "));
  registerTwoPhaseEvent("onSelect", "focusout contextmenu dragend focusin keydown keyup
mousedown mouseup selectionchange".split(" "));
  registerTwoPhaseEvent("onBeforeInput", ["compositionend", "keypress", "textInput", "paste"]);
  registerTwoPhaseEvent("onCompositionEnd", "compositionend focusout keydown keypress keyup
mousedown".split(" "));
  registerTwoPhaseEvent("onCompositionStart", "compositionstart focusout keydown keypress keyup
mousedown".split(" "));
  registerTwoPhaseEvent("onCompositionUpdate", "compositionupdate focusout keydown keypress
keyup mousedown".split(" "));
  var mediaEventTypes = "abort canplay canplaythrough durationchange emptied encrypted ended error
loadeddata loadedmetadata loadstart pause play playing progress ratechange resize seeked seeking
stalled suspend timeupdate volumechange waiting".split(" "),
    nonDelegatedEvents = new Set("beforetoggle cancel close invalid load scroll scrollend
toggle".split(" ").concat(mediaEventTypes)),
    listeningMarker = "_reactListening" + Math.random().toString(36).slice(2),
    didWarnControlledToUncontrolled = !1,
    didWarnUncontrolledToControlled = !1,
    didWarnFormActionType = !1,
    didWarnFormActionName = !1,
    didWarnFormActionTarget = !1,
    didWarnFormActionMethod = !1,
    didWarnPopoverTargetObject = !1;
  var didWarnForNewBooleanPropsWithEmptyValue = {};
  var canDiffStyleForHydrationWarning = !0;
  var NORMALIZE_NEWLINES_REGEX = /\r\n?/g,
    NORMALIZE_NULL_AND_REPLACEMENT_REGEX = /\u0000|\uFFFD/g,
    xlinkNamespace = "http://www.w3.org/1999/xlink",
    xmlNamespace = "http://www.w3.org/XML/1998/namespace",
    EXPECTED_FORM_ACTION_URL = "javascript:throw new Error('React form unexpectedly
submitted.')",
    SUPPRESS_HYDRATION_WARNING = "suppressHydrationWarning",
    SUSPENSE_START_DATA = "$",
    SUSPENSE_END_DATA = "/$",
    SUSPENSE_PENDING_START_DATA = "$?",
    SUSPENSE_FALLBACK_START_DATA = "$!",
    FORM_STATE_IS_MATCHING = "F!",
    FORM_STATE_IS_NOT_MATCHING = "F",
    STYLE = "style",
    HostContextNamespaceNone = 0,
    HostContextNamespaceSvg = 1,
```

```
    HostContextNamespaceMath = 2,
    eventsEnabled = null,
    selectionInformation = null,
    warnedUnknownTags = {
      dialog: !0,
      webview: !0
    },
    currentPopstateTransitionEvent = null,
    scheduleTimeout = "function" === typeof setTimeout ? setTimeout : void 0,
    cancelTimeout = "function" === typeof clearTimeout ? clearTimeout : void 0,
    noTimeout = -1,
    localPromise = "function" === typeof Promise ? Promise : void 0,
    scheduleMicrotask = "function" === typeof queueMicrotask ? queueMicrotask : "undefined" !==
typeof localPromise ? function (callback) {
      return localPromise.resolve(null).then(callback).catch(handleErrorInNextTick);
    } : scheduleTimeout,
    NotLoaded = 0,
    Loaded = 1,
    Errored = 2,
    Settled = 3,
    Inserted = 4,
    preloadPropsMap = new Map(),
    preconnectsSet = new Set(),
    previousDispatcher = ReactDOMSharedInternals.d;
  ReactDOMSharedInternals.d = {
    f: function () {
      var previousWasRendering = previousDispatcher.f(),
        wasRendering = flushSyncWork$1();
      return previousWasRendering || wasRendering;
    },
    r: function (form) {
      var formInst = getInstanceFromNode(form);
      null !== formInst && 5 === formInst.tag && "form" === formInst.type ?
requestFormReset$1(formInst) : previousDispatcher.r(form);
    },
    D: function (href) {
      previousDispatcher.D(href);
      preconnectAs("dns-prefetch", href, null);
    },
    C: function (href, crossOrigin) {
      previousDispatcher.C(href, crossOrigin);
      preconnectAs("preconnect", href, crossOrigin);
    },
    L: function (href, as, options) {
      previousDispatcher.L(href, as, options);
      var ownerDocument = globalDocument;

      if (ownerDocument && href && as) {
        var preloadSelector = 'link[rel="preload"][as="' +
```

```
escapeSelectorAttributeValueInsideDoubleQuotes(as) + '"]';
      "image" === as ? options && options.imageSrcSet ? (preloadSelector += '[imagesrcset="' +
escapeSelectorAttributeValueInsideDoubleQuotes(options.imageSrcSet) + '"]', "string" === typeof
options.imageSizes && (preloadSelector += '[imagesizes="' +
escapeSelectorAttributeValueInsideDoubleQuotes(options.imageSizes) + '"]')) : preloadSelector +=
'[href="' + escapeSelectorAttributeValueInsideDoubleQuotes(href) + '"]' : preloadSelector += '[href="'
+ escapeSelectorAttributeValueInsideDoubleQuotes(href) + '"]';
      var key = preloadSelector;
      switch (as) {
        case "style":
          key = getStyleKey(href);
          break;
        case "script":
          key = getScriptKey(href);
      }
      preloadPropsMap.has(key) || (href = assign({
        rel: "preload",
        href: "image" === as && options && options.imageSrcSet ? void 0 : href,
        as: as
      }, options), preloadPropsMap.set(key, href), null !==
ownerDocument.querySelector(preloadSelector) || "style" === as &&
ownerDocument.querySelector(getStylesheetSelectorFromKey(key)) || "script" === as &&
ownerDocument.querySelector(getScriptSelectorFromKey(key)) || (as =
ownerDocument.createElement("link"), setInitialProperties(as, "link", href),
markNodeAsHoistable(as), ownerDocument.head.appendChild(as)));
    }
  },
  m: function (href, options) {
    previousDispatcher.m(href, options);
    var ownerDocument = globalDocument;
    if (ownerDocument && href) {
      var as = options && "string" === typeof options.as ? options.as : "script",
        preloadSelector = 'link[rel="modulepreload"][as="' +
escapeSelectorAttributeValueInsideDoubleQuotes(as) + '"][href="' +
escapeSelectorAttributeValueInsideDoubleQuotes(href) + '"]',
        key = preloadSelector;
      switch (as) {
        case "audioworklet":
        case "paintworklet":
        case "serviceworker":
        case "sharedworker":
        case "worker":
        case "script":
          key = getScriptKey(href);
      }
      if (!preloadPropsMap.has(key) && (href = assign({
        rel: "modulepreload",
        href: href
      }, options), preloadPropsMap.set(key, href), null ===
```

```
ownerDocument.querySelector(preloadSelector))) {
        switch (as) {
          case "audioworklet":
          case "paintworklet":
          case "serviceworker":
          case "sharedworker":
          case "worker":
          case "script":
            if (ownerDocument.querySelector(getScriptSelectorFromKey(key))) return;
        }
        as = ownerDocument.createElement("link");
        setInitialProperties(as, "link", href);
        markNodeAsHoistable(as);
        ownerDocument.head.appendChild(as);
      }
    }
  },
  X: function (src, options) {
    previousDispatcher.X(src, options);
    var ownerDocument = globalDocument;
    if (ownerDocument && src) {
      var scripts = getResourcesFromRoot(ownerDocument).hoistableScripts,
        key = getScriptKey(src),
        resource = scripts.get(key);
      resource || (resource = ownerDocument.querySelector(getScriptSelectorFromKey(key)), resource
|| (src = assign({
        src: src,
        async: !0
      }, options), (options = preloadPropsMap.get(key)) && adoptPreloadPropsForScript(src, options),
resource = ownerDocument.createElement("script"), markNodeAsHoistable(resource),
setInitialProperties(resource, "link", src), ownerDocument.head.appendChild(resource)), resource = {
        type: "script",
        instance: resource,
        count: 1,
        state: null
      }, scripts.set(key, resource));
    }
  },
  S: function (href, precedence, options) {
    previousDispatcher.S(href, precedence, options);
    var ownerDocument = globalDocument;
    if (ownerDocument && href) {
      var styles = getResourcesFromRoot(ownerDocument).hoistableStyles,
        key = getStyleKey(href);
      precedence = precedence || "default";
      var resource = styles.get(key);
      if (!resource) {
        var state = {
          loading: NotLoaded,
```

```
          preload: null
        };
        if (resource = ownerDocument.querySelector(getStylesheetSelectorFromKey(key))) state.loading
= Loaded | Inserted;else {
          href = assign({
            rel: "stylesheet",
            href: href,
            "data-precedence": precedence
          }, options);
          (options = preloadPropsMap.get(key)) && adoptPreloadPropsForStylesheet(href, options);
          var link = resource = ownerDocument.createElement("link");
          markNodeAsHoistable(link);
          setInitialProperties(link, "link", href);
          link._p = new Promise(function (resolve, reject) {
            link.onload = resolve;
            link.onerror = reject;
          });
          link.addEventListener("load", function () {
            state.loading |= Loaded;
          });
          link.addEventListener("error", function () {
            state.loading |= Errored;
          });
          state.loading |= Inserted;
          insertStylesheet(resource, precedence, ownerDocument);
        }
        resource = {
          type: "stylesheet",
          instance: resource,
          count: 1,
          state: state
        };
        styles.set(key, resource);
      }
    }
  },
  M: function (src, options) {
    previousDispatcher.M(src, options);
    var ownerDocument = globalDocument;
    if (ownerDocument && src) {
      var scripts = getResourcesFromRoot(ownerDocument).hoistableScripts,
        key = getScriptKey(src),
        resource = scripts.get(key);
      resource || (resource = ownerDocument.querySelector(getScriptSelectorFromKey(key)), resource
|| (src = assign({
          src: src,
          async: !0,
          type: "module"
        }, options), (options = preloadPropsMap.get(key)) && adoptPreloadPropsForScript(src, options),
```

```
resource = ownerDocument.createElement("script"), markNodeAsHoistable(resource),
setInitialProperties(resource, "link", src), ownerDocument.head.appendChild(resource)), resource = {
          type: "script",
          instance: resource,
          count: 1,
          state: null
        }, scripts.set(key, resource));
      }
    }
  };
  var globalDocument = "undefined" === typeof document ? null : document,
    tagCaches = null,
    suspendedState = null,
    LAST_PRECEDENCE = null,
    precedencesByRoot = null,
    NotPendingTransition = NotPending,
    HostTransitionContext = {
      $$typeof: REACT_CONTEXT_TYPE,
      Provider: null,
      Consumer: null,
      _currentValue: NotPendingTransition,
      _currentValue2: NotPendingTransition,
      _threadCount: 0
    },
    badgeFormat = "%c%s%c ",
    badgeStyle = "background: #e6e6e6;background: light-dark(rgba(0,0,0,0.1),
rgba(255,255,255,0.25));color: #000000;color: light-dark(#000000, #ffffff);border-radius: 2px",
    resetStyle = "",
    pad = " ",
    bind = Function.prototype.bind;
  var didWarnAboutNestedUpdates = !1;
  var overrideHookState = null,
    overrideHookStateDeletePath = null,
    overrideHookStateRenamePath = null,
    overrideProps = null,
    overridePropsDeletePath = null,
    overridePropsRenamePath = null,
    scheduleUpdate = null,
    setErrorHandler = null,
    setSuspenseHandler = null;
  overrideHookState = function (fiber, id, path, value) {
    id = findHook(fiber, id);
    null !== id && (path = copyWithSetImpl(id.memoizedState, path, 0, value), id.memoizedState =
path, id.baseState = path, fiber.memoizedProps = assign({}, fiber.memoizedProps), path =
enqueueConcurrentRenderForLane(fiber, 2), null !== path && scheduleUpdateOnFiber(path, fiber, 2));
  };
  overrideHookStateDeletePath = function (fiber, id, path) {
    id = findHook(fiber, id);
    null !== id && (path = copyWithDeleteImpl(id.memoizedState, path, 0), id.memoizedState = path,
```

```
id.baseState = path, fiber.memoizedProps = assign({}, fiber.memoizedProps), path =
enqueueConcurrentRenderForLane(fiber, 2), null !== path && scheduleUpdateOnFiber(path, fiber, 2));
  };
  overrideHookStateRenamePath = function (fiber, id, oldPath, newPath) {
    id = findHook(fiber, id);
    null !== id && (oldPath = copyWithRename(id.memoizedState, oldPath, newPath),
id.memoizedState = oldPath, id.baseState = oldPath, fiber.memoizedProps = assign({},
fiber.memoizedProps), oldPath = enqueueConcurrentRenderForLane(fiber, 2), null !== oldPath &&
scheduleUpdateOnFiber(oldPath, fiber, 2));
  };
  overrideProps = function (fiber, path, value) {
    fiber.pendingProps = copyWithSetImpl(fiber.memoizedProps, path, 0, value);
    fiber.alternate && (fiber.alternate.pendingProps = fiber.pendingProps);
    path = enqueueConcurrentRenderForLane(fiber, 2);
    null !== path && scheduleUpdateOnFiber(path, fiber, 2);
  };
  overridePropsDeletePath = function (fiber, path) {
    fiber.pendingProps = copyWithDeleteImpl(fiber.memoizedProps, path, 0);
    fiber.alternate && (fiber.alternate.pendingProps = fiber.pendingProps);
    path = enqueueConcurrentRenderForLane(fiber, 2);
    null !== path && scheduleUpdateOnFiber(path, fiber, 2);
  };
  overridePropsRenamePath = function (fiber, oldPath, newPath) {
    fiber.pendingProps = copyWithRename(fiber.memoizedProps, oldPath, newPath);
    fiber.alternate && (fiber.alternate.pendingProps = fiber.pendingProps);
    oldPath = enqueueConcurrentRenderForLane(fiber, 2);
    null !== oldPath && scheduleUpdateOnFiber(oldPath, fiber, 2);
  };
  scheduleUpdate = function (fiber) {
    var root = enqueueConcurrentRenderForLane(fiber, 2);
    null !== root && scheduleUpdateOnFiber(root, fiber, 2);
  };
  setErrorHandler
 = function (newShouldErrorImpl) {
    shouldErrorImpl = newShouldErrorImpl;
  };
  setSuspenseHandler = function (newShouldSuspendImpl) {
    shouldSuspendImpl = newShouldSuspendImpl;
  };
  var _enabled = !0,
    return_targetInst = null,
    hasScheduledReplayAttempt = !1,
    queuedFocus = null,
    queuedDrag = null,
    queuedMouse = null,
    queuedPointers = new Map(),
    queuedPointerCaptures = new Map(),
    queuedExplicitHydrationTargets = [],
    discreteReplayableEvents = "mousedown mouseup touchcancel touchend touchstart auxclick
```

```
dblclick pointercancel pointerdown pointerup dragend dragstart drop compositionend compositionstart keydown keypress keyup input textInput copy cut paste click change contextmenu reset".split(" "),
    lastScheduledReplayQueue = null;
  ReactDOMHydrationRoot.prototype.render = ReactDOMRoot.prototype.render = function (children, JSCompiler_OptimizeArgumentsArray_p2) {
    var root = this._internalRoot;
    if (null === root) throw Error("Cannot update an unmounted root.");
    "function" === typeof JSCompiler_OptimizeArgumentsArray_p2 ? console.error("does not support the second callback argument. To execute a side effect after rendering, declare it in a component body with useEffect().") : isValidContainer(JSCompiler_OptimizeArgumentsArray_p2) ? console.error("You passed a container to the second argument of root.render(...). You don't need to pass it again since you already passed it to create the root.") : "undefined" !== typeof JSCompiler_OptimizeArgumentsArray_p2 && console.error("You passed a second argument to root.render(...) but it only accepts one argument.");
    JSCompiler_OptimizeArgumentsArray_p2 = root.current;
    var lane = requestUpdateLane(JSCompiler_OptimizeArgumentsArray_p2);
    updateContainerImpl(JSCompiler_OptimizeArgumentsArray_p2, lane, children, root, null, null);
  };
  ReactDOMHydrationRoot.prototype.unmount = ReactDOMRoot.prototype.unmount = function (JSCompiler_OptimizeArgumentsArray_p3) {
    "function" === typeof JSCompiler_OptimizeArgumentsArray_p3 && console.error("does not support a callback argument. To execute a side effect after rendering, declare it in a component body with useEffect().");
    JSCompiler_OptimizeArgumentsArray_p3 = this._internalRoot;
    if (null !== JSCompiler_OptimizeArgumentsArray_p3) {
      this._internalRoot = null;
      var container = JSCompiler_OptimizeArgumentsArray_p3.containerInfo;
      (executionContext & (RenderContext | CommitContext)) !== NoContext && console.error("Attempted to synchronously unmount a root while React was already rendering. React cannot finish unmounting the root until the current render has completed, which may lead to a race condition.");
      updateContainerSync(null, JSCompiler_OptimizeArgumentsArray_p3, null, null);
      flushSyncWork$1();
      container[internalContainerInstanceKey] = null;
    }
  };
  ReactDOMHydrationRoot.prototype.unstable_scheduleHydration = function (target) {
    if (target) {
      var updatePriority = resolveUpdatePriority();
      target = {
        blockedOn: null,
        target: target,
        priority: updatePriority
      };
      for (var i = 0; i < queuedExplicitHydrationTargets.length && 0 !== updatePriority && updatePriority < queuedExplicitHydrationTargets[i].priority; i++);
      queuedExplicitHydrationTargets.splice(i, 0, target);
      0 === i && attemptExplicitHydrationTarget(target);
    }
```

```
  };
  (function () {
    var isomorphicReactPackageVersion = React.version;
    if ("19.0.0" !== isomorphicReactPackageVersion) throw Error('Incompatible React versions: The
"react" and "react-dom" packages must have the exact same version. Instead got:\n  - react:      ' +
(isomorphicReactPackageVersion + "\n  - react-dom:  19.0.0\nLearn more:
https://react.dev/warnings/version-mismatch"));
  })();
  "function" === typeof Map && null != Map.prototype && "function" === typeof
Map.prototype.forEach && "function" === typeof Set && null != Set.prototype && "function" ===
typeof Set.prototype.clear && "function" === typeof Set.prototype.forEach || console.error("React
depends on Map and Set built-in types. Make sure that you load a polyfill in older browsers.
https://react.dev/link/react-polyfills");
  ReactDOMSharedInternals.findDOMNode = function (componentOrElement) {
    var fiber = componentOrElement._reactInternals;
    if (void 0 === fiber) {
      if ("function" === typeof componentOrElement.render) throw Error("Unable to find node on an
unmounted component.");
      componentOrElement = Object.keys(componentOrElement).join(",");
      throw Error("Argument appears to not be a ReactComponent. Keys: " + componentOrElement);
    }
    componentOrElement = findCurrentFiberUsingSlowPath(fiber);
    componentOrElement = null !== componentOrElement ?
findCurrentHostFiberImpl(componentOrElement) : null;
    componentOrElement = null === componentOrElement ? null : componentOrElement.stateNode;
    return componentOrElement;
  };
  if (!function () {
    var internals = {
      bundleType: 1,
      version: "19.0.0",
      rendererPackageName: "react-dom",
      currentDispatcherRef: ReactSharedInternals,
      findFiberByHostInstance: getClosestInstanceFromNode,
      reconcilerVersion: "19.0.0"
    };
    internals.overrideHookState = overrideHookState;
    internals.overrideHookStateDeletePath = overrideHookStateDeletePath;
    internals.overrideHookStateRenamePath = overrideHookStateRenamePath;
    internals.overrideProps = overrideProps;
    internals.overridePropsDeletePath = overridePropsDeletePath;
    internals.overridePropsRenamePath = overridePropsRenamePath;
    internals.scheduleUpdate = scheduleUpdate;
    internals.setErrorHandler = setErrorHandler;
    internals.setSuspenseHandler = setSuspenseHandler;
    internals.scheduleRefresh = scheduleRefresh;
    internals.scheduleRoot = scheduleRoot;
    internals.setRefreshHandler = setRefreshHandler;
    internals.getCurrentFiber = getCurrentFiberForDevTools;
```

```
    internals.getLaneLabelMap = getLaneLabelMap;
    internals.injectProfilingHooks = injectProfilingHooks;
    return injectInternals(internals);
  }() && canUseDOM && window.top === window.self && (-1 <
navigator.userAgent.indexOf("Chrome") && -1 === navigator.userAgent.indexOf("Edge") || -1 <
navigator.userAgent.indexOf("Firefox"))) {
    var protocol = window.location.protocol;
    /^(https?|file):$/.test(protocol) && console.info("%cDownload the React DevTools for a better
development experience: https://react.dev/link/react-devtools" + ("file:" === protocol ? "\nYou might
need to use a local HTTP server (instead of file://): https://react.dev/link/react-devtools-faq" : ""),
"font-weight:bold");
  }
  exports.createRoot = function (container, options) {
    if (!isValidContainer(container)) throw Error("Target container is not a DOM element.");
    warnIfReactDOMContainerInDEV(container);
    var isStrictMode = !1,
      identifierPrefix = "",
      onUncaughtError = defaultOnUncaughtError,
      onCaughtError = defaultOnCaughtError,
      onRecoverableError = defaultOnRecoverableError,
      transitionCallbacks = null;
    null !== options && void 0 !== options && (options.hydrate ? console.warn("hydrate through
createRoot is deprecated. Use ReactDOMClient.hydrateRoot(container, <App />) instead.") : "object"
=== typeof options && null !== options && options.$$typeof === REACT_ELEMENT_TYPE &&
console.error("You passed a JSX element to createRoot. You probably meant to call root.render instead.
Example usage:\n\n  let root = createRoot(domContainer);\n  root.render(<App />);"), !0 ===
options.unstable_strictMode && (isStrictMode = !0), void 0 !== options.identifierPrefix &&
(identifierPrefix = options.identifierPrefix), void 0 !== options.onUncaughtError &&
(onUncaughtError = options.onUncaughtError), void 0 !== options.onCaughtError && (onCaughtError
= options.onCaughtError), void 0 !== options.onRecoverableError && (onRecoverableError =
options.onRecoverableError), void 0 !== options.unstable_transitionCallbacks && (transitionCallbacks
= options.unstable_transitionCallbacks));
    options = createFiberRoot(container, 1, !1, null, null, isStrictMode, identifierPrefix,
onUncaughtError, onCaughtError, onRecoverableError, transitionCallbacks, null);
    container[internalContainerInstanceKey] = options.current;
    listenToAllSupportedEvents(8 === container.nodeType ? container.parentNode : container);
    return new ReactDOMRoot(options);
  };
  exports.hydrateRoot = function (container, initialChildren, options) {
    if (!isValidContainer(container)) throw Error("Target container is not a DOM element.");
    warnIfReactDOMContainerInDEV(container);
    void 0 === initialChildren && console.error("Must provide initial children as second argument to
hydrateRoot. Example usage: hydrateRoot(domContainer, <App />)");
    var isStrictMode = !1,
      identifierPrefix = "",
      onUncaughtError = defaultOnUncaughtError,
      onCaughtError = defaultOnCaughtError,
      onRecoverableError = defaultOnRecoverableError,
      transitionCallbacks = null,
```

```
      formState = null;
    null !== options && void 0 !== options && (!0 === options.unstable_strictMode && (isStrictMode
= !0), void 0 !== options.identifierPrefix && (identifierPrefix = options.identifierPrefix), void 0 !==
options.onUncaughtError && (onUncaughtError = options.onUncaughtError), void 0 !==
options.onCaughtError && (onCaughtError = options.onCaughtError), void 0 !==
options.onRecoverableError && (onRecoverableError = options.onRecoverableError), void 0 !==
options.unstable_transitionCallbacks && (transitionCallbacks = options.unstable_transitionCallbacks),
void 0 !== options.formState && (formState = options.formState));
    initialChildren = createFiberRoot(container, 1, !0, initialChildren, null != options ? options : null,
isStrictMode, identifierPrefix, onUncaughtError,
 onCaughtError, onRecoverableError, transitionCallbacks, formState);
    initialChildren.context = getContextForSubtree(null);
    options = initialChildren.current;
    isStrictMode = requestUpdateLane(options);
    identifierPrefix = createUpdate(isStrictMode);
    identifierPrefix.callback = null;
    enqueueUpdate(options, identifierPrefix, isStrictMode);
    initialChildren.current.lanes = isStrictMode;
    markRootUpdated$1(initialChildren, isStrictMode);
    ensureRootIsScheduled(initialChildren);
    container[internalContainerInstanceKey] = initialChildren.current;
    listenToAllSupportedEvents(container);
    return new ReactDOMHydrationRoot(initialChildren);
  };
  exports.version = "19.0.0";
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop(Error());
}();

/***/ },

/***/ "./node_modules/react-dom/cjs/react-dom.development.js"
/*!*************************************************************!*\
  !*** ./node_modules/react-dom/cjs/react-dom.development.js ***!
  \*************************************************************/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";
/**
 * @license React
 * react-dom.development.js
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
 */
```

```
 true && function () {
  function noop() {}
  function testStringCoercion(value) {
    return "" + value;
  }
  function createPortal$1(children, containerInfo, implementation) {
    var key = 3 < arguments.length && void 0 !== arguments[3] ? arguments[3] : null;
    try {
      testStringCoercion(key);
      var JSCompiler_inline_result = !1;
    } catch (e) {
      JSCompiler_inline_result = !0;
    }
    JSCompiler_inline_result && (console.error("The provided key is an unsupported type %s. This
value must be coerced to a string before using it here.", "function" === typeof Symbol &&
Symbol.toStringTag && key[Symbol.toStringTag] || key.constructor.name || "Object"),
testStringCoercion(key));
    return {
      $$typeof: REACT_PORTAL_TYPE,
      key: null == key ? null : "" + key,
      children: children,
      containerInfo: containerInfo,
      implementation: implementation
    };
  }
  function getCrossOriginStringAs(as, input) {
    if ("font" === as) return "";
    if ("string" === typeof input) return "use-credentials" === input ? input : "";
  }
  function getValueDescriptorExpectingObjectForWarning(thing) {
    return null === thing ? "`null`" : void 0 === thing ? "`undefined`" : "" === thing ? "an empty
string" : 'something with type "' + typeof thing + '"';
  }
  function getValueDescriptorExpectingEnumForWarning(thing) {
    return null === thing ? "`null`" : void 0 === thing ? "`undefined`" : "" === thing ? "an empty
string" : "string" === typeof thing ? JSON.stringify(thing) : "number" === typeof thing ? "`" + thing +
"`" : 'something with type "' + typeof thing + '"';
  }
  function resolveDispatcher() {
    var dispatcher = ReactSharedInternals.H;
    null === dispatcher && console.error("Invalid hook call. Hooks can only be called inside of the
body of a function component. This could happen for one of the following reasons:\n1. You might have
mismatching versions of React and the renderer (such as React DOM)\n2. You might be breaking the
Rules of Hooks\n3. You might have more than one copy of React in the same app\nSee
https://react.dev/link/invalid-hook-call for tips about how to debug and fix this problem.");
    return dispatcher;
  }
```

```
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart(Error());
  var React = __webpack_require__(/*! react */ "./node_modules/react/index.js"),
    Internals = {
      d: {
        f: noop,
        r: function () {
          throw Error("Invalid form element. requestFormReset must be passed a form that was rendered
by React.");
        },
        D: noop,
        C: noop,
        L: noop,
        m: noop,
        X: noop,
        S: noop,
        M: noop
      },
      p: 0,
      findDOMNode: null
    },
    REACT_PORTAL_TYPE = Symbol.for("react.portal"),
    ReactSharedInternals =
React.__CLIENT_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRAD
E;
  "function" === typeof Map && null != Map.prototype && "function" === typeof
Map.prototype.forEach && "function" === typeof Set && null != Set.prototype && "function" ===
typeof Set.prototype.clear && "function" === typeof Set.prototype.forEach || console.error("React
depends on Map and Set built-in types. Make sure that you load a polyfill in older browsers.
https://reactjs.org/link/react-polyfills");

exports.__DOM_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRADE
= Internals;
  exports.createPortal = function (children, container) {
    var key = 2 < arguments.length && void 0 !== arguments[2] ? arguments[2] : null;
    if (!container || 1 !== container.nodeType && 9 !== container.nodeType && 11 !==
container.nodeType) throw Error("Target container is not a DOM element.");
    return createPortal$1(children, container, null, key);
  };
  exports.flushSync = function (fn) {
    var previousTransition = ReactSharedInternals.T,
      previousUpdatePriority = Internals.p;
    try {
      if (ReactSharedInternals.T = null, Internals.p = 2, fn) return fn();
    } finally {
      ReactSharedInternals.T = previousTransition, Internals.p = previousUpdatePriority, Internals.d.f()
&& console.error("flushSync was called from inside a lifecycle method. React cannot flush when
React is already rendering. Consider moving this call to a scheduler task or micro task.");
```

```
    }
  };
  exports.preconnect = function (href, options) {
    "string" === typeof href && href ? null != options && "object" !== typeof options ?
console.error("ReactDOM.preconnect(): Expected the `options` argument (second) to be an object but encountered %s instead. The only supported option at this time is `crossOrigin` which accepts a string.", getValueDescriptorExpectingEnumForWarning(options)) : null != options && "string" !==
typeof options.crossOrigin && console.error("ReactDOM.preconnect(): Expected the `crossOrigin`
option (second argument) to be a string but encountered %s instead. Try removing this option or passing a string value instead.", getValueDescriptorExpectingObjectForWarning(options.crossOrigin)) :
console.error("ReactDOM.preconnect(): Expected the `href` argument (first) to be a non-empty string but encountered %s instead.", getValueDescriptorExpectingObjectForWarning(href));
    "string" === typeof href && (options ? (options = options.crossOrigin, options = "string" === typeof
options ? "use-credentials" === options ? options : "" : void 0) : options = null, Internals.d.C(href,
options));
  };
  exports.prefetchDNS = function (href) {
    if ("string" !== typeof href || !href) console.error("ReactDOM.prefetchDNS(): Expected the `href`
argument (first) to be a non-empty string but encountered %s instead.",
getValueDescriptorExpectingObjectForWarning(href));else if (1 < arguments.length) {
      var options = arguments[1];
      "object" === typeof options && options.hasOwnProperty("crossOrigin") ?
console.error("ReactDOM.prefetchDNS(): Expected only one argument, `href`, but encountered %s as a second argument instead. This argument is reserved for future options and is currently disallowed. It looks like the you are attempting to set a crossOrigin property for this DNS lookup hint. Browsers do not perform DNS queries using CORS and setting this attribute on the resource hint has no effect. Try calling ReactDOM.prefetchDNS() with just a single string argument, `href`.",
getValueDescriptorExpectingEnumForWarning(options)) : console.error("ReactDOM.prefetchDNS():
Expected only one argument, `href`, but encountered %s as a second argument instead. This argument is reserved for future options and is currently disallowed. Try calling ReactDOM.prefetchDNS() with just a single string argument, `href`.", getValueDescriptorExpectingEnumForWarning(options));
    }
    "string" === typeof href && Internals.d.D(href);
  };
  exports.preinit = function (href, options) {
    "string" === typeof href && href ? null == options || "object" !== typeof options ?
console.error("ReactDOM.preinit(): Expected the `options` argument (second) to be an object with an `as` property describing the type of resource to be preinitialized but encountered %s instead.",
getValueDescriptorExpectingEnumForWarning(options)) : "style" !== options.as && "script" !==
options.as && console.error('ReactDOM.preinit(): Expected the `as` property in the `options` argument (second) to contain a valid value describing the type of resource to be preinitialized but encountered %s instead. Valid values for `as` are "style" and "script".',
getValueDescriptorExpectingEnumForWarning(options.as)) : console.error("ReactDOM.preinit():
Expected the `href` argument (first) to be a non-empty string but encountered %s instead.",
getValueDescriptorExpectingObjectForWarning(href));
    if ("string" === typeof href && options && "string" === typeof options.as) {
      var as = options.as,
        crossOrigin = getCrossOriginStringAs(as, options.crossOrigin),
        integrity = "string" === typeof options.integrity ? options.integrity : void 0,
```

```
      fetchPriority = "string" === typeof options.fetchPriority ? options.fetchPriority : void 0;
    "style" === as ? Internals.d.S(href, "string" === typeof options.precedence ? options.precedence :
void 0, {
      crossOrigin: crossOrigin,
      integrity: integrity,
      fetchPriority: fetchPriority

    }) : "script" === as && Internals.d.X(href, {
      crossOrigin: crossOrigin,
      integrity: integrity,
      fetchPriority: fetchPriority,
      nonce: "string" === typeof options.nonce ? options.nonce : void 0
    });
  }
};
exports.preinitModule = function (href, options) {
  var encountered = "";
  "string" === typeof href && href || (encountered += " The `href` argument encountered was " +
getValueDescriptorExpectingObjectForWarning(href) + ".");
  void 0 !== options && "object" !== typeof options ? encountered += " The `options` argument
encountered was " + getValueDescriptorExpectingObjectForWarning(options) + "." : options && "as"
in options && "script" !== options.as && (encountered += " The `as` option encountered was " +
getValueDescriptorExpectingEnumForWarning(options.as) + ".");
  if (encountered) console.error("ReactDOM.preinitModule(): Expected up to two arguments, a non-
empty `href` string and, optionally, an `options` object with a valid `as` property.%s", encountered);else
switch (encountered = options && "string" === typeof options.as ? options.as : "script", encountered) {
    case "script":
      break;
    default:
      encountered = getValueDescriptorExpectingEnumForWarning(encountered),
console.error('ReactDOM.preinitModule(): Currently the only supported "as" type for this function is
"script" but received "%s" instead. This warning was generated for `href` "%s". In the future other
module types will be supported, aligning with the import-attributes proposal. Learn more here:
(https://github.com/tc39/proposal-import-attributes)', encountered, href);
  }
  if ("string" === typeof href) if ("object" === typeof options && null !== options) {
    if (null == options.as || "script" === options.as) encountered = getCrossOriginStringAs(options.as,
options.crossOrigin), Internals.d.M(href, {
      crossOrigin: encountered,
      integrity: "string" === typeof options.integrity ? options.integrity : void 0,
      nonce: "string" === typeof options.nonce ? options.nonce : void 0
    });
  } else null == options && Internals.d.M(href);
};
exports.preload = function (href, options) {
  var encountered = "";
  "string" === typeof href && href || (encountered += " The `href` argument encountered was " +
getValueDescriptorExpectingObjectForWarning(href) + ".");
  null == options || "object" !== typeof options ? encountered += " The `options` argument
```

```
encountered was " + getValueDescriptorExpectingObjectForWarning(options) + "." : "string" ===
typeof options.as && options.as || (encountered += " The `as` option encountered was " +
getValueDescriptorExpectingObjectForWarning(options.as) + ".");
    encountered && console.error('ReactDOM.preload(): Expected two arguments, a non-empty `href`
string and an `options` object with an `as` property valid for a `<link rel="preload" as="..." />` tag.%s',
encountered);
    if ("string" === typeof href && "object" === typeof options && null !== options && "string" ===
typeof options.as) {
      encountered = options.as;
      var crossOrigin = getCrossOriginStringAs(encountered, options.crossOrigin);
      Internals.d.L(href, encountered, {
        crossOrigin: crossOrigin,
        integrity: "string" === typeof options.integrity ? options.integrity : void 0,
        nonce: "string" === typeof options.nonce ? options.nonce : void 0,
        type: "string" === typeof options.type ? options.type : void 0,
        fetchPriority: "string" === typeof options.fetchPriority ? options.fetchPriority : void 0,
        referrerPolicy: "string" === typeof options.referrerPolicy ? options.referrerPolicy : void 0,
        imageSrcSet: "string" === typeof options.imageSrcSet ? options.imageSrcSet : void 0,
        imageSizes: "string" === typeof options.imageSizes ? options.imageSizes : void 0,
        media: "string" === typeof options.media ? options.media : void 0
      });
    }
  };
  exports.preloadModule = function (href, options) {
    var encountered = "";
    "string" === typeof href && href || (encountered += " The `href` argument encountered was " +
getValueDescriptorExpectingObjectForWarning(href) + ".");
    void 0 !== options && "object" !== typeof options ? encountered += " The `options` argument
encountered was " + getValueDescriptorExpectingObjectForWarning(options) + "." : options && "as"
in options && "string" !== typeof options.as && (encountered += " The `as` option encountered was "
+ getValueDescriptorExpectingObjectForWarning(options.as) + ".");
    encountered && console.error('ReactDOM.preloadModule(): Expected two arguments, a non-empty
`href` string and, optionally, an `options` object with an `as` property valid for a `<link
rel="modulepreload" as="..." />` tag.%s', encountered);
    "string" === typeof href && (options ? (encountered = getCrossOriginStringAs(options.as,
options.crossOrigin), Internals.d.m(href, {
      as: "string" === typeof options.as && "script" !== options.as ? options.as : void 0,
      crossOrigin: encountered,
      integrity: "string" === typeof options.integrity ? options.integrity : void 0
    })) : Internals.d.m(href));
  };
  exports.requestFormReset = function (form) {
    Internals.d.r(form);
  };
  exports.unstable_batchedUpdates = function (fn, a) {
    return fn(a);
  };
  exports.useFormState = function (action, initialState, permalink) {
    return resolveDispatcher().useFormState(action, initialState, permalink);
```

```
  };
  exports.useFormStatus = function () {
    return resolveDispatcher().useHostTransitionStatus();
  };
  exports.version = "19.0.0";
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop(Error());
}();

/***/ },

/***/ "./node_modules/react-dom/client.js"
/*!*****************************************!*\
  !*** ./node_modules/react-dom/client.js ***!
  \*****************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


function checkDCE() {
  /* global __REACT_DEVTOOLS_GLOBAL_HOOK__ */
  if (typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ === 'undefined' || typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.checkDCE !== 'function') {
    return;
  }
  if (true) {
    // This branch is unreachable because this function is only called
    // in production, but the condition is true only in development.
    // Therefore if the branch is still here, dead code elimination wasn't
    // properly applied.
    // Don't change the message. React DevTools relies on it. Also make sure
    // this message doesn't occur elsewhere in this function, or it will cause
    // a false positive.
    throw new Error('^_^');
  }
  // removed by dead control flow

}
if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/react-dom-client.development.js */
"./node_modules/react-dom/cjs/react-dom-client.development.js");
}

/***/ },

/***/ "./node_modules/react-dom/index.js"
```

```
/*!*****************************************!*\
  !*** ./node_modules/react-dom/index.js ***!
  \*****************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


function checkDCE() {
  /* global __REACT_DEVTOOLS_GLOBAL_HOOK__ */
  if (typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ === 'undefined' || typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.checkDCE !== 'function') {
    return;
  }
  if (true) {
    // This branch is unreachable because this function is only called
    // in production, but the condition is true only in development.
    // Therefore if the branch is still here, dead code elimination wasn't
    // properly applied.
    // Don't change the message. React DevTools relies on it. Also make sure
    // this message doesn't occur elsewhere in this function, or it will cause
    // a false positive.
    throw new Error('^_^');
  }
  // removed by dead control flow

}
if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/react-dom.development.js */ "./node_modules/react-
dom/cjs/react-dom.development.js");
}

/***/ },

/***/ "./node_modules/react-refresh/cjs/react-refresh-runtime.development.js"
/*!*************************************************************************!*\
  !*** ./node_modules/react-refresh/cjs/react-refresh-runtime.development.js ***!
  \*************************************************************************/
(__unused_webpack_module, exports) {

"use strict";
/** @license React vundefined
 * react-refresh-runtime.development.js
 *
 * Copyright (c) Facebook, Inc. and its affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
```

```
 */



if (true) {
  (function () {
    'use strict';

    // ATTENTION
    // When adding new symbols to this file,
    // Please consider also adding to 'react-devtools-shared/src/backend/ReactSymbols'
    // The Symbol used to tag the ReactElement-like types. If there is no native Symbol
    // nor polyfill, then a plain number is used for performance.
    var REACT_ELEMENT_TYPE = 0xeac7;
    var REACT_PORTAL_TYPE = 0xeaca;
    var REACT_FRAGMENT_TYPE = 0xeacb;
    var REACT_STRICT_MODE_TYPE = 0xeacc;
    var REACT_PROFILER_TYPE = 0xead2;
    var REACT_PROVIDER_TYPE = 0xeacd;
    var REACT_CONTEXT_TYPE = 0xeace;
    var REACT_FORWARD_REF_TYPE = 0xead0;
    var REACT_SUSPENSE_TYPE = 0xead1;
    var REACT_SUSPENSE_LIST_TYPE = 0xead8;
    var REACT_MEMO_TYPE = 0xead3;
    var REACT_LAZY_TYPE = 0xead4;
    var REACT_SCOPE_TYPE = 0xead7;
    var REACT_DEBUG_TRACING_MODE_TYPE = 0xeae1;
    var REACT_OFFSCREEN_TYPE = 0xeae2;
    var REACT_LEGACY_HIDDEN_TYPE = 0xeae3;
    var REACT_CACHE_TYPE = 0xeae4;
    if (typeof Symbol === 'function' && Symbol.for)
  {
      var symbolFor = Symbol.for;
      REACT_ELEMENT_TYPE = symbolFor('react.element');
      REACT_PORTAL_TYPE = symbolFor('react.portal');
      REACT_FRAGMENT_TYPE = symbolFor('react.fragment');
      REACT_STRICT_MODE_TYPE = symbolFor('react.strict_mode');
      REACT_PROFILER_TYPE = symbolFor('react.profiler');
      REACT_PROVIDER_TYPE = symbolFor('react.provider');
      REACT_CONTEXT_TYPE = symbolFor('react.context');
      REACT_FORWARD_REF_TYPE = symbolFor('react.forward_ref');
      REACT_SUSPENSE_TYPE = symbolFor('react.suspense');
      REACT_SUSPENSE_LIST_TYPE = symbolFor('react.suspense_list');
      REACT_MEMO_TYPE = symbolFor('react.memo');
      REACT_LAZY_TYPE = symbolFor('react.lazy');
      REACT_SCOPE_TYPE = symbolFor('react.scope');
      REACT_DEBUG_TRACING_MODE_TYPE = symbolFor('react.debug_trace_mode');
      REACT_OFFSCREEN_TYPE = symbolFor('react.offscreen');
      REACT_LEGACY_HIDDEN_TYPE = symbolFor('react.legacy_hidden');
```

```
    REACT_CACHE_TYPE = symbolFor('react.cache');
  }
  var PossiblyWeakMap = typeof WeakMap === 'function' ? WeakMap : Map; // We never remove these associations.
  // It's OK to reference families, but use WeakMap/Set for types.

  var allFamiliesByID = new Map();
  var allFamiliesByType = new PossiblyWeakMap();
  var allSignaturesByType = new PossiblyWeakMap(); // This WeakMap is read by React, so we only put families
  // that have actually been edited here. This keeps checks fast.
  // $FlowIssue

  var updatedFamiliesByType = new PossiblyWeakMap(); // This is cleared on every performReactRefresh() call.
  // It is an array of [Family, NextType] tuples.

  var pendingUpdates = []; // This is injected by the renderer via DevTools global hook.

  var helpersByRendererID = new Map();
  var helpersByRoot = new Map(); // We keep track of mounted roots so we can schedule updates.

  var mountedRoots = new Set(); // If a root captures an error, we remember it so we can retry on edit.

  var failedRoots = new Set(); // In environments that support WeakMap, we also remember the last element for every root.
  // It needs to be weak because we do this even for roots that failed to mount.
  // If there is no WeakMap, we won't attempt to do retrying.
  // $FlowIssue

  var rootElements =
  // $FlowIssue
  typeof WeakMap === 'function' ? new WeakMap() : null;
  var isPerformingRefresh = false;
  function computeFullKey(signature) {
    if (signature.fullKey !== null) {
      return signature.fullKey;
    }
    var fullKey = signature.ownKey;
    var hooks;
    try {
      hooks = signature.getCustomHooks();
    } catch (err) {
      // This can happen in an edge case, e.g. if expression like Foo.useSomething
      // depends on Foo which is lazily initialized during rendering.
      // In that case just assume we'll have to remount.
      signature.forceReset = true;
      signature.fullKey = fullKey;
      return fullKey;
```

```
  }
  for (var i = 0; i < hooks.length; i++) {
    var hook = hooks[i];
    if (typeof hook !== 'function') {
      // Something's wrong. Assume we need to remount.
      signature.forceReset = true;
      signature.fullKey = fullKey;
      return fullKey;
    }
    var nestedHookSignature = allSignaturesByType.get(hook);
    if (nestedHookSignature === undefined) {
      // No signature means Hook wasn't in the source code, e.g. in a library.
      // We'll skip it because we can assume it won't change during this session.
      continue;
    }
    var nestedHookKey = computeFullKey(nestedHookSignature);
    if (nestedHookSignature.forceReset) {
      signature.forceReset = true;
    }
    fullKey += '\n---\n' + nestedHookKey;
  }
  signature.fullKey = fullKey;
  return fullKey;
}
function haveEqualSignatures(prevType, nextType) {
  var prevSignature = allSignaturesByType.get(prevType);
  var nextSignature = allSignaturesByType.get(nextType);
  if (prevSignature === undefined && nextSignature === undefined) {
    return true;
  }
  if (prevSignature === undefined || nextSignature === undefined) {
    return false;
  }
  if (computeFullKey(prevSignature) !== computeFullKey(nextSignature)) {
    return false;
  }
  if (nextSignature.forceReset) {
    return false;
  }
  return true;
}
function isReactClass(type) {
  return type.prototype && type.prototype.isReactComponent;
}
function canPreserveStateBetween(prevType, nextType) {
  if (isReactClass(prevType) || isReactClass(nextType)) {
    return false;
  }
  if (haveEqualSignatures(prevType, nextType)) {
```

```
    return true;
  }
  return false;
}
function resolveFamily(type) {
  // Only check updated types to keep lookups fast.
  return updatedFamiliesByType.get(type);
} // If we didn't care about IE11, we could use new Map/Set(iterable).

function cloneMap(map) {
  var clone = new Map();
  map.forEach(function (value, key) {
    clone.set(key, value);
  });
  return clone;
}
function cloneSet(set) {
  var clone = new Set();
  set.forEach(function (value) {
    clone.add(value);
  });
  return clone;
} // This is a safety mechanism to protect against rogue getters and Proxies.

function getProperty(object, property) {
  try {
    return object[property];
  } catch (err) {
    // Intentionally ignore.
    return undefined;
  }
}
function performReactRefresh() {
  if (pendingUpdates.length === 0) {
    return null;
  }
  if (isPerformingRefresh) {
    return null;
  }
  isPerformingRefresh = true;
  try {
    var staleFamilies = new Set();
    var updatedFamilies = new Set();
    var updates = pendingUpdates;
    pendingUpdates = [];
    updates.forEach(function (_ref) {
      var family = _ref[0],
        nextType = _ref[1];
      // Now that we got a real edit, we can create associations
```

```
  // that will be read by the React reconciler.
  var prevType = family.current;
  updatedFamiliesByType.set(prevType, family);
  updatedFamiliesByType.set(nextType, family);
  family.current = nextType; // Determine whether this should be a re-render or a re-mount.

  if (canPreserveStateBetween(prevType, nextType)) {
    updatedFamilies.add(family);
  } else {
    staleFamilies.add(family);
  }
}); // TODO: rename these fields to something more meaningful.

var update = {
  updatedFamilies: updatedFamilies,
  // Families that will re-render preserving state
  staleFamilies: staleFamilies // Families that will be remounted
};
helpersByRendererID.forEach(function (helpers) {
  // Even if there are no roots, set the handler on first update.
  // This ensures that if *new* roots are mounted, they'll use the resolve handler.
  helpers.setRefreshHandler(resolveFamily);
});
var didError = false;
var firstError = null; // We snapshot maps and sets that are mutated during commits.
// If we don't do this, there is a risk they will be mutated while
// we iterate over them. For example, trying to recover a failed root
// may cause another root to be added to the failed list -- an infinite loop.

var failedRootsSnapshot = cloneSet(failedRoots);
var mountedRootsSnapshot = cloneSet(mountedRoots);
var helpersByRootSnapshot = cloneMap(helpersByRoot);
failedRootsSnapshot.forEach(function (root) {
  var helpers = helpersByRootSnapshot.get(root);
  if (helpers === undefined) {
    throw new Error('Could not find helpers for a root. This is a bug in React Refresh.');
  }
  if (!failedRoots.has(root)) {// No longer failed.
  }
  if (rootElements === null) {
    return;
  }
  if (!rootElements.has(root)) {
    return;
  }
  var element = rootElements.get(root);
  try {
    helpers.scheduleRoot(root, element);
  } catch (err) {
```

```
          if (!didError) {
            didError = true;
            firstError = err;
          } // Keep trying other roots.
        }
      });
      mountedRootsSnapshot.forEach(function (root) {
        var helpers = helpersByRootSnapshot.get(root);
        if (helpers === undefined) {
          throw new Error('Could not find helpers for a root. This is a bug in React Refresh.');
        }
        if (!mountedRoots.has(root)) {// No longer mounted.
        }
        try {
          helpers.scheduleRefresh(root, update);
        } catch (err) {
          if (!didError) {
            didError = true;
            firstError = err;
          } // Keep trying other roots.
        }
      });
      if (didError) {
        throw firstError;
      }
      return update;
    } finally {
      isPerformingRefresh = false;
    }
  }
  function register(type, id) {
    {
      if (type === null) {
        return;
      }
      if (typeof type !== 'function' && typeof type !== 'object') {
        return;
      } // This can happen in an edge case, e.g. if we register
      // return value of a HOC but it returns a cached component.
      // Ignore anything but the first registration for each type.

      if (allFamiliesByType.has(type)) {
        return;
      } // Create family or remember to update it.
      // None of this bookkeeping affects reconciliation
      // until the first performReactRefresh() call above.


var family = allFamiliesByID.get(id);
```

```
      if (family === undefined) {
        family = {
          current: type
        };
        allFamiliesByID.set(id, family);
      } else {
        pendingUpdates.push([family, type]);
      }
      allFamiliesByType.set(type, family); // Visit inner types because we might not have registered
them.

      if (typeof type === 'object' && type !== null) {
        switch (getProperty(type, '$$typeof')) {
          case REACT_FORWARD_REF_TYPE:
            register(type.render, id + '$render');
            break;
          case REACT_MEMO_TYPE:
            register(type.type, id + '$type');
            break;
        }
      }
    }
  }
  function setSignature(type, key) {
    var forceReset = arguments.length > 2 && arguments[2] !== undefined ? arguments[2] : false;
    var getCustomHooks = arguments.length > 3 ? arguments[3] : undefined;
    {
      if (!allSignaturesByType.has(type)) {
        allSignaturesByType.set(type, {
          forceReset: forceReset,
          ownKey: key,
          fullKey: null,
          getCustomHooks: getCustomHooks || function () {
            return [];
          }
        });
      } // Visit inner types because we might not have signed them.

      if (typeof type === 'object' && type !== null) {
        switch (getProperty(type, '$$typeof')) {
          case REACT_FORWARD_REF_TYPE:
            setSignature(type.render, key, forceReset, getCustomHooks);
            break;
          case REACT_MEMO_TYPE:
            setSignature(type.type, key, forceReset, getCustomHooks);
            break;
        }
      }
    }
```

```
} // This is lazily called during first render for a type.
// It captures Hook list at that time so inline requires don't break comparisons.

function collectCustomHooksForSignature(type) {
  {
    var signature = allSignaturesByType.get(type);
    if (signature !== undefined) {
      computeFullKey(signature);
    }
  }
}
function getFamilyByID(id) {
  {
    return allFamiliesByID.get(id);
  }
}
function getFamilyByType(type) {
  {
    return allFamiliesByType.get(type);
  }
}
function findAffectedHostInstances(families) {
  {
    var affectedInstances = new Set();
    mountedRoots.forEach(function (root) {
      var helpers = helpersByRoot.get(root);
      if (helpers === undefined) {
        throw new Error('Could not find helpers for a root. This is a bug in React Refresh.');
      }
      var instancesForRoot = helpers.findHostInstancesForRefresh(root, families);
      instancesForRoot.forEach(function (inst) {
        affectedInstances.add(inst);
      });
    });
    return affectedInstances;
  }
}
function injectIntoGlobalHook(globalObject) {
  {
    // For React Native, the global hook will be set up by require('react-devtools-core').
    // That code will run before us. So we need to monkeypatch functions on existing hook.
    // For React Web, the global hook will be set up by the extension.
    // This will also run before us.
    var hook = globalObject.__REACT_DEVTOOLS_GLOBAL_HOOK__;
    if (hook === undefined) {
      // However, if there is no DevTools extension, we'll need to set up the global hook ourselves.
      // Note that in this case it's important that renderer code runs *after* this method call.
      // Otherwise, the renderer will think that there is no global hook, and won't do the injection.
      var nextID = 0;
```

```
        globalObject.__REACT_DEVTOOLS_GLOBAL_HOOK__ = hook = {
          renderers: new Map(),
          supportsFiber: true,
          inject: function (injected) {
            return nextID++;
          },
          onScheduleFiberRoot: function (id, root, children) {},
          onCommitFiberRoot: function (id, root, maybePriorityLevel, didError) {},
          onCommitFiberUnmount: function () {}
        };
      }
      if (hook.isDisabled) {
        // This isn't a real property on the hook, but it can be set to opt out
        // of DevTools integration and associated warnings and logs.
        // Using console['warn'] to evade Babel and ESLint
        console['warn']('Something has shimmed the React DevTools global hook
(__REACT_DEVTOOLS_GLOBAL_HOOK__). ' + 'Fast Refresh is not compatible with this shim and
will be disabled.');
        return;
      } // Here, we just want to get a reference to scheduleRefresh.

      var oldInject = hook.inject;
      hook.inject = function (injected) {
        var id = oldInject.apply(this, arguments);
        if (typeof injected.scheduleRefresh === 'function' && typeof injected.setRefreshHandler ===
'function') {
          // This version supports React Refresh.
          helpersByRendererID.set(id, injected);
        }
        return id;
      }; // Do the same for any already injected roots.
      // This is useful if ReactDOM has already been initialized.
      // https://github.com/facebook/react/issues/17626

      hook.renderers.forEach(function (injected, id) {
        if (typeof injected.scheduleRefresh === 'function' && typeof injected.setRefreshHandler ===
'function') {
          // This version supports React Refresh.
          helpersByRendererID.set(id, injected);
        }
      }); // We also want to track currently mounted roots.

      var oldOnCommitFiberRoot = hook.onCommitFiberRoot;
      var oldOnScheduleFiberRoot = hook.onScheduleFiberRoot || function () {};
      hook.onScheduleFiberRoot = function (id, root, children) {
        if (!isPerformingRefresh) {
          // If it was intentionally scheduled, don't attempt to restore.
          // This includes intentionally scheduled unmounts.
          failedRoots.delete(root);
```

```
          if (rootElements !== null) {
            rootElements.set(root, children);
          }
        }
        return oldOnScheduleFiberRoot.apply(this, arguments);
      };
      hook.onCommitFiberRoot = function (id, root, maybePriorityLevel, didError) {
        var helpers = helpersByRendererID.get(id);
        if (helpers !== undefined) {
          helpersByRoot.set(root, helpers);
          var current = root.current;
          var alternate = current.alternate; // We need to determine whether this root has just
(un)mounted.
          // This logic is copy-pasted from similar logic in the DevTools backend.
          // If this breaks with some refactoring, you'll want to update DevTools too.

          if (alternate !== null) {
            var wasMounted = alternate.memoizedState != null && alternate.memoizedState.element !=
null;
            var isMounted = current.memoizedState != null && current.memoizedState.element != null;
            if (!wasMounted && isMounted) {
              // Mount a new root.
              mountedRoots.add(root);
              failedRoots.delete(root);
            } else if (wasMounted && isMounted) ;else if (wasMounted && !isMounted) {
              // Unmount an existing root.
              mountedRoots.delete(root);
              if (didError) {
                // We'll remount it on future edits.
                failedRoots.add(root);
              } else {
                helpersByRoot.delete(root);
              }
            } else if (!wasMounted && !isMounted) {
              if (didError) {
                // We'll remount it on future edits.
                failedRoots.add(root);
              }
            }
          } else {
            // Mount a new root.
            mountedRoots.add(root);
          }
        } // Always call the decorated DevTools hook.

        return oldOnCommitFiberRoot.apply(this, arguments);
      };
    }
  }
```

```
  function hasUnrecoverableErrors() {
    // TODO: delete this after removing dependency in RN.
    return false;
  } // Exposed for testing.

  function _getMountedRootCount() {
    {
      return mountedRoots.size;
    }
  } // This is a wrapper over more primitive functions for setting signature.
  // Signatures let us decide whether the Hook order has changed on refresh.
  //
  // This function is intended to be used as a transform target, e.g.:
  // var _s = createSignatureFunctionForTransform()
  //
  // function Hello() {
  //   const [foo, setFoo] = useState(0);
  //   const value = useCustomHook();
  //   _s(); /* Call without arguments triggers collecting the custom Hook list.
  //          * This doesn't happen during the module evaluation because we
  //          * don't want to change the module order with inline requires.
  //          * Next calls are noops. */
  //   return <h1>Hi</h1>;
  // }
  //
  // /* Call with arguments attaches the signature to the type: */
  // _s(
  //   Hello,
  //   'useState{[foo, setFoo]}(0)',
  //   () => [useCustomHook], /* Lazy to avoid triggering inline requires */
  // );

  function createSignatureFunctionForTransform() {
    {
      var savedType;
      var hasCustomHooks;
      var didCollectHooks = false;
      return function (type, key, forceReset, getCustomHooks) {
        if (typeof key === 'string') {
          // We're in the initial phase that associates signatures
          // with the functions. Note this may be called multiple times
          // in HOC chains like _s(hoc1(_s(hoc2(_s(actualFunction))))).
          if (!savedType) {
            // We're in the innermost call, so this is the actual type.
            savedType = type;
            hasCustomHooks = typeof getCustomHooks === 'function';
          } // Set the
signature for all types (even wrappers!) in case
          // they have no signatures of their own. This is to prevent
```

```
      // problems like https://github.com/facebook/react/issues/20417.

      if (type != null && (typeof type === 'function' || typeof type === 'object')) {
        setSignature(type, key, forceReset, getCustomHooks);
      }
      return type;
    } else {
      // We're in the _s() call without arguments, which means
      // this is the time to collect custom Hook signatures.
      // Only do this once. This path is hot and runs *inside* every render!
      if (!didCollectHooks && hasCustomHooks) {
        didCollectHooks = true;
        collectCustomHooksForSignature(savedType);
      }
    }
  };
 }
}
function isLikelyComponentType(type) {
 {
  switch (typeof type) {
   case 'function':
    {
     // First, deal with classes.
     if (type.prototype != null) {
      if (type.prototype.isReactComponent) {
       // React class.
       return true;
      }
      var ownNames = Object.getOwnPropertyNames(type.prototype);
      if (ownNames.length > 1 || ownNames[0] !== 'constructor') {
       // This looks like a class.
       return false;
      } // eslint-disable-next-line no-proto

      if (type.prototype.__proto__ !== Object.prototype) {
       // It has a superclass.
       return false;
      } // Pass through.
      // This looks like a regular function with empty prototype.
     } // For plain functions and arrows, use name as a heuristic.

     var name = type.name || type.displayName;
     return typeof name === 'string' && /^[A-Z]/.test(name);
    }
   case 'object':
    {
     if (type != null) {
      switch (getProperty(type, '$$typeof')) {
```

```
              case REACT_FORWARD_REF_TYPE:
              case REACT_MEMO_TYPE:
                // Definitely React components.
                return true;
              default:
                return false;
            }
          }
          return false;
        }
      default:
        {
          return false;
        }
    }
  }
  exports._getMountedRootCount = _getMountedRootCount;
  exports.collectCustomHooksForSignature = collectCustomHooksForSignature;
  exports.createSignatureFunctionForTransform = createSignatureFunctionForTransform;
  exports.findAffectedHostInstances = findAffectedHostInstances;
  exports.getFamilyByID = getFamilyByID;
  exports.getFamilyByType = getFamilyByType;
  exports.hasUnrecoverableErrors = hasUnrecoverableErrors;
  exports.injectIntoGlobalHook = injectIntoGlobalHook;
  exports.isLikelyComponentType = isLikelyComponentType;
  exports.performReactRefresh = performReactRefresh;
  exports.register = register;
  exports.setSignature = setSignature;
 })();
}

/***/ },

/***/ "./node_modules/react-refresh/runtime.js"
/*!**********************************************!*\
  !*** ./node_modules/react-refresh/runtime.js ***!
  \**********************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


if (false) // removed by dead control flow
{} else {
 module.exports = __webpack_require__(/*! ./cjs/react-refresh-runtime.development.js */
"./node_modules/react-refresh/cjs/react-refresh-runtime.development.js");
}
```

```
/***/ },

/***/ "./node_modules/react/cjs/react-jsx-dev-runtime.development.js"
/*!*****************************************************************!*\
  !*** ./node_modules/react/cjs/react-jsx-dev-runtime.development.js ***!
  \*****************************************************************/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";
/**
 * @license React
 * react-jsx-dev-runtime.development.js
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
 */



 true && function () {
  function getComponentNameFromType(type) {
    if (null == type) return null;
    if ("function" === typeof type) return type.$$typeof === REACT_CLIENT_REFERENCE$2 ?
null : type.displayName || type.name || null;
    if ("string" === typeof type) return type;
    switch (type) {
      case REACT_FRAGMENT_TYPE:
        return "Fragment";
      case REACT_PORTAL_TYPE:
        return "Portal";
      case REACT_PROFILER_TYPE:
        return "Profiler";
      case REACT_STRICT_MODE_TYPE:
        return "StrictMode";
      case REACT_SUSPENSE_TYPE:
        return "Suspense";
      case REACT_SUSPENSE_LIST_TYPE:
        return "SuspenseList";
    }
    if ("object" === typeof type) switch ("number" === typeof type.tag && console.error("Received an
unexpected object in getComponentNameFromType(). This is likely a bug in React. Please file an
issue."), type.$$typeof) {
      case REACT_CONTEXT_TYPE:
        return (type.displayName || "Context") + ".Provider";
      case REACT_CONSUMER_TYPE:
        return (type._context.displayName || "Context") + ".Consumer";
      case REACT_FORWARD_REF_TYPE:
```

```
        var innerType = type.render;
        type = type.displayName;
        type || (type = innerType.displayName || innerType.name || "", type = "" !== type ? "ForwardRef("
+ type + ")" : "ForwardRef");
        return type;
      case REACT_MEMO_TYPE:
        return innerType = type.displayName || null, null !== innerType ? innerType :
getComponentNameFromType(type.type) || "Memo";
      case REACT_LAZY_TYPE:
        innerType = type._payload;
        type = type._init;
        try {
          return getComponentNameFromType(type(innerType));
        } catch (x) {}
    }
    return null;
  }
  function testStringCoercion(value) {
    return "" + value;
  }
  function checkKeyStringCoercion(value) {
    try {
      testStringCoercion(value);
      var JSCompiler_inline_result = !1;
    } catch (e) {
      JSCompiler_inline_result = !0;
    }
    if (JSCompiler_inline_result) {
      JSCompiler_inline_result = console;
      var JSCompiler_temp_const = JSCompiler_inline_result.error;
      var JSCompiler_inline_result$jscomp$0 = "function" === typeof Symbol && Symbol.toStringTag
&& value[Symbol.toStringTag] || value.constructor.name || "Object";
      JSCompiler_temp_const.call(JSCompiler_inline_result, "The provided key is an unsupported type
%s. This value must be coerced to a string before using it here.", JSCompiler_inline_result$jscomp$0);
      return testStringCoercion(value);
    }
  }
  function disabledLog() {}
  function disableLogs() {
    if (0 === disabledDepth) {
      prevLog = console.log;
      prevInfo = console.info;
      prevWarn = console.warn;
      prevError = console.error;
      prevGroup = console.group;
      prevGroupCollapsed = console.groupCollapsed;
      prevGroupEnd = console.groupEnd;
      var props = {
        configurable: !0,
```

```
      enumerable: !0,
      value: disabledLog,
      writable: !0
    };
    Object.defineProperties(console, {
      info: props,
      log: props,
      warn: props,
      error: props,
      group: props,
      groupCollapsed: props,
      groupEnd: props
    });
  }
  disabledDepth++;
}
function reenableLogs() {
  disabledDepth--;
  if (0 === disabledDepth) {
    var props = {
      configurable: !0,
      enumerable: !0,
      writable: !0
    };
    Object.defineProperties(console, {
      log: assign({}, props, {
        value: prevLog
      }),
      info: assign({}, props, {
        value: prevInfo
      }),
      warn: assign({}, props, {
        value: prevWarn
      }),
      error: assign({}, props, {
        value: prevError
      }),
      group: assign({}, props, {
        value: prevGroup
      }),
      groupCollapsed: assign({}, props, {
        value: prevGroupCollapsed
      }),
      groupEnd: assign({}, props, {
        value: prevGroupEnd
      })
    });
  }
  0 > disabledDepth && console.error("disabledDepth fell below zero. This is a bug in React. Please
```

```
file an issue.");
  }
  function describeBuiltInComponentFrame(name) {
    if (void 0 === prefix) try {
      throw Error();
    } catch (x) {
      var match = x.stack.trim().match(/\n( *(at )?)/);
      prefix = match && match[1] || "";
      suffix = -1 < x.stack.indexOf("\n    at") ? " (<anonymous>)" : -1 < x.stack.indexOf("@") ?
"@unknown:0:0" : "";
    }
    return "\n" + prefix + name + suffix;
  }
  function describeNativeComponentFrame(fn, construct) {
    if (!fn || reentry) return "";
    var frame = componentFrameCache.get(fn);
    if (void 0 !== frame) return frame;
    reentry = !0;
    frame = Error.prepareStackTrace;
    Error.prepareStackTrace = void 0;
    var previousDispatcher = null;
    previousDispatcher = ReactSharedInternals.H;
    ReactSharedInternals.H = null;
    disableLogs();
    try {
      var RunInRootFrame = {
        DetermineComponentFrameRoot: function () {
          try {
            if (construct) {
              var Fake = function () {
                throw Error();
              };
              Object.defineProperty(Fake.prototype, "props", {
                set: function () {
                  throw Error();
                }
              });
              if ("object" === typeof Reflect && Reflect.construct) {
                try {
                  Reflect.construct(Fake, []);
                } catch (x) {
                  var control = x;
                }
                Reflect.construct(fn,
 [], Fake);
              } else {
                try {
                  Fake.call();
                } catch (x$0) {
```

```
            control = x$0;
           }
           fn.call(Fake.prototype);
          }
         } else {
          try {
           throw Error();
          } catch (x$1) {
           control = x$1;
          }
          (Fake = fn()) && "function" === typeof Fake.catch && Fake.catch(function () {});
         }
        } catch (sample) {
         if (sample && control && "string" === typeof sample.stack) return [sample.stack,
control.stack];
        }
        return [null, null];
       }
      };
      RunInRootFrame.DetermineComponentFrameRoot.displayName =
"DetermineComponentFrameRoot";
      var namePropDescriptor =
Object.getOwnPropertyDescriptor(RunInRootFrame.DetermineComponentFrameRoot, "name");
      namePropDescriptor && namePropDescriptor.configurable &&
Object.defineProperty(RunInRootFrame.DetermineComponentFrameRoot, "name", {
       value: "DetermineComponentFrameRoot"
      });
      var _RunInRootFrame$Deter = RunInRootFrame.DetermineComponentFrameRoot(),
       sampleStack = _RunInRootFrame$Deter[0],
       controlStack = _RunInRootFrame$Deter[1];
      if (sampleStack && controlStack) {
       var sampleLines = sampleStack.split("\n"),
        controlLines = controlStack.split("\n");
       for (_RunInRootFrame$Deter = namePropDescriptor = 0; namePropDescriptor <
sampleLines.length && !
sampleLines[namePropDescriptor].includes("DetermineComponentFrameRoot");)
namePropDescriptor++;
       for (; _RunInRootFrame$Deter < controlLines.length && !
controlLines[_RunInRootFrame$Deter].includes("DetermineComponentFrameRoot");)
_RunInRootFrame$Deter++;
       if (namePropDescriptor === sampleLines.length || _RunInRootFrame$Deter ===
controlLines.length) for (namePropDescriptor = sampleLines.length - 1, _RunInRootFrame$Deter =
controlLines.length - 1; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter &&
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter];)
_RunInRootFrame$Deter--;
       for (; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter; namePropDescriptor--,
_RunInRootFrame$Deter--) if (sampleLines[namePropDescriptor] !==
controlLines[_RunInRootFrame$Deter]) {
        if (1 !== namePropDescriptor || 1 !== _RunInRootFrame$Deter) {
```

```
          do if (namePropDescriptor--, _RunInRootFrame$Deter--, 0 > _RunInRootFrame$Deter ||
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter]) {
            var _frame = "\n" + sampleLines[namePropDescriptor].replace(" at new ", " at ");
            fn.displayName && _frame.includes("<anonymous>") && (_frame =
_frame.replace("<anonymous>", fn.displayName));
            "function" === typeof fn && componentFrameCache.set(fn, _frame);
            return _frame;
          } while (1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter);
        }
        break;
      }
    }
  } finally {
    reentry = !1, ReactSharedInternals.H = previousDispatcher, reenableLogs(),
Error.prepareStackTrace = frame;
  }
  sampleLines = (sampleLines = fn ? fn.displayName || fn.name : "") ?
describeBuiltInComponentFrame(sampleLines) : "";
  "function" === typeof fn && componentFrameCache.set(fn, sampleLines);
  return sampleLines;
}
function describeUnknownElementTypeFrameInDEV(type) {
  if (null == type) return "";
  if ("function" === typeof type) {
    var prototype = type.prototype;
    return describeNativeComponentFrame(type, !(!prototype || !prototype.isReactComponent));
  }
  if ("string" === typeof type) return describeBuiltInComponentFrame(type);
  switch (type) {
    case REACT_SUSPENSE_TYPE:
      return describeBuiltInComponentFrame("Suspense");
    case REACT_SUSPENSE_LIST_TYPE:
      return describeBuiltInComponentFrame("SuspenseList");
  }
  if ("object" === typeof type) switch (type.$$typeof) {
    case REACT_FORWARD_REF_TYPE:
      return type = describeNativeComponentFrame(type.render, !1), type;
    case REACT_MEMO_TYPE:
      return describeUnknownElementTypeFrameInDEV(type.type);
    case REACT_LAZY_TYPE:
      prototype = type._payload;
      type = type._init;
      try {
        return describeUnknownElementTypeFrameInDEV(type(prototype));
      } catch (x) {}
  }
  return "";
}
function getOwner() {
```

```
    var dispatcher = ReactSharedInternals.A;
    return null === dispatcher ? null : dispatcher.getOwner();
  }
  function hasValidKey(config) {
    if (hasOwnProperty.call(config, "key")) {
      var getter = Object.getOwnPropertyDescriptor(config, "key").get;
      if (getter && getter.isReactWarning) return !1;
    }
    return void 0 !== config.key;
  }
  function defineKeyPropWarningGetter(props, displayName) {
    function warnAboutAccessingKey() {
      specialPropKeyWarningShown || (specialPropKeyWarningShown = !0, console.error("%s: `key` is not a prop. Trying to access it will result in `undefined` being returned. If you need to access the same value within the child component, you should pass it as a different prop. (https://react.dev/link/special-props)", displayName));
    }
    warnAboutAccessingKey.isReactWarning = !0;
    Object.defineProperty(props, "key", {
      get: warnAboutAccessingKey,
      configurable: !0
    });
  }
  function elementRefGetterWithDeprecationWarning() {
    var componentName = getComponentNameFromType(this.type);
    didWarnAboutElementRef[componentName] || (didWarnAboutElementRef[componentName] = !0, console.error("Accessing element.ref was removed in React 19. ref is now a regular prop. It will be removed from the JSX Element type in a future release."));
    componentName = this.props.ref;
    return void 0 !== componentName ? componentName : null;
  }
  function ReactElement(type, key, self, source, owner, props) {
    self = props.ref;
    type = {
      $$typeof: REACT_ELEMENT_TYPE,
      type: type,
      key: key,
      props: props,
      _owner: owner
    };
    null !== (void 0 !== self ? self : null) ? Object.defineProperty(type, "ref", {
      enumerable: !1,
      get: elementRefGetterWithDeprecationWarning
    }) : Object.defineProperty(type, "ref", {
      enumerable: !1,
      value: null
    });
    type._store = {};
    Object.defineProperty(type._store, "validated", {
```

```
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: 0
    });
    Object.defineProperty(type, "_debugInfo", {
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: null
    });
    Object.freeze && (Object.freeze(type.props), Object.freeze(type));
    return type;
  }
  function jsxDEVImpl(type, config, maybeKey, isStaticChildren, source, self) {
    if ("string" === typeof type || "function" === typeof type || type === REACT_FRAGMENT_TYPE ||
type === REACT_PROFILER_TYPE || type === REACT_STRICT_MODE_TYPE || type ===
REACT_SUSPENSE_TYPE || type === REACT_SUSPENSE_LIST_TYPE || type ===
REACT_OFFSCREEN_TYPE || "object" === typeof type && null !== type && (type.$$typeof ===
REACT_LAZY_TYPE || type.$$typeof === REACT_MEMO_TYPE || type.$$typeof ===
REACT_CONTEXT_TYPE || type.$$typeof === REACT_CONSUMER_TYPE || type.$$typeof ===
REACT_FORWARD_REF_TYPE || type.$$typeof === REACT_CLIENT_REFERENCE$1 || void 0 !
== type.getModuleId)) {
      var children = config.children;
      if (void 0 !== children) if (isStaticChildren) {
        if (isArrayImpl(children)) {
          for (isStaticChildren = 0; isStaticChildren < children.length; isStaticChildren++)
validateChildKeys(children[isStaticChildren], type);
          Object.freeze && Object.freeze(children);
        } else console.error("React.jsx: Static children should always be an array. You are likely explicitly
calling React.jsxs or React.jsxDEV. Use the Babel transform instead.");
      } else validateChildKeys(children, type);
    } else {
      children = "";
      if (void 0 === type || "object" === typeof type && null !== type && 0 ===
Object.keys(type).length) children += " You likely forgot to export your component from the file it's
defined in, or you might have mixed up default and named imports.";
      null === type ? isStaticChildren = "null" : isArrayImpl(type) ? isStaticChildren = "array" : void 0 !
== type && type.$$typeof === REACT_ELEMENT_TYPE ? (isStaticChildren = "<" +
(getComponentNameFromType(type.type) || "Unknown") + " />", children = " Did you accidentally
export a JSX literal instead of a component?") : isStaticChildren = typeof type;
      console.error("React.jsx: type is invalid -- expected a string (for built-in components) or a
class/function (for composite components) but got: %s.%s", isStaticChildren, children);
    }
    if (hasOwnProperty.call(config, "key")) {
      children = getComponentNameFromType(type);
      var keys = Object.keys(config).filter(function (k) {
        return "key" !== k;
      });
```

```
    isStaticChildren = 0 < keys.length ? "{key: someKey, " + keys.join(": ..., ") + ": ...}" : "{key:
someKey}";
    didWarnAboutKeySpread[children + isStaticChildren] || (keys = 0 < keys.length ? "{" + keys.join(":
..., ") + ": ...}" : "{}", console.error('A props object containing a "key" prop is being spread into JSX:\n
let props = %s;\n  <%s {...props} />\nReact keys must be passed directly to JSX without using
spread:\n  let props = %s;\n  <%s key={someKey} {...props} />', isStaticChildren, children, keys,
children), didWarnAboutKeySpread[children + isStaticChildren] = !0);
  }
  children = null;
  void 0 !== maybeKey && (checkKeyStringCoercion(maybeKey), children = "" + maybeKey);
  hasValidKey(config) && (checkKeyStringCoercion(config.key), children = "" + config.key);
  if ("key" in config) {
    maybeKey = {};
    for (var propName in config) "key" !== propName && (maybeKey[propName]
 = config[propName]);
  } else maybeKey = config;
  children && defineKeyPropWarningGetter(maybeKey, "function" === typeof type ?
type.displayName || type.name || "Unknown" : type);
  return ReactElement(type, children, self, source, getOwner(), maybeKey);
 }
 function validateChildKeys(node, parentType) {
  if ("object" === typeof node && node && node.$$typeof !== REACT_CLIENT_REFERENCE) if
(isArrayImpl(node)) for (var i = 0; i < node.length; i++) {
    var child = node[i];
    isValidElement(child) && validateExplicitKey(child, parentType);
  } else if (isValidElement(node)) node._store && (node._store.validated = 1);else if (null === node ||
"object" !== typeof node ? i = null : (i = MAYBE_ITERATOR_SYMBOL &&
node[MAYBE_ITERATOR_SYMBOL] || node["@@iterator"], i = "function" === typeof i ? i : null),
"function" === typeof i && i !== node.entries && (i = i.call(node), i !== node)) for (; !(node =
i.next()).done;) isValidElement(node.value) && validateExplicitKey(node.value, parentType);
 }
 function isValidElement(object) {
  return "object" === typeof object && null !== object && object.$$typeof ===
REACT_ELEMENT_TYPE;
 }
 function validateExplicitKey(element, parentType) {
  if (element._store && !element._store.validated && null == element.key &&
(element._store.validated = 1, parentType = getCurrentComponentErrorInfo(parentType), !
ownerHasKeyUseWarning[parentType])) {
    ownerHasKeyUseWarning[parentType] = !0;
    var childOwner = "";
    element && null != element._owner && element._owner !== getOwner() && (childOwner = null,
"number" === typeof element._owner.tag ? childOwner =
getComponentNameFromType(element._owner.type) : "string" === typeof element._owner.name &&
(childOwner = element._owner.name), childOwner = " It was passed a child from " + childOwner +
".");
    var prevGetCurrentStack = ReactSharedInternals.getCurrentStack;
    ReactSharedInternals.getCurrentStack = function () {
      var stack = describeUnknownElementTypeFrameInDEV(element.type);
```

```
        prevGetCurrentStack && (stack += prevGetCurrentStack() || "");
        return stack;
      };
      console.error('Each child in a list should have a unique "key" prop.%s%s See
https://react.dev/link/warning-keys for more information.', parentType, childOwner);
      ReactSharedInternals.getCurrentStack = prevGetCurrentStack;
    }
  }
  function getCurrentComponentErrorInfo(parentType) {
    var info = "",
      owner = getOwner();
    owner && (owner = getComponentNameFromType(owner.type)) && (info = "\n\nCheck the render
method of `" + owner + "`.");
    info || (parentType = getComponentNameFromType(parentType)) && (info = "\n\nCheck the top-
level render call using <" + parentType + ">.");
    return info;
  }
  var React = __webpack_require__(/*! react */ "./node_modules/react/index.js"),
    REACT_ELEMENT_TYPE = Symbol.for("react.transitional.element"),
    REACT_PORTAL_TYPE = Symbol.for("react.portal"),
    REACT_FRAGMENT_TYPE = Symbol.for("react.fragment"),
    REACT_STRICT_MODE_TYPE = Symbol.for("react.strict_mode"),
    REACT_PROFILER_TYPE = Symbol.for("react.profiler");
  Symbol.for("react.provider");
  var REACT_CONSUMER_TYPE = Symbol.for("react.consumer"),
    REACT_CONTEXT_TYPE = Symbol.for("react.context"),
    REACT_FORWARD_REF_TYPE = Symbol.for("react.forward_ref"),
    REACT_SUSPENSE_TYPE = Symbol.for("react.suspense"),
    REACT_SUSPENSE_LIST_TYPE = Symbol.for("react.suspense_list"),
    REACT_MEMO_TYPE = Symbol.for("react.memo"),
    REACT_LAZY_TYPE = Symbol.for("react.lazy"),
    REACT_OFFSCREEN_TYPE = Symbol.for("react.offscreen"),
    MAYBE_ITERATOR_SYMBOL = Symbol.iterator,
    REACT_CLIENT_REFERENCE$2 = Symbol.for("react.client.reference"),
    ReactSharedInternals =
React.__CLIENT_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRAD
E,
    hasOwnProperty = Object.prototype.hasOwnProperty,
    assign = Object.assign,
    REACT_CLIENT_REFERENCE$1 = Symbol.for("react.client.reference"),
    isArrayImpl = Array.isArray,
    disabledDepth = 0,
    prevLog,
    prevInfo,
    prevWarn,
    prevError,
    prevGroup,
    prevGroupCollapsed,
    prevGroupEnd;
```

```
  disabledLog.__reactDisabledLog = !0;
  var prefix,
    suffix,
    reentry = !1;
  var componentFrameCache = new ("function" === typeof WeakMap ? WeakMap : Map)();
  var REACT_CLIENT_REFERENCE = Symbol.for("react.client.reference"),
    specialPropKeyWarningShown;
  var didWarnAboutElementRef = {};
  var didWarnAboutKeySpread = {},
    ownerHasKeyUseWarning = {};
  exports.Fragment = REACT_FRAGMENT_TYPE;
  exports.jsxDEV = function (type, config, maybeKey, isStaticChildren, source, self) {
    return jsxDEVImpl(type, config, maybeKey, isStaticChildren, source, self);
  };
}();

/***/ },

/***/ "./node_modules/react/cjs/react-jsx-runtime.development.js"
/*!*****************************************************************!*\
  !*** ./node_modules/react/cjs/react-jsx-runtime.development.js ***!
  \*****************************************************************/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";
/**
 * @license React
 * react-jsx-runtime.development.js
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
 */



 true && function () {
  function getComponentNameFromType(type) {
    if (null == type) return null;
    if ("function" === typeof type) return type.$$typeof === REACT_CLIENT_REFERENCE$2 ?
null : type.displayName || type.name || null;
    if ("string" === typeof type) return type;
    switch (type) {
      case REACT_FRAGMENT_TYPE:
        return "Fragment";
      case REACT_PORTAL_TYPE:
        return "Portal";
      case REACT_PROFILER_TYPE:
```

```
        return "Profiler";
      case REACT_STRICT_MODE_TYPE:
        return "StrictMode";
      case REACT_SUSPENSE_TYPE:
        return "Suspense";
      case REACT_SUSPENSE_LIST_TYPE:
        return "SuspenseList";
    }
    if ("object" === typeof type) switch ("number" === typeof type.tag && console.error("Received an
unexpected object in getComponentNameFromType(). This is likely a bug in React. Please file an
issue."), type.$$typeof) {
      case REACT_CONTEXT_TYPE:
        return (type.displayName || "Context") + ".Provider";
      case REACT_CONSUMER_TYPE:
        return (type._context.displayName || "Context") + ".Consumer";
      case REACT_FORWARD_REF_TYPE:
        var innerType = type.render;
        type = type.displayName;
        type || (type = innerType.displayName || innerType.name || "", type = "" !== type ? "ForwardRef("
+ type + ")" : "ForwardRef");
        return type;
      case REACT_MEMO_TYPE:
        return innerType = type.displayName || null, null !== innerType ? innerType :
getComponentNameFromType(type.type) || "Memo";
      case REACT_LAZY_TYPE:
        innerType = type._payload;
        type = type._init;
        try {
          return getComponentNameFromType(type(innerType));
        } catch (x) {}
    }
    return null;
  }
  function testStringCoercion(value) {
    return "" + value;
  }
  function checkKeyStringCoercion(value) {
    try {
      testStringCoercion(value);
      var JSCompiler_inline_result = !1;
    } catch (e) {
      JSCompiler_inline_result = !0;
    }
    if (JSCompiler_inline_result) {
      JSCompiler_inline_result = console;
      var JSCompiler_temp_const = JSCompiler_inline_result.error;
      var JSCompiler_inline_result$jscomp$0 = "function" === typeof Symbol && Symbol.toStringTag
&& value[Symbol.toStringTag] || value.constructor.name || "Object";
      JSCompiler_temp_const.call(JSCompiler_inline_result, "The provided key is an unsupported type
```

```
%s. This value must be coerced to a string before using it here.", JSCompiler_inline_result$jscomp$0);
      return testStringCoercion(value);
    }
  }
  function disabledLog() {}
  function disableLogs() {
    if (0 === disabledDepth) {
      prevLog = console.log;
      prevInfo = console.info;
      prevWarn = console.warn;
      prevError = console.error;
      prevGroup = console.group;
      prevGroupCollapsed = console.groupCollapsed;
      prevGroupEnd = console.groupEnd;
      var props = {
        configurable: !0,
        enumerable: !0,
        value: disabledLog,
        writable: !0
      };
      Object.defineProperties(console, {
        info: props,
        log: props,
        warn: props,
        error: props,
        group: props,
        groupCollapsed: props,
        groupEnd: props
      });
    }
    disabledDepth++;
  }
  function reenableLogs() {
    disabledDepth--;
    if (0 === disabledDepth) {
      var props = {
        configurable: !0,
        enumerable: !0,
        writable: !0
      };
      Object.defineProperties(console, {
        log: assign({}, props, {
          value: prevLog
        }),
        info: assign({}, props, {
          value: prevInfo
        }),
        warn: assign({}, props, {
          value: prevWarn
```

```
      }),
      error: assign({}, props, {
        value: prevError
      }),
      group: assign({}, props, {
        value: prevGroup
      }),
      groupCollapsed: assign({}, props, {
        value: prevGroupCollapsed
      }),
      groupEnd: assign({}, props, {
        value: prevGroupEnd
      })
    });
  }
  0 > disabledDepth && console.error("disabledDepth fell below zero. This is a bug in React. Please file an issue.");
 }
 function describeBuiltInComponentFrame(name) {
  if (void 0 === prefix) try {
    throw Error();
  } catch (x) {
    var match = x.stack.trim().match(/\n( *(at )?)/);
    prefix = match && match[1] || "";
    suffix = -1 < x.stack.indexOf("\n    at") ? " (<anonymous>)" : -1 < x.stack.indexOf("@") ? "@unknown:0:0" : "";
  }
  return "\n" + prefix + name + suffix;
 }
 function describeNativeComponentFrame(fn, construct) {
  if (!fn || reentry) return "";
  var frame = componentFrameCache.get(fn);
  if (void 0 !== frame) return frame;
  reentry = !0;
  frame = Error.prepareStackTrace;
  Error.prepareStackTrace = void 0;
  var previousDispatcher = null;
  previousDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = null;
  disableLogs();
  try {
    var RunInRootFrame = {
      DetermineComponentFrameRoot: function () {
        try {
          if (construct) {
            var Fake = function () {
              throw Error();
            };
```

```
            Object.defineProperty(Fake.prototype, "props", {
              set: function () {
                throw Error();
              }
            });
            if ("object" === typeof Reflect && Reflect.construct) {
              try {
                Reflect.construct(Fake, []);
              } catch (x) {
                var control = x;
              }
              Reflect.construct(fn, [], Fake);
            } else {
              try {
                Fake.call();
              } catch (x$0) {
                control = x$0;
              }
              fn.call(Fake.prototype);
            }
          } else {
            try {
              throw Error();
            } catch (x$1) {
              control = x$1;
            }
            (Fake = fn()) && "function" === typeof Fake.catch && Fake.catch(function () {});
          }
        } catch (sample) {
          if (sample && control && "string" === typeof sample.stack) return [sample.stack,
control.stack];
        }
        return [null, null];
      }
    };
    RunInRootFrame.DetermineComponentFrameRoot.displayName =
"DetermineComponentFrameRoot";
    var namePropDescriptor =
Object.getOwnPropertyDescriptor(RunInRootFrame.DetermineComponentFrameRoot, "name");
    namePropDescriptor && namePropDescriptor.configurable &&
Object.defineProperty(RunInRootFrame.DetermineComponentFrameRoot, "name", {
      value: "DetermineComponentFrameRoot"
    });
    var _RunInRootFrame$Deter = RunInRootFrame.DetermineComponentFrameRoot(),
      sampleStack = _RunInRootFrame$Deter[0],
      controlStack = _RunInRootFrame$Deter[1];
    if (sampleStack && controlStack) {
      var sampleLines = sampleStack.split("\n"),
        controlLines = controlStack.split("\n");
```

```
      for (_RunInRootFrame$Deter = namePropDescriptor = 0; namePropDescriptor <
sampleLines.length && !
sampleLines[namePropDescriptor].includes("DetermineComponentFrameRoot");)
namePropDescriptor++;
      for (; _RunInRootFrame$Deter < controlLines.length && !
controlLines[_RunInRootFrame$Deter].includes("DetermineComponentFrameRoot");)
_RunInRootFrame$Deter++;
      if (namePropDescriptor === sampleLines.length || _RunInRootFrame$Deter ===
controlLines.length) for (namePropDescriptor = sampleLines.length - 1, _RunInRootFrame$Deter =
controlLines.length - 1; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter &&
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter];)
_RunInRootFrame$Deter--;
      for (; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter; namePropDescriptor--,
_RunInRootFrame$Deter--) if (sampleLines[namePropDescriptor] !==
controlLines[_RunInRootFrame$Deter]) {
        if (1 !== namePropDescriptor || 1 !== _RunInRootFrame$Deter) {
          do if (namePropDescriptor--, _RunInRootFrame$Deter--, 0 > _RunInRootFrame$Deter ||
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter]) {
            var _frame = "\n" + sampleLines[namePropDescriptor].replace(" at new ", " at ");
            fn.displayName && _frame.includes("<anonymous>") && (_frame =
_frame.replace("<anonymous>", fn.displayName));
            "function" === typeof fn && componentFrameCache.set(fn, _frame);
            return _frame;
          } while (1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter);
        }
        break;
      }
    }
  } finally {
    reentry = !1, ReactSharedInternals.H = previousDispatcher, reenableLogs(),
Error.prepareStackTrace = frame;
  }
  sampleLines = (sampleLines = fn ? fn.displayName || fn.name : "") ?
describeBuiltInComponentFrame(sampleLines) : "";
  "function" === typeof fn && componentFrameCache.set(fn, sampleLines);
  return sampleLines;
}
function describeUnknownElementTypeFrameInDEV(type) {
  if (null == type) return "";
  if ("function" === typeof type) {
    var prototype = type.prototype;
    return describeNativeComponentFrame(type, !(!prototype || !prototype.isReactComponent));
  }
  if ("string" === typeof type) return describeBuiltInComponentFrame(type);
  switch (type) {
    case REACT_SUSPENSE_TYPE:
      return describeBuiltInComponentFrame("Suspense");
    case REACT_SUSPENSE_LIST_TYPE:
      return describeBuiltInComponentFrame("SuspenseList");
```

```
    }
    if ("object" === typeof type) switch (type.$$typeof) {
      case REACT_FORWARD_REF_TYPE:
        return type = describeNativeComponentFrame(type.render, !1), type;
      case REACT_MEMO_TYPE:
        return describeUnknownElementTypeFrameInDEV(type.type);
      case REACT_LAZY_TYPE:
        prototype = type._payload;
        type = type._init;
        try {
          return describeUnknownElementTypeFrameInDEV(type(prototype));
        } catch (x) {}
    }
    return "";
  }
  function getOwner() {
    var dispatcher = ReactSharedInternals.A;
    return null === dispatcher ? null : dispatcher.getOwner();
  }
  function hasValidKey(config) {
    if (hasOwnProperty.call(config, "key")) {
      var getter = Object.getOwnPropertyDescriptor(config, "key").get;
      if (getter && getter.isReactWarning) return !1;
    }
    return void 0 !== config.key;
  }
  function defineKeyPropWarningGetter(props, displayName) {
    function warnAboutAccessingKey() {
      specialPropKeyWarningShown || (specialPropKeyWarningShown = !0, console.error("%s: `key` is not a prop. Trying to access it will result in `undefined` being returned. If you need to access the same value within the child component, you should pass it as a different prop. (https://react.dev/link/special-props)", displayName));
    }
    warnAboutAccessingKey.isReactWarning = !0;
    Object.defineProperty(props, "key", {
      get: warnAboutAccessingKey,
      configurable: !0
    });
  }
  function elementRefGetterWithDeprecationWarning() {
    var componentName = getComponentNameFromType(this.type);
    didWarnAboutElementRef[componentName] || (didWarnAboutElementRef[componentName] = !0, console.error("Accessing element.ref was removed in React 19. ref is now a regular prop. It will be removed from the JSX Element type in a future release."));
    componentName = this.props.ref;
    return void 0 !== componentName ? componentName : null;
  }
  function ReactElement(type, key, self, source, owner, props) {
    self = props.ref;
```

```
    type = {
      $$typeof: REACT_ELEMENT_TYPE,
      type: type,
      key: key,
      props: props,
      _owner: owner
    };
    null !== (void 0 !== self ? self : null) ? Object.defineProperty(type, "ref", {
      enumerable: !1,
      get: elementRefGetterWithDeprecationWarning
    }) : Object.defineProperty(type, "ref", {
      enumerable: !1,
      value: null
    });
    type._store = {};
    Object.defineProperty(type._store, "validated", {
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: 0
    });
    Object.defineProperty(type, "_debugInfo", {
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: null
    });
    Object.freeze && (Object.freeze(type.props), Object.freeze(type));
    return type;
  }
  function jsxDEVImpl(type, config, maybeKey, isStaticChildren, source, self) {
    if ("string" === typeof type || "function" === typeof type || type === REACT_FRAGMENT_TYPE ||
type === REACT_PROFILER_TYPE || type === REACT_STRICT_MODE_TYPE || type ===
REACT_SUSPENSE_TYPE || type === REACT_SUSPENSE_LIST_TYPE || type ===
REACT_OFFSCREEN_TYPE || "object" === typeof type && null !== type && (type.$$typeof ===
REACT_LAZY_TYPE || type.$$typeof === REACT_MEMO_TYPE || type.$$typeof ===
REACT_CONTEXT_TYPE || type.$$typeof === REACT_CONSUMER_TYPE || type.$$typeof ===
REACT_FORWARD_REF_TYPE || type.$$typeof === REACT_CLIENT_REFERENCE$1 || void 0 !
== type.getModuleId)) {
      var children = config.children;
      if (void 0 !== children) if (isStaticChildren) {
        if (isArrayImpl(children)) {
          for (isStaticChildren = 0; isStaticChildren < children.length; isStaticChildren++)
validateChildKeys(children[isStaticChildren], type);
          Object.freeze && Object.freeze(children);
        } else console.error("React.jsx: Static children should always be an array. You are likely explicitly
calling React.jsxs or React.jsxDEV. Use the Babel transform instead.");
      } else validateChildKeys(children, type);
    } else {
```

```
      children = "";
      if (void 0 === type || "object" === typeof type && null !== type && 0 ===
Object.keys(type).length) children += " You likely forgot to export your component from the file it's
defined in, or you might have mixed up default and named imports.";
      null === type ? isStaticChildren = "null" : isArrayImpl(type) ? isStaticChildren = "array" : void 0 !
== type && type.$$typeof === REACT_ELEMENT_TYPE ? (isStaticChildren = "<" +
(getComponentNameFromType(type.type) || "Unknown") + " />", children = " Did you accidentally
export a JSX literal instead of a component?") : isStaticChildren = typeof type;
      console.error("React.jsx: type is invalid -- expected a string (for built-in components) or a
class/function (for composite components) but got: %s.%s", isStaticChildren, children);
    }
    if (hasOwnProperty.call(config, "key")) {
      children = getComponentNameFromType(type);

      var keys = Object.keys(config).filter(function (k) {
        return "key" !== k;
      });
      isStaticChildren = 0 < keys.length ? "{key: someKey, " + keys.join(": ..., ") + ": ...}" : "{key:
someKey}";
      didWarnAboutKeySpread[children + isStaticChildren] || (keys = 0 < keys.length ? "{" + keys.join(":
..., ") + ": ...}" : "{}", console.error('A props object containing a "key" prop is being spread into JSX:\n
let props = %s;\n  <%s {...props} />\nReact keys must be passed directly to JSX without using
spread:\n  let props = %s;\n  <%s key={someKey} {...props} />', isStaticChildren, children, keys,
children), didWarnAboutKeySpread[children + isStaticChildren] = !0);
    }
    children = null;
    void 0 !== maybeKey && (checkKeyStringCoercion(maybeKey), children = "" + maybeKey);
    hasValidKey(config) && (checkKeyStringCoercion(config.key), children = "" + config.key);
    if ("key" in config) {
      maybeKey = {};
      for (var propName in config) "key" !== propName && (maybeKey[propName] =
config[propName]);
    } else maybeKey = config;
    children && defineKeyPropWarningGetter(maybeKey, "function" === typeof type ?
type.displayName || type.name || "Unknown" : type);
    return ReactElement(type, children, self, source, getOwner(), maybeKey);
  }
  function validateChildKeys(node, parentType) {
    if ("object" === typeof node && node && node.$$typeof !== REACT_CLIENT_REFERENCE) if
(isArrayImpl(node)) for (var i = 0; i < node.length; i++) {
      var child = node[i];
      isValidElement(child) && validateExplicitKey(child, parentType);
    } else if (isValidElement(node)) node._store && (node._store.validated = 1);else if (null === node ||
"object" !== typeof node ? i = null : (i = MAYBE_ITERATOR_SYMBOL &&
node[MAYBE_ITERATOR_SYMBOL] || node["@@iterator"], i = "function" === typeof i ? i : null),
"function" === typeof i && i !== node.entries && (i = i.call(node), i !== node)) for (; !(node =
i.next()).done;) isValidElement(node.value) && validateExplicitKey(node.value, parentType);
  }
  function isValidElement(object) {
```

```
    return "object" === typeof object && null !== object && object.$$typeof ===
REACT_ELEMENT_TYPE;
  }
  function validateExplicitKey(element, parentType) {
    if (element._store && !element._store.validated && null == element.key &&
(element._store.validated = 1, parentType = getCurrentComponentErrorInfo(parentType), !
ownerHasKeyUseWarning[parentType])) {
      ownerHasKeyUseWarning[parentType] = !0;
      var childOwner = "";
      element && null != element._owner && element._owner !== getOwner() && (childOwner = null,
"number" === typeof element._owner.tag ? childOwner =
getComponentNameFromType(element._owner.type) : "string" === typeof element._owner.name &&
(childOwner = element._owner.name), childOwner = " It was passed a child from " + childOwner +
".");
      var prevGetCurrentStack = ReactSharedInternals.getCurrentStack;
      ReactSharedInternals.getCurrentStack = function () {
        var stack = describeUnknownElementTypeFrameInDEV(element.type);
        prevGetCurrentStack && (stack += prevGetCurrentStack() || "");
        return stack;
      };
      console.error('Each child in a list should have a unique "key" prop.%s%s See
https://react.dev/link/warning-keys for more information.', parentType, childOwner);
      ReactSharedInternals.getCurrentStack = prevGetCurrentStack;
    }
  }
  function getCurrentComponentErrorInfo(parentType) {
    var info = "",
      owner = getOwner();
    owner && (owner = getComponentNameFromType(owner.type)) && (info = "\n\nCheck the render
method of `" + owner + "`.");
    info || (parentType = getComponentNameFromType(parentType)) && (info = "\n\nCheck the top-
level render call using <" + parentType + ">.");
    return info;
  }
  var React = __webpack_require__(/*! react */ "./node_modules/react/index.js"),
    REACT_ELEMENT_TYPE = Symbol.for("react.transitional.element"),
    REACT_PORTAL_TYPE = Symbol.for("react.portal"),
    REACT_FRAGMENT_TYPE = Symbol.for("react.fragment"),
    REACT_STRICT_MODE_TYPE = Symbol.for("react.strict_mode"),
    REACT_PROFILER_TYPE = Symbol.for("react.profiler");
  Symbol.for("react.provider");
  var REACT_CONSUMER_TYPE = Symbol.for("react.consumer"),
    REACT_CONTEXT_TYPE = Symbol.for("react.context"),
    REACT_FORWARD_REF_TYPE = Symbol.for("react.forward_ref"),
    REACT_SUSPENSE_TYPE = Symbol.for("react.suspense"),
    REACT_SUSPENSE_LIST_TYPE = Symbol.for("react.suspense_list"),
    REACT_MEMO_TYPE = Symbol.for("react.memo"),
    REACT_LAZY_TYPE = Symbol.for("react.lazy"),
    REACT_OFFSCREEN_TYPE = Symbol.for("react.offscreen"),
```

```
    MAYBE_ITERATOR_SYMBOL = Symbol.iterator,
    REACT_CLIENT_REFERENCE$2 = Symbol.for("react.client.reference"),
    ReactSharedInternals =
React.__CLIENT_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRAD
E,
    hasOwnProperty = Object.prototype.hasOwnProperty,
    assign = Object.assign,
    REACT_CLIENT_REFERENCE$1 = Symbol.for("react.client.reference"),
    isArrayImpl = Array.isArray,
    disabledDepth = 0,
    prevLog,
    prevInfo,
    prevWarn,
    prevError,
    prevGroup,
    prevGroupCollapsed,
    prevGroupEnd;
  disabledLog.__reactDisabledLog = !0;
  var prefix,
    suffix,
    reentry = !1;
  var componentFrameCache = new ("function" === typeof WeakMap ? WeakMap : Map)();
  var REACT_CLIENT_REFERENCE = Symbol.for("react.client.reference"),
    specialPropKeyWarningShown;
  var didWarnAboutElementRef = {};
  var didWarnAboutKeySpread = {},
    ownerHasKeyUseWarning = {};
  exports.Fragment = REACT_FRAGMENT_TYPE;
  exports.jsx = function (type, config, maybeKey, source, self) {
    return jsxDEVImpl(type, config, maybeKey, !1, source, self);
  };
  exports.jsxs = function (type, config, maybeKey, source, self) {
    return jsxDEVImpl(type, config, maybeKey, !0, source, self);
  };
}();

/***/ },

/***/ "./node_modules/react/cjs/react.development.js"
/*!*****************************************************!*\
  !*** ./node_modules/react/cjs/react.development.js ***!
  \*****************************************************/
(module, exports, __webpack_require__) {

"use strict";
/* module decorator */ module = __webpack_require__.nmd(module);
/**
 * @license React
 * react.development.js
```

```
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
 */



 true && function () {
  function defineDeprecationWarning(methodName, info) {
    Object.defineProperty(Component.prototype, methodName, {
      get: function () {
        console.warn("%s(...) is deprecated in plain JavaScript React classes. %s", info[0], info[1]);
      }
    });
  }
  function getIteratorFn(maybeIterable) {
    if (null === maybeIterable || "object" !== typeof maybeIterable) return null;
    maybeIterable = MAYBE_ITERATOR_SYMBOL &&
maybeIterable[MAYBE_ITERATOR_SYMBOL] || maybeIterable["@@iterator"];
    return "function" === typeof maybeIterable ? maybeIterable : null;
  }
  function warnNoop(publicInstance, callerName) {
    publicInstance = (publicInstance = publicInstance.constructor) && (publicInstance.displayName ||
publicInstance.name) || "ReactClass";
    var warningKey = publicInstance + "." + callerName;
    didWarnStateUpdateForUnmountedComponent[warningKey] || (console.error("Can't call %s on a
component that is not yet mounted. This is a no-op, but it might indicate a bug in your application.
Instead, assign to `this.state` directly or define a `state = {};` class property with the desired state in the
%s component.", callerName, publicInstance),
didWarnStateUpdateForUnmountedComponent[warningKey] = !0);
  }
  function Component(props, context, updater) {
    this.props = props;
    this.context = context;
    this.refs = emptyObject;
    this.updater = updater || ReactNoopUpdateQueue;
  }
  function ComponentDummy() {}
  function PureComponent(props, context, updater) {
    this.props = props;
    this.context = context;
    this.refs = emptyObject;
    this.updater = updater || ReactNoopUpdateQueue;
  }
  function testStringCoercion(value) {
    return "" + value;
  }
```

```
  function checkKeyStringCoercion(value) {
    try {
      testStringCoercion(value);
      var JSCompiler_inline_result = !1;
    } catch (e) {
      JSCompiler_inline_result = !0;
    }
    if (JSCompiler_inline_result) {
      JSCompiler_inline_result = console;
      var JSCompiler_temp_const = JSCompiler_inline_result.error;
      var JSCompiler_inline_result$jscomp$0 = "function" === typeof Symbol && Symbol.toStringTag
&& value[Symbol.toStringTag] || value.constructor.name || "Object";
      JSCompiler_temp_const.call(JSCompiler_inline_result, "The provided key is an unsupported type
%s. This value must be coerced to a string before using it here.", JSCompiler_inline_result$jscomp$0);
      return testStringCoercion(value);
    }
  }
  function getComponentNameFromType(type) {
    if (null == type) return null;
    if ("function" === typeof type) return type.$$typeof === REACT_CLIENT_REFERENCE$2 ?
null : type.displayName || type.name || null;
    if ("string" === typeof type) return type;
    switch (type) {
      case REACT_FRAGMENT_TYPE:
        return "Fragment";
      case REACT_PORTAL_TYPE:
        return "Portal";
      case REACT_PROFILER_TYPE:
        return "Profiler";
      case REACT_STRICT_MODE_TYPE:
        return "StrictMode";
      case REACT_SUSPENSE_TYPE:
        return "Suspense";
      case REACT_SUSPENSE_LIST_TYPE:
        return "SuspenseList";
    }
    if ("object" === typeof type) switch ("number" === typeof type.tag && console.error("Received an
unexpected object in getComponentNameFromType(). This is likely a bug in React. Please file an
issue."), type.$$typeof) {
      case REACT_CONTEXT_TYPE:
        return (type.displayName || "Context") + ".Provider";

      case REACT_CONSUMER_TYPE:
        return (type._context.displayName || "Context") + ".Consumer";
      case REACT_FORWARD_REF_TYPE:
        var innerType = type.render;
        type = type.displayName;
        type || (type = innerType.displayName || innerType.name || "", type = "" !== type ? "ForwardRef("
+ type + ")" : "ForwardRef");
```

```
        return type;
      case REACT_MEMO_TYPE:
        return innerType = type.displayName || null, null !== innerType ? innerType :
getComponentNameFromType(type.type) || "Memo";
      case REACT_LAZY_TYPE:
        innerType = type._payload;
        type = type._init;
        try {
          return getComponentNameFromType(type(innerType));
        } catch (x) {}
    }
    return null;
  }
  function isValidElementType(type) {
    return "string" === typeof type || "function" === typeof type || type ===
REACT_FRAGMENT_TYPE || type === REACT_PROFILER_TYPE || type ===
REACT_STRICT_MODE_TYPE || type === REACT_SUSPENSE_TYPE || type ===
REACT_SUSPENSE_LIST_TYPE || type === REACT_OFFSCREEN_TYPE || "object" === typeof
type && null !== type && (type.$$typeof === REACT_LAZY_TYPE || type.$$typeof ===
REACT_MEMO_TYPE || type.$$typeof === REACT_CONTEXT_TYPE || type.$$typeof ===
REACT_CONSUMER_TYPE || type.$$typeof === REACT_FORWARD_REF_TYPE || type.$$typeof
=== REACT_CLIENT_REFERENCE$1 || void 0 !== type.getModuleId) ? !0 : !1;
  }
  function disabledLog() {}
  function disableLogs() {
    if (0 === disabledDepth) {
      prevLog = console.log;
      prevInfo = console.info;
      prevWarn = console.warn;
      prevError = console.error;
      prevGroup = console.group;
      prevGroupCollapsed = console.groupCollapsed;
      prevGroupEnd = console.groupEnd;
      var props = {
        configurable: !0,
        enumerable: !0,
        value: disabledLog,
        writable: !0
      };
      Object.defineProperties(console, {
        info: props,
        log: props,
        warn: props,
        error: props,
        group: props,
        groupCollapsed: props,
        groupEnd: props
      });
    }
```

```
    disabledDepth++;
  }
  function reenableLogs() {
    disabledDepth--;
    if (0 === disabledDepth) {
      var props = {
        configurable: !0,
        enumerable: !0,
        writable: !0
      };
      Object.defineProperties(console, {
        log: assign({}, props, {
          value: prevLog
        }),
        info: assign({}, props, {
          value: prevInfo
        }),
        warn: assign({}, props, {
          value: prevWarn
        }),
        error: assign({}, props, {
          value: prevError
        }),
        group: assign({}, props, {
          value: prevGroup
        }),
        groupCollapsed: assign({}, props, {
          value: prevGroupCollapsed
        }),
        groupEnd: assign({}, props, {
          value: prevGroupEnd
        })
      });
    }
    0 > disabledDepth && console.error("disabledDepth fell below zero. This is a bug in React. Please
file an issue.");
  }
  function describeBuiltInComponentFrame(name) {
    if (void 0 === prefix) try {
      throw Error();
    } catch (x) {
      var match = x.stack.trim().match(/\n( *(at )?)/);
      prefix = match && match[1] || "";
      suffix = -1 < x.stack.indexOf("\n    at") ? " (<anonymous>)" : -1 < x.stack.indexOf("@") ?
"@unknown:0:0" : "";
    }
    return "\n" + prefix + name + suffix;
  }
  function describeNativeComponentFrame(fn, construct) {
```

```
  if (!fn || reentry) return "";
  var frame = componentFrameCache.get(fn);
  if (void 0 !== frame) return frame;
  reentry = !0;
  frame = Error.prepareStackTrace;
  Error.prepareStackTrace = void 0;
  var previousDispatcher = null;
  previousDispatcher = ReactSharedInternals.H;
  ReactSharedInternals.H = null;
  disableLogs();
  try {
    var RunInRootFrame = {
      DetermineComponentFrameRoot: function () {
        try {
          if (construct) {
            var Fake = function () {
              throw Error();
            };
            Object.defineProperty(Fake.prototype, "props", {
              set: function () {
                throw Error();
              }
            });
            if ("object" === typeof Reflect && Reflect.construct) {
              try {
                Reflect.construct(Fake, []);
              } catch (x) {
                var control = x;
              }
              Reflect.construct(fn, [], Fake);
            } else {
              try {
                Fake.call();
              } catch (x$0) {
                control = x$0;
              }
              fn.call(Fake.prototype);
            }
          } else {
            try {
              throw Error();
            } catch (x$1) {
              control = x$1;
            }
            (Fake = fn()) && "function" === typeof Fake.catch && Fake.catch(function () {});
          }
        } catch (sample) {
          if (sample && control && "string" === typeof sample.stack) return [sample.stack,
control.stack];
```

```
        }
        return [null, null];
      }
    };
    RunInRootFrame.DetermineComponentFrameRoot.displayName =
"DetermineComponentFrameRoot";
    var namePropDescriptor =
Object.getOwnPropertyDescriptor(RunInRootFrame.DetermineComponentFrameRoot, "name");
    namePropDescriptor && namePropDescriptor.configurable &&
Object.defineProperty(RunInRootFrame.DetermineComponentFrameRoot, "name", {
      value: "DetermineComponentFrameRoot"
    });
    var _RunInRootFrame$Deter = RunInRootFrame.DetermineComponentFrameRoot(),
      sampleStack = _RunInRootFrame$Deter[0],
      controlStack = _RunInRootFrame$Deter[1];
    if (sampleStack && controlStack) {
      var sampleLines = sampleStack.split("\n"),
        controlLines = controlStack.split("\n");
      for (_RunInRootFrame$Deter = namePropDescriptor = 0; namePropDescriptor <
sampleLines.length && !
sampleLines[namePropDescriptor].includes("DetermineComponentFrameRoot");)
namePropDescriptor++;
      for (; _RunInRootFrame$Deter < controlLines.length && !
controlLines[_RunInRootFrame$Deter].includes("DetermineComponentFrameRoot");)
_RunInRootFrame$Deter++;
      if (namePropDescriptor === sampleLines.length || _RunInRootFrame$Deter ===
controlLines.length) for (namePropDescriptor = sampleLines.length - 1, _RunInRootFrame$Deter =
controlLines.length - 1; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter &&
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter];)
_RunInRootFrame$Deter--;
      for (; 1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter; namePropDescriptor--,
_RunInRootFrame$Deter--) if (sampleLines[namePropDescriptor] !==
controlLines[_RunInRootFrame$Deter]) {
        if (1 !== namePropDescriptor || 1 !== _RunInRootFrame$Deter) {
          do if (namePropDescriptor--, _RunInRootFrame$Deter--, 0 > _RunInRootFrame$Deter ||
sampleLines[namePropDescriptor] !== controlLines[_RunInRootFrame$Deter]) {
            var _frame = "\n" + sampleLines[namePropDescriptor].replace(" at new ", " at ");
            fn.displayName && _frame.includes("<anonymous>") && (_frame =
_frame.replace("<anonymous>", fn.displayName));
            "function" === typeof fn && componentFrameCache.set(fn, _frame);
            return _frame;
          } while (1 <= namePropDescriptor && 0 <= _RunInRootFrame$Deter);
        }
        break;
      }
    }
  } finally {
    reentry = !1, ReactSharedInternals.H = previousDispatcher, reenableLogs(),
Error.prepareStackTrace = frame;
```

```
    }
    sampleLines = (sampleLines = fn ? fn.displayName || fn.name : "") ?
describeBuiltInComponentFrame(sampleLines) : "";
    "function" === typeof fn && componentFrameCache.set(fn, sampleLines);
    return sampleLines;
  }
  function describeUnknownElementTypeFrameInDEV(type) {
    if (null == type) return "";
    if ("function" === typeof type) {
      var prototype = type.prototype;
      return describeNativeComponentFrame(type, !(!prototype || !prototype.isReactComponent));
    }
    if ("string" === typeof type) return describeBuiltInComponentFrame(type);
    switch (type) {
      case REACT_SUSPENSE_TYPE:
        return describeBuiltInComponentFrame("Suspense");
      case REACT_SUSPENSE_LIST_TYPE:
        return describeBuiltInComponentFrame("SuspenseList");
    }
    if ("object" === typeof type) switch (type.$$typeof) {
      case REACT_FORWARD_REF_TYPE:
        return type = describeNativeComponentFrame(type.render, !1), type;
      case REACT_MEMO_TYPE:
        return describeUnknownElementTypeFrameInDEV(type.type);
      case REACT_LAZY_TYPE:
        prototype = type._payload;
        type = type._init;
        try {
          return describeUnknownElementTypeFrameInDEV(type(prototype));
        } catch (x) {}
    }
    return "";
  }
  function getOwner() {
    var dispatcher = ReactSharedInternals.A;
    return null === dispatcher ? null : dispatcher.getOwner();
  }
  function hasValidKey(config) {
    if (hasOwnProperty.call(config, "key")) {
      var getter = Object.getOwnPropertyDescriptor(config, "key").get;
      if (getter && getter.isReactWarning) return !1;
    }
    return void 0 !== config.key;
  }
  function defineKeyPropWarningGetter(props, displayName) {
    function warnAboutAccessingKey() {
      specialPropKeyWarningShown || (specialPropKeyWarningShown = !0, console.error("%s: `key` is
not a prop. Trying to access it will result in `undefined` being returned. If you need to access the same
value within the child component, you should pass it as a different prop. (https://react.dev/link/special-
```

```
props)", displayName));
    }
    warnAboutAccessingKey.isReactWarning = !0;
    Object.defineProperty(props, "key", {
      get: warnAboutAccessingKey,
      configurable: !0
    });
  }
  function elementRefGetterWithDeprecationWarning() {
    var componentName
 = getComponentNameFromType(this.type);
    didWarnAboutElementRef[componentName] || (didWarnAboutElementRef[componentName] = !0,
console.error("Accessing element.ref was removed in React 19. ref is now a regular prop. It will be
removed from the JSX Element type in a future release."));
    componentName = this.props.ref;
    return void 0 !== componentName ? componentName : null;
  }
  function ReactElement(type, key, self, source, owner, props) {
    self = props.ref;
    type = {
      $$typeof: REACT_ELEMENT_TYPE,
      type: type,
      key: key,
      props: props,
      _owner: owner
    };
    null !== (void 0 !== self ? self : null) ? Object.defineProperty(type, "ref", {
      enumerable: !1,
      get: elementRefGetterWithDeprecationWarning
    }) : Object.defineProperty(type, "ref", {
      enumerable: !1,
      value: null
    });
    type._store = {};
    Object.defineProperty(type._store, "validated", {
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: 0
    });
    Object.defineProperty(type, "_debugInfo", {
      configurable: !1,
      enumerable: !1,
      writable: !0,
      value: null
    });
    Object.freeze && (Object.freeze(type.props), Object.freeze(type));
    return type;
  }
```

```
  function cloneAndReplaceKey(oldElement, newKey) {
    newKey = ReactElement(oldElement.type, newKey, void 0, void 0, oldElement._owner,
oldElement.props);
    newKey._store.validated = oldElement._store.validated;
    return newKey;
  }
  function validateChildKeys(node, parentType) {
    if ("object" === typeof node && node && node.$$typeof !== REACT_CLIENT_REFERENCE) if
(isArrayImpl(node)) for (var i = 0; i < node.length; i++) {
      var child = node[i];
      isValidElement(child) && validateExplicitKey(child, parentType);
    } else if (isValidElement(node)) node._store && (node._store.validated = 1);else if (i =
getIteratorFn(node), "function" === typeof i && i !== node.entries && (i = i.call(node), i !== node))
for (; !(node = i.next()).done;) isValidElement(node.value) && validateExplicitKey(node.value,
parentType);
  }
  function isValidElement(object) {
    return "object" === typeof object && null !== object && object.$$typeof ===
REACT_ELEMENT_TYPE;
  }
  function validateExplicitKey(element, parentType) {
    if (element._store && !element._store.validated && null == element.key &&
(element._store.validated = 1, parentType = getCurrentComponentErrorInfo(parentType), !
ownerHasKeyUseWarning[parentType])) {
      ownerHasKeyUseWarning[parentType] = !0;
      var childOwner = "";
      element && null != element._owner && element._owner !== getOwner() && (childOwner = null,
"number" === typeof element._owner.tag ? childOwner =
getComponentNameFromType(element._owner.type) : "string" === typeof element._owner.name &&
(childOwner = element._owner.name), childOwner = " It was passed a child from " + childOwner +
".");
      var prevGetCurrentStack = ReactSharedInternals.getCurrentStack;
      ReactSharedInternals.getCurrentStack = function () {
        var stack = describeUnknownElementTypeFrameInDEV(element.type);
        prevGetCurrentStack && (stack += prevGetCurrentStack() || "");
        return stack;
      };
      console.error('Each child in a list should have a unique "key" prop.%s%s See
https://react.dev/link/warning-keys for more information.', parentType, childOwner);
      ReactSharedInternals.getCurrentStack = prevGetCurrentStack;
    }
  }
  function getCurrentComponentErrorInfo(parentType) {
    var info = "",
      owner = getOwner();
    owner && (owner = getComponentNameFromType(owner.type)) && (info = "\n\nCheck the render
method of `" + owner + "`.");
    info || (parentType = getComponentNameFromType(parentType)) && (info = "\n\nCheck the top-
level render call using <" + parentType + ">.");
```

```
    return info;
  }
  function escape(key) {
    var escaperLookup = {
      "=": "=0",
      ":": "=2"
    };
    return "$" + key.replace(/[=:]/g, function (match) {
      return escaperLookup[match];
    });
  }
  function getElementKey(element, index) {
    return "object" === typeof element && null !== element && null != element.key ?
(checkKeyStringCoercion(element.key), escape("" + element.key)) : index.toString(36);
  }
  function noop$1() {}
  function resolveThenable(thenable) {
    switch (thenable.status) {
      case "fulfilled":
        return thenable.value;
      case "rejected":
        throw thenable.reason;
      default:
        switch ("string" === typeof thenable.status ? thenable.then(noop$1, noop$1) : (thenable.status =
"pending", thenable.then(function (fulfilledValue) {
          "pending" === thenable.status && (thenable.status = "fulfilled", thenable.value = fulfilledValue);
        }, function (error) {
          "pending" === thenable.status && (thenable.status = "rejected", thenable.reason = error);
        })), thenable.status) {
          case "fulfilled":
            return thenable.value;
          case "rejected":
            throw thenable.reason;
        }
    }
    throw thenable;
  }
  function mapIntoArray(children, array, escapedPrefix, nameSoFar, callback) {
    var type = typeof children;
    if ("undefined" === type || "boolean" === type) children = null;
    var invokeCallback = !1;
    if (null === children) invokeCallback = !0;else switch (type) {
      case "bigint":
      case "string":
      case "number":
        invokeCallback = !0;
        break;
      case "object":
        switch (children.$$typeof) {
```

```
        case REACT_ELEMENT_TYPE:
        case REACT_PORTAL_TYPE:
          invokeCallback = !0;
          break;
        case REACT_LAZY_TYPE:
          return invokeCallback = children._init, mapIntoArray(invokeCallback(children._payload),
array, escapedPrefix, nameSoFar, callback);
      }
    }
    if (invokeCallback) {
      invokeCallback = children;
      callback = callback(invokeCallback);
      var childKey = "" === nameSoFar ? "." + getElementKey(invokeCallback, 0) : nameSoFar;
      isArrayImpl(callback) ? (escapedPrefix = "", null != childKey && (escapedPrefix =
childKey.replace(userProvidedKeyEscapeRegex, "$&/") + "/"), mapIntoArray(callback, array,
escapedPrefix, "", function (c) {
        return c;
      })) : null != callback && (isValidElement(callback) && (null != callback.key && (invokeCallback
&& invokeCallback.key === callback.key || checkKeyStringCoercion(callback.key)), escapedPrefix =
cloneAndReplaceKey(callback, escapedPrefix + (null == callback.key || invokeCallback &&
invokeCallback.key === callback.key ? "" : ("" + callback.key).replace(userProvidedKeyEscapeRegex,
"$&/") + "/") + childKey), "" !== nameSoFar && null != invokeCallback &&
isValidElement(invokeCallback) && null == invokeCallback.key && invokeCallback._store && !
invokeCallback._store.validated && (escapedPrefix._store.validated = 2), callback = escapedPrefix),
array.push(callback));
      return 1;
    }
    invokeCallback = 0;
    childKey = "" === nameSoFar ? "." : nameSoFar + ":";
    if (isArrayImpl(children)) for (var i = 0; i < children.length; i++) nameSoFar = children[i], type =
childKey + getElementKey(nameSoFar, i), invokeCallback += mapIntoArray(nameSoFar, array,
escapedPrefix, type, callback);else if (i = getIteratorFn(children), "function" === typeof i) for (i ===
children.entries && (didWarnAboutMaps || console.warn("Using Maps as children is not supported.
Use an array of keyed ReactElements instead."), didWarnAboutMaps = !0), children = i.call(children), i
= 0; !(nameSoFar = children.next()).done;) nameSoFar = nameSoFar.value, type = childKey +
getElementKey(nameSoFar, i++), invokeCallback += mapIntoArray(nameSoFar, array, escapedPrefix,
type, callback);else if ("object" === type) {
      if ("function" === typeof children.then) return mapIntoArray(resolveThenable(children), array,
escapedPrefix, nameSoFar, callback);
      array = String(children);
      throw Error("Objects are not valid as a React child (found: " + ("[object Object]" === array ?
"object with keys {" + Object.keys(children).join(", ") + "}" : array) + "). If you meant to render a
collection of children, use an array instead.");
    }
    return invokeCallback;
  }
  function mapChildren(children, func, context) {
    if (null == children) return children;
    var result = [],
```

```
      count = 0;
    mapIntoArray(children, result, "", "", function (child) {
      return func.call(context, child, count++);
    });
    return result;
  }
  function lazyInitializer(payload) {
    if (-1 === payload._status) {
      var ctor = payload._result;
      ctor = ctor();
      ctor.then(function (moduleObject) {
        if (0 === payload._status || -1 === payload._status) payload._status = 1, payload._result =
moduleObject;
      }, function (error) {
        if (0 === payload._status || -1 === payload._status) payload._status = 2, payload._result = error;
      });
      -1 === payload._status && (payload._status = 0, payload._result = ctor);
    }
    if (1 === payload._status) return ctor = payload._result, void 0 === ctor && console.error("lazy:
Expected the result of a dynamic import() call. Instead received: %s\n\nYour code should look like: \n
const MyComponent = lazy(() => import('./MyComponent'))\n\nDid you accidentally put curly braces
around the import?", ctor), "default" in ctor || console.error("lazy: Expected the result of a dynamic
import() call. Instead received: %s\n\nYour code should look like: \n  const MyComponent = lazy(() =>
import('./MyComponent'))", ctor), ctor.default;
    throw payload._result;
  }
  function resolveDispatcher() {
    var dispatcher = ReactSharedInternals.H;
    null === dispatcher && console.error("Invalid hook call. Hooks can only be called inside of the
body of a function component. This could happen for one of the following reasons:\n1. You might have
mismatching versions of React and the renderer
 (such as React DOM)\n2. You might be breaking the Rules of Hooks\n3. You might have more than
one copy of React in the same app\nSee https://react.dev/link/invalid-hook-call for tips about how to
debug and fix this problem.");
    return dispatcher;
  }
  function noop() {}
  function enqueueTask(task) {
    if (null === enqueueTaskImpl) try {
      var requireString = ("require" + Math.random()).slice(0, 7);
      enqueueTaskImpl = (module && module[requireString]).call(module, "timers").setImmediate;
    } catch (_err) {
      enqueueTaskImpl = function (callback) {
        !1 === didWarnAboutMessageChannel && (didWarnAboutMessageChannel = !0, "undefined"
=== typeof MessageChannel && console.error("This browser does not have a MessageChannel
implementation, so enqueuing tasks via await act(async () => ...) will fail. Please file an issue at
https://github.com/facebook/react/issues if you encounter this warning."));
        var channel = new MessageChannel();
        channel.port1.onmessage = callback;
```

```
      channel.port2.postMessage(void 0);
    };
  }
  return enqueueTaskImpl(task);
}
function aggregateErrors(errors) {
  return 1 < errors.length && "function" === typeof AggregateError ? new AggregateError(errors) :
errors[0];
}
function popActScope(prevActQueue, prevActScopeDepth) {
  prevActScopeDepth !== actScopeDepth - 1 && console.error("You seem to have overlapping act()
calls, this is not supported. Be sure to await previous act() calls before making a new one. ");
  actScopeDepth = prevActScopeDepth;
}
function recursivelyFlushAsyncActWork(returnValue, resolve, reject) {
  var queue = ReactSharedInternals.actQueue;
  if (null !== queue) if (0 !== queue.length) try {
    flushActQueue(queue);
    enqueueTask(function () {
      return recursivelyFlushAsyncActWork(returnValue, resolve, reject);
    });
    return;
  } catch (error) {
    ReactSharedInternals.thrownErrors.push(error);
  } else ReactSharedInternals.actQueue = null;
  0 < ReactSharedInternals.thrownErrors.length ? (queue =
aggregateErrors(ReactSharedInternals.thrownErrors), ReactSharedInternals.thrownErrors.length = 0,
reject(queue)) : resolve(returnValue);
}
function flushActQueue(queue) {
  if (!isFlushing) {
    isFlushing = !0;
    var i = 0;
    try {
      for (; i < queue.length; i++) {
        var callback = queue[i];
        do {
          ReactSharedInternals.didUsePromise = !1;
          var continuation = callback(!1);
          if (null !== continuation) {
            if (ReactSharedInternals.didUsePromise) {
              queue[i] = callback;
              queue.splice(0, i);
              return;
            }
            callback = continuation;
          } else break;
        } while (1);
      }
```

```
        queue.length = 0;
      } catch (error) {
        queue.splice(0, i + 1), ReactSharedInternals.thrownErrors.push(error);
      } finally {
        isFlushing = !1;
      }
    }
  }
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart(Error());
  var REACT_ELEMENT_TYPE = Symbol.for("react.transitional.element"),
    REACT_PORTAL_TYPE = Symbol.for("react.portal"),
    REACT_FRAGMENT_TYPE = Symbol.for("react.fragment"),
    REACT_STRICT_MODE_TYPE = Symbol.for("react.strict_mode"),
    REACT_PROFILER_TYPE = Symbol.for("react.profiler");
  Symbol.for("react.provider");
  var REACT_CONSUMER_TYPE = Symbol.for("react.consumer"),
    REACT_CONTEXT_TYPE = Symbol.for("react.context"),
    REACT_FORWARD_REF_TYPE = Symbol.for("react.forward_ref"),
    REACT_SUSPENSE_TYPE = Symbol.for("react.suspense"),
    REACT_SUSPENSE_LIST_TYPE = Symbol.for("react.suspense_list"),
    REACT_MEMO_TYPE = Symbol.for("react.memo"),
    REACT_LAZY_TYPE = Symbol.for("react.lazy"),
    REACT_OFFSCREEN_TYPE = Symbol.for("react.offscreen"),
    MAYBE_ITERATOR_SYMBOL = Symbol.iterator,
    didWarnStateUpdateForUnmountedComponent = {},
    ReactNoopUpdateQueue = {
      isMounted: function () {
        return !1;
      },
      enqueueForceUpdate: function (publicInstance) {
        warnNoop(publicInstance, "forceUpdate");
      },
      enqueueReplaceState: function (publicInstance) {
        warnNoop(publicInstance, "replaceState");
      },
      enqueueSetState: function (publicInstance) {
        warnNoop(publicInstance, "setState");
      }
    },
    assign = Object.assign,
    emptyObject = {};
  Object.freeze(emptyObject);
  Component.prototype.isReactComponent = {};
  Component.prototype.setState = function (partialState, callback) {
    if ("object" !== typeof partialState && "function" !== typeof partialState && null != partialState)
throw Error("takes an object of state variables to update or a function which returns an object of state
variables.");
```

```
    this.updater.enqueueSetState(this, partialState, callback, "setState");
  };
  Component.prototype.forceUpdate = function (callback) {
    this.updater.enqueueForceUpdate(this, callback, "forceUpdate");
  };
  var deprecatedAPIs = {
      isMounted: ["isMounted", "Instead, make sure to clean up subscriptions and pending requests in
componentWillUnmount to prevent memory leaks."],
      replaceState: ["replaceState", "Refactor your code to use setState instead (see
https://github.com/facebook/react/issues/3236)."]
    },
    fnName;
  for (fnName in deprecatedAPIs) deprecatedAPIs.hasOwnProperty(fnName) &&
defineDeprecationWarning(fnName, deprecatedAPIs[fnName]);
  ComponentDummy.prototype = Component.prototype;
  deprecatedAPIs = PureComponent.prototype = new ComponentDummy();
  deprecatedAPIs.constructor = PureComponent;
  assign(deprecatedAPIs, Component.prototype);
  deprecatedAPIs.isPureReactComponent = !0;
  var isArrayImpl = Array.isArray,
    REACT_CLIENT_REFERENCE$2 = Symbol.for("react.client.reference"),
    ReactSharedInternals = {
      H: null,
      A: null,
      T: null,
      S: null,
      actQueue: null,
      isBatchingLegacy: !1,
      didScheduleLegacyUpdate: !1,
      didUsePromise: !1,
      thrownErrors: [],
      getCurrentStack: null
    },
    hasOwnProperty = Object.prototype.hasOwnProperty,
    REACT_CLIENT_REFERENCE$1 = Symbol.for("react.client.reference"),
    disabledDepth = 0,
    prevLog,
    prevInfo,
    prevWarn,
    prevError,
    prevGroup,
    prevGroupCollapsed,
    prevGroupEnd;
  disabledLog.__reactDisabledLog = !0;
  var prefix,
    suffix,
    reentry = !1;
  var componentFrameCache = new ("function" === typeof WeakMap ? WeakMap : Map)();
  var REACT_CLIENT_REFERENCE = Symbol.for("react.client.reference"),
```

```
    specialPropKeyWarningShown,
    didWarnAboutOldJSXRuntime;
  var didWarnAboutElementRef = {};
  var ownerHasKeyUseWarning = {},
    didWarnAboutMaps = !1,
    userProvidedKeyEscapeRegex = /\/+/g,
    reportGlobalError = "function" === typeof reportError ? reportError : function (error) {
      if ("object" === typeof window && "function" === typeof window.ErrorEvent) {
        var event = new window.ErrorEvent("error", {
          bubbles: !0,
          cancelable: !0,
          message: "object" === typeof error && null !== error && "string" === typeof error.message ?
String(error.message) : String(error),
          error: error
        });
        if (!window.dispatchEvent(event)) return;
      } else if ("object" === typeof process && "function" === typeof process.emit) {
        process.emit("uncaughtException", error);
        return;
      }
      console.error(error);
    },
    didWarnAboutMessageChannel = !1,
    enqueueTaskImpl = null,
    actScopeDepth = 0,
    didWarnNoAwaitAct = !1,
    isFlushing = !1,
    queueSeveralMicrotasks = "function" === typeof queueMicrotask ? function (callback) {
      queueMicrotask(function () {
        return queueMicrotask(callback);
      });
    } : enqueueTask;
  exports.Children = {
    map: mapChildren,
    forEach: function (children, forEachFunc, forEachContext) {
      mapChildren(children, function () {
        forEachFunc.apply(this, arguments);
      }, forEachContext);
    },
    count: function (children) {
      var n = 0;
      mapChildren(children, function () {
        n++;
      });
      return n;
    },
    toArray: function (children) {
      return mapChildren(children, function (child) {
        return child;
```

```
    }) || [];
  },
  only: function (children) {
    if (!isValidElement(children)) throw Error("React.Children.only expected to receive a single React
element child.");
    return children;
  }
};
exports.Component = Component;
exports.Fragment = REACT_FRAGMENT_TYPE;
exports.Profiler = REACT_PROFILER_TYPE;
exports.PureComponent = PureComponent;
exports.StrictMode = REACT_STRICT_MODE_TYPE;
exports.Suspense = REACT_SUSPENSE_TYPE;

exports.__CLIENT_INTERNALS_DO_NOT_USE_OR_WARN_USERS_THEY_CANNOT_UPGRA
DE = ReactSharedInternals;
exports.act = function (callback) {
  var prevActQueue = ReactSharedInternals.actQueue,
    prevActScopeDepth = actScopeDepth;
  actScopeDepth++;
  var queue = ReactSharedInternals.actQueue = null !== prevActQueue ? prevActQueue : [],
    didAwaitActCall = !1;
  try {
    var result = callback();
  } catch (error) {
    ReactSharedInternals.thrownErrors.push(error);
  }
  if (0 < ReactSharedInternals.thrownErrors.length) throw popActScope(prevActQueue,
prevActScopeDepth), callback = aggregateErrors(ReactSharedInternals.thrownErrors),
ReactSharedInternals.thrownErrors.length = 0, callback;
  if (null !== result && "object" === typeof result && "function" === typeof result.then) {
    var thenable = result;
    queueSeveralMicrotasks(function () {
      didAwaitActCall || didWarnNoAwaitAct || (didWarnNoAwaitAct = !0, console.error("You called
act(async () => ...) without
 await. This could lead to unexpected testing behaviour, interleaving multiple act calls and mixing their
scopes. You should - await act(async () => ...);"));
    });
    return {
      then: function (resolve, reject) {
        didAwaitActCall = !0;
        thenable.then(function (returnValue) {
          popActScope(prevActQueue, prevActScopeDepth);
          if (0 === prevActScopeDepth) {
            try {
              flushActQueue(queue), enqueueTask(function () {
                return recursivelyFlushAsyncActWork(returnValue, resolve, reject);
              });
```

```
            } catch (error$2) {
              ReactSharedInternals.thrownErrors.push(error$2);
            }
            if (0 < ReactSharedInternals.thrownErrors.length) {
              var _thrownError = aggregateErrors(ReactSharedInternals.thrownErrors);
              ReactSharedInternals.thrownErrors.length = 0;
              reject(_thrownError);
            }
          } else resolve(returnValue);
        }, function (error) {
          popActScope(prevActQueue, prevActScopeDepth);
          0 < ReactSharedInternals.thrownErrors.length ? (error =
aggregateErrors(ReactSharedInternals.thrownErrors), ReactSharedInternals.thrownErrors.length = 0,
reject(error)) : reject(error);
        });
      }
    };
  }
  var returnValue$jscomp$0 = result;
  popActScope(prevActQueue, prevActScopeDepth);
  0 === prevActScopeDepth && (flushActQueue(queue), 0 !== queue.length &&
queueSeveralMicrotasks(function () {
    didAwaitActCall || didWarnNoAwaitAct || (didWarnNoAwaitAct = !0, console.error("A component
suspended inside an `act` scope, but the `act` call was not awaited. When testing React components that
depend on asynchronous data, you must await the result:\n\nawait act(() => ...)"));
  }), ReactSharedInternals.actQueue = null);
  if (0 < ReactSharedInternals.thrownErrors.length) throw callback =
aggregateErrors(ReactSharedInternals.thrownErrors), ReactSharedInternals.thrownErrors.length = 0,
callback;
  return {
    then: function (resolve, reject) {
      didAwaitActCall = !0;
      0 === prevActScopeDepth ? (ReactSharedInternals.actQueue = queue, enqueueTask(function () {
        return recursivelyFlushAsyncActWork(returnValue$jscomp$0, resolve, reject);
      })) : resolve(returnValue$jscomp$0);
    }
  };
};
exports.cache = function (fn) {
  return function () {
    return fn.apply(null, arguments);
  };
};
exports.cloneElement = function (element, config, children) {
  if (null === element || void 0 === element) throw Error("The argument must be a React element, but
you passed " + element + ".");
  var props = assign({}, element.props),
    key = element.key,
    owner = element._owner;
```

```
    if (null != config) {
      var JSCompiler_inline_result;
      a: {
        if (hasOwnProperty.call(config, "ref") && (JSCompiler_inline_result =
Object.getOwnPropertyDescriptor(config, "ref").get) && JSCompiler_inline_result.isReactWarning) {
          JSCompiler_inline_result = !1;
          break a;
        }
        JSCompiler_inline_result = void 0 !== config.ref;
      }
      JSCompiler_inline_result && (owner = getOwner());
      hasValidKey(config) && (checkKeyStringCoercion(config.key), key = "" + config.key);
      for (propName in config) !hasOwnProperty.call(config, propName) || "key" === propName ||
"__self" === propName || "__source" === propName || "ref" === propName && void 0 === config.ref
|| (props[propName] = config[propName]);
    }
    var propName = arguments.length - 2;
    if (1 === propName) props.children = children;else if (1 < propName) {
      JSCompiler_inline_result = Array(propName);
      for (var i = 0; i < propName; i++) JSCompiler_inline_result[i] = arguments[i + 2];
      props.children = JSCompiler_inline_result;
    }
    props = ReactElement(element.type, key, void 0, void 0, owner, props);
    for (key = 2; key < arguments.length; key++) validateChildKeys(arguments[key], props.type);
    return props;
  };
  exports.createContext = function (defaultValue) {
    defaultValue = {
      $$typeof: REACT_CONTEXT_TYPE,
      _currentValue: defaultValue,
      _currentValue2: defaultValue,
      _threadCount: 0,
      Provider: null,
      Consumer: null
    };
    defaultValue.Provider = defaultValue;
    defaultValue.Consumer = {
      $$typeof: REACT_CONSUMER_TYPE,
      _context: defaultValue
    };
    defaultValue._currentRenderer = null;
    defaultValue._currentRenderer2 = null;
    return defaultValue;
  };
  exports.createElement = function (type, config, children) {
    if (isValidElementType(type)) for (var i = 2; i < arguments.length; i++)
validateChildKeys(arguments[i], type);else {
      i = "";
      if (void 0 === type || "object" === typeof type && null !== type && 0 ===
```

```
Object.keys(type).length) i += " You likely forgot to export your component from the file it's defined in, or you might have mixed up default and named imports.";
      if (null === type) var typeString = "null";else isArrayImpl(type) ? typeString = "array" : void 0 !== type && type.$$typeof === REACT_ELEMENT_TYPE ? (typeString = "<" + (getComponentNameFromType(type.type) || "Unknown") + " />", i = " Did you accidentally export a JSX literal instead of a component?") : typeString = typeof type;
      console.error("React.createElement: type is invalid -- expected a string (for built-in components) or a class/function (for composite components) but got: %s.%s", typeString, i);
    }
    var propName;
    i = {};
    typeString = null;
    if (null != config) for (propName in didWarnAboutOldJSXRuntime || !("__self" in config) || "key" in config || (didWarnAboutOldJSXRuntime = !0, console.warn("Your app (or one of its dependencies) is using an outdated JSX transform. Update to the modern JSX transform for faster performance: https://react.dev/link/new-jsx-transform")), hasValidKey(config) && (checkKeyStringCoercion(config.key), typeString = "" + config.key), config) hasOwnProperty.call(config, propName) && "key" !== propName && "__self" !== propName && "__source" !== propName && (i[propName] = config[propName]);
    var childrenLength = arguments.length - 2;
    if (1 === childrenLength) i.children = children;else if (1 < childrenLength) {
      for (var childArray = Array(childrenLength), _i = 0; _i < childrenLength; _i++) childArray[_i] = arguments[_i + 2];
      Object.freeze && Object.freeze(childArray);
      i.children = childArray;
    }
    if (type && type.defaultProps) for (propName in childrenLength = type.defaultProps, childrenLength) void 0 === i[propName] && (i[propName] = childrenLength[propName]);
    typeString && defineKeyPropWarningGetter(i, "function" === typeof type ? type.displayName || type.name || "Unknown" : type);
    return ReactElement(type, typeString, void 0, void 0, getOwner(), i);
  };
  exports.createRef = function () {
    var refObject = {
      current: null
    };
    Object.seal(refObject);
    return refObject;
  };
  exports.forwardRef = function (render) {
    null != render && render.$$typeof === REACT_MEMO_TYPE ? console.error("forwardRef requires a render function but received a `memo` component. Instead of forwardRef(memo(...)), use memo(forwardRef(...)).") : "function" !== typeof render ? console.error("forwardRef requires a render function but was given %s.", null === render ? "null" : typeof render) : 0 !== render.length && 2 !== render.length && console.error("forwardRef render functions accept exactly two parameters: props and ref. %s", 1 === render.length ? "Did you forget to use the ref parameter?" : "Any additional parameter will be undefined.");
    null != render && null != render.defaultProps && console.error("forwardRef render functions do not support defaultProps. Did you accidentally pass a React component?");
```

```
    var elementType = {
      $$typeof: REACT_FORWARD_REF_TYPE,
      render: render
    },
    ownName;
    Object.defineProperty(elementType, "displayName", {
      enumerable: !1,
      configurable: !0,
      get: function () {
        return ownName;
      },
      set: function (name) {
        ownName = name;
        render.name || render.displayName || (Object.defineProperty(render, "name", {
          value: name
        }), render.displayName = name);
      }
    });
    return elementType;
  };
  exports.isValidElement = isValidElement;
  exports.lazy = function (ctor) {
    return {
      $$typeof: REACT_LAZY_TYPE,
      _payload: {
        _status: -1,
        _result: ctor
      },
      _init: lazyInitializer
    };
  };
  exports.memo = function (type, compare) {
    isValidElementType(type) || console.error("memo: The first argument must be a component. Instead
received: %s", null === type ? "null" : typeof type);
    compare = {
      $$typeof: REACT_MEMO_TYPE,
      type: type,
      compare: void 0 === compare ? null : compare
    };
    var ownName;
    Object.defineProperty(compare, "displayName", {
      enumerable: !1,
      configurable: !0,
      get: function () {
        return ownName;
      },
      set: function (name) {
        ownName = name;
        type.name || type.displayName || (Object.defineProperty(type, "name", {
```

```
          value: name
        }), type.displayName = name);
      }
    });
    return compare;
  };
  exports.startTransition = function (scope) {
    var prevTransition = ReactSharedInternals.T,
      currentTransition = {};
    ReactSharedInternals.T = currentTransition;
    currentTransition._updatedFibers = new Set();
    try {
      var returnValue = scope(),
        onStartTransitionFinish = ReactSharedInternals.S;
      null !== onStartTransitionFinish && onStartTransitionFinish(currentTransition, returnValue);
      "object" === typeof returnValue && null !== returnValue && "function" === typeof
returnValue.then
 && returnValue.then(noop, reportGlobalError);
    } catch (error) {
      reportGlobalError(error);
    } finally {
      null === prevTransition && currentTransition._updatedFibers && (scope =
currentTransition._updatedFibers.size, currentTransition._updatedFibers.clear(), 10 < scope &&
console.warn("Detected a large number of updates inside startTransition. If this is due to a subscription
please re-write it to use React provided hooks. Otherwise concurrent mode guarantees are off the
table.")), ReactSharedInternals.T = prevTransition;
    }
  };
  exports.unstable_useCacheRefresh = function () {
    return resolveDispatcher().useCacheRefresh();
  };
  exports.use = function (usable) {
    return resolveDispatcher().use(usable);
  };
  exports.useActionState = function (action, initialState, permalink) {
    return resolveDispatcher().useActionState(action, initialState, permalink);
  };
  exports.useCallback = function (callback, deps) {
    return resolveDispatcher().useCallback(callback, deps);
  };
  exports.useContext = function (Context) {
    var dispatcher = resolveDispatcher();
    Context.$$typeof === REACT_CONSUMER_TYPE && console.error("Calling
useContext(Context.Consumer) is not supported and will cause bugs. Did you mean to call
useContext(Context) instead?");
    return dispatcher.useContext(Context);
  };
  exports.useDebugValue = function (value, formatterFn) {
    return resolveDispatcher().useDebugValue(value, formatterFn);
```

```
  };
  exports.useDeferredValue = function (value, initialValue) {
    return resolveDispatcher().useDeferredValue(value, initialValue);
  };
  exports.useEffect = function (create, deps) {
    return resolveDispatcher().useEffect(create, deps);
  };
  exports.useId = function () {
    return resolveDispatcher().useId();
  };
  exports.useImperativeHandle = function (ref, create, deps) {
    return resolveDispatcher().useImperativeHandle(ref, create, deps);
  };
  exports.useInsertionEffect = function (create, deps) {
    return resolveDispatcher().useInsertionEffect(create, deps);
  };
  exports.useLayoutEffect = function (create, deps) {
    return resolveDispatcher().useLayoutEffect(create, deps);
  };
  exports.useMemo = function (create, deps) {
    return resolveDispatcher().useMemo(create, deps);
  };
  exports.useOptimistic = function (passthrough, reducer) {
    return resolveDispatcher().useOptimistic(passthrough, reducer);
  };
  exports.useReducer = function (reducer, initialArg, init) {
    return resolveDispatcher().useReducer(reducer, initialArg, init);
  };
  exports.useRef = function (initialValue) {
    return resolveDispatcher().useRef(initialValue);
  };
  exports.useState = function (initialState) {
    return resolveDispatcher().useState(initialState);
  };
  exports.useSyncExternalStore = function (subscribe, getSnapshot, getServerSnapshot) {
    return resolveDispatcher().useSyncExternalStore(subscribe, getSnapshot, getServerSnapshot);
  };
  exports.useTransition = function () {
    return resolveDispatcher().useTransition();
  };
  exports.version = "19.0.0";
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop(Error());
}();

/***/ },

/***/ "./node_modules/react/index.js"
```

```
/*!*************************************!*\
  !*** ./node_modules/react/index.js ***!
  \*************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/react.development.js */
"./node_modules/react/cjs/react.development.js");
}

/***/ },

/***/ "./node_modules/react/jsx-dev-runtime.js"
/*!***********************************************!*\
  !*** ./node_modules/react/jsx-dev-runtime.js ***!
  \***********************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/react-jsx-dev-runtime.development.js */
"./node_modules/react/cjs/react-jsx-dev-runtime.development.js");
}

/***/ },

/***/ "./node_modules/react/jsx-runtime.js"
/*!*******************************************!*\
  !*** ./node_modules/react/jsx-runtime.js ***!
  \*******************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/react-jsx-runtime.development.js */
"./node_modules/react/cjs/react-jsx-runtime.development.js");
}

/***/ },
```

```
/***/ "./node_modules/scheduler/cjs/scheduler.development.js"
/*!*****************************************************************!*\
  !*** ./node_modules/scheduler/cjs/scheduler.development.js ***!
  \*****************************************************************/
(__unused_webpack_module, exports) {

"use strict";
/**
 * @license React
 * scheduler.development.js
 *
 * Copyright (c) Meta Platforms, Inc. and affiliates.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE file in the root directory of this source tree.
 */



 true && function () {
  function performWorkUntilDeadline() {
    if (isMessageLoopRunning) {
      var currentTime = exports.unstable_now();
      startTime = currentTime;
      var hasMoreWork = !0;
      try {
        a: {
          isHostCallbackScheduled = !1;
          isHostTimeoutScheduled && (isHostTimeoutScheduled = !1,
localClearTimeout(taskTimeoutID), taskTimeoutID = -1);
          isPerformingWork = !0;
          var previousPriorityLevel = currentPriorityLevel;
          try {
            b: {
              advanceTimers(currentTime);
              for (currentTask = peek(taskQueue); null !== currentTask && !(currentTask.expirationTime >
currentTime && shouldYieldToHost());) {
                var callback = currentTask.callback;
                if ("function" === typeof callback) {
                  currentTask.callback = null;
                  currentPriorityLevel = currentTask.priorityLevel;
                  var continuationCallback = callback(currentTask.expirationTime <= currentTime);
                  currentTime = exports.unstable_now();
                  if ("function" === typeof continuationCallback) {
                    currentTask.callback = continuationCallback;
                    advanceTimers(currentTime);
                    hasMoreWork = !0;
                    break b;
```

```
            }
            currentTask === peek(taskQueue) && pop(taskQueue);
            advanceTimers(currentTime);
          } else pop(taskQueue);
          currentTask = peek(taskQueue);
        }
        if (null !== currentTask) hasMoreWork = !0;else {
          var firstTimer = peek(timerQueue);
          null !== firstTimer && requestHostTimeout(handleTimeout, firstTimer.startTime -
currentTime);
          hasMoreWork = !1;
        }
      }
      break a;
    } finally {
      currentTask = null, currentPriorityLevel = previousPriorityLevel, isPerformingWork = !1;
    }
    hasMoreWork = void 0;
  }
 } finally {
  hasMoreWork ? schedulePerformWorkUntilDeadline() : isMessageLoopRunning = !1;
 }
 }
}
function push(heap, node) {
 var index = heap.length;
 heap.push(node);
 a: for (; 0 < index;) {
  var parentIndex = index - 1 >>> 1,
   parent = heap[parentIndex];
  if (0 < compare(parent, node)) heap[parentIndex] = node, heap[index] = parent, index =
parentIndex;else break a;
 }
}
function peek(heap) {
 return 0 === heap.length ? null : heap[0];
}
function pop(heap) {
 if (0 === heap.length) return null;
 var first = heap[0],
  last = heap.pop();
 if (last !== first) {
  heap[0] = last;
  a: for (var index = 0, length = heap.length, halfLength = length >>> 1; index < halfLength;) {
   var leftIndex = 2 * (index + 1) - 1,
    left = heap[leftIndex],
    rightIndex = leftIndex + 1,
    right = heap[rightIndex];
   if (0 > compare(left, last)) rightIndex < length && 0 > compare(right, left) ? (heap[index] = right,
```

```
heap[rightIndex] = last, index = rightIndex) : (heap[index] = left, heap[leftIndex] = last, index =
leftIndex);else if (rightIndex < length && 0 > compare(right, last)) heap[index] = right,
heap[rightIndex] = last, index = rightIndex;else break a;
      }
    }
    return first;
  }
  function compare(a, b) {
    var diff = a.sortIndex - b.sortIndex;
    return 0 !== diff ? diff : a.id - b.id;
  }
  function advanceTimers(currentTime) {
    for (var timer = peek(timerQueue); null !== timer;) {
      if (null === timer.callback) pop(timerQueue);else if (timer.startTime <= currentTime)
pop(timerQueue), timer.sortIndex = timer.expirationTime, push(taskQueue, timer);else break;
      timer = peek(timerQueue);
    }
  }
  function handleTimeout(currentTime) {
    isHostTimeoutScheduled = !1;
    advanceTimers(currentTime);
    if (!isHostCallbackScheduled) if (null !== peek(taskQueue)) isHostCallbackScheduled = !0,
requestHostCallback();else {
      var firstTimer = peek(timerQueue);
      null !== firstTimer && requestHostTimeout(handleTimeout, firstTimer.startTime - currentTime);
    }
  }
  function shouldYieldToHost() {
    return exports.unstable_now() - startTime < frameInterval ? !1 : !0;
  }
  function requestHostCallback() {
    isMessageLoopRunning || (isMessageLoopRunning = !0, schedulePerformWorkUntilDeadline());
  }
  function requestHostTimeout(callback, ms) {
    taskTimeoutID = localSetTimeout(function () {
      callback(exports.unstable_now());
    }, ms);
  }
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__
 && "function" === typeof __REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart
&& __REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStart(Error());
  exports.unstable_now = void 0;
  if ("object" === typeof performance && "function" === typeof performance.now) {
    var localPerformance = performance;
    exports.unstable_now = function () {
      return localPerformance.now();
    };
  } else {
    var localDate = Date,
```

```
    initialTime = localDate.now();
   exports.unstable_now = function () {
    return localDate.now() - initialTime;
   };
  }
  var taskQueue = [],
   timerQueue = [],
   taskIdCounter = 1,
   currentTask = null,
   currentPriorityLevel = 3,
   isPerformingWork = !1,
   isHostCallbackScheduled = !1,
   isHostTimeoutScheduled = !1,
   localSetTimeout = "function" === typeof setTimeout ? setTimeout : null,
   localClearTimeout = "function" === typeof clearTimeout ? clearTimeout : null,
   localSetImmediate = "undefined" !== typeof setImmediate ? setImmediate : null,
   isMessageLoopRunning = !1,
   taskTimeoutID = -1,
   frameInterval = 5,
   startTime = -1;
  if ("function" === typeof localSetImmediate) var schedulePerformWorkUntilDeadline = function () {
   localSetImmediate(performWorkUntilDeadline);
  };else if ("undefined" !== typeof MessageChannel) {
   var channel = new MessageChannel(),
    port = channel.port2;
   channel.port1.onmessage = performWorkUntilDeadline;
   schedulePerformWorkUntilDeadline = function () {
    port.postMessage(null);
   };
  } else schedulePerformWorkUntilDeadline = function () {
   localSetTimeout(performWorkUntilDeadline, 0);
  };
  exports.unstable_IdlePriority = 5;
  exports.unstable_ImmediatePriority = 1;
  exports.unstable_LowPriority = 4;
  exports.unstable_NormalPriority = 3;
  exports.unstable_Profiling = null;
  exports.unstable_UserBlockingPriority = 2;
  exports.unstable_cancelCallback = function (task) {
   task.callback = null;
  };
  exports.unstable_continueExecution = function () {
   isHostCallbackScheduled || isPerformingWork || (isHostCallbackScheduled = !0,
requestHostCallback());
  };
  exports.unstable_forceFrameRate = function (fps) {
   0 > fps || 125 < fps ? console.error("forceFrameRate takes a positive int between 0 and 125, forcing
frame rates higher than 125 fps is not supported") : frameInterval = 0 < fps ? Math.floor(1e3 / fps) : 5;
  };
```

```
  exports.unstable_getCurrentPriorityLevel = function () {
    return currentPriorityLevel;
  };
  exports.unstable_getFirstCallbackNode = function () {
    return peek(taskQueue);
  };
  exports.unstable_next = function (eventHandler) {
    switch (currentPriorityLevel) {
      case 1:
      case 2:
      case 3:
        var priorityLevel = 3;
        break;
      default:
        priorityLevel = currentPriorityLevel;
    }
    var previousPriorityLevel = currentPriorityLevel;
    currentPriorityLevel = priorityLevel;
    try {
      return eventHandler();
    } finally {
      currentPriorityLevel = previousPriorityLevel;
    }
  };
  exports.unstable_pauseExecution = function () {};
  exports.unstable_requestPaint = function () {};
  exports.unstable_runWithPriority = function (priorityLevel, eventHandler) {
    switch (priorityLevel) {
      case 1:
      case 2:
      case 3:
      case 4:
      case 5:
        break;
      default:
        priorityLevel = 3;
    }
    var previousPriorityLevel = currentPriorityLevel;
    currentPriorityLevel = priorityLevel;
    try {
      return eventHandler();
    } finally {
      currentPriorityLevel = previousPriorityLevel;
    }
  };
  exports.unstable_scheduleCallback = function (priorityLevel, callback, options) {
    var currentTime = exports.unstable_now();
    "object" === typeof options && null !== options ? (options = options.delay, options = "number"
=== typeof options && 0 < options ? currentTime + options : currentTime) : options = currentTime;
```

```
    switch (priorityLevel) {
      case 1:
        var timeout = -1;
        break;
      case 2:
        timeout = 250;
        break;
      case 5:
        timeout = 1073741823;
        break;
      case 4:
        timeout = 1e4;
        break;
      default:
        timeout = 5e3;
    }
    timeout = options + timeout;
    priorityLevel = {
      id: taskIdCounter++,
      callback: callback,
      priorityLevel: priorityLevel,
      startTime: options,
      expirationTime: timeout,
      sortIndex: -1
    };
    options > currentTime ? (priorityLevel.sortIndex = options, push(timerQueue, priorityLevel), null
=== peek(taskQueue) && priorityLevel === peek(timerQueue) && (isHostTimeoutScheduled ?
(localClearTimeout(taskTimeoutID), taskTimeoutID = -1) : isHostTimeoutScheduled = !0,
requestHostTimeout(handleTimeout, options - currentTime))) : (priorityLevel.sortIndex = timeout,
push(taskQueue, priorityLevel), isHostCallbackScheduled || isPerformingWork ||
(isHostCallbackScheduled = !0, requestHostCallback()));
    return priorityLevel;
  };
  exports.unstable_shouldYield = shouldYieldToHost;
  exports.unstable_wrapCallback = function (callback) {
    var parentPriorityLevel = currentPriorityLevel;
    return function () {
      var previousPriorityLevel = currentPriorityLevel;
      currentPriorityLevel = parentPriorityLevel;
      try {
        return callback.apply(this, arguments);
      } finally {
        currentPriorityLevel = previousPriorityLevel;
      }
    };
  };
  "undefined" !== typeof __REACT_DEVTOOLS_GLOBAL_HOOK__ && "function" === typeof
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop &&
__REACT_DEVTOOLS_GLOBAL_HOOK__.registerInternalModuleStop(Error());
```

```
}();

/***/ },

/***/ "./node_modules/scheduler/index.js"
/*!*****************************************!*\
  !*** ./node_modules/scheduler/index.js ***!
  \*****************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


if (false) // removed by dead control flow
{} else {
  module.exports = __webpack_require__(/*! ./cjs/scheduler.development.js */
"./node_modules/scheduler/cjs/scheduler.development.js");
}

/***/ },

/***/ "./node_modules/webpack-dev-server/client/clients/WebSocketClient.js"
/*!***************************************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/clients/WebSocketClient.js ***!
  \***************************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ WebSocketClient)
/* harmony export */ });
/* harmony import */ var _utils_log_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils/log.js */ "./node_modules/webpack-dev-server/client/utils/log.js");
function _typeof(o) {
  "@babel/helpers - typeof";

  return _typeof = "function" == typeof Symbol && "symbol" == typeof Symbol.iterator ? function (o)
{
    return typeof o;
  } : function (o) {
    return o && "function" == typeof Symbol && o.constructor === Symbol && o !==
Symbol.prototype ? "symbol" : typeof o;
  }, _typeof(o);
}
function _classCallCheck(a, n) {
  if (!(a instanceof n)) throw new TypeError("Cannot call a class as a function");
}
function _defineProperties(e, r) {
```

```
  for (var t = 0; t < r.length; t++) {
    var o = r[t];
    o.enumerable = o.enumerable || !1, o.configurable = !0, "value" in o && (o.writable = !0),
Object.defineProperty(e, _toPropertyKey(o.key), o);
  }
}
function _createClass(e, r, t) {
  return r && _defineProperties(e.prototype, r), t && _defineProperties(e, t), Object.defineProperty(e,
"prototype", {
    writable: !1
  }), e;
}
function _toPropertyKey(t) {
  var i = _toPrimitive(t, "string");
  return "symbol" == _typeof(i) ? i : i + "";
}
function _toPrimitive(t, r) {
  if ("object" != _typeof(t) || !t) return t;
  var e = t[Symbol.toPrimitive];
  if (void 0 !== e) {
    var i = e.call(t, r || "default");
    if ("object" != _typeof(i)) return i;
    throw new TypeError("@@toPrimitive must return a primitive value.");
  }
  return ("string" === r ? String : Number)(t);
}


/** @typedef {import("../index").EXPECTED_ANY} EXPECTED_ANY */

/**
 * @implements {CommunicationClient}
 */
var WebSocketClient = /*#__PURE__*/function () {
  /**
   * @param {string} url url to connect
   */
  function WebSocketClient(url) {
    _classCallCheck(this, WebSocketClient);
    this.client = new WebSocket(url);
    this.client.onerror = function (error) {
      _utils_log_js__WEBPACK_IMPORTED_MODULE_0__.log.error(error);
    };
  }

  /**
   * @param {(...args: EXPECTED_ANY[]) => void} fn function
   */
  return _createClass(WebSocketClient, [{
```

```
    key: "onOpen",
    value: function onOpen(fn) {
      this.client.onopen = fn;
    }

    /**
     * @param {(...args: EXPECTED_ANY[]) => void} fn function
     */
  }, {
    key: "onClose",
    value: function onClose(fn) {
      this.client.onclose = fn;
    }

    // call f with the message string as the first argument
    /**
     * @param {(...args: EXPECTED_ANY[]) => void} fn function
     */
  }, {
    key: "onMessage",
    value: function onMessage(fn) {
      this.client.onmessage = function (err) {
        fn(err.data);
      };
    }
  }]);
}();


/***/ },

/***/ "./node_modules/webpack-dev-server/client/index.js?protocol=ws
%3A&hostname=0.0.0.0&port=443&pathname=%2Fws&logging=none&overlay=%7B%22errors
%22%3Atrue%2C%22warnings%22%3Afalse%7D&reconnect=10&hot=true&live-reload=true"
/*!
**********************************************************************************
**********************************************************************************
**********************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/index.js?protocol=ws
%3A&hostname=0.0.0.0&port=443&pathname=%2Fws&logging=none&overlay=%7B%22errors
%22%3Atrue%2C%22warnings%
22%3Afalse%7D&reconnect=10&hot=true&live-reload=true ***!

\**********************************************************************************
**********************************************************************************
**********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
```

```
var __resourceQuery = "?protocol=ws%3A&hostname=0.0.0.0&port=443&pathname=
%2Fws&logging=none&overlay=%7B%22errors%22%3Atrue%2C%22warnings%22%3Afalse
%7D&reconnect=10&hot=true&live-reload=true";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   createSocketURL: () => (/* binding */ createSocketURL),
/* harmony export */   getCurrentScriptSource: () => (/* binding */ getCurrentScriptSource),
/* harmony export */   parseURL: () => (/* binding */ parseURL)
/* harmony export */ });
/* harmony import */ var webpack_hot_emitter_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! webpack/hot/emitter.js */ "./node_modules/webpack/hot/emitter.js");
/* harmony import */ var webpack_hot_emitter_js__WEBPACK_IMPORTED_MODULE_0___default
=
/*#__PURE__*/__webpack_require__.n(webpack_hot_emitter_js__WEBPACK_IMPORTED_MODU
LE_0__);
/* harmony import */ var webpack_hot_log_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! webpack/hot/log.js */ "./node_modules/webpack/hot/log.js");
/* harmony import */ var webpack_hot_log_js__WEBPACK_IMPORTED_MODULE_1___default
=
/*#__PURE__*/__webpack_require__.n(webpack_hot_log_js__WEBPACK_IMPORTED_MODULE_
1__);
/* harmony import */ var _overlay_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./overlay.js */ "./node_modules/webpack-dev-server/client/overlay.js");
/* harmony import */ var _progress_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./progress.js */ "./node_modules/webpack-dev-server/client/progress.js");
/* harmony import */ var _socket_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ./socket.js */ "./node_modules/webpack-dev-server/client/socket.js");
/* harmony import */ var _utils_log_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ./utils/log.js */ "./node_modules/webpack-dev-server/client/utils/log.js");
/* harmony import */ var _utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ./utils/sendMessage.js */ "./node_modules/webpack-dev-
server/client/utils/sendMessage.js");
function ownKeys(e, r) {
  var t = Object.keys(e);
  if (Object.getOwnPropertySymbols) {
    var o = Object.getOwnPropertySymbols(e);
    r && (o = o.filter(function (r) {
      return Object.getOwnPropertyDescriptor(e, r).enumerable;
    })), t.push.apply(t, o);
  }
  return t;
}
function _objectSpread(e) {
  for (var r = 1; r < arguments.length; r++) {
    var t = null != arguments[r] ? arguments[r] : {};
    r % 2 ? ownKeys(Object(t), !0).forEach(function (r) {
      _defineProperty(e, r, t[r]);
    }) : Object.getOwnPropertyDescriptors ? Object.defineProperties(e,
Object.getOwnPropertyDescriptors(t)) : ownKeys(Object(t)).forEach(function (r) {
```

```
      Object.defineProperty(e, r, Object.getOwnPropertyDescriptor(t, r));
    });
  }
  return e;
}
function _defineProperty(e, r, t) {
  return (r = _toPropertyKey(r)) in e ? Object.defineProperty(e, r, {
    value: t,
    enumerable: !0,
    configurable: !0,
    writable: !0
  }) : e[r] = t, e;
}
function _toPropertyKey(t) {
  var i = _toPrimitive(t, "string");
  return "symbol" == _typeof(i) ? i : i + "";
}
function _toPrimitive(t, r) {
  if ("object" != _typeof(t) || !t) return t;
  var e = t[Symbol.toPrimitive];
  if (void 0 !== e) {
    var i = e.call(t, r || "default");
    if ("object" != _typeof(i)) return i;
    throw new TypeError("@@toPrimitive must return a primitive value.");
  }
  return ("string" === r ? String : Number)(t);
}
function _typeof(o) {
  "@babel/helpers - typeof";

  return _typeof = "function" == typeof Symbol && "symbol" == typeof Symbol.iterator ? function (o)
{
    return typeof o;
  } : function (o) {
    return o && "function" == typeof Symbol && o.constructor === Symbol && o !==
Symbol.prototype ? "symbol" : typeof o;
  }, _typeof(o);
}
/* global __resourceQuery, __webpack_hash__ */
// @ts-expect-error

// @ts-expect-error
```

```
// eslint-disable-next-line jsdoc/no-restricted-syntax
/** @typedef {any} EXPECTED_ANY */

/**
 * @typedef {object} RawOverlayOptions
 * @property {string=} warnings warnings
 * @property {string=} errors errors
 * @property {string=} runtimeErrors runtime errors
 * @property {string=} trustedTypesPolicyName trusted types policy name
 */

/**
 * @typedef {object} OverlayOptions
 * @property {(boolean | ((error: Error) => boolean))=} warnings warnings
 * @property {(boolean | ((error: Error) => boolean))=} errors errors
 * @property {(boolean | ((error: Error) => boolean))=} runtimeErrors runtime errors
 * @property {string=} trustedTypesPolicyName trusted types policy name
 */

/** @typedef {false | true | "none" | "error" | "warn" | "info" | "log" | "verbose"} LogLevel */

/**
 * @typedef {object} Options
 * @property {boolean} hot true when hot enabled, otherwise false
 * @property {boolean} liveReload true when live reload enabled, otherwise false
 * @property {boolean} progress true when need to show progress, otherwise false
 * @property {boolean | OverlayOptions} overlay overlay options
 * @property {LogLevel=} logging logging level
 * @property {number=} reconnect count of allowed reconnection
 */

/**
 * @typedef {object} Status
 * @property {boolean} isUnloading true when unloaded, otherwise false
 * @property {string} currentHash current hash
 * @property {string=} previousHash previous hash
 */

/**
 * @param {boolean | RawOverlayOptions | OverlayOptions} overlayOptions overlay options
 */
var decodeOverlayOptions = function decodeOverlayOptions(overlayOptions) {
  if (_typeof(overlayOptions) === "object") {
    var requiredOptions = ["warnings", "errors", "runtimeErrors"];
    for (var i = 0; i < requiredOptions.length; i++) {
      var property = /** @type {keyof Omit<RawOverlayOptions, "trustedTypesPolicyName">} */
      requiredOptions[i];
      if (typeof overlayOptions[property] === "string") {
        var overlayFilterFunctionString = decodeURIComponent(overlayOptions[property]);
```

```
      /** @type {OverlayOptions} */
      overlayOptions[property] = /** @type {(error: Error) => boolean} */
      // eslint-disable-next-line no-new-func
      new Function("message", "var callback = ".concat(overlayFilterFunctionString, "\n        return callback(message)"));
    }
   }
  }
};

/**
 * @type {Status}
 */
var status = {
  isUnloading: false,
  currentHash: __webpack_require__.h()
};

/**
 * @returns {string} current script source
 */
var getCurrentScriptSource = function getCurrentScriptSource() {
  // `document.currentScript` is the most accurate way to find the current script,
  // but is not supported in all browsers.
  if (document.currentScript) {
    return /** @type {string} */document.currentScript.getAttribute("src");
  }

  // Fallback to getting all scripts running in the document.
  var scriptElements = document.scripts || [];
  var scriptElementsWithSrc = Array.prototype.filter.call(scriptElements, function (element) {
    return element.getAttribute("src");
  });
  if (scriptElementsWithSrc.length > 0) {
    var currentScript = scriptElementsWithSrc[scriptElementsWithSrc.length - 1];
    return currentScript.getAttribute("src");
  }

  // Fail as there was no script to use.
  throw new Error("[webpack-dev-server] Failed to get current script source.");
};

/** @typedef {{ hot?: string, ["live-reload"]?: string, progress?: string, reconnect?: string, logging?: LogLevel, overlay?: string, fromCurrentScript?: boolean }} AdditionalParsedURL */
/** @typedef {Partial<URL> & AdditionalParsedURL} ParsedURL */

/**
 * @param {string} resourceQuery resource query
```

```
 * @returns {ParsedURL} parsed URL
 */
var parseURL = function parseURL(resourceQuery) {
  /** @type {ParsedURL} */
  var result = {};
  if (typeof resourceQuery === "string" && resourceQuery !== "") {
    var searchParams = resourceQuery.slice(1).split("&");
    for (var i = 0; i < searchParams.length; i++) {
      var pair = searchParams[i].split("=");

      /** @type {EXPECTED_ANY} */
      result[pair[0]] = decodeURIComponent(pair[1]);
    }
  } else {
    // Else, get the url from the <script> this file was called with.
    var scriptSource = getCurrentScriptSource();
    var scriptSourceURL;
    try {
      // The placeholder `baseURL` with `window.location.href`,
      // is to allow parsing of path-relative or protocol-relative URLs,
      // and will have no effect if `scriptSource` is a fully valid URL.
      scriptSourceURL = new URL(scriptSource, self.location.href);
    } catch (_err) {
      // URL parsing failed, do nothing.
      // We will still proceed to see if we can recover using `resourceQuery`
    }
    if (scriptSourceURL) {
      result = scriptSourceURL;
      result.fromCurrentScript = true;
    }
  }
  return result;
};
var parsedResourceQuery = parseURL(__resourceQuery);

/** @typedef {{ ["Hot Module Replacement"]: boolean, ["Live Reloading"]: boolean, Progress:
boolean, Overlay: boolean }} Features */

/** @type {Features} */
var enabledFeatures = {
  "Hot Module Replacement": false,
  "Live Reloading": false,
  Progress: false,
  Overlay: false
};

/** @type {Options} */
var options = {
  hot: false,
```

```
  liveReload: false,
  progress: false,
  overlay: false
};
if (parsedResourceQuery.hot === "true") {
  options.hot = true;
  enabledFeatures["Hot Module Replacement"] = true;
}
if (parsedResourceQuery["live-reload"] === "true") {
  options.liveReload = true;
  enabledFeatures["Live Reloading"] = true;
}
if (parsedResourceQuery.progress === "true") {
  options.progress = true;

  enabledFeatures.Progress = true;
}
if (parsedResourceQuery.overlay) {
  try {
    options.overlay = JSON.parse(parsedResourceQuery.overlay);
  } catch (err) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.error("Error parsing overlay options
from resource query:", err);
  }

  // Fill in default "true" params for partially-specified objects.
  if (_typeof(options.overlay) === "object") {
    options.overlay = _objectSpread({
      errors: true,
      warnings: true,
      runtimeErrors: true
    }, options.overlay);
    decodeOverlayOptions(options.overlay);
  }
  enabledFeatures.Overlay = options.overlay !== false;
}
if (parsedResourceQuery.logging) {
  options.logging = parsedResourceQuery.logging;
}
if (typeof parsedResourceQuery.reconnect !== "undefined") {
  options.reconnect = Number(parsedResourceQuery.reconnect);
}

/**
 * @param {false | true | "none" | "error" | "warn" | "info" | "log" | "verbose"} level level
 */
var setAllLogLevel = function setAllLogLevel(level) {
  // This is needed because the HMR logger operate separately from dev server logger
  webpack_hot_log_js__WEBPACK_IMPORTED_MODULE_1___default().setLogLevel(level ===
```

```
"verbose" || level === "log" ? "info" : level);
  (0,_utils_log_js__WEBPACK_IMPORTED_MODULE_5__.setLogLevel)(level);
};
if (options.logging) {
  setAllLogLevel(options.logging);
}

/**
 * @param {Features} features features
 */
var logEnabledFeatures = function logEnabledFeatures(features) {
  var listEnabledFeatures = Object.keys(features);
  if (!features || listEnabledFeatures.length === 0) {
    return;
  }
  var logString = "Server started:";

  // Server started: Hot Module Replacement enabled, Live Reloading enabled, Overlay disabled.
  for (var i = 0; i < listEnabledFeatures.length; i++) {
    var key = /** @type {keyof Features} */listEnabledFeatures[i];
    logString += " ".concat(key, " ").concat(features[key] ? "enabled" : "disabled", ",");
  }
  // replace last comma with a period
  logString = logString.slice(0, -1).concat(".");
  _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info(logString);
};
logEnabledFeatures(enabledFeatures);
self.addEventListener("beforeunload", function () {
  status.isUnloading = true;
});
var overlay = typeof window !== "undefined" ?
(0,_overlay_js__WEBPACK_IMPORTED_MODULE_2__.createOverlay)(_typeof(options.overlay)
=== "object" ? {
  trustedTypesPolicyName: options.overlay.trustedTypesPolicyName,
  catchRuntimeError: options.overlay.runtimeErrors
} : {
  trustedTypesPolicyName: false,
  catchRuntimeError: options.overlay
}) : {
  send: function send() {}
};

/**
 * @param {Options} options options
 * @param {Status} currentStatus current status
 */
var reloadApp = function reloadApp(_ref, currentStatus) {
  var hot = _ref.hot,
    liveReload = _ref.liveReload;
```

```
  if (currentStatus.isUnloading) {
    return;
  }
  var currentHash = currentStatus.currentHash,
    previousHash = currentStatus.previousHash;
  var isInitial = currentHash.indexOf(/** @type {string} */previousHash) >= 0;
  if (isInitial) {
    return;
  }

  /**
   * @param {Window} rootWindow root window
   * @param {number} intervalId interval id
   */
  function applyReload(rootWindow, intervalId) {
    clearInterval(intervalId);
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("App updated. Reloading...");
    rootWindow.location.reload();
  }
  var search = self.location.search.toLowerCase();
  var allowToHot = search.indexOf("webpack-dev-server-hot=false") === -1;
  var allowToLiveReload = search.indexOf("webpack-dev-server-live-reload=false") === -1;
  if (hot && allowToHot) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("App hot update...");
    if (typeof EventTarget !== "undefined" &&
(webpack_hot_emitter_js__WEBPACK_IMPORTED_MODULE_0___default()) instanceof
EventTarget) {
      var event = new CustomEvent("webpackHotUpdate", {
        detail: {
          currentHash: currentStatus.currentHash
        },
        bubbles: true,
        cancelable: false
      });

webpack_hot_emitter_js__WEBPACK_IMPORTED_MODULE_0___default().dispatchEvent(event);
    } else {

webpack_hot_emitter_js__WEBPACK_IMPORTED_MODULE_0___default().emit("webpackHotUpd
ate", currentStatus.currentHash);
    }
    if (typeof self !== "undefined" && self.window) {
      // broadcast update to window
      self.postMessage("webpackHotUpdate".concat(currentStatus.currentHash), "*");
    }
  }
  // allow refreshing the page only if liveReload isn't disabled
  else if (liveReload && allowToLiveReload) {
    /** @type {Window} */
```

```
    var rootWindow = self;

    // use parent window for reload (in case we're in an iframe with no valid src)
    var intervalId = self.setInterval(function () {
      if (rootWindow.location.protocol !== "about:") {
        // reload immediately if protocol is valid
        applyReload(rootWindow, intervalId);
      } else {
        rootWindow = rootWindow.parent;
        if (rootWindow.parent === rootWindow) {
          // if parent equals current window we've reached the root which would continue forever, so
trigger a reload anyways
          applyReload(rootWindow, intervalId);
        }
      }
    });
  }
};
var ansiRegex = new RegExp(["[\\u001B\\u009B][[\\]()#;?]*(?:(?:(?:(?:;[-a-zA-Z\\d\\/#&.:=?%@~_]
+)*|[a-zA-Z\\d]+(?:;[-a-zA-Z\\d\\/#&.:=?%@~_]*)*)?\\u0007)", "(?:(?:\\d{1,4}(?:;\\d{0,4})*)?[\\dA-
PR-TZcf-nq-uy=><~]))"].join("|"), "g");

/**
 * Strip [ANSI escape codes](https://en.wikipedia.org/wiki/ANSI_escape_code) from a string.
 * Adapted from code originally released by Sindre Sorhus
 * Licensed the MIT License
 * @param {string} string string
 * @returns {string} string without ansi
 */
var stripAnsi = function stripAnsi(string) {
  if (typeof string !== "string") {
    throw new TypeError("Expected a `string`, got `".concat(_typeof(string), "`"));
  }
  return string.replace(ansiRegex, "");
};
var onSocketMessage = {
  hot: function hot() {
    if (parsedResourceQuery.hot === "false") {
      return;
    }
    options.hot = true;
  },
  liveReload: function liveReload() {
    if (parsedResourceQuery["live-reload"] === "false") {
      return;
    }
    options.liveReload = true;
  },
  invalid: function invalid() {
```

```
  _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("App updated. Recompiling...");

  // Fixes #1042. overlay doesn't clear if errors are fixed but warnings remain.
  if (options.overlay) {
    overlay.send({
      type: "DISMISS"
    });
  }
  (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Invalid");
},
/**
 * @param {string} hash hash
 */
hash: function hash(_hash) {
  status.previousHash = status.currentHash;
  status.currentHash = _hash;
},
logging: setAllLogLevel,
/**
 * @param {boolean} value overlay value
 */
overlay: function overlay(value) {
  if (typeof document === "undefined") {
    return;
  }
  options.overlay = value;
  decodeOverlayOptions(options.overlay);
},
/**
 * @param {number} value reconnect value
 */
reconnect: function reconnect(value) {
  if (parsedResourceQuery.reconnect === "false") {
    return;
  }
  options.reconnect = value;
},
/**
 * @param {boolean} value progress value
 */
progress: function progress(value) {
  options.progress = value;
},
/**
 * @param {{ pluginName?: string, percent: string, msg: string }} data date with progress
 */
"progress-update": function progressUpdate(data) {
  if (options.progress) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("".concat(data.pluginName ?
```

```
"[".concat(data.pluginName, "] ") : "").concat(data.percent, "% - ").concat(data.msg, "."));
    }
    if ((0,_progress_js__WEBPACK_IMPORTED_MODULE_3__.isProgressSupported)() && typeof
options.progress === "string") {
      var progress = document.querySelector("wds-progress");
      if (!progress) {
        (0,_progress_js__WEBPACK_IMPORTED_MODULE_3__.defineProgressElement)();
        progress = document.createElement("wds-progress");
        document.body.appendChild(progress);
      }
      progress.setAttribute("progress", data.percent);
      progress.setAttribute("type", options.progress);
    }
    (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Progress", data);
  },
  "still-ok": function stillOk() {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("Nothing changed.");
    if (options.overlay) {
      overlay.send({
        type: "DISMISS"
      });
    }
    (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("StillOk");
  },
  ok: function ok() {
    (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Ok");
    if (options.overlay) {
      overlay.send({
        type: "DISMISS"
      });
    }
    reloadApp(options, status);
  },
  /**
   * @param {string} file changed file
   */
  "static-changed": function staticChanged(file) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("".concat(file ? "\"".concat(file,
"\"") : "Content", " from static directory was changed. Reloading..."));
    self.location.reload();
  },
  /**
   * @param {Error[]} warnings warnings
   * @param {{ preventReloading: boolean }=} params extra params
   */
  warnings: function warnings(_warnings, params) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.warn("Warnings while compiling.");
    var printableWarnings = _warnings.map(function (error) {
      var _formatProblem = (0,_overlay_js__WEBPACK_IMPORTED_MODULE_2__.formatProblem)
```

```
("warning", error),
      header = _formatProblem.header,
      body = _formatProblem.body;
    return "".concat(header, "\n").concat(stripAnsi(body));
  });
  (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Warnings",
printableWarnings);
  for (var i = 0; i < printableWarnings.length; i++) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.warn(printableWarnings[i]);

  }
  var overlayWarningsSetting = typeof options.overlay === "boolean" ? options.overlay :
options.overlay && options.overlay.warnings;
  if (overlayWarningsSetting) {
    var warningsToDisplay = typeof overlayWarningsSetting === "function" ?
_warnings.filter(overlayWarningsSetting) : _warnings;
    if (warningsToDisplay.length) {
      overlay.send({
        type: "BUILD_ERROR",
        level: "warning",
        messages: _warnings
      });
    }
  }
  if (params && params.preventReloading) {
    return;
  }
  reloadApp(options, status);
 },
 /**
  * @param {Error[]} errors errors
  */
 errors: function errors(_errors) {
  _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.error("Errors while compiling. Reload
prevented.");
  var printableErrors = _errors.map(function (error) {
    var _formatProblem2 =
(0,_overlay_js__WEBPACK_IMPORTED_MODULE_2__.formatProblem)("error", error),
      header = _formatProblem2.header,
      body = _formatProblem2.body;
    return "".concat(header, "\n").concat(stripAnsi(body));
  });
  (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Errors",
printableErrors);
  for (var i = 0; i < printableErrors.length; i++) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.error(printableErrors[i]);
  }
  var overlayErrorsSettings = typeof options.overlay === "boolean" ? options.overlay :
options.overlay && options.overlay.errors;
```

```
    if (overlayErrorsSettings) {
      var errorsToDisplay = typeof overlayErrorsSettings === "function" ?
_errors.filter(overlayErrorsSettings) : _errors;
      if (errorsToDisplay.length) {
        overlay.send({
          type: "BUILD_ERROR",
          level: "error",
          messages: _errors
        });
      }
    }
  },
  /**
   * @param {Error} error error
   */
  error: function error(_error) {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.error(_error);
  },
  close: function close() {
    _utils_log_js__WEBPACK_IMPORTED_MODULE_5__.log.info("Disconnected!");
    if (options.overlay) {
      overlay.send({
        type: "DISMISS"
      });
    }
    (0,_utils_sendMessage_js__WEBPACK_IMPORTED_MODULE_6__["default"])("Close");
  }
};

/**
 * @param {{ protocol?: string, auth?: string, hostname?: string, port?: string, pathname?: string,
search?: string, hash?: string, slashes?: boolean }} objURL object URL
 * @returns {string} formatted url
 */
var formatURL = function formatURL(objURL) {
  var protocol = objURL.protocol || "";
  if (protocol && protocol.slice(-1) !== ":") {
    protocol += ":";
  }
  var auth = objURL.auth || "";
  if (auth) {
    auth = encodeURIComponent(auth);
    auth = auth.replace(/%3A/i, ":");
    auth += "@";
  }
  var host = "";
  if (objURL.hostname) {
    host = auth + (objURL.hostname.indexOf(":") === -1 ? objURL.hostname :
"[".concat(objURL.hostname, "]"));
```

```
    if (objURL.port) {
      host += ":".concat(objURL.port);
    }
  }
  var pathname = objURL.pathname || "";
  if (objURL.slashes) {
    host = "//".concat(host || "");
    if (pathname && pathname.charAt(0) !== "/") {
      pathname = "/".concat(pathname);
    }
  } else if (!host) {
    host = "";
  }
  var search = objURL.search || "";
  if (search && search.charAt(0) !== "?") {
    search = "?".concat(search);
  }
  var hash = objURL.hash || "";
  if (hash && hash.charAt(0) !== "#") {
    hash = "#".concat(hash);
  }
  pathname = pathname.replace(/[?#]/g,
  /**
   * @param {string} match matched string
   * @returns {string} encoded URI component
   */
  function (match) {
    return encodeURIComponent(match);
  });
  search = search.replace("#", "%23");
  return "".concat(protocol).concat(host).concat(pathname).concat(search).concat(hash);
};

/**
 * @param {ParsedURL} parsedURL parsed URL
 * @returns {string} socket URL
 */
var createSocketURL = function createSocketURL(parsedURL) {
  var hostname = parsedURL.hostname;

  // Node.js module parses it as `::`
  // `new URL(urlString, [baseURLString])` parses it as '[::]'
  var isInAddrAny = hostname === "0.0.0.0" || hostname === "::" || hostname === "[::]";

  // why do we need this check?
  // hostname n/a for file protocol (example, when using electron, ionic)
  // see: https://github.com/webpack/webpack-dev-server/pull/384
  if (isInAddrAny && self.location.hostname && self.location.protocol.indexOf("http") === 0) {
    hostname = self.location.hostname;
```

```
  }
  var socketURLProtocol = parsedURL.protocol || self.location.protocol;

  // When https is used in the app, secure web sockets are always necessary because the browser doesn't
accept non-secure web sockets.
  if (socketURLProtocol === "auto:" || hostname && isInAddrAny && self.location.protocol ===
"https:") {
    socketURLProtocol = self.location.protocol;
  }
  socketURLProtocol = socketURLProtocol.replace(/^(?:http|.+-extension|file)/i, "ws");
  var socketURLAuth = "";

  // `new URL(urlString, [baseURLstring])` doesn't have `auth` property
  // Parse authentication credentials in case we need them
  if (parsedURL.username) {
    socketURLAuth = parsedURL.username;

    // Since HTTP basic authentication does not allow empty username,
    // we only include password if the username is not empty.
    if (parsedURL.password) {
      // Result: <username>:<password>
      socketURLAuth = socketURLAuth.concat(":", parsedURL.password);
    }
  }

  // In case the host is a raw IPv6 address, it can be enclosed in
  // the brackets as the brackets are needed in the final URL string.
  // Need to remove those as url.format blindly adds its own set of brackets
  // if the host string contains colons. That would lead to non-working
  // double brackets (e.g. [[::]]) host
  //
  // All of these web socket url params are optionally passed in through resourceQuery,
  // so we need to fall back to the default if they are not provided
  var socketURLHostname = (hostname || self.location.hostname || "localhost").replace(/^\[(.*)\]$/,
"$1");
  var socketURLPort = parsedURL.port;
  if (!socketURLPort || socketURLPort === "0") {
    socketURLPort = self.location.port;
  }

  // If path is provided it'll be passed in via the resourceQuery as a
  // query param so it has to be parsed out of the querystring in order for the
  // client to open the socket to the correct location.
  var socketURLPathname = "/ws";
  if (parsedURL.pathname && !parsedURL.fromCurrentScript) {
    socketURLPathname = parsedURL.pathname;
  }
  return formatURL({
    protocol: socketURLProtocol,
```

```
    auth: socketURLAuth,
    hostname: socketURLHostname,
    port: socketURLPort,
    pathname: socketURLPathname,
    slashes: true
  });
};
var socketURL = createSocketURL(parsedResourceQuery);
(0,_socket_js__WEBPACK_IMPORTED_MODULE_4__["default"])(socketURL, onSocketMessage,
options.reconnect);


/***/ },

/***/ "./node_modules/webpack-dev-server/client/modules/logger/index.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/modules/logger/index.js ***!
  \*****************************************************************************/
(__unused_webpack_module, exports) {

/******/(function () {
  // webpackBootstrap
  /******/
  "use strict";

  /******/
  var __webpack_modules__ = {
    /***/"./client-src/modules/logger/tapable.js": (
    /*!*********************************************!*\
      !*** ./client-src/modules/logger/tapable.js ***!
      \*********************************************/
    /***/
    function (__unused_webpack_module, __nested_webpack_exports__,
__nested_webpack_require_404__) {
      __nested_webpack_require_404__.r(__nested_webpack_exports__);
      /* harmony export */
      __nested_webpack_require_404__.d(__nested_webpack_exports__, {
        /* harmony export */SyncBailHook: function () {
          return /* binding */SyncBailHook;
        }
        /* harmony export */
      });
      /**
       * @returns {SyncBailHook} mocked sync bail hook
       * @constructor
       */
      function SyncBailHook() {
        return {
          call: function call() {}
```

```
      };
    }

    /**
     * Client stub for tapable SyncBailHook
     */

    /***/
  }),
  /***/"./node_modules/webpack/lib/logging/Logger.js": (
  /*!*****************************************************!*\
    !*** ./node_modules/webpack/lib/logging/Logger.js ***!
    \*****************************************************/
  /***/
  function (module) {
    /*
        MIT License http://www.opensource.org/licenses/mit-license.php
        Author Tobias Koppers @sokra
    */

    function _typeof(o) {
      "@babel/helpers - typeof";

      return _typeof = "function" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }) && "symbol" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }).iterator ? function (o) {
        return typeof o;
      } : function (o) {
        return o && "function" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }) && o.constructor === (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }) && o !== (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }).prototype ? "symbol" : typeof o;
      }, _typeof(o);
    }
    function _toConsumableArray(r) {
      return _arrayWithoutHoles(r) || _iterableToArray(r) || _unsupportedIterableToArray(r) ||
_nonIterableSpread();
    }
    function _nonIterableSpread() {
      throw new TypeError("Invalid attempt to spread non-iterable instance.\nIn order to be iterable,
non-array objects must have a [Symbol.iterator]() method.");
    }
    function _unsupportedIterableToArray(r, a) {
      if (r) {
```

```
        if ("string" == typeof r) return
 _arrayLikeToArray(r, a);
        var t = {}.toString.call(r).slice(8, -1);
        return "Object" === t && r.constructor && (t = r.constructor.name), "Map" === t || "Set" === t ?
Array.from(r) : "Arguments" === t || /^(?:Ui|I)nt(?:8|16|32)(?:Clamped)?Array$/.test(t) ?
_arrayLikeToArray(r, a) : void 0;
       }
      }
      function _iterableToArray(r) {
       if ("undefined" != typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
       }) && null != r[(typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
       }).iterator] || null != r["@@iterator"]) return Array.from(r);
      }
      function _arrayWithoutHoles(r) {
       if (Array.isArray(r)) return _arrayLikeToArray(r);
      }
      function _arrayLikeToArray(r, a) {
       (null == a || a > r.length) && (a = r.length);
       for (var e = 0, n = Array(a); e < a; e++) n[e] = r[e];
       return n;
      }
      function _classCallCheck(a, n) {
       if (!(a instanceof n)) throw new TypeError("Cannot call a class as a function");
      }
      function _defineProperties(e, r) {
       for (var t = 0; t < r.length; t++) {
        var o = r[t];
        o.enumerable = o.enumerable || !1, o.configurable = !0, "value" in o && (o.writable = !0),
Object.defineProperty(e, _toPropertyKey(o.key), o);
       }
      }
      function _createClass(e, r, t) {
       return r && _defineProperties(e.prototype, r), t && _defineProperties(e, t),
Object.defineProperty(e, "prototype", {
        writable: !1
       }), e;
      }
      function _toPropertyKey(t) {
       var i = _toPrimitive(t, "string");
       return "symbol" == _typeof(i) ? i : i + "";
      }
      function _toPrimitive(t, r) {
       if ("object" != _typeof(t) || !t) return t;
       var e = t[(typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
       }).toPrimitive];
       if (void 0 !== e) {
```

```
    var i = e.call(t, r || "default");
    if ("object" != _typeof(i)) return i;
    throw new TypeError("@@toPrimitive must return a primitive value.");
  }
  return ("string" === r ? String : Number)(t);
}
var LogType = Object.freeze({
  error: (/** @type {"error"} */"error"),
  // message, c style arguments
  warn: (/** @type {"warn"} */"warn"),
  // message, c style arguments
  info: (/** @type {"info"} */"info"),
  // message, c style arguments
  log: (/** @type {"log"} */"log"),
  // message, c style arguments
  debug: (/** @type {"debug"} */"debug"),
  // message, c style arguments

  trace: (/** @type {"trace"} */"trace"),
  // no arguments

  group: (/** @type {"group"} */"group"),
  // [label]
  groupCollapsed: (/** @type {"groupCollapsed"} */"groupCollapsed"),
  // [label]
  groupEnd: (/** @type {"groupEnd"} */"groupEnd"),
  // [label]

  profile: (/** @type {"profile"} */"profile"),
  // [profileName]
  profileEnd: (/** @type {"profileEnd"} */"profileEnd"),
  // [profileName]

  time: (/** @type {"time"} */"time"),
  // name, time as [seconds, nanoseconds]

  clear: (/** @type {"clear"} */"clear"),
  // no arguments
  status: (/** @type {"status"} */"status") // message, arguments
});
module.exports.LogType = LogType;

/** @typedef {typeof LogType[keyof typeof LogType]} LogTypeEnum */
/** @typedef {Map<string | undefined, [number, number]>} TimersMap */

var LOG_SYMBOL = (typeof Symbol !== "undefined" ? Symbol : function (i) {
  return i;
})("webpack logger raw log method");
var TIMERS_SYMBOL = (typeof Symbol !== "undefined" ? Symbol : function (i) {
```

```
  return i;
 })("webpack logger times");
 var TIMERS_AGGREGATES_SYMBOL = (typeof Symbol !== "undefined" ? Symbol : function
(i) {
  return i;
 })("webpack logger aggregated times");

 /** @typedef {EXPECTED_ANY[]} Args */
 /** @typedef {(type: LogTypeEnum, args?: Args) => void} LogFn */
 /** @typedef {(name: string | (() => string)) => WebpackLogger} GetChildLogger */
 var WebpackLogger = /*#__PURE__*/function () {
  /**
   * Creates an instance of WebpackLogger.
   * @param {LogFn} log log function
   * @param {GetChildLogger} getChildLogger function to create child logger
   */
  function WebpackLogger(log, getChildLogger) {
   _classCallCheck(this, WebpackLogger);
   /** @type {LogFn} */
   this[LOG_SYMBOL] = log;
   /** @type {GetChildLogger} */
   this.getChildLogger = getChildLogger;
  }

  /**
   * Processes the provided arg.
   * @param {Args} args args
   */
  return _createClass(WebpackLogger, [{
   key: "error",
   value: function error() {
    for (var _len = arguments.length, args = new Array(_len), _key = 0; _key < _len; _key++) {
     args[_key] = arguments[_key];
    }
    this[LOG_SYMBOL](LogType.error, args);
   }

   /**
    * Processes the provided arg.
    * @param {Args} args args
    */
  }, {
   key: "warn",
   value: function warn() {
    for (var _len2 = arguments.length, args = new Array(_len2), _key2 = 0; _key2 < _len2; _key2+
+) {
     args[_key2] = arguments[_key2];
    }
    this[LOG_SYMBOL](LogType.warn, args);
```

```
      }

      /**
       * Processes the provided arg.
       * @param {Args} args args
       */
    }, {
      key: "info",
      value: function info() {
        for (var _len3 = arguments.length, args = new Array(_len3), _key3 = 0; _key3 < _len3; _key3+
+) {
          args[_key3] = arguments[_key3];
        }
        this[LOG_SYMBOL](LogType.info, args);
      }

      /**
       * Processes the provided arg.
       * @param {Args} args args
       */
    }, {
      key: "log",
      value: function log() {
        for (var _len4 = arguments.length, args = new Array(_len4), _key4 = 0; _key4 < _len4; _key4+
+) {
          args[_key4] = arguments[_key4];
        }
        this[LOG_SYMBOL](LogType.log, args);
      }

      /**
       * Processes the provided arg.
       * @param {Args} args args
       */
    }, {
      key: "debug",
      value: function debug() {
        for (var _len5 = arguments.length, args = new Array(_len5), _key5 = 0; _key5 < _len5; _key5+
+) {
          args[_key5] = arguments[_key5];
        }
        this[LOG_SYMBOL](LogType.debug, args);
      }

      /**
       * Processes the provided condition.
       * @param {boolean=} condition condition
       * @param {Args} args args
       */
```

```
    }, {
      key: "assert",
      value: function assert(condition) {
        if (!condition) {
          for (var _len6 = arguments.length, args = new Array(_len6 > 1 ? _len6 - 1 : 0), _key6 = 1;
_key6 < _len6; _key6++) {
            args[_key6 - 1] = arguments[_key6];
          }
          this[LOG_SYMBOL](LogType.error, args);
        }
      }
    }, {
      key: "trace",
      value: function trace() {
        this[LOG_SYMBOL](LogType.trace, ["Trace"]);
      }
    }, {
      key: "clear",
      value: function clear() {
        this[LOG_SYMBOL](LogType.clear);
      }

      /**
       * Processes the provided arg.
       * @param {Args} args args
       */
    }, {
      key: "status",
      value: function status() {
        for (var _len7 = arguments.length, args = new Array(_len7), _key7 = 0; _key7 < _len7; _key7+
+) {
          args[_key7] = arguments[_key7];
        }
        this[LOG_SYMBOL](LogType.status, args);
      }

      /**
       * Processes the provided arg.
       * @param {Args} args args
       */
    }, {
      key: "group",
      value: function group() {
        for (var _len8 = arguments.length, args = new Array(_len8), _key8 = 0; _key8 < _len8; _key8+
+) {
          args[_key8] = arguments[_key8];
        }
        this[LOG_SYMBOL](LogType.group, args);
      }
```

```
        /**
         * Processes the provided arg.
         * @param {Args} args args
         */
        }, {
         key: "groupCollapsed",
         value: function groupCollapsed() {
          for (var _len9 = arguments.length, args = new Array(_len9), _key9 = 0; _key9 < _len9; _key9+
+) {
           args[_key9] = arguments[_key9];
          }
          this[LOG_SYMBOL](LogType.groupCollapsed, args);
         }
        }, {
         key: "groupEnd",
         value: function groupEnd() {
          this[LOG_SYMBOL](LogType.groupEnd);
         }

         /**
          * Processes the provided label.
          * @param {string=} label label
          */
        }, {
         key: "profile",
         value: function profile(label) {
          this[LOG_SYMBOL](LogType.profile, [label]);
         }

         /**
          * Processes the provided label.
          * @param {string=} label label
          */
        }, {
         key: "profileEnd",
         value: function profileEnd(label) {
          this[LOG_SYMBOL](LogType.profileEnd, [label]);
         }

         /**
          * Processes the provided label.
          * @param {string} label label
          */
        }, {
         key: "time",
         value: function time(label) {
          /** @type {TimersMap} */
          this[TIMERS_SYMBOL] = this[TIMERS_SYMBOL] || new Map();
```

```
    this[TIMERS_SYMBOL].set(label, process.hrtime());

  }

  /**
   * Processes the provided label.
   * @param {string=} label label
   */
}, {
  key: "timeLog",
  value: function timeLog(label) {
    var prev = this[TIMERS_SYMBOL] && this[TIMERS_SYMBOL].get(label);
    if (!prev) {
      throw new Error("No such label '".concat(label, "' for WebpackLogger.timeLog()"));
    }
    var time = process.hrtime(prev);
    this[LOG_SYMBOL](LogType.time, [label].concat(_toConsumableArray(time)));
  }

  /**
   * Processes the provided label.
   * @param {string=} label label
   */
}, {
  key: "timeEnd",
  value: function timeEnd(label) {
    var prev = this[TIMERS_SYMBOL] && this[TIMERS_SYMBOL].get(label);
    if (!prev) {
      throw new Error("No such label '".concat(label, "' for WebpackLogger.timeEnd()"));
    }
    var time = process.hrtime(prev);
    /** @type {TimersMap} */
    this[TIMERS_SYMBOL].delete(label);
    this[LOG_SYMBOL](LogType.time, [label].concat(_toConsumableArray(time)));
  }

  /**
   * Processes the provided label.
   * @param {string=} label label
   */
}, {
  key: "timeAggregate",
  value: function timeAggregate(label) {
    var prev = this[TIMERS_SYMBOL] && this[TIMERS_SYMBOL].get(label);
    if (!prev) {
      throw new Error("No such label '".concat(label, "' for WebpackLogger.timeAggregate()"));
    }
    var time = process.hrtime(prev);
    /** @type {TimersMap} */
```

```
        this[TIMERS_SYMBOL].delete(label);
        /** @type {TimersMap} */
        this[TIMERS_AGGREGATES_SYMBOL] = this[TIMERS_AGGREGATES_SYMBOL] ||
new Map();
        var current = this[TIMERS_AGGREGATES_SYMBOL].get(label);
        if (current !== undefined) {
          if (time[1] + current[1] > 1e9) {
            time[0] += current[0] + 1;
            time[1] = time[1] - 1e9 + current[1];
          } else {
            time[0] += current[0];
            time[1] += current[1];
          }
        }
        this[TIMERS_AGGREGATES_SYMBOL].set(label, time);
      }

      /**
       * Time aggregate end.
       * @param {string=} label label
       */
    }, {
      key: "timeAggregateEnd",
      value: function timeAggregateEnd(label) {
        if (this[TIMERS_AGGREGATES_SYMBOL] === undefined) return;
        var time = this[TIMERS_AGGREGATES_SYMBOL].get(label);
        if (time === undefined) return;
        this[TIMERS_AGGREGATES_SYMBOL].delete(label);
        this[LOG_SYMBOL](LogType.time, [label].concat(_toConsumableArray(time)));
      }
    }]);
  }();
  module.exports.Logger = WebpackLogger;

  /***/
},
/***/"./node_modules/webpack/lib/logging/createConsoleLogger.js": (
/*!*****************************************************************!*\
  !*** ./node_modules/webpack/lib/logging/createConsoleLogger.js ***!
  \*****************************************************************/
/***/
function (module, __unused_webpack_exports, __nested_webpack_require_15919__) {
  /*
      MIT License http://www.opensource.org/licenses/mit-license.php
      Author Tobias Koppers @sokra
  */

  function _slicedToArray(r, e) {
    return _arrayWithHoles(r) || _iterableToArrayLimit(r, e) || _unsupportedIterableToArray(r, e) ||
```

```
_nonIterableRest();
    }
    function _nonIterableRest() {
      throw new TypeError("Invalid attempt to destructure non-iterable instance.\nIn order to be
iterable, non-array objects must have a [Symbol.iterator]() method.");
    }
    function _iterableToArrayLimit(r, l) {
      var t = null == r ? null : "undefined" != typeof (typeof Symbol !== "undefined" ? Symbol :
function (i) {
        return i;
      }) && r[(typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }).iterator] || r["@@iterator"];
      if (null != t) {
        var e,
          n,
          i,
          u,
          a = [],
          f = !0,
          o = !1;
        try {
          if (i = (t = t.call(r)).next, 0 === l) {
            if (Object(t) !== t) return;
            f = !1;
          } else for (; !(f = (e = i.call(t)).done) && (a.push(e.value), a.length !== l); f = !0);
        } catch (r) {
          o = !0, n = r;
        } finally {
          try {
            if (!f && null != t.return && (u = t.return(), Object(u) !== u)) return;
          } finally {
            if (o) throw n;
          }
        }
        return a;
      }
    }
    function _arrayWithHoles(r) {
      if (Array.isArray(r)) return r;
    }
    function _toConsumableArray(r) {
      return _arrayWithoutHoles(r) || _iterableToArray(r) || _unsupportedIterableToArray(r) ||
_nonIterableSpread();
    }
    function _nonIterableSpread() {
      throw new TypeError("Invalid attempt to spread non-iterable instance.\nIn order to be iterable,
non-array objects must have a [Symbol.iterator]() method.");
    }
```

```
    function _unsupportedIterableToArray(r, a) {
      if (r) {
        if ("string" == typeof r) return _arrayLikeToArray(r, a);
        var t = {}.toString.call(r).slice(8, -1);
        return "Object" === t && r.constructor && (t = r.constructor.name), "Map" === t || "Set" === t ?
Array.from(r) : "Arguments" === t || /^(?:Ui|I)nt(?:8|16|32)(?:Clamped)?Array$/.test(t) ?
_arrayLikeToArray(r, a) : void 0;
      }
    }
    function _iterableToArray(r) {
      if ("undefined" != typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }) && null != r[(typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }).iterator] || null != r["@@iterator"]) return Array.from(r);
    }
    function _arrayWithoutHoles(r) {
      if (Array.isArray(r)) return _arrayLikeToArray(r);
    }
    function _arrayLikeToArray(r, a) {
      (null == a || a > r.length) && (a = r.length);
      for (var e = 0, n = Array(a); e < a; e++) n[e] = r[e];
      return n;
    }
    function _typeof(o) {
      "@babel/helpers - typeof";

      return _typeof = "function" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }) && "symbol" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
        return i;
      }).iterator ? function (o) {
        return typeof o;
      } : function (o) {
        return o && "function" == typeof (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }) && o.constructor === (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }) && o !== (typeof Symbol !== "undefined" ? Symbol : function (i) {
          return i;
        }).prototype ? "symbol" : typeof o;
      }, _typeof(o);
    }
    var _require = __nested_webpack_require_15919__(/*! ./Logger
*/"./node_modules/webpack/lib/logging/Logger.js"),
      LogType = _require.LogType;

    /** @typedef {import("../../declarations/WebpackOptions").FilterItemTypes} FilterItemTypes */
    /** @typedef {import("../../declarations/WebpackOptions").FilterTypes} FilterTypes */
```

```
    /** @typedef {import("./Logger").LogTypeEnum} LogTypeEnum */
    /** @typedef {import("./Logger").Args} Args */

    /** @typedef {(item: string) => boolean} FilterFunction */
    /** @typedef {(value: string, type: LogTypeEnum, args?: Args) => void} LoggingFunction */

    /**
     * Defines the logger console type used by this module.
     * @typedef {object} LoggerConsole
     * @property {() => void} clear
     * @property {() => void} trace
     * @property {(...args: Args) => void} info
     * @property {(...args: Args) => void} log
     * @property {(...args: Args) => void} warn
     * @property {(...args: Args) => void} error
     * @property {(...args: Args) => void=} debug
     * @property {(...args: Args) => void=} group
     * @property {(...args: Args) => void=} groupCollapsed
     * @property {(...args: Args) => void=} groupEnd
     * @property {(...args: Args) => void=} status
     * @property {(...args: Args) => void=} profile
     * @property {(...args: Args) => void=} profileEnd
     * @property {(...args: Args) => void=} logTime
     */

    /**
     * Defines the logger options type used by this module.
     * @typedef {object} LoggerOptions
     * @property {false | true | "none" | "error" | "warn" | "info" | "log" | "verbose"} level loglevel
     * @property {FilterTypes | boolean} debug filter for debug logging
     * @property {LoggerConsole} console the console to log to
     */

    /**
     * Filter to function.
     * @param {FilterItemTypes} item an input item
     * @returns {FilterFunction | undefined} filter function
     */
    var filterToFunction = function filterToFunction(item) {
      if (typeof item === "string") {
        var regExp = new RegExp("[\\\\/]".concat(item.replace(/[-[\]{}()*+?.\\^$|]/g, "\\$&"), "([\\\\/]|
$|!|\\?)"));
        return function (ident) {
          return regExp.test(ident);
        };
      }
      if (item && _typeof(item) === "object" && typeof item.test === "function") {
        return function (ident) {
          return item.test(ident);
```

```
      };
    }
    if (typeof item === "function") {
      return item;
    }
    if (typeof item === "boolean") {
      return function () {
        return item;
      };
    }
  };

  /**

   * Enumerates the available values.
   * @enum {number}
   */
  var LogLevel = {
    none: 6,
    false: 6,
    error: 5,
    warn: 4,
    info: 3,
    log: 2,
    true: 2,
    verbose: 1
  };

  /**
   * Returns logging function.
   * @param {LoggerOptions} options options object
   * @returns {LoggingFunction} logging function
   */
  module.exports = function (_ref) {
    var _ref$level = _ref.level,
      level = _ref$level === void 0 ? "info" : _ref$level,
      _ref$debug = _ref.debug,
      debug = _ref$debug === void 0 ? false : _ref$debug,
      console = _ref.console;
    var debugFilters = /** @type {FilterFunction[]} */

    typeof debug === "boolean" ? [function () {
      return debug;
    }] : /** @type {FilterItemTypes[]} */_toConsumableArray(Array.isArray(debug) ? debug :
[debug]).map(filterToFunction);
    var loglevel = LogLevel[""].concat(level)] || 0;

    /**
     * Processes the provided name.
```

```
 * @param {string} name name of the logger
 * @param {LogTypeEnum} type type of the log entry
 * @param {Args=} args arguments of the log entry
 * @returns {void}
 */
var logger = function logger(name, type, args) {
  /**
   * Returns labeled args.
   * @template T
   * @returns {[string?, ...T[]]} labeled args
   */
  var labeledArgs = function labeledArgs() {
    if (Array.isArray(args)) {
      if (args.length > 0 && typeof args[0] === "string") {
        return ["[".concat(name, "] ").concat(args[0])].concat(_toConsumableArray(args.slice(1)));
      }
      return ["[".concat(name, "]")].concat(_toConsumableArray(args));
    }
    return [];
  };
  var debug = debugFilters.some(function (f) {
    return f(name);
  });
  switch (type) {
    case LogType.debug:
      if (!debug) return;
      if (typeof console.debug === "function") {
        console.debug.apply(console, _toConsumableArray(labeledArgs()));
      } else {
        console.log.apply(console, _toConsumableArray(labeledArgs()));
      }
      break;
    case LogType.log:
      if (!debug && loglevel > LogLevel.log) return;
      console.log.apply(console, _toConsumableArray(labeledArgs()));
      break;
    case LogType.info:
      if (!debug && loglevel > LogLevel.info) return;
      console.info.apply(console, _toConsumableArray(labeledArgs()));
      break;
    case LogType.warn:
      if (!debug && loglevel > LogLevel.warn) return;
      console.warn.apply(console, _toConsumableArray(labeledArgs()));
      break;
    case LogType.error:
      if (!debug && loglevel > LogLevel.error) return;
      console.error.apply(console, _toConsumableArray(labeledArgs()));
      break;
    case LogType.trace:
```

```
  if (!debug) return;
  console.trace();
  break;
 case LogType.groupCollapsed:
  if (!debug && loglevel > LogLevel.log) return;
  if (!debug && loglevel > LogLevel.verbose) {
   if (typeof console.groupCollapsed === "function") {
    console.groupCollapsed.apply(console, _toConsumableArray(labeledArgs()));
   } else {
    console.log.apply(console, _toConsumableArray(labeledArgs()));
   }
   break;
  }
 // falls through
 case LogType.group:
  if (!debug && loglevel > LogLevel.log) return;
  if (typeof console.group === "function") {
   console.group.apply(console, _toConsumableArray(labeledArgs()));
  } else {
   console.log.apply(console, _toConsumableArray(labeledArgs()));
  }
  break;
 case LogType.groupEnd:
  if (!debug && loglevel > LogLevel.log) return;
  if (typeof console.groupEnd === "function") {
   console.groupEnd();
  }
  break;
 case LogType.time:
  {
   if (!debug && loglevel > LogLevel.log) return;
   var _args = _slicedToArray(/** @type {[string, number, number]} */
    args, 3),
    label = _args[0],
    start = _args[1],
    end = _args[2];
   var ms = start * 1000 + end / 1000000;
   var msg = "[".concat(name, "] ").concat(label, ": ").concat(ms, " ms");
   if (typeof console.logTime === "function") {
    console.logTime(msg);
   } else {
    console.log(msg);
   }
   break;
  }
 case LogType.profile:
  if (typeof console.profile === "function") {
   console.profile.apply(console, _toConsumableArray(labeledArgs()));
  }
```

```
        break;
      case LogType.profileEnd:
        if (typeof console.profileEnd === "function") {
          console.profileEnd.apply(console, _toConsumableArray(labeledArgs()));
        }
        break;
      case LogType.clear:
        if (!debug && loglevel > LogLevel.log) return;
        if (typeof console.clear === "function") {
          console.clear();
        }
        break;
      case LogType.status:
        if (!debug && loglevel > LogLevel.info) return;
        if (typeof console.status === "function") {
          if (!args || args.length === 0) {
            console.status();
          } else {
            console.status.apply(console, _toConsumableArray(labeledArgs()));
          }
        } else if (args && args.length !== 0) {
          console.info.apply(console, _toConsumableArray(labeledArgs()));
        }
        break;
      default:
        throw new Error("Unexpected LogType ".concat(type));
    }
  };
  return logger;
};

/***/
}),
/***/"./node_modules/webpack/lib/logging/runtime.js": (
/*!*****************************************************!*\
  !*** ./node_modules/webpack/lib/logging/runtime.js ***!
  \*****************************************************/
function (module, __unused_webpack_exports, __nested_webpack_require_29156__) {
  /*
      MIT License http://www.opensource.org/licenses/mit-license.php
      Author Tobias Koppers @sokra
  */

  function _extends() {
    return _extends = Object.assign ? Object.assign.bind() : function (n) {
      for (var e = 1; e < arguments.length; e++) {
        var t = arguments[e];
        for (var r in t) ({}).hasOwnProperty.call(t, r) && (n[r] = t[r]);
```

```
        }
        return n;
      }, _extends.apply(null, arguments);
    }
    var _require = __nested_webpack_require_29156__(/*! tapable */"./client-
src/modules/logger/tapable.js"),
      SyncBailHook = _require.SyncBailHook;
    var _require2 = __nested_webpack_require_29156__(/*! ./Logger
*/"./node_modules/webpack/lib/logging/Logger.js"),
      Logger = _require2.Logger;
    var createConsoleLogger = __nested_webpack_require_29156__(/*! ./createConsoleLogger
*/"./node_modules/webpack/lib/logging/createConsoleLogger.js");

    /** @type {createConsoleLogger.LoggerOptions} */
    var currentDefaultLoggerOptions = {
      level: "info",
      debug: false,
      console: console
    };
    var currentDefaultLogger = createConsoleLogger(currentDefaultLoggerOptions);

    /**
     * Processes the provided create console logger.logger option.
     * @param {createConsoleLogger.LoggerOptions} options new options, merge with old options
     * @returns {void}
     */
    module.exports.configureDefaultLogger = function (options) {
      _extends(currentDefaultLoggerOptions, options);
      currentDefaultLogger = createConsoleLogger(currentDefaultLoggerOptions);
    };

    /**
     * Returns a logger.
     * @param {string} name name of the logger
     * @returns {Logger} a logger
     */
    module.exports.getLogger = function (name) {
      return new Logger(function (type, args) {
        if (module.exports.hooks.log.call(name, type, args) === undefined) {
          currentDefaultLogger(name, type, args);
        }
      }, function (childName) {
        return module.exports.getLogger("".concat(name, "/").concat(childName));
      });
    };
    module.exports.hooks = {
      log: new SyncBailHook(["origin", "type", "args"])
    };
```

```
    /***/
  })

  /******/
};
/************************************************************************/
/******/ // The module cache
/******/
var __webpack_module_cache__ = {};
/******/
/******/ // The require function
/******/
function __nested_webpack_require_31641__(moduleId) {
  /******/ // Check if module is in cache
  /******/var cachedModule = __webpack_module_cache__[moduleId];
  /******/
  if (cachedModule !== undefined) {
    /******/return cachedModule.exports;
    /******/
  }
  /******/ // Create a new module (and put it into the cache)
  /******/
  var module = __webpack_module_cache__[moduleId] = {
    /******/ // no module.id needed
    /******/ // no module.loaded needed
    /******/exports: {}
    /******/
  };
  /******/
  /******/ // Execute the module function
  /******/
  if (!(moduleId in __webpack_modules__)) {
    /******/delete
__webpack_module_cache__[moduleId];
    /******/
    var e = new Error("Cannot find module '" + moduleId + "'");
    /******/
    e.code = 'MODULE_NOT_FOUND';
    /******/
    throw e;
    /******/
  }
  /******/
  __webpack_modules__[moduleId](module, module.exports, __nested_webpack_require_31641__);
  /******/
  /******/ // Return the exports of the module
  /******/
  return module.exports;
  /******/
```

```
  }
  /******/
  /************************************************************************/
  /******/ /* webpack/runtime/define property getters */
  /******/
  !function () {
    /******/ // define getter functions for harmony exports
    /******/__nested_webpack_require_31641__.d = function (exports, definition) {
      /******/for (var key in definition) {
        /******/if (__nested_webpack_require_31641__.o(definition, key) && !
__nested_webpack_require_31641__.o(exports, key)) {
          /******/Object.defineProperty(exports, key, {
            enumerable: true,
            get: definition[key]
          });
          /******/
        }
        /******/
      }
      /******/
    };
    /******/
  }();
  /******/
  /******/ /* webpack/runtime/hasOwnProperty shorthand */
  /******/
  !function () {
    /******/__nested_webpack_require_31641__.o = function (obj, prop) {
      return Object.prototype.hasOwnProperty.call(obj, prop);
    };
    /******/
  }();
  /******/
  /******/ /* webpack/runtime/make namespace object */
  /******/
  !function () {
    /******/ // define __esModule on exports
    /******/__nested_webpack_require_31641__.r = function (exports) {
      /******/if (typeof Symbol !== 'undefined' && Symbol.toStringTag) {
        /******/Object.defineProperty(exports, Symbol.toStringTag, {
          value: 'Module'
        });
        /******/
      }
      /******/
      Object.defineProperty(exports, '__esModule', {
        value: true
      });
      /******/
```

```
  };
  /******/
 })();
 /******/
 /************************************************************************/
 var __nested_webpack_exports__ = {};
 // This entry needs to be wrapped in an IIFE because it needs to be isolated against other modules in the chunk.
 !function () {
  /*!*****************************************************!*\
    !*** ./client-src/modules/logger/index.js ***!
    \*****************************************************/
  __nested_webpack_require_31641__.r(__nested_webpack_exports__);
  /* harmony export */
  __nested_webpack_require_31641__.d(__nested_webpack_exports__, {
   /* harmony export */"default": function () {
    return /* reexport default export from named module */webpack_lib_logging_runtime_js__WEBPACK_IMPORTED_MODULE_0__;
   }
   /* harmony export */
  });
  /* harmony import */
  var webpack_lib_logging_runtime_js__WEBPACK_IMPORTED_MODULE_0__ = __nested_webpack_require_31641__(/*! webpack/lib/logging/runtime.js */"./node_modules/webpack/lib/logging/runtime.js");
  // @ts-expect-error
 }();
 var __webpack_export_target__ = exports;
 for (var __webpack_i__ in __nested_webpack_exports__) __webpack_export_target__[__webpack_i__] = __nested_webpack_exports__[__webpack_i__];
 if (__nested_webpack_exports__.__esModule) Object.defineProperty(__webpack_export_target__, "__esModule", {
  value: true
 });
 /******/
})();

/***/ },

/***/ "./node_modules/webpack-dev-server/client/overlay.js"
/*!***********************************************************!*\
 !*** ./node_modules/webpack-dev-server/client/overlay.js ***!
 \***********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   createOverlay: () => (/* binding */ createOverlay),
```

```
/* harmony export */   formatProblem: () => (/* binding */ formatProblem)
/* harmony export */ });
/* harmony import */ var ansi_html_community__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ansi-html-community */ "./node_modules/ansi-html-community/index.js");
/* harmony import */ var ansi_html_community__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(ansi_html_community__WEBPACK_IMPORTED_MODUL
E_0__);
function _typeof(o) {
  "@babel/helpers - typeof";

  return _typeof = "function" == typeof Symbol && "symbol" == typeof Symbol.iterator ? function (o)
{
    return typeof o;
  } : function (o) {
    return o && "function" == typeof Symbol && o.constructor === Symbol && o !==
Symbol.prototype ? "symbol" : typeof o;
  }, _typeof(o);
}
function ownKeys(e, r) {
  var t = Object.keys(e);
  if (Object.getOwnPropertySymbols) {
    var o = Object.getOwnPropertySymbols(e);
    r && (o = o.filter(function (r) {
      return Object.getOwnPropertyDescriptor(e, r).enumerable;
    })), t.push.apply(t, o);
  }
  return t;
}
function _objectSpread(e) {
  for (var r = 1; r < arguments.length; r++) {
    var t = null != arguments[r] ? arguments[r] : {};
    r % 2 ? ownKeys(Object(t), !0).forEach(function (r) {
      _defineProperty(e, r, t[r]);
    }) : Object.getOwnPropertyDescriptors ? Object.defineProperties(e,
Object.getOwnPropertyDescriptors(t)) : ownKeys(Object(t)).forEach(function (r) {
      Object.defineProperty(e, r, Object.getOwnPropertyDescriptor(t, r));
    });
  }
  return e;
}
function _defineProperty(e, r, t) {
  return (r = _toPropertyKey(r)) in e ? Object.defineProperty(e, r, {
    value: t,
    enumerable: !0,
    configurable: !0,
    writable: !0
  }) : e[r] = t, e;
}
function _toPropertyKey(t) {
```

```
  var i = _toPrimitive(t, "string");
  return "symbol" == _typeof(i) ? i : i + "";
}
function _toPrimitive(t, r) {
  if ("object" != _typeof(t) || !t) return t;
  var e = t[Symbol.toPrimitive];
  if (void 0 !== e) {
    var i = e.call(t, r || "default");
    if ("object" != _typeof(i)) return i;
    throw new TypeError("@@toPrimitive must return a primitive value.");
  }
  return ("string" === r ? String : Number)(t);
}
// The error overlay is inspired (and mostly copied) from Create React App
(https://github.com/facebookincubator/create-react-app)
// They, in turn, got inspired by webpack-hot-middleware (https://github.com/glenjamin/webpack-hot-
middleware).



/** @typedef {import("./index").EXPECTED_ANY} EXPECTED_ANY */

/**
 * @type {(input: string, position: number) => number | undefined}
 */
// @ts-expect-error
var getCodePoint = String.prototype.codePointAt ?
// @ts-expect-error
function (input, position) {
  return input.codePointAt(position);
} : function (input, position) {
  return (input.charCodeAt(position) - 0xd800) * 0x400 + input.charCodeAt(position + 1) - 0xdc00 +
0x10000;
};

/**
 * @param {string} macroText macro text
 * @param {RegExp} macroRegExp macro reg exp
 * @param {(input: string) => string} macroReplacer macro replacer
 * @returns {string} result
 */
var replaceUsingRegExp = function replaceUsingRegExp(macroText, macroRegExp, macroReplacer)
{
  macroRegExp.lastIndex = 0;
  var replaceMatch = macroRegExp.exec(macroText);
  var replaceResult;
  if (replaceMatch) {
    replaceResult = "";
    var replaceLastIndex = 0;
```

```
    do {
      if (replaceLastIndex !== replaceMatch.index) {
        replaceResult += macroText.slice(replaceLastIndex, replaceMatch.index);
      }
      var replaceInput = replaceMatch[0];
      replaceResult += macroReplacer(replaceInput);
      replaceLastIndex = replaceMatch.index + replaceInput.length;
    } while (replaceMatch = macroRegExp.exec(macroText));
    if (replaceLastIndex !== macroText.length) {
      replaceResult += macroText.slice(replaceLastIndex);
    }
  } else {
    replaceResult = macroText;
  }
  return replaceResult;
};
var references = {
  "<": "&lt;",
  ">": "&gt;",
  "": "&quot;",
  "'": "&apos;",
  "&": "&amp;"
};

/**
 * @param {string} text text
 * @returns {string} encoded text
 */
function encode(text) {
  if (!text) {
    return "";
  }
  return replaceUsingRegExp(text, /[<>'"&]/g, function (input) {
    var result = references[(/** @type {keyof typeof references} */input)];
    if (!result) {
      var code = input.length > 1 ? getCodePoint(input, 0) : input.charCodeAt(0);
      result = "&#".concat(code, ";");
    }
    return result;
  });
}

/**
 * @typedef {object} Context
 * @property {'warning' | 'error'} level level
 * @property {(string | Message)[]} messages messages
 * @property {'build' | 'runtime'} messageSource message source
 */
```

```
/** @typedef {{ type: string } & Record<string, EXPECTED_ANY>} Event */

/**
 * @typedef {object} Options
 * @property {{ [state: string]: { on: Record<string, { target: string; actions?: Array<string> }> } }}
states states
 * @property {Context} context context
 * @property {string} initial initial
 */

/**
 * @typedef {object} Implementation
 * @property {{ [actionName: string]: (ctx: Context, event: Event) => Context | void }} actions actions
 */

/**
 * @typedef {{ send: (event: Event) => void }} StateMachine
 */

/**
 * A simplified `createMachine` from `@xstate/fsm` with the following differences:
 * - the returned machine is technically a "service". No `interpret(machine).start()` is needed.
 * - the state definition only support `on` and target must be declared with { target: 'nextState', actions:
[] } explicitly.
 * - event passed to `send` must be an object with `type` property.
 * - actions implementation will be [assign action]
(https://xstate.js.org/docs/guides/context.html#assign-action) if you return any value.
 * Do not return anything if you just want to invoke side effect.
 *
 * The goal of this custom function is to avoid installing the entire `'xstate/fsm'` package, while
enabling modeling using
 * state machine. You can copy the first parameter into the editor at https://stately.ai/viz to visualize the
state machine.
 * @param {Options} options
 options
 * @param {Implementation} implementation implementation
 * @returns {StateMachine} state machine
 */
function createMachine(_ref, _ref2) {
  var states = _ref.states,
    context = _ref.context,
    initial = _ref.initial;
  var actions = _ref2.actions;
  var currentState = initial;
  var currentContext = context;
  return {
    send: function send(event) {
      var currentStateOn = states[currentState].on;
      var transitionConfig = currentStateOn && currentStateOn[event.type];
```

```
    if (transitionConfig) {
      currentState = transitionConfig.target;
      if (transitionConfig.actions) {
        transitionConfig.actions.forEach(function (actName) {
          var actionImpl = actions[actName];
          var nextContextValue = actionImpl && actionImpl(currentContext, event);
          if (nextContextValue) {
            currentContext = _objectSpread(_objectSpread({}, currentContext), nextContextValue);
          }
        });
      }
    }
  }
 };
}

/**
 * @typedef {object} ShowOverlayData
 * @property {'warning' | 'error'} level level
 * @property {(string  | Message)[]} messages messages
 * @property {'build' | 'runtime'} messageSource message source
 */

/**
 * @typedef {object} CreateOverlayMachineOptions
 * @property {(data: ShowOverlayData) => void} showOverlay show overlay
 * @property {() => void} hideOverlay hide overlay
 */

/**
 * @param {CreateOverlayMachineOptions} options options
 * @returns {StateMachine} state machine
 */
var createOverlayMachine = function createOverlayMachine(options) {
 var hideOverlay = options.hideOverlay,
   showOverlay = options.showOverlay;
 return createMachine({
   initial: "hidden",
   context: {
     level: "error",
     messages: [],
     messageSource: "build"
   },
   states: {
     hidden: {
       on: {
         BUILD_ERROR: {
           target: "displayBuildError",
           actions: ["setMessages", "showOverlay"]
```

```
      },
      RUNTIME_ERROR: {
        target: "displayRuntimeError",
        actions: ["setMessages", "showOverlay"]
      }
    }
  },
  displayBuildError: {
    on: {
      DISMISS: {
        target: "hidden",
        actions: ["dismissMessages", "hideOverlay"]
      },
      BUILD_ERROR: {
        target: "displayBuildError",
        actions: ["appendMessages", "showOverlay"]
      }
    }
  },
  displayRuntimeError: {
    on: {
      DISMISS: {
        target: "hidden",
        actions: ["dismissMessages", "hideOverlay"]
      },
      RUNTIME_ERROR: {
        target: "displayRuntimeError",
        actions: ["appendMessages", "showOverlay"]
      },
      BUILD_ERROR: {
        target: "displayBuildError",
        actions: ["setMessages", "showOverlay"]
      }
    }
  }
 }
}, {
 actions: {
  dismissMessages: function dismissMessages() {
    return {
      messages: [],
      level: "error",
      messageSource: "build"
    };
  },
  appendMessages: function appendMessages(context, event) {
    return {
      messages: context.messages.concat(event.messages),
      level: event.level || context.level,
```

```
        messageSource: event.type === "RUNTIME_ERROR" ? "runtime" : "build"
       };
      },
      setMessages: function setMessages(context, event) {
       return {
        messages: event.messages,
        level: event.level || context.level,
        messageSource: event.type === "RUNTIME_ERROR" ? "runtime" : "build"
       };
      },
      hideOverlay: hideOverlay,
      showOverlay: showOverlay
     }
    });
};

/**
 * @param {Error} error error
 * @returns {undefined | string[]} stack
 */
var parseErrorToStacks = function parseErrorToStacks(error) {
  if (!error || !(error instanceof Error)) {
    throw new Error("parseErrorToStacks expects Error object");
  }
  if (typeof error.stack === "string") {
    return error.stack.split("\n").filter(function (stack) {
      return stack !== "Error: ".concat(error.message);
    });
  }
};

/**
 * @callback ErrorCallback
 * @param {ErrorEvent} error
 * @returns {void}
 */

/**
 * @param {ErrorCallback} callback callback
 * @returns {() => void} cleanup
 */
var listenToRuntimeError = function listenToRuntimeError(callback) {
  window.addEventListener("error", callback);
  return function cleanup() {
    window.removeEventListener("error", callback);
  };
};

/**
```

```
 * @callback UnhandledRejectionCallback
 * @param {PromiseRejectionEvent} rejectionEvent
 * @returns {void}
 */

/**
 * @param {UnhandledRejectionCallback} callback callback
 * @returns {() => void} cleanup
 */
var listenToUnhandledRejection = function listenToUnhandledRejection(callback) {
  window.addEventListener("unhandledrejection", callback);
  return function cleanup() {
    window.removeEventListener("unhandledrejection", callback);
  };
};

// Styles are inspired by `react-error-overlay`

var msgStyles = {
  error: {
    backgroundColor: "rgba(206, 17, 38, 0.1)",
    color: "#fccfcf"
  },
  warning: {
    backgroundColor: "rgba(251, 245, 180, 0.1)",
    color: "#fbf5b4"
  }
};
var iframeStyle = {
  position: "fixed",
  top: "0px",
  left: "0px",
  right: "0px",
  bottom: "0px",
  width: "100vw",
  height: "100vh",
  border: "none",
  "z-index": 9999999999
};
var containerStyle = {
  position: "fixed",
  boxSizing: "border-box",
  left: "0px",
  top: "0px",
  right: "0px",
  bottom: "0px",
  width: "100vw",
  height: "100vh",
  fontSize: "large",
```

```
  padding: "2rem 2rem 4rem 2rem",
  lineHeight: "1.2",
  whiteSpace: "pre-wrap",
  overflow: "auto",
  backgroundColor: "rgba(0, 0, 0, 0.9)",
  color: "white"
};
var headerStyle = {
  color: "#e83b46",
  fontSize: "2em",
  whiteSpace: "pre-wrap",
  fontFamily: "sans-serif",
  margin: "0 2rem 2rem 0",
  flex: "0 0 auto",
  maxHeight: "50%",
  overflow: "auto"
};
var dismissButtonStyle = {
  color: "#ffffff",
  lineHeight: "1rem",
  fontSize: "1.5rem",
  padding: "1rem",
  cursor: "pointer",
  position: "absolute",
  right: "0px",
  top: "0px",
  backgroundColor: "transparent",
  border: "none"
};
var msgTypeStyle = {
  color: "#e83b46",
  fontSize: "1.2em",
  marginBottom: "1rem",
  fontFamily: "sans-serif"
};
var msgTextStyle = {
  lineHeight: "1.5",
  fontSize: "1rem",
  fontFamily: "Menlo, Consolas, monospace"
};

// ANSI HTML

var colors = {
  reset: ["transparent", "transparent"],
  black: "181818",
  red: "E36049",
  green: "B3CB74",
  yellow: "FFD080",
```

```
  blue: "7CAFC2",
  magenta: "7FACCA",
  cyan: "C3C2EF",
  lightgrey: "EBE7E3",
  darkgrey: "6D7891"
};
ansi_html_community__WEBPACK_IMPORTED_MODULE_0___default().setColors(colors);

/** @typedef {Error & { file?: string, moduleName?: string, moduleIdentifier?: string, loc?: string,
message?: string; stack?: string | string[] }} Message */

/**
 * @param {string} type type
 * @param {string | Message} item item
 * @returns {{ header: string, body: string }} formatted problem
 */
var formatProblem = function formatProblem(type, item) {
  var header = type === "warning" ? "WARNING" : "ERROR";
  var body = "";
  if (typeof item === "string") {
    body += item;
  } else {
    var file = item.file || "";
    var moduleName = item.moduleName ? item.moduleName.indexOf("!") !== -1 ?
"".concat(item.moduleName.replace(/^(\s|\S)*!/, ""), " (").concat(item.moduleName, ")") :
"".concat(item.moduleName) : "";
    var loc = item.loc;
    header += "".concat(moduleName || file ? " in ".concat(moduleName ?
"".concat(moduleName).concat(file ? " (".concat(file, ")") : "") : file).concat(loc ? " ".concat(loc) : "") :
"");
    body += item.message || "";
  }
  if (typeof item !== "string" && Array.isArray(item.stack)) {
    item.stack.forEach(function (stack) {
      if (typeof stack === "string") {
        body += "\r\n".concat(stack);
      }
    });
  }
  return {
    header: header,
    body: body
  };
};

/**
 * @typedef {object} CreateOverlayOptions
 * @property {(false | string)=} trustedTypesPolicyName trusted types policy name
 * @property {(boolean | ((error: Error) => void))=} catchRuntimeError runtime error catcher
```

```
 */

/**
 * @param {CreateOverlayOptions} options options
 * @returns {StateMachine} overlay
 */
var createOverlay = function createOverlay(options) {
  /** @type {HTMLIFrameElement | null | undefined} */
  var iframeContainerElement;
  /** @type {HTMLDivElement | null | undefined} */
  var containerElement;
  /** @type {HTMLDivElement | null | undefined} */
  var headerElement;
  /** @type {Array<(element: HTMLDivElement) => void>} */
  var onLoadQueue = [];
  /** @type {Omit<TrustedTypePolicy, "createScript" | "createScriptURL"> | undefined} */
  var overlayTrustedTypesPolicy;

  /** @typedef {Extract<keyof CSSStyleDeclaration, "string">} CSSStyleDeclarationKeys */

  /**
   * @param {HTMLElement} element element
   * @param {Partial<CSSStyleDeclaration>} style style
   */
  function applyStyle(element, style) {
    Object.keys(style).forEach(function (prop) {
      element.style[(/** @type {CSSStyleDeclarationKeys} */prop)] = /** @type {string} */
      style[(/** @type {CSSStyleDeclarationKeys} */prop)];
    });
  }

  /**
   * @param {string | false | undefined} trustedTypesPolicyName trusted types police name
   */
  function createContainer(trustedTypesPolicyName) {
    // Enable Trusted Types if they are available in the current browser.
    if (window.trustedTypes) {
      overlayTrustedTypesPolicy = window.trustedTypes.createPolicy(trustedTypesPolicyName ||
"webpack-dev-server#overlay", {
        createHTML: function createHTML(value) {
          return value;
        }
      });
    }
    iframeContainerElement = document.createElement("iframe");
    iframeContainerElement.id = "webpack-dev-server-client-overlay";
    iframeContainerElement.src = "about:blank";
    applyStyle(iframeContainerElement,
  iframeStyle);
```

```
    iframeContainerElement.onload = function () {
      var contentElement = /** @type {Document} */
      (/** @type {HTMLIFrameElement} */
      iframeContainerElement.contentDocument).createElement("div");
      containerElement = /** @type {Document} */
      (/** @type {HTMLIFrameElement} */
      iframeContainerElement.contentDocument).createElement("div");
      contentElement.id = "webpack-dev-server-client-overlay-div";
      applyStyle(contentElement, containerStyle);
      headerElement = document.createElement("div");
      headerElement.innerText = "Compiled with problems:";
      applyStyle(headerElement, headerStyle);
      var closeButtonElement = document.createElement("button");
      applyStyle(closeButtonElement, dismissButtonStyle);
      closeButtonElement.innerText = "×";
      closeButtonElement.ariaLabel = "Dismiss";
      closeButtonElement.addEventListener("click", function () {
        // eslint-disable-next-line no-use-before-define
        overlayService.send({
          type: "DISMISS"
        });
      });
      contentElement.appendChild(headerElement);
      contentElement.appendChild(closeButtonElement);
      contentElement.appendChild(containerElement);

      /** @type {Document} */
      (/** @type {HTMLIFrameElement} */
      iframeContainerElement.contentDocument).body.appendChild(contentElement);
      onLoadQueue.forEach(function (onLoad) {
        onLoad(/** @type {HTMLDivElement} */contentElement);
      });
      onLoadQueue = [];

      /** @type {HTMLIFrameElement} */
      iframeContainerElement.onload = null;
    };
    document.body.appendChild(iframeContainerElement);
  }

  /**
   * @param {(element: HTMLDivElement) => void} callback callback
   * @param {string | false | undefined} trustedTypesPolicyName trusted types policy name
   */
  function ensureOverlayExists(callback, trustedTypesPolicyName) {
    if (containerElement) {
      // @ts-expect-error https://github.com/microsoft/TypeScript/issues/30024
      containerElement.innerHTML = overlayTrustedTypesPolicy ?
overlayTrustedTypesPolicy.createHTML("") : "";
```

```
    // Everything is ready, call the callback right away.
    callback(containerElement);
    return;
  }
  onLoadQueue.push(callback);
  if (iframeContainerElement) {
    return;
  }
  createContainer(trustedTypesPolicyName);
}

// Successful compilation.
/**
 * @returns {void}
 */
function hide() {
  if (!iframeContainerElement) {
    return;
  }

  // Clean up and reset internal state.
  document.body.removeChild(iframeContainerElement);
  iframeContainerElement = null;
  containerElement = null;
}

// Compilation with errors (e.g. syntax error or missing modules).
/**
 * @param {string} type type
 * @param {(string | Message)[]} messages messages
 * @param {undefined | false | string} trustedTypesPolicyName trusted types policy name
 * @param {'build' | 'runtime'} messageSource message source
 */
function show(type, messages, trustedTypesPolicyName, messageSource) {
  ensureOverlayExists(function () {
    /** @type {HTMLDivElement} */
    headerElement.innerText = messageSource === "runtime" ? "Uncaught runtime errors:" :
"Compiled with problems:";
    messages.forEach(function (message) {
      var entryElement = document.createElement("div");
      var msgStyle = type === "warning" ? msgStyles.warning : msgStyles.error;
      applyStyle(entryElement, _objectSpread(_objectSpread({}, msgStyle), {}, {
        padding: "1rem 1rem 1.5rem 1rem"
      }));
      var typeElement = document.createElement("div");
      var _formatProblem = formatProblem(type, message),
        header = _formatProblem.header,
        body = _formatProblem.body;
      typeElement.innerText = header;
```

```
      applyStyle(typeElement, msgTypeStyle);
      if (typeof message !== "string" && message.moduleIdentifier) {
        applyStyle(typeElement, {
          cursor: "pointer"
        });
        // element.dataset not supported in IE
        typeElement.setAttribute("data-can-open", "true");
        typeElement.addEventListener("click", function () {
          fetch("/webpack-dev-server/open-editor?fileName=".concat(message.moduleIdentifier));
        });
      }

      // Make it look similar to our terminal.
      var text = ansi_html_community__WEBPACK_IMPORTED_MODULE_0___default()
(encode(body));
      var messageTextNode = document.createElement("div");
      applyStyle(messageTextNode, msgTextStyle);

      // @ts-expect-error https://github.com/microsoft/TypeScript/issues/30024
      messageTextNode.innerHTML = overlayTrustedTypesPolicy ?
overlayTrustedTypesPolicy.createHTML(text) : text;
      entryElement.appendChild(typeElement);
      entryElement.appendChild(messageTextNode);

      /** @type {HTMLDivElement} */
      containerElement.appendChild(entryElement);
    });
  }, trustedTypesPolicyName);
}

/** @type {(event: KeyboardEvent) => void} */
var handleEscapeKey;

/**
 * @returns {void}
 */

var hideOverlayWithEscCleanup = function hideOverlayWithEscCleanup() {
  window.removeEventListener("keydown", handleEscapeKey);
  hide();
};
var overlayService = createOverlayMachine({
  showOverlay: function showOverlay(_ref3) {
    var _ref3$level = _ref3.level,
      level = _ref3$level === void 0 ? "error" : _ref3$level,
      messages = _ref3.messages,
      messageSource = _ref3.messageSource;
    return show(level, messages, options.trustedTypesPolicyName, messageSource);
  },
```

```
    hideOverlay: hideOverlayWithEscCleanup
  });
  /**
   * ESC key press to dismiss the overlay.
   * @param {KeyboardEvent} event Keydown event
   */
  handleEscapeKey = function handleEscapeKey(event) {
    if (event.key === "Escape" || event.key === "Esc" || event.keyCode === 27) {
      overlayService.send({
        type: "DISMISS"
      });
    }
  };
  window.addEventListener("keydown", handleEscapeKey);
  if (options.catchRuntimeError) {
    /**
     * @param {Error | undefined} error error
     * @param {string} fallbackMessage fallback message
     */
    var handleError = function handleError(error, fallbackMessage) {
      var errorObject = error instanceof Error ? error : new Error(error || fallbackMessage, {
        cause: error
      });
      var shouldDisplay = typeof options.catchRuntimeError === "function" ?
options.catchRuntimeError(errorObject) : true;
      if (shouldDisplay) {
        overlayService.send({
          type: "RUNTIME_ERROR",
          messages: [{
            message: errorObject.message,
            stack: parseErrorToStacks(errorObject)
          }]
        });
      }
    };
    listenToRuntimeError(function (errorEvent) {
      // error property may be empty in older browser like IE
      var error = errorEvent.error,
        message = errorEvent.message;
      if (!error && !message) {
        return;
      }

      // if error stack indicates a React error boundary caught the error, do not show overlay.
      if (error && error.stack && error.stack.includes("invokeGuardedCallbackDev")) {
        return;
      }
      handleError(error, message);
    });
```

```
    listenToUnhandledRejection(function (promiseRejectionEvent) {
      var reason = promiseRejectionEvent.reason;
      handleError(reason, "Unknown promise rejection reason");
    });
  }
  return overlayService;
};


/***/ },

/***/ "./node_modules/webpack-dev-server/client/progress.js"
/*!*****************************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/progress.js ***!
  \*****************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   defineProgressElement: () => (/* binding */ defineProgressElement),
/* harmony export */   isProgressSupported: () => (/* binding */ isProgressSupported)
/* harmony export */ });
function _typeof(o) {
  "@babel/helpers - typeof";

  return _typeof = "function" == typeof Symbol && "symbol" == typeof Symbol.iterator ? function (o)
{
    return typeof o;
  } : function (o) {
    return o && "function" == typeof Symbol && o.constructor === Symbol && o !==
Symbol.prototype ? "symbol" : typeof o;
  }, _typeof(o);
}
function _classCallCheck(a, n) {
  if (!(a instanceof n)) throw new TypeError("Cannot call a class as a function");
}
function _defineProperties(e, r) {
  for (var t = 0; t < r.length; t++) {
    var o = r[t];
    o.enumerable = o.enumerable || !1, o.configurable = !0, "value" in o && (o.writable = !0),
Object.defineProperty(e, _toPropertyKey(o.key), o);
  }
}
function _createClass(e, r, t) {
  return r && _defineProperties(e.prototype, r), t && _defineProperties(e, t), Object.defineProperty(e,
"prototype", {
    writable: !1
  }), e;
```

```
}
function _toPropertyKey(t) {
  var i = _toPrimitive(t, "string");
  return "symbol" == _typeof(i) ? i : i + "";
}
function _toPrimitive(t, r) {
  if ("object" != _typeof(t) || !t) return t;
  var e = t[Symbol.toPrimitive];
  if (void 0 !== e) {
    var i = e.call(t, r || "default");
    if ("object" != _typeof(i)) return i;
    throw new TypeError("@@toPrimitive must return a primitive value.");
  }
  return ("string" === r ? String : Number)(t);
}
function _callSuper(t, o, e) {
  return o = _getPrototypeOf(o), _possibleConstructorReturn(t, _isNativeReflectConstruct() ?
Reflect.construct(o, e || [], _getPrototypeOf(t).constructor) : o.apply(t, e));
}
function _possibleConstructorReturn(t, e) {
  if (e && ("object" == _typeof(e) || "function" == typeof e)) return e;
  if (void 0 !== e) throw new TypeError("Derived constructors may only return object or undefined");
  return _assertThisInitialized(t);
}
function
 _assertThisInitialized(e) {
  if (void 0 === e) throw new ReferenceError("this hasn't been initialised - super() hasn't been called");
  return e;
}
function _inherits(t, e) {
  if ("function" != typeof e && null !== e) throw new TypeError("Super expression must either be null
or a function");
  t.prototype = Object.create(e && e.prototype, {
    constructor: {
      value: t,
      writable: !0,
      configurable: !0
    }
  }), Object.defineProperty(t, "prototype", {
    writable: !1
  }), e && _setPrototypeOf(t, e);
}
function _wrapNativeSuper(t) {
  var r = "function" == typeof Map ? new Map() : void 0;
  return _wrapNativeSuper = function _wrapNativeSuper(t) {
    if (null === t || !_isNativeFunction(t)) return t;
    if ("function" != typeof t) throw new TypeError("Super expression must either be null or a
function");
    if (void 0 !== r) {
```

```
      if (r.has(t)) return r.get(t);
      r.set(t, Wrapper);
    }
    function Wrapper() {
      return _construct(t, arguments, _getPrototypeOf(this).constructor);
    }
    return Wrapper.prototype = Object.create(t.prototype, {
      constructor: {
        value: Wrapper,
        enumerable: !1,
        writable: !0,
        configurable: !0
      }
    }), _setPrototypeOf(Wrapper, t);
  }, _wrapNativeSuper(t);
}
function _construct(t, e, r) {
  if (_isNativeReflectConstruct()) return Reflect.construct.apply(null, arguments);
  var o = [null];
  o.push.apply(o, e);
  var p = new (t.bind.apply(t, o))();
  return r && _setPrototypeOf(p, r.prototype), p;
}
function _isNativeReflectConstruct() {
  try {
    var t = !Boolean.prototype.valueOf.call(Reflect.construct(Boolean, [], function () {}));
  } catch (t) {}
  return (_isNativeReflectConstruct = function _isNativeReflectConstruct() {
    return !!t;
  })();
}
function _isNativeFunction(t) {
  try {
    return -1 !== Function.toString.call(t).indexOf("[native code]");
  } catch (n) {
    return "function" == typeof t;
  }
}
function _setPrototypeOf(t, e) {
  return _setPrototypeOf = Object.setPrototypeOf ? Object.setPrototypeOf.bind() : function (t, e) {
    return t.__proto__ = e, t;
  }, _setPrototypeOf(t, e);
}
function _getPrototypeOf(t) {
  return _getPrototypeOf = Object.setPrototypeOf ? Object.getPrototypeOf.bind() : function (t) {
    return t.__proto__ || Object.getPrototypeOf(t);
  }, _getPrototypeOf(t);
}
function _classPrivateMethodInitSpec(e, a) {
```

```
  _checkPrivateRedeclaration(e, a), a.add(e);
}
function _checkPrivateRedeclaration(e, t) {
  if (t.has(e)) throw new TypeError("Cannot initialize the same private elements twice on an object");
}
function _assertClassBrand(e, t, n) {
  if ("function" == typeof e ? e === t : e.has(t)) return arguments.length < 3 ? t : n;
  throw new TypeError("Private element is not present on this object");
}
/**
 * @returns {boolean} true when custom elements supported, otherwise false
 */
function isProgressSupported() {
  return "customElements" in self && Boolean(HTMLElement.prototype.attachShadow);
}

/**
 * @returns {void}
 */
function defineProgressElement() {
  var _WebpackDevServerProgress;
  if (customElements.get("wds-progress")) {
    return;
  }
  var _WebpackDevServerProgress_brand = /*#__PURE__*/new WeakSet();
  var WebpackDevServerProgress = /*#__PURE__*/function (_HTMLElement) {
    function WebpackDevServerProgress() {
      var _this;
      _classCallCheck(this, WebpackDevServerProgress);
      _this = _callSuper(this, WebpackDevServerProgress);
      _classPrivateMethodInitSpec(_this, _WebpackDevServerProgress_brand);
      _this.attachShadow({
        mode: "open"
      });
      _this.maxDashOffset = -219.99078369140625;
      _this.animationTimer = null;
      return _this;
    }
    _inherits(WebpackDevServerProgress, _HTMLElement);
    return _createClass(WebpackDevServerProgress, [{
      key: "connectedCallback",
      value: function connectedCallback() {
        _assertClassBrand(_WebpackDevServerProgress_brand, this, _reset).call(this);
      }
    }, {
      key: "attributeChangedCallback",
      value:
      /**
       * @param {string} name name
```

```
     * @param {string} oldValue old value
     * @param {string} newValue new value
     */
    function attributeChangedCallback(name, oldValue, newValue) {
      if (name === "progress") {
        _assertClassBrand(_WebpackDevServerProgress_brand, this, _update).call(this,
Number(newValue));
      } else if (name === "type") {
        _assertClassBrand(_WebpackDevServerProgress_brand, this, _reset).call(this);
      }
    }

    /**
     * @param {number} percent percent
     */
  }], [{
    key: "observedAttributes",
    get: function get() {
      return ["progress", "type"];
    }
  }]);
 }(/*#__PURE__*/_wrapNativeSuper(HTMLElement));
 _WebpackDevServerProgress = WebpackDevServerProgress;
 function _reset() {
  var _this$getAttribute;
  clearTimeout(this.animationTimer);
  this.animationTimer = null;
  var typeAttr = (_this$getAttribute = this.getAttribute("type")) === null || _this$getAttribute ===
void 0 ? void 0 : _this$getAttribute.toLowerCase();
  this.type = typeAttr === "circular" ? "circular" : "linear";
  var innerHTML = this.type === "circular" ? _circularTemplate.call(_WebpackDevServerProgress) :
_linearTemplate.call(_WebpackDevServerProgress);
  /** @type {ShadowRoot} */
  this.shadowRoot.innerHTML = innerHTML;
  var progressValue = this.getAttribute("progress");
  this.initialProgress = progressValue ? Number(progressValue) : 0;
  _assertClassBrand(_WebpackDevServerProgress_brand, this, _update).call(this, this.initialProgress);
 }
 function _circularTemplate() {
  return "\n      <style>\n      :host {\n          width: 200px;\n          height: 200px;\n          position:
fixed;\n          right: 5%;\n          top: 5%;\n          pointer-events: none;\n          transition: opacity .
25s ease-in-out;\n          z-index: 2147483645;\n      }\n\n      circle {\n          fill:
#282d35;\n      }\n\n      path {\n          fill: rgba(0, 0, 0, 0);\n          stroke: rgb(186, 223, 172);\n
stroke-dasharray: 219.99078369140625;\n          stroke-dashoffset: -219.99078369140625;\n
stroke-width: 10;\n          transform: rotate(90deg) translate(0px, -80px);\n      }\n\n      text {\n
font-family: 'Open Sans', sans-serif;\n          font-size: 18px;\n          fill: #ffffff;\n          dominant-
baseline: middle;\n          text-anchor: middle;\n      }\n\n      tspan#percent-super {\n          fill:
#bdc3c7;\n          font-size: 0.45em;\n          baseline-shift: 10%;\n      }\n\n      @keyframes fade
{\n          0% { opacity: 1; transform: scale(1); }\n          100% { opacity: 0; transform: scale(0); }\n
```

```
}\n\n       .disappear {\n           animation: fade 0.3s;\n           animation-fill-mode: forwards;\n
animation-delay: 0.5s;\n       }\n\n       .hidden {\n           display: none;\n       }\n       </style>\n
<svg id=\"progress\" class=\"hidden noselect\" viewBox=\"0 0 80 80\">\n       <circle cx=\"50%\"
cy=\"50%\" r=\"35\"></circle>\n       <path d=\"M5,40a35,35 0 1,0 70,0a35,35 0 1,0 -70,0\"></path>\n
<text x=\"50%\" y=\"51%\">\n           <tspan id=\"percent-value\">0</tspan>\n           <tspan
id=\"percent-super\">%</tspan>\n       </text>\n       </svg>\n     ";
  }
  function _linearTemplate() {
    return "\n       <style>\n       :host {\n           position: fixed;\n           top: 0;\n           left: 0;\n
pointer-events: none;\n           height: 4px;\n           width: 100vw;\n           z-index: 2147483645;\n
}\n\n       #bar {\n           width: 0%;\n           height: 4px;\n           background-color: rgb(186, 223,
172);\n       }\n\n       @keyframes fade {\n           0% { opacity: 1; }\n           100% { opacity: 0; }\n
}\n\n       .disappear {\n           animation: fade 0.3s;\n           animation-fill-mode: forwards;\n
animation-delay: 0.5s;\n       }\n\n       .hidden {\n           display: none;\n       }\n       </style>\n
<div id=\"progress\"></div>\n       ";
  }
  function _update(percent) {
    var shadowRoot = /** @type {ShadowRoot} */this.shadowRoot;
    var element = /** @type {HTMLElement} */
    shadowRoot.querySelector("#progress");
    if (this.type === "circular") {
      var path = /** @type {SVGPathElement} */
      shadowRoot.querySelector("path");
      var value = /** @type {HTMLElement} */
      shadowRoot.querySelector("#percent-value");
      var offset = (100 - percent) / 100 * this.maxDashOffset;
      path.style.strokeDashoffset = String(offset);
      value.textContent = String(percent);
    } else {
      element.style.width = "".concat(percent, "%");
    }
    if (percent >= 100) {
      _assertClassBrand(_WebpackDevServerProgress_brand, this, _hide).call(this);
    } else if (percent > 0) {
      _assertClassBrand(_WebpackDevServerProgress_brand, this, _show).call(this);
    }
  }
  function _show() {
    var shadowRoot = /** @type {ShadowRoot} */this.shadowRoot;
    var element = /** @type {HTMLElement} */
    shadowRoot.querySelector("#progress");
    element.classList.remove("hidden");
  }
  function _hide() {
    var _this2 = this;
    var shadowRoot = /** @type {ShadowRoot} */this.shadowRoot;
    var element = /** @type {HTMLElement} */
    shadowRoot.querySelector("#progress");
    if (this.type === "circular") {
```

```
      element.classList.add("disappear");
      element.addEventListener("animationend", function () {
        element.classList.add("hidden");
        _assertClassBrand(_WebpackDevServerProgress_brand, _this2, _update).call(_this2, 0);
      }, {
        once: true
      });
    } else if (this.type === "linear") {
      element.classList.add("disappear");

      this.animationTimer = setTimeout(function () {
        element.classList.remove("disappear");
        element.classList.add("hidden");
        element.style.width = "0%";
        _this2.animationTimer = null;
      }, 800);
    }
  }
  customElements.define("wds-progress", WebpackDevServerProgress);
}

/***/ },

/***/ "./node_modules/webpack-dev-server/client/socket.js"
/*!*********************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/socket.js ***!
  \*********************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   client: () => (/* binding */ client),
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _clients_WebSocketClient_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./clients/WebSocketClient.js */ "./node_modules/webpack-dev-
server/client/clients/WebSocketClient.js");
/* harmony import */ var _utils_log_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./utils/log.js */ "./node_modules/webpack-dev-server/client/utils/log.js");
/* provided dependency */ var __webpack_dev_server_client__ = __webpack_require__(/*!
./node_modules/webpack-dev-server/client/clients/WebSocketClient.js */ "./node_modules/webpack-
dev-server/client/clients/WebSocketClient.js");
/* global __webpack_dev_server_client__ */



/** @typedef {import("./index.js").EXPECTED_ANY} EXPECTED_ANY */
```

```
/** @typedef {import("./clients/SockJSClient")} SockJSClient */

// this WebsocketClient is here as a default fallback, in case the client is not injected
/** @type {CommunicationClientConstructor} */
var Client = typeof __webpack_dev_server_client__ !== "undefined" ? typeof (/** @type {{ default:
CommunicationClientConstructor }} */
__webpack_dev_server_client__.default) !== "undefined" ? /** @type {{ default:
CommunicationClientConstructor }} */
__webpack_dev_server_client__.default : (/** @type {CommunicationClientConstructor} */
__webpack_dev_server_client__) :
_clients_WebSocketClient_js__WEBPACK_IMPORTED_MODULE_0__["default"];
var retries = 0;
var maxRetries = 10;

// Initialized client is exported so external consumers can utilize the same instance
// It is mutable to enforce singleton
/** @type {CommunicationClient | null} */
// eslint-disable-next-line import/no-mutable-exports
var client = null;

/** @type {ReturnType<typeof setTimeout> | undefined} */
var timeout;

/**
 * @param {string} url url
 * @param {{ [handler: string]: (data?: EXPECTED_ANY, params?: EXPECTED_ANY) =>
EXPECTED_ANY }} handlers handlers
 * @param {number=} reconnect count of reconnections
 */
function socket(url, handlers, reconnect) {
  client = new Client(url);
  client.onOpen(function () {
    retries = 0;
    if (timeout) {
      clearTimeout(timeout);
    }
    if (typeof reconnect !== "undefined") {
      maxRetries = reconnect;
    }
  });
  client.onClose(function () {
    if (retries === 0) {
      handlers.close();
    }

    // Try to reconnect.
    client = null;

    // After 10 retries stop trying, to prevent logspam.
```

```
    if (retries < maxRetries) {
      // Exponentially increase timeout to reconnect.
      // Respectfully copied from the package `got`.
      var retryInMs = 1000 * Math.pow(2, retries) + Math.random() * 100;
      retries += 1;
      _utils_log_js__WEBPACK_IMPORTED_MODULE_1__.log.info("Trying to reconnect...");
      timeout = setTimeout(function () {
        socket(url, handlers, reconnect);
      }, retryInMs);
    }
  });
  client.onMessage(
  /**
   * @param {EXPECTED_ANY} data data
   */
  function (data) {
    var message = JSON.parse(data);
    if (handlers[message.type]) {
      handlers[message.type](message.data, message.params);
    }
  });
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (socket);

/***/ },

/***/ "./node_modules/webpack-dev-server/client/utils/log.js"
/*!************************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/utils/log.js ***!
  \************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   log: () => (/* binding */ log),
/* harmony export */   setLogLevel: () => (/* binding */ setLogLevel)
/* harmony export */ });
/* harmony import */ var _modules_logger_index_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../modules/logger/index.js */ "./node_modules/webpack-dev-
server/client/modules/logger/index.js");
/* harmony import */ var
_modules_logger_index_js__WEBPACK_IMPORTED_MODULE_0___default =
/*#__PURE__*/__webpack_require__.n(_modules_logger_index_js__WEBPACK_IMPORTED_MO
DULE_0__);

var name = "webpack-dev-server";
// default level is set on the client side, so it does not need
// to be set by the CLI or API
```

```
var defaultLevel = "info";

// options new options, merge with old options
/**
 * @param {false | true | "none" | "error" | "warn" | "info" | "log" | "verbose"} level level
 * @returns {void}
 */
function setLogLevel(level) {

_modules_logger_index_js__WEBPACK_IMPORTED_MODULE_0___default().configureDefaultLo
gger({
    level: level
  });
}
setLogLevel(defaultLevel);
var log =
_modules_logger_index_js__WEBPACK_IMPORTED_MODULE_0___default().getLogger(name);


/***/ },

/***/ "./node_modules/webpack-dev-server/client/utils/sendMessage.js"
/*!*****************************************************************!*\
  !*** ./node_modules/webpack-dev-server/client/utils/sendMessage.js ***!
  \*****************************************************************/
(__unused_webpack_module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* global WorkerGlobalScope */

/** @typedef {import("../index").EXPECTED_ANY} EXPECTED_ANY */

// Send messages to the outside, so plugins can consume it.
/**
 * @param {string} type type
 * @param {EXPECTED_ANY=} data data
 */
function sendMsg(type, data) {
  if (typeof self !== "undefined" && (typeof WorkerGlobalScope === "undefined" || !(self instanceof
WorkerGlobalScope))) {
    self.postMessage({
      type: "webpack".concat(type),
      data: data
    }, "*");
  }
```

```
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (sendMsg);

/***/ },

/***/ "./node_modules/webpack/hot/dev-server.js"
/*!*****************************************************!*\
  !*** ./node_modules/webpack/hot/dev-server.js ***!
  \*****************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

/*
	MIT License http://www.opensource.org/licenses/mit-license.php
	Author Tobias Koppers @sokra
*/
/* globals __webpack_hash__ */
if (true) {
  /** @type {undefined|string} */
  var lastHash;
  var upToDate = function upToDate() {
    return /** @type {string} */lastHash.indexOf(__webpack_require__.h()) >= 0;
  };
  var log = __webpack_require__(/*! ./log */ "./node_modules/webpack/hot/log.js");
  var check = function check() {
    module.hot.check(true).then(function (updatedModules) {
      if (!updatedModules) {
        log("warning", "[HMR] Cannot find update. " + (typeof window !== "undefined" ? "Need to do a
full reload!" : "Please reload manually!"));
        log("warning", "[HMR] (Probably because of restarting the webpack-dev-server)");
        if (typeof window !== "undefined") {
          window.location.reload();
        }
        return;
      }
      if (!upToDate()) {
        check();
      }
      __webpack_require__(/*! ./log-apply-result */ "./node_modules/webpack/hot/log-apply-result.js")
(updatedModules, updatedModules);
      if (upToDate()) {
        log("info", "[HMR] App is up to date.");
      }
    }).catch(function (err) {
      var status = module.hot.status();
      if (["abort", "fail"].indexOf(status) >= 0) {
        log("warning", "[HMR] Cannot apply update. " + (typeof window !== "undefined" ? "Need to do
a full reload!" : "Please reload manually!"));
        log("warning", "[HMR] " + log.formatError(err));
        if (typeof window !== "undefined") {
```

```
        window.location.reload();
       }
      } else {
       log("warning", "[HMR] Update failed: " + log.formatError(err));
      }
     });
    };
    /** @type {EventTarget | NodeJS.EventEmitter} */
    var hotEmitter = __webpack_require__(/*! ./emitter */ "./node_modules/webpack/hot/emitter.js");
    /**
     * @param {CustomEvent<{ currentHash: string }>} event event or hash
     */
    var handler = function (event) {
     lastHash = typeof event === "string" ? event : event.detail.currentHash;
     if (!upToDate() && module.hot.status() === "idle") {
      log("info", "[HMR] Checking for updates on the server...");
      check();
     }
    };
    if (typeof EventTarget !== "undefined" && hotEmitter instanceof EventTarget) {
     hotEmitter.addEventListener("webpackHotUpdate", /** @type {EventListener} */
     handler);
    } else {
     hotEmitter.on("webpackHotUpdate", handler);
    }
    log("info", "[HMR] Waiting for update signal from WDS...");
  } else // removed by dead control flow
  {}

  /***/ },

  /***/ "./node_modules/webpack/hot/emitter.js"
  /*!*********************************************!*\
    !*** ./node_modules/webpack/hot/emitter.js ***!
    \*********************************************/
  (module, __unused_webpack_exports, __webpack_require__) {

  var EventEmitter = __webpack_require__(/*! events */ "./node_modules/events/events.js");
  module.exports
   = new EventEmitter();

  /***/ },

  /***/ "./node_modules/webpack/hot/log-apply-result.js"
  /*!*****************************************************!*\
    !*** ./node_modules/webpack/hot/log-apply-result.js ***!
    \*****************************************************/
  (module, __unused_webpack_exports, __webpack_require__) {
```

```
/*
	MIT License http://www.opensource.org/licenses/mit-license.php
	Author Tobias Koppers @sokra
*/

/**
 * @param {(string | number)[]} updatedModules updated modules
 * @param {(string | number)[] | null} renewedModules renewed modules
 */
module.exports = function (updatedModules, renewedModules) {
  var unacceptedModules = updatedModules.filter(function (moduleId) {
    return renewedModules && renewedModules.indexOf(moduleId) < 0;
  });
  var log = __webpack_require__(/*! ./log */ "./node_modules/webpack/hot/log.js");
  if (unacceptedModules.length > 0) {
    log("warning", "[HMR] The following modules couldn't be hot updated: (They would need a full
reload!)");
    unacceptedModules.forEach(function (moduleId) {
      log("warning", "[HMR]  - " + moduleId);
    });
  }
  if (!renewedModules || renewedModules.length === 0) {
    log("info", "[HMR] Nothing hot updated.");
  } else {
    log("info", "[HMR] Updated modules:");
    renewedModules.forEach(function (moduleId) {
      if (typeof moduleId === "string" && moduleId.indexOf("!") !== -1) {
        var parts = moduleId.split("!");
        log.groupCollapsed("info", "[HMR]  - " + parts.pop());
        log("info", "[HMR]  - " + moduleId);
        log.groupEnd("info");
      } else {
        log("info", "[HMR]  - " + moduleId);
      }
    });
    var numberIds = renewedModules.every(function (moduleId) {
      return typeof moduleId === "number";
    });
    if (numberIds) log("info", '[HMR] Consider using the optimization.moduleIds: "named" for module
names.');
  }
};

/***/ },

/***/ "./node_modules/webpack/hot/log.js"
/*!*****************************************!*\
  !*** ./node_modules/webpack/hot/log.js ***!
  \*****************************************/
```

```
(module) {

/** @typedef {"info" | "warning" | "error"} LogLevel */

/** @type {LogLevel} */
var logLevel = "info";
function dummy() {}

/**
 * @param {LogLevel} level log level
 * @returns {boolean} true, if should log
 */
function shouldLog(level) {
  var shouldLog = logLevel === "info" && level === "info" || ["info", "warning"].indexOf(logLevel)
>= 0 && level === "warning" || ["info", "warning", "error"].indexOf(logLevel) >= 0 && level ===
"error";
  return shouldLog;
}

/**
 * @param {(msg?: string) => void} logFn log function
 * @returns {(level: LogLevel, msg?: string) => void} function that logs when log level is sufficient
 */
function logGroup(logFn) {
  return function (level, msg) {
    if (shouldLog(level)) {
      logFn(msg);
    }
  };
}

/**
 * @param {LogLevel} level log level
 * @param {string|Error} msg message
 */
module.exports = function (level, msg) {
  if (shouldLog(level)) {
    if (level === "info") {
      console.log(msg);
    } else if (level === "warning") {
      console.warn(msg);
    } else if (level === "error") {
      console.error(msg);
    }
  }
};

/**
 * @param {Error} err error
```

```
 * @returns {string} formatted error
 */
module.exports.formatError = function (err) {
  var message = err.message;
  var stack = err.stack;
  if (!stack) {
    return message;
  } else if (stack.indexOf(message) < 0) {
    return message + "\n" + stack;
  }
  return stack;
};
var group = console.group || dummy;
var groupCollapsed = console.groupCollapsed || dummy;
var groupEnd = console.groupEnd || dummy;
module.exports.group = logGroup(group);
module.exports.groupCollapsed = logGroup(groupCollapsed);
module.exports.groupEnd = logGroup(groupEnd);

/**
 * @param {LogLevel} level log level
 */
module.exports.setLogLevel = function (level) {
  logLevel = level;
};

/***/ },

/***/ "./node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cjs.js!./src/App.css"
/*!
**********************************************************************************
**********************************************************************************
*****************************************************!*\
  !*** ./node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cjs.js!./src/App.css ***!

\**********************************************************************************
**********************************************************************************
*****************************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
```

```
/* harmony import */ var
_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0__
= __webpack_require__(/*! ../node_modules/css-loader/dist/runtime/sourceMaps.js */
"./node_modules/css-loader/dist/runtime/sourceMaps.js");
/* harmony import */ var
_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0__
_default =
/*#__PURE__*/__webpack_require__.n(_node_modules_css_loader_dist_runtime_sourceMaps_js__
WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../node_modules/css-loader/dist/runtime/api.js */ "./node_modules/css-
loader/dist/runtime/api.js");
/* harmony import */ var
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1___default
=
/*#__PURE__*/__webpack_require__.n(_node_modules_css_loader_dist_runtime_api_js__WEBPAC
K_IMPORTED_MODULE_1__);
// Imports


var ___CSS_LOADER_EXPORT___ =
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1___default(
)
((_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0_
__default()));
// Module
___CSS_LOADER_EXPORT___.push([module.id, `/* Global app CSS handled in index.css */
.App { min-height: 100vh; text-align: left; }
`, "",{"version":3,"sources":["webpack://./src/App.css"],"names":
[],"mappings":"AAAA,wCAAwC;AACxC,OAAO,iBAAiB,EAAE,gBAAgB,EAAE","sourcesContent"
:["/* Global app CSS handled in index.css *\/\n.App { min-height: 100vh; text-align:
left; }\n"],"sourceRoot":""}]);
// Exports
___CSS_LOADER_EXPORT___.locals = {};
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(___CSS_LOADER_EXPORT___);


/***/ },

/***/ "./node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cjs.js!./src/index.css"
/*!
**********************************************************************************
**********************************************************************************
**********************************************************!*\
  !*** ./node_modules/css-loader/dist/cjs.js??
```

```
ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cjs.js!./src/index.css ***!

\*************************************************************************************
*************************************************************************************
*************************************************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var
_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0__
= __webpack_require__(/*! ../node_modules/css-loader/dist/runtime/sourceMaps.js */
"./node_modules/css-loader/dist/runtime/sourceMaps.js");
/* harmony import */ var
_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0__
_default =
/*#__PURE__*/__webpack_require__.n(_node_modules_css_loader_dist_runtime_sourceMaps_js__
WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../node_modules/css-loader/dist/runtime/api.js */ "./node_modules/css-
loader/dist/runtime/api.js");
/* harmony import */ var
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1___default
=
/*#__PURE__*/__webpack_require__.n(_node_modules_css_loader_dist_runtime_api_js__WEBPAC
K_IMPORTED_MODULE_1__);
// Imports


var ___CSS_LOADER_EXPORT___ =
_node_modules_css_loader_dist_runtime_api_js__WEBPACK_IMPORTED_MODULE_1___default(
)
((_node_modules_css_loader_dist_runtime_sourceMaps_js__WEBPACK_IMPORTED_MODULE_0_
__default()));
___CSS_LOADER_EXPORT___.push([module.id, "@import url(https://fonts.googleapis.com/css2?
family=Outfit:wght@400;500;600;700;800&family=Inter:wght@400;500;600;700&family=JetBrains+
Mono:wght@400;500;600;700&display=swap);"]);
// Module
___CSS_LOADER_EXPORT___.push([module.id, `*, ::before, ::after{
  --tw-border-spacing-x: 0;
  --tw-border-spacing-y: 0;
  --tw-translate-x: 0;
  --tw-translate-y: 0;
  --tw-rotate: 0;
```

```
  --tw-skew-x: 0;
  --tw-skew-y: 0;
  --tw-scale-x: 1;
  --tw-scale-y: 1;
  --tw-pan-x:  ;
  --tw-pan-y:  ;
  --tw-pinch-zoom:  ;
  --tw-scroll-snap-strictness: proximity;
  --tw-gradient-from-position:  ;
  --tw-gradient-via-position:  ;
  --tw-gradient-to-position:  ;
  --tw-ordinal:  ;
  --tw-slashed-zero:  ;
  --tw-numeric-figure:  ;
  --tw-numeric-spacing:  ;
  --tw-numeric-fraction:  ;
  --tw-ring-inset:
  ;
  --tw-ring-offset-width: 0px;
  --tw-ring-offset-color: #fff;
  --tw-ring-color: rgb(59 130 246 / 0.5);
  --tw-ring-offset-shadow: 0 0 #0000;
  --tw-ring-shadow: 0 0 #0000;
  --tw-shadow: 0 0 #0000;
  --tw-shadow-colored: 0 0 #0000;
  --tw-blur:  ;
  --tw-brightness:  ;
  --tw-contrast:  ;
  --tw-grayscale:  ;
  --tw-hue-rotate:  ;
  --tw-invert:  ;
  --tw-saturate:  ;
  --tw-sepia:  ;
  --tw-drop-shadow:  ;
  --tw-backdrop-blur:  ;
  --tw-backdrop-brightness:  ;
  --tw-backdrop-contrast:  ;
  --tw-backdrop-grayscale:  ;
  --tw-backdrop-hue-rotate:  ;
  --tw-backdrop-invert:  ;
  --tw-backdrop-opacity:  ;
  --tw-backdrop-saturate:  ;
  --tw-backdrop-sepia:  ;
  --tw-contain-size:  ;
  --tw-contain-layout:  ;
  --tw-contain-paint:  ;
  --tw-contain-style:  ;
}
```

```
::backdrop{
  --tw-border-spacing-x: 0;
  --tw-border-spacing-y: 0;
  --tw-translate-x: 0;
  --tw-translate-y: 0;
  --tw-rotate: 0;
  --tw-skew-x: 0;
  --tw-skew-y: 0;
  --tw-scale-x: 1;
  --tw-scale-y: 1;
  --tw-pan-x:  ;
  --tw-pan-y:  ;
  --tw-pinch-zoom:  ;
  --tw-scroll-snap-strictness: proximity;
  --tw-gradient-from-position:  ;
  --tw-gradient-via-position:  ;
  --tw-gradient-to-position:  ;
  --tw-ordinal:  ;
  --tw-slashed-zero:  ;
  --tw-numeric-figure:  ;
  --tw-numeric-spacing:  ;
  --tw-numeric-fraction:  ;
  --tw-ring-inset:  ;
  --tw-ring-offset-width: 0px;
  --tw-ring-offset-color: #fff;
  --tw-ring-color: rgb(59 130 246 / 0.5);
  --tw-ring-offset-shadow: 0 0 #0000;
  --tw-ring-shadow: 0 0 #0000;
  --tw-shadow: 0 0 #0000;
  --tw-shadow-colored: 0 0 #0000;
  --tw-blur:  ;
  --tw-brightness:  ;
  --tw-contrast:  ;
  --tw-grayscale:  ;
  --tw-hue-rotate:  ;
  --tw-invert:  ;
  --tw-saturate:  ;
  --tw-sepia:  ;
  --tw-drop-shadow:  ;
  --tw-backdrop-blur:  ;
  --tw-backdrop-brightness:  ;
  --tw-backdrop-contrast:  ;
  --tw-backdrop-grayscale:  ;
  --tw-backdrop-hue-rotate:  ;
  --tw-backdrop-invert:  ;
  --tw-backdrop-opacity:  ;
  --tw-backdrop-saturate:  ;
  --tw-backdrop-sepia:  ;
  --tw-contain-size:  ;
```

```
  --tw-contain-layout:  ;
  --tw-contain-paint:  ;
  --tw-contain-style:  ;
}

/*
! tailwindcss v3.4.17 | MIT License | https://tailwindcss.com
*/

/*
1. Prevent padding and border from affecting element width.
(https://github.com/mozdevs/cssremedy/issues/4)
2. Allow adding a border to an element by just adding a border-width.
(https://github.com/tailwindcss/tailwindcss/pull/116)
*/

*,
::before,
::after {
  box-sizing: border-box; /* 1 */
  border-width: 0; /* 2 */
  border-style: solid; /* 2 */
  border-color: #e5e7eb; /* 2 */
}

::before,
::after {
  --tw-content: '';
}

/*
1. Use a consistent sensible line-height in all browsers.
2. Prevent adjustments of font size after orientation changes in iOS.
3. Use a more readable tab size.
4. Use the user's configured \`sans\` font-family by default.
5. Use the user's configured \`sans\` font-feature-settings by default.
6. Use the user's configured \`sans\` font-variation-settings by default.
7. Disable tap highlights on iOS
*/

html,
:host {
  line-height: 1.5; /* 1 */
  -webkit-text-size-adjust: 100%; /* 2 */ /* 3 */
  tab-size: 4; /* 3 */
  font-family: ui-sans-serif, system-ui, sans-serif, "Apple Color Emoji", "Segoe UI Emoji", "Segoe UI
Symbol", "Noto Color Emoji"; /* 4 */
  font-feature-settings: normal; /* 5 */
  font-variation-settings: normal; /* 6 */
```

```
  -webkit-tap-highlight-color: transparent; /* 7 */
}

/*
1. Remove the margin in all browsers.
2. Inherit line-height from \`html\` so users can set them as a class directly on the \`html\` element.
*/

body {
  margin: 0; /* 1 */
  line-height: inherit; /* 2 */
}

/*
1. Add the correct height in Firefox.
2. Correct the inheritance of border color in Firefox. (https://bugzilla.mozilla.org/show_bug.cgi?
id=190655)
3. Ensure horizontal rules are visible by default.
*/

hr {
  height: 0; /* 1 */
  color: inherit; /* 2 */
  border-top-width: 1px; /* 3 */
}

/*
Add the correct text decoration in Chrome, Edge, and Safari.
*/

abbr:where([title]) {
  text-decoration: underline dotted;
}

/*
Remove the default font size and weight for headings.
*/

h1,
h2,
h3,
h4,
h5,
h6 {
  font-size: inherit;
  font-weight: inherit;
}

/*
```

```
Reset links to optimize for opt-in styling instead of opt-out.
*/

a {
  color: inherit;
  text-decoration: inherit;
}

/*
Add the correct font weight in Edge and Safari.
*/

b,
strong {
  font-weight: bolder;
}

/*
1. Use the user's configured \`mono\` font-family by default.
2. Use the user's configured \`mono\` font-feature-settings by default.
3. Use the user's configured \`mono\` font-variation-settings by default.
4. Correct the odd \`em\` font sizing in all browsers.
*/

code,
kbd,
samp,
pre {
  font-family: ui-monospace, SFMono-Regular, Menlo, Monaco, Consolas, "Liberation Mono",
"Courier New", monospace; /* 1 */
  font-feature-settings: normal; /* 2 */
  font-variation-settings: normal; /* 3 */
  font-size: 1em; /* 4 */
}

/*
Add the correct font size in all browsers.
*/

small {
  font-size: 80%;
}

/*
Prevent \`sub\` and \`sup\` elements from affecting the line height in all browsers.
*/

sub,
sup {
```

```
  font-size: 75%;
  line-height: 0;
  position: relative;
  vertical-align: baseline;
}

sub {
  bottom: -0.25em;
}

sup {
  top: -0.5em;
}

/*
1. Remove text indentation from table contents in Chrome and Safari.
(https://bugs.chromium.org/p/chromium/issues/detail?id=999088,
https://bugs.webkit.org/show_bug.cgi?id=201297)
2. Correct table border color inheritance in all Chrome and Safari.
(https://bugs.chromium.org/p/chromium/issues/detail?id=935729,
https://bugs.webkit.org/show_bug.cgi?id=195016)
3. Remove gaps between table borders by default.
*/

table {
  text-indent: 0; /* 1 */
  border-color: inherit; /* 2 */
  border-collapse: collapse; /* 3 */
}

/*
1. Change the font styles in all browsers.
2. Remove the margin in Firefox and Safari.
3. Remove default padding in all browsers.
*/

button,
input,
optgroup,
select,
textarea {
  font-family: inherit; /* 1 */
  font-feature-settings: inherit; /* 1 */
  font-variation-settings: inherit; /* 1 */
  font-size: 100%; /* 1 */
  font-weight: inherit; /* 1 */
  line-height: inherit; /* 1 */
  letter-spacing: inherit; /* 1 */
  color: inherit; /* 1 */
```

```
  margin: 0; /* 2 */
  padding: 0; /* 3 */
}

/*
Remove the inheritance of text transform in Edge and Firefox.
*/

button,
select {
  text-transform: none;
}

/*
1. Correct the inability to style clickable types in iOS and Safari.
2. Remove default button styles.
*/

button,
input:where([type='button']),
input:where([type='reset']),
input:where([type='submit']) {
  -webkit-appearance: button; /* 1 */
  background-color: transparent; /* 2 */
  background-image: none; /* 2 */
}

/*
Use the modern Firefox focus style for all focusable elements.
*/

:-moz-focusring {
  outline: auto;
}

/*
Remove the additional \`:invalid\` styles in Firefox. (https://github.com/mozilla/gecko-
dev/blob/2f9eacd9d3d995c937b4251a5557d95d494c9be1/layout/style/res/forms.css#L728-L737)
*/

:-moz-ui-invalid {
  box-shadow: none;
}

/*
Add the correct vertical alignment in Chrome and Firefox.
*/

progress {
```

```
  vertical-align: baseline;
}

/*
Correct the cursor style of increment and decrement buttons in Safari.
*/

::-webkit-inner-spin-button,
::-webkit-outer-spin-button {
  height: auto;
}

/*
1. Correct the odd appearance in Chrome and Safari.
2. Correct the outline style in Safari.
*/

[type='search'] {
  -webkit-appearance: textfield; /* 1 */
  outline-offset: -2px; /* 2 */
}

/*
Remove the inner padding in Chrome and Safari on macOS.
*/

::-webkit-search-decoration {
  -webkit-appearance: none;
}

/*
1. Correct the inability to style clickable types in iOS and Safari.
2. Change font properties to \`inherit\` in Safari.
*/

::-webkit-file-upload-button {
  -webkit-appearance: button; /* 1 */
  font: inherit; /* 2 */
}

/*
Add the correct display in Chrome and Safari.
*/

summary {
  display: list-item;
}

/*
```

```
Removes the default spacing and border for appropriate elements.
*/

blockquote,
dl,
dd,
h1,
h2,
h3,
h4,
h5,
h6,
hr,
figure,
p,
pre {
  margin: 0;
}

fieldset {
  margin: 0;
  padding: 0;
}

legend {
  padding: 0;
}

ol,
ul,
menu {
  list-style: none;
  margin: 0;
  padding: 0;
}

/*
Reset default styling for dialogs.
*/

dialog {
  padding: 0;
}

/*
Prevent resizing textareas horizontally by default.
*/

textarea {
```

```
  resize: vertical;
}

/*
1. Reset the default placeholder opacity in Firefox.
(https://github.com/tailwindlabs/tailwindcss/issues/3300)
2. Set the default placeholder color to the user's configured gray 400 color.
*/

input::placeholder,
textarea::placeholder {
  opacity: 1; /* 1 */
  color: #9ca3af; /* 2 */
}

/*
Set the default cursor for buttons.
*/

button,
[role="button"] {
  cursor: pointer;
}

/*
Make sure disabled buttons don't get the pointer cursor.
*/

:disabled {
  cursor: default;
}

/*
1. Make replaced elements \`display: block\` by default.
(https://github.com/mozdevs/cssremedy/issues/14)
2. Add \`vertical-align: middle\` to align replaced elements more sensibly by default.
(https://github.com/jensimmons/cssremedy/issues/14#issuecomment-634934210)
   This can trigger a poorly considered lint error in some tools but is included by design.
*/

img,
svg,
video,
canvas,
audio,
iframe,
embed,
object {
  display: block; /* 1 */
```

```
  vertical-align: middle; /* 2 */
}

/*
Constrain images and videos to the parent width and preserve their intrinsic aspect ratio.
(https://github.com/mozdevs/cssremedy/issues/14)
*/

img,
video {
  max-width: 100%;
  height: auto;
}

/* Make elements with the HTML hidden attribute stay hidden by default */

[hidden]:where(:not([hidden="until-found"])) {
  display: none;
}

:root {
    --background: 220 26% 8%;
    --foreground: 220 15% 92%;
    --card: 222 33% 11%;
    --card-foreground: 220 15% 92%;
    --popover: 222 33% 11%;
    --popover-foreground: 220 15% 92%;
    --primary: 186 100% 50%;

  --primary-foreground: 220 26% 8%;
    --secondary: 220 15% 22%;
    --secondary-foreground: 220 15% 92%;
    --muted: 220 15% 22%;
    --muted-foreground: 220 10% 60%;
    --accent: 40 100% 50%;
    --accent-foreground: 220 26% 8%;
    --destructive: 0 65% 55%;
    --destructive-foreground: 220 15% 92%;
    --border: 220 15% 22%;
    --input: 220 15% 22%;
    --ring: 186 100% 50%;
    --radius: 0.65rem;
  }
.sr-only{
  position: absolute;
  width: 1px;
  height: 1px;
  padding: 0;
  margin: -1px;
```

```
  overflow: hidden;
  clip: rect(0, 0, 0, 0);
  white-space: nowrap;
  border-width: 0;
}
.pointer-events-none{
  pointer-events: none;
}
.pointer-events-auto{
  pointer-events: auto;
}
.visible{
  visibility: visible;
}
.invisible{
  visibility: hidden;
}
.fixed{
  position: fixed;
}
.absolute{
  position: absolute;
}
.relative{
  position: relative;
}
.sticky{
  position: sticky;
}
.inset-0{
  inset: 0px;
}
.inset-x-0{
  left: 0px;
  right: 0px;
}
.inset-y-0{
  top: 0px;
  bottom: 0px;
}
.-bottom-12{
  bottom: -3rem;
}
.-left-12{
  left: -3rem;
}
.-right-12{
  right: -3rem;
}
```

```
.-top-12{
  top: -3rem;
}
.bottom-0{
  bottom: 0px;
}
.left-0{
  left: 0px;
}
.left-1{
  left: 0.25rem;
}
.left-1\\/2{
  left: 50%;
}
.left-2{
  left: 0.5rem;
}
.left-\\[50\\%\\]{
  left: 50%;
}
.right-0{
  right: 0px;
}
.right-1{
  right: 0.25rem;
}
.right-2{
  right: 0.5rem;
}
.right-4{
  right: 1rem;
}
.top-0{
  top: 0px;
}
.top-1{
  top: 0.25rem;
}
.top-1\\/2{
  top: 50%;
}
.top-4{
  top: 1rem;
}
.top-\\[1px\\]{
  top: 1px;
}
.top-\\[50\\%\\]{
```

```
  top: 50%;
}
.top-\\[60\\%\\]{
  top: 60%;
}
.top-full{
  top: 100%;
}
.isolate{
  isolation: isolate;
}
.z-10{
  z-index: 10;
}
.z-30{
  z-index: 30;
}
.z-50{
  z-index: 50;
}
.z-\\[100\\]{
  z-index: 100;
}
.z-\\[1\\]{
  z-index: 1;
}
.col-span-1{
  grid-column: span 1 / span 1;
}
.col-span-2{
  grid-column: span 2 / span 2;
}
.-mx-1{
  margin-left: -0.25rem;
  margin-right: -0.25rem;
}
.mx-auto{
  margin-left: auto;
  margin-right: auto;
}
.my-1{
  margin-top: 0.25rem;
  margin-bottom: 0.25rem;
}
.my-2{
  margin-top: 0.5rem;
  margin-bottom: 0.5rem;
}
.-ml-4{
```

```
  margin-left: -1rem;
}
.-mt-4{
  margin-top: -1rem;
}
.mb-1{
  margin-bottom: 0.25rem;
}
.mb-2{
  margin-bottom: 0.5rem;
}
.mb-3{
  margin-bottom: 0.75rem;
}
.ml-1{
  margin-left: 0.25rem;
}
.ml-2{
  margin-left: 0.5rem;
}
.ml-3{
  margin-left: 0.75rem;
}
.ml-auto{
  margin-left: auto;
}
.mr-2{
  margin-right: 0.5rem;
}
.mt-1{
  margin-top: 0.25rem;
}
.mt-1\\.5{
  margin-top: 0.375rem;
}
.mt-2{
  margin-top: 0.5rem;
}
.mt-24{
  margin-top: 6rem;
}
.mt-3{
  margin-top: 0.75rem;
}
.mt-4{
  margin-top: 1rem;
}
.mt-6{
  margin-top: 1.5rem;
```

```
}
.mt-8{
  margin-top: 2rem;
}
.mt-auto{
  margin-top: auto;
}
.\\!block{
  display: block !important;
}
.block{
  display: block;
}
.inline-block{
  display: inline-block;
}
.flex{
  display: flex;
}
.inline-flex{
  display: inline-flex;
}
.table{
  display: table;
}
.grid{
  display: grid;
}
.hidden{
  display: none;
}
.aspect-square{
  aspect-ratio: 1 / 1;
}
.h-1\\.5{
  height: 0.375rem;
}
.h-10{
  height: 2.5rem;
}
.h-2{
  height: 0.5rem;
}
.h-2\\.5{
  height: 0.625rem;
}
.h-3{
  height: 0.75rem;
}
```

```
.h-3\\.5{
  height: 0.875rem;
}
.h-4{
  height: 1rem;
}
.h-5{
  height: 1.25rem;
}
.h-7{
  height: 1.75rem;
}
.h-8{
  height: 2rem;
}
.h-9{
  height: 2.25rem;
}
.h-\\[1px\\]{
  height: 1px;
}
.h-\\[var\\(--radix-navigation-menu-viewport-height\\)\\]{
  height: var(--radix-navigation-menu-viewport-height);
}
.h-\\[var\\(--radix-select-trigger-height\\)\\]{
  height: var(--radix-select-trigger-height);
}
.h-auto{
  height: auto;
}
.h-full{
  height: 100%;
}
.h-px{
  height: 1px;
}
.max-h-\\[--radix-context-menu-content-available-height\\]{
  max-height: var(--radix-context-menu-content-available-height);
}
.max-h-\\[--radix-select-content-available-height\\]{
  max-height: var(--radix-select-content-available-height);
}
.max-h-\\[300px\\]{
  max-height: 300px;
}
.max-h-\\[var\\(--radix-dropdown-menu-content-available-height\\)\\]{
  max-height: var(--radix-dropdown-menu-content-available-height);
}
.max-h-screen{
```

```
  max-height: 100vh;
}
.min-h-\\[60px\\]{
  min-height: 60px;
}
.min-h-screen{
  min-height: 100vh;
}
.w-10{
  width: 2.5rem;
}
.w-2{
  width: 0.5rem;
}
.w-2\\.5{
  width: 0.625rem;
}
.w-3{
  width: 0.75rem;
}
.w-3\\.5{
  width: 0.875rem;
}
.w-3\\/4{
  width: 75%;
}
.w-4{
  width: 1rem;
}
.w-6{
  width: 1.5rem;
}
.w-64{
  width: 16rem;
}
.w-7{
  width: 1.75rem;
}
.w-72{
  width: 18rem;
}
.w-8{
  width: 2rem;
}
.w-9{
  width: 2.25rem;
}
.w-\\[100px\\]{
  width: 100px;
```

```
}
.w-\\[1px\\]{
  width: 1px;
}
.w-full{
  width: 100%;
}
.w-max{
  width: max-content;
}
.w-px{
  width: 1px;
}
.min-w-0{
  min-width: 0px;
}
.min-w-10{
  min-width: 2.5rem;
}
.min-w-8{
  min-width: 2rem;
}
.min-w-9{
  min-width: 2.25rem;
}
.min-w-\\[120px\\]{
  min-width: 120px;
}
.min-w-\\[12rem\\]{
  min-width: 12rem;
}
.min-w-\\[220px\\]{
  min-width: 220px;
}
.min-w-\\[240px\\]{
  min-width: 240px;
}
.min-w-\\[8rem\\]{
  min-width: 8rem;
}
.min-w-\\[var\\(--radix-select-trigger-width\\)\\]{
  min-width: var(--radix-select-trigger-width);
}
.max-w-2xl{
  max-width: 42rem;
}
.max-w-\\[1440px\\]{
  max-width: 1440px;
}
```

```
.max-w-full{
  max-width: 100%;
}
.max-w-lg{
  max-width: 32rem;
}
.max-w-max{
  max-width: max-content;
}
.max-w-xl{
  max-width: 36rem;
}
.flex-1{
  flex: 1 1;
}
.shrink-0{
  flex-shrink: 0;
}
.grow{
  flex-grow: 1;
}
.grow-0{
  flex-grow: 0;
}
.basis-full{
  flex-basis: 100%;
}
.caption-bottom{
  caption-side: bottom;
}
.border-collapse{
  border-collapse: collapse;
}
.origin-\\[--radix-context-menu-content-transform-origin\\]{
  transform-origin: var(--radix-context-menu-content-transform-origin);
}
.origin-\\[--radix-dropdown-menu-content-transform-origin\\]{
  transform-origin: var(--radix-dropdown-menu-content-transform-origin);
}
.origin-\\[--radix-hover-card-content-transform-origin\\]{
  transform-origin: var(--radix-hover-card-content-transform-origin);
}
.origin-\\[--radix-menubar-content-transform-origin\\]{
  transform-origin: var(--radix-menubar-content-transform-origin);
}
.origin-\\[--radix-popover-content-transform-origin\\]{
  transform-origin: var(--radix-popover-content-transform-origin);
}
.origin-\\[--radix-select-content-transform-origin\\]{
```

```
  transform-origin: var(--radix-select-content-transform-origin);
}
.origin-\\[--radix-tooltip-content-transform-origin\\]{
  transform-origin: var(--radix-tooltip-content-transform-origin);
}
.-translate-x-1\\/2{
  --tw-translate-x: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.-translate-y-1\\/2{
  --tw-translate-y: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.translate-x-\\[-50\\%\\]{
  --tw-translate-x: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.translate-y-\\[-50\\%\\]{
  --tw-translate-y: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.rotate-45{
  --tw-rotate: 45deg;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.rotate-90{
  --tw-rotate: 90deg;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
.transform{
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}
@keyframes pulse{

  50%{
    opacity: .5;
  }
}
.animate-pulse{
  animation: pulse 2s cubic-bezier(0.4, 0, 0.6, 1) infinite;
}
.cursor-default{
```

```
  cursor: default;
}
.cursor-pointer{
  cursor: pointer;
}
.touch-none{
  touch-action: none;
}
.select-none{
  -webkit-user-select: none;
          user-select: none;
}
.list-none{
  list-style-type: none;
}
.grid-cols-1{
  grid-template-columns: repeat(1, minmax(0, 1fr));
}
.grid-cols-2{
  grid-template-columns: repeat(2, minmax(0, 1fr));
}
.grid-cols-3{
  grid-template-columns: repeat(3, minmax(0, 1fr));
}
.flex-row{
  flex-direction: row;
}
.flex-col{
  flex-direction: column;
}
.flex-col-reverse{
  flex-direction: column-reverse;
}
.flex-wrap{
  flex-wrap: wrap;
}
.items-start{
  align-items: flex-start;
}
.items-end{
  align-items: flex-end;
}
.items-center{
  align-items: center;
}
.items-baseline{
  align-items: baseline;
}
.justify-end{
```

```
  justify-content: flex-end;
}
.justify-center{
  justify-content: center;
}
.justify-between{
  justify-content: space-between;
}
.gap-1{
  gap: 0.25rem;
}
.gap-1\\.5{
  gap: 0.375rem;
}
.gap-2{
  gap: 0.5rem;
}
.gap-3{
  gap: 0.75rem;
}
.gap-4{
  gap: 1rem;
}
.gap-5{
  gap: 1.25rem;
}
.gap-6{
  gap: 1.5rem;
}
.space-x-1 > :not([hidden]) ~ :not([hidden]){
  --tw-space-x-reverse: 0;
  margin-right: calc(0.25rem * var(--tw-space-x-reverse));
  margin-left: calc(0.25rem * calc(1 - var(--tw-space-x-reverse)));
}
.space-x-2 > :not([hidden]) ~ :not([hidden]){
  --tw-space-x-reverse: 0;
  margin-right: calc(0.5rem * var(--tw-space-x-reverse));
  margin-left: calc(0.5rem * calc(1 - var(--tw-space-x-reverse)));
}
.space-y-1 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(0.25rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(0.25rem
 * var(--tw-space-y-reverse));
}
.space-y-1\\.5 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(0.375rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(0.375rem * var(--tw-space-y-reverse));
```

```
}
.space-y-2 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(0.5rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(0.5rem * var(--tw-space-y-reverse));
}
.space-y-4 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(1rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(1rem * var(--tw-space-y-reverse));
}
.space-y-6 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(1.5rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(1.5rem * var(--tw-space-y-reverse));
}
.space-y-8 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(2rem * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(2rem * var(--tw-space-y-reverse));
}
.overflow-auto{
  overflow: auto;
}
.overflow-hidden{
  overflow: hidden;
}
.overflow-y-auto{
  overflow-y: auto;
}
.overflow-x-hidden{
  overflow-x: hidden;
}
.truncate{
  overflow: hidden;
  text-overflow: ellipsis;
  white-space: nowrap;
}
.whitespace-nowrap{
  white-space: nowrap;
}
.break-words{
  overflow-wrap: break-word;
}
.break-all{
  word-break: break-all;
}
.rounded{
  border-radius: 0.25rem;
```

```
}
.rounded-\\[inherit\\]{
  border-radius: inherit;
}
.rounded-full{
  border-radius: 9999px;
}
.rounded-lg{
  border-radius: var(--radius);
}
.rounded-md{
  border-radius: calc(var(--radius) - 2px);
}
.rounded-sm{
  border-radius: calc(var(--radius) - 4px);
}
.rounded-xl{
  border-radius: 0.75rem;
}
.rounded-t-\\[10px\\]{
  border-top-left-radius: 10px;
  border-top-right-radius: 10px;
}
.rounded-tl-sm{
  border-top-left-radius: calc(var(--radius) - 4px);
}
.border{
  border-width: 1px;
}
.border-2{
  border-width: 2px;
}
.border-y{
  border-top-width: 1px;
  border-bottom-width: 1px;
}
.border-b{
  border-bottom-width: 1px;
}
.border-l{
  border-left-width: 1px;
}
.border-r{
  border-right-width: 1px;
}
.border-t{
  border-top-width: 1px;
}
.border-destructive{
```

```
  border-color: hsl(var(--destructive));
}
.border-destructive\\/50{
  border-color: hsl(var(--destructive) / 0.5);
}
.border-input{
  border-color: hsl(var(--input));
}
.border-primary{
  border-color: hsl(var(--primary));
}
.border-primary\\/50{
  border-color: hsl(var(--primary) / 0.5);
}
.border-transparent{
  border-color: transparent;
}
.border-l-transparent{
  border-left-color: transparent;
}
.border-t-transparent{
  border-top-color: transparent;
}
.bg-accent{
  background-color: hsl(var(--accent));
}
.bg-background{
  background-color: hsl(var(--background));
}
.bg-black\\/80{
  background-color: rgb(0 0 0 / 0.8);
}
.bg-border{
  background-color: hsl(var(--border));
}
.bg-card{
  background-color: hsl(var(--card));
}
.bg-destructive{
  background-color: hsl(var(--destructive));
}
.bg-foreground{
  background-color: hsl(var(--foreground));
}
.bg-muted{
  background-color: hsl(var(--muted));
}
.bg-muted\\/50{
  background-color: hsl(var(--muted) / 0.5);
```

```
}
.bg-popover{
  background-color: hsl(var(--popover));
}
.bg-primary{
  background-color: hsl(var(--primary));
}
.bg-primary\\/10{
  background-color: hsl(var(--primary) / 0.1);
}
.bg-primary\\/20{
  background-color: hsl(var(--primary) / 0.2);
}
.bg-secondary{
  background-color: hsl(var(--secondary));
}
.bg-transparent{
  background-color: transparent;
}
.fill-current{
  fill: currentColor;
}
.fill-primary{
  fill: hsl(var(--primary));
}
.p-0{
  padding: 0px;
}
.p-1{
  padding: 0.25rem;
}
.p-2{
  padding: 0.5rem;
}
.p-3{
  padding: 0.75rem;
}
.p-4{
  padding: 1rem;
}
.p-5{
  padding: 1.25rem;
}
.p-6{
  padding: 1.5rem;
}
.p-8{
  padding: 2rem;
}
```

```
.p-\\[1px\\]{
  padding: 1px;
}
.px-1\\.5{
  padding-left: 0.375rem;
  padding-right: 0.375rem;
}
.px-2{
  padding-left: 0.5rem;
  padding-right: 0.5rem;
}
.px-2\\.5{
  padding-left: 0.625rem;
  padding-right: 0.625rem;
}
.px-3{
  padding-left: 0.75rem;
  padding-right: 0.75rem;
}
.px-4{
  padding-left: 1rem;
  padding-right: 1rem;
}
.px-6{
  padding-left: 1.5rem;
  padding-right: 1.5rem;
}
.px-8{
  padding-left: 2rem;
  padding-right: 2rem;
}
.py-0\\.5{
  padding-top: 0.125rem;
  padding-bottom: 0.125rem;
}
.py-1{
  padding-top: 0.25rem;
  padding-bottom: 0.25rem;
}
.py-1\\.5{
  padding-top: 0.375rem;
  padding-bottom: 0.375rem;
}
.py-2{
  padding-top: 0.5rem;
  padding-bottom: 0.5rem;
}
.py-3{
  padding-top: 0.75rem;
```

```
  padding-bottom: 0.75rem;
}
.py-4{
  padding-top: 1rem;
  padding-bottom: 1rem;
}
.py-6{
  padding-top: 1.5rem;
  padding-bottom: 1.5rem;
}
.py-8{
  padding-top: 2rem;
  padding-bottom: 2rem;
}
.pb-4{
  padding-bottom: 1rem;
}
.pl-2{
  padding-left: 0.5rem;
}
.pl-2\\.5{
  padding-left: 0.625rem;
}
.pl-4{
  padding-left: 1rem;
}
.pl-8{
  padding-left: 2rem;
}
.pr-2{
  padding-right: 0.5rem;
}
.pr-2\\.5{
  padding-right: 0.625rem;
}
.pr-6{
  padding-right: 1.5rem;
}
.pr-8{
  padding-right: 2rem;
}
.pt-0{
  padding-top: 0px;
}
.pt-1{
  padding-top: 0.25rem;
}
.pt-4{
  padding-top: 1rem;
```

```
}
.text-left{
  text-align: left;
}
.text-center{
  text-align: center;
}
.align-middle{
  vertical-align: middle;
}
.font-mono{
  font-family: ui-monospace, SFMono-Regular, Menlo, Monaco, Consolas, "Liberation Mono",
"Courier New", monospace;
}
.text-2xl{
  font-size: 1.5rem;
  line-height: 2rem;
}
.text-4xl{
  font-size: 2.25rem;
  line-height: 2.5rem;
}
.text-\\[0\\.8rem\\]{
  font-size: 0.8rem;
}
.text-base{
  font-size: 1rem;
  line-height: 1.5rem;
}
.text-lg{
  font-size: 1.125rem;
  line-height: 1.75rem;
}
.text-sm{
  font-size: 0.875rem;
  line-height: 1.25rem;
}
.text-xl{
  font-size: 1.25rem;
  line-height: 1.75rem;
}
.text-xs{
  font-size: 0.75rem;
  line-height: 1rem;
}
.font-bold{
  font-weight: 700;
}
.font-extrabold{
```

```
  font-weight: 800;
}
.font-medium{
  font-weight: 500;
}
.font-normal{
  font-weight: 400;
}
.font-semibold{
  font-weight: 600;
}
.leading-none{
  line-height: 1;
}
.leading-tight{
  line-height: 1.25;
}
.tracking-tight{
  letter-spacing: -0.025em;
}
.tracking-widest{
  letter-spacing: 0.1em;
}
.text-accent-foreground{
  color: hsl(var(--accent-foreground));
}
.text-card-foreground{
  color: hsl(var(--card-foreground));
}
.text-current{
  color: currentColor;
}
.text-destructive{
  color: hsl(var(--destructive));
}
.text-destructive-foreground{
  color: hsl(var(--destructive-foreground));
}
.text-foreground{
  color: hsl(var(--foreground));
}
.text-foreground\\/50{
  color: hsl(var(--foreground) / 0.5);
}
.text-muted-foreground{
  color: hsl(var(--muted-foreground));
}
.text-popover-foreground{
  color: hsl(var(--popover-foreground));
```

```
}
.text-primary{
  color: hsl(var(--primary));
}
.text-primary-foreground{
  color: hsl(var(--primary-foreground));
}
.text-secondary-foreground{
  color: hsl(var(--secondary-foreground));
}
.underline-offset-4{
  text-underline-offset: 4px;
}
.opacity-0{
  opacity: 0;
}
.opacity-50{
  opacity: 0.5;
}
.opacity-60{
  opacity: 0.6;
}
.opacity-70{
  opacity: 0.7;
}
.opacity-90{
  opacity: 0.9;
}
.shadow{
  --tw-shadow: 0 1px 3px 0 rgb(0 0 0 / 0.1), 0 1px 2px -1px rgb(0 0 0 / 0.1);
  --tw-shadow-colored: 0 1px 3px 0 var(--tw-shadow-color), 0 1px 2px -1px var(--tw-shadow-color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
.shadow-lg{
  --tw-shadow: 0 10px 15px -3px rgb(0 0 0 / 0.1), 0 4px 6px -4px rgb(0 0 0 / 0.1);
  --tw-shadow-colored: 0 10px 15px -3px var(--tw-shadow-color), 0 4px 6px -4px var(--tw-shadow-
color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
.shadow-md{
  --tw-shadow: 0 4px 6px -1px rgb(0 0 0 / 0.1), 0 2px 4px -2px rgb(0 0 0 / 0.1);
  --tw-shadow-colored: 0 4px 6px -1px var(--tw-shadow-color), 0 2px 4px -2px var(--tw-shadow-
color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
.shadow-sm{
```

```
  --tw-shadow: 0 1px 2px 0 rgb(0 0 0 / 0.05);
  --tw-shadow-colored: 0 1px 2px 0 var(--tw-shadow-color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
.outline-none{
  outline: 2px solid transparent;
  outline-offset: 2px;
}
.outline{
  outline-style: solid;
}
.ring{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-
color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(3px + var(--tw-ring-offset-width)) var(--tw-ring-
color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}
.ring-0{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-
color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(0px + var(--tw-ring-offset-width)) var(--tw-ring-
color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}
.ring-1{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-
color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(1px + var(--tw-ring-offset-width)) var(--tw-ring-
color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}
.ring-ring{
  --tw-ring-color: hsl(var(--ring));
}
.ring-offset-background{
  --tw-ring-offset-color: hsl(var(--background));
}
.blur{
  --tw-blur: blur(8px);
  filter: var(--tw-blur) var(--tw-brightness) var(--tw-contrast) var(--tw-grayscale) var(--tw-hue-rotate)
var(--tw-invert) var(--tw-saturate) var(--tw-sepia) var(--tw-drop-shadow);
}
.invert{
  --tw-invert: invert(100%);
  filter: var(--tw-blur) var(--tw-brightness) var(--tw-contrast) var(--tw-grayscale) var(--tw-hue-rotate)
var(--tw-invert) var(--tw-saturate) var(--tw-sepia)
 var(--tw-drop-shadow);
```

```
}
.filter{
  filter: var(--tw-blur) var(--tw-brightness) var(--tw-contrast) var(--tw-grayscale) var(--tw-hue-rotate) var(--tw-invert) var(--tw-saturate) var(--tw-sepia) var(--tw-drop-shadow);
}
.transition{
  transition-property: color, background-color, border-color, text-decoration-color, fill, stroke, opacity, box-shadow, transform, filter, backdrop-filter;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  transition-duration: 150ms;
}
.transition-all{
  transition-property: all;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  transition-duration: 150ms;
}
.transition-colors{
  transition-property: color, background-color, border-color, text-decoration-color, fill, stroke;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  transition-duration: 150ms;
}
.transition-opacity{
  transition-property: opacity;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  transition-duration: 150ms;
}
.transition-transform{
  transition-property: transform;
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
  transition-duration: 150ms;
}
.duration-1000{
  transition-duration: 1000ms;
}
.duration-200{
  transition-duration: 200ms;
}
.duration-300{
  transition-duration: 300ms;
}
.ease-in-out{
  transition-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
}
@keyframes enter{

  from{
    opacity: var(--tw-enter-opacity, 1);
    transform: translate3d(var(--tw-enter-translate-x, 0), var(--tw-enter-translate-y, 0), 0) scale3d(var(--tw-enter-scale, 1), var(--tw-enter-scale, 1), var(--tw-enter-scale, 1)) rotate(var(--tw-enter-rotate, 0));
```

```
  }
}
@keyframes exit{

  to{
    opacity: var(--tw-exit-opacity, 1);
    transform: translate3d(var(--tw-exit-translate-x, 0), var(--tw-exit-translate-y, 0), 0) scale3d(var(--tw-exit-scale, 1), var(--tw-exit-scale, 1), var(--tw-exit-scale, 1)) rotate(var(--tw-exit-rotate, 0));
  }
}
.animate-in{
  animation-name: enter;
  animation-duration: 150ms;
  --tw-enter-opacity: initial;
  --tw-enter-scale: initial;
  --tw-enter-rotate: initial;
  --tw-enter-translate-x: initial;
  --tw-enter-translate-y: initial;
}
.fade-in-0{
  --tw-enter-opacity: 0;
}
.zoom-in-95{
  --tw-enter-scale: .95;
}
.duration-1000{
  animation-duration: 1000ms;
}
.duration-200{
  animation-duration: 200ms;
}
.duration-300{
  animation-duration: 300ms;
}
.ease-in-out{
  animation-timing-function: cubic-bezier(0.4, 0, 0.2, 1);
}
.running{
  animation-play-state: running;
}

:root {
  --ink-0: #05070d;
  --ink-1: #0b0f19;
  --ink-2: #111827;
  --ink-3: #1f2937;
  --line: rgba(255, 255, 255, 0.08);
  --line-strong: rgba(255, 255, 255, 0.14);
  --teal: #00f0ff;
```

```
  --teal-soft: rgba(0, 240, 255, 0.14);
  --amber: #ffb000;
  --amber-soft: rgba(255, 176, 0, 0.14);
  --magenta: #e024a6;
  --text: #e5e7eb;
  --muted: #9ca3af;
  --dim: #6b7280;
}

* { border-color: var(--line); }

html, body, #root { background: var(--ink-1); }

body {
  margin: 0;
  color: var(--text);
  font-family: "Inter", -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
  -webkit-font-smoothing: antialiased;
  -moz-osx-font-smoothing: grayscale;
  background:
    radial-gradient(1200px 700px at 12% -10%, rgba(0, 240, 255, 0.08), transparent 60%),
    radial-gradient(900px 600px at 88% 10%, rgba(255, 176, 0, 0.06), transparent 60%),
    var(--ink-1);
  background-attachment: fixed;
  min-height: 100vh;
}

.font-heading { font-family: "Outfit", sans-serif; letter-spacing: -0.01em; }
.font-mono { font-family: "JetBrains Mono", "Fira Code", monospace; }

.eyebrow {
  font-family: "JetBrains Mono", monospace;
  font-size: 11px;
  letter-spacing: 0.24em;
  text-transform: uppercase;
  color: rgba(0, 240, 255, 0.7);
}

.panel {
  background: linear-gradient(180deg, rgba(31, 41, 55, 0.55), rgba(17, 24, 39, 0.55));
  border: 1px solid var(--line);
  border-radius: 12px;
  backdrop-filter: blur(6px);
}
.panel-strong {
  background: rgba(17, 24, 39, 0.9);
  border: 1px solid var(--line-strong);
  border-radius: 12px;
}
```

```
.pill {
  display: inline-flex;
  align-items: center;
  gap: 6px;
  padding: 3px 10px;
  border-radius: 999px;
  border: 1px solid var(--line);
  background: rgba(255,255,255,0.03);
  font-family: "JetBrains Mono", monospace;
  font-size: 11px;
  color: var(--muted);
}

.lego {
  display: inline-block;
  padding: 6px 8px;
  margin: 3px;
  border-radius: 6px;
  font-family: "JetBrains Mono", monospace;
  font-size: 12px;
  line-height: 1.2;
  border: 1px solid;
  position: relative;
  cursor: pointer;
  transition: transform 120ms ease, box-shadow 200ms ease, filter 200ms ease;
  white-space: nowrap;
  box-shadow: inset 0 1px 0 rgba(255,255,255,0.06), 0 1px 0 rgba(0,0,0,0.5);
}
.lego:hover { transform: translateY(-1px); filter: brightness(1.12); }
.lego.selected { outline: 2px solid var(--teal); outline-offset: 2px; }

.depth-ring {
  position: absolute;
  top: -3px; right: -3px;
  min-width: 14px; height: 14px;
  padding: 0 4px;
  border-radius: 999px;
  background: var(--ink-2);
  color: var(--teal);
  border: 1px solid var(--teal);
  font-size: 9px;
  display: inline-flex;
  align-items: center;
  justify-content: center;
  box-shadow: 0 0 8px rgba(0, 240, 255, 0.35);
}

.mirror-bar {
```

```
  display: inline-block;
  width: 2px;
  height: 20px;
  margin: 0 3px;
  vertical-align: middle;
  background: linear-gradient(180deg, transparent, var(--amber), transparent);
  border-radius: 2px;
  opacity: 0.85;
}

.btn {
  display: inline-flex;
  align-items: center;
  gap: 8px;
  padding: 8px 14px;
  border-radius: 999px;
  border: 1px solid var(--line-strong);
  background: rgba(31,41,55,0.6);
  color: var(--text);
  font-weight: 500;
  transition: all 160ms ease;
  cursor: pointer;
  font-size: 13px;
}
.btn:hover { border-color: rgba(0, 240, 255, 0.4); box-shadow: 0 0 0 3px rgba(0, 240, 255, 0.06); }
.btn-primary {
  background: var(--teal);
  color: #05070d;
  border-color: var(--teal);
  font-weight: 700;
}
.btn-primary:hover { box-shadow: 0 0 24px rgba(0, 240, 255, 0.35); }
.btn-amber {
  background: var(--amber);
  color: #05070d;
  border-color: var(--amber);
  font-weight: 700;
}
.btn-ghost {
  background: transparent;
  border: 1px dashed var(--line-strong);
}
.btn:disabled { opacity: 0.5; cursor: not-allowed; }

.input, .select, .textarea {
  background: rgba(5,7,13,0.6);
  border: 1px solid var(--line);
  color: var(--text);
  border-radius: 10px;
```

```
  padding: 9px 12px;
  font-family: "JetBrains Mono", monospace;
  font-size: 13px;
  width: 100%;
  outline: none;
}
.textarea { min-height: 120px; resize: vertical; }
.input:focus, .select:focus, .textarea:focus {
  border-color: var(--teal);
  box-shadow: 0 0 0 3px rgba(0, 240, 255, 0.12);
}

.range { -webkit-appearance: none; height: 4px; background: var(--line-strong); border-radius: 2px; }
.range::-webkit-slider-thumb {
  -webkit-appearance: none; width: 14px; height: 14px; border-radius: 50%;
  background: var(--teal); box-shadow: 0 0 8px rgba(0, 240, 255, 0.4);
}

.tab {
  padding: 8px 14px;
  border-radius: 999px;
  border: 1px solid transparent;
  color: var(--muted);
  font-weight: 500;
  cursor: pointer;
  transition: all 160ms;
  font-size: 13px;
}
.tab:hover { color: var(--text); }
.tab.active {
  background: rgba(0, 240, 255, 0.08);
  color: var(--teal);
  border-color: rgba(0, 240, 255, 0.28);
}

.stat {
  padding: 10px 14px;
  border-right: 1px dashed var(--line);
}
.stat:last-child { border-right: none; }
.stat .label { font-family: "JetBrains Mono", monospace; font-size: 10px; letter-spacing: 0.18em; color:
var(--dim); text-transform: uppercase; }
.stat .value { font-family: "Outfit", sans-serif; font-size: 22px; color: var(--text); font-weight: 600; }
.stat .value.teal { color: var(--teal); }

.scroll-x { overflow-x: auto; }
.scroll-x::-webkit-scrollbar { height: 8px; }
.scroll-x::-webkit-scrollbar-thumb { background: var(--line-strong); border-radius: 8px; }
```

```
.grid-bg {
  background-image:
    linear-gradient(rgba(255,255,255,0.03) 1px, transparent 1px),
    linear-gradient(90deg, rgba(255,255,255,0.03) 1px, transparent 1px);
  background-size: 32px 32px;
}

.file\\:border-0::file-selector-button{
  border-width: 0px;
}

.file\\:bg-transparent::file-selector-button{
  background-color: transparent;
}

.file\\:text-sm::file-selector-button{
  font-size: 0.875rem;
  line-height: 1.25rem;
}

.file\\:font-medium::file-selector-button{
  font-weight: 500;
}

.file\\:text-foreground::file-selector-button{
  color: hsl(var(--foreground));
}

.placeholder\\:text-muted-foreground::placeholder{
  color: hsl(var(--muted-foreground));
}

.after\\:absolute::after{
  content: var(--tw-content);
  position: absolute;
}

.after\\:inset-y-0::after{
  content: var(--tw-content);
  top: 0px;
  bottom: 0px;
}

.after\\:left-1\\/2::after{
  content: var(--tw-content);
  left: 50%;
}

.after\\:w-1::after{
```

```
  content: var(--tw-content);
  width: 0.25rem;
}

.after\\:-translate-x-1\\/2::after{
  content: var(--tw-content);
  --tw-translate-x: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.first\\:rounded-l-md:first-child{
  border-top-left-radius: calc(var(--radius) - 2px);
  border-bottom-left-radius: calc(var(--radius) - 2px);
}

.first\\:border-l:first-child{
  border-left-width: 1px;
}

.last\\:rounded-r-md:last-child{
  border-top-right-radius: calc(var(--radius) - 2px);
  border-bottom-right-radius: calc(var(--radius) - 2px);
}

.focus-within\\:relative:focus-within{
  position: relative;
}

.focus-within\\:z-20:focus-within{
  z-index: 20;
}

.hover\\:bg-accent:hover{
  background-color: hsl(var(--accent));
}

.hover\\:bg-destructive\\/80:hover{
  background-color: hsl(var(--destructive) / 0.8);
}

.hover\\:bg-destructive\\/90:hover{
  background-color: hsl(var(--destructive)
 / 0.9);
}

.hover\\:bg-muted:hover{
  background-color: hsl(var(--muted));
}
```

```
.hover\\:bg-muted\\/50:hover{
  background-color: hsl(var(--muted) / 0.5);
}

.hover\\:bg-primary:hover{
  background-color: hsl(var(--primary));
}

.hover\\:bg-primary\\/80:hover{
  background-color: hsl(var(--primary) / 0.8);
}

.hover\\:bg-primary\\/90:hover{
  background-color: hsl(var(--primary) / 0.9);
}

.hover\\:bg-secondary:hover{
  background-color: hsl(var(--secondary));
}

.hover\\:bg-secondary\\/80:hover{
  background-color: hsl(var(--secondary) / 0.8);
}

.hover\\:text-accent-foreground:hover{
  color: hsl(var(--accent-foreground));
}

.hover\\:text-foreground:hover{
  color: hsl(var(--foreground));
}

.hover\\:text-muted-foreground:hover{
  color: hsl(var(--muted-foreground));
}

.hover\\:text-primary-foreground:hover{
  color: hsl(var(--primary-foreground));
}

.hover\\:underline:hover{
  text-decoration-line: underline;
}

.hover\\:opacity-100:hover{
  opacity: 1;
}
```

```
.focus\\:bg-accent:focus{
  background-color: hsl(var(--accent));
}

.focus\\:bg-primary:focus{
  background-color: hsl(var(--primary));
}

.focus\\:text-accent-foreground:focus{
  color: hsl(var(--accent-foreground));
}

.focus\\:text-primary-foreground:focus{
  color: hsl(var(--primary-foreground));
}

.focus\\:opacity-100:focus{
  opacity: 1;
}

.focus\\:outline-none:focus{
  outline: 2px solid transparent;
  outline-offset: 2px;
}

.focus\\:ring-1:focus{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-
color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(1px + var(--tw-ring-offset-width)) var(--tw-ring-
color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}

.focus\\:ring-2:focus{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-
color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(2px + var(--tw-ring-offset-width)) var(--tw-ring-
color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}

.focus\\:ring-ring:focus{
  --tw-ring-color: hsl(var(--ring));
}

.focus\\:ring-offset-2:focus{
  --tw-ring-offset-width: 2px;
}
```

```
.focus-visible\\:outline-none:focus-visible{
  outline: 2px solid transparent;
  outline-offset: 2px;
}

.focus-visible\\:ring-1:focus-visible{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(1px + var(--tw-ring-offset-width)) var(--tw-ring-color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}

.focus-visible\\:ring-2:focus-visible{
  --tw-ring-offset-shadow: var(--tw-ring-inset) 0 0 0 var(--tw-ring-offset-width) var(--tw-ring-offset-color);
  --tw-ring-shadow: var(--tw-ring-inset) 0 0 0 calc(2px + var(--tw-ring-offset-width)) var(--tw-ring-color);
  box-shadow: var(--tw-ring-offset-shadow), var(--tw-ring-shadow), var(--tw-shadow, 0 0 #0000);
}

.focus-visible\\:ring-ring:focus-visible{
  --tw-ring-color: hsl(var(--ring));
}

.focus-visible\\:ring-offset-1:focus-visible{
  --tw-ring-offset-width: 1px;
}

.focus-visible\\:ring-offset-2:focus-visible{
  --tw-ring-offset-width: 2px;
}

.focus-visible\\:ring-offset-background:focus-visible{
  --tw-ring-offset-color: hsl(var(--background));
}

.disabled\\:pointer-events-none:disabled{
  pointer-events: none;
}

.disabled\\:cursor-not-allowed:disabled{
  cursor: not-allowed;
}

.disabled\\:opacity-50:disabled{
  opacity: 0.5;
}
```

```
.group:hover .group-hover\\:opacity-100{
  opacity: 1;
}

.group.destructive .group-\\[\\.destructive\\]\\:border-muted\\/40{
  border-color: hsl(var(--muted) / 0.4);
}

.group.toaster .group-\\[\\.toaster\\]\\:border-border{
  border-color: hsl(var(--border));
}

.group.toast .group-\\[\\.toast\\]\\:bg-muted{
  background-color: hsl(var(--muted));
}

.group.toast .group-\\[\\.toast\\]\\:bg-primary{
  background-color: hsl(var(--primary));
}

.group.toaster .group-\\[\\.toaster\\]\\:bg-background{
  background-color: hsl(var(--background));
}

.group.destructive .group-\\[\\.destructive\\]\\:text-red-300{
  --tw-text-opacity: 1;
  color: rgb(252 165 165 / var(--tw-text-opacity, 1));
}

.group.toast .group-\\[\\.toast\\]\\:text-muted-foreground{
  color: hsl(var(--muted-foreground));
}

.group.toast .group-\\[\\.toast\\]\\:text-primary-foreground{
  color: hsl(var(--primary-foreground));
}

.group.toaster .group-\\[\\.toaster\\]\\:text-foreground{
  color: hsl(var(--foreground));
}

.group.toaster .group-\\[\\.toaster\\]\\:shadow-lg{
  --tw-shadow: 0 10px 15px -3px rgb(0 0 0 / 0.1), 0 4px 6px -4px rgb(0 0 0 / 0.1);
  --tw-shadow-colored: 0 10px 15px -3px var(--tw-shadow-color), 0 4px 6px -4px var(--tw-shadow-
color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
```

```
.group.destructive .group-\\[\\.destructive\\]\\:hover\\:border-destructive\\/30:hover{
  border-color: hsl(var(--destructive) / 0.3);
}

.group.destructive .group-\\[\\.destructive\\]\\:hover\\:bg-destructive:hover{
  background-color: hsl(var(--destructive));
}

.group.destructive .group-\\[\\.destructive\\]\\:hover\\:text-destructive-foreground:hover{
  color: hsl(var(--destructive-foreground));
}

.group.destructive .group-\\[\\.destructive\\]\\:hover\\:text-red-50:hover{
  --tw-text-opacity: 1;
  color: rgb(254 242 242 / var(--tw-text-opacity, 1));
}

.group.destructive .group-\\[\\.destructive\\]\\:focus\\:ring-destructive:focus{
  --tw-ring-color: hsl(var(--destructive));
}

.group.destructive .group-\\[\\.destructive\\]\\:focus\\:ring-red-400:focus{
  --tw-ring-opacity: 1;
  --tw-ring-color: rgb(248 113 113 / var(--tw-ring-opacity, 1));
}

.group.destructive .group-\\[\\.destructive\\]\\:focus\\:ring-offset-red-600:focus{
  --tw-ring-offset-color: #dc2626;
}

.peer:disabled ~ .peer-disabled\\:cursor-not-allowed{
  cursor: not-allowed;
}

.peer:disabled ~ .peer-disabled\\:opacity-70{
  opacity: 0.7;
}

.has-\\[\\:disabled\\]\\:opacity-50:has(:disabled){
  opacity: 0.5;
}

.aria-selected\\:bg-accent[aria-selected="true"]{
  background-color: hsl(var(--accent));
}

.aria-selected\\:bg-accent\\/50[aria-selected="true"]{
  background-color: hsl(var(--accent) / 0.5);
}
```

```
.aria-selected\\:text-accent-foreground[aria-selected="true"]{
  color: hsl(var(--accent-foreground));
}

.aria-selected\\:text-muted-foreground[aria-selected="true"]{
  color: hsl(var(--muted-foreground));
}

.aria-selected\\:opacity-100[aria-selected="true"]{
  opacity: 1;
}

.data-\\[disabled\\=true\\]\\:pointer-events-none[data-disabled="true"]{
  pointer-events: none;
}

.data-\\[disabled\\]\\:pointer-events-none[data-disabled]{
  pointer-events: none;
}

.data-\\[panel-group-direction\\=vertical\\]\\:h-px[data-panel-group-direction="vertical"]{
  height: 1px;
}

.data-\\[panel-group-direction\\=vertical\\]\\:w-full[data-panel-group-direction="vertical"]{
  width: 100%;
}

.data-\\[side\\=bottom\\]\\:translate-y-1[data-side="bottom"]{
  --tw-translate-y: 0.25rem;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[side\\=left\\]\\:-translate-x-1[data-side="left"]{
  --tw-translate-x: -0.25rem;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[side\\=right\\]\\:translate-x-1[data-side="right"]{
  --tw-translate-x: 0.25rem;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[side\\=top\\]\\:-translate-y-1[data-side="top"]{
  --tw-translate-y: -0.25rem;
```

```
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[state\\=checked\\]\\:translate-x-4[data-state="checked"]{
  --tw-translate-x: 1rem;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[state\\=unchecked\\]\\:translate-x-0[data-state="unchecked"]{
  --tw-translate-x: 0px;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[swipe\\=cancel\\]\\:translate-x-0[data-swipe="cancel"]{
  --tw-translate-x: 0px;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[swipe\\=end\\]\\:translate-x-\\[var\\(--radix-toast-swipe-end-x\\)\\][data-swipe="end"]{
  --tw-translate-x: var(--radix-toast-swipe-end-x);
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[swipe\\=move\\]\\:translate-x-\\[var\\(--radix-toast-swipe-move-x\\)\\][data-swipe="move"]{
  --tw-translate-x: var(--radix-toast-swipe-move-x);
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

@keyframes accordion-up{

  from{
    height: var(--radix-accordion-content-height);
  }

  to{
    height: 0;
  }
}

.data-\\[state\\=closed\\]\\:animate-accordion-up[data-state="closed"]{

  animation: accordion-up 0.2s ease-out;
}
```

```
@keyframes accordion-down{

  from{
    height: 0;
  }

  to{
    height: var(--radix-accordion-content-height);
  }
}

.data-\\[state\\=open\\]\\:animate-accordion-down[data-state="open"]{
  animation: accordion-down 0.2s ease-out;
}

.data-\\[panel-group-direction\\=vertical\\]\\:flex-col[data-panel-group-direction="vertical"]{
  flex-direction: column;
}

.data-\\[selected\\=true\\]\\:bg-accent[data-selected="true"]{
  background-color: hsl(var(--accent));
}

.data-\\[state\\=active\\]\\:bg-background[data-state="active"]{
  background-color: hsl(var(--background));
}

.data-\\[state\\=checked\\]\\:bg-primary[data-state="checked"]{
  background-color: hsl(var(--primary));
}

.data-\\[state\\=on\\]\\:bg-accent[data-state="on"]{
  background-color: hsl(var(--accent));
}

.data-\\[state\\=open\\]\\:bg-accent[data-state="open"]{
  background-color: hsl(var(--accent));
}

.data-\\[state\\=open\\]\\:bg-accent\\/50[data-state="open"]{
  background-color: hsl(var(--accent) / 0.5);
}

.data-\\[state\\=open\\]\\:bg-secondary[data-state="open"]{
  background-color: hsl(var(--secondary));
}

.data-\\[state\\=selected\\]\\:bg-muted[data-state="selected"]{
```

```
  background-color: hsl(var(--muted));
}

.data-\\[state\\=unchecked\\]\\:bg-input[data-state="unchecked"]{
  background-color: hsl(var(--input));
}

.data-\\[placeholder\\]\\:text-muted-foreground[data-placeholder]{
  color: hsl(var(--muted-foreground));
}

.data-\\[selected\\=true\\]\\:text-accent-foreground[data-selected="true"]{
  color: hsl(var(--accent-foreground));
}

.data-\\[state\\=active\\]\\:text-foreground[data-state="active"]{
  color: hsl(var(--foreground));
}

.data-\\[state\\=checked\\]\\:text-primary-foreground[data-state="checked"]{
  color: hsl(var(--primary-foreground));
}

.data-\\[state\\=on\\]\\:text-accent-foreground[data-state="on"]{
  color: hsl(var(--accent-foreground));
}

.data-\\[state\\=open\\]\\:text-accent-foreground[data-state="open"]{
  color: hsl(var(--accent-foreground));
}

.data-\\[state\\=open\\]\\:text-muted-foreground[data-state="open"]{
  color: hsl(var(--muted-foreground));
}

.data-\\[disabled\\=true\\]\\:opacity-50[data-disabled="true"]{
  opacity: 0.5;
}

.data-\\[disabled\\]\\:opacity-50[data-disabled]{
  opacity: 0.5;
}

.data-\\[state\\=active\\]\\:shadow[data-state="active"]{
  --tw-shadow: 0 1px 3px 0 rgb(0 0 0 / 0.1), 0 1px 2px -1px rgb(0 0 0 / 0.1);
  --tw-shadow-colored: 0 1px 3px 0 var(--tw-shadow-color), 0 1px 2px -1px var(--tw-shadow-color);
  box-shadow: var(--tw-ring-offset-shadow, 0 0 #0000), var(--tw-ring-shadow, 0 0 #0000), var(--tw-
shadow);
}
```

```
.data-\\[swipe\\=move\\]\\:transition-none[data-swipe="move"]{
  transition-property: none;
}

.data-\\[state\\=closed\\]\\:duration-300[data-state="closed"]{
  transition-duration: 300ms;
}

.data-\\[state\\=open\\]\\:duration-500[data-state="open"]{
  transition-duration: 500ms;
}

.data-\\[motion\\^\\=from-\\]\\:animate-in[data-motion^="from-"]{
  animation-name: enter;
  animation-duration: 150ms;
  --tw-enter-opacity: initial;
  --tw-enter-scale: initial;
  --tw-enter-rotate: initial;
  --tw-enter-translate-x: initial;
  --tw-enter-translate-y: initial;
}

.data-\\[state\\=open\\]\\:animate-in[data-state="open"]{
  animation-name: enter;
  animation-duration: 150ms;
  --tw-enter-opacity: initial;
  --tw-enter-scale: initial;
  --tw-enter-rotate: initial;
  --tw-enter-translate-x: initial;
  --tw-enter-translate-y: initial;
}

.data-\\[state\\=visible\\]\\:animate-in[data-state="visible"]{
  animation-name: enter;
  animation-duration: 150ms;
  --tw-enter-opacity: initial;
  --tw-enter-scale: initial;
  --tw-enter-rotate: initial;
  --tw-enter-translate-x: initial;
  --tw-enter-translate-y: initial;
}

.data-\\[motion\\^\\=to-\\]\\:animate-out[data-motion^="to-"]{
  animation-name: exit;
  animation-duration: 150ms;
  --tw-exit-opacity: initial;
  --tw-exit-scale: initial;
  --tw-exit-rotate: initial;
```

```
  --tw-exit-translate-x: initial;
  --tw-exit-translate-y: initial;
}

.data-\\[state\\=closed\\]\\:animate-out[data-state="closed"]{
  animation-name: exit;
  animation-duration: 150ms;
  --tw-exit-opacity: initial;
  --tw-exit-scale: initial;
  --tw-exit-rotate: initial;
  --tw-exit-translate-x: initial;
  --tw-exit-translate-y: initial;
}

.data-\\[state\\=hidden\\]\\:animate-out[data-state="hidden"]{
  animation-name: exit;
  animation-duration: 150ms;
  --tw-exit-opacity: initial;
  --tw-exit-scale: initial;
  --tw-exit-rotate: initial;
  --tw-exit-translate-x: initial;
  --tw-exit-translate-y: initial;
}

.data-\\[swipe\\=end\\]\\:animate-out[data-swipe="end"]{
  animation-name: exit;
  animation-duration: 150ms;
  --tw-exit-opacity: initial;
  --tw-exit-scale: initial;
  --tw-exit-rotate: initial;
  --tw-exit-translate-x: initial;
  --tw-exit-translate-y: initial;
}

.data-\\[motion\\^\\=from-\\]\\:fade-in[data-motion^="from-"]{
  --tw-enter-opacity: 0;
}

.data-\\[motion\\^\\=to-\\]\\:fade-out[data-motion^="to-"]{
  --tw-exit-opacity: 0;
}

.data-\\[state\\=closed\\]\\:fade-out-0[data-state="closed"]{
  --tw-exit-opacity: 0;
}

.data-\\[state\\=closed\\]\\:fade-out-80[data-state="closed"]{
  --tw-exit-opacity: 0.8;
}
```

```
.data-\\[state\\=hidden\\]\\:fade-out[data-state="hidden"]{
  --tw-exit-opacity: 0;
}

.data-\\[state\\=open\\]\\:fade-in-0[data-state="open"]{
  --tw-enter-opacity: 0;
}

.data-\\[state\\=visible\\]\\:fade-in[data-state="visible"]{
  --tw-enter-opacity: 0;
}

.data-\\[state\\=closed\\]\\:zoom-out-95[data-state="closed"]{
  --tw-exit-scale: .95;
}

.data-\\[state\\=open\\]\\:zoom-in-90[data-state="open"]{
  --tw-enter-scale: .9;
}

.data-\\[state\\=open\\]\\:zoom-in-95[data-state="open"]{
  --tw-enter-scale: .95;
}

.data-\\[motion\\=from-end\\]\\:slide-in-from-right-52[data-motion="from-end"]{
  --tw-enter-translate-x: 13rem;
}

.data-\\[motion\\=from-start\\]\\:slide-in-from-left-52[data-motion="from-start"]{
  --tw-enter-translate-x: -13rem;
}

.data-\\[motion\\=to-end\\]\\:slide-out-to-right-52[data-motion="to-end"]{
  --tw-exit-translate-x: 13rem;
}

.data-\\[motion\\=to-start\\]\\:slide-out-to-left-52[data-motion="to-start"]{
  --tw-exit-translate-x: -13rem;
}

.data-\\[side\\=bottom\\]\\:slide-in-from-top-2[data-side="bottom"]{
  --tw-enter-translate-y: -0.5rem;
}

.data-\\[side\\=left\\]\\:slide-in-from-right-2[data-side="left"]{
  --tw-enter-translate-x: 0.5rem;
}
```

```
.data-\\[side\\=right\\]\\:slide-in-from-left-2[data-side="right"]{
  --tw-enter-translate-x: -0.5rem;
}

.data-\\[side\\=top\\]\\:slide-in-from-bottom-2[data-side="top"]{
  --tw-enter-translate-y: 0.5rem;
}

.data-\\[state\\=closed\\]\\:slide-out-to-bottom[data-state="closed"]{
  --tw-exit-translate-y: 100%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-left[data-state="closed"]{
  --tw-exit-translate-x: -100%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-left-1\\/2[data-state="closed"]{
  --tw-exit-translate-x: -50%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-right[data-state="closed"]{
  --tw-exit-translate-x: 100%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-right-full[data-state="closed"]{
  --tw-exit-translate-x: 100%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-top[data-state="closed"]{
  --tw-exit-translate-y: -100%;
}

.data-\\[state\\=closed\\]\\:slide-out-to-top-\\[48\\%\\][data-state="closed"]{
  --tw-exit-translate-y: -48%;
}

.data-\\[state\\=open\\]\\:slide-in-from-bottom[data-state="open"]{
  --tw-enter-translate-y: 100%;
}

.data-\\[state\\=open\\]\\:slide-in-from-left[data-state="open"]{
  --tw-enter-translate-x: -100%;
}

.data-\\[state\\=open\\]\\:slide-in-from-left-1\\/2[data-state="open"]{
  --tw-enter-translate-x: -50%;
}

.data-\\[state\\=open\\]\\:slide-in-from-right[data-state="open"]{
```

```
  --tw-enter-translate-x: 100%;
}

.data-\\[state\\=open\\]\\:slide-in-from-top[data-state="open"]{
  --tw-enter-translate-y: -100%;
}

.data-\\[state\\=open\\]\\:slide-in-from-top-\\[48\\%\\][data-state="open"]{
  --tw-enter-translate-y: -48%;
}

.data-\\[state\\=open\\]\\:slide-in-from-top-full[data-state="open"]{
  --tw-enter-translate-y: -100%;
}

.data-\\[state\\=closed\\]\\:duration-300[data-state="closed"]{
  animation-duration: 300ms;
}

.data-\\[state\\=open\\]\\:duration-500[data-state="open"]{
  animation-duration: 500ms;
}

.data-\\[panel-group-direction\\=vertical\\]\\:after\\:left-0[data-panel-group-direction="vertical"]::after{
  content: var(--tw-content);
  left: 0px;
}

.data-\\[panel-group-direction\\=vertical\\]\\:after\\:h-1[data-panel-group-direction="vertical"]::after{
  content: var(--tw-content);
  height: 0.25rem;
}

.data-\\[panel-group-direction\\=vertical\\]\\:after\\:w-full[data-panel-group-direction="vertical"]::after{
  content: var(--tw-content);
  width: 100%;
}

.data-\\[panel-group-direction\\=vertical\\]\\:after\\:-translate-y-1\\/2[data-panel-group-
direction="vertical"]::after{
  content: var(--tw-content);
  --tw-translate-y: -50%;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[panel-group-direction\\=vertical\\]\\:after\\:translate-x-0[data-panel-group-
direction="vertical"]::after{
  content: var(--tw-content);
```

```
  --tw-translate-x: 0px;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.data-\\[state\\=open\\]\\:hover\\:bg-accent:hover[data-state="open"]{
  background-color: hsl(var(--accent));
}

.data-\\[state\\=open\\]\\:focus\\:bg-accent:focus[data-state="open"]{
  background-color: hsl(var(--accent));
}

.group[data-state="open"] .group-data-\\[state\\=open\\]\\:rotate-180{
  --tw-rotate: 180deg;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate))
 skewX(var(--tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-
y));
}

.dark\\:border-destructive:is(.dark *){
  border-color: hsl(var(--destructive));
}

@media (min-width: 640px){

  .sm\\:bottom-0{
    bottom: 0px;
  }

  .sm\\:right-0{
    right: 0px;
  }

  .sm\\:top-auto{
    top: auto;
  }

  .sm\\:mt-0{
    margin-top: 0px;
  }

  .sm\\:max-w-sm{
    max-width: 24rem;
  }

  .sm\\:grid-cols-3{
    grid-template-columns: repeat(3, minmax(0, 1fr));
  }
```

```
.sm\\:flex-row{
  flex-direction: row;
}

.sm\\:flex-col{
  flex-direction: column;
}

.sm\\:justify-end{
  justify-content: flex-end;
}

.sm\\:gap-2\\.5{
  gap: 0.625rem;
}

.sm\\:space-x-2 > :not([hidden]) ~ :not([hidden]){
  --tw-space-x-reverse: 0;
  margin-right: calc(0.5rem * var(--tw-space-x-reverse));
  margin-left: calc(0.5rem * calc(1 - var(--tw-space-x-reverse)));
}

.sm\\:space-x-4 > :not([hidden]) ~ :not([hidden]){
  --tw-space-x-reverse: 0;
  margin-right: calc(1rem * var(--tw-space-x-reverse));
  margin-left: calc(1rem * calc(1 - var(--tw-space-x-reverse)));
}

.sm\\:space-y-0 > :not([hidden]) ~ :not([hidden]){
  --tw-space-y-reverse: 0;
  margin-top: calc(0px * calc(1 - var(--tw-space-y-reverse)));
  margin-bottom: calc(0px * var(--tw-space-y-reverse));
}

.sm\\:rounded-lg{
  border-radius: var(--radius);
}

.sm\\:text-left{
  text-align: left;
}

.sm\\:text-3xl{
  font-size: 1.875rem;
  line-height: 2.25rem;
}

.sm\\:text-5xl{
```

```
    font-size: 3rem;
    line-height: 1;
  }

  .data-\\[state\\=open\\]\\:sm\\:slide-in-from-bottom-full[data-state="open"]{
    --tw-enter-translate-y: 100%;
  }
}

@media (min-width: 768px){

  .md\\:absolute{
    position: absolute;
  }

  .md\\:w-\\[var\\(--radix-navigation-menu-viewport-width\\)\\]{
    width: var(--radix-navigation-menu-viewport-width);
  }

  .md\\:w-auto{
    width: auto;
  }

  .md\\:max-w-\\[420px\\]{
    max-width: 420px;
  }

  .md\\:grid-cols-2{
    grid-template-columns: repeat(2, minmax(0, 1fr));
  }

  .md\\:text-sm{
    font-size: 0.875rem;
    line-height: 1.25rem;
  }
}

@media (min-width: 1024px){

  .lg\\:col-span-5{
    grid-column: span 5 / span 5;
  }

  .lg\\:col-span-7{
    grid-column: span 7 / span 7;
  }

  .lg\\:grid-cols-12{
    grid-template-columns: repeat(12, minmax(0, 1fr));
```

```
  }

  .lg\\:grid-cols-2{
    grid-template-columns: repeat(2, minmax(0, 1fr));
  }

  .lg\\:grid-cols-3{
    grid-template-columns: repeat(3, minmax(0, 1fr));
  }

  .lg\\:grid-cols-4{
    grid-template-columns: repeat(4, minmax(0, 1fr));
  }

  .lg\\:text-6xl{
    font-size: 3.75rem;
    line-height: 1;
  }
}

.\\[\\&\\+div\\]\\:text-xs+div{
  font-size: 0.75rem;
  line-height: 1rem;
}

.\\[\\&\\:has\\(\\>\\.day-range-end\\)\\]\\:rounded-r-md:has(>.day-range-end){
  border-top-right-radius: calc(var(--radius) - 2px);
  border-bottom-right-radius: calc(var(--radius) - 2px);
}

.\\[\\&\\:has\\(\\>\\.day-range-start\\)\\]\\:rounded-l-md:has(>.day-range-start){
  border-top-left-radius: calc(var(--radius) - 2px);
  border-bottom-left-radius: calc(var(--radius) - 2px);
}

.\\[\\&\\:has\\(\\[aria-selected\\]\\)\\]\\:rounded-md:has([aria-selected]){
  border-radius: calc(var(--radius) - 2px);
}

.\\[\\&\\:has\\(\\[aria-selected\\]\\)\\]\\:bg-accent:has([aria-selected]){
  background-color: hsl(var(--accent));
}

.first\\:\\[\\&\\:has\\(\\[aria-selected\\]\\)\\]\\:rounded-l-md:has([aria-selected]):first-child{
  border-top-left-radius: calc(var(--radius) - 2px);
  border-bottom-left-radius: calc(var(--radius) - 2px);
}

.last\\:\\[\\&\\:has\\(\\[aria-selected\\]\\)\\]\\:rounded-r-md:has([aria-selected]):last-child{
```

```
  border-top-right-radius: calc(var(--radius) - 2px);
  border-bottom-right-radius: calc(var(--radius) - 2px);
}

.\\[\\&\\:has\\(\\[aria-selected\\]\\.day-outside\\)\\]\\:bg-accent\\/50:has([aria-selected].day-outside){
  background-color: hsl(var(--accent) / 0.5);
}

.\\[\\&\\:has\\(\\[aria-selected\\]\\.day-range-end\\)\\]\\:rounded-r-md:has([aria-selected].day-range-end)
{
  border-top-right-radius: calc(var(--radius) - 2px);
  border-bottom-right-radius: calc(var(--radius) - 2px);
}

.\\[\\&\\:has\\(\\[role\\=checkbox\\]\\)\\]\\:pr-0:has([role=checkbox]){
  padding-right: 0px;
}

.\\[\\&\\>\\[role\\=checkbox\\]\\]\\:translate-y-\\[2px\\]>[role=checkbox]{
  --tw-translate-y: 2px;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.\\[\\&\\>span\\]\\:line-clamp-1>span{
  overflow: hidden;
  display: -webkit-box;
  -webkit-box-orient: vertical;
  -webkit-line-clamp: 1;
}

.\\[\\&\\>svg\\+div\\]\\:translate-y-\\[-3px\\]>svg+div{
  --tw-translate-y: -3px;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.\\[\\&\\>svg\\]\\:absolute>svg{
  position: absolute;
}

.\\[\\&\\>svg\\]\\:left-4>svg{
  left: 1rem;
}

.\\[\\&\\>svg\\]\\:top-4>svg{
  top: 1rem;
}
```

```
.\\[\\&\\>svg\\]\\:size-4>svg{
  width: 1rem;
  height: 1rem;
}

.\\[\\&\\>svg\\]\\:h-3\\.5>svg{
  height: 0.875rem;
}

.\\[\\&\\>svg\\]\\:w-3\\.5>svg{
  width: 0.875rem;
}

.\\[\\&\\>svg\\]\\:shrink-0>svg{
  flex-shrink: 0;
}

.\\[\\&\\>svg\\]\\:text-destructive>svg{
  color: hsl(var(--destructive));
}

.\\[\\&\\>svg\\]\\:text-foreground>svg{
  color: hsl(var(--foreground));
}

.\\[\\&\\>svg\\~\\*\\]\\:pl-7>svg~*{
  padding-left: 1.75rem;
}

.\\[\\&\\>tr\\]\\:last\\:border-b-0:last-child>tr{
  border-bottom-width: 0px;
}

.\\[\\&\\[data-panel-group-direction\\=vertical\\]\\>div\\]\\:rotate-90[data-panel-group-
direction=vertical]>div{
  --tw-rotate: 90deg;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.\\[\\&\\[data-state\\=open\\]\\>svg\\]\\:rotate-180[data-state=open]>svg{
  --tw-rotate: 180deg;
  transform: translate(var(--tw-translate-x), var(--tw-translate-y)) rotate(var(--tw-rotate)) skewX(var(--
tw-skew-x)) skewY(var(--tw-skew-y)) scaleX(var(--tw-scale-x)) scaleY(var(--tw-scale-y));
}

.\\[\\&_\\[cmdk-group-heading\\]\\]\\:px-2 [cmdk-group-heading]{
  padding-left: 0.5rem;
  padding-right: 0.5rem;
```

```
}

.\\[\\&_\\[cmdk-group-heading\\]\\]\\:py-1\\.5 [cmdk-group-heading]{
  padding-top: 0.375rem;
  padding-bottom: 0.375rem;
}

.\\[\\&_\\[cmdk-group-heading\\]\\]\\:text-xs [cmdk-group-heading]{
  font-size: 0.75rem;
  line-height: 1rem;
}

.\\[\\&_\\[cmdk-group-heading\\]\\]\\:font-medium [cmdk-group-heading]{
  font-weight: 500;
}

.\\[\\&_\\[cmdk-group-heading\\]\\]\\:text-muted-foreground [cmdk-group-heading]{
  color: hsl(var(--muted-foreground));
}

.\\[\\&_\\[cmdk-group\\]\\:not\\(\\[hidden\\]\\)_\\~\\[cmdk-group\\]\\]\\:pt-0 [cmdk-group]:not([hidden])
~[cmdk-group]{
  padding-top: 0px;
}

.\\[\\&_\\[cmdk-group\\]\\]\\:px-2 [cmdk-group]{
  padding-left: 0.5rem;
  padding-right: 0.5rem;
}

.\\[\\&_\\[cmdk-input-wrapper\\]_svg\\]\\:h-5 [cmdk-input-wrapper] svg{
  height: 1.25rem;
}

.\\[\\&_\\[cmdk-input-wrapper\\]_svg\\]\\:w-5 [cmdk-input-wrapper] svg{
  width: 1.25rem;
}

.\\[\\&_\\[cmdk-input\\]\\]\\:h-12 [cmdk-input]{
  height: 3rem;
}

.\\[\\&_\\[cmdk-item\\]\\]\\:px-2 [cmdk-item]{
  padding-left: 0.5rem;
  padding-right: 0.5rem;
}

.\\[\\&_\\[cmdk-item\\]\\]\\:py-3 [cmdk-item]{
  padding-top: 0.75rem;
```

```
  padding-bottom: 0.75rem;
}

.\\[\\&_\\[cmdk-item\\]_svg\\]\\:h-5 [cmdk-item] svg{
  height: 1.25rem;
}

.\\[\\&_\\[cmdk-item\\]_svg\\]\\:w-5 [cmdk-item] svg{
  width: 1.25rem;
}

.\\[\\&_p\\]\\:leading-relaxed p{
  line-height: 1.625;
}

.\\[\\&_svg\\]\\:pointer-events-none svg{
  pointer-events: none;
}

.\\[\\&_svg\\]\\:size-4 svg{
  width: 1rem;
  height: 1rem;
}

.\\[\\&_svg\\]\\:shrink-0 svg{
  flex-shrink: 0;
}

.\\[\\&_tr\\:last-child\\]\\:border-0 tr:last-child{
  border-width: 0px;
}

.\\[\\&_tr\\]\\:border-b tr{
  border-bottom-width: 1px;
}
`, "",{"version":3,"sources":["webpack://./src/index.css"],"names":
[],"mappings":"AAEA;EAAA,wBAAc;EAAd,wBAAc;EAAd,mBAAc;EAAd,mBAAc;EAAd,cAAc;EAAd,cAAc;EAAd,cAAc;EAAd,eAAc;EAAd,eAAc;EAAd,aAAc;EAAd,aAAc;EAAd,kBAAc;EAAd,sBAAc;EAAd,8BAAc;EAAd,6BAAc;EAAd,4BAAc;EAAd,eAAc;EAAd,oBAAc;EAAd,sBAAc;EAAd,uBAAc;EAAd,wBAAc;EAAd,kBAAc;EAAd,2BAAc;EAAd,4BAAc;EAAd,sBAAc;EAAd,kBAAc;EAAd,2BAAc;EAAd,sBAAc;EAAd,8BAAc;EAAd,YAAc;EAAd,kBAAc;EAAd,gBAAc;EAAd,iBAAc;EAAd,kBAAc;EAAd,cAAc;EAAd,gBAAc;EAAd,aAAc;EAAd,mBAAc;EAAd,qBAAc;EAAd,2BAAc;EAAd,yBAAc;EAAd,0BAAc;EAAd,2BAAc;EAAd,uBAAc;EAAd,wBAAc;EAAd,yBAAc;EAAd,sBAAc;EAAd,oBAAc;EAAd,sBAAc;EAAd,qBAAc;EAAd;AAAc;;;AAAd;EAAA,wBAAc;EAAd,wBAAc;EAAd,mBAAc;EAAd,mBAAc;EAAd,cAAc;EAAd,cAAc;EAAd,cAAc;EAAd,eAAc;EAAd,eAAc;EAAd,aAAc;EAAd,aAAc;EAAd,kBAAc;EAAd,sBAAc;EAAd,8BAAc;EAAd,6BAAc;EAAd,4BAAc;EAAd,eAAc;EAAd,oBAAc;EAAd,sBAAc;EAAd,uBAAc;EAAd,wBAAc;EAAd,kBAAc;EAAd,2BAAc;EAAd,4BAAc;EAAd,sBAAc;EAAd,kBAAc;EAAd,2BAAc;EAAd,sBAAc;EAAd,8BAAc;EAAd,YAAc;EAAd,kBAAc;EAAd,gBAAc;EAAd,iBAAc;EAAd,kBAAc;EAAd,cAAc;EAAd,gBAAc;EAAd,a
```

AAc;EAAd,mBAAc;EAAd,qBAAc;EAAd,2BAAc;EAAd,yBAAc;EAAd,0BAAc;EAAd,2BAAc;EAA
d,uBAAc;EAAd,wBAAc;EAAd,yBAAc;EAAd,sBAAc;EAAd,oBAAc;EAAd,sBAAc;EAAd,qBAAc;E
AAd;AAAc;;AAAd;;CAAc;;AAAd;;;CAAc;;AAAd;;;EAAA,sBAAc,EAAd,MAAc;EAAd,eAAc,EAA
d,MAAc;EAAd,mBAAc,EAAd,MAAc;EAAd,qBAAc,EAAd,MAAc;AAAA;;AAAd;;EAAA,gBAAc;
AAAA;;AAAd;;;;;;;;CAAc;;AAAd;;EAAA,gBAAc,EAAd,MAAc;EAAd,8BAAc,EAAd,MAAc,EAAd
,MAAc;EAAd,WAAc,EAAd,MAAc;EAAd,
+HAAc,EAAd,MAAc;EAAd,6BAAc,EAAd,MAAc;EAAd,
+BAAc,EAAd,MAAc;EAAd,wCAAc,EAAd,MAAc;AAAA;;AAAd;;;CAAc;;AAAd;EAAA,SAAc,EA
Ad,MAAc;EAAd,oBAAc,EAAd,MAAc;AAAA;;AAAd;;;;CAAc;;AAAd;EAAA,SAAc,EAAd,MAAc;
EAAd,cAAc,EAAd,MAAc;EAAd,qBAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,iCAA
c;AAAA;;AAAd;;CAAc;;AAAd;;;;;;EAAA,kBAAc;EAAd,oBAAc;AAAA;;AAAd;;CAAc;;AAAd;EA
AA,cAAc;EAAd,wBAAc;AAAA;;AAAd;;CAAc;;AAAd;;EAAA,mBAAc;AAAA;;AAAd;;;;;CAAc;;
AAAd;;;;EAAA,+GA
Ac,EAAd,MAAc;EAAd,6BAAc,EAAd,MAAc;EAAd,
+BAAc,EAAd,MAAc;EAAd,cAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,cAAc;AAA
A;;AAAd;;CAAc;;AAAd;;EAAA,cAAc;EAAd,cAAc;EAAd,kBAAc;EAAd,wBAAc;AAAA;;AAAd;E
AAA,eAAc;AAAA;;AAAd;EAAA,WAAc;AAAA;;AAAd;;;;CAAc;;AAAd;EAAA,cAAc,EAAd,MAA
c;EAAd,qBAAc,EAAd,MAAc;EAAd,yBAAc,EAAd,MAAc;AAAA;;AAAd;;;;CAAc;;AAAd;;;;;EAA
A,oBAAc,EAAd,MAAc;EAAd,8BAAc,EAAd,MAAc;EAAd,gCAAc,EAAd,MAAc;EAAd,eAAc,EAA
d,MAAc;EAAd,oBAAc,EAAd,MAAc;EAAd,oBAAc,EAAd,MAAc;EAAd,uBAAc,EAAd,MAAc;EA
Ad,cAAc,EAAd,MAAc;EAAd,SAAc,EAAd,MAAc;EAAd,UAAc,EAAd,MAAc;AAAA;;AAAd;;CA
Ac;;AAAd;;EAAA,oBAAc;AAAA;;AAAd;;;CAAc;;AAAd;;;;EAAA,0BAAc,EAAd,MAAc;EAAd,6B
AAc,EAAd,MAAc;EAAd,sBAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,aAAc;AAAA;
;AAAd;;CAAc;;AAAd;EAAA,gBAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,wBAAc;AAAA;;AAAd
;;CAAc;;AAAd;;EAAA,YAAc;AAAA;;AAAd;;;CAAc;;AAAd;EAAA,6BAAc,EAAd,MAAc;EAAd,o
BAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,wBAAc;AAAA;;AAAd;;;CAAc;;AAAd;
EAAA,0BAAc,EAAd,MAAc;EAAd,aAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,kBA
Ac;AAAA;;AAAd;;CAAc;;AAAd;;;;;;;;;;;;EAAA,SAAc;AAAA;;AAAd;EAAA,SAAc;EAAd,UAAc;
AAAA;;AAAd;EAAA,UAAc;AAAA;;AAAd;;;EAAA,gBAAc;EAAd,SAAc;EAAd,UAAc;AAAA;;A
AAd;;CAAc;;AAAd;EAAA,UAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,gBAAc;AAAA;;AAAd;;;C
AAc;;AAAd;;EAAA,UAAc,EAAd,MAAc;EAAd,cAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;
;EAAA,eAAc;AAAA;;AAAd;;CAAc;;AAAd;EAAA,eAAc;AAAA;;AAAd;;;;CAAc;;AAAd;;;;;;;EA
AA,cAAc,EAAd,MAAc;EAAd,sBAAc,EAAd,MAAc;AAAA;;AAAd;;CAAc;;AAAd;;EAAA,eAAc;E
AAd,YAAc;AAAA;;AAAd,wEAAc;;AAAd;EAAA,aAAc;AAAA;;AAAd;IAAA,wBAAc;IAAd,yBAA
c;IAAd,mBAAc;IAAd,8BAAc;IAAd,sBAAc;IAAd,iCAAc;IAAd,uBAAc;IAAd,gCAAc;IAAd,wBAA
c;IAAd,mCAAc;IAAd,oBAAc;IAAd,+BAAc;IAAd,qBAAc;IAAd,
+BAAc;IAAd,wBAAc;IAAd,qCAAc;IAAd,qBAAc;IAAd,oBAAc;IAAd,oBAAc;IAAd,iBAAc;EAAA
;AAEd;EAAA,kBAAmB;EAAnB,UAAmB;EAAnB,WAAmB;EAAnB,UAAmB;EAAnB,YAAmB;EA
AnB,gBAAmB;EAAnB,sBAAmB;EAAnB,mBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA,SAAmB;EAAnB;AAAmB;AAAnB;EAAA,QAAmB;EAAnB;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAA
nB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA

mB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,qBAAmB;EAAnB;AAAmB;
AAAnB;EAAA,iBAAmB;EAAnB;AAAmB;AAAnB;EAAA,mBAAmB;EAAnB;AAAmB;AAAnB;E
AAA,kBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAA
A;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EA
AA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAA
nB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA
mB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AA
AmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;A
AAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;
AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAA
A;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EA
AA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAA
nB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA
mB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AA
AmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;A
AAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,
sBAAmB;EAAnB;AAAmB;AAAnB;EAAA,sBAAmB;EAAnB;AAAmB;AAAnB;EAAA,sBAAmB;E
AAnB;AAAmB;AAAnB;EAAA,sBAAmB;EAAnB;AAAmB;AAAnB;EAAA,kBAAmB;EAAnB;AA
AmB;AAAnB;EAAA,kBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;;EAAA;IAAA;
EAAmB;AAAA;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAn
B;EAAA;AAAmB;AAAnB;EAAA,yBAAmB;UAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAA
nB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA,uBAAmB;EAAnB,uDAAmB;EAAnB;AAAmB;AAAnB;E
AAA,uBAAmB;EAAnB,sDAAmB;EAAnB;AAAmB;AAAnB;EAAA,uBAAmB;EAAnB,
+DAAmB;EAAnB;AAAmB;AAAnB;EAAA,uBAAmB;EAAnB,gEAAmB;EAAnB;AAAmB;AAAnB
;EAAA,uBAAmB;EAAnB,8DAAmB;EAAnB;AAAmB;AAAnB;EAAA,uBAAmB;EAAnB,4DAAmB
;EAAnB;AAAmB;AAAnB;EAAA,uBAAmB;EAAnB,8DAAmB;EAAnB;AAAmB;AAAnB;EAAA,u
BAAmB;EAAnB,4DAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,gBAAmB;EAAnB,uBAAmB;EAA
nB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,4BAAmB;EAA
nB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E

AAA,qBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAA
A;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EA
AA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;E
AAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB
;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAA
nB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA
mB;AAAnB;EAAA,sBAAmB;EAAnB;AAAmB;AAAnB;EAAA,oBAAmB;EAAnB;AAAmB;AAAn
B;EAAA,sBAAmB;EAAnB;AAAmB;AAAnB;EAAA,qBAAmB;EAAnB;AAAmB;AAAnB;EAAA,k
BAAmB;EAAnB;AAAmB;AAAnB;EAAA,oBAAmB;EAAnB;AAAmB;AAAnB;EAAA,kBAAmB;E
AAnB;AAAmB;AAAnB;EAAA,qBAAmB;EAAnB;AAAmB;AAAnB;EAAA,oBAAmB;EAAnB;AA
AmB;AAAnB;EAAA,qBAAmB;EAAnB;AAAmB;AAAnB;EAAA,mBAAmB;EAAnB;AAAmB;AA
AnB;EAAA,oBAAmB;EAAnB;AAAmB;AAAnB;EAAA,iBAAmB;EAAnB;AAAmB;AAAnB;EAAA
,mBAAmB;EAAnB;AAAmB;AAAnB;EAAA,iBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA
mB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AA
AmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,i
BAAmB;EAAnB;AAAmB;AAAnB;EAAA,kBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA,eAAmB;EAAnB;AAAmB;AAAnB;EAAA,mBAAmB;EAAnB;AAAmB;AAAnB;EAA
A,mBAAmB;EAAnB;AAAmB;AAAnB;EAAA,kBAAmB;EAAnB;AAAmB;AAAnB;EAAA,kBAAm
B;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AA
AnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;A
AAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;
AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAA
mB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AA
AmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,0
EAAmB;EAAnB,8FAAmB;EAAnB;AAAmB;AAAnB;EAAA,
+EAAmB;EAAnB,mGAAmB;EAAnB;AAAmB;AAAnB;EAAA,6EAAmB;EAAnB,iGAAmB;EAAn
B;AAAmB;AAAnB;EAAA,0CAAmB;EAAnB,uDAAmB;EAAnB;AAAmB;AAAnB;EAAA,8BAAm
B;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA,2GAAmB;EAAnB,yGAAmB;EAAnB;
AAAmB;AAAnB;EAAA,2GAAmB;EAAnB,yGAAmB;EAAnB;AAAmB;AAAnB;EAAA,2GAAmB;
EAAnB,yGAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EA
AA,oBAAmB;EAAnB;AAAmB;AAAnB;EAAA,yBAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA,wJAAmB;EAAnB,wDAAmB;EAAnB;AAAmB;AAAnB;EAAA,wBAAmB;EAAn
B,wDAAmB;EAAnB;AAAmB;AAAnB;EAAA,
+FAAmB;EAAnB,wDAAmB;EAAnB;AAAmB;AAAnB;EAAA,4BAAmB;EAAnB,wDAAmB;EAAn
B;AAAmB;AAAnB;EAAA,8BAAmB;EAAnB,wDAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAm
B;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;;;EAAA;IAA
A,mCAAmB;IAAnB;EAAmB;AAAA;AAAnB;;;EAAA;IAAA,kCAAmB;IAAnB;EAAmB;AAAA;AA
AnB;EAAA,qBAAmB;EAAnB,yBAAmB;EAAnB,2BAAmB;EAAnB,yBAAmB;EAAnB,0BAAmB;E
AAnB,
+BAAmB;EAAnB;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AA
AmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;AAAmB;AAAnB;EAAA;A
AAmB;;AAEnB;EACE,gBAAgB;EAChB,gBAAgB;EAChB,gBAAgB;EAChB,gBAAgB;EAChB,iCA

AiC;EACjC,wCAAwC;EACxC,eAAe;EACf,oCAAoC;EACpC,gBAAgB;EAChB,qCAAqC;EACrC,k
BAAkB;EAClB,eAAe;EACf,gBAAgB;EAChB,cAAc;AAChB;;AA2BA,IAAI,yBAAyB,EAAE;;AAE/
B,oBAAoB,wBAAwB,EAAE;;AAE9C;EACE,SAAS;EACT,kBAAkB;EAClB,
+EAA+E;EAC/E,mCAAmC;EACnC,kCAAkC;EAClC;;;gBAGc;EACd,4BAA4B;EAC5B,iBAAiB;A
ACnB;;AAEA,gBAAgB,iCAAiC,EAAE,uBAAuB,EAAE;AAC5E,aAAa,qDAAqD,EAAE;;AAEpE;E
ACE,wCAAwC;EACxC,eAAe;EACf,sBAAsB;EACtB,yBAAyB;EACzB,6BAA6B;AAC/B;;AAEA;E
ACE,mFAAmF;EACnF,6BAA6B;EAC7B,mBAAmB;EACnB,0BAA0B;AAC5B;AACA;EACE,iCAAi
C;EACjC,oCAAoC;EACpC,mBAAmB;AACrB;;AAEA;EACE,oBAAoB;EACpB,mBAAmB;EACnB,
QAAQ;EACR,iBAAiB;EACjB,oBAAoB;EACpB,6BAA6B;EAC7B,kCAAkC;EAClC,wCAAwC;EAC
xC,eAAe;EACf,mBAAmB;AACrB;;AAEA;EACE,qBAAqB;EACrB,gBAAgB;EAChB,WAAW;EAC
X,kBAAkB;EAClB,wCAAwC;EACxC,eAAe;EACf,gBAAgB;EAChB,iBAAiB;EACjB,kBAAkB;EA
ClB,eAAe;EACf,0EAA0E;EAC1E,mBAAmB;EACnB,yEAAyE;AAC3E;AACA,cAAc,2BAA2B,EAA
E,wBAAwB,EAAE;AACrE,iBAAiB,8BAA8B,EAAE,mBAAmB,EAAE;;AAEtE;EACE,kBAAkB;EA
ClB,SAAS,EAAE,WAAW;EACtB,eAAe,EAAE,YAAY;EAC7B,cAAc;EACd,oBAAoB;EACpB,wBA
AwB;EACxB,kBAAkB;EAClB,6BA6B;
EAC7B,cAAc;EACd,oBAAoB;EACpB,mBAAmB;EACnB,uBAAuB;EACvB,2CAA2C;AAC7C;;AA
EA;EACE,qBAAqB;EACrB,UAAU;EACV,YAAY;EACZ,aAAa;EACb,sBAAsB;EACtB,2EAA2E;EA
C3E,kBAAkB;EAClB,aAAa;AACf;;AAEA;EACE,oBAAoB;EACpB,mBAAmB;EACnB,QAAQ;EAC
R,iBAAiB;EACjB,oBAAoB;EACpB,oCAAoC;EACpC,8BAA8B;EAC9B,kBAAkB;EAClB,gBAAgB;
EAChB,0BAA0B;EAC1B,eAAe;EACf,eAAe;AACjB;AACA,aAAa,oCAAoC,EAAE,6CAA6C,EAAE
;AAClG;EACE,uBAAuB;EACvB,cAAc;EACd,yBAAyB;EACzB,gBAAgB;AAClB;AACA,qBAAqB,
4CAA4C,EAAE;AACnE;EACE,wBAAwB;EACxB,cAAc;EACd,0BAA0B;EAC1B,gBAAgB;AAClB;
AACA;EACE,uBAAuB;EACvB,qCAAqC;AACvC;AACA,gBAAgB,YAAY,EAAE,mBAAmB,EAAE;
;AAEnD;EACE,4BAA4B;EAC5B,6BA6B;EAC7B,kBAAkB;EAClB,mBAAmB;EACnB,iBAAiB;E
ACjB,wCAAwC;EACxC,eAAe;EACf,WAAW;EACX,aAAa;AACf;AACA,YAAY,iBAAiB,EAAE,gB
AAgB,EAAE;AACjD;EACE,yBAAyB;EACzB,6CAA6C;AAC/C;;AAEA,SAAS,wBAAwB,EAAE,W
AAW,EAAE,8BA8B,EAAE,kBAAkB,EAAE;AACpG;EACE,wBAAwB,EAAE,WAAW,EAAE,YAA
Y,EAAE,kBAAkB;EAClE,uBAAuB,EAAE,0CA0C;AACrE;;AAEA;EACE,iBAAiB;EACjB,oBAA
oB;EACpB,6BA6B;EAC7B,mBAAmB;EACnB,gBAAgB;EAChB,eAAe;EACf,qBAAqB;EACrB,eA
Ae;AACjB;AACA,aAAa,kBAAkB,EAAE;AACjC;EACE,mCAAmC;EACnC,kBAAkB;EAClB,qCAA
qC;AACvC;;AAEA;EACE,kBAAkB;EAClB,oCAAoC;AACtC;AACA,mBAAmB,kBAAkB,EAAE;A
ACvC,eAAe,wCAAwC,EAAE,eAAe,EAAE,sBAAsB,EAAE,iBAAiB,EAAE,yBAAyB,EAAE;AAChJ,
eAAe,iCAAiC,EAAE,eAAe,EAAE,kBAAkB,EAAE,gBAAgB,EAAE;AACzG,oBAAoB,kBAAkB,EA
AE;;AAExC,YAAY,gBAAgB,EAAE;AAC9B,
+BAA+B,WAAW,EAAE;AAC5C,qCAAqC,8BAA8B,EAAE,kBAAkB,EAAE;;AAEzF;EACE;;uEAE
qE;ECrE,0BAA0B;AAC5B;;AA/OA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,mBA
gPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAh
PA;EAAA,0BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EAhPA,QAgPA;EAhPA;AAgPA;;AAh
PA;EAAA,0BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAg
PA;EAhPA,sBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,iDAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgP
A;;AAhPA;EAAA,kDAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhP
A;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA
;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;E
AAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAA
A;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA
;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA
A;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA
;AAgPA;;AAhPA;EAAA,8BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,2GAgPA;EAhPA,yGAgPA;EAhP
A;AAgPA;;AAhPA;EAAA,2GAgPA;EAhPA,yGAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAh
PA;EAAA;AAgPA;;AAhPA;EAAA,8BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,2GAgPA;EAhPA,yGAg

PA;EAhPA;AAgPA;;AAhPA;EAAA,2GAgPA;EAhPA,yGAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAg
PA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgP
A;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA
;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;
AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;
EAAA;AAgPA;;AAhPA;EAAA,
+EAgPA;EAhPA,mGAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhP
A;EAAA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA
,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;
AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;A
AhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AA
hPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,yBAgPA;EAhPA;AAgPA;;AAhPA;EA
AA,0BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,yBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EA
hPA;AAgPA;;AAhPA;EAAA,sBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,qBAgPA;EAhPA;AAgPA;;AA
hPA;EAAA,qBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,gDAgPA;EAhPA;AAgPA;;AAhPA;EAAA,iDA
gPA;EAhPA;AAgPA;;AAhPA;;EAAA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;AAAA;;AAhPA;EAAA;
AAgPA;;AAhPA;;EAAA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;AAAA;;AAhPA;EAAA;AAgPA;;AA
hPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAh
PA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhP
A;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA
;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;E
AAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,0EAgPA;EAhPA,8F
AgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;A
AhPA;EAAA,qBAgPA;EAhPA,yBAgPA;EAhPA,2BAgPA;EAhPA,yBAgPA;EAhPA,0BAgPA;EAhPA,
+BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,qBAgPA;EAhPA,yBAgPA;EAhPA,2BAgPA;EAhPA,yBAg
PA;EAhPA,0BAgPA;EAhPA,
+BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,qBAgPA;EAhPA,yBAgPA;EAhPA,2BAgPA;EAhPA,yBAg
PA;EAhPA,0BAgPA;EAhPA,
+BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA,yBAgPA;EAhPA,0BAgPA;EAhPA,wBAg
PA;EAhPA,yBAgPA;EAhPA,8BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA,yBAgPA;EA
hPA,0BAgPA;EAhPA,wBAgPA;EAhPA,yBAgPA;EAhPA,8BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,o
BAgPA;EAhPA,yBAgPA;EAhPA,0BAgPA;EAhPA,wBAgPA;EAhPA,yBAgPA;EAhPA,8BAgPA;EAhP
A;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA,yBAgPA;EAhPA,0BAgPA;EAhPA,wBAgPA;EAhPA,yB
AgPA;EAhPA,8BAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;E
AAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EA
AA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAA
A;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA
;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;
AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;A
AgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AA
gPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAg
PA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,0BAgP
A;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EAhPA;AAgP
A;;AAhPA;EAAA,0BAgPA;EAhPA,sBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,0BAgPA;EAhPA,qBAg
PA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,mBAgPA;EAh
PA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;;EAAA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;
IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;
EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA,uBAgP
A;IAhPA,sDAgPA;IAhPA;EAgPA;;EAhPA;IAAA,uBAgPA;IAhPA,oDAgPA;IAhPA;EAgPA;;EAhPA;I

AAA,uBAgPA;IAhPA,2DAgPA;IAhPA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA,mBAgPA;IAhPA;EAgPA;;EAhPA;IAAA,eAgPA;IAhPA;EAgPA;;EAhPA;IAAA;EAgPA;AAAA;;AAhPA;;EAAA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA,mBAgPA;IAhPA;EAgPA;AAAA;;AAhPA;;EAAA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA;EAgPA;;EAhPA;IAAA,kBAgPA;IAhPA;EAgPA;AAAA;;AAhPA;EAAA,kBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,kDAgPA;EAhPA;AAgPA;;AAhPA;EAAA,iDAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,iDAgPA;EAhPA;AAgPA;;AAhPA;EAAA,kDAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,kDAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,qBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,gBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,4BAgPA;EAhPA;AAgPA;;AAhPA;EAAA,sBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,WAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,kBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,mBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,qBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,kBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA,oBAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA,WAgPA;EAhPA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA;;AAhPA;EAAA;AAgPA","sourcesContent":["@import url(\"https://fonts.googleapis.com/css2?family=Outfit:wght@400;500;600;700;800&family=Inter:wght@400;500;600;700&family=JetBrains+Mono:wght@400;500;600;700&display=swap\");\n\n@tailwind base;\n@tailwind components;\n@tailwind utilities;\n\n:root {\n --ink-0: #05070d;\n --ink-1: #0b0f19;\n --ink-2: #111827;\n --ink-3: #1f2937;\n --line: rgba(255, 255, 255, 0.08);\n --line-strong: rgba(255, 255, 255, 0.14);\n --teal: #00f0ff;\n --teal-soft: rgba(0, 240, 255, 0.14);\n --amber: #ffb000;\n --amber-soft: rgba(255, 176, 0, 0.14);\n --magenta: #e024a6;\n --text: #e5e7eb;\n --muted: #9ca3af;\n --dim: #6b7280;\n}\n\n@layer base {\n :root {\n   --background: 220 26% 8%;\n   --foreground: 220 15% 92%;\n   --card: 222 33% 11%;\n   --card-foreground: 220 15% 92%;\n   --popover: 222 33% 11%;\n   --popover-foreground: 220 15% 92%;\n   --primary: 186 100% 50%;\n   --primary-foreground: 220 26% 8%;\n   --secondary: 220 15% 22%;\n   --secondary-foreground: 220 15% 92%;\n   --muted: 220 15% 22%;\n   --muted-foreground: 220 10% 60%;\n   --accent: 40 100% 50%;\n   --accent-foreground: 220 26% 8%;\n   --destructive: 0 65% 55%;\n   --destructive-foreground: 220 15% 92%;\n   --border: 220 15% 22%;\n   --input: 220 15% 22%;\n   --ring: 186 100% 50%;\n   --radius: 0.65rem;\n }\n}\n\n* { border-color: var(--line); }\n\nhtml, body, #root { background: var(--ink-1); }\n\nbody {\n margin: 0;\n color: var(--text);\n font-family: \"Inter\", -apple-system, BlinkMacSystemFont, \"Segoe UI\", sans-serif;\n -webkit-font-smoothing: antialiased;\n -moz-osx-font-smoothing: grayscale;\n background:\n   radial-gradient(1200px 700px at 12% -10%, rgba(0, 240, 255, 0.08), transparent 60%),\n   radial-gradient(900px 600px at 88% 10%, rgba(255, 176, 0, 0.06), transparent 60%),\n   var(--ink-1);\n background-attachment: fixed;\n min-height: 100vh;\n}\n\n.font-heading { font-family: \"Outfit\", sans-serif; letter-spacing: -0.01em; }\n.font-mono { font-family: \"JetBrains Mono\", \"Fira Code\", monospace; }\n\n.eyebrow {\n font-family: \"JetBrains Mono\", monospace;\n font-size: 11px;\n letter-spacing: 0.24em;\n text-transform: uppercase;\n color: rgba(0, 240, 255, 0.7);\n}\n\n.panel {\n background: linear-gradient(180deg, rgba(31, 41, 55, 0.55), rgba(17, 24, 39, 0.55));\n border: 1px solid var(--line);\n border-radius: 12px;\n backdrop-filter: blur(6px);\n}\n.panel-strong {\n background:\n rgba(17, 24, 39, 0.9);\n border: 1px solid var(--line-strong);\n border-radius: 12px;\n}\n\n.pill {\n display: inline-flex;\n align-items: center;\n gap: 6px;\n padding: 3px 10px;\n border-radius:

999px;\n border: 1px solid var(--line);\n background: rgba(255,255,255,0.03);\n font-family: \"JetBrains Mono\", monospace;\n font-size: 11px;\n color: var(--muted);\n}\n\n.lego {\n display: inline-block;\n padding: 6px 8px;\n margin: 3px;\n border-radius: 6px;\n font-family: \"JetBrains Mono\", monospace;\n font-size: 12px;\n line-height: 1.2;\n border: 1px solid;\n position: relative;\n cursor: pointer;\n transition: transform 120ms ease, box-shadow 200ms ease, filter 200ms ease;\n white-space: nowrap;\n box-shadow: inset 0 1px 0 rgba(255,255,255,0.06), 0 1px 0 rgba(0,0,0,0.5);\n}\n.lego:hover { transform: translateY(-1px); filter: brightness(1.12); }\n.lego.selected { outline: 2px solid var(--teal); outline-offset: 2px; }\n\n.depth-ring {\n position: absolute;\n top: -3px; right: -3px;\n min-width: 14px; height: 14px;\n padding: 0 4px;\n border-radius: 999px;\n background: var(--ink-2);\n color: var(--teal);\n border: 1px solid var(--teal);\n font-size: 9px;\n display: inline-flex;\n align-items: center;\n justify-content: center;\n box-shadow: 0 0 8px rgba(0, 240, 255, 0.35);\n}\n\n.mirror-bar {\n display: inline-block;\n width: 2px;\n height: 20px;\n margin: 0 3px;\n vertical-align: middle;\n background: linear-gradient(180deg, transparent, var(--amber), transparent);\n border-radius: 2px;\n opacity: 0.85;\n}\n\n.btn {\n display: inline-flex;\n align-items: center;\n gap: 8px;\n padding: 8px 14px;\n border-radius: 999px;\n border: 1px solid var(--line-strong);\n background: rgba(31,41,55,0.6);\n color: var(--text);\n font-weight: 500;\n transition: all 160ms ease;\n cursor: pointer;\n font-size: 13px;\n}\n.btn:hover { border-color: rgba(0, 240, 255, 0.4); box-shadow: 0 0 0 3px rgba(0, 240, 255, 0.06); }\n.btn-primary {\n background: var(--teal);\n color: #05070d;\n border-color: var(--teal);\n font-weight: 700;\n}\n.btn-primary:hover { box-shadow: 0 0 24px rgba(0, 240, 255, 0.35); }\n.btn-amber {\n background: var(--amber);\n color: #05070d;\n border-color: var(--amber);\n font-weight: 700;\n}\n.btn-ghost {\n background: transparent;\n border: 1px dashed var(--line-strong);\n}\n.btn:disabled { opacity: 0.5; cursor: not-allowed; }\n\n.input, .select, .textarea {\n background: rgba(5,7,13,0.6);\n border: 1px solid var(--line);\n color: var(--text);\n border-radius: 10px;\n padding: 9px 12px;\n font-family: \"JetBrains Mono\", monospace;\n font-size: 13px;\n width: 100%;\n outline: none;\n}\n.textarea { min-height: 120px; resize: vertical; }\n.input:focus, .select:focus, .textarea:focus {\n border-color: var(--teal);\n box-shadow: 0 0 0 3px rgba(0, 240, 255, 0.12);\n}\n\n.range { -webkit-appearance: none; height: 4px; background: var(--line-strong); border-radius: 2px; }\n.range::-webkit-slider-thumb {\n -webkit-appearance: none; width: 14px; height: 14px; border-radius: 50%;\n background: var(--teal); box-shadow: 0 0 8px rgba(0, 240, 255, 0.4);\n}\n\n.tab {\n padding: 8px 14px;\n border-radius: 999px;\n border: 1px solid transparent;\n color: var(--muted);\n font-weight: 500;\n cursor: pointer;\n transition: all 160ms;\n font-size: 13px;\n}\n.tab:hover { color: var(--text); }\n.tab.active {\n background: rgba(0, 240, 255, 0.08);\n color: var(--teal);\n border-color: rgba(0, 240, 255, 0.28);\n}\n\n.stat {\n padding: 10px 14px;\n border-right: 1px dashed var(--line);\n}\n.stat:last-child { border-right: none; }\n.stat .label { font-family: \"JetBrains Mono\", monospace; font-size: 10px; letter-spacing: 0.18em; color: var(--dim); text-transform: uppercase; }\n.stat .value { font-family: \"Outfit\", sans-serif; font-size: 22px; color: var(--text); font-weight: 600; }\n.stat .value.teal { color: var(--teal); }\n\n.scroll-x { overflow-x: auto; }\n.scroll-x::-webkit-scrollbar { height: 8px; }\n.scroll-x::-webkit-scrollbar-thumb { background: var(--line-strong); border-radius: 8px; }\n\n.grid-bg {\n background-image:\n   linear-gradient(rgba(255,255,255,0.03) 1px, transparent 1px),\n   linear-gradient(90deg, rgba(255,255,255,0.03) 1px, transparent 1px);\n background-size: 32px 32px;\n}\n\"],\"sourceRoot\":\"\"}]);
// Exports
___CSS_LOADER_EXPORT___.locals = {};
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (___CSS_LOADER_EXPORT___);

/***/ },

```
/***/ "./node_modules/style-loader/dist/runtime/injectStylesIntoStyleTag.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/style-loader/dist/runtime/injectStylesIntoStyleTag.js ***!
  \*****************************************************************************/
(module) {

"use strict";


var stylesInDOM = [];
function getIndexByIdentifier(identifier) {
  var result = -1;
  for (var i = 0; i < stylesInDOM.length; i++) {
    if (stylesInDOM[i].identifier === identifier) {
      result = i;
      break;
    }
  }
  return result;
}
function modulesToDom(list, options) {
  var idCountMap = {};
  var identifiers = [];
  for (var i = 0; i < list.length; i++) {
    var item = list[i];
    var id = options.base ? item[0] + options.base : item[0];
    var count = idCountMap[id] || 0;
    var identifier = "".concat(id, " ").concat(count);
    idCountMap[id] = count + 1;
    var indexByIdentifier = getIndexByIdentifier(identifier);
    var obj = {
      css: item[1],
      media: item[2],
      sourceMap: item[3],
      supports: item[4],
      layer: item[5]
    };
    if (indexByIdentifier !== -1) {
      stylesInDOM[indexByIdentifier].references++;
      stylesInDOM[indexByIdentifier].updater(obj);
    } else {
      var updater = addElementStyle(obj, options);
      options.byIndex = i;
      stylesInDOM.splice(i, 0, {
        identifier: identifier,
        updater: updater,
        references: 1
      });
```

```
    }
    identifiers.push(identifier);
  }
  return identifiers;
}
function addElementStyle(obj, options) {
  var api = options.domAPI(options);
  api.update(obj);
  var updater = function updater(newObj) {
    if (newObj) {
      if (newObj.css === obj.css && newObj.media === obj.media && newObj.sourceMap ===
obj.sourceMap && newObj.supports === obj.supports && newObj.layer === obj.layer) {
        return;
      }
      api.update(obj = newObj);
    } else {
      api.remove();
    }
  };
  return updater;
}
module.exports = function (list, options) {
  options = options || {};
  list = list || [];
  var lastIdentifiers = modulesToDom(list, options);
  return function update(newList) {
    newList = newList || [];
    for (var i = 0; i < lastIdentifiers.length; i++) {
      var identifier = lastIdentifiers[i];
      var index = getIndexByIdentifier(identifier);
      stylesInDOM[index].references--;
    }
    var newLastIdentifiers = modulesToDom(newList, options);
    for (var _i = 0; _i < lastIdentifiers.length; _i++) {
      var _identifier = lastIdentifiers[_i];
      var _index = getIndexByIdentifier(_identifier);
      if (stylesInDOM[_index].references === 0) {
        stylesInDOM[_index].updater();
        stylesInDOM.splice(_index, 1);
      }
    }
    lastIdentifiers = newLastIdentifiers;
  };
};

/***/ },

/***/ "./node_modules/style-loader/dist/runtime/insertBySelector.js"
/*!**********************************************************************!*\
```

```
  !*** ./node_modules/style-loader/dist/runtime/insertBySelector.js ***!
  \*****************************************************************/
(module) {

"use strict";


var memo = {};

/* istanbul ignore next  */
function getTarget(target) {
  if (typeof memo[target] === "undefined") {
    var styleTarget = document.querySelector(target);

    // Special case to return head of iframe instead of iframe itself
    if (window.HTMLIFrameElement && styleTarget instanceof window.HTMLIFrameElement) {
      try {
        // This will throw an exception if access to iframe is blocked
        // due to cross-origin restrictions
        styleTarget = styleTarget.contentDocument.head;
      } catch (e) {
        // istanbul ignore next
        styleTarget = null;
      }
    }
    memo[target] = styleTarget;
  }
  return memo[target];
}

/* istanbul ignore next  */
function insertBySelector(insert, style) {
  var target = getTarget(insert);
  if (!target) {
    throw new Error("Couldn't find a style target. This probably means that the value for the 'insert'
parameter is invalid.");
  }
  target.appendChild(style);
}
module.exports = insertBySelector;

/***/ },

/***/ "./node_modules/style-loader/dist/runtime/insertStyleElement.js"
/*!*********************************************************************!*\
  !*** ./node_modules/style-loader/dist/runtime/insertStyleElement.js ***!
  \*********************************************************************/
(module) {
```

```
"use strict";


/* istanbul ignore next  */
function insertStyleElement(options) {
  var element = document.createElement("style");
  options.setAttributes(element, options.attributes);
  options.insert(element, options.options);
  return element;
}
module.exports = insertStyleElement;

/***/ },

/***/ "./node_modules/style-loader/dist/runtime/setAttributesWithoutAttributes.js"
/*!
**********************************************************************************!
*\
  !*** ./node_modules/style-loader/dist/runtime/setAttributesWithoutAttributes.js ***!

\**********************************************************************************
/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


/* istanbul ignore next  */
function setAttributesWithoutAttributes(styleElement) {
  var nonce =  true ? __webpack_require__.nc : 0;
  if (nonce) {
    styleElement.setAttribute("nonce", nonce);
  }
}
module.exports
 = setAttributesWithoutAttributes;

/***/ },

/***/ "./node_modules/style-loader/dist/runtime/styleDomAPI.js"
/*!*****************************************************************!*\
  !*** ./node_modules/style-loader/dist/runtime/styleDomAPI.js ***!
  \*****************************************************************/
(module) {

"use strict";


/* istanbul ignore next  */
```

```
function apply(styleElement, options, obj) {
  var css = "";
  if (obj.supports) {
    css += "@supports (".concat(obj.supports, ") {");
  }
  if (obj.media) {
    css += "@media ".concat(obj.media, " {");
  }
  var needLayer = typeof obj.layer !== "undefined";
  if (needLayer) {
    css += "@layer".concat(obj.layer.length > 0 ? " ".concat(obj.layer) : "", " {");
  }
  css += obj.css;
  if (needLayer) {
    css += "}";
  }
  if (obj.media) {
    css += "}";
  }
  if (obj.supports) {
    css += "}";
  }
  var sourceMap = obj.sourceMap;
  if (sourceMap && typeof btoa !== "undefined") {
    css += "\n/*#
sourceMappingURL=data:application/json;base64,".concat(btoa(unescape(encodeURIComponent(JSO
N.stringify(sourceMap)))), " */");
  }

  // For old IE
  /* istanbul ignore if  */
  options.styleTagTransform(css, styleElement, options.options);
}
function removeStyleElement(styleElement) {
  // istanbul ignore if
  if (styleElement.parentNode === null) {
    return false;
  }
  styleElement.parentNode.removeChild(styleElement);
}

/* istanbul ignore next  */
function domAPI(options) {
  if (typeof document === "undefined") {
    return {
      update: function update() {},
      remove: function remove() {}
    };
  }
```

```
  var styleElement = options.insertStyleElement(options);
  return {
    update: function update(obj) {
      apply(styleElement, options, obj);
    },
    remove: function remove() {
      removeStyleElement(styleElement);
    }
  };
}
module.exports = domAPI;

/***/ },

/***/ "./node_modules/style-loader/dist/runtime/styleTagTransform.js"
/*!**********************************************************************!*\
  !*** ./node_modules/style-loader/dist/runtime/styleTagTransform.js ***!
  \**********************************************************************/
(module) {

"use strict";


/* istanbul ignore next  */
function styleTagTransform(css, styleElement) {
  if (styleElement.styleSheet) {
    styleElement.styleSheet.cssText = css;
  } else {
    while (styleElement.firstChild) {
      styleElement.removeChild(styleElement.firstChild);
    }
    styleElement.appendChild(document.createTextNode(css));
  }
}
module.exports = styleTagTransform;

/***/ },

/***/ "./src/App.css"
/*!*********************!*\
  !*** ./src/App.css ***!
  \*********************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
```

```
/* harmony import */ var
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_M
ODULE_0__ = __webpack_require__(/*! !../node_modules/style-
loader/dist/runtime/injectStylesIntoStyleTag.js */ "./node_modules/style-
loader/dist/runtime/injectStylesIntoStyleTag.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_M
ODULE_0___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_injectStylesIntoSt
yleTag_js__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/styleDomAPI.js */
"./node_modules/style-loader/dist/runtime/styleDomAPI.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_styleDomAPI_js_
_WEBPACK_IMPORTED_MODULE_1__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODUL
E_2__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/insertBySelector.js */
"./node_modules/style-loader/dist/runtime/insertBySelector.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODUL
E_2___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_insertBySelector_
js__WEBPACK_IMPORTED_MODULE_2__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPORT
ED_MODULE_3__ = __webpack_require__(/*! !../node_modules/style-
loader/dist/runtime/setAttributesWithoutAttributes.js */ "./node_modules/style-
loader/dist/runtime/setAttributesWithoutAttributes.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPORT
ED_MODULE_3___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_setAttributesWith
outAttributes_js__WEBPACK_IMPORTED_MODULE_3__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MODU
LE_4__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/insertStyleElement.js
*/ "./node_modules/style-loader/dist/runtime/insertStyleElement.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MODU
LE_4___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_insertStyleEleme
nt_js__WEBPACK_IMPORTED_MODULE_4__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MODU
```

```
LE_5__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/styleTagTransform.js
*/ "./node_modules/style-loader/dist/runtime/styleTagTransform.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MODU
LE_5___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_styleTagTransfor
m_js__WEBPACK_IMPORTED_MODULE_5__);
/* harmony import */ var
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! !!../node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./App.css */
"./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-
loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-
loader/dist/cjs.js!./src/App.css");
```

```
var options = {};

options.styleTagTransform =
(_node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MOD
ULE_5___default());
options.setAttributes =
(_node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPOR
TED_MODULE_3___default());

      options.insert =
_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODUL
E_2___default().bind(null, "head");

options.domAPI =
(_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1___default());
options.insertStyleElement =
(_node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MOD
ULE_4___default());

var update =
```

```
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_MODULE_0___default()
(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__["default"], options);



if (true) {
  if (!
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals || module.hot.invalidate) {
    var isEqualLocals = function isEqualLocals(a, b, isNamedExport) {
  if (!a && b || a && !b) {
    return false;
  }
  var p;
  for (p in a) {
    if (isNamedExport && p === "default") {
      // eslint-disable-next-line no-continue
      continue;
    }
    if (a[p] !== b[p]) {
      return false;
    }
  }
  for (p in b) {
    if (isNamedExport && p === "default") {
      // eslint-disable-next-line no-continue
      continue;
    }
    if (!a[p]) {
      return false;
    }
  }
  return true;
};
    var isNamedExport = !
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals;
    var oldLocals = isNamedExport ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals;
```

```
   module.hot.accept(
     /*! !!../node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./App.css */
"./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-
loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cj
s.js!./src/App.css",
     __WEBPACK_OUTDATED_DEPENDENCIES__ => { /* harmony import */
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! !!../node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./App.css */
"./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-
loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-
loader/dist/cjs.js!./src/App.css");
 return (function () {
       if (!isEqualLocals(oldLocals, isNamedExport ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals, isNamedExport)) {
             module.hot.invalidate();

             return;
            }

            oldLocals = isNamedExport ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals;


update(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_po
stcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_
cjs_js_App_css__WEBPACK_IMPORTED_MODULE_6__["default"]);
     })(__WEBPACK_OUTDATED_DEPENDENCIES__); }
   )
 }

 module.hot.dispose(function() {
   update();
 });
```

```
}


      /* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_l
oader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__["default"] &&
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
App_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals : undefined);


/***/ },

/***/ "./src/index.css"
/*!************************!*\
  !*** ./src/index.css ***!
  \************************/
(module, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_M
ODULE_0__ = __webpack_require__(/*! !../node_modules/style-
loader/dist/runtime/injectStylesIntoStyleTag.js */ "./node_modules/style-
loader/dist/runtime/injectStylesIntoStyleTag.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_M
ODULE_0___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_injectStylesIntoSt
yleTag_js__WEBPACK_IMPORTED_MODULE_0__);
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/styleDomAPI.js */
"./node_modules/style-loader/dist/runtime/styleDomAPI.js");
/* harmony import */ var
_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1___default =
/*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_styleDomAPI_js_
_WEBPACK_IMPORTED_MODULE_1__);
/* harmony import */ var
```

```
_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODULE_2__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/insertBySelector.js */ "./node_modules/style-loader/dist/runtime/insertBySelector.js");
/* harmony import */ var _node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODULE_2___default = /*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODULE_2__);
/* harmony import */ var _node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPORTED_MODULE_3__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/setAttributesWithoutAttributes.js */ "./node_modules/style-loader/dist/runtime/setAttributesWithoutAttributes.js");
/* harmony import */ var _node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPORTED_MODULE_3___default = /*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPORTED_MODULE_3__);
/* harmony import */ var _node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MODULE_4__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/insertStyleElement.js */ "./node_modules/style-loader/dist/runtime/insertStyleElement.js");
/* harmony import */ var _node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MODULE_4___default = /*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MODULE_4__);
/* harmony import */ var _node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MODULE_5__ = __webpack_require__(/*! !../node_modules/style-loader/dist/runtime/styleTagTransform.js */ "./node_modules/style-loader/dist/runtime/styleTagTransform.js");
/* harmony import */ var _node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MODULE_5___default = /*#__PURE__*/__webpack_require__.n(_node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MODULE_5__);
/* harmony import */ var _node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__ = __webpack_require__(/*! !!../node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./index.css */ "./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-loader/dist/cjs.js!./src/index.css");
```

```
var options = {};

options.styleTagTransform =
(_node_modules_style_loader_dist_runtime_styleTagTransform_js__WEBPACK_IMPORTED_MOD
ULE_5___default());
options.setAttributes =
(_node_modules_style_loader_dist_runtime_setAttributesWithoutAttributes_js__WEBPACK_IMPOR
TED_MODULE_3___default());

      options.insert =
_node_modules_style_loader_dist_runtime_insertBySelector_js__WEBPACK_IMPORTED_MODUL
E_2___default().bind(null, "head");

options.domAPI =
(_node_modules_style_loader_dist_runtime_styleDomAPI_js__WEBPACK_IMPORTED_MODULE_
1___default());
options.insertStyleElement =
(_node_modules_style_loader_dist_runtime_insertStyleElement_js__WEBPACK_IMPORTED_MOD
ULE_4___default());

var update =
_node_modules_style_loader_dist_runtime_injectStylesIntoStyleTag_js__WEBPACK_IMPORTED_M
ODULE_0___default()
(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_l
oader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_
index_css__WEBPACK_IMPORTED_MODULE_6__["default"], options);


if (true) {
  if (!
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_i
ndex_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals || module.hot.invalidate) {
    var isEqualLocals = function isEqualLocals(a, b, isNamedExport) {
  if (!a && b || a && !b) {
    return false;
  }
  var p;
  for (p in a) {
    if (isNamedExport && p === "default") {
      // eslint-disable-next-line no-continue
```

```
      continue;
    }
    if (a[p] !== b[p]) {
      return false;
    }
  }
  for (p in b) {
    if (isNamedExport && p === "default") {
      // eslint-disable-next-line no-continue
      continue;
    }
    if (!a[p]) {
      return false;
    }
  }
  return true;
};
    var isNamedExport = !
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_i
ndex_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals;
    var oldLocals = isNamedExport ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_i
ndex_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use
_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_
6__["default"].locals;

    module.hot.accept(
      /*! !!../node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./index.css */
"./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-
loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-
loader/dist/cjs.js!./src/index.css",
      __WEBPACK_OUTDATED_DEPENDENCIES__ => { /* harmony import */
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_lo
ader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_i
ndex_css__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! !!../node_modules/css-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[1]!../node_modules/postcss-loader/dist/cjs.js??
ruleSet[1].rules[1].oneOf[5].use[2]!../node_modules/source-map-loader/dist/cjs.js!./index.css */
"./node_modules/css-loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[1]!./node_modules/postcss-
loader/dist/cjs.js??ruleSet[1].rules[1].oneOf[5].use[2]!./node_modules/source-map-
loader/dist/cjs.js!./src/index.css");
  return (function () {
        if (!isEqualLocals(oldLocals, isNamedExport ?
```

```
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals, isNamedExport)) {
            module.hot.invalidate();

            return;
          }

          oldLocals = isNamedExport ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__ :
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals;


update(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"]);
    })(__WEBPACK_OUTDATED_DEPENDENCIES__); }
  )
 }

 module.hot.dispose(function() {
  update();
 });
}



    /* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"] &&
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals ?
_node_modules_css_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_1_node_modules_postcss_loader_dist_cjs_js_ruleSet_1_rules_1_oneOf_5_use_2_node_modules_source_map_loader_dist_cjs_js_index_css__WEBPACK_IMPORTED_MODULE_6__["default"].locals : undefined);


/***/ },

/***/ "./node_modules/@pmmmwh/react-refresh-webpack-plugin/client/ReactRefreshEntry.js"
```

```
/*!
*****************************************************************************
****!*\
  !*** ./node_modules/@pmmmwh/react-refresh-webpack-plugin/client/ReactRefreshEntry.js ***!

\*****************************************************************************
*****/
(__unused_webpack_module, __unused_webpack_exports, __webpack_require__) {

/* global __react_refresh_library__ */

const safeThis = __webpack_require__(/*! core-js-pure/features/global-this */ "./node_modules/core-
js-pure/features/global-this.js");
const RefreshRuntime = __webpack_require__(/*! react-refresh/runtime */ "./node_modules/react-
refresh/runtime.js");
if (true) {
  if (typeof safeThis !== 'undefined') {
    var $RefreshInjected$ = '__reactRefreshInjected';
    // Namespace the injected flag (if necessary) for monorepo compatibility
    if (false) // removed by dead control flow
{}

    // Only inject the runtime if it hasn't been injected
    if (!safeThis[$RefreshInjected$]) {
      // Inject refresh runtime into global scope
      RefreshRuntime.injectIntoGlobalHook(safeThis);

      // Mark the runtime as injected to prevent double-injection
      safeThis[$RefreshInjected$] = true;
    }
  }
}

/***/ },

/***/ "./node_modules/core-js-pure/actual/global-this.js"
/*!*************************************************************!*\
  !*** ./node_modules/core-js-pure/actual/global-this.js ***!
  \*************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var parent = __webpack_require__(/*! ../stable/global-this */ "./node_modules/core-js-
pure/stable/global-this.js");
module.exports = parent;

/***/ },
```

```
/***/ "./node_modules/core-js-pure/es/global-this.js"
/*!*****************************************************!*\
  !*** ./node_modules/core-js-pure/es/global-this.js ***!
  \*****************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


__webpack_require__(/*! ../modules/es.global-this */ "./node_modules/core-js-pure/modules/es.global-this.js");
module.exports = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");

/***/ },

/***/ "./node_modules/core-js-pure/features/global-this.js"
/*!***********************************************************!*\
  !*** ./node_modules/core-js-pure/features/global-this.js ***!
  \***********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


module.exports = __webpack_require__(/*! ../full/global-this */ "./node_modules/core-js-pure/full/global-this.js");

/***/ },

/***/ "./node_modules/core-js-pure/full/global-this.js"
/*!******************************************************!*\
  !*** ./node_modules/core-js-pure/full/global-this.js ***!
  \******************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


// TODO: remove from `core-js@4`
__webpack_require__(/*! ../modules/esnext.global-this */ "./node_modules/core-js-pure/modules/esnext.global-this.js");
var parent = __webpack_require__(/*! ../actual/global-this */ "./node_modules/core-js-pure/actual/global-this.js");
module.exports = parent;

/***/ },
```

```
/***/ "./node_modules/core-js-pure/internals/a-callable.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/a-callable.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-pure/internals/is-callable.js");
var tryToString = __webpack_require__(/*! ../internals/try-to-string */ "./node_modules/core-js-pure/internals/try-to-string.js");
var $TypeError = TypeError;

// `Assert: IsCallable(argument) is true`
module.exports = function (argument) {
  if (isCallable(argument)) return argument;
  throw new $TypeError(tryToString(argument) + ' is not a function');
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/an-object.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/an-object.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var isObject = __webpack_require__(/*! ../internals/is-object */ "./node_modules/core-js-pure/internals/is-object.js");
var $String = String;
var $TypeError = TypeError;

// `Assert: Type(argument) is Object`
module.exports = function (argument) {
  if (isObject(argument)) return argument;
  throw new $TypeError($String(argument) + ' is not an object');
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/classof-raw.js"
/*!***********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/classof-raw.js ***!
  \***********************************************************/
```

```
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-
js-pure/internals/function-uncurry-this.js");
var toString = uncurryThis({}.toString);
var stringSlice = uncurryThis(".slice);
module.exports = function (it) {
  return stringSlice(toString(it), 8, -1);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/create-non-enumerable-property.js"
/*!*****************************************************************************!
*\
  !*** ./node_modules/core-js-pure/internals/create-non-enumerable-property.js ***!
  \*****************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var DESCRIPTORS = __webpack_require__(/*! ../internals/descriptors */ "./node_modules/core-js-
pure/internals/descriptors.js");
var definePropertyModule = __webpack_require__(/*! ../internals/object-define-property */
"./node_modules/core-js-pure/internals/object-define-property.js");
var
 createPropertyDescriptor = __webpack_require__(/*! ../internals/create-property-descriptor */
"./node_modules/core-js-pure/internals/create-property-descriptor.js");
module.exports = DESCRIPTORS ? function (object, key, value) {
  return definePropertyModule.f(object, key, createPropertyDescriptor(1, value));
} : function (object, key, value) {
  object[key] = value;
  return object;
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/create-property-descriptor.js"
/*!****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/create-property-descriptor.js ***!
  \****************************************************************************/
(module) {

"use strict";
```

```
module.exports = function (bitmap, value) {
  return {
    enumerable: !(bitmap & 1),
    configurable: !(bitmap & 2),
    writable: !(bitmap & 4),
    value: value
  };
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/define-global-property.js"
/*!***********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/define-global-property.js ***!
  \***********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");

// eslint-disable-next-line es/no-object-defineproperty -- safe
var defineProperty = Object.defineProperty;
module.exports = function (key, value) {
  try {
    defineProperty(globalThis, key, {
      value: value,
      configurable: true,
      writable: true
    });
  } catch (error) {
    globalThis[key] = value;
  }
  return value;
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/descriptors.js"
/*!************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/descriptors.js ***!
  \************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";
```

```
var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-pure/internals/fails.js");

// Detect IE8's incomplete defineProperty implementation
module.exports = !fails(function () {
  // eslint-disable-next-line es/no-object-defineproperty -- required for testing
  return Object.defineProperty({}, 1, {
    get: function () {
      return 7;
    }
  })[1] !== 7;
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/document-create-element.js"
/*!************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/document-create-element.js ***!
  \************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");
var isObject = __webpack_require__(/*! ../internals/is-object */ "./node_modules/core-js-pure/internals/is-object.js");
var document = globalThis.document;
// typeof document.createElement is 'object' in old IE
var EXISTS = isObject(document) && isObject(document.createElement);
module.exports = function (it) {
  return EXISTS ? document.createElement(it) : {};
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/environment-user-agent.js"
/*!***********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/environment-user-agent.js ***!
  \***********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");
```

```
var navigator = globalThis.navigator;
var userAgent = navigator && navigator.userAgent;
module.exports = userAgent ? String(userAgent) : '';

/***/ },

/***/ "./node_modules/core-js-pure/internals/environment-v8-version.js"
/*!*************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/environment-v8-version.js ***!
  \*************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-
pure/internals/global-this.js");
var userAgent = __webpack_require__(/*! ../internals/environment-user-agent */
"./node_modules/core-js-pure/internals/environment-user-agent.js");
var process = globalThis.process;
var Deno = globalThis.Deno;
var versions = process && process.versions || Deno && Deno.version;
var v8 = versions && versions.v8;
var match, version;
if (v8) {
  match = v8.split('.');
  // in old Chrome, versions of V8 isn't V8 = Chrome / 10
  // but their correct versions are not interesting for us
  version = match[0] > 0 && match[0] < 4 ? 1 : +(match[0] + match[1]);
}

// BrowserFS NodeJS `process` polyfill incorrectly set `.v8` to `0.0`
// so check `userAgent` even if `.v8` exists, but 0
if (!version && userAgent) {
  match = userAgent.match(/Edge\/(\d+)/);
  if (!match || match[1] >= 74) {
    match = userAgent.match(/Chrome\/(\d+)/);
    if (match) version = +match[1];
  }
}
module.exports = version;

/***/ },

/***/ "./node_modules/core-js-pure/internals/export.js"
/*!*******************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/export.js ***!
  \*******************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {
```

```
"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");
var apply = __webpack_require__(/*! ../internals/function-apply */ "./node_modules/core-js-pure/internals/function-apply.js");
var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this-clause */ "./node_modules/core-js-pure/internals/function-uncurry-this-clause.js");
var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-pure/internals/is-callable.js");
var getOwnPropertyDescriptor = (__webpack_require__(/*! ../internals/object-get-own-property-descriptor */ "./node_modules/core-js-pure/internals/object-get-own-property-descriptor.js").f);
var isForced = __webpack_require__(/*! ../internals/is-forced */ "./node_modules/core-js-pure/internals/is-forced.js");
var path = __webpack_require__(/*! ../internals/path */ "./node_modules/core-js-pure/internals/path.js");
var bind = __webpack_require__(/*! ../internals/function-bind-context */ "./node_modules/core-js-pure/internals/function-bind-context.js");
var createNonEnumerableProperty = __webpack_require__(/*! ../internals/create-non-enumerable-property */ "./node_modules/core-js-pure/internals/create-non-enumerable-property.js");
var hasOwn = __webpack_require__(/*! ../internals/has-own-property */ "./node_modules/core-js-pure/internals/has-own-property.js");
// add debugging info
__webpack_require__(/*! ../internals/shared-store */ "./node_modules/core-js-pure/internals/shared-store.js");
var wrapConstructor = function (NativeConstructor) {
  var Wrapper = function (a, b, c) {
    if (this instanceof Wrapper) {
      switch (arguments.length) {
        case 0:
          return new NativeConstructor();
        case 1:
          return new NativeConstructor(a);
        case 2:
          return new NativeConstructor(a, b);
      }
      return new NativeConstructor(a, b, c);
    }
    return apply(NativeConstructor, this, arguments);
  };
  Wrapper.prototype = NativeConstructor.prototype;
  return Wrapper;
};

/*
  options.target         - name of the target object
  options.global         - target is the global object
```

```
  options.stat          - export as static methods of target
  options.proto          - export as prototype methods of target
  options.real          - real prototype method for the `pure` version
  options.forced         - export even if the native feature is available
  options.bind          - bind methods to the target, required for the `pure` version
  options.wrap          - wrap constructors to preventing global pollution, required for the `pure` version
  options.unsafe        - use the simple assignment of property instead of delete + defineProperty
  options.sham          - add a flag to not completely full polyfills
  options.enumerable     - export as enumerable property
  options.dontCallGetSet - prevent calling a getter on target
  options.name          - the .name of the function if it does not match the key
*/
module.exports = function (options, source) {
  var TARGET = options.target;
  var GLOBAL = options.global;
  var STATIC = options.stat;
  var PROTO = options.proto;
  var nativeSource = GLOBAL ? globalThis : STATIC ? globalThis[TARGET] : globalThis[TARGET]
&& globalThis[TARGET].prototype;
  var target = GLOBAL ? path : path[TARGET] || createNonEnumerableProperty(path, TARGET, {})
[TARGET];
  var targetPrototype = target.prototype;
  var FORCED, USE_NATIVE, VIRTUAL_PROTOTYPE;
  var key, sourceProperty, targetProperty, nativeProperty, resultProperty, descriptor;
  for (key in source) {
    FORCED = isForced(GLOBAL ? key : TARGET + (STATIC ? '.' : '#') + key, options.forced);
    // contains in native
    USE_NATIVE = !FORCED && nativeSource && hasOwn(nativeSource, key);
    targetProperty = target[key];
    if (USE_NATIVE) if (options.dontCallGetSet) {
      descriptor = getOwnPropertyDescriptor(nativeSource, key);
      nativeProperty = descriptor && descriptor.value;
    } else nativeProperty = nativeSource[key];

    // export native or implementation
    sourceProperty
 = USE_NATIVE && nativeProperty ? nativeProperty : source[key];
    if (!FORCED && !PROTO && typeof targetProperty == typeof sourceProperty) continue;

    // bind methods to global for calling from export context
    if (options.bind && USE_NATIVE) resultProperty = bind(sourceProperty, globalThis);
    // wrap global constructors for prevent changes in this version
    else if (options.wrap && USE_NATIVE) resultProperty = wrapConstructor(sourceProperty);
    // make static versions for prototype methods
    else if (PROTO && isCallable(sourceProperty)) resultProperty = uncurryThis(sourceProperty);
    // default case
    else resultProperty = sourceProperty;

    // add a flag to not completely full polyfills
```

```
    if (options.sham || sourceProperty && sourceProperty.sham || targetProperty &&
targetProperty.sham) {
      createNonEnumerableProperty(resultProperty, 'sham', true);
    }
    createNonEnumerableProperty(target, key, resultProperty);
    if (PROTO) {
      VIRTUAL_PROTOTYPE = TARGET + 'Prototype';
      if (!hasOwn(path, VIRTUAL_PROTOTYPE)) {
        createNonEnumerableProperty(path, VIRTUAL_PROTOTYPE, {});
      }
      // export virtual prototype methods
      createNonEnumerableProperty(path[VIRTUAL_PROTOTYPE], key, sourceProperty);
      // export real prototype methods
      if (options.real && targetPrototype && (FORCED || !targetPrototype[key])) {
        createNonEnumerableProperty(targetPrototype, key, sourceProperty);
      }
    }
  }
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/fails.js"
/*!******************************************************!*\
  !*** ./node_modules/core-js-pure/internals/fails.js ***!
  \******************************************************/
(module) {

"use strict";


module.exports = function (exec) {
  try {
    return !!exec();
  } catch (error) {
    return true;
  }
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-apply.js"
/*!**************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-apply.js ***!
  \**************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";
```

```
var NATIVE_BIND = __webpack_require__(/*! ../internals/function-bind-native */
"./node_modules/core-js-pure/internals/function-bind-native.js");
var FunctionPrototype = Function.prototype;
var apply = FunctionPrototype.apply;
var call = FunctionPrototype.call;

// eslint-disable-next-line es/no-function-prototype-bind, es/no-reflect -- safe
module.exports = typeof Reflect == 'object' && Reflect.apply || (NATIVE_BIND ? call.bind(apply) :
function () {
  return call.apply(apply, arguments);
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-bind-context.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-bind-context.js ***!
  \*****************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this-clause */
"./node_modules/core-js-pure/internals/function-uncurry-this-clause.js");
var aCallable = __webpack_require__(/*! ../internals/a-callable */ "./node_modules/core-js-
pure/internals/a-callable.js");
var NATIVE_BIND = __webpack_require__(/*! ../internals/function-bind-native */
"./node_modules/core-js-pure/internals/function-bind-native.js");
var bind = uncurryThis(uncurryThis.bind);

// optional / simple context binding
module.exports = function (fn, that) {
  aCallable(fn);
  return that === undefined ? fn : NATIVE_BIND ? bind(fn, that) : function /* ...args */
  () {
    return fn.apply(that, arguments);
  };
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-bind-native.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-bind-native.js ***!
  \*****************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {
```

```
"use strict";


var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
pure/internals/fails.js");
module.exports = !fails(function () {
  // eslint-disable-next-line es/no-function-prototype-bind -- safe
  var test = function () {/* empty */}.bind();
  // eslint-disable-next-line no-prototype-builtins -- safe
  return typeof test != 'function' || test.hasOwnProperty('prototype');
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-call.js"
/*!*************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-call.js ***!
  \*************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var NATIVE_BIND = __webpack_require__(/*! ../internals/function-bind-native */
"./node_modules/core-js-pure/internals/function-bind-native.js");
var call = Function.prototype.call;
// eslint-disable-next-line es/no-function-prototype-bind -- safe
module.exports = NATIVE_BIND ? call.bind(call) : function () {
  return call.apply(call, arguments);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-uncurry-this-clause.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-uncurry-this-clause.js ***!
  \*****************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var classofRaw = __webpack_require__(/*! ../internals/classof-raw */ "./node_modules/core-js-
pure/internals/classof-raw.js");
var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-
js-pure/internals/function-uncurry-this.js");
module.exports = function (fn) {
  // Nashorn bug:
  //   https://github.com/zloirock/core-js/issues/1128
```

```
  //   https://github.com/zloirock/core-js/issues/1130
  if (classofRaw(fn) === 'Function') return uncurryThis(fn);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/function-uncurry-this.js"
/*!**********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/function-uncurry-this.js ***!
  \**********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var NATIVE_BIND = __webpack_require__(/*! ../internals/function-bind-native */
"./node_modules/core-js-pure/internals/function-bind-native.js");
var FunctionPrototype = Function.prototype;
var call = FunctionPrototype.call;
// eslint-disable-next-line es/no-function-prototype-bind -- safe
var uncurryThisWithBind = NATIVE_BIND && FunctionPrototype.bind.bind(call, call);
module.exports = NATIVE_BIND ? uncurryThisWithBind : function (fn) {
  return function () {
    return call.apply(fn, arguments);
  };
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/get-built-in.js"
/*!************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/get-built-in.js ***!
  \************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var path = __webpack_require__(/*! ../internals/path */ "./node_modules/core-js-
pure/internals/path.js");
var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-
pure/internals/global-this.js");
var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-
pure/internals/is-callable.js");
var aFunction = function (variable) {
  return isCallable(variable) ? variable : undefined;
};
module.exports = function (namespace, method) {
  return arguments.length < 2 ? aFunction(path[namespace]) || aFunction(globalThis[namespace]) :
```

```
path[namespace] && path[namespace][method] || globalThis[namespace] && globalThis[namespace]
[method];
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/get-method.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/get-method.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var aCallable = __webpack_require__(/*! ../internals/a-callable */ "./node_modules/core-js-
pure/internals/a-callable.js");
var isNullOrUndefined = __webpack_require__(/*! ../internals/is-null-or-undefined */
"./node_modules/core-js-pure/internals/is-null-or-undefined.js");

// `GetMethod` abstract operation
// https://tc39.es/ecma262/#sec-getmethod
module.exports = function (V, P) {
  var func = V[P];
  return isNullOrUndefined(func) ? undefined : aCallable(func);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/global-this.js"
/*!***********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/global-this.js ***!
  \***********************************************************/
(module) {

"use strict";


var check = function (it) {
  return it && it.Math === Math && it;
};

// https://github.com/zloirock/core-js/issues/86#issuecomment-115759028
module.exports =
// eslint-disable-next-line es/no-global-this -- safe
check(typeof globalThis == 'object' && globalThis) || check(typeof window == 'object' && window) ||
// eslint-disable-next-line no-restricted-globals -- safe
check(typeof self == 'object' && self) || check(typeof globalThis == 'object' && globalThis) ||
check(typeof this == 'object' && this) ||
```

```
// eslint-disable-next-line no-new-func -- fallback
function () {
  return this;
}() || Function('return this')();

/***/ },

/***/ "./node_modules/core-js-pure/internals/has-own-property.js"
/*!*****************************************
*****************************!*\
  !*** ./node_modules/core-js-pure/internals/has-own-property.js ***!
  \*****************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-
js-pure/internals/function-uncurry-this.js");
var toObject = __webpack_require__(/*! ../internals/to-object */ "./node_modules/core-js-
pure/internals/to-object.js");
var hasOwnProperty = uncurryThis({}.hasOwnProperty);

// `HasOwnProperty` abstract operation
// https://tc39.es/ecma262/#sec-hasownproperty
// eslint-disable-next-line es/no-object-hasown -- safe
module.exports = Object.hasOwn || function hasOwn(it, key) {
  return hasOwnProperty(toObject(it), key);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/ie8-dom-define.js"
/*!**************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/ie8-dom-define.js ***!
  \**************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var DESCRIPTORS = __webpack_require__(/*! ../internals/descriptors */ "./node_modules/core-js-
pure/internals/descriptors.js");
var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
pure/internals/fails.js");
var createElement = __webpack_require__(/*! ../internals/document-create-element */
"./node_modules/core-js-pure/internals/document-create-element.js");

// Thanks to IE8 for its funny defineProperty
```

```
module.exports = !DESCRIPTORS && !fails(function () {
  // eslint-disable-next-line es/no-object-defineproperty -- required for testing
  return Object.defineProperty(createElement('div'), 'a', {
    get: function () {
      return 7;
    }
  }).a !== 7;
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/indexed-object.js"
/*!***************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/indexed-object.js ***!
  \***************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-
js-pure/internals/function-uncurry-this.js");
var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
pure/internals/fails.js");
var classof = __webpack_require__(/*! ../internals/classof-raw */ "./node_modules/core-js-
pure/internals/classof-raw.js");
var $Object = Object;
var split = uncurryThis(".split);

// fallback for non-array-like ES3 and non-enumerable old V8 strings
module.exports = fails(function () {
  // throws an error in rhino, see https://github.com/mozilla/rhino/issues/346
  // eslint-disable-next-line no-prototype-builtins -- safe
  return !$Object('z').propertyIsEnumerable(0);
}) ? function (it) {
  return classof(it) === 'String' ? split(it, '') : $Object(it);
} : $Object;

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-callable.js"
/*!************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-callable.js ***!
  \************************************************************/
(module) {

"use strict";
```

```
// https://tc39.es/ecma262/#sec-IsHTMLDDA-internal-slot
var documentAll = typeof document == 'object' && document.all;

// `IsCallable` abstract operation
// https://tc39.es/ecma262/#sec-iscallable
// eslint-disable-next-line unicorn/no-typeof-undefined -- required for testing
module.exports = typeof documentAll == 'undefined' && documentAll !== undefined ? function
(argument) {
  return typeof argument == 'function' || argument === documentAll;
} : function (argument) {
  return typeof argument == 'function';
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-forced.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-forced.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
pure/internals/fails.js");
var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-
pure/internals/is-callable.js");
var replacement = /#|\.prototype\./;
var isForced = function (feature, detection) {
  var value = data[normalize(feature)];
  return value === POLYFILL ? true : value === NATIVE ? false : isCallable(detection) ?
fails(detection) : !!detection;
};
var normalize = isForced.normalize = function (string) {
  return String(string).replace(replacement, '.').toLowerCase();
};
var data = isForced.data = {};
var NATIVE = isForced.NATIVE = 'N';
var POLYFILL = isForced.POLYFILL = 'P';
module.exports = isForced;

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-null-or-undefined.js"
/*!*********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-null-or-undefined.js ***!
  \*********************************************************************/
(module) {
```

```
"use strict";


// we can't use just `it == null` since of `document.all` special case
// https://tc39.es/ecma262/#sec-IsHTMLDDA-internal-slot-aec
module.exports = function (it) {
  return it === null || it === undefined;
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-object.js"
/*!**********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-object.js ***!
  \**********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-
pure/internals/is-callable.js");
module.exports = function (it) {
  return typeof it == 'object' ? it !== null : isCallable(it);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-pure.js"
/*!*******************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-pure.js ***!
  \*******************************************************/
(module) {

"use strict";


module.exports = true;

/***/ },

/***/ "./node_modules/core-js-pure/internals/is-symbol.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/is-symbol.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";
```

```
var getBuiltIn = __webpack_require__(/*! ../internals/get-built-in */ "./node_modules/core-js-pure/internals/get-built-in.js");
var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-pure/internals/is-callable.js");
var isPrototypeOf = __webpack_require__(/*! ../internals/object-is-prototype-of */ "./node_modules/core-js-pure/internals/object-is-prototype-of.js");
var USE_SYMBOL_AS_UID = __webpack_require__(/*! ../internals/use-symbol-as-uid */ "./node_modules/core-js-pure/internals/use-symbol-as-uid.js");
var $Object = Object;
module.exports = USE_SYMBOL_AS_UID ? function (it) {
  return typeof it == 'symbol';
} : function (it) {
  var $Symbol = getBuiltIn('Symbol');
  return isCallable($Symbol) && isPrototypeOf($Symbol.prototype, $Object(it));
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/object-define-property.js"
/*!***********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/object-define-property.js ***!
  \***********************************************************************/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";


var DESCRIPTORS = __webpack_require__(/*! ../internals/descriptors */ "./node_modules/core-js-pure/internals/descriptors.js");
var IE8_DOM_DEFINE = __webpack_require__(/*! ../internals/ie8-dom-define */ "./node_modules/core-js-pure/internals/ie8-dom-define.js");
var V8_PROTOTYPE_DEFINE_BUG = __webpack_require__(/*! ../internals/v8-prototype-define-bug */ "./node_modules/core-js-pure/internals/v8-prototype-define-bug.js");
var anObject = __webpack_require__(/*! ../internals/an-object */ "./node_modules/core-js-pure/internals/an-object.js");
var toPropertyKey = __webpack_require__(/*! ../internals/to-property-key */ "./node_modules/core-js-pure/internals/to-property-key.js");
var $TypeError = TypeError;
// eslint-disable-next-line es/no-object-defineproperty -- safe
var $defineProperty = Object.defineProperty;
// eslint-disable-next-line es/no-object-getownpropertydescriptor -- safe
var $getOwnPropertyDescriptor = Object.getOwnPropertyDescriptor;
var ENUMERABLE = 'enumerable';
var CONFIGURABLE = 'configurable';
var WRITABLE = 'writable';

// `Object.defineProperty` method
```

```
// https://tc39.es/ecma262/#sec-object.defineproperty
exports.f = DESCRIPTORS ? V8_PROTOTYPE_DEFINE_BUG ? function defineProperty(O, P,
Attributes) {
  anObject(O);
  P = toPropertyKey(P);
  anObject(Attributes);
  if (typeof O === 'function' && P === 'prototype' && 'value' in Attributes && WRITABLE in
Attributes && !Attributes[WRITABLE]) {
    var current = $getOwnPropertyDescriptor(O, P);
    if (current && current[WRITABLE]) {
      O[P] = Attributes.value;
      Attributes = {
        configurable: CONFIGURABLE in Attributes ? Attributes[CONFIGURABLE] :
current[CONFIGURABLE],
        enumerable: ENUMERABLE in Attributes ? Attributes[ENUMERABLE] :
current[ENUMERABLE],
        writable: false
      };
    }
  }
  return $defineProperty(O, P, Attributes);
} : $defineProperty : function defineProperty(O, P, Attributes) {
  anObject(O);
  P = toPropertyKey(P);
  anObject(Attributes);
  if (IE8_DOM_DEFINE) try {
    return $defineProperty(O,
 P, Attributes);
  } catch (error) {/* empty */}
  if ('get' in Attributes || 'set' in Attributes) throw new $TypeError('Accessors not supported');
  if ('value' in Attributes) O[P] = Attributes.value;
  return O;
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/object-get-own-property-descriptor.js"
/*!
**********************************************************************************
!*\
  !*** ./node_modules/core-js-pure/internals/object-get-own-property-descriptor.js ***!

\**********************************************************************************
*/
(__unused_webpack_module, exports, __webpack_require__) {

"use strict";
```

```
var DESCRIPTORS = __webpack_require__(/*! ../internals/descriptors */ "./node_modules/core-js-pure/internals/descriptors.js");
var call = __webpack_require__(/*! ../internals/function-call */ "./node_modules/core-js-pure/internals/function-call.js");
var propertyIsEnumerableModule = __webpack_require__(/*! ../internals/object-property-is-enumerable */ "./node_modules/core-js-pure/internals/object-property-is-enumerable.js");
var createPropertyDescriptor = __webpack_require__(/*! ../internals/create-property-descriptor */ "./node_modules/core-js-pure/internals/create-property-descriptor.js");
var toIndexedObject = __webpack_require__(/*! ../internals/to-indexed-object */ "./node_modules/core-js-pure/internals/to-indexed-object.js");
var toPropertyKey = __webpack_require__(/*! ../internals/to-property-key */ "./node_modules/core-js-pure/internals/to-property-key.js");
var hasOwn = __webpack_require__(/*! ../internals/has-own-property */ "./node_modules/core-js-pure/internals/has-own-property.js");
var IE8_DOM_DEFINE = __webpack_require__(/*! ../internals/ie8-dom-define */ "./node_modules/core-js-pure/internals/ie8-dom-define.js");

// eslint-disable-next-line es/no-object-getownpropertydescriptor -- safe
var $getOwnPropertyDescriptor = Object.getOwnPropertyDescriptor;

// `Object.getOwnPropertyDescriptor` method
// https://tc39.es/ecma262/#sec-object.getownpropertydescriptor
exports.f = DESCRIPTORS ? $getOwnPropertyDescriptor : function getOwnPropertyDescriptor(O, P) {
  O = toIndexedObject(O);
  P = toPropertyKey(P);
  if (IE8_DOM_DEFINE) try {
    return $getOwnPropertyDescriptor(O, P);
  } catch (error) {/* empty */}
  if (hasOwn(O, P)) return createPropertyDescriptor(!call(propertyIsEnumerableModule.f, O, P), O[P]);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/object-is-prototype-of.js"
/*!***********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/object-is-prototype-of.js ***!
  \***********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-js-pure/internals/function-uncurry-this.js");
module.exports = uncurryThis({}.isPrototypeOf);

/***/ },
```

```
/***/ "./node_modules/core-js-pure/internals/object-property-is-enumerable.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/object-property-is-enumerable.js ***!
  \*****************************************************************************/
(__unused_webpack_module, exports) {

"use strict";


var $propertyIsEnumerable = {}.propertyIsEnumerable;
// eslint-disable-next-line es/no-object-getownpropertydescriptor -- safe
var getOwnPropertyDescriptor = Object.getOwnPropertyDescriptor;

// Nashorn ~ JDK8 bug
var NASHORN_BUG = getOwnPropertyDescriptor && !$propertyIsEnumerable.call({
  1: 2
}, 1);

// `Object.prototype.propertyIsEnumerable` method implementation
// https://tc39.es/ecma262/#sec-object.prototype.propertyisenumerable
exports.f = NASHORN_BUG ? function propertyIsEnumerable(V) {
  var descriptor = getOwnPropertyDescriptor(this, V);
  return !!descriptor && descriptor.enumerable;
} : $propertyIsEnumerable;

/***/ },

/***/ "./node_modules/core-js-pure/internals/ordinary-to-primitive.js"
/*!**********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/ordinary-to-primitive.js ***!
  \**********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var call = __webpack_require__(/*! ../internals/function-call */ "./node_modules/core-js-
pure/internals/function-call.js");
var isCallable = __webpack_require__(/*! ../internals/is-callable */ "./node_modules/core-js-
pure/internals/is-callable.js");
var isObject = __webpack_require__(/*! ../internals/is-object */ "./node_modules/core-js-
pure/internals/is-object.js");
var $TypeError = TypeError;

// `OrdinaryToPrimitive` abstract operation
// https://tc39.es/ecma262/#sec-ordinarytoprimitive
module.exports = function (input, pref) {
  var fn, val;
  if (pref === 'string' && isCallable(fn = input.toString) && !isObject(val = call(fn, input))) return val;
```

```
  if (isCallable(fn = input.valueOf) && !isObject(val = call(fn, input))) return val;
  if (pref !== 'string' && isCallable(fn = input.toString) && !isObject(val = call(fn, input))) return val;
  throw new $TypeError("Can't convert object to primitive value");
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/path.js"
/*!****************************************************!*\
  !*** ./node_modules/core-js-pure/internals/path.js ***!
  \****************************************************/
(module) {

"use strict";


module.exports = {};

/***/ },

/***/ "./node_modules/core-js-pure/internals/require-object-coercible.js"
/*!************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/require-object-coercible.js ***!
  \************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var isNullOrUndefined = __webpack_require__(/*! ../internals/is-null-or-undefined */
"./node_modules/core-js-pure/internals/is-null-or-undefined.js");
var $TypeError = TypeError;

// `RequireObjectCoercible` abstract operation
// https://tc39.es/ecma262/#sec-requireobjectcoercible
module.exports = function (it) {
  if (isNullOrUndefined(it)) throw new $TypeError("Can't call method on " + it);
  return it;
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/shared-store.js"
/*!************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/shared-store.js ***!
  \************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";
```

```
var IS_PURE = __webpack_require__(/*! ../internals/is-pure */ "./node_modules/core-js-pure/internals/is-pure.js");
var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");
var defineGlobalProperty = __webpack_require__(/*! ../internals/define-global-property */ "./node_modules/core-js-pure/internals/define-global-property.js");
var SHARED = '__core-js_shared__';
var store = module.exports = globalThis[SHARED] || defineGlobalProperty(SHARED, {});
(store.versions || (store.versions = [])).push({
  version: '3.49.0',
  mode: IS_PURE ? 'pure' : 'global',
  copyright: '© 2013–2025 Denis Pushkarev (zloirock.ru), 2025–2026 CoreJS Company (core-js.io). All rights reserved.',
  license: 'https://github.com/zloirock/core-js/blob/v3.49.0/LICENSE',
  source: 'https://github.com/zloirock/core-js'
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/shared.js"
/*!******************************************************!*\
  !*** ./node_modules/core-js-pure/internals/shared.js ***!
  \******************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var store = __webpack_require__(/*! ../internals/shared-store */ "./node_modules/core-js-pure/internals/shared-store.js");
module.exports = function (key, value) {
  return store[key] || (store[key] = value || {});
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/symbol-constructor-detection.js"
/*!*****************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/symbol-constructor-detection.js ***!
  \*****************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


/* eslint-disable es/no-symbol -- required for testing */
var V8_VERSION = __webpack_require__(/*! ../internals/environment-v8-version */
```

```
"./node_modules/core-js-pure/internals/environment-v8-version.js");
var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
pure/internals/fails.js");
var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-
pure/internals/global-this.js");
var $String = globalThis.String;

// eslint-disable-next-line es/no-object-getownpropertysymbols -- required for testing
module.exports = !!Object.getOwnPropertySymbols && !fails(function () {
  var symbol = Symbol('symbol detection');
  // Chrome 38 Symbol has incorrect toString conversion
  // `get-own-property-symbols` polyfill symbols converted to object are not Symbol instances
  // nb: Do not call `String` directly to avoid this being optimized out to `symbol+"` which will,
  // of course, fail.
  return !$String(symbol) || !(Object(symbol) instanceof Symbol) ||
  // Chrome 38-40 symbols are not inherited from DOM collections prototypes to instances
  !Symbol.sham && V8_VERSION && V8_VERSION < 41;
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/to-indexed-object.js"
/*!*****************************************************************!*\
  !***
 ./node_modules/core-js-pure/internals/to-indexed-object.js ***!
  \*****************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


// toObject with fallback for non-array-like ES3 strings
var IndexedObject = __webpack_require__(/*! ../internals/indexed-object */ "./node_modules/core-js-
pure/internals/indexed-object.js");
var requireObjectCoercible = __webpack_require__(/*! ../internals/require-object-coercible */
"./node_modules/core-js-pure/internals/require-object-coercible.js");
module.exports = function (it) {
  return IndexedObject(requireObjectCoercible(it));
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/to-object.js"
/*!*********************************************************!*\
  !*** ./node_modules/core-js-pure/internals/to-object.js ***!
  \*********************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";
```

```
var requireObjectCoercible = __webpack_require__(/*! ../internals/require-object-coercible */
"./node_modules/core-js-pure/internals/require-object-coercible.js");
var $Object = Object;

// `ToObject` abstract operation
// https://tc39.es/ecma262/#sec-toobject
module.exports = function (argument) {
  return $Object(requireObjectCoercible(argument));
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/to-primitive.js"
/*!*****************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/to-primitive.js ***!
  \*****************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var call = __webpack_require__(/*! ../internals/function-call */ "./node_modules/core-js-
pure/internals/function-call.js");
var isObject = __webpack_require__(/*! ../internals/is-object */ "./node_modules/core-js-
pure/internals/is-object.js");
var isSymbol = __webpack_require__(/*! ../internals/is-symbol */ "./node_modules/core-js-
pure/internals/is-symbol.js");
var getMethod = __webpack_require__(/*! ../internals/get-method */ "./node_modules/core-js-
pure/internals/get-method.js");
var ordinaryToPrimitive = __webpack_require__(/*! ../internals/ordinary-to-primitive */
"./node_modules/core-js-pure/internals/ordinary-to-primitive.js");
var wellKnownSymbol = __webpack_require__(/*! ../internals/well-known-symbol */
"./node_modules/core-js-pure/internals/well-known-symbol.js");
var $TypeError = TypeError;
var TO_PRIMITIVE = wellKnownSymbol('toPrimitive');

// `ToPrimitive` abstract operation
// https://tc39.es/ecma262/#sec-toprimitive
module.exports = function (input, pref) {
  if (!isObject(input) || isSymbol(input)) return input;
  var exoticToPrim = getMethod(input, TO_PRIMITIVE);
  var result;
  if (exoticToPrim) {
    if (pref === undefined) pref = 'default';
    result = call(exoticToPrim, input, pref);
    if (!isObject(result) || isSymbol(result)) return result;
    throw new $TypeError("Can't convert object to primitive value");
```

```
  }
  if (pref === undefined) pref = 'number';
  return ordinaryToPrimitive(input, pref);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/to-property-key.js"
/*!****************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/to-property-key.js ***!
  \****************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var toPrimitive = __webpack_require__(/*! ../internals/to-primitive */ "./node_modules/core-js-pure/internals/to-primitive.js");
var isSymbol = __webpack_require__(/*! ../internals/is-symbol */ "./node_modules/core-js-pure/internals/is-symbol.js");

// `ToPropertyKey` abstract operation
// https://tc39.es/ecma262/#sec-topropertykey
module.exports = function (argument) {
  var key = toPrimitive(argument, 'string');
  return isSymbol(key) ? key : key + '';
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/try-to-string.js"
/*!**************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/try-to-string.js ***!
  \**************************************************************/
(module) {

"use strict";


var $String = String;
module.exports = function (argument) {
  try {
    return $String(argument);
  } catch (error) {
    return 'Object';
  }
};

/***/ },
```

```
/***/ "./node_modules/core-js-pure/internals/uid.js"
/*!*************************************************!*\
  !*** ./node_modules/core-js-pure/internals/uid.js ***!
  \*************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var uncurryThis = __webpack_require__(/*! ../internals/function-uncurry-this */ "./node_modules/core-
js-pure/internals/function-uncurry-this.js");
var id = 0;
var postfix = Math.random();
var toString = uncurryThis(1.1.toString);
module.exports = function (key) {
  return 'Symbol(' + (key === undefined ? '' : key) + ')_' + toString(++id + postfix, 36);
};

/***/ },

/***/ "./node_modules/core-js-pure/internals/use-symbol-as-uid.js"
/*!*****************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/use-symbol-as-uid.js ***!
  \*****************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


/* eslint-disable es/no-symbol -- required for testing */
var NATIVE_SYMBOL = __webpack_require__(/*! ../internals/symbol-constructor-detection */
"./node_modules/core-js-pure/internals/symbol-constructor-detection.js");
module.exports = NATIVE_SYMBOL && !Symbol.sham && typeof Symbol.iterator == 'symbol';

/***/ },

/***/ "./node_modules/core-js-pure/internals/v8-prototype-define-bug.js"
/*!***********************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/v8-prototype-define-bug.js ***!
  \***********************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var DESCRIPTORS = __webpack_require__(/*! ../internals/descriptors */ "./node_modules/core-js-
pure/internals/descriptors.js");
var fails = __webpack_require__(/*! ../internals/fails */ "./node_modules/core-js-
```

```
pure/internals/fails.js");

// V8 ~ Chrome 36-
// https://bugs.chromium.org/p/v8/issues/detail?id=3334
module.exports = DESCRIPTORS && fails(function () {
  // eslint-disable-next-line es/no-object-defineproperty -- required for testing
  return Object.defineProperty(function () {/* empty */}, 'prototype', {
    value: 42,
    writable: false
  }).prototype !== 42;
});

/***/ },

/***/ "./node_modules/core-js-pure/internals/well-known-symbol.js"
/*!*************************************************************************!*\
  !*** ./node_modules/core-js-pure/internals/well-known-symbol.js ***!
  \*************************************************************************/
(module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-
pure/internals/global-this.js");
var shared = __webpack_require__(/*! ../internals/shared */ "./node_modules/core-js-
pure/internals/shared.js");
var hasOwn = __webpack_require__(/*! ../internals/has-own-property */ "./node_modules/core-js-
pure/internals/has-own-property.js");
var uid = __webpack_require__(/*! ../internals/uid */ "./node_modules/core-js-pure/internals/uid.js");
var NATIVE_SYMBOL = __webpack_require__(/*! ../internals/symbol-constructor-detection */
"./node_modules/core-js-pure/internals/symbol-constructor-detection.js");
var USE_SYMBOL_AS_UID = __webpack_require__(/*! ../internals/use-symbol-as-uid */
"./node_modules/core-js-pure/internals/use-symbol-as-uid.js");
var Symbol = globalThis.Symbol;
var WellKnownSymbolsStore = shared('wks');
var createWellKnownSymbol = USE_SYMBOL_AS_UID ? Symbol['for'] || Symbol : Symbol &&
Symbol.withoutSetter || uid;
module.exports = function (name) {
  if (!hasOwn(WellKnownSymbolsStore, name)) {
    WellKnownSymbolsStore[name] = NATIVE_SYMBOL && hasOwn(Symbol, name) ?
Symbol[name] : createWellKnownSymbol('Symbol.' + name);
  }
  return WellKnownSymbolsStore[name];
};

/***/ },

/***/ "./node_modules/core-js-pure/modules/es.global-this.js"
```

```
/*!*****************************************************************!*\
  !*** ./node_modules/core-js-pure/modules/es.global-this.js ***!
  \*****************************************************************/
(__unused_webpack_module, __unused_webpack_exports, __webpack_require__) {

"use strict";


var $ = __webpack_require__(/*! ../internals/export */ "./node_modules/core-js-pure/internals/export.js");
var globalThis = __webpack_require__(/*! ../internals/global-this */ "./node_modules/core-js-pure/internals/global-this.js");

// `globalThis` object
// https://tc39.es/ecma262/#sec-globalthis
$({
  global: true,
  forced: globalThis.globalThis !== globalThis
}, {
  globalThis: globalThis
});

/***/ },

/***/ "./node_modules/core-js-pure/modules/esnext.global-this.js"
/*!*****************************************************************!*\
  !*** ./node_modules/core-js-pure/modules/esnext.global-this.js ***!
  \*****************************************************************/
(__unused_webpack_module, __unused_webpack_exports, __webpack_require__) {

"use strict";


// TODO: Remove from `core-js@4`
__webpack_require__(/*! ../modules/es.global-this */ "./node_modules/core-js-pure/modules/es.global-this.js");

/***/ },

/***/ "./node_modules/core-js-pure/stable/global-this.js"
/*!*****************************************************************!*\
  !*** ./node_modules/core-js-pure/stable/global-this.js ***!
  \*****************************************************************/
(module, __unused_webpack_exports,
 __webpack_require__) {

"use strict";
```

```
var parent = __webpack_require__(/*! ../es/global-this */ "./node_modules/core-js-pure/es/global-this.js");
module.exports = parent;

/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/focusManager.js"
/*!**********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/focusManager.js ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   FocusManager: () => (/* binding */ FocusManager),
/* harmony export */   focusManager: () => (/* binding */ focusManager)
/* harmony export */ });
/* harmony import */ var _subscribable_js__WEBPACK_IMPORTED_MODULE_0__ = __webpack_require__(/*! ./subscribable.js */ "./node_modules/@tanstack/query-core/build/modern/subscribable.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_1__ = __webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
// src/focusManager.ts


var FocusManager = class extends _subscribable_js__WEBPACK_IMPORTED_MODULE_0__.Subscribable {
  #focused;
  #cleanup;
  #setup;
  constructor() {
    super();
    this.#setup = onFocus => {
      if (!_utils_js__WEBPACK_IMPORTED_MODULE_1__.isServer && window.addEventListener) {
        const listener = () => onFocus();
        window.addEventListener("visibilitychange", listener, false);
        return () => {
          window.removeEventListener("visibilitychange", listener);
        };
      }
      return;
    };
  }
  onSubscribe() {
    if (!this.#cleanup) {
      this.setEventListener(this.#setup);
    }
```

```
  }
  onUnsubscribe() {
    if (!this.hasListeners()) {
      this.#cleanup?.();
      this.#cleanup = void 0;
    }
  }
  setEventListener(setup) {
    this.#setup = setup;
    this.#cleanup?.();
    this.#cleanup = setup(focused => {
      if (typeof focused === "boolean") {
        this.setFocused(focused);
      } else {
        this.onFocus();
      }
    });
  }
  setFocused(focused) {
    const changed = this.#focused !== focused;
    if (changed) {
      this.#focused = focused;
      this.onFocus();
    }
  }
  onFocus() {
    const isFocused = this.isFocused();
    this.listeners.forEach(listener => {
      listener(isFocused);
    });
  }
  isFocused() {
    if (typeof this.#focused === "boolean") {
      return this.#focused;
    }
    return globalThis.document?.visibilityState !== "hidden";
  }
};
var focusManager = new FocusManager();


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/infiniteQueryBehavior.js"
/*!
**********************************************************************************!
*\
  !*** ./node_modules/@tanstack/query-core/build/modern/infiniteQueryBehavior.js ***!
```

```
\*****************************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   hasNextPage: () => (/* binding */ hasNextPage),
/* harmony export */   hasPreviousPage: () => (/* binding */ hasPreviousPage),
/* harmony export */   infiniteQueryBehavior: () => (/* binding */ infiniteQueryBehavior)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
// src/infiniteQueryBehavior.ts

function infiniteQueryBehavior(pages) {
  return {
    onFetch: (context, query) => {
      const options = context.options;
      const direction = context.fetchOptions?.meta?.fetchMore?.direction;
      const oldPages = context.state.data?.pages || [];
      const oldPageParams = context.state.data?.pageParams || [];
      let result = {
        pages: [],
        pageParams: []
      };
      let currentPage = 0;
      const fetchFn = async () => {
        let cancelled = false;
        const addSignalProperty = object => {
          Object.defineProperty(object, "signal", {
            enumerable: true,
            get: () => {
              if (context.signal.aborted) {
                cancelled = true;
              } else {
                context.signal.addEventListener("abort", () => {
                  cancelled = true;
                });
              }
              return context.signal;
            }
          });
        };
        const queryFn = (0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.ensureQueryFn)
(context.options, context.fetchOptions);
        const fetchPage = async (data, param, previous) => {
          if (cancelled) {
            return Promise.reject();
          }
```

```
        if (param == null && data.pages.length) {
          return Promise.resolve(data);
        }
        const queryFnContext = {
          queryKey: context.queryKey,
          pageParam: param,
          direction: previous ? "backward" : "forward",
          meta: context.options.meta
        };
        addSignalProperty(queryFnContext);
        const page = await queryFn(queryFnContext);
        const {
          maxPages
        } = context.options;
        const addTo = previous ? _utils_js__WEBPACK_IMPORTED_MODULE_0__.addToStart :
_utils_js__WEBPACK_IMPORTED_MODULE_0__.addToEnd;
        return {
          pages: addTo(data.pages, page, maxPages),
          pageParams: addTo(data.pageParams, param, maxPages)
        };
      };
      if (direction && oldPages.length) {
        const previous = direction === "backward";
        const pageParamFn = previous ? getPreviousPageParam : getNextPageParam;
        const oldData = {
          pages: oldPages,
          pageParams: oldPageParams
        };
        const param = pageParamFn(options, oldData);
        result = await fetchPage(oldData, param, previous);
      } else {
        const remainingPages = pages ?? oldPages.length;
        do {
          const param = currentPage === 0 ? oldPageParams[0] ?? options.initialPageParam :
getNextPageParam(options, result);
          if (currentPage > 0 && param == null) {
            break;
          }
          result = await fetchPage(result, param);
          currentPage++;
        } while (currentPage < remainingPages);
      }
      return result;
    };
    if (context.options.persister) {
      context.fetchFn = () => {
        return context.options.persister?.(fetchFn, {
          queryKey: context.queryKey,
          meta: context.options.meta,
```

```
          signal: context.signal
        }, query);
      };
    } else {
      context.fetchFn = fetchFn;
    }
  }
};
}
function getNextPageParam(options, {
  pages,
  pageParams
}) {
  const lastIndex = pages.length - 1;
  return pages.length > 0 ? options.getNextPageParam(pages[lastIndex], pages, pageParams[lastIndex],
pageParams) : void 0;
}
function getPreviousPageParam(options, {
  pages,
  pageParams
}) {
  return pages.length > 0 ? options.getPreviousPageParam?.(pages[0], pages, pageParams[0],
pageParams) : void 0;
}
function hasNextPage(options, data) {
  if (!data) return false;
  return getNextPageParam(options, data) != null;
}
function hasPreviousPage(options, data) {
  if (!data || !options.getPreviousPageParam) return false;
  return getPreviousPageParam(options, data) != null;
}


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/mutation.js"
/*!*********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/mutation.js ***!
  \*********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Mutation: () => (/* binding */ Mutation),
/* harmony export */   getDefaultState: () => (/* binding */ getDefaultState)
/* harmony export */ });
/* harmony import */ var _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__ =
```

```
__webpack_require__(/*! ./notifyManager.js */ "./node_modules/@tanstack/query-
core/build/modern/notifyManager.js");
/* harmony import */ var _removable_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./removable.js */ "./node_modules/@tanstack/query-
core/build/modern/removable.js");
/* harmony import */ var _retryer_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./retryer.js */ "./node_modules/@tanstack/query-
core/build/modern/retryer.js");
// src/mutation.ts



var Mutation = class extends _removable_js__WEBPACK_IMPORTED_MODULE_1__.Removable {
  #observers;
  #mutationCache;
  #retryer;
  constructor(config) {
    super();
    this.mutationId = config.mutationId;
    this.#mutationCache = config.mutationCache;
    this.#observers = [];
    this.state = config.state || getDefaultState();
    this.setOptions(config.options);
    this.scheduleGc();
  }
  setOptions(options) {
    this.options = options;
    this.updateGcTime(this.options.gcTime);
  }
  get meta() {
    return this.options.meta;
  }
  addObserver(observer) {
    if (!this.#observers.includes(observer)) {
      this.#observers.push(observer);
      this.clearGcTimeout();
      this.#mutationCache.notify({
        type: "observerAdded",
        mutation: this,
        observer
      });
    }
  }
  removeObserver(observer) {
    this.#observers = this.#observers.filter(x => x !== observer);
    this.scheduleGc();
    this.#mutationCache.notify({
      type: "observerRemoved",
```

```
  mutation: this,
    observer
  });
}
optionalRemove() {
  if (!this.#observers.length) {
    if (this.state.status === "pending") {
      this.scheduleGc();
    } else {
      this.#mutationCache.remove(this);
    }
  }
}
continue() {
  return this.#retryer?.continue() ??
  // continuing a mutation assumes that variables are set, mutation must have been dehydrated before
  this.execute(this.state.variables);
}
async execute(variables) {
  this.#retryer = (0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.createRetryer)({
    fn: () => {
      if (!this.options.mutationFn) {
        return Promise.reject(new Error("No mutationFn found"));
      }
      return this.options.mutationFn(variables);
    },
    onFail: (failureCount, error) => {
      this.#dispatch({
        type: "failed",
        failureCount,
        error
      });
    },
    onPause: () => {
      this.#dispatch({
        type: "pause"
      });
    },
    onContinue: () => {
      this.#dispatch({
        type: "continue"
      });
    },
    retry: this.options.retry ?? 0,
    retryDelay: this.options.retryDelay,
    networkMode: this.options.networkMode,
    canRun: () => this.#mutationCache.canRun(this)
  });
  const restored = this.state.status === "pending";
```

```
    const isPaused = !this.#retryer.canStart();
    try {
      if (!restored) {
        this.#dispatch({
          type: "pending",
          variables,
          isPaused
        });
        await this.#mutationCache.config.onMutate?.(variables, this);
        const context = await this.options.onMutate?.(variables);
        if (context !== this.state.context) {
          this.#dispatch({
            type: "pending",
            context,
            variables,
            isPaused
          });
        }
      }
      const data = await this.#retryer.start();
      await this.#mutationCache.config.onSuccess?.(data, variables, this.state.context, this);
      await this.options.onSuccess?.(data, variables, this.state.context);
      await this.#mutationCache.config.onSettled?.(data, null, this.state.variables, this.state.context, this);
      await this.options.onSettled?.(data, null, variables, this.state.context);
      this.#dispatch({
        type: "success",
        data
      });
      return data;
    } catch (error) {
      try {
        await this.#mutationCache.config.onError?.(error, variables, this.state.context, this);
        await this.options.onError?.(error, variables, this.state.context);
        await this.#mutationCache.config.onSettled?.(void 0, error, this.state.variables, this.state.context,
this);
        await this.options.onSettled?.(void 0, error, variables, this.state.context);
        throw error;
      } finally {
        this.#dispatch({
          type: "error",
          error
        });
      }
    } finally {
      this.#mutationCache.runNext(this);
    }
  }
  #dispatch(action) {
    const reducer = state => {
```

```
switch (action.type) {
  case "failed":
    return {
      ...state,
      failureCount: action.failureCount,
      failureReason: action.error
    };
  case "pause":
    return {
      ...state,
      isPaused: true
    };
  case "continue":
    return {
      ...state,
      isPaused: false
    };
  case "pending":
    return {
      ...state,
      context: action.context,
      data: void 0,
      failureCount: 0,
      failureReason: null,
      error: null,
      isPaused: action.isPaused,
      status: "pending",
      variables: action.variables,
      submittedAt: Date.now()
    };
  case "success":
    return {
      ...state,
      data: action.data,
      failureCount: 0,
      failureReason: null,
      error: null,
      status: "success",
      isPaused: false
    };
  case "error":
    return {
      ...state,
      data: void 0,
      error: action.error,
      failureCount: state.failureCount + 1,
      failureReason: action.error,
      isPaused: false,
      status: "error"
```

```
        };
      }
    };
    this.state = reducer(this.state);
    _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__.notifyManager.batch(() => {
      this.#observers.forEach(observer => {
        observer.onMutationUpdate(action);
      });
      this.#mutationCache.notify({
        mutation: this,
        type: "updated",
        action
      });
    });
  }
};
function getDefaultState() {
  return {
    context: void 0,
    data: void 0,
    error: null,
    failureCount: 0,
    failureReason: null,
    isPaused: false,
    status: "idle",
    variables: void 0,
    submittedAt: 0
  };
}


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/mutationCache.js"
/*!************************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/mutationCache.js ***!
  \************************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   MutationCache: () => (/* binding */ MutationCache)
/* harmony export */ });
/* harmony import */ var _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./notifyManager.js */ "./node_modules/@tanstack/query-
core/build/modern/notifyManager.js");
/* harmony import */ var _mutation_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./mutation.js */ "./node_modules/@tanstack/query-
```

```
core/build/modern/mutation.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
/* harmony import */ var _subscribable_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./subscribable.js */ "./node_modules/@tanstack/query-
core/build/modern/subscribable.js");
// src/mutationCache.ts



var MutationCache = class extends
_subscribable_js__WEBPACK_IMPORTED_MODULE_3__.Subscribable {
  constructor(config = {}) {
    super();
    this.config = config;
    this.#mutations = /* @__PURE__ */new Map();
    this.#mutationId = Date.now();
  }
  #mutations;
  #mutationId;
  build(client, options, state) {
    const mutation = new _mutation_js__WEBPACK_IMPORTED_MODULE_1__.Mutation({
      mutationCache: this,
      mutationId: ++this.#mutationId,
      options: client.defaultMutationOptions(options),
      state
    });
    this.add(mutation);
    return mutation;
  }
  add(mutation) {
    const scope = scopeFor(mutation);
    const mutations = this.#mutations.get(scope) ?? [];
    mutations.push(mutation);
    this.#mutations.set(scope, mutations);
    this.notify({
      type: "added",
      mutation
    });
  }
  remove(mutation) {
    const scope = scopeFor(mutation);
    if (this.#mutations.has(scope)) {
      const mutations = this.#mutations.get(scope)?.filter(x => x !== mutation);
      if (mutations) {
        if (mutations.length === 0) {
          this.#mutations.delete(scope);
        } else {
```

```
        this.#mutations.set(scope, mutations);
       }
      }
     }
     this.notify({
      type: "removed",
      mutation
     });
    }
    canRun(mutation) {
     const firstPendingMutation = this.#mutations.get(scopeFor(mutation))?.find(m => m.state.status ===
"pending");
     return !firstPendingMutation || firstPendingMutation === mutation;
    }
    runNext(mutation) {
     const foundMutation = this.#mutations.get(scopeFor(mutation))?.find(m => m !== mutation &&
m.state.isPaused);
     return foundMutation?.continue() ?? Promise.resolve();
    }
    clear() {
     _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__.notifyManager.batch(() => {
      this.getAll().forEach(mutation => {
       this.remove(mutation);
      });
     });
    }
    getAll() {
     return [...this.#mutations.values()].flat();
    }
    find(filters) {
     const defaultedFilters = {
      exact: true,
      ...filters
     };
     return this.getAll().find(mutation =>
(0,_utils_js__WEBPACK_IMPORTED_MODULE_2__.matchMutation)(defaultedFilters, mutation));
    }
    findAll(filters = {}) {
     return this.getAll().filter(mutation =>
(0,_utils_js__WEBPACK_IMPORTED_MODULE_2__.matchMutation)(filters, mutation));
    }
    notify(event) {
     _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__.notifyManager.batch(() => {
      this.listeners.forEach(listener => {
       listener(event);
      });
     });
    }
    resumePausedMutations() {
```

```
    const pausedMutations = this.getAll().filter(x => x.state.isPaused);
    return _notifyManager_js__WEBPACK_IMPORTED_MODULE_0__.notifyManager.batch(() =>
Promise.all(pausedMutations.map(mutation =>
mutation.continue().catch(_utils_js__WEBPACK_IMPORTED_MODULE_2__.noop))));
  }
};
function scopeFor(mutation) {
  return mutation.options.scope?.id ?? String(mutation.mutationId);
}


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/notifyManager.js"
/*!*************************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/notifyManager.js ***!
  \*************************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   createNotifyManager: () => (/* binding */ createNotifyManager),
/* harmony export */   notifyManager: () => (/* binding */ notifyManager)
/* harmony export
 */ });
// src/notifyManager.ts
function createNotifyManager() {
  let queue = [];
  let transactions = 0;
  let notifyFn = callback => {
    callback();
  };
  let batchNotifyFn = callback => {
    callback();
  };
  let scheduleFn = cb => setTimeout(cb, 0);
  const schedule = callback => {
    if (transactions) {
      queue.push(callback);
    } else {
      scheduleFn(() => {
        notifyFn(callback);
      });
    }
  };
  const flush = () => {
    const originalQueue = queue;
    queue = [];
```

```
  if (originalQueue.length) {
    scheduleFn(() => {
      batchNotifyFn(() => {
        originalQueue.forEach(callback => {
          notifyFn(callback);
        });
      });
    });
  }
};
return {
  batch: callback => {
    let result;
    transactions++;
    try {
      result = callback();
    } finally {
      transactions--;
      if (!transactions) {
        flush();
      }
    }
    return result;
  },
  /**
   * All calls to the wrapped function will be batched.
   */
  batchCalls: callback => {
    return (...args) => {
      schedule(() => {
        callback(...args);
      });
    };
  },
  schedule,
  /**
   * Use this method to set a custom notify function.
   * This can be used to for example wrap notifications with `React.act` while running tests.
   */
  setNotifyFunction: fn => {
    notifyFn = fn;
  },
  /**
   * Use this method to set a custom function to batch notifications together into a single tick.
   * By default React Query will use the batch function provided by ReactDOM or React Native.
   */
  setBatchNotifyFunction: fn => {
    batchNotifyFn = fn;
  },
```

```
    setScheduler: fn => {
      scheduleFn = fn;
    }
  };
}
var notifyManager = createNotifyManager();


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/onlineManager.js"
/*!*************************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/onlineManager.js ***!
  \*************************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   OnlineManager: () => (/* binding */ OnlineManager),
/* harmony export */   onlineManager: () => (/* binding */ onlineManager)
/* harmony export */ });
/* harmony import */ var _subscribable_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./subscribable.js */ "./node_modules/@tanstack/query-
core/build/modern/subscribable.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
// src/onlineManager.ts


var OnlineManager = class extends
_subscribable_js__WEBPACK_IMPORTED_MODULE_0__.Subscribable {
  #online = true;
  #cleanup;
  #setup;
  constructor() {
    super();
    this.#setup = onOnline => {
      if (!_utils_js__WEBPACK_IMPORTED_MODULE_1__.isServer && window.addEventListener)
{
        const onlineListener = () => onOnline(true);
        const offlineListener = () => onOnline(false);
        window.addEventListener("online", onlineListener, false);
        window.addEventListener("offline", offlineListener, false);
        return () => {
          window.removeEventListener("online", onlineListener);
          window.removeEventListener("offline", offlineListener);
        };
      }
```

```
      return;
    };
  }
  onSubscribe() {
    if (!this.#cleanup) {
      this.setEventListener(this.#setup);
    }
  }
  onUnsubscribe() {
    if (!this.hasListeners()) {
      this.#cleanup?.();
      this.#cleanup = void 0;
    }
  }
  setEventListener(setup) {
    this.#setup = setup;
    this.#cleanup?.();
    this.#cleanup = setup(this.setOnline.bind(this));
  }
  setOnline(online) {
    const changed = this.#online !== online;
    if (changed) {
      this.#online = online;
      this.listeners.forEach(listener => {
        listener(online);
      });
    }
  }
  isOnline() {
    return this.#online;
  }
};
var onlineManager = new OnlineManager();


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/query.js"
/*!*********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/query.js ***!
  \*********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Query: () => (/* binding */ Query),
/* harmony export */   fetchState: () => (/* binding */ fetchState)
/* harmony export */ });
```

```
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
/* harmony import */ var _notifyManager_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./notifyManager.js */ "./node_modules/@tanstack/query-
core/build/modern/notifyManager.js");
/* harmony import */ var _retryer_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./retryer.js */ "./node_modules/@tanstack/query-
core/build/modern/retryer.js");
/* harmony import */ var _removable_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./removable.js */ "./node_modules/@tanstack/query-
core/build/modern/removable.js");
// src/query.ts



var Query = class extends _removable_js__WEBPACK_IMPORTED_MODULE_3__.Removable {
  #initialState;
  #revertState;
  #cache;
  #retryer;
  #defaultOptions;
  #abortSignalConsumed;
  constructor(config) {
    super();
    this.#abortSignalConsumed = false;
    this.#defaultOptions = config.defaultOptions;
    this.setOptions(config.options);
    this.observers = [];
    this.#cache = config.cache;
    this.queryKey = config.queryKey;
    this.queryHash = config.queryHash;
    this.#initialState = getDefaultState(this.options);
    this.state = config.state ?? this.#initialState;
    this.scheduleGc();
  }
  get meta() {
    return this.options.meta;
  }
  get promise() {
    return this.#retryer?.promise;
  }
  setOptions(options) {
    this.options = {
      ...this.#defaultOptions,
      ...options
    };
    this.updateGcTime(this.options.gcTime);
  }
```

```
  optionalRemove() {
    if (!this.observers.length && this.state.fetchStatus === "idle") {
      this.#cache.remove(this);
    }
  }
  setData(newData, options) {
    const data = (0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.replaceData)(this.state.data,
newData, this.options);
    this.#dispatch({
      data,
      type: "success",
      dataUpdatedAt: options?.updatedAt,
      manual: options?.manual
    });
    return data;
  }
  setState(state, setStateOptions) {
    this.#dispatch({
      type: "setState",
      state,
      setStateOptions
    });
  }
  cancel(options) {
    const promise = this.#retryer?.promise;
    this.#retryer?.cancel(options);
    return promise ?
promise.then(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop).catch(_utils_js__WEBPACK
_IMPORTED_MODULE_0__.noop) : Promise.resolve();
  }
  destroy() {
    super.destroy();
    this.cancel({
      silent: true
    });
  }
  reset() {
    this.destroy();
    this.setState(this.#initialState);
  }
  isActive() {
    return this.observers.some(observer =>
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.resolveEnabled)(observer.options.enabled,
this) !== false);
  }
  isDisabled() {
    return this.getObserversCount() > 0 && !this.isActive();
  }
  isStale() {
```

```
    if (this.state.isInvalidated) {
      return true;
    }
    if (this.getObserversCount() > 0) {
      return this.observers.some(observer => observer.getCurrentResult().isStale);
    }
    return this.state.data === void 0;
  }
  isStaleByTime(staleTime = 0) {
    return this.state.isInvalidated || this.state.data === void 0 || !
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.timeUntilStale)(this.state.dataUpdatedAt,
staleTime);
  }
  onFocus() {
    const observer = this.observers.find(x => x.shouldFetchOnWindowFocus());
    observer?.refetch({
      cancelRefetch: false
    });
    this.#retryer?.continue();
  }
  onOnline() {
    const observer = this.observers.find(x => x.shouldFetchOnReconnect());
    observer?.refetch({
      cancelRefetch: false
    });
    this.#retryer?.continue();
  }
  addObserver(observer) {
    if (!this.observers.includes(observer)) {
      this.observers.push(observer);
      this.clearGcTimeout();
      this.#cache.notify({
        type: "observerAdded",
        query: this,
        observer
      });
    }
  }
  removeObserver(observer) {
    if (this.observers.includes(observer)) {
      this.observers = this.observers.filter(x => x !== observer);
      if (!this.observers.length) {
        if (this.#retryer) {
          if (this.#abortSignalConsumed) {
            this.#retryer.cancel({
              revert: true
            });
          } else {
            this.#retryer.cancelRetry();
```

```
        }
      }
      this.scheduleGc();
    }
    this.#cache.notify({
      type: "observerRemoved",
      query: this,
      observer
    });
  }
}
getObserversCount() {
  return this.observers.length;
}
invalidate() {
  if (!this.state.isInvalidated) {
    this.#dispatch({
      type: "invalidate"
    });
  }
}
fetch(options, fetchOptions) {
  if (this.state.fetchStatus !== "idle") {
    if (this.state.data !== void 0 && fetchOptions?.cancelRefetch) {
      this.cancel({
        silent: true
      });
    } else if (this.#retryer) {
      this.#retryer.continueRetry();
      return this.#retryer.promise;
    }
  }
  if (options) {
    this.setOptions(options);

  }
  if (!this.options.queryFn) {
    const observer = this.observers.find(x => x.options.queryFn);
    if (observer) {
      this.setOptions(observer.options);
    }
  }
  if (true) {
    if (!Array.isArray(this.options.queryKey)) {
      console.error(`As of v4, queryKey needs to be an Array. If you are using a string like 'repoData',
please change it to an Array, e.g. ['repoData']`);
    }
  }
  const abortController = new AbortController();
```

```
    const addSignalProperty = object => {
      Object.defineProperty(object, "signal", {
        enumerable: true,
        get: () => {
          this.#abortSignalConsumed = true;
          return abortController.signal;
        }
      });
    };
    const fetchFn = () => {
      const queryFn = (0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.ensureQueryFn)
(this.options, fetchOptions);
      const queryFnContext = {
        queryKey: this.queryKey,
        meta: this.meta
      };
      addSignalProperty(queryFnContext);
      this.#abortSignalConsumed = false;
      if (this.options.persister) {
        return this.options.persister(queryFn, queryFnContext, this);
      }
      return queryFn(queryFnContext);
    };
    const context = {
      fetchOptions,
      options: this.options,
      queryKey: this.queryKey,
      state: this.state,
      fetchFn
    };
    addSignalProperty(context);
    this.options.behavior?.onFetch(context, this);
    this.#revertState = this.state;
    if (this.state.fetchStatus === "idle" || this.state.fetchMeta !== context.fetchOptions?.meta) {
      this.#dispatch({
        type: "fetch",
        meta: context.fetchOptions?.meta
      });
    }
    const onError = error => {
      if (!((0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.isCancelledError)(error) &&
error.silent)) {
        this.#dispatch({
          type: "error",
          error
        });
      }
      if (!(0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.isCancelledError)(error)) {
        this.#cache.config.onError?.(error, this);
```

```
      this.#cache.config.onSettled?.(this.state.data, error, this);
    }
    if (!this.isFetchingOptimistic) {
      this.scheduleGc();
    }
    this.isFetchingOptimistic = false;
  };
  this.#retryer = (0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.createRetryer)({
    initialPromise: fetchOptions?.initialPromise,
    fn: context.fetchFn,
    abort: abortController.abort.bind(abortController),
    onSuccess: data => {
      if (data === void 0) {
        if (true) {
          console.error(`Query data cannot be undefined. Please make sure to return a value other than undefined from your query function. Affected query key: ${this.queryHash}`);
        }
        onError(new Error(`${this.queryHash} data is undefined`));
        return;
      }
      try {
        this.setData(data);
      } catch (error) {
        onError(error);
        return;
      }
      this.#cache.config.onSuccess?.(data, this);
      this.#cache.config.onSettled?.(data, this.state.error, this);
      if (!this.isFetchingOptimistic) {
        this.scheduleGc();
      }
      this.isFetchingOptimistic = false;
    },
    onError,
    onFail: (failureCount, error) => {
      this.#dispatch({
        type: "failed",
        failureCount,
        error
      });
    },
    onPause: () => {
      this.#dispatch({
        type: "pause"
      });
    },
    onContinue: () => {
      this.#dispatch({
        type: "continue"
```

```
      });
    },
    retry: context.options.retry,
    retryDelay: context.options.retryDelay,
    networkMode: context.options.networkMode,
    canRun: () => true
  });
  return this.#retryer.start();
}
#dispatch(action) {
  const reducer = state => {
    switch (action.type) {
      case "failed":
        return {
          ...state,
          fetchFailureCount: action.failureCount,
          fetchFailureReason: action.error
        };
      case "pause":
        return {
          ...state,
          fetchStatus: "paused"
        };
      case "continue":
        return {
          ...state,
          fetchStatus: "fetching"
        };
      case "fetch":
        return {
          ...state,
          ...fetchState(state.data, this.options),
          fetchMeta: action.meta ?? null
        };
      case "success":
        return {
          ...state,
          data: action.data,
          dataUpdateCount: state.dataUpdateCount + 1,
          dataUpdatedAt: action.dataUpdatedAt ?? Date.now(),
          error: null,
          isInvalidated: false,
          status: "success",
          ...(!action.manual && {
            fetchStatus: "idle",
            fetchFailureCount: 0,
            fetchFailureReason: null
          })
        };
```

```
      case "error":
        const error = action.error;
        if ((0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.isCancelledError)(error) &&
error.revert && this.#revertState) {
          return {
            ...this.#revertState,
            fetchStatus: "idle"
          };
        }
        return {
          ...state,
          error,
          errorUpdateCount: state.errorUpdateCount + 1,
          errorUpdatedAt: Date.now(),
          fetchFailureCount: state.fetchFailureCount + 1,
          fetchFailureReason: error,
          fetchStatus: "idle",
          status: "error"
        };
      case "invalidate":
        return {
          ...state,
          isInvalidated: true
        };
      case "setState":
        return {
          ...state,
          ...action.state
        };
    }
  };
  this.state = reducer(this.state);
  _notifyManager_js__WEBPACK_IMPORTED_MODULE_1__.notifyManager.batch(() => {
    this.observers.forEach(observer => {
      observer.onQueryUpdate();
    });
    this.#cache.notify({
      query: this,
      type: "updated",
      action
    });
  });
 }
};
function fetchState(data, options) {
 return {
  fetchFailureCount: 0,
  fetchFailureReason: null,
  fetchStatus: (0,_retryer_js__WEBPACK_IMPORTED_MODULE_2__.canFetch)
```

```
(options.networkMode) ? "fetching" : "paused",
    ...(data === void 0 && {
      error: null,
      status: "pending"
    })
  };
}
function getDefaultState(options) {
  const data = typeof options.initialData === "function" ? options.initialData() : options.initialData;
  const hasData = data !== void 0;
  const initialDataUpdatedAt = hasData ? typeof options.initialDataUpdatedAt === "function" ?
options.initialDataUpdatedAt() : options.initialDataUpdatedAt : 0;
  return {
    data,
    dataUpdateCount: 0,
    dataUpdatedAt: hasData ? initialDataUpdatedAt ?? Date.now() : 0,
    error: null,
    errorUpdateCount: 0,
    errorUpdatedAt: 0,
    fetchFailureCount: 0,
    fetchFailureReason: null,
    fetchMeta: null,
    isInvalidated: false,
    status: hasData ? "success" : "pending",
    fetchStatus: "idle"
  };
}


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/queryCache.js"
/*!**********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/queryCache.js ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   QueryCache: () => (/* binding */ QueryCache)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
/* harmony import */ var _query_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./query.js */ "./node_modules/@tanstack/query-core/build/modern/query.js");
/* harmony import */ var _notifyManager_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./notifyManager.js */ "./node_modules/@tanstack/query-
core/build/modern/notifyManager.js");
```

```
/* harmony import */ var _subscribable_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./subscribable.js */ "./node_modules/@tanstack/query-
core/build/modern/subscribable.js");
// src/queryCache.ts



var QueryCache = class extends
_subscribable_js__WEBPACK_IMPORTED_MODULE_3__.Subscribable {
  constructor(config = {}) {
    super();
    this.config = config;
    this.#queries = /* @__PURE__ */new Map();
  }
  #queries;
  build(client, options, state) {
    const queryKey = options.queryKey;
    const queryHash = options.queryHash ??
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.hashQueryKeyByOptions)(queryKey,
options);
    let query = this.get(queryHash);
    if (!query) {
      query = new _query_js__WEBPACK_IMPORTED_MODULE_1__.Query({
        cache: this,
        queryKey,
        queryHash,
        options: client.defaultQueryOptions(options),
        state,
        defaultOptions: client.getQueryDefaults(queryKey)
      });
      this.add(query);
    }
    return query;
  }
  add(query) {
    if (!this.#queries.has(query.queryHash)) {
      this.#queries.set(query.queryHash, query);
      this.notify({
        type: "added",
        query
      });
    }
  }
  remove(query) {
    const queryInMap = this.#queries.get(query.queryHash);
    if (queryInMap) {
      query.destroy();
      if (queryInMap === query) {
```

```
      this.#queries.delete(query.queryHash);
    }
    this.notify({
      type: "removed",
      query
    });
  }
}
clear() {
  _notifyManager_js__WEBPACK_IMPORTED_MODULE_2__.notifyManager.batch(() => {
    this.getAll().forEach(query => {
      this.remove(query);
    });
  });
}
get(queryHash) {
  return this.#queries.get(queryHash);

}
getAll() {
  return [...this.#queries.values()];
}
find(filters) {
  const defaultedFilters = {
    exact: true,
    ...filters
  };
  return this.getAll().find(query =>
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.matchQuery)(defaultedFilters, query));
}
findAll(filters = {}) {
  const queries = this.getAll();
  return Object.keys(filters).length > 0 ? queries.filter(query =>
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.matchQuery)(filters, query)) : queries;
}
notify(event) {
  _notifyManager_js__WEBPACK_IMPORTED_MODULE_2__.notifyManager.batch(() => {
    this.listeners.forEach(listener => {
      listener(event);
    });
  });
}
onFocus() {
  _notifyManager_js__WEBPACK_IMPORTED_MODULE_2__.notifyManager.batch(() => {
    this.getAll().forEach(query => {
      query.onFocus();
    });
  });
}
```

```
  onOnline() {
    _notifyManager_js__WEBPACK_IMPORTED_MODULE_2__.notifyManager.batch(() => {
      this.getAll().forEach(query => {
        query.onOnline();
      });
    });
  }
};


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/queryClient.js"
/*!**********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/queryClient.js ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   QueryClient: () => (/* binding */ QueryClient)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
/* harmony import */ var _queryCache_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./queryCache.js */ "./node_modules/@tanstack/query-
core/build/modern/queryCache.js");
/* harmony import */ var _mutationCache_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./mutationCache.js */ "./node_modules/@tanstack/query-
core/build/modern/mutationCache.js");
/* harmony import */ var _focusManager_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./focusManager.js */ "./node_modules/@tanstack/query-
core/build/modern/focusManager.js");
/* harmony import */ var _onlineManager_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ./onlineManager.js */ "./node_modules/@tanstack/query-
core/build/modern/onlineManager.js");
/* harmony import */ var _notifyManager_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ./notifyManager.js */ "./node_modules/@tanstack/query-
core/build/modern/notifyManager.js");
/* harmony import */ var _infiniteQueryBehavior_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ./infiniteQueryBehavior.js */ "./node_modules/@tanstack/query-
core/build/modern/infiniteQueryBehavior.js");
// src/queryClient.ts
```

```
var QueryClient = class {
  #queryCache;
  #mutationCache;
  #defaultOptions;
  #queryDefaults;
  #mutationDefaults;
  #mountCount;
  #unsubscribeFocus;
  #unsubscribeOnline;
  constructor(config = {}) {
    this.#queryCache = config.queryCache || new
_queryCache_js__WEBPACK_IMPORTED_MODULE_1__.QueryCache();
    this.#mutationCache = config.mutationCache || new
_mutationCache_js__WEBPACK_IMPORTED_MODULE_2__.MutationCache();
    this.#defaultOptions = config.defaultOptions || {};
    this.#queryDefaults = /* @__PURE__ */new Map();
    this.#mutationDefaults = /* @__PURE__ */new Map();
    this.#mountCount = 0;
  }
  mount() {
    this.#mountCount++;
    if (this.#mountCount !== 1) return;
    this.#unsubscribeFocus =
_focusManager_js__WEBPACK_IMPORTED_MODULE_3__.focusManager.subscribe(async focused
=> {
      if (focused) {
        await this.resumePausedMutations();
        this.#queryCache.onFocus();
      }
    });
    this.#unsubscribeOnline =
_onlineManager_js__WEBPACK_IMPORTED_MODULE_4__.onlineManager.subscribe(async online
=> {
      if (online) {
        await this.resumePausedMutations();
        this.#queryCache.onOnline();
      }
    });
  }
  unmount() {
    this.#mountCount--;
    if (this.#mountCount !== 0) return;
    this.#unsubscribeFocus?.();
    this.#unsubscribeFocus = void 0;
    this.#unsubscribeOnline?.();
    this.#unsubscribeOnline = void 0;
  }
```

```
  isFetching(filters) {
    return this.#queryCache.findAll({
      ...filters,
      fetchStatus: "fetching"
    }).length;
  }
  isMutating(filters) {
    return this.#mutationCache.findAll({
      ...filters,
      status: "pending"
    }).length;
  }
  getQueryData(queryKey) {
    const options = this.defaultQueryOptions({
      queryKey
    });
    return this.#queryCache.get(options.queryHash)?.state.data;
  }
  ensureQueryData(options) {
    const cachedData = this.getQueryData(options.queryKey);
    if (cachedData === void 0) return this.fetchQuery(options);else {
      const defaultedOptions = this.defaultQueryOptions(options);
      const query = this.#queryCache.build(this, defaultedOptions);
      if (options.revalidateIfStale &&
query.isStaleByTime((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.resolveStaleTime)
(defaultedOptions.staleTime, query))) {
        void this.prefetchQuery(defaultedOptions);
      }
      return Promise.resolve(cachedData);
    }
  }
  getQueriesData(filters) {
    return this.#queryCache.findAll(filters).map(({
      queryKey,
      state
    }) => {
      const data = state.data;
      return [queryKey, data];
    });
  }
  setQueryData(queryKey, updater, options) {
    const defaultedOptions = this.defaultQueryOptions({
      queryKey
    });
    const query = this.#queryCache.get(defaultedOptions.queryHash);
    const prevData = query?.state.data;
    const data = (0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.functionalUpdate)(updater,
prevData);
    if (data === void 0) {
```

```
      return void 0;
    }
    return this.#queryCache.build(this, defaultedOptions).setData(data, {
      ...options,
      manual: true
    });
  }
  setQueriesData(filters, updater, options) {
    return _notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() =>
this.#queryCache.findAll(filters).map(({
      queryKey
    }) => [queryKey, this.setQueryData(queryKey, updater, options)]));
  }
  getQueryState(queryKey) {
    const options = this.defaultQueryOptions({
      queryKey
    });
    return this.#queryCache.get(options.queryHash)?.state;
  }
  removeQueries(filters) {
    const queryCache = this.#queryCache;
    _notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() => {
      queryCache.findAll(filters).forEach(query => {
        queryCache.remove(query);
      });
    });
  }
  resetQueries(filters, options) {
    const queryCache = this.#queryCache;
    const refetchFilters = {
      type: "active",
      ...filters
    };
    return _notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() => {
      queryCache.findAll(filters).forEach(query => {
        query.reset();
      });
      return this.refetchQueries(refetchFilters, options);
    });
  }
  cancelQueries(filters = {}, cancelOptions = {}) {
    const defaultedCancelOptions = {
      revert: true,
      ...cancelOptions
    };
    const promises =
_notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() =>
this.#queryCache.findAll(filters).map(query => query.cancel(defaultedCancelOptions)));
    return
```

```
Promise.all(promises).then(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop).catch(_utils_js
__WEBPACK_IMPORTED_MODULE_0__.noop);
  }
  invalidateQueries(filters = {}, options = {}) {
    return _notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() => {
      this.#queryCache.findAll(filters).forEach(query => {
        query.invalidate();
      });
      if (filters.refetchType === "none") {
        return Promise.resolve();
      }
      const refetchFilters = {
        ...filters,
        type: filters.refetchType ?? filters.type ?? "active"
      };
      return this.refetchQueries(refetchFilters, options);
    });
  }
  refetchQueries(filters = {}, options) {
    const fetchOptions = {
      ...options,
      cancelRefetch: options?.cancelRefetch ?? true
    };
    const promises =
_notifyManager_js__WEBPACK_IMPORTED_MODULE_5__.notifyManager.batch(() =>
this.#queryCache.findAll(filters).filter(query => !query.isDisabled()).map(query => {
      let promise = query.fetch(void 0, fetchOptions);
      if (!fetchOptions.throwOnError) {
        promise = promise.catch(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop);
      }
      return query.state.fetchStatus === "paused" ? Promise.resolve() : promise;
    }));
    return Promise.all(promises).then(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop);
  }
  fetchQuery(options) {
    const defaultedOptions = this.defaultQueryOptions(options);
    if (defaultedOptions.retry === void 0) {
      defaultedOptions.retry = false;
    }
    const query = this.#queryCache.build(this, defaultedOptions);
    return
query.isStaleByTime((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.resolveStaleTime)
(defaultedOptions.staleTime, query)) ? query.fetch(defaultedOptions) :
Promise.resolve(query.state.data);
  }
  prefetchQuery(options) {
    return
this.fetchQuery(options).then(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop).catch(_utils
_js__WEBPACK_IMPORTED_MODULE_0__.noop);
```

```
  }
  fetchInfiniteQuery(options) {
    options.behavior =
(0,_infiniteQueryBehavior_js__WEBPACK_IMPORTED_MODULE_6__.infiniteQueryBehavior)
(options.pages);
    return this.fetchQuery(options);
  }
  prefetchInfiniteQuery(options) {
    return
this.fetchInfiniteQuery(options).then(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop).catch
(_utils_js__WEBPACK_IMPORTED_MODULE_0__.noop);
  }
  ensureInfiniteQueryData(options) {
    options.behavior =
(0,_infiniteQueryBehavior_js__WEBPACK_IMPORTED_MODULE_6__.infiniteQueryBehavior)
(options.pages);

    return this.ensureQueryData(options);
  }
  resumePausedMutations() {
    if (_onlineManager_js__WEBPACK_IMPORTED_MODULE_4__.onlineManager.isOnline()) {
      return this.#mutationCache.resumePausedMutations();
    }
    return Promise.resolve();
  }
  getQueryCache() {
    return this.#queryCache;
  }
  getMutationCache() {
    return this.#mutationCache;
  }
  getDefaultOptions() {
    return this.#defaultOptions;
  }
  setDefaultOptions(options) {
    this.#defaultOptions = options;
  }
  setQueryDefaults(queryKey, options) {
    this.#queryDefaults.set((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.hashKey)
(queryKey), {
      queryKey,
      defaultOptions: options
    });
  }
  getQueryDefaults(queryKey) {
    const defaults = [...this.#queryDefaults.values()];
    let result = {};
    defaults.forEach(queryDefault => {
      if ((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.partialMatchKey)(queryKey,
```

```
queryDefault.queryKey)) {
        result = {
          ...result,
          ...queryDefault.defaultOptions
        };
      }
    });
    return result;
  }
  setMutationDefaults(mutationKey, options) {
    this.#mutationDefaults.set((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.hashKey)
(mutationKey), {
      mutationKey,
      defaultOptions: options
    });
  }
  getMutationDefaults(mutationKey) {
    const defaults = [...this.#mutationDefaults.values()];
    let result = {};
    defaults.forEach(queryDefault => {
      if ((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.partialMatchKey)(mutationKey,
queryDefault.mutationKey)) {
        result = {
          ...result,
          ...queryDefault.defaultOptions
        };
      }
    });
    return result;
  }
  defaultQueryOptions(options) {
    if (options._defaulted) {
      return options;
    }
    const defaultedOptions = {
      ...this.#defaultOptions.queries,
      ...this.getQueryDefaults(options.queryKey),
      ...options,
      _defaulted: true
    };
    if (!defaultedOptions.queryHash) {
      defaultedOptions.queryHash =
(0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.hashQueryKeyByOptions)
(defaultedOptions.queryKey, defaultedOptions);
    }
    if (defaultedOptions.refetchOnReconnect === void 0) {
      defaultedOptions.refetchOnReconnect = defaultedOptions.networkMode !== "always";
    }
    if (defaultedOptions.throwOnError === void 0) {
```

```
      defaultedOptions.throwOnError = !!defaultedOptions.suspense;
    }
    if (!defaultedOptions.networkMode && defaultedOptions.persister) {
      defaultedOptions.networkMode = "offlineFirst";
    }
    if (defaultedOptions.enabled !== true && defaultedOptions.queryFn ===
_utils_js__WEBPACK_IMPORTED_MODULE_0__.skipToken) {
      defaultedOptions.enabled = false;
    }
    return defaultedOptions;
  }
  defaultMutationOptions(options) {
    if (options?._defaulted) {
      return options;
    }
    return {
      ...this.#defaultOptions.mutations,
      ...(options?.mutationKey && this.getMutationDefaults(options.mutationKey)),
      ...options,
      _defaulted: true
    };
  }
  clear() {
    this.#queryCache.clear();
    this.#mutationCache.clear();
  }
};


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/removable.js"
/*!*********************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/removable.js ***!
  \*********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Removable: () => (/* binding */ Removable)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
// src/removable.ts

var Removable = class {
  #gcTimeout;
  destroy() {
```

```
    this.clearGcTimeout();
  }
  scheduleGc() {
    this.clearGcTimeout();
    if ((0,_utils_js__WEBPACK_IMPORTED_MODULE_0__.isValidTimeout)(this.gcTime)) {
      this.#gcTimeout = setTimeout(() => {
        this.optionalRemove();
      }, this.gcTime);
    }
  }
  updateGcTime(newGcTime) {
    this.gcTime = Math.max(this.gcTime || 0, newGcTime ??
(_utils_js__WEBPACK_IMPORTED_MODULE_0__.isServer ? Infinity : 5 * 60 * 1e3));
  }
  clearGcTimeout() {
    if (this.#gcTimeout) {
      clearTimeout(this.#gcTimeout);
      this.#gcTimeout = void 0;
    }
  }
};


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/retryer.js"
/*!*******************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/retryer.js ***!
  \*******************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   CancelledError: () => (/* binding */ CancelledError),
/* harmony export */   canFetch: () => (/* binding */ canFetch),
/* harmony export */   createRetryer: () => (/* binding */ createRetryer),
/* harmony export */   isCancelledError: () => (/* binding */ isCancelledError)
/* harmony export */ });
/* harmony import */ var _focusManager_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./focusManager.js */ "./node_modules/@tanstack/query-
core/build/modern/focusManager.js");
/* harmony import */ var _onlineManager_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./onlineManager.js */ "./node_modules/@tanstack/query-
core/build/modern/onlineManager.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/@tanstack/query-core/build/modern/utils.js");
// src/retryer.ts
```

```
function defaultRetryDelay(failureCount) {
  return Math.min(1e3 * 2 ** failureCount, 3e4);
}
function canFetch(networkMode) {
  return (networkMode ?? "online") === "online" ?
_onlineManager_js__WEBPACK_IMPORTED_MODULE_1__.onlineManager.isOnline() : true;
}
var CancelledError = class extends Error {
  constructor(options) {
    super("CancelledError");
    this.revert = options?.revert;
    this.silent = options?.silent;
  }
};
function isCancelledError(value) {
  return value instanceof CancelledError;
}
function createRetryer(config) {
  let isRetryCancelled = false;
  let failureCount = 0;
  let isResolved = false;
  let continueFn;
  let promiseResolve;
  let promiseReject;
  const promise = new Promise((outerResolve, outerReject) => {
    promiseResolve = outerResolve;
    promiseReject = outerReject;
  });
  const cancel = cancelOptions => {
    if (!isResolved) {
      reject(new CancelledError(cancelOptions));
      config.abort?.();
    }
  };
  const cancelRetry = () => {
    isRetryCancelled = true;
  };
  const continueRetry = () => {
    isRetryCancelled = false;
  };
  const canContinue = () =>
_focusManager_js__WEBPACK_IMPORTED_MODULE_0__.focusManager.isFocused() &&
(config.networkMode === "always" ||
_onlineManager_js__WEBPACK_IMPORTED_MODULE_1__.onlineManager.isOnline()) &&
config.canRun();
  const canStart = () => canFetch(config.networkMode) && config.canRun();
  const resolve = value => {
```

```
    if (!isResolved) {
      isResolved = true;
      config.onSuccess?.(value);
      continueFn?.();
      promiseResolve(value);
    }
  };
  const reject = value => {
    if (!isResolved) {
      isResolved = true;
      config.onError?.(value);
      continueFn?.();
      promiseReject(value);
    }
  };
  const pause = () => {
    return new Promise(continueResolve => {
      continueFn = value => {
        if (isResolved || canContinue()) {
          continueResolve(value);
        }
      };
      config.onPause?.();
    }).then(() => {
      continueFn = void 0;
      if (!isResolved) {
        config.onContinue?.();
      }
    });
  };
  const run = () => {
    if (isResolved) {
      return;
    }
    let promiseOrValue;
    const initialPromise = failureCount === 0 ? config.initialPromise : void 0;
    try {
      promiseOrValue = initialPromise ?? config.fn();
    } catch (error) {
      promiseOrValue = Promise.reject(error);
    }
    Promise.resolve(promiseOrValue).then(resolve).catch(error => {
      if (isResolved) {
        return;
      }
      const retry = config.retry ?? (_utils_js__WEBPACK_IMPORTED_MODULE_2__.isServer ? 0 :
3);
      const retryDelay = config.retryDelay ?? defaultRetryDelay;
      const delay = typeof retryDelay === "function" ? retryDelay(failureCount, error) : retryDelay;
```

```
    const shouldRetry = retry === true || typeof retry === "number" && failureCount < retry || typeof retry === "function" && retry(failureCount, error);
    if (isRetryCancelled || !shouldRetry) {
      reject(error);
      return;
    }
    failureCount++;
    config.onFail?.(failureCount, error);
    (0,_utils_js__WEBPACK_IMPORTED_MODULE_2__.sleep)(delay).then(() => {
      return canContinue() ? void 0 : pause();
    }).then(() => {
      if (isRetryCancelled) {
        reject(error);
      } else {
        run();
      }
    });
  });
 };
 return {
  promise,
  cancel,
  continue: () => {
   continueFn?.();
   return promise;
  },
  cancelRetry,
  continueRetry,
  canStart,
  start: () => {
   if (canStart()) {
    run();
   } else {
    pause().then(run);
   }
   return promise;
  }
 };
}


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/subscribable.js"
/*!************************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/subscribable.js ***!
  \************************************************************************/
(__unused_webpack___webpack_module__,
 __webpack_exports__, __webpack_require__) {
```

```
"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Subscribable: () => (/* binding */ Subscribable)
/* harmony export */ });
// src/subscribable.ts
var Subscribable = class {
  constructor() {
    this.listeners = /* @__PURE__ */new Set();
    this.subscribe = this.subscribe.bind(this);
  }
  subscribe(listener) {
    this.listeners.add(listener);
    this.onSubscribe();
    return () => {
      this.listeners.delete(listener);
      this.onUnsubscribe();
    };
  }
  hasListeners() {
    return this.listeners.size > 0;
  }
  onSubscribe() {}
  onUnsubscribe() {}
};


/***/ },

/***/ "./node_modules/@tanstack/query-core/build/modern/utils.js"
/*!*****************************************************************!*\
  !*** ./node_modules/@tanstack/query-core/build/modern/utils.js ***!
  \*****************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   addToEnd: () => (/* binding */ addToEnd),
/* harmony export */   addToStart: () => (/* binding */ addToStart),
/* harmony export */   ensureQueryFn: () => (/* binding */ ensureQueryFn),
/* harmony export */   functionalUpdate: () => (/* binding */ functionalUpdate),
/* harmony export */   hashKey: () => (/* binding */ hashKey),
/* harmony export */   hashQueryKeyByOptions: () => (/* binding */ hashQueryKeyByOptions),
/* harmony export */   isPlainArray: () => (/* binding */ isPlainArray),
/* harmony export */   isPlainObject: () => (/* binding */ isPlainObject),
/* harmony export */   isServer: () => (/* binding */ isServer),
/* harmony export */   isValidTimeout: () => (/* binding */ isValidTimeout),
```

```
/* harmony export */   keepPreviousData: () => (/* binding */ keepPreviousData),
/* harmony export */   matchMutation: () => (/* binding */ matchMutation),
/* harmony export */   matchQuery: () => (/* binding */ matchQuery),
/* harmony export */   noop: () => (/* binding */ noop),
/* harmony export */   partialMatchKey: () => (/* binding */ partialMatchKey),
/* harmony export */   replaceData: () => (/* binding */ replaceData),
/* harmony export */   replaceEqualDeep: () => (/* binding */ replaceEqualDeep),
/* harmony export */   resolveEnabled: () => (/* binding */ resolveEnabled),
/* harmony export */   resolveStaleTime: () => (/* binding */ resolveStaleTime),
/* harmony export */   shallowEqualObjects: () => (/* binding */ shallowEqualObjects),
/* harmony export */   skipToken: () => (/* binding */ skipToken),
/* harmony export */   sleep: () => (/* binding */ sleep),
/* harmony export */   timeUntilStale: () => (/* binding */ timeUntilStale)
/* harmony export */ });
// src/utils.ts
var isServer = typeof window === "undefined" || "Deno" in globalThis;
function noop() {
  return void 0;
}
function functionalUpdate(updater, input) {
  return typeof updater === "function" ? updater(input) : updater;
}
function isValidTimeout(value) {
  return typeof value === "number" && value >= 0 && value !== Infinity;
}
function timeUntilStale(updatedAt, staleTime) {
  return Math.max(updatedAt + (staleTime || 0) - Date.now(), 0);
}
function resolveStaleTime(staleTime, query) {
  return typeof staleTime === "function" ? staleTime(query) : staleTime;
}
function resolveEnabled(enabled, query) {
  return typeof enabled === "function" ? enabled(query) : enabled;
}
function matchQuery(filters, query) {
  const {
    type = "all",
    exact,
    fetchStatus,
    predicate,
    queryKey,
    stale
  } = filters;
  if (queryKey) {
    if (exact) {
      if (query.queryHash !== hashQueryKeyByOptions(queryKey, query.options)) {
        return false;
      }
    } else if (!partialMatchKey(query.queryKey, queryKey)) {
```

```
      return false;
    }
  }
  if (type !== "all") {
    const isActive = query.isActive();
    if (type === "active" && !isActive) {
      return false;
    }
    if (type === "inactive" && isActive) {
      return false;
    }
  }
  if (typeof stale === "boolean" && query.isStale() !== stale) {
    return false;
  }
  if (fetchStatus && fetchStatus !== query.state.fetchStatus) {
    return false;
  }
  if (predicate && !predicate(query)) {
    return false;
  }
  return true;
}
function matchMutation(filters, mutation) {
  const {
    exact,
    status,
    predicate,
    mutationKey
  } = filters;
  if (mutationKey) {
    if (!mutation.options.mutationKey) {
      return false;
    }
    if (exact) {
      if (hashKey(mutation.options.mutationKey) !== hashKey(mutationKey)) {
        return false;
      }
    } else if (!partialMatchKey(mutation.options.mutationKey, mutationKey)) {
      return false;
    }
  }
  if (status && mutation.state.status !== status) {
    return false;
  }
  if (predicate && !predicate(mutation)) {
    return false;
  }
  return true;
```

```
}
function hashQueryKeyByOptions(queryKey, options) {
  const hashFn = options?.queryKeyHashFn || hashKey;
  return hashFn(queryKey);
}
function hashKey(queryKey) {
  return JSON.stringify(queryKey, (_, val) => isPlainObject(val) ?
Object.keys(val).sort().reduce((result, key) => {
    result[key] = val[key];
    return result;
  }, {}) : val);
}
function partialMatchKey(a, b) {
  if (a === b) {
    return true;
  }
  if (typeof a !== typeof b) {
    return false;
  }
  if (a && b && typeof a === "object" && typeof b === "object") {
    return !Object.keys(b).some(key => !partialMatchKey(a[key], b[key]));
  }
  return false;
}
function replaceEqualDeep(a, b) {
  if (a === b) {
    return a;
  }
  const array = isPlainArray(a) && isPlainArray(b);
  if (array || isPlainObject(a) && isPlainObject(b)) {
    const aItems = array ? a : Object.keys(a);
    const aSize = aItems.length;
    const bItems = array ? b : Object.keys(b);
    const bSize = bItems.length;
    const copy = array ? [] : {};
    let equalItems = 0;
    for (let i = 0; i < bSize; i++) {
      const key = array ? i : bItems[i];
      if ((!array && aItems.includes(key) || array) && a[key] === void 0 && b[key] === void 0) {
        copy[key] = void 0;
        equalItems++;
      } else {
        copy[key] = replaceEqualDeep(a[key], b[key]);
        if (copy[key] === a[key] && a[key] !== void 0) {
          equalItems++;
        }
      }
    }
    return aSize === bSize && equalItems === aSize ? a : copy;
```

```
  }
  return b;
}
function shallowEqualObjects(a, b) {
  if (!b || Object.keys(a).length !== Object.keys(b).length) {
    return false;
  }
  for (const key in a) {
    if (a[key] !== b[key]) {
      return false;
    }
  }
  return true;
}
function isPlainArray(value) {
  return Array.isArray(value) && value.length === Object.keys(value).length;
}
function isPlainObject(o) {
  if (!hasObjectPrototype(o)) {
    return false;
  }
  const ctor = o.constructor;
  if (ctor === void 0) {
    return true;
  }
  const prot = ctor.prototype;
  if (!hasObjectPrototype(prot)) {
    return false;
  }
  if (!prot.hasOwnProperty("isPrototypeOf")) {
    return false;
  }
  if (Object.getPrototypeOf(o) !== Object.prototype) {
    return false;
  }
  return true;
}
function hasObjectPrototype(o) {
  return Object.prototype.toString.call(o) === "[object Object]";
}
function sleep(timeout) {
  return new Promise(resolve => {
    setTimeout(resolve, timeout);
  });
}
function replaceData(prevData, data, options) {
  if (typeof options.structuralSharing === "function") {
    return options.structuralSharing(prevData, data);
  } else if (options.structuralSharing !== false) {
```

```
    if (true) {
      try {
        return replaceEqualDeep(prevData, data);
      } catch (error) {
        console.error(`Structural sharing requires data to be JSON serializable. To fix this, turn off
structuralSharing or return JSON-serializable data from your queryFn. [${options.queryHash}]: $
{error}`);
      }
    }
    return replaceEqualDeep(prevData, data);
  }
  return data;
}
function keepPreviousData(previousData) {
  return previousData;
}
function addToEnd(items, item, max = 0) {
  const newItems = [...items, item];
  return max && newItems.length > max ? newItems.slice(1) : newItems;
}
function addToStart(items, item, max = 0) {
  const newItems = [item, ...items];
  return max && newItems.length > max ? newItems.slice(0, -1) : newItems;
}
var skipToken = Symbol();
function ensureQueryFn(options, fetchOptions) {
  if (true) {
    if (options.queryFn === skipToken) {
      console.error(`Attempted to invoke queryFn when set to skipToken. This is likely a configuration
error. Query hash: '${options.queryHash}'`);
    }
  }
  if (!options.queryFn && fetchOptions?.initialPromise) {
    return () => fetchOptions.initialPromise;
  }
  if (!options.queryFn || options.queryFn === skipToken) {
    return () => Promise.reject(new Error(`Missing queryFn: '${options.queryHash}'`));
  }
  return options.queryFn;
}


/***/ },

/***/ "./node_modules/@tanstack/react-query/build/modern/QueryClientProvider.js"
/*!*************************************************************************************!
*\
  !*** ./node_modules/@tanstack/react-query/build/modern/QueryClientProvider.js ***!
  \*************************************************************************************/
```

```
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   QueryClientContext: () => (/* binding */ QueryClientContext),
/* harmony export */   QueryClientProvider: () => (/* binding */ QueryClientProvider),
/* harmony export */   useQueryClient: () => (/* binding */ useQueryClient)
/* harmony export */ });
/* harmony
 import */ var react__WEBPACK_IMPORTED_MODULE_0__ = __webpack_require__(/*! react */
"./node_modules/react/index.js");
/* harmony import */ var react_jsx_runtime__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react/jsx-runtime */ "./node_modules/react/jsx-runtime.js");
"use client";

// src/QueryClientProvider.tsx


var QueryClientContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(void 0);
var useQueryClient = queryClient => {
  const client = react__WEBPACK_IMPORTED_MODULE_0__.useContext(QueryClientContext);
  if (queryClient) {
    return queryClient;
  }
  if (!client) {
    throw new Error("No QueryClient set, use QueryClientProvider to set one");
  }
  return client;
};
var QueryClientProvider = ({
  client,
  children
}) => {
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    client.mount();
    return () => {
      client.unmount();
    };
  }, [client]);
  return /* @__PURE__ */(0,react_jsx_runtime__WEBPACK_IMPORTED_MODULE_1__.jsx)
(QueryClientContext.Provider, {
    value: client,
    children
  });
};


/***/ },
```

```
/***/ "./node_modules/axios/lib/adapters/adapters.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/adapters/adapters.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _http_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./http.js */ "./node_modules/axios/lib/helpers/null.js");
/* harmony import */ var _xhr_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./xhr.js */ "./node_modules/axios/lib/adapters/xhr.js");
/* harmony import */ var _fetch_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./fetch.js */ "./node_modules/axios/lib/adapters/fetch.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");




/**
 * Known adapters mapping.
 * Provides environment-specific adapters for Axios:
 * - `http` for Node.js
 * - `xhr` for browsers
 * - `fetch` for fetch API-based requests
 *
 * @type {Object<string, Function|Object>}
 */
const knownAdapters = {
  http: _http_js__WEBPACK_IMPORTED_MODULE_1__["default"],
  xhr: _xhr_js__WEBPACK_IMPORTED_MODULE_2__["default"],
  fetch: {
    get: _fetch_js__WEBPACK_IMPORTED_MODULE_3__.getFetch
  }
};

// Assign adapter names for easier debugging and identification
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(knownAdapters, (fn, value)
=> {
  if (fn) {
```

```
    try {
      // Null-proto descriptors so a polluted Object.prototype.get cannot turn
      // these data descriptors into accessor descriptors on the way in.
      Object.defineProperty(fn, 'name', {
        __proto__: null,
        value
      });
    } catch (e) {
      // eslint-disable-next-line no-empty
    }
    Object.defineProperty(fn, 'adapterName', {
      __proto__: null,
      value
    });
  }
});

/**
 * Render a rejection reason string for unknown or unsupported adapters
 *
 * @param {string} reason
 * @returns {string}
 */
const renderReason = reason => `- ${reason}`;

/**
 * Check if the adapter is resolved (function, null, or false)
 *
 * @param {Function|null|false} adapter
 * @returns {boolean}
 */
const isResolvedHandle = adapter =>
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(adapter) || adapter === null
|| adapter === false;

/**
 * Get the first suitable adapter from the provided list.
 * Tries each adapter in order until a supported one is found.
 * Throws an AxiosError if no adapter is suitable.
 *
 * @param {Array<string|Function>|string|Function} adapters - Adapter(s) by name or function.
 * @param {Object} config - Axios request configuration
 * @throws {AxiosError} If no suitable adapter is available
 * @returns {Function} The resolved adapter function
 */
function getAdapter(adapters, config) {
  adapters = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(adapters) ?
adapters : [adapters];
  const {
```

```
    length
  } = adapters;
  let nameOrAdapter;
  let adapter;
  const rejectedReasons = {};
  for (let i = 0; i < length; i++) {
    nameOrAdapter = adapters[i];
    let id;
    adapter = nameOrAdapter;
    if (!isResolvedHandle(nameOrAdapter)) {
      adapter = knownAdapters[(id = String(nameOrAdapter)).toLowerCase()];
      if (adapter === undefined) {
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_4__["default"]
(`Unknown adapter '${id}'`);
      }
    }
    if (adapter && (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(adapter)
|| (adapter = adapter.get(config)))) {
      break;
    }
    rejectedReasons[id || '#' + i] = adapter;
  }
  if (!adapter) {
    const reasons = Object.entries(rejectedReasons).map(([id, state]) => `adapter ${id} ` + (state ===
false ? 'is not supported by the environment' : 'is not available in the build'));
    let s = length ? reasons.length > 1 ? 'since :\n' + reasons.map(renderReason).join('\n') : ' ' +
renderReason(reasons[0]) : 'as no adapter specified';
    throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_4__["default"](`There is no
suitable adapter to dispatch the request ` + s, 'ERR_NOT_SUPPORT');
  }
  return adapter;
}

/**
 * Exports Axios adapters and utility to resolve an adapter
 */
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  /**
   * Resolve an adapter from a list of adapter names or functions.
   * @type {Function}
   */
  getAdapter,
  /**
   * Exposes all known adapters
   * @type {Object<string, Function|Object>}
   */
  adapters: knownAdapters
});
```

```
/***/ },

/***/ "./node_modules/axios/lib/adapters/fetch.js"
/*!**************************************************!*\
  !*** ./node_modules/axios/lib/adapters/fetch.js ***!
  \**************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__),
/* harmony export */   getFetch: () => (/* binding */ getFetch)
/* harmony export */ });
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _helpers_composeSignals_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../helpers/composeSignals.js */
"./node_modules/axios/lib/helpers/composeSignals.js");
/* harmony import */ var _helpers_trackStream_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../helpers/trackStream.js */
"./node_modules/axios/lib/helpers/trackStream.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../core/AxiosHeaders.js */
"./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var
_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../helpers/progressEventReducer.js */
"./node_modules/axios/lib/helpers/progressEventReducer.js");
/* harmony import */ var _helpers_resolveConfig_js__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ../helpers/resolveConfig.js */
"./node_modules/axios/lib/helpers/resolveConfig.js");
/* harmony import */ var _core_settle_js__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ../core/settle.js */ "./node_modules/axios/lib/core/settle.js");
/* harmony import */ var
_helpers_estimateDataURLDecodedBytes_js__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ../helpers/estimateDataURLDecodedBytes.js */
"./node_modules/axios/lib/helpers/estimateDataURLDecodedBytes.js");
/* harmony import */ var _env_data_js__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! ../env/data.js */ "./node_modules/axios/lib/env/data.js");
/* harmony import */ var
_helpers_sanitizeHeaderValue_js__WEBPACK_IMPORTED_MODULE_11__ =
__webpack_require__(/*! ../helpers/sanitizeHeaderValue.js */
"./node_modules/axios/lib/helpers/sanitizeHeaderValue.js");
```

```
const DEFAULT_CHUNK_SIZE = 64 * 1024;
const {
  isFunction
} = _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"];

/**
 * Encode a UTF-8 string to a Latin-1 byte string for use with btoa().
 * This is a modern replacement for the deprecated unescape(encodeURIComponent(str)) pattern.
 *
 * @param {string} str The string to encode
 *
 * @returns {string} UTF-8 bytes as a Latin-1 string
 */
const encodeUTF8 = str => encodeURIComponent(str).replace(/%([0-9A-F]{2})/gi, (_, hex) =>
String.fromCharCode(parseInt(hex, 16)));

// Node's WHATWG URL parser returns `username` and `password` percent-encoded.
// Decode before composing the `auth` option so credentials such as
// `my%40email.com:pass` are sent as `my@email.com:pass`. Falls back to the
// original value for malformed input so a bad encoding never throws.
const decodeURIComponentSafe = value => {
  if (!_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isString(value)) {
    return value;
  }
  try {
    return decodeURIComponent(value);
  } catch (error) {
    return value;
  }
};
const test = (fn,
 ...args) => {
  try {
    return !!fn(...args);
  } catch (e) {
    return false;
  }
};
```

```
const maybeWithAuthCredentials = url => {
  const protocolIndex = url.indexOf('://');
  let urlToCheck = url;
  if (protocolIndex !== -1) {
    urlToCheck = urlToCheck.slice(protocolIndex + 3);
  }
  return urlToCheck.includes('@') || urlToCheck.includes(':');
};
const factory = env => {
  const globalObject = _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].global !==
undefined && _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].global !== null ?
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].global : globalThis;
  const {
    ReadableStream,
    TextEncoder
  } = globalObject;
  env = _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].merge.call({
    skipUndefined: true
  }, {
    Request: globalObject.Request,
    Response: globalObject.Response
  }, env);
  const {
    fetch: envFetch,
    Request,
    Response
  } = env;
  const isFetchSupported = envFetch ? isFunction(envFetch) : typeof fetch === 'function';
  const isRequestSupported = isFunction(Request);
  const isResponseSupported = isFunction(Response);
  if (!isFetchSupported) {
    return false;
  }
  const isReadableStreamSupported = isFetchSupported && isFunction(ReadableStream);
  const encodeText = isFetchSupported && (typeof TextEncoder === 'function' ? (encoder => str =>
encoder.encode(str))(new TextEncoder()) : async str => new Uint8Array(await new
Request(str).arrayBuffer()));
  const supportsRequestStream = isRequestSupported && isReadableStreamSupported && test(() => {
    let duplexAccessed = false;
    const request = new
Request(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].origin, {
      body: new ReadableStream(),
      method: 'POST',
      get duplex() {
        duplexAccessed = true;
        return 'half';
      }
    });
    const hasContentType = request.headers.has('Content-Type');
```

```
    if (request.body != null) {
      request.body.cancel();
    }
    return duplexAccessed && !hasContentType;
  });
  const supportsResponseStream = isResponseSupported && isReadableStreamSupported && test(()
=> _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isReadableStream(new
Response('').body));
  const resolvers = {
    stream: supportsResponseStream && (res => res.body)
  };
  isFetchSupported && (() => {
    ['text', 'arrayBuffer', 'blob', 'formData', 'stream'].forEach(type => {
      !resolvers[type] && (resolvers[type] = (res, config) => {
        let method = res && res[type];
        if (method) {
          return method.call(res);
        }
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]
(`Response type '${type}' is not supported`,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_NOT_SUPPORT,
config);
      });
    });
  })();
  const getBodyLength = async body => {
    if (body == null) {
      return 0;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isBlob(body)) {
      return body.size;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isSpecCompliantForm(body)) {
      const _request = new
Request(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].origin, {
        method: 'POST',
        body
      });
      return (await _request.arrayBuffer()).byteLength;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isArrayBufferView(body) ||
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isArrayBuffer(body)) {
      return body.byteLength;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isURLSearchParams(body)) {
      body = body + '';
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isString(body)) {
      return (await encodeText(body)).byteLength;
```

```
    }
  };
  const resolveBodyLength = async (headers, body) => {
    const length =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].toFiniteNumber(headers.getContentLe
ngth());
    return length == null ? getBodyLength(body) : length;
  };
  return async config => {
    let {
      url,
      method,
      data,
      signal,
      cancelToken,
      timeout,
      onDownloadProgress,
      onUploadProgress,
      responseType,
      headers,
      withCredentials = 'same-origin',
      fetchOptions,
      maxContentLength,
      maxBodyLength
    } = (0,_helpers_resolveConfig_js__WEBPACK_IMPORTED_MODULE_7__["default"])(config);
    const hasMaxContentLength =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isNumber(maxContentLength) &&
maxContentLength > -1;
    const hasMaxBodyLength =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isNumber(maxBodyLength) &&
maxBodyLength > -1;
    const own = key =>
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].hasOwnProp(config, key) ?
config[key] : undefined;
    let _fetch = envFetch || fetch;
    responseType = responseType ? (responseType + '').toLowerCase() : 'text';
    let composedSignal =
(0,_helpers_composeSignals_js__WEBPACK_IMPORTED_MODULE_3__["default"])([signal,
cancelToken && cancelToken.toAbortSignal()], timeout);
    let request = null;
    const unsubscribe = composedSignal && composedSignal.unsubscribe && (() => {
      composedSignal.unsubscribe();
    });
    let requestContentLength;

    // AxiosError we raise while the request body is being streamed. Captured
    // by identity so the catch block can surface it directly, regardless of
    // how the runtime wraps the resulting fetch rejection (undici exposes it
    // as `err.cause`; some browsers drop the original error entirely).
```

```
    let pendingBodyError = null;
    const maxBodyLengthError = () => new
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]('Request body larger than
maxBodyLength limit',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_BAD_REQUEST,
config, request);
    try {
      // HTTP basic authentication
      let auth = undefined;
      const configAuth = own('auth');
      if (configAuth) {
        const username =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].getSafeProp(configAuth, 'username') ||
'';
        const password =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].getSafeProp(configAuth, 'password') ||
'';
        auth = {
          username,
          password
        };
      }
      if (maybeWithAuthCredentials(url)) {
        const parsedURL = new URL(url,
_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].origin);
        if (!auth && (parsedURL.username || parsedURL.password)) {
          const urlUsername = decodeURIComponentSafe(parsedURL.username);
          const urlPassword = decodeURIComponentSafe(parsedURL.password);
          auth = {
            username: urlUsername,
            password: urlPassword
          };
        }
        if (parsedURL.username || parsedURL.password) {
          parsedURL.username = '';
          parsedURL.password = '';
          url = parsedURL.href;
        }
      }
      if (auth) {
        headers.delete('authorization');
        headers.set('Authorization', 'Basic ' + btoa(encodeUTF8((auth.username || '') + ':' + (auth.password
|| ''))));
      }

      // Enforce maxContentLength for data: URLs up-front so we never materialize
      // an oversized payload. The HTTP adapter applies the same check (see http.js
      // "if (protocol === 'data:')" branch).
      if (hasMaxContentLength && typeof url === 'string' && url.startsWith('data:')) {
```

```
      const estimated =
(0,_helpers_estimateDataURLDecodedBytes_js__WEBPACK_IMPORTED_MODULE_9__["default"
])(url);
      if (estimated > maxContentLength) {
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]
('maxContentLength size of ' + maxContentLength + ' exceeded',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_BAD_RESPONSE,
config, request);
      }
    }

    // Enforce maxBodyLength against known-size bodies before dispatch using
    // the body's *actual* size — never a caller-declared Content-Length,
    // which could under-report to slip an oversized body past the check.
    // Unknown-size streams return undefined here and are counted per-chunk
    // below as fetch consumes them.
    if (hasMaxBodyLength && method !== 'get' && method !== 'head') {
      const outboundLength = await getBodyLength(data);
      if (typeof outboundLength === 'number' && isFinite(outboundLength)) {
        requestContentLength = outboundLength;
        if (outboundLength > maxBodyLength) {
          throw maxBodyLengthError();
        }
      }
    }

    // A streamed body under maxBodyLength must be counted as fetch consumes
    // it; its size is never trusted from a caller-declared Content-Length.
    const mustEnforceStreamBody = hasMaxBodyLength &&
(_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isReadableStream(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isStream(data));
    const trackRequestStream = (stream, onProgress, flush) =>
(0,_helpers_trackStream_js__WEBPACK_IMPORTED_MODULE_4__.trackStream)(stream,
DEFAULT_CHUNK_SIZE, loadedBytes => {
      if (hasMaxBodyLength && loadedBytes > maxBodyLength) {
        throw pendingBodyError = maxBodyLengthError();
      }
      onProgress && onProgress(loadedBytes);
    }, flush);
    if (supportsRequestStream && method !== 'get' && method !== 'head' && (onUploadProgress ||
mustEnforceStreamBody)) {
      requestContentLength = requestContentLength == null ? await resolveBodyLength(headers,
data) : requestContentLength;

      // A declared length of 0 is only trusted to skip the wrap when we are
      // not enforcing a stream limit (which must not rely on that header).
      if (requestContentLength !== 0 || mustEnforceStreamBody) {
        let _request = new Request(url, {
          method: 'POST',
```

```
          body: data,
          duplex: 'half'
        });
        let contentTypeHeader;
        if
 (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isFormData(data) &&
(contentTypeHeader = _request.headers.get('content-type'))) {
          headers.setContentType(contentTypeHeader);
        }
        if (_request.body) {
          const [onProgress, flush] = onUploadProgress &&
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.progressEventDeco
rator)(requestContentLength,
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.progressEventRedu
cer)
((0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.asyncDecorator)
(onUploadProgress))) || [];
          data = trackRequestStream(_request.body, onProgress, flush);
        }
      }
    } else if (mustEnforceStreamBody && !isRequestSupported && isReadableStreamSupported &&
method !== 'get' && method !== 'head') {
      data = trackRequestStream(data);
    } else if (mustEnforceStreamBody && isRequestSupported && !supportsRequestStream &&
method !== 'get' && method !== 'head') {
      throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]('Stream
request bodies are not supported by the current fetch implementation',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_NOT_SUPPORT,
config, request);
    }
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isString(withCredentials)) {
      withCredentials = withCredentials ? 'include' : 'omit';
    }

    // Cloudflare Workers throws when credentials are defined
    // see https://github.com/cloudflare/workerd/issues/902
    const isCredentialsSupported = isRequestSupported && 'credentials' in Request.prototype;

    // If data is FormData and Content-Type is multipart/form-data without boundary,
    // delete it so fetch can set it correctly with the boundary
    if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isFormData(data)) {
      const contentType = headers.getContentType();
      if (contentType && /^multipart\/form-data/i.test(contentType)
&& !/boundary=/i.test(contentType)) {
        headers.delete('content-type');
      }
    }

    // Set User-Agent header if not already set (fetch defaults to 'node' in Node.js)
```

```
    headers.set('User-Agent', 'axios/' +
_env_data_js__WEBPACK_IMPORTED_MODULE_10__.VERSION, false);
    const resolvedOptions = {
      ...fetchOptions,
      signal: composedSignal,
      method: method.toUpperCase(),
      headers:
(0,_helpers_sanitizeHeaderValue_js__WEBPACK_IMPORTED_MODULE_11__.toByteStringHeader
Object)(headers.normalize()),
      body: data,
      duplex: 'half',
      credentials: isCredentialsSupported ? withCredentials : undefined
    };
    request = isRequestSupported && new Request(url, resolvedOptions);
    let response = await (isRequestSupported ? _fetch(request, fetchOptions) : _fetch(url,
resolvedOptions));
    const responseHeaders =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_5__["default"].from(response.headers
);

    // Cheap pre-check: if the server honestly declares a content-length that
    // already exceeds the cap, reject before we start streaming.
    if (hasMaxContentLength) {
      const declaredLength =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].toFiniteNumber(responseHeaders.get
ContentLength());
      if (declaredLength != null && declaredLength > maxContentLength) {
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]
('maxContentLength size of ' + maxContentLength + ' exceeded',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_BAD_RESPONSE,
config, request);
      }
    }
    const isStreamResponse = supportsResponseStream && (responseType === 'stream' ||
responseType === 'response');
    if (supportsResponseStream && response.body && (onDownloadProgress ||
hasMaxContentLength || isStreamResponse && unsubscribe)) {
      const options = {};
      ['status', 'statusText', 'headers'].forEach(prop => {
        options[prop] = response[prop];
      });
      const responseContentLength =
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].toFiniteNumber(responseHeaders.get
ContentLength());
      const [onProgress, flush] = onDownloadProgress &&
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.progressEventDeco
rator)(responseContentLength,
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.progressEventRedu
cer)
```

```
((0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_6__.asyncDecorator)
(onDownloadProgress), true)) || [];
      let bytesRead = 0;
      const onChunkProgress = loadedBytes => {
        if (hasMaxContentLength) {
          bytesRead = loadedBytes;
          if (bytesRead > maxContentLength) {
            throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]
('maxContentLength size of ' + maxContentLength + ' exceeded',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_BAD_RESPONSE,
config, request);
          }
        }
        onProgress && onProgress(loadedBytes);
      };
      response = new
Response((0,_helpers_trackStream_js__WEBPACK_IMPORTED_MODULE_4__.trackStream)
(response.body, DEFAULT_CHUNK_SIZE, onChunkProgress, () => {
        flush && flush();
        unsubscribe && unsubscribe();
      }), options);
    }
    responseType = responseType || 'text';
    let responseData = await
resolvers[_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].findKey(resolvers,
responseType) || 'text'](response, config);

    // Fallback enforcement for environments without ReadableStream support
    // (legacy runtimes). Detect materialized size from typed output; skip
    // streams/Response passthrough since the user will read those themselves.
    if (hasMaxContentLength && !supportsResponseStream && !isStreamResponse) {
      let materializedSize;
      if (responseData != null) {
        if (typeof responseData.byteLength === 'number') {
          materializedSize = responseData.byteLength;
        } else if (typeof responseData.size === 'number') {
          materializedSize = responseData.size;
        } else if (typeof responseData === 'string') {
          materializedSize = typeof TextEncoder === 'function' ? new
TextEncoder().encode(responseData).byteLength : responseData.length;
        }
      }
      if (typeof materializedSize === 'number' && materializedSize > maxContentLength) {
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]
('maxContentLength size of ' + maxContentLength + ' exceeded',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_BAD_RESPONSE,
config, request);
      }
    }
```

```
      !isStreamResponse && unsubscribe && unsubscribe();
      return await new Promise((resolve, reject) => {
        (0,_core_settle_js__WEBPACK_IMPORTED_MODULE_8__["default"])(resolve, reject, {
          data: responseData,
          headers:
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_5__["default"].from(response.headers
),
          status: response.status,
          statusText: response.statusText,
          config,
          request
        });
      });
    } catch (err) {
      unsubscribe && unsubscribe();

      // Safari can surface fetch aborts as a DOMException-like object whose
      // branded getters throw. Prefer our composed signal reason before reading
      // the caught error, preserving timeout vs cancellation semantics.
      if (composedSignal && composedSignal.aborted && composedSignal.reason instanceof
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]) {
        const canceledError = composedSignal.reason;
        canceledError.config = config;
        request && (canceledError.request = request);
        err !== canceledError && (canceledError.cause = err);
        throw canceledError;
      }

      // Surface a maxBodyLength violation we raised while the request body was
      // being streamed. Matching by identity (rather than reading
      // `err.cause.isAxiosError`) keeps the error deterministic across runtimes
      // and avoids both prototype-pollution reads and mis-attributing a foreign
      // AxiosError that merely happened to land in `err.cause`.
      if (pendingBodyError) {
        request && !pendingBodyError.request && (pendingBodyError.request = request);
        throw pendingBodyError;
      }

      // Re-throw AxiosErrors we raised synchronously (data: URL / content-length
      // pre-checks, response size enforcement) without re-wrapping them.
      if (err instanceof _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]) {
        request && !err.request && (err.request = request);
        throw err;
      }
      if (err && err.name === 'TypeError' && /Load failed|fetch/i.test(err.message)) {
        throw Object.assign(new
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"]('Network Error',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].ERR_NETWORK,
config, request, err && err.response), {
```

```
        cause: err.cause || err
      });
    }
    throw _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_2__["default"].from(err, err
&& err.code, config, request, err && err.response);
  }
 };
};
const seedCache = new Map();
const getFetch = config => {
 let env = config && config.env || {};
 const {
  fetch,
  Request,
  Response
 } = env;
 const seeds = [Request, Response, fetch];
 let len = seeds.length,
  i = len,
  seed,
  target,
  map = seedCache;
 while (i--) {
  seed = seeds[i];
  target = map.get(seed);
  target === undefined && map.set(seed, target = i ? new Map() : factory(env));
  map = target;
 }
 return target;
};
const adapter = getFetch();
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (adapter);

/***/ },

/***/ "./node_modules/axios/lib/adapters/xhr.js"
/*!***********************************************!*\

 !*** ./node_modules/axios/lib/adapters/xhr.js ***!
 \***********************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
```

```
/* harmony import */ var _core_settle_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/settle.js */ "./node_modules/axios/lib/core/settle.js");
/* harmony import */ var _defaults_transitional_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../defaults/transitional.js */
"./node_modules/axios/lib/defaults/transitional.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../cancel/CanceledError.js */
"./node_modules/axios/lib/cancel/CanceledError.js");
/* harmony import */ var _helpers_parseProtocol_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../helpers/parseProtocol.js */
"./node_modules/axios/lib/helpers/parseProtocol.js");
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ../core/AxiosHeaders.js */
"./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var
_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ../helpers/progressEventReducer.js */
"./node_modules/axios/lib/helpers/progressEventReducer.js");
/* harmony import */ var _helpers_resolveConfig_js__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ../helpers/resolveConfig.js */
"./node_modules/axios/lib/helpers/resolveConfig.js");
/* harmony import */ var
_helpers_sanitizeHeaderValue_js__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! ../helpers/sanitizeHeaderValue.js */
"./node_modules/axios/lib/helpers/sanitizeHeaderValue.js");
```

```
const isXHRAdapterSupported = typeof XMLHttpRequest !== 'undefined';
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(isXHRAdapterSupported && function (config) {
  return new Promise(function dispatchXhrRequest(resolve, reject) {
    const _config =
(0,_helpers_resolveConfig_js__WEBPACK_IMPORTED_MODULE_9__["default"])(config);
    let requestData = _config.data;
    const requestHeaders =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_7__["default"].from(_config.headers).
```

```
normalize();
    let {
      responseType,
      onUploadProgress,
      onDownloadProgress
    } = _config;
    let onCanceled;
    let uploadThrottled, downloadThrottled;
    let flushUpload, flushDownload;
    function done() {
      flushUpload && flushUpload(); // flush events
      flushDownload && flushDownload(); // flush events

      _config.cancelToken && _config.cancelToken.unsubscribe(onCanceled);
      _config.signal && _config.signal.removeEventListener('abort', onCanceled);
    }
    let request = new XMLHttpRequest();
    request.open(_config.method.toUpperCase(), _config.url, true);

    // Set the request timeout in MS
    request.timeout = _config.timeout;
    function onloadend() {
      if (!request) {
        return;
      }
      // Prepare the response
      const responseHeaders =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_7__["default"].from('getAllResponse
Headers' in request && request.getAllResponseHeaders());
      const responseData = !responseType || responseType === 'text' || responseType === 'json' ?
request.responseText : request.response;
      const response = {
        data: responseData,
        status: request.status,
        statusText: request.statusText,
        headers: responseHeaders,
        config,
        request
      };
      (0,_core_settle_js__WEBPACK_IMPORTED_MODULE_1__["default"])(function _resolve(value)
{
        resolve(value);
        done();
      }, function _reject(err) {
        reject(err);
        done();
      }, response);

      // Clean up request
```

```
      request = null;
    }
    if ('onloadend' in request) {
      // Use onloadend if available
      request.onloadend = onloadend;
    } else {
      // Listen for ready state to emulate onloadend
      request.onreadystatechange = function handleLoad() {
        if (!request || request.readyState !== 4) {
          return;
        }

        // The request errored out and we didn't get a response, this will be
        // handled by onerror instead
        // With one exception: request that using file: protocol, most browsers
        // will return status as 0 even though it's a successful request
        if (request.status === 0 && !(request.responseURL && request.responseURL.startsWith('file:')))
{
          return;
        }
        // readystate handler is calling before onerror or ontimeout handlers,
        // so we should call onloadend on the next 'tick'
        setTimeout(onloadend);
      };
    }

    // Handle browser request cancellation (as opposed to a manual cancellation)
    request.onabort = function handleAbort() {
      if (!request) {
        return;
      }
      reject(new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"]('Request
aborted',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"].ECONNABORTED,
config, request));
      done();

      // Clean up request
      request = null;
    };

    // Handle low level network errors
    request.onerror = function handleError(event) {
      // Browsers deliver a ProgressEvent in XHR onerror
      // (message may be empty; when present, surface it)
      // See https://developer.mozilla.org/docs/Web/API/XMLHttpRequest/error_event
      const msg = event && event.message ? event.message : 'Network Error';
      const err = new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"](msg,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"].ERR_NETWORK,
```

```
config, request);
      // attach the underlying event for consumers who want details
      err.event = event || null;
      reject(err);
      done();
      request = null;
    };

    // Handle timeout
    request.ontimeout = function handleTimeout() {
      let timeoutErrorMessage = _config.timeout ? 'timeout of ' + _config.timeout + 'ms exceeded' :
'timeout exceeded';
      const transitional = _config.transitional ||
_defaults_transitional_js__WEBPACK_IMPORTED_MODULE_2__["default"];
      if (_config.timeoutErrorMessage) {
        timeoutErrorMessage = _config.timeoutErrorMessage;
      }
      reject(new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"]
(timeoutErrorMessage, transitional.clarifyTimeoutError ?
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"].ETIMEDOUT :
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"].ECONNABORTED,
config, request));
      done();

      // Clean up request
      request = null;
    };

    // Remove Content-Type if data is undefined
    requestData === undefined && requestHeaders.setContentType(null);

    // Add headers to the request
    if ('setRequestHeader' in request) {

_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach((0,_helpers_sanitizeHeaderVa
lue_js__WEBPACK_IMPORTED_MODULE_10__.toByteStringHeaderObject)(requestHeaders),
function setRequestHeader(val, key) {
        request.setRequestHeader(key, val);
      });
    }

    // Add withCredentials to request if needed
    if (!
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(_config.withCredentials))
{
      request.withCredentials = !!_config.withCredentials;
    }

    // Add responseType to request if needed
```

```
    if (responseType && responseType !== 'json') {
      request.responseType = _config.responseType;
    }

    // Handle progress if needed
    if (onDownloadProgress) {
      [downloadThrottled, flushDownload] =
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_8__.progressEventReducer)(onDownloadProgress, true);
      request.addEventListener('progress', downloadThrottled);
    }

    // Not all browsers support upload events
    if (onUploadProgress && request.upload) {
      [uploadThrottled, flushUpload] =
(0,_helpers_progressEventReducer_js__WEBPACK_IMPORTED_MODULE_8__.progressEventReducer)(onUploadProgress);
      request.upload.addEventListener('progress', uploadThrottled);
      request.upload.addEventListener('loadend', flushUpload);
    }
    if (_config.cancelToken || _config.signal) {
      // Handle cancellation
      // eslint-disable-next-line func-names
      onCanceled = cancel => {
        if (!request) {
          return;
        }
        reject(!cancel || cancel.type ? new
_cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_4__["default"](null, config,
request) : cancel);
        request.abort();
        done();
        request = null;
      };
      _config.cancelToken && _config.cancelToken.subscribe(onCanceled);
      if (_config.signal) {
        _config.signal.aborted ? onCanceled() : _config.signal.addEventListener('abort', onCanceled);
      }
    }
    const protocol =
(0,_helpers_parseProtocol_js__WEBPACK_IMPORTED_MODULE_5__["default"])(_config.url);
    if (protocol && !
_platform_index_js__WEBPACK_IMPORTED_MODULE_6__["default"].protocols.includes(protocol
)) {
      reject(new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"]
('Unsupported protocol ' + protocol + ':',
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_3__["default"].ERR_BAD_REQUEST,
config));
      return;
```

```
    }


    // Send the request
    request.send(requestData || null);
  });
});

/***/ },

/***/ "./node_modules/axios/lib/axios.js"
/*!*****************************************!*\
  !*** ./node_modules/axios/lib/axios.js ***!
  \*****************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _helpers_bind_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./helpers/bind.js */ "./node_modules/axios/lib/helpers/bind.js");
/* harmony import */ var _core_Axios_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./core/Axios.js */ "./node_modules/axios/lib/core/Axios.js");
/* harmony import */ var _core_mergeConfig_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./core/mergeConfig.js */ "./node_modules/axios/lib/core/mergeConfig.js");
/* harmony import */ var _defaults_index_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ./defaults/index.js */ "./node_modules/axios/lib/defaults/index.js");
/* harmony import */ var _helpers_formDataToJSON_js__WEBPACK_IMPORTED_MODULE_5__
= __webpack_require__(/*! ./helpers/formDataToJSON.js */
"./node_modules/axios/lib/helpers/formDataToJSON.js");
/* harmony import */ var _cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ./cancel/CanceledError.js */
"./node_modules/axios/lib/cancel/CanceledError.js");
/* harmony import */ var _cancel_CancelToken_js__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ./cancel/CancelToken.js */
"./node_modules/axios/lib/cancel/CancelToken.js");
/* harmony import */ var _cancel_isCancel_js__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ./cancel/isCancel.js */ "./node_modules/axios/lib/cancel/isCancel.js");
/* harmony import */ var _env_data_js__WEBPACK_IMPORTED_MODULE_9__ =
__webpack_require__(/*! ./env/data.js */ "./node_modules/axios/lib/env/data.js");
/* harmony import */ var _helpers_toFormData_js__WEBPACK_IMPORTED_MODULE_10__ =
__webpack_require__(/*! ./helpers/toFormData.js */
"./node_modules/axios/lib/helpers/toFormData.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_11__ =
__webpack_require__(/*! ./core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
```

```
/* harmony import */ var _helpers_spread_js__WEBPACK_IMPORTED_MODULE_12__ =
__webpack_require__(/*! ./helpers/spread.js */ "./node_modules/axios/lib/helpers/spread.js");
/* harmony import */ var _helpers_isAxiosError_js__WEBPACK_IMPORTED_MODULE_13__ =
__webpack_require__(/*! ./helpers/isAxiosError.js */
"./node_modules/axios/lib/helpers/isAxiosError.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_14__ =
__webpack_require__(/*! ./core/AxiosHeaders.js */ "./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var _adapters_adapters_js__WEBPACK_IMPORTED_MODULE_15__ =
__webpack_require__(/*! ./adapters/adapters.js */ "./node_modules/axios/lib/adapters/adapters.js");
/* harmony import */ var _helpers_HttpStatusCode_js__WEBPACK_IMPORTED_MODULE_16__ =
__webpack_require__(/*! ./helpers/HttpStatusCode.js */
"./node_modules/axios/lib/helpers/HttpStatusCode.js");
```

```
/**
 * Create an instance of Axios
 *
 * @param {Object} defaultConfig The default config for the instance
 *
 * @returns {Axios} A new instance of Axios
 */
function createInstance(defaultConfig) {
  const context = new _core_Axios_js__WEBPACK_IMPORTED_MODULE_2__["default"]
(defaultConfig);
  const instance = (0,_helpers_bind_js__WEBPACK_IMPORTED_MODULE_1__["default"])
(_core_Axios_js__WEBPACK_IMPORTED_MODULE_2__["default"].prototype.request, context);

  // Copy axios.prototype to instance
  _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].extend(instance,
_core_Axios_js__WEBPACK_IMPORTED_MODULE_2__["default"].prototype, context, {
    allOwnKeys: true
```

```
  });

  // Copy context to instance
  _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].extend(instance, context, null, {
    allOwnKeys: true
  });

  // Factory for creating new instances
  instance.create = function create(instanceConfig) {
    return
createInstance((0,_core_mergeConfig_js__WEBPACK_IMPORTED_MODULE_3__["default"])
(defaultConfig, instanceConfig));
  };
  return instance;
}

// Create the default instance to be exported
const axios =
createInstance(_defaults_index_js__WEBPACK_IMPORTED_MODULE_4__["default"]);

// Expose Axios class to allow class inheritance
axios.Axios = _core_Axios_js__WEBPACK_IMPORTED_MODULE_2__["default"];

// Expose Cancel & CancelToken
axios.CanceledError =
_cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_6__["default"];
axios.CancelToken = _cancel_CancelToken_js__WEBPACK_IMPORTED_MODULE_7__["default"];
axios.isCancel = _cancel_isCancel_js__WEBPACK_IMPORTED_MODULE_8__["default"];
axios.VERSION = _env_data_js__WEBPACK_IMPORTED_MODULE_9__.VERSION;
axios.toFormData = _helpers_toFormData_js__WEBPACK_IMPORTED_MODULE_10__["default"];

// Expose AxiosError class
axios.AxiosError = _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_11__["default"];

// alias for CanceledError for backward compatibility
axios.Cancel = axios.CanceledError;

// Expose all/spread
axios.all = function all(promises) {
  return Promise.all(promises);
};
axios.spread = _helpers_spread_js__WEBPACK_IMPORTED_MODULE_12__["default"];

// Expose isAxiosError
axios.isAxiosError =
_helpers_isAxiosError_js__WEBPACK_IMPORTED_MODULE_13__["default"];

// Expose mergeConfig
axios.mergeConfig = _core_mergeConfig_js__WEBPACK_IMPORTED_MODULE_3__["default"];
```

```
axios.AxiosHeaders =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_14__["default"];
axios.formToJSON = thing =>
(0,_helpers_formDataToJSON_js__WEBPACK_IMPORTED_MODULE_5__["default"])
(_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isHTMLForm(thing) ? new
FormData(thing) : thing);
axios.getAdapter =
_adapters_adapters_js__WEBPACK_IMPORTED_MODULE_15__["default"].getAdapter;
axios.HttpStatusCode =
_helpers_HttpStatusCode_js__WEBPACK_IMPORTED_MODULE_16__["default"];
axios.default = axios;

// this module should only have a default export
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (axios);

/***/ },

/***/ "./node_modules/axios/lib/cancel/CancelToken.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/cancel/CancelToken.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _CanceledError_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./CanceledError.js */ "./node_modules/axios/lib/cancel/CanceledError.js");




/**
 * A `CancelToken` is an object that can be used to request cancellation of an operation.
 *
 * @param {Function} executor The executor function.
 *
 * @returns {CancelToken}
 */
class CancelToken {
  constructor(executor) {
    if (typeof executor !== 'function') {
      throw new TypeError('executor must be a function.');
    }
    let resolvePromise;
    this.promise = new Promise(function promiseExecutor(resolve) {
      resolvePromise = resolve;
```

```
    });
    const token = this;

    // eslint-disable-next-line func-names
    this.promise.then(cancel => {
      if (!token._listeners) return;
      let i = token._listeners.length;
      while (i-- > 0) {
        token._listeners[i](cancel);
      }
      token._listeners = null;
    });

    // eslint-disable-next-line func-names
    this.promise.then = onfulfilled => {
      let _resolve;
      // eslint-disable-next-line func-names
      const promise = new Promise(resolve => {
        token.subscribe(resolve);
        _resolve = resolve;
      }).then(onfulfilled);
      promise.cancel = function reject() {
        token.unsubscribe(_resolve);
      };
      return promise;
    };
    executor(function cancel(message, config, request) {
      if (token.reason) {
        // Cancellation has already been requested
        return;
      }
      token.reason = new _CanceledError_js__WEBPACK_IMPORTED_MODULE_0__["default"]
(message, config, request);
      resolvePromise(token.reason);
    });
  }

  /**
   * Throws a `CanceledError` if cancellation has been requested.
   */
  throwIfRequested() {
    if (this.reason) {
      throw this.reason;
    }
  }

  /**
   * Subscribe to the cancel signal
   */
```

```
subscribe(listener) {
  if (this.reason) {
    listener(this.reason);
    return;
  }
  if (this._listeners) {
    this._listeners.push(listener);
  } else {
    this._listeners = [listener];
  }
}

/**
 * Unsubscribe from the cancel signal
 */

unsubscribe(listener) {
  if (!this._listeners) {
    return;
  }
  const index = this._listeners.indexOf(listener);
  if (index !== -1) {
    this._listeners.splice(index, 1);
  }
}
toAbortSignal() {
  const controller = new AbortController();
  const abort = err => {
    controller.abort(err);
  };
  this.subscribe(abort);
  controller.signal.unsubscribe = () => this.unsubscribe(abort);
  return controller.signal;
}

/**
 * Returns an object that contains a new `CancelToken` and a function that, when called,
 * cancels the `CancelToken`.
 */
static source() {
  let cancel;
  const token = new CancelToken(function executor(c) {
    cancel = c;
  });
  return {

   token,
    cancel
```

```
    };
  }
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (CancelToken);

/***/ },

/***/ "./node_modules/axios/lib/cancel/CanceledError.js"
/*!*******************************************************!*\
  !*** ./node_modules/axios/lib/cancel/CanceledError.js ***!
  \*******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");



class CanceledError extends
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"] {
  /**
   * A `CanceledError` is an object that is thrown when an operation is canceled.
   *
   * @param {string=} message The message.
   * @param {Object=} config The config.
   * @param {Object=} request The request.
   *
   * @returns {CanceledError} The created error.
   */
  constructor(message, config, request) {
    super(message == null ? 'canceled' : message,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"].ERR_CANCELED,
config, request);
    this.name = 'CanceledError';
    this.__CANCEL__ = true;
  }
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (CanceledError);

/***/ },

/***/ "./node_modules/axios/lib/cancel/isCancel.js"
/*!***************************************************!*\
  !*** ./node_modules/axios/lib/cancel/isCancel.js ***!
```

```
  \*************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ isCancel)
/* harmony export */ });


function isCancel(value) {
  return !!(value && value.__CANCEL__);
}

/***/ },

/***/ "./node_modules/axios/lib/core/Axios.js"
/*!**********************************************!*\
  !*** ./node_modules/axios/lib/core/Axios.js ***!
  \**********************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _helpers_buildURL_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../helpers/buildURL.js */ "./node_modules/axios/lib/helpers/buildURL.js");
/* harmony import */ var _InterceptorManager_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./InterceptorManager.js */
"./node_modules/axios/lib/core/InterceptorManager.js");
/* harmony import */ var _dispatchRequest_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./dispatchRequest.js */ "./node_modules/axios/lib/core/dispatchRequest.js");
/* harmony import */ var _mergeConfig_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ./mergeConfig.js */ "./node_modules/axios/lib/core/mergeConfig.js");
/* harmony import */ var _buildFullPath_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ./buildFullPath.js */ "./node_modules/axios/lib/core/buildFullPath.js");
/* harmony import */ var _helpers_validator_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../helpers/validator.js */ "./node_modules/axios/lib/helpers/validator.js");
/* harmony import */ var _AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ./AxiosHeaders.js */ "./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var _defaults_transitional_js__WEBPACK_IMPORTED_MODULE_8__ =
__webpack_require__(/*! ../defaults/transitional.js */
"./node_modules/axios/lib/defaults/transitional.js");
```

```
const validators =
_helpers_validator_js__WEBPACK_IMPORTED_MODULE_6__["default"].validators;

/**
 * Create a new instance of Axios
 *
 * @param {Object} instanceConfig The default config for the instance
 *
 * @return {Axios} A new instance of Axios
 */
class Axios {
  constructor(instanceConfig) {
    this.defaults = instanceConfig || {};
    this.interceptors = {
      request: new _InterceptorManager_js__WEBPACK_IMPORTED_MODULE_2__["default"](),
      response: new _InterceptorManager_js__WEBPACK_IMPORTED_MODULE_2__["default"]()
    };
  }

  /**
   * Dispatch a request
   *
   * @param {String|Object} configOrUrl The config specific for this request (merged with
this.defaults)
   * @param {?Object} config
   *
   * @returns {Promise} The Promise to be fulfilled
   */
  async request(configOrUrl, config) {
    try {
      return await this._request(configOrUrl, config);
    } catch (err) {
      if (err instanceof Error) {
        let dummy = {};
        Error.captureStackTrace ? Error.captureStackTrace(dummy) : dummy = new Error();

        // slice off the Error: ... line
        const stack = (() => {
          if (!dummy.stack) {
            return '';
```

```
        }
        const firstNewlineIndex = dummy.stack.indexOf('\n');
        return firstNewlineIndex === -1 ? '' : dummy.stack.slice(firstNewlineIndex + 1);
      })();
      try {
        if (!err.stack) {
          err.stack = stack;
          // match without the 2 top stack lines
        } else if (stack) {
          const firstNewlineIndex = stack.indexOf('\n');
          const secondNewlineIndex = firstNewlineIndex === -1 ? -1 : stack.indexOf('\n',
firstNewlineIndex + 1);
          const stackWithoutTwoTopLines = secondNewlineIndex === -1 ? '' :
stack.slice(secondNewlineIndex + 1);
          if (!String(err.stack).endsWith(stackWithoutTwoTopLines)) {
            err.stack += '\n' + stack;
          }
        }
      } catch (e) {
        // ignore the case where "stack" is an un-writable property
      }
    }
    throw err;
  }
 }
 _request(configOrUrl, config) {
  /*eslint no-param-reassign:0*/
  // Allow for axios('example/url'[, config]) a la fetch API
  if (typeof configOrUrl === 'string') {
    config = config || {};
    config.url = configOrUrl;
  } else {
    config = configOrUrl || {};
  }
  config = (0,_mergeConfig_js__WEBPACK_IMPORTED_MODULE_4__["default"])(this.defaults,
config);
  const {
    transitional,
    paramsSerializer,
    headers
  } = config;
  if (transitional !== undefined) {

_helpers_validator_js__WEBPACK_IMPORTED_MODULE_6__["default"].assertOptions(transitional
, {
      silentJSONParsing: validators.transitional(validators.boolean),
      forcedJSONParsing: validators.transitional(validators.boolean),
      clarifyTimeoutError: validators.transitional(validators.boolean),
      legacyInterceptorReqResOrdering: validators.transitional(validators.boolean),
```

```
      advertiseZstdAcceptEncoding: validators.transitional(validators.boolean),
      validateStatusUndefinedResolves: validators.transitional(validators.boolean)
    }, false);
  }
  if (paramsSerializer != null) {
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(paramsSerializer)) {
      config.paramsSerializer = {
        serialize: paramsSerializer
      };
    } else {

_helpers_validator_js__WEBPACK_IMPORTED_MODULE_6__["default"].assertOptions(paramsSeri
alizer, {
        encode: validators.function,
        serialize: validators.function
      }, true);
    }
  }

  // Set config.allowAbsoluteUrls
  if (config.allowAbsoluteUrls !== undefined) {
    // do nothing
  } else if (this.defaults.allowAbsoluteUrls !== undefined) {
    config.allowAbsoluteUrls = this.defaults.allowAbsoluteUrls;
  } else {
    config.allowAbsoluteUrls = true;
  }
  _helpers_validator_js__WEBPACK_IMPORTED_MODULE_6__["default"].assertOptions(config,
{
    baseUrl: validators.spelling('baseURL'),
    withXsrfToken: validators.spelling('withXSRFToken')
  }, true);

  // Set config.method
  config.method = (config.method || this.defaults.method || 'get').toLowerCase();

  // Flatten headers
  let contextHeaders = headers &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].merge(headers.common,
headers[config.method]);
  headers && _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(['delete', 'get',
'head', 'post', 'put', 'patch', 'query', 'common'], method => {
    delete headers[method];
  });
  config.headers =
_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_7__["default"].concat(contextHeaders,
headers);

  // filter out skipped interceptors
```

```
    const requestInterceptorChain = [];
    let synchronousRequestInterceptors = true;
    this.interceptors.request.forEach(function unshiftRequestInterceptors(interceptor) {
      if (typeof interceptor.runWhen === 'function' && interceptor.runWhen(config) === false) {
        return;
      }
      synchronousRequestInterceptors = synchronousRequestInterceptors && interceptor.synchronous;
      const transitional = config.transitional ||
_defaults_transitional_js__WEBPACK_IMPORTED_MODULE_8__["default"];
      const legacyInterceptorReqResOrdering = transitional &&
transitional.legacyInterceptorReqResOrdering;
      if (legacyInterceptorReqResOrdering) {
        requestInterceptorChain.unshift(interceptor.fulfilled, interceptor.rejected);
      } else {
        requestInterceptorChain.push(interceptor.fulfilled, interceptor.rejected);
      }
    });
    const responseInterceptorChain = [];
    this.interceptors.response.forEach(function
 pushResponseInterceptors(interceptor) {
      responseInterceptorChain.push(interceptor.fulfilled, interceptor.rejected);
    });
    let promise;
    let i = 0;
    let len;
    if (!synchronousRequestInterceptors) {
      const chain =
[_dispatchRequest_js__WEBPACK_IMPORTED_MODULE_3__["default"].bind(this), undefined];
      chain.unshift(...requestInterceptorChain);
      chain.push(...responseInterceptorChain);
      len = chain.length;
      promise = Promise.resolve(config);
      while (i < len) {
        promise = promise.then(chain[i++], chain[i++]);
      }
      return promise;
    }
    len = requestInterceptorChain.length;
    let newConfig = config;
    while (i < len) {
      const onFulfilled = requestInterceptorChain[i++];
      const onRejected = requestInterceptorChain[i++];
      try {
        newConfig = onFulfilled(newConfig);
      } catch (error) {
        onRejected.call(this, error);
        break;
      }
    }
```

```
    try {
      promise = _dispatchRequest_js__WEBPACK_IMPORTED_MODULE_3__["default"].call(this,
newConfig);
    } catch (error) {
      return Promise.reject(error);
    }
    i = 0;
    len = responseInterceptorChain.length;
    while (i < len) {
      promise = promise.then(responseInterceptorChain[i++], responseInterceptorChain[i++]);
    }
    return promise;
  }
  getUri(config) {
    config = (0,_mergeConfig_js__WEBPACK_IMPORTED_MODULE_4__["default"])(this.defaults,
config);
    const fullPath = (0,_buildFullPath_js__WEBPACK_IMPORTED_MODULE_5__["default"])
(config.baseURL, config.url, config.allowAbsoluteUrls, config);
    return (0,_helpers_buildURL_js__WEBPACK_IMPORTED_MODULE_1__["default"])(fullPath,
config.params, config.paramsSerializer);
  }
}

// Provide aliases for supported request methods
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(['delete', 'get', 'head',
'options'], function forEachMethodNoData(method) {
  /*eslint func-names:0*/
  Axios.prototype[method] = function (url, config) {
    return this.request((0,_mergeConfig_js__WEBPACK_IMPORTED_MODULE_4__["default"])
(config || {}, {
      method,
      url,
      data: config &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config, 'data') ?
config.data : undefined
    }));
  };
});
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(['post', 'put', 'patch', 'query'],
function forEachMethodWithData(method) {
  function generateHTTPMethod(isForm) {
    return function httpMethod(url, data, config) {
      return this.request((0,_mergeConfig_js__WEBPACK_IMPORTED_MODULE_4__["default"])
(config || {}, {
        method,
        headers: isForm ? {
          'Content-Type': 'multipart/form-data'
        } : {},
        url,
```

```
      data
    }));
  };
 }
 Axios.prototype[method] = generateHTTPMethod();

 // QUERY is a safe/idempotent read method; multipart form bodies don't fit
 // its semantics, so no queryForm shorthand is generated.
 if (method !== 'query') {
  Axios.prototype[method + 'Form'] = generateHTTPMethod(true);
 }
});
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (Axios);

/***/ },

/***/ "./node_modules/axios/lib/core/AxiosError.js"
/*!***************************************************!*\
  !*** ./node_modules/axios/lib/core/AxiosError.js ***!
  \***************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./AxiosHeaders.js */ "./node_modules/axios/lib/core/AxiosHeaders.js");




const REDACTED = '[REDACTED ****]';
function hasOwnOrPrototypeToJSON(source) {
 if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(source, 'toJSON')) {
  return true;
 }
 let prototype = Object.getPrototypeOf(source);
 while (prototype && prototype !== Object.prototype) {
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(prototype,
'toJSON')) {
    return true;
  }
  prototype = Object.getPrototypeOf(prototype);
 }
 return false;
```

```
}

// Build a plain-object snapshot of `config` and replace the value of any key
// (case-insensitive) listed in `redactKeys` with REDACTED. Walks through arrays
// and AxiosHeaders, and short-circuits on circular references.
function redactConfig(config, redactKeys) {
  const lowerKeys = new Set(redactKeys.map(k => String(k).toLowerCase()));
  const seen = [];
  const visit = source => {
    if (source === null || typeof source !== 'object') return source;
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBuffer(source)) return source;
    if (seen.indexOf(source) !== -1) return undefined;
    if (source instanceof _AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_1__["default"]) {
      source = source.toJSON();
    }
    seen.push(source);
    let result;
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(source)) {
      result = [];
      source.forEach((v, i) => {
        const reducedValue = visit(v);
        if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(reducedValue))
{
          result[i] = reducedValue;
        }
      });
    } else {
      if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(source) &&
hasOwnOrPrototypeToJSON(source)) {
        seen.pop();
        return source;
      }
      result = Object.create(null);
      for (const [key, value] of Object.entries(source)) {
        const reducedValue = lowerKeys.has(key.toLowerCase()) ? REDACTED : visit(value);
        if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(reducedValue))
{
          result[key] = reducedValue;
        }
      }
    }
    seen.pop();
    return result;
  };
  return visit(config);
}
class AxiosError extends Error {
  static from(error, code, config, request, response, customProps) {
    const axiosError = new AxiosError(error.message, code || error.code, config, request, response);
```

```
  axiosError.cause = error;
  axiosError.name = error.name;

  // Preserve status from the original error if not already set from response
  if (error.status != null && axiosError.status == null) {
    axiosError.status = error.status;
  }
  customProps && Object.assign(axiosError, customProps);
  return axiosError;
}

/**
 * Create an Error with the specified message, config, error code, request and response.
 *
 * @param {string} message The error message.
 * @param {string} [code] The error code (for example, 'ECONNABORTED').
 * @param {Object} [config] The config.
 * @param {Object} [request] The request.
 * @param {Object} [response] The response.
 *
 * @returns {Error} The created error.
 */
constructor(message, code, config, request, response) {
  super(message);

  // Make message enumerable to maintain backward compatibility
  // The native Error constructor sets message as non-enumerable,
  // but axios < v1.13.3 had it as enumerable
  Object.defineProperty(this, 'message', {
    // Null-proto descriptor so a polluted Object.prototype.get cannot turn
    // this data descriptor into an accessor descriptor on the way in.
    __proto__: null,
    value: message,
    enumerable: true,
    writable: true,
    configurable: true
  });
  this.name = 'AxiosError';
  this.isAxiosError = true;
  code && (this.code = code);
  config && (this.config = config);
  request && (this.request = request);
  if (response) {
    this.response = response;
    this.status = response.status;
  }
}
toJSON() {
  // Opt-in redaction: when the request config carries a `redact` array, the
```

```
    // value of any matching key (case-insensitive, at any depth) is replaced
    // with REDACTED in the serialized snapshot. Undefined or empty leaves the
    // existing serialization behavior unchanged.
    const config = this.config;
    const redactKeys = config &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config, 'redact') ?
config.redact : undefined;
    const serializedConfig =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(redactKeys) &&
redactKeys.length > 0 ? redactConfig(config, redactKeys) :
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toJSONObject(config);
    return {
      // Standard
      message: this.message,
      name: this.name,
      // Microsoft
      description: this.description,
      number: this.number,
      // Mozilla
      fileName: this.fileName,
      lineNumber: this.lineNumber,
      columnNumber: this.columnNumber,
      stack: this.stack,
      // Axios
      config: serializedConfig,
      code: this.code,
      status: this.status
    };
  }
}

// This can be changed to static properties as soon as the parser options in .eslint.cjs are updated.
AxiosError.ERR_BAD_OPTION_VALUE = 'ERR_BAD_OPTION_VALUE';
AxiosError.ERR_BAD_OPTION = 'ERR_BAD_OPTION';
AxiosError.ECONNABORTED = 'ECONNABORTED';
AxiosError.ETIMEDOUT = 'ETIMEDOUT';
AxiosError.ECONNREFUSED = 'ECONNREFUSED';
AxiosError.ERR_NETWORK = 'ERR_NETWORK';
AxiosError.ERR_FR_TOO_MANY_REDIRECTS = 'ERR_FR_TOO_MANY_REDIRECTS';
AxiosError.ERR_DEPRECATED = 'ERR_DEPRECATED';
AxiosError.ERR_BAD_RESPONSE = 'ERR_BAD_RESPONSE';
AxiosError.ERR_BAD_REQUEST = 'ERR_BAD_REQUEST';
AxiosError.ERR_CANCELED = 'ERR_CANCELED';
AxiosError.ERR_NOT_SUPPORT = 'ERR_NOT_SUPPORT';
AxiosError.ERR_INVALID_URL = 'ERR_INVALID_URL';
AxiosError.ERR_FORM_DATA_DEPTH_EXCEEDED =
'ERR_FORM_DATA_DEPTH_EXCEEDED';
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (AxiosError);
```

```
/***/
 },

/***/ "./node_modules/axios/lib/core/AxiosHeaders.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/core/AxiosHeaders.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _helpers_parseHeaders_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../helpers/parseHeaders.js */
"./node_modules/axios/lib/helpers/parseHeaders.js");
/* harmony import */ var
_helpers_sanitizeHeaderValue_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../helpers/sanitizeHeaderValue.js */
"./node_modules/axios/lib/helpers/sanitizeHeaderValue.js");




const $internals = Symbol('internals');
function normalizeHeader(header) {
  return header && String(header).trim().toLowerCase();
}
function normalizeValue(value) {
  if (value === false || value == null) {
    return value;
  }
  return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(value) ?
value.map(normalizeValue) :
(0,_helpers_sanitizeHeaderValue_js__WEBPACK_IMPORTED_MODULE_2__.sanitizeHeaderValue)
(String(value));
}
function parseTokens(str) {
  const tokens = Object.create(null);
  const tokensRE = /([^\s,;=]+)\s*(?:=\s*([^,;]+))?/g;
  let match;
  while (match = tokensRE.exec(str)) {
    tokens[match[1]] = match[2];
  }
  return tokens;
```

```
}
const isValidHeaderName = str => /^[-_a-zA-Z0-9^`|~,!#$%&'*+.]+$/.test(str.trim());
function matchHeaderValue(context, value, header, filter, isHeaderNameFilter) {
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(filter)) {
    return filter.call(this, value, header);
  }
  if (isHeaderNameFilter) {
    value = header;
  }
  if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(value)) return;
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(filter)) {
    return value.indexOf(filter) !== -1;
  }
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isRegExp(filter)) {
    return filter.test(value);
  }
}
function formatHeader(header) {
  return header.trim().toLowerCase().replace(/([a-z\d])(\w*)/g, (w, char, str) => {
    return char.toUpperCase() + str;
  });
}
function buildAccessors(obj, header) {
  const accessorName =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toCamelCase(' ' + header);
  ['get', 'set', 'has'].forEach(methodName => {
    Object.defineProperty(obj, methodName + accessorName, {
      // Null-proto descriptor so a polluted Object.prototype.get cannot turn
      // this data descriptor into an accessor descriptor on the way in.
      __proto__: null,
      value: function (arg1, arg2, arg3) {
        return this[methodName].call(this, header, arg1, arg2, arg3);
      },
      configurable: true
    });
  });
}
class AxiosHeaders {
  constructor(headers) {
    headers && this.set(headers);
  }
  set(header, valueOrRewrite, rewrite) {
    const self = this;
    function setHeader(_value, _header, _rewrite) {
      const lHeader = normalizeHeader(_header);
      if (!lHeader) {
        return;
      }
      const key = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].findKey(self,
```

```
lHeader);
      if (!key || self[key] === undefined || _rewrite === true || _rewrite === undefined && self[key] !==
false) {
        self[key || _header] = normalizeValue(_value);
      }
    }
    const setHeaders = (headers, _rewrite) =>
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(headers, (_value, _header) =>
setHeader(_value, _header, _rewrite));
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(header) || header
instanceof this.constructor) {
      setHeaders(header, valueOrRewrite);
    } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(header) &&
(header = header.trim()) && !isValidHeaderName(header)) {
      setHeaders((0,_helpers_parseHeaders_js__WEBPACK_IMPORTED_MODULE_1__["default"])
(header), valueOrRewrite);
    } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(header) &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isSafeIterable(header)) {
      let obj = Object.create(null),
        dest,
        key;
      for (const entry of header) {
        if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(entry)) {
          throw new TypeError('Object iterator must return a key-value pair');
        }
        key = entry[0];
        if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(obj, key)) {
          dest = obj[key];
          obj[key] = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(dest) ?
[...dest, entry[1]] : [dest, entry[1]];
        } else {
          obj[key] = entry[1];
        }
      }
      setHeaders(obj, valueOrRewrite);
    } else {
      header != null && setHeader(valueOrRewrite, header, rewrite);
    }
    return this;
  }
  get(header, parser) {
    header = normalizeHeader(header);
    if (header) {
      const key = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].findKey(this, header);
      if (key) {
        const value = this[key];
        if (!parser) {
          return value;
        }
```

```
      if (parser === true) {
        return parseTokens(value);
      }
      if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(parser)) {
        return parser.call(this, value, key);
      }
      if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isRegExp(parser)) {
        return parser.exec(value);
      }
      throw new TypeError('parser must be boolean|regexp|function');
    }
  }
 }
 has(header, matcher) {
  header = normalizeHeader(header);
  if (header) {
    const key = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].findKey(this, header);
    return !!(key && this[key] !== undefined && (!matcher || matchHeaderValue(this, this[key], key,
matcher)));
  }
  return false;
 }
 delete(header, matcher) {
  const self = this;
  let deleted = false;
  function deleteHeader(_header) {
    _header = normalizeHeader(_header);
    if (_header) {
      const key = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].findKey(self,
_header);
      if (key && (!matcher || matchHeaderValue(self, self[key], key, matcher))) {
        delete self[key];
        deleted = true;
      }
    }
  }
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(header)) {
    header.forEach(deleteHeader);
  } else {
    deleteHeader(header);
  }
  return deleted;
 }
 clear(matcher) {
  const keys = Object.keys(this);
  let i = keys.length;
  let deleted = false;
  while (i--) {
    const key = keys[i];
```

```
      if (!matcher || matchHeaderValue(this, this[key], key, matcher, true)) {
        delete this[key];
        deleted = true;
      }
    }
    return deleted;
  }
  normalize(format) {
    const self = this;
    const headers = {};
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(this, (value, header) => {
      const key = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].findKey(headers,
header);
      if (key) {
        self[key] = normalizeValue(value);
        delete self[header];
        return;
      }
      const normalized = format ? formatHeader(header) : String(header).trim();
      if (normalized !== header) {
        delete self[header];
      }
      self[normalized] = normalizeValue(value);
      headers[normalized] = true;
    });
    return this;
  }
  concat(...targets) {
    return this.constructor.concat(this, ...targets);
  }
  toJSON(asStrings) {
    const obj = Object.create(null);
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(this, (value, header) => {
      value != null && value !== false && (obj[header] = asStrings &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(value) ? value.join(', ') :
value);
    });
    return obj;
  }
  [Symbol.iterator]() {
    return Object.entries(this.toJSON())[Symbol.iterator]();
  }
  toString() {
    return Object.entries(this.toJSON()).map(([header, value]) => header + ': ' + value).join('\n');
  }
  getSetCookie() {
    return this.get('set-cookie') || [];
  }
  get [Symbol.toStringTag]() {
```

```
    return 'AxiosHeaders';
  }
  static from(thing) {
    return thing instanceof this ? thing : new this(thing);
  }
  static concat(first, ...targets) {
    const computed = new this(first);
    targets.forEach(target => computed.set(target));
    return computed;
  }
  static accessor(header) {
    const internals = this[$internals] = this[$internals] = {
      accessors: {}
    };
    const accessors = internals.accessors;
    const prototype = this.prototype;
    function defineAccessor(_header) {
      const lHeader = normalizeHeader(_header);
      if (!accessors[lHeader]) {
        buildAccessors(prototype, _header);
        accessors[lHeader] = true;
      }
    }
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(header) ?
header.forEach(defineAccessor) : defineAccessor(header);
    return this;
  }
}
AxiosHeaders.accessor(['Content-Type', 'Content-Length', 'Accept', 'Accept-Encoding', 'User-Agent',
'Authorization']);

// reserved names hotfix
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].reduceDescriptors(AxiosHeaders.prot
otype, ({
  value
}, key) => {
  let mapped = key[0].toUpperCase() + key.slice(1); // map `set` => `Set`
  return {
    get: () => value,
    set(headerValue) {
      this[mapped] = headerValue;
    }
  };
});
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].freezeMethods(AxiosHeaders);
/* harmony default
 export */ const __WEBPACK_DEFAULT_EXPORT__ = (AxiosHeaders);

/***/ },
```

```
/***/ "./node_modules/axios/lib/core/InterceptorManager.js"
/*!*****************************************************************!*\
  !*** ./node_modules/axios/lib/core/InterceptorManager.js ***!
  \*****************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");



class InterceptorManager {
  constructor() {
    this.handlers = [];
  }

  /**
   * Add a new interceptor to the stack
   *
   * @param {Function} fulfilled The function to handle `then` for a `Promise`
   * @param {Function} rejected The function to handle `reject` for a `Promise`
   * @param {Object} options The options for the interceptor, synchronous and runWhen
   *
   * @return {Number} An ID used to remove interceptor later
   */
  use(fulfilled, rejected, options) {
    this.handlers.push({
      fulfilled,
      rejected,
      synchronous: options ? options.synchronous : false,
      runWhen: options ? options.runWhen : null
    });
    return this.handlers.length - 1;
  }

  /**
   * Remove an interceptor from the stack
   *
   * @param {Number} id The ID that was returned by `use`
   *
   * @returns {void}
   */
  eject(id) {
```

```
    if (this.handlers[id]) {
      this.handlers[id] = null;
    }
  }

  /**
   * Clear all interceptors from the stack
   *
   * @returns {void}
   */
  clear() {
    if (this.handlers) {
      this.handlers = [];
    }
  }

  /**
   * Iterate over all the registered interceptors
   *
   * This method is particularly useful for skipping over any
   * interceptors that may have become `null` calling `eject`.
   *
   * @param {Function} fn The function to call for each interceptor
   *
   * @returns {void}
   */
  forEach(fn) {
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(this.handlers, function
forEachHandler(h) {
      if (h !== null) {
        fn(h);
      }
    });
  }
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (InterceptorManager);

/***/ },

/***/ "./node_modules/axios/lib/core/buildFullPath.js"
/*!******************************************************!*\
  !*** ./node_modules/axios/lib/core/buildFullPath.js ***!
  \******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ buildFullPath)
```

```
/* harmony export */ });
/* harmony import */ var _AxiosError_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _helpers_isAbsoluteURL_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../helpers/isAbsoluteURL.js */
"./node_modules/axios/lib/helpers/isAbsoluteURL.js");
/* harmony import */ var _helpers_combineURLs_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../helpers/combineURLs.js */
"./node_modules/axios/lib/helpers/combineURLs.js");




const malformedHttpProtocol = /^https?:(?!\/\/)/i;
const httpProtocolControlCharacters = /[\t\n\r]/g;
function stripLeadingC0ControlOrSpace(url) {
  let i = 0;
  while (i < url.length && url.charCodeAt(i) <= 0x20) {
    i++;
  }
  return url.slice(i);
}
function normalizeURLForProtocolCheck(url) {
  return stripLeadingC0ControlOrSpace(url).replace(httpProtocolControlCharacters, '');
}
function assertValidHttpProtocolURL(url, config) {
  if (typeof url === 'string' && malformedHttpProtocol.test(normalizeURLForProtocolCheck(url))) {
    throw new _AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"]('Invalid URL:
missing "//" after protocol',
_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"].ERR_INVALID_URL, config);
  }
}

/**
 * Creates a new URL by combining the baseURL with the requestedURL,
 * only when the requestedURL is not already an absolute URL.
 * If the requestURL is absolute, this function returns the requestedURL untouched.
 *
 * @param {string} baseURL The base URL
 * @param {string} requestedURL Absolute or relative URL to combine
 *
 * @returns {string} The combined full path
 */
function buildFullPath(baseURL, requestedURL, allowAbsoluteUrls, config) {
  assertValidHttpProtocolURL(requestedURL, config);
  let isRelativeUrl = !
(0,_helpers_isAbsoluteURL_js__WEBPACK_IMPORTED_MODULE_1__["default"])
(requestedURL);
```

```
  if (baseURL && (isRelativeUrl || allowAbsoluteUrls === false)) {
    assertValidHttpProtocolURL(baseURL, config);
    return (0,_helpers_combineURLs_js__WEBPACK_IMPORTED_MODULE_2__["default"])
(baseURL, requestedURL);
  }
  return requestedURL;
}

/***/ },

/***/ "./node_modules/axios/lib/core/dispatchRequest.js"
/*!*******************************************************!*\
  !*** ./node_modules/axios/lib/core/dispatchRequest.js ***!
  \*******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ dispatchRequest)
/* harmony export */ });
/* harmony import */ var _transformData_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./transformData.js */ "./node_modules/axios/lib/core/transformData.js");
/* harmony import */ var _cancel_isCancel_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../cancel/isCancel.js */ "./node_modules/axios/lib/cancel/isCancel.js");
/* harmony import */ var _defaults_index_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../defaults/index.js */ "./node_modules/axios/lib/defaults/index.js");
/* harmony import */ var _cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../cancel/CanceledError.js */
"./node_modules/axios/lib/cancel/CanceledError.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../core/AxiosHeaders.js */
"./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var _adapters_adapters_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../adapters/adapters.js */ "./node_modules/axios/lib/adapters/adapters.js");

/**
 * Throws a `CanceledError` if cancellation has been requested.
 *
 * @param {Object} config The config that is to be used for the request
 *
```

```
 * @returns {void}
 */
function throwIfCancellationRequested(config) {
  if (config.cancelToken) {
    config.cancelToken.throwIfRequested();
  }
  if (config.signal && config.signal.aborted) {
    throw new _cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_3__["default"](null,
config);
  }
}

/**
 * Dispatch a request to the server using the configured adapter.
 *
 * @param {object} config The config that is to be used for the request
 *
 * @returns {Promise} The Promise to be fulfilled
 */
function dispatchRequest(config) {
  throwIfCancellationRequested(config);
  config.headers =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_4__["default"].from(config.headers);

  // Transform request data
  config.data = _transformData_js__WEBPACK_IMPORTED_MODULE_0__["default"].call(config,
config.transformRequest);
  if (['post', 'put', 'patch'].indexOf(config.method) !== -1) {
    config.headers.setContentType('application/x-www-form-urlencoded', false);
  }
  const adapter =
_adapters_adapters_js__WEBPACK_IMPORTED_MODULE_5__["default"].getAdapter(config.adapt
er || _defaults_index_js__WEBPACK_IMPORTED_MODULE_2__["default"].adapter, config);
  return adapter(config).then(function onAdapterResolution(response) {
    throwIfCancellationRequested(config);

    // Expose the current response on config so that transformResponse can
    // attach it to any AxiosError it throws (e.g. on JSON parse failure).
    // We clean it up afterwards to avoid polluting the config object.
    config.response = response;
    try {
      response.data =
_transformData_js__WEBPACK_IMPORTED_MODULE_0__["default"].call(config,
config.transformResponse, response);
    } finally {
      delete config.response;
    }
    response.headers =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_4__["default"].from(response.headers
```

```
);
    return response;
  }, function onAdapterRejection(reason) {
    if (!(0,_cancel_isCancel_js__WEBPACK_IMPORTED_MODULE_1__["default"])(reason)) {
      throwIfCancellationRequested(config);

      // Transform response data
      if (reason && reason.response) {
        config.response = reason.response;
        try {
          reason.response.data =
_transformData_js__WEBPACK_IMPORTED_MODULE_0__["default"].call(config,
config.transformResponse, reason.response);
        } finally {
          delete config.response;
        }
        reason.response.headers =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_4__["default"].from(reason.response.
headers);
      }
    }
    return Promise.reject(reason);
  });
}

/***/ },

/***/ "./node_modules/axios/lib/core/mergeConfig.js"
/*!****************************************************!*\
  !*** ./node_modules/axios/lib/core/mergeConfig.js ***!
  \****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding
 */ mergeConfig)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./AxiosHeaders.js */ "./node_modules/axios/lib/core/AxiosHeaders.js");




const headersToObject = thing => thing instanceof
_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_1__["default"] ? {
```

```
  ...thing
} : thing;

/**
 * Config-specific merge-function which creates a new config-object
 * by merging two configuration objects together.
 *
 * @param {Object} config1
 * @param {Object} config2
 *
 * @returns {Object} New object resulting from merging config2 to config1
 */
function mergeConfig(config1, config2) {
  // eslint-disable-next-line no-param-reassign
  config2 = config2 || {};

  // Use a null-prototype object so that downstream reads such as `config.auth`
  // or `config.baseURL` cannot inherit polluted values from Object.prototype.
  // `hasOwnProperty` is restored as a non-enumerable own slot to preserve
  // ergonomics for user code that relies on it.
  const config = Object.create(null);
  Object.defineProperty(config, 'hasOwnProperty', {
    // Null-proto descriptor so a polluted Object.prototype.get cannot turn
    // this data descriptor into an accessor descriptor on the way in.
    __proto__: null,
    value: Object.prototype.hasOwnProperty,
    enumerable: false,
    writable: true,
    configurable: true
  });
  function getMergedValue(target, source, prop, caseless) {
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(target) &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(source)) {
      return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].merge.call({
        caseless
      }, target, source);
    } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(source)) {
      return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].merge({}, source);
    } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(source)) {
      return source.slice();
    }
    return source;
  }
  function mergeDeepProperties(a, b, prop, caseless) {
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(b)) {
      return getMergedValue(a, b, prop, caseless);
    } else if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(a)) {
      return getMergedValue(undefined, a, prop, caseless);
    }
```

```
  }

  // eslint-disable-next-line consistent-return
  function valueFromConfig2(a, b) {
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(b)) {
      return getMergedValue(undefined, b);
    }
  }

  // eslint-disable-next-line consistent-return
  function defaultToConfig2(a, b) {
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(b)) {
      return getMergedValue(undefined, b);
    } else if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(a)) {
      return getMergedValue(undefined, a);
    }
  }
  function getMergedTransitionalOption(prop) {
    const transitional2 =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config2, 'transitional') ?
config2.transitional : undefined;
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(transitional2)) {
      if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(transitional2)) {
        if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(transitional2,
prop)) {
          return transitional2[prop];
        }
      } else {
        return undefined;
      }
    }
    const transitional1 =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config1, 'transitional') ?
config1.transitional : undefined;
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(transitional1) &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(transitional1, prop)) {
      return transitional1[prop];
    }
    return undefined;
  }

  // eslint-disable-next-line consistent-return
  function mergeDirectKeys(a, b, prop) {
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config2, prop)) {
      return getMergedValue(a, b);
    } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config1,
prop)) {
      return getMergedValue(undefined, a);
    }
```

```
  }
  const mergeMap = {
    url: valueFromConfig2,
    method: valueFromConfig2,
    data: valueFromConfig2,
    baseURL: defaultToConfig2,
    transformRequest: defaultToConfig2,
    transformResponse: defaultToConfig2,
    paramsSerializer: defaultToConfig2,
    timeout: defaultToConfig2,
    timeoutMessage: defaultToConfig2,
    withCredentials: defaultToConfig2,
    withXSRFToken: defaultToConfig2,
    adapter: defaultToConfig2,
    responseType: defaultToConfig2,
    xsrfCookieName: defaultToConfig2,
    xsrfHeaderName: defaultToConfig2,
    onUploadProgress: defaultToConfig2,
    onDownloadProgress: defaultToConfig2,
    decompress: defaultToConfig2,
    maxContentLength: defaultToConfig2,
    maxBodyLength: defaultToConfig2,
    beforeRedirect: defaultToConfig2,
    transport: defaultToConfig2,
    httpAgent: defaultToConfig2,
    httpsAgent: defaultToConfig2,
    cancelToken: defaultToConfig2,
    socketPath: defaultToConfig2,
    allowedSocketPaths: defaultToConfig2,
    responseEncoding: defaultToConfig2,
    validateStatus: mergeDirectKeys,
    headers: (a, b, prop) => mergeDeepProperties(headersToObject(a), headersToObject(b), prop, true)
  };
  _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(Object.keys({
    ...config1,
    ...config2
  }), function computeConfigValue(prop) {
    if (prop === '__proto__' || prop === 'constructor' || prop === 'prototype') return;
    const merge =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(mergeMap, prop) ?
mergeMap[prop] : mergeDeepProperties;
    const a = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config1,
prop) ? config1[prop] : undefined;
    const b = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config2,
prop) ? config2[prop] : undefined;
    const configValue = merge(a, b, prop);
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(configValue) &&
merge !== mergeDirectKeys || (config[prop] = configValue);
  });
```

```
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config2,
'validateStatus') &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(config2.validateStatus)
&& getMergedTransitionalOption('validateStatusUndefinedResolves') === false) {
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(config1,
'validateStatus')) {
      config.validateStatus = getMergedValue(undefined, config1.validateStatus);
    } else {
      delete config.validateStatus;
    }
  }
  return config;
}

/***/ },

/***/ "./node_modules/axios/lib/core/settle.js"
/*!**********************************************!*\
  !*** ./node_modules/axios/lib/core/settle.js ***!
  \**********************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ settle)
/* harmony export */ });
/* harmony import */ var _AxiosError_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");




/**
 * Resolve or reject a Promise based on response status.
 *
 * @param {Function} resolve A function that resolves the promise.
 * @param {Function} reject A function that rejects the promise.
 * @param {object} response The response.
 *
 * @returns {object} The response.
 */
function settle(resolve, reject, response) {
  const validateStatus = response.config.validateStatus;
  if (!response.status || !validateStatus || validateStatus(response.status)) {
    resolve(response);
  } else {
    reject(new _AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"]('Request failed
with status code ' + response.status, response.status >= 400 && response.status < 500 ?
```

```
_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"].ERR_BAD_REQUEST :
_AxiosError_js__WEBPACK_IMPORTED_MODULE_0__["default"].ERR_BAD_RESPONSE,
response.config, response.request, response));
  }
}

/***/ },

/***/ "./node_modules/axios/lib/core/transformData.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/core/transformData.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ transformData)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _defaults_index_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../defaults/index.js */ "./node_modules/axios/lib/defaults/index.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../core/AxiosHeaders.js */
"./node_modules/axios/lib/core/AxiosHeaders.js");




/**
 * Transform the data for a request or a response
 *
 * @param {Array|Function} fns A single function or Array of functions
 * @param {?Object} response The response object
 *
 * @returns {*} The resulting transformed data
 */
function transformData(fns, response) {
  const config = this || _defaults_index_js__WEBPACK_IMPORTED_MODULE_1__["default"];
  const context = response || config;
  const headers =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_2__["default"].from(context.headers);

  let data = context.data;
  _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(fns, function transform(fn) {
    data = fn.call(config, data, headers.normalize(), response ? response.status : undefined);
```

```
  });
  headers.normalize();
  return data;
}

/***/ },

/***/ "./node_modules/axios/lib/defaults/index.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/defaults/index.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _transitional_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./transitional.js */ "./node_modules/axios/lib/defaults/transitional.js");
/* harmony import */ var _helpers_toFormData_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ../helpers/toFormData.js */
"./node_modules/axios/lib/helpers/toFormData.js");
/* harmony import */ var
_helpers_toURLEncodedForm_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../helpers/toURLEncodedForm.js */
"./node_modules/axios/lib/helpers/toURLEncodedForm.js");
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");
/* harmony import */ var _helpers_formDataToJSON_js__WEBPACK_IMPORTED_MODULE_6__
= __webpack_require__(/*! ../helpers/formDataToJSON.js */
"./node_modules/axios/lib/helpers/formDataToJSON.js");









const own = (obj, key) => obj != null &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(obj, key) ? obj[key] :
undefined;
```

```
/**
 * It takes a string, tries to parse it, and if it fails, it returns the stringified version
 * of the input
 *
 * @param {any} rawValue - The value to be stringified.
 * @param {Function} parser - A function that parses a string into a JavaScript object.
 * @param {Function} encoder - A function that takes a value and returns a string.
 *
 * @returns {string} A stringified version of the rawValue.
 */
function stringifySafely(rawValue, parser, encoder) {
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(rawValue)) {
    try {
      (parser || JSON.parse)(rawValue);
      return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].trim(rawValue);
    } catch (e) {
      if (e.name !== 'SyntaxError') {
        throw e;
      }
    }
  }
  return (encoder || JSON.stringify)(rawValue);
}
const defaults = {
  transitional: _transitional_js__WEBPACK_IMPORTED_MODULE_2__["default"],
  adapter: ['xhr', 'http', 'fetch'],
  transformRequest: [function transformRequest(data, headers) {
    const contentType = headers.getContentType() || '';
    const hasJSONContentType = contentType.indexOf('application/json') > -1;
    const isObjectPayload =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(data);
    if (isObjectPayload &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isHTMLForm(data)) {
      data = new FormData(data);
    }
    const isFormData =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFormData(data);
    if (isFormData) {
      return hasJSONContentType ?
JSON.stringify((0,_helpers_formDataToJSON_js__WEBPACK_IMPORTED_MODULE_6__["default
"])(data)) : data;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArrayBuffer(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBuffer(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isStream(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFile(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBlob(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isReadableStream(data)) {
      return data;
```

```
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArrayBufferView(data)) {
      return data.buffer;
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isURLSearchParams(data)) {
      headers.setContentType('application/x-www-form-urlencoded;charset=utf-8', false);
      return data.toString();
    }
    let isFileList;
    if (isObjectPayload) {
      const formSerializer = own(this, 'formSerializer');
      if (contentType.indexOf('application/x-www-form-urlencoded') > -1) {
        return
(0,_helpers_toURLEncodedForm_js__WEBPACK_IMPORTED_MODULE_4__["default"])(data,
formSerializer).toString();
      }
      if ((isFileList = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFileList(data)) ||
contentType.indexOf('multipart/form-data') > -1) {
        const env = own(this, 'env');
        const _FormData = env && env.FormData;
        return (0,_helpers_toFormData_js__WEBPACK_IMPORTED_MODULE_3__["default"])
(isFileList ? {
          'files[]': data
        } : data, _FormData && new _FormData(), formSerializer);
      }
    }
    if (isObjectPayload || hasJSONContentType) {
      headers.setContentType('application/json', false);
      return stringifySafely(data);
    }
    return data;
  }],
  transformResponse: [function transformResponse(data) {
    const transitional = own(this, 'transitional') || defaults.transitional;
    const forcedJSONParsing = transitional && transitional.forcedJSONParsing;
    const responseType = own(this, 'responseType');
    const JSONRequested = responseType === 'json';
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isResponse(data) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isReadableStream(data)) {
      return data;
    }
    if (data && _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(data) &&
(forcedJSONParsing && !responseType || JSONRequested)) {
      const silentJSONParsing = transitional && transitional.silentJSONParsing;
      const strictJSONParsing = !silentJSONParsing && JSONRequested;
      try {
        return JSON.parse(data, own(this, 'parseReviver'));
      } catch (e) {
        if (strictJSONParsing) {
```

```
        if (e.name === 'SyntaxError') {
          throw _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].from(e,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_BAD_RESPONSE,
this, null, own(this, 'response'));
        }
        throw e;
       }
      }
    }
    return data;
  }],
  /**
   * A timeout in milliseconds to abort a request. If set to 0 (default) a
   * timeout is not created.
   */
  timeout: 0,
  xsrfCookieName: 'XSRF-TOKEN',
  xsrfHeaderName: 'X-XSRF-TOKEN',
  maxContentLength: -1,
  maxBodyLength: -1,
  env: {
    FormData:
_platform_index_js__WEBPACK_IMPORTED_MODULE_5__["default"].classes.FormData,
    Blob: _platform_index_js__WEBPACK_IMPORTED_MODULE_5__["default"].classes.Blob
  },
  validateStatus: function validateStatus(status) {
    return status >= 200 && status < 300;
  },
  headers: {
    common: {
      Accept: 'application/json, text/plain, */*',
      'Content-Type': undefined
    }
  }
};
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(['delete', 'get', 'head', 'post',
'put', 'patch', 'query'], method => {
  defaults.headers[method] = {};
});
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (defaults);

/***/ },

/***/ "./node_modules/axios/lib/defaults/transitional.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/defaults/transitional.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {
```

```
"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });


/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  silentJSONParsing: true,
  forcedJSONParsing: true,
  clarifyTimeoutError: false,
  legacyInterceptorReqResOrdering: true,
  advertiseZstdAcceptEncoding: false,
  validateStatusUndefinedResolves: true
});

/***/ },

/***/ "./node_modules/axios/lib/env/data.js"
/*!********************************************!*\
  !*** ./node_modules/axios/lib/env/data.js ***!
  \********************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   VERSION: () => (/* binding */ VERSION)
/* harmony export */ });
const VERSION = "1.18.0";

/***/ },

/***/ "./node_modules/axios/lib/helpers/AxiosURLSearchParams.js"
/*!***************************************************************!*\
  !*** ./node_modules/axios/lib/helpers/AxiosURLSearchParams.js ***!
  \***************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _toFormData_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./toFormData.js */ "./node_modules/axios/lib/helpers/toFormData.js");
```

```
/**
 * It encodes a string by replacing all characters that are not in the unreserved set with
 * their percent-encoded equivalents
 *
 * @param {string} str - The string to encode.
 *

 * @returns {string} The encoded string.
 */
function encode(str) {
  const charMap = {
    '!': '%21',
    "'": '%27',
    '(': '%28',
    ')': '%29',
    '~': '%7E',
    '%20': '+'
  };
  return encodeURIComponent(str).replace(/[!'()~]|%20/g, function replacer(match) {
    return charMap[match];
  });
}

/**
 * It takes a params object and converts it to a FormData object
 *
 * @param {Object<string, any>} params - The parameters to be converted to a FormData object.
 * @param {Object<string, any>} options - The options object passed to the Axios constructor.
 *
 * @returns {void}
 */
function AxiosURLSearchParams(params, options) {
  this._pairs = [];
  params && (0,_toFormData_js__WEBPACK_IMPORTED_MODULE_0__["default"])(params, this,
options);
}
const prototype = AxiosURLSearchParams.prototype;
prototype.append = function append(name, value) {
  this._pairs.push([name, value]);
};
prototype.toString = function toString(encoder) {
  const _encode = encoder ? function (value) {
    return encoder.call(this, value, encode);
  } : encode;
  return this._pairs.map(function each(pair) {
    return _encode(pair[0]) + '=' + _encode(pair[1]);
  }, '').join('&');
};
```

```
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(AxiosURLSearchParams);

/***/ },

/***/ "./node_modules/axios/lib/helpers/HttpStatusCode.js"
/*!**********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/HttpStatusCode.js ***!
  \**********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
const HttpStatusCode = {
  Continue: 100,
  SwitchingProtocols: 101,
  Processing: 102,
  EarlyHints: 103,
  Ok: 200,
  Created: 201,
  Accepted: 202,
  NonAuthoritativeInformation: 203,
  NoContent: 204,
  ResetContent: 205,
  PartialContent: 206,
  MultiStatus: 207,
  AlreadyReported: 208,
  ImUsed: 226,
  MultipleChoices: 300,
  MovedPermanently: 301,
  Found: 302,
  SeeOther: 303,
  NotModified: 304,
  UseProxy: 305,
  Unused: 306,
  TemporaryRedirect: 307,
  PermanentRedirect: 308,
  BadRequest: 400,
  Unauthorized: 401,
  PaymentRequired: 402,
  Forbidden: 403,
  NotFound: 404,
  MethodNotAllowed: 405,
  NotAcceptable: 406,
  ProxyAuthenticationRequired: 407,
  RequestTimeout: 408,
```

```
  Conflict: 409,
  Gone: 410,
  LengthRequired: 411,
  PreconditionFailed: 412,
  PayloadTooLarge: 413,
  UriTooLong: 414,
  UnsupportedMediaType: 415,
  RangeNotSatisfiable: 416,
  ExpectationFailed: 417,
  ImATeapot: 418,
  MisdirectedRequest: 421,
  UnprocessableEntity: 422,
  Locked: 423,
  FailedDependency: 424,
  TooEarly: 425,
  UpgradeRequired: 426,
  PreconditionRequired: 428,
  TooManyRequests: 429,
  RequestHeaderFieldsTooLarge: 431,
  UnavailableForLegalReasons: 451,
  InternalServerError: 500,
  NotImplemented: 501,
  BadGateway: 502,
  ServiceUnavailable: 503,
  GatewayTimeout: 504,
  HttpVersionNotSupported: 505,
  VariantAlsoNegotiates: 506,
  InsufficientStorage: 507,
  LoopDetected: 508,
  NotExtended: 510,
  NetworkAuthenticationRequired: 511,
  WebServerIsDown: 521,
  ConnectionTimedOut: 522,
  OriginIsUnreachable: 523,
  TimeoutOccurred: 524,
  SslHandshakeFailed: 525,
  InvalidSslCertificate: 526
};
Object.entries(HttpStatusCode).forEach(([key, value]) => {
  HttpStatusCode[value] = key;
});
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (HttpStatusCode);

/***/ },

/***/ "./node_modules/axios/lib/helpers/bind.js"
/*!************************************************!*\
  !*** ./node_modules/axios/lib/helpers/bind.js ***!
  \************************************************/
```

```
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ bind)
/* harmony export */ });


/**
 * Create a bound version of a function with a specified `this` context
 *
 * @param {Function} fn - The function to bind
 * @param {*} thisArg - The value to be passed as the `this` parameter
 * @returns {Function} A new function that will call the original function with the specified `this`
context
 */
function bind(fn, thisArg) {
  return function wrap() {
    return fn.apply(thisArg, arguments);
  };
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/buildURL.js"
/*!****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/buildURL.js ***!
  \****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ buildURL),
/* harmony export */   encode: () => (/* binding */ encode)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _AxiosURLSearchParams_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./AxiosURLSearchParams.js */
"./node_modules/axios/lib/helpers/AxiosURLSearchParams.js");




/**
 * It replaces URL-encoded forms of `:`, `$`, `,`, and spaces with
```

```
 * their plain counterparts (`:`, `$`, `,`, `+`).
 *
 * @param {string} val The value to be encoded.
 *
 * @returns {string} The encoded value.
 */
function encode(val) {
  return encodeURIComponent(val).replace(/%3A/gi, ':').replace(/%24/g, '$').replace(/%2C/gi,
',').replace(/%20/g, '+');
}

/**
 * Build a URL by appending params to the end
 *
 * @param {string} url The base of the url (e.g., http://www.google.com)
 * @param {object} [params] The params to be appended
 * @param {?(object|Function)} options
 *
 * @returns {string} The formatted url
 */
function buildURL(url, params, options) {
  if (!params) {
    return url;
  }
  const _options =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(options) ? {
    serialize: options
  } : options;

  // Read serializer options pollution-safely: own properties and methods on a
  // class/template prototype are honored, but values injected onto a polluted
  // Object.prototype are ignored.
  const _encode =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].getSafeProp(_options, 'encode') ||
encode;
  const serializeFn =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].getSafeProp(_options, 'serialize');
  let serializedParams;
  if (serializeFn) {
    serializedParams = serializeFn(params, _options);
  } else {
    serializedParams =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isURLSearchParams(params) ?
params.toString() : new
_AxiosURLSearchParams_js__WEBPACK_IMPORTED_MODULE_1__["default"](params,
_options).toString(_encode);
  }
  if (serializedParams) {
    const hashmarkIndex = url.indexOf('#');
```

```
    if (hashmarkIndex !== -1) {
      url = url.slice(0, hashmarkIndex);
    }
    url += (url.indexOf('?') === -1 ? '?' : '&') + serializedParams;
  }
  return url;
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/combineURLs.js"
/*!******************************************************!*\
  !*** ./node_modules/axios/lib/helpers/combineURLs.js ***!
  \******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ combineURLs)
/* harmony export */ });


/**
 * Creates a new URL by combining the specified URLs
 *
 * @param {string} baseURL The base URL
 * @param {string} relativeURL The relative URL
 *
 * @returns {string} The combined URL
 */
function combineURLs(baseURL, relativeURL) {
  return relativeURL ? baseURL.replace(/\/?\/$/, '') + '/' + relativeURL.replace(/^\/+/, '') : baseURL;
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/composeSignals.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/composeSignals.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_0__ =
```

```
__webpack_require__(/*! ../cancel/CanceledError.js */
"./node_modules/axios/lib/cancel/CanceledError.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");



const composeSignals = (signals, timeout) => {
  signals = signals ? signals.filter(Boolean) : [];
  if (!timeout && !signals.length) {
    return;
  }
  const controller = new AbortController();
  let aborted = false;
  const onabort = function (reason) {
    if (!aborted) {
      aborted = true;
      unsubscribe();
      const err = reason instanceof Error ? reason : this.reason;
      controller.abort(err instanceof
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"] ? err : new
_cancel_CanceledError_js__WEBPACK_IMPORTED_MODULE_0__["default"](err instanceof
Error ? err.message : err));

    }
  };
  let timer = timeout && setTimeout(() => {
    timer = null;
    onabort(new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"](`timeout
of ${timeout}ms exceeded`,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ETIMEDOUT));
  }, timeout);
  const unsubscribe = () => {
    if (!signals) {
      return;
    }
    timer && clearTimeout(timer);
    timer = null;
    signals.forEach(signal => {
      signal.unsubscribe ? signal.unsubscribe(onabort) : signal.removeEventListener('abort', onabort);
    });
    signals = null;
  };
  signals.forEach(signal => signal.addEventListener('abort', onabort));
  const {
    signal
  } = controller;
```

```
  signal.unsubscribe = () =>
_utils_js__WEBPACK_IMPORTED_MODULE_2__["default"].asap(unsubscribe);
  return signal;
};
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (composeSignals);

/***/ },

/***/ "./node_modules/axios/lib/helpers/cookies.js"
/*!****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/cookies.js ***!
  \****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");


/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(_platform_index_js__WEBPACK_IMPORTED_MODULE_1__["default"].hasStandardBrowserEnv ?
// Standard browser envs support document.cookie
{
  write(name, value, expires, path, domain, secure, sameSite) {
    if (typeof document === 'undefined') return;
    const cookie = [`${name}=${encodeURIComponent(value)}`];
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isNumber(expires)) {
      cookie.push(`expires=${new Date(expires).toUTCString()}`);
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(path)) {
      cookie.push(`path=${path}`);
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(domain)) {
      cookie.push(`domain=${domain}`);
    }
    if (secure === true) {
      cookie.push('secure');
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(sameSite)) {
      cookie.push(`SameSite=${sameSite}`);
    }
    document.cookie = cookie.join('; ');
  },
```

```
  read(name) {
    if (typeof document === 'undefined') return null;
    // Match name=value by splitting on the semicolon separator instead of building a
    // RegExp from `name` — interpolating an unescaped string into a RegExp would let
    // metacharacters (e.g. `.+?` in an attacker-influenced cookie name) cause ReDoS or
    // match the wrong cookie. Browsers may serialize cookie pairs as either ";" or
    // "; ", so ignore optional whitespace before each cookie name.
    const cookies = document.cookie.split(';');
    for (let i = 0; i < cookies.length; i++) {
      const cookie = cookies[i].replace(/^\s+/, '');
      const eq = cookie.indexOf('=');
      if (eq !== -1 && cookie.slice(0, eq) === name) {
        return decodeURIComponent(cookie.slice(eq + 1));
      }
    }
    return null;
  },
  remove(name) {
    this.write(name, '', Date.now() - 86400000, '/');
  }
} :
// Non-standard browser env (web workers, react-native) lack needed support.
{
  write() {},
  read() {
    return null;
  },
  remove() {}
});

/***/ },

/***/ "./node_modules/axios/lib/helpers/estimateDataURLDecodedBytes.js"
/*!**********************************************************************!*\
  !*** ./node_modules/axios/lib/helpers/estimateDataURLDecodedBytes.js ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ estimateDataURLDecodedBytes)
/* harmony export */ });
/**
 * Estimate decoded byte length of a data:// URL *without* allocating large buffers.
 * - For base64: compute exact decoded size using length and padding;
 *               handle %XX at the character-count level (no string allocation).
 * - For non-base64: compute the exact percent-decoded UTF-8 byte length.
 *
```

```
 * @param {string} url
 * @returns {number}
 */
const isHexDigit = charCode => charCode >= 48 && charCode <= 57 || charCode >= 65 && charCode
<= 70 || charCode >= 97 && charCode <= 102;
const isPercentEncodedByte = (str, i, len) => i + 2 < len && isHexDigit(str.charCodeAt(i + 1)) &&
isHexDigit(str.charCodeAt(i + 2));
function estimateDataURLDecodedBytes(url) {
  if (!url || typeof url !== 'string') return 0;
  if (!url.startsWith('data:')) return 0;
  const comma = url.indexOf(',');
  if (comma < 0) return 0;
  const meta = url.slice(5, comma);
  const body = url.slice(comma + 1);
  const isBase64 = /;base64/i.test(meta);
  if (isBase64) {
    let effectiveLen = body.length;
    const len = body.length; // cache length

    for (let i = 0; i < len; i++) {
      if (body.charCodeAt(i) === 37 /* '%' */ && i + 2 < len) {
        const a = body.charCodeAt(i + 1);
        const b = body.charCodeAt(i + 2);
        const isHex = isHexDigit(a) && isHexDigit(b);
        if (isHex) {
          effectiveLen -= 2;
          i += 2;
        }
      }
    }
    let pad = 0;
    let idx = len - 1;
    const tailIsPct3D = j => j >= 2 && body.charCodeAt(j - 2) === 37 &&
    // '%'
    body.charCodeAt(j - 1) === 51 && (
    // '3'
    body.charCodeAt(j) === 68 || body.charCodeAt(j) === 100); // 'D' or 'd'

    if (idx >= 0) {
      if (body.charCodeAt(idx) === 61 /* '=' */) {
        pad++;
        idx--;
      } else if (tailIsPct3D(idx)) {
        pad++;
        idx -= 3;
      }
    }
    if (pad === 1 && idx >= 0) {
      if (body.charCodeAt(idx) === 61 /* '=' */) {
```

```
      pad++;
    } else if (tailIsPct3D(idx)) {
      pad++;
    }
  }
  const groups = Math.floor(effectiveLen / 4);
  const bytes = groups * 3 - (pad || 0);
  return bytes > 0 ? bytes : 0;
}

// Compute UTF-8 byte length directly from UTF-16 code units without allocating
// a byte buffer (TextEncoder.encode would defeat the DoS guard on large bodies).
// Valid %XX triplets count as one decoded byte; this matches the bytes that
// decodeURIComponent(body) would produce before Buffer re-encodes the string.
let bytes = 0;
for (let i = 0, len = body.length; i < len; i++) {
  const c = body.charCodeAt(i);
  if (c === 37 /* '%' */ && isPercentEncodedByte(body, i, len)) {
    bytes += 1;
    i += 2;
  } else if (c < 0x80) {
    bytes += 1;
  } else if (c < 0x800) {
    bytes += 2;
  } else if (c >= 0xd800 && c <= 0xdbff && i + 1 < len) {
    const next = body.charCodeAt(i + 1);
    if (next >= 0xdc00 && next <= 0xdfff) {
      bytes += 4;
      i++;
    } else {
      bytes += 3;
    }
  } else {
    bytes += 3;
  }
}
return bytes;
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/formDataToJSON.js"
/*!**********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/formDataToJSON.js ***!
  \**********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
```

```
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var _toFormData_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./toFormData.js */ "./node_modules/axios/lib/helpers/toFormData.js");



const MAX_DEPTH =
_toFormData_js__WEBPACK_IMPORTED_MODULE_2__.DEFAULT_FORM_DATA_MAX_DEPT
H;
function throwIfDepthExceeded(index) {
  if (index > MAX_DEPTH) {
    throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('FormData
field is too deeply nested (' + index + ' levels). Max depth: ' + MAX_DEPTH,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_FORM_DATA_DE
PTH_EXCEEDED);
  }
}

/**
 * It takes a string like `foo[x][y][z]` and returns an array like `['foo', 'x', 'y', 'z']
 *
 * @param {string} name - The name of the property to get.
 *
 * @returns An array of strings.
 */
function parsePropPath(name) {
  // foo[x][y][z]
  // foo.x.y.z
  // foo-x-y-z
  // foo x y z
  const path = [];
  const pattern = /\w+|\[(\w*)]/g;
  let match;
  while ((match = pattern.exec(name)) !== null) {
    throwIfDepthExceeded(path.length);
    path.push(match[0] === '[]' ? '' : match[1] || match[0]);
  }
  return path;
}

/**
```

```
 * Convert an array to an object.
 *
 * @param {Array<any>} arr - The array to convert to an object.
 *
 * @returns An object with the same keys and values as the array.
 */
function arrayToObject(arr) {
  const obj = {};
  const keys = Object.keys(arr);
  let i;
  const len = keys.length;
  let key;
  for (i = 0; i < len; i++) {
    key = keys[i];
    obj[key] = arr[key];
  }
  return obj;
}

/**
 * It takes a FormData object and returns a JavaScript object
 *
 * @param {string} formData The FormData
 object to convert to JSON.
 *
 * @returns {Object<string, any> | null} The converted object.
 */
function formDataToJSON(formData) {
  function buildPath(path, value, target, index) {
    throwIfDepthExceeded(index);
    let name = path[index++];
    if (name === '__proto__') return true;
    const isNumericKey = Number.isFinite(+name);
    const isLast = index >= path.length;
    name = !name && _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(target) ?
target.length : name;
    if (isLast) {
      if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(target, name)) {
        target[name] =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(target[name]) ?
target[name].concat(value) : [target[name], value];
      } else {
        target[name] = value;
      }
      return !isNumericKey;
    }
    if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasOwnProp(target, name) || !
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(target[name])) {
      target[name] = [];
```

```
    }
    const result = buildPath(path, value, target[name], index);
    if (result &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(target[name])) {
      target[name] = arrayToObject(target[name]);
    }
    return !isNumericKey;
  }
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFormData(formData) &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(formData.entries)) {
    const obj = {};
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEachEntry(formData, (name,
value) => {
      buildPath(parsePropPath(name), value, obj, 0);
    });
    return obj;
  }
  return null;
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (formDataToJSON);

/***/ },

/***/ "./node_modules/axios/lib/helpers/isAbsoluteURL.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/isAbsoluteURL.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ isAbsoluteURL)
/* harmony export */ });


/**
 * Determines whether the specified URL is absolute
 *
 * @param {string} url The URL to test
 *
 * @returns {boolean} True if the specified URL is absolute, otherwise false
 */
function isAbsoluteURL(url) {
  // A URL is considered absolute if it begins with "<scheme>://" or "//" (protocol-relative URL).
  // RFC 3986 defines scheme name as a sequence of characters beginning with a letter and followed
  // by any combination of letters, digits, plus, period, or hyphen.
  if (typeof url !== 'string') {
    return false;
```

```
  }
  return /^([a-z][a-z\d+\-.]*:)?\/\//i.test(url);
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/isAxiosError.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/isAxiosError.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ isAxiosError)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");




/**
 * Determines whether the payload is an error thrown by Axios
 *
 * @param {*} payload The value to test
 *
 * @returns {boolean} True if the payload is an error thrown by Axios, otherwise false
 */
function isAxiosError(payload) {
  return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(payload) &&
payload.isAxiosError === true;
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/isURLSameOrigin.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/isURLSameOrigin.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_0__ =
```

```
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");

/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ =
(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasStandardBrowserEnv ?
((origin, isMSIE) => url => {
  url = new URL(url,
_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].origin);
  return origin.protocol === url.protocol && origin.host === url.host && (isMSIE || origin.port ===
url.port);
})(new URL(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].origin),
_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].navigator && /(msie|
trident)/i.test(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].navigator.use
rAgent)) : () => true);

/***/ },

/***/ "./node_modules/axios/lib/helpers/null.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/null.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
// eslint-disable-next-line strict
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (null);

/***/ },

/***/ "./node_modules/axios/lib/helpers/parseHeaders.js"
/*!**********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/parseHeaders.js ***!
  \**********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
```

```
// RawAxiosHeaders whose duplicates are ignored by node
// c.f. https://nodejs.org/api/http.html#http_message_headers
const ignoreDuplicateOf =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toObjectSet(['age', 'authorization',
'content-length', 'content-type', 'etag', 'expires', 'from', 'host', 'if-modified-since', 'if-unmodified-since',
'last-modified', 'location', 'max-forwards', 'proxy-authorization', 'referer', 'retry-after', 'user-agent']);

/**
 * Parse headers into an object
 *
 * ```
 * Date: Wed, 27 Aug 2014 08:58:49 GMT
 * Content-Type: application/json
 * Connection: keep-alive
 * Transfer-Encoding: chunked
 * ```
 *
 * @param {String} rawHeaders Headers needing to be parsed
 *
 * @returns {Object} Headers parsed into an object
 */
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (rawHeaders => {
  const parsed = {};
  let key;
  let val;
  let i;
  rawHeaders && rawHeaders.split('\n').forEach(function parser(line) {
    i = line.indexOf(':');
    key = line.substring(0, i).trim().toLowerCase();
    val = line.substring(i + 1).trim();
    if (!key || parsed[key] && ignoreDuplicateOf[key]) {
      return;
    }
    if (key === 'set-cookie') {
      if (parsed[key]) {
        parsed[key].push(val);
      } else {
        parsed[key] = [val];
      }
    } else {
      parsed[key] = parsed[key] ? parsed[key] + ', ' + val : val;
    }
  });
  return parsed;
});
__webpack_require__.dn(__WEBPACK_DEFAULT_EXPORT__);

/***/ },
```

```
/***/ "./node_modules/axios/lib/helpers/parseProtocol.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/parseProtocol.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ parseProtocol)
/* harmony export */ });


function parseProtocol(url) {
  const match = /^([-+\w]{1,25}):(?:\/\/)?/.exec(url);
  return match && match[1] || '';
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/progressEventReducer.js"
/*!***************************************************************!*\
  !*** ./node_modules/axios/lib/helpers/progressEventReducer.js ***!
  \***************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   asyncDecorator: () => (/* binding */ asyncDecorator),
/* harmony export */   progressEventDecorator: () => (/* binding */ progressEventDecorator),
/* harmony export */   progressEventReducer: () => (/* binding */ progressEventReducer)
/* harmony export */ });
/* harmony import */ var _speedometer_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./speedometer.js */ "./node_modules/axios/lib/helpers/speedometer.js");
/* harmony import */ var _throttle_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./throttle.js */ "./node_modules/axios/lib/helpers/throttle.js");
/* harmony import
 */ var _utils_js__WEBPACK_IMPORTED_MODULE_2__ = __webpack_require__(/*! ../utils.js */
"./node_modules/axios/lib/utils.js");



const progressEventReducer = (listener, isDownloadStream, freq = 3) => {
  let bytesNotified = 0;
  const _speedometer = (0,_speedometer_js__WEBPACK_IMPORTED_MODULE_0__["default"])
(50, 250);
  return (0,_throttle_js__WEBPACK_IMPORTED_MODULE_1__["default"])(e => {
    if (!e || typeof e.loaded !== 'number') {
```

```
      return;
    }
    const rawLoaded = e.loaded;
    const total = e.lengthComputable ? e.total : undefined;
    const loaded = total != null ? Math.min(rawLoaded, total) : rawLoaded;
    const progressBytes = Math.max(0, loaded - bytesNotified);
    const rate = _speedometer(progressBytes);
    bytesNotified = Math.max(bytesNotified, loaded);
    const data = {
      loaded,
      total,
      progress: total ? loaded / total : undefined,
      bytes: progressBytes,
      rate: rate ? rate : undefined,
      estimated: rate && total ? (total - loaded) / rate : undefined,
      event: e,
      lengthComputable: total != null,
      [isDownloadStream ? 'download' : 'upload']: true
    };
    listener(data);
  }, freq);
};
const progressEventDecorator = (total, throttled) => {
  const lengthComputable = total != null;
  return [loaded => throttled[0]({
    lengthComputable,
    total,
    loaded
  }), throttled[1]];
};
const asyncDecorator = fn => (...args) =>
_utils_js__WEBPACK_IMPORTED_MODULE_2__["default"].asap(() => fn(...args));

/***/ },

/***/ "./node_modules/axios/lib/helpers/resolveConfig.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/resolveConfig.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_1__ =
```

```
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _isURLSameOrigin_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./isURLSameOrigin.js */
"./node_modules/axios/lib/helpers/isURLSameOrigin.js");
/* harmony import */ var _cookies_js__WEBPACK_IMPORTED_MODULE_3__ =
__webpack_require__(/*! ./cookies.js */ "./node_modules/axios/lib/helpers/cookies.js");
/* harmony import */ var _core_buildFullPath_js__WEBPACK_IMPORTED_MODULE_4__ =
__webpack_require__(/*! ../core/buildFullPath.js */ "./node_modules/axios/lib/core/buildFullPath.js");
/* harmony import */ var _core_mergeConfig_js__WEBPACK_IMPORTED_MODULE_5__ =
__webpack_require__(/*! ../core/mergeConfig.js */ "./node_modules/axios/lib/core/mergeConfig.js");
/* harmony import */ var _core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_6__ =
__webpack_require__(/*! ../core/AxiosHeaders.js */
"./node_modules/axios/lib/core/AxiosHeaders.js");
/* harmony import */ var _buildURL_js__WEBPACK_IMPORTED_MODULE_7__ =
__webpack_require__(/*! ./buildURL.js */ "./node_modules/axios/lib/helpers/buildURL.js");
```

```
const FORM_DATA_CONTENT_HEADERS = ['content-type', 'content-length'];
function setFormDataHeaders(headers, formHeaders, policy) {
  if (policy !== 'content-only') {
    headers.set(formHeaders);
    return;
  }
  Object.entries(formHeaders).forEach(([key, val]) => {
    if (FORM_DATA_CONTENT_HEADERS.includes(key.toLowerCase())) {
      headers.set(key, val);
    }
  });
}

/**
 * Encode a UTF-8 string to a Latin-1 byte string for use with btoa().
 * This is a modern replacement for the deprecated unescape(encodeURIComponent(str)) pattern.
 *
 * @param {string} str The string to encode
 *
 * @returns {string} UTF-8 bytes as a Latin-1 string
 */
const encodeUTF8 = str => encodeURIComponent(str).replace(/%([0-9A-F]{2})/gi, (_, hex) =>
String.fromCharCode(parseInt(hex, 16)));
function resolveConfig(config) {
  const newConfig = (0,_core_mergeConfig_js__WEBPACK_IMPORTED_MODULE_5__["default"])
({}, config);
```

```
  // Read only own properties to prevent prototype pollution gadgets
  // (e.g. Object.prototype.baseURL = 'https://evil.com').
  const own = key =>
_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].hasOwnProp(newConfig, key) ?
newConfig[key] : undefined;
  const data = own('data');
  let withXSRFToken = own('withXSRFToken');
  const xsrfHeaderName = own('xsrfHeaderName');
  const xsrfCookieName = own('xsrfCookieName');
  let headers = own('headers');
  const auth = own('auth');
  const baseURL = own('baseURL');
  const allowAbsoluteUrls = own('allowAbsoluteUrls');
  const url = own('url');
  newConfig.headers = headers =
_core_AxiosHeaders_js__WEBPACK_IMPORTED_MODULE_6__["default"].from(headers);
  newConfig.url = (0,_buildURL_js__WEBPACK_IMPORTED_MODULE_7__["default"])
((0,_core_buildFullPath_js__WEBPACK_IMPORTED_MODULE_4__["default"])(baseURL, url,
allowAbsoluteUrls, newConfig), own('params'), own('paramsSerializer'));

  // HTTP basic authentication
  if (auth) {
    const username = _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].getSafeProp(auth,
'username') || '';
    const password = _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].getSafeProp(auth,
'password') || '';
    headers.set('Authorization', 'Basic ' + btoa(username + ':' + (password ? encodeUTF8(password) :
'')));
  }
  if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isFormData(data)) {
    if
(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasStandardBrowserEnv ||
_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasStandardBrowserWebW
orkerEnv || _utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isReactNative(data)) {
      headers.setContentType(undefined); // browser/web worker/RN handles it
    } else if
(_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isFunction(data.getHeaders)) {
      // Node.js FormData (like form-data package)
      setFormDataHeaders(headers, data.getHeaders(), own('formDataHeaderPolicy'));
    }
  }

  // Add xsrf header
  // This is only done if running in a standard browser environment.
  // Specifically not if we're in a web worker, or react-native.

  if
(_platform_index_js__WEBPACK_IMPORTED_MODULE_0__["default"].hasStandardBrowserEnv)
```

```
{
   if (_utils_js__WEBPACK_IMPORTED_MODULE_1__["default"].isFunction(withXSRFToken)) {
     withXSRFToken = withXSRFToken(newConfig);
   }

   // Strict boolean check — prevents proto-pollution gadgets (e.g. Object.prototype.withXSRFToken =
1)
   // and misconfigurations (e.g. "false") from short-circuiting the same-origin check and leaking
   // the XSRF token cross-origin.
   const shouldSendXSRF = withXSRFToken === true || withXSRFToken == null &&
(0,_isURLSameOrigin_js__WEBPACK_IMPORTED_MODULE_2__["default"])(newConfig.url);
   if (shouldSendXSRF) {
     const xsrfValue = xsrfHeaderName && xsrfCookieName &&
_cookies_js__WEBPACK_IMPORTED_MODULE_3__["default"].read(xsrfCookieName);
     if (xsrfValue) {
       headers.set(xsrfHeaderName, xsrfValue);
     }
   }
  }
  return newConfig;
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (resolveConfig);

/***/ },

/***/ "./node_modules/axios/lib/helpers/sanitizeHeaderValue.js"
/*!***************************************************************!*\
  !*** ./node_modules/axios/lib/helpers/sanitizeHeaderValue.js ***!
  \***************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   sanitizeByteStringHeaderValue: () => (/* binding */
sanitizeByteStringHeaderValue),
/* harmony export */   sanitizeHeaderValue: () => (/* binding */ sanitizeHeaderValue),
/* harmony export */   toByteStringHeaderObject: () => (/* binding */ toByteStringHeaderObject)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");



function trimSPorHTAB(str) {
  let start = 0;
  let end = str.length;
  while (start < end) {
    const code = str.charCodeAt(start);
```

```
    if (code !== 0x09 && code !== 0x20) {
      break;
    }
    start += 1;
  }
  while (end > start) {
    const code = str.charCodeAt(end - 1);
    if (code !== 0x09 && code !== 0x20) {
      break;
    }
    end -= 1;
  }
  return start === 0 && end === str.length ? str : str.slice(start, end);
}

// The control-code ranges are intentional: header sanitization strips C0/DEL bytes.
// eslint-disable-next-line no-control-regex
const INVALID_UNICODE_HEADER_VALUE_CHARS = new
RegExp('[\\u0000-\\u0008\\u000a-\\u001f\\u007f]+', 'g');
// eslint-disable-next-line no-control-regex
const INVALID_BYTE_STRING_HEADER_VALUE_CHARS = new
RegExp('[^\\u0009\\u0020-\\u007e\\u0080-\\u00ff]+', 'g');
function sanitizeValue(value, invalidChars) {
  if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(value)) {
    return value.map(item => sanitizeValue(item, invalidChars));
  }
  return trimSPorHTAB(String(value).replace(invalidChars, ""));
}
const sanitizeHeaderValue = value => sanitizeValue(value,
INVALID_UNICODE_HEADER_VALUE_CHARS);
const sanitizeByteStringHeaderValue = value => sanitizeValue(value,
INVALID_BYTE_STRING_HEADER_VALUE_CHARS);
function toByteStringHeaderObject(headers) {
  const byteStringHeaders = Object.create(null);
  _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(headers.toJSON(), (value,
header) => {
    byteStringHeaders[header] = sanitizeByteStringHeaderValue(value);

  });
  return byteStringHeaders;
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/speedometer.js"
/*!******************************************************!*\
  !*** ./node_modules/axios/lib/helpers/speedometer.js ***!
  \******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {
```

```
"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });


/**
 * Calculate data maxRate
 * @param {Number} [samplesCount= 10]
 * @param {Number} [min= 1000]
 * @returns {Function}
 */
function speedometer(samplesCount, min) {
  samplesCount = samplesCount || 10;
  const bytes = new Array(samplesCount);
  const timestamps = new Array(samplesCount);
  let head = 0;
  let tail = 0;
  let firstSampleTS;
  min = min !== undefined ? min : 1000;
  return function push(chunkLength) {
    const now = Date.now();
    const startedAt = timestamps[tail];
    if (!firstSampleTS) {
      firstSampleTS = now;
    }
    bytes[head] = chunkLength;
    timestamps[head] = now;
    let i = tail;
    let bytesCount = 0;
    while (i !== head) {
      bytesCount += bytes[i++];
      i = i % samplesCount;
    }
    head = (head + 1) % samplesCount;
    if (head === tail) {
      tail = (tail + 1) % samplesCount;
    }
    if (now - firstSampleTS < min) {
      return;
    }
    const passed = startedAt && now - startedAt;
    return passed ? Math.round(bytesCount * 1000 / passed) : undefined;
  };
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (speedometer);
```

```
/***/ },

/***/ "./node_modules/axios/lib/helpers/spread.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/spread.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ spread)
/* harmony export */ });


/**
 * Syntactic sugar for invoking a function and expanding an array for arguments.
 *
 * Common use case would be to use `Function.prototype.apply`.
 *
 *  ```js
 *  function f(x, y, z) {}
 *  const args = [1, 2, 3];
 *  f.apply(null, args);
 *  ```
 *
 * With `spread` this example can be re-written.
 *
 *  ```js
 *  spread(function(x, y, z) {})([1, 2, 3]);
 *  ```
 *
 * @param {Function} callback
 *
 * @returns {Function}
 */
function spread(callback) {
  return function wrap(arr) {
    return callback.apply(null, arr);
  };
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/throttle.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/throttle.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {
```

```
"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/**
 * Throttle decorator
 * @param {Function} fn
 * @param {Number} freq
 * @return {Function}
 */
function throttle(fn, freq) {
  let timestamp = 0;
  let threshold = 1000 / freq;
  let lastArgs;
  let timer;
  const invoke = (args, now = Date.now()) => {
    timestamp = now;
    lastArgs = null;
    if (timer) {
      clearTimeout(timer);
      timer = null;
    }
    fn(...args);
  };
  const throttled = (...args) => {
    const now = Date.now();
    const passed = now - timestamp;
    if (passed >= threshold) {
      invoke(args, now);
    } else {
      lastArgs = args;
      if (!timer) {
        timer = setTimeout(() => {
          timer = null;
          invoke(lastArgs);
        }, threshold - passed);
      }
    }
  };
  const flush = () => lastArgs && invoke(lastArgs);
  return [throttled, flush];
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (throttle);

/***/ },

/***/ "./node_modules/axios/lib/helpers/toFormData.js"
```

```
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/toFormData.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   DEFAULT_FORM_DATA_MAX_DEPTH: () => (/* binding */
DEFAULT_FORM_DATA_MAX_DEPTH),
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");
/* harmony import */ var
_platform_node_classes_FormData_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../platform/node/classes/FormData.js */
"./node_modules/axios/lib/helpers/null.js");



// temporary hotfix to avoid circular references until AxiosURLSearchParams is refactored


// Default nesting limit shared with the inverse transform (formDataToJSON) so
// the FormData <-> JSON round-trip stays symmetric.
const DEFAULT_FORM_DATA_MAX_DEPTH = 100;

/**
 * Determines if the given thing is a array or js object.
 *
 * @param {string} thing - The object or array to be visited.
 *
 * @returns {boolean}
 */
function isVisitable(thing) {
  return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isPlainObject(thing) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(thing);
}

/**
 * It removes the brackets from the end of a string
 *
 * @param {string} key - The key of the parameter.
 *
 * @returns {string} the key without the brackets.
```

```
 */
function removeBrackets(key) {
  return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].endsWith(key, '[]') ?
key.slice(0, -2) : key;
}

/**
 * It takes a path, a key, and a boolean, and returns a string
 *
 * @param {string} path - The path to the current key.
 * @param {string} key - The key of the current object being iterated over.
 * @param {string} dots - If true, the key will be rendered with dots instead of brackets.
 *
 * @returns {string} The path to the current key.
 */
function renderKey(path, key, dots) {
  if (!path) return key;
  return path.concat(key).map(function each(token, i) {
    // eslint-disable-next-line no-param-reassign
    token = removeBrackets(token);
    return !dots && i ? '[' + token + ']' : token;
  }).join(dots ? '.' : '');
}

/**
 * If the array is an array and none of its elements are visitable, then it's a flat array.
 *
 * @param {Array<any>} arr - The array to check
 *
 * @returns {boolean}
 */
function isFlatArray(arr) {
  return _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(arr) && !
arr.some(isVisitable);
}
const predicates =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toFlatObject(_utils_js__WEBPACK_I
MPORTED_MODULE_0__["default"], {}, null, function filter(prop) {
  return /^is[A-Z]/.test(prop);
});

/**
 * Convert a data object to FormData
 *
 * @param {Object} obj
 * @param {?Object} [formData]
 * @param {?Object} [options]
 * @param {Function} [options.visitor]
 * @param {Boolean} [options.metaTokens = true]
```

```
 * @param {Boolean} [options.dots = false]
 * @param {?Boolean} [options.indexes = false]
 *
 * @returns {Object}
 **/

/**
 * It converts an object into a FormData object
 *
 * @param {Object<any, any>} obj - The object to convert to form data.
 * @param {string} formData - The FormData object to append to.
 * @param {Object<string, any>} options
 *
 * @returns
 */
function toFormData(obj, formData, options) {
  if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(obj)) {
    throw new TypeError('target must be an object');
  }

  // eslint-disable-next-line no-param-reassign
  formData = formData || new
(_platform_node_classes_FormData_js__WEBPACK_IMPORTED_MODULE_2__["default"] ||
FormData)();

  // eslint-disable-next-line no-param-reassign
  options = _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toFlatObject(options, {
    metaTokens: true,
    dots: false,
    indexes: false
  }, false, function defined(option, source) {
    // eslint-disable-next-line no-eq-null,eqeqeq
    return !
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(source[option]);
  });
  const metaTokens = options.metaTokens;
  // eslint-disable-next-line no-use-before-define
  const visitor = options.visitor || defaultVisitor;
  const dots = options.dots;
  const indexes = options.indexes;
  const _Blob = options.Blob || typeof Blob !== 'undefined' && Blob;
  const maxDepth = options.maxDepth === undefined ? DEFAULT_FORM_DATA_MAX_DEPTH :
options.maxDepth;
  const useBlob = _Blob &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isSpecCompliantForm(formData);
  const stack = [];
  if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFunction(visitor)) {
    throw new TypeError('visitor must be a function');
  }
```

```
  function convertValue(value) {
    if (value === null) return '';
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isDate(value)) {
      return value.toISOString();
    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBoolean(value)) {
      return value.toString();
    }
    if (!useBlob && _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBlob(value)) {
      throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('Blob is
not supported. Use a Buffer instead.');

    }
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArrayBuffer(value) ||
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isTypedArray(value)) {
      return useBlob && typeof Blob === 'function' ? new Blob([value]) : Buffer.from(value);
    }
    return value;
  }
  function throwIfMaxDepthExceeded(depth) {
    if (depth > maxDepth) {
      throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('Object is
too deeply nested (' + depth + ' levels). Max depth: ' + maxDepth,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_FORM_DATA_DE
PTH_EXCEEDED);
    }
  }
  function stringifyWithDepthLimit(value, depth) {
    if (maxDepth === Infinity) {
      return JSON.stringify(value);
    }
    const ancestors = [];
    return JSON.stringify(value, function limitDepth(_key, currentValue) {
      if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(currentValue)) {
        return currentValue;
      }
      while (ancestors.length && ancestors[ancestors.length - 1] !== this) {
        ancestors.pop();
      }
      ancestors.push(currentValue);
      throwIfMaxDepthExceeded(depth + ancestors.length - 1);
      return currentValue;
    });
  }

  /**
   * Default visitor.
   *
   * @param {*} value
```

```
   * @param {String|Number} key
   * @param {Array<String|Number>} path
   * @this {FormData}
   *
   * @returns {boolean} return true to visit the each prop of the value recursively
   */
  function defaultVisitor(value, key, path) {
    let arr = value;
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isReactNative(formData) &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isReactNativeBlob(value)) {
      formData.append(renderKey(path, key, dots), convertValue(value));
      return false;
    }
    if (value && !path && typeof value === 'object') {
      if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].endsWith(key, '{}')) {
        // eslint-disable-next-line no-param-reassign
        key = metaTokens ? key : key.slice(0, -2);
        // eslint-disable-next-line no-param-reassign
        value = stringifyWithDepthLimit(value, 1);
      } else if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isArray(value) &&
isFlatArray(value) || (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isFileList(value)
|| _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].endsWith(key, '[]')) && (arr =
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].toArray(value))) {
        // eslint-disable-next-line no-param-reassign
        key = removeBrackets(key);
        arr.forEach(function each(el, index) {
          !(_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(el) || el === null)
&& formData.append(
          // eslint-disable-next-line no-nested-ternary
          indexes === true ? renderKey([key], index, dots) : indexes === null ? key : key + '[]',
convertValue(el));
        });
        return false;
      }
    }
    if (isVisitable(value)) {
      return true;
    }
    formData.append(renderKey(path, key, dots), convertValue(value));
    return false;
  }
  const exposedHelpers = Object.assign(predicates, {
    defaultVisitor,
    convertValue,
    isVisitable
  });
  function build(value, path, depth = 0) {
    if (_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(value)) return;
    throwIfMaxDepthExceeded(depth);
```

```
    if (stack.indexOf(value) !== -1) {
      throw new Error('Circular reference detected in ' + path.join('.'));
    }
    stack.push(value);
    _utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].forEach(value, function each(el,
key) {
      const result = !(_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isUndefined(el) ||
el === null) && visitor.call(formData, el,
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isString(key) ? key.trim() : key, path,
exposedHelpers);
      if (result === true) {
        build(el, path ? path.concat(key) : [key], depth + 1);
      }
    });
    stack.pop();
  }
  if (!_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isObject(obj)) {
    throw new TypeError('data must be an object');
  }
  build(obj);
  return formData;
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (toFormData);

/***/ },

/***/ "./node_modules/axios/lib/helpers/toURLEncodedForm.js"
/*!***********************************************************!*\
  !*** ./node_modules/axios/lib/helpers/toURLEncodedForm.js ***!
  \***********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (/* binding */ toURLEncodedForm)
/* harmony export */ });
/* harmony import */ var _utils_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../utils.js */ "./node_modules/axios/lib/utils.js");
/* harmony import */ var _toFormData_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./toFormData.js */ "./node_modules/axios/lib/helpers/toFormData.js");
/* harmony import */ var _platform_index_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ../platform/index.js */ "./node_modules/axios/lib/platform/index.js");



function toURLEncodedForm(data, options) {
```

```
  return (0,_toFormData_js__WEBPACK_IMPORTED_MODULE_1__["default"])(data, new
_platform_index_js__WEBPACK_IMPORTED_MODULE_2__["default"].classes.URLSearchParams(
), {
    visitor: function (value, key, path, helpers) {
      if (_platform_index_js__WEBPACK_IMPORTED_MODULE_2__["default"].isNode &&
_utils_js__WEBPACK_IMPORTED_MODULE_0__["default"].isBuffer(value)) {
        this.append(key, value.toString('base64'));
        return false;
      }
      return helpers.defaultVisitor.apply(this, arguments);
    },
    ...options
  });
}

/***/ },

/***/ "./node_modules/axios/lib/helpers/trackStream.js"
/*!*******************************************************!*\
  !*** ./node_modules/axios/lib/helpers/trackStream.js ***!
  \*******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   readBytes: () => (/* binding */ readBytes),
/* harmony export */   streamChunk: () => (/* binding */ streamChunk),
/* harmony export */   trackStream: () => (/* binding */ trackStream)
/* harmony export */ });
const streamChunk = function* (chunk, chunkSize) {
  let len = chunk.byteLength;
  if (!chunkSize || len < chunkSize) {
    yield chunk;
    return;
  }
  let pos = 0;
  let end;
  while (pos < len) {
    end = pos + chunkSize;
    yield chunk.slice(pos, end);
    pos = end;
  }
};
const readBytes = async function* (iterable, chunkSize) {
  for await (const chunk of readStream(iterable)) {
    yield* streamChunk(chunk, chunkSize);
  }
};
```

```
const readStream = async function* (stream) {
  if (stream[Symbol.asyncIterator]) {
    yield* stream;
    return;
  }
  const reader = stream.getReader();
  try {
    for (;;) {
      const {
        done,
        value
      } = await reader.read();
      if (done) {
        break;
      }
      yield value;
    }
  } finally {
    await reader.cancel();
  }
};
const trackStream = (stream, chunkSize, onProgress, onFinish) => {
  const iterator = readBytes(stream, chunkSize);
  let bytes = 0;
  let done;
  let _onFinish = e => {
    if (!done) {
      done = true;
      onFinish && onFinish(e);
    }
  };
  return new ReadableStream({
    async pull(controller) {
      try {
        const {
          done,
          value
        } = await iterator.next();
        if (done) {
          _onFinish();
          controller.close();
          return;
        }
        let len = value.byteLength;
        if (onProgress) {
          let loadedBytes = bytes += len;
          onProgress(loadedBytes);
        }
        controller.enqueue(new Uint8Array(value));
```

```
      } catch (err) {
        _onFinish(err);
        throw err;
      }
    },
    cancel(reason) {
      _onFinish(reason);
      return iterator.return();
    }
  }, {
    highWaterMark: 2
  });
};

/***/ },

/***/ "./node_modules/axios/lib/helpers/validator.js"
/*!*****************************************************!*\
  !*** ./node_modules/axios/lib/helpers/validator.js ***!
  \*****************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _env_data_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../env/data.js */ "./node_modules/axios/lib/env/data.js");
/* harmony import */ var _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ../core/AxiosError.js */ "./node_modules/axios/lib/core/AxiosError.js");




const validators = {};

// eslint-disable-next-line func-names
['object', 'boolean', 'number', 'function', 'string', 'symbol'].forEach((type, i) => {
  validators[type] = function validator(thing) {
    return typeof thing === type || 'a' + (i < 1 ? 'n ' : ' ') + type;
  };
});
const deprecatedWarnings = {};

/**
 * Transitional option validator
 *
 * @param {function|boolean?} validator - set to false if the transitional option has been removed
```

```
 * @param {string?} version - deprecated version / removed since version
 * @param {string?} message - some message with additional info
 *
 * @returns {function}
 */
validators.transitional = function transitional(validator, version, message) {
  function formatMessage(opt, desc) {
    return '[Axios v' + _env_data_js__WEBPACK_IMPORTED_MODULE_0__.VERSION
 + "] Transitional option '" + opt + "'" + desc + (message ? '. ' + message : '');
  }

  // eslint-disable-next-line func-names
  return (value, opt, opts) => {
    if (validator === false) {
      throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]
(formatMessage(opt, ' has been removed' + (version ? ' in ' + version : '')),
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_DEPRECATED);
    }
    if (version && !deprecatedWarnings[opt]) {
      deprecatedWarnings[opt] = true;
      // eslint-disable-next-line no-console
      console.warn(formatMessage(opt, ' has been deprecated since v' + version + ' and will be removed
in the near future'));
    }
    return validator ? validator(value, opt, opts) : true;
  };
};
validators.spelling = function spelling(correctSpelling) {
  return (value, opt) => {
    // eslint-disable-next-line no-console
    console.warn(`${opt} is likely a misspelling of ${correctSpelling}`);
    return true;
  };
};

/**
 * Assert object's properties type
 *
 * @param {object} options
 * @param {object} schema
 * @param {boolean?} allowUnknown
 *
 * @returns {object}
 */

function assertOptions(options, schema, allowUnknown) {
  if (typeof options !== 'object') {
    throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('options
must be an object',
```

```
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_BAD_OPTION_V
ALUE);
  }
  const keys = Object.keys(options);
  let i = keys.length;
  while (i-- > 0) {
    const opt = keys[i];
    // Use hasOwnProperty so a polluted Object.prototype.<opt> cannot supply
    // a non-function validator and cause a TypeError.
    const validator = Object.prototype.hasOwnProperty.call(schema, opt) ? schema[opt] : undefined;
    if (validator) {
      const value = options[opt];
      const result = value === undefined || validator(value, opt, options);
      if (result !== true) {
        throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('option '
+ opt + ' must be ' + result,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_BAD_OPTION_V
ALUE);
      }
      continue;
    }
    if (allowUnknown !== true) {
      throw new _core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"]('Unknown
option ' + opt,
_core_AxiosError_js__WEBPACK_IMPORTED_MODULE_1__["default"].ERR_BAD_OPTION);
    }
  }
}
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  assertOptions,
  validators
});

/***/ },

/***/ "./node_modules/axios/lib/platform/browser/classes/Blob.js"
/*!*****************************************************************!*\
  !*** ./node_modules/axios/lib/platform/browser/classes/Blob.js ***!
  \*****************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });


/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (typeof Blob !==
```

```
'undefined' ? Blob : null);

/***/ },

/***/ "./node_modules/axios/lib/platform/browser/classes/FormData.js"
/*!**********************************************************************!*\
  !*** ./node_modules/axios/lib/platform/browser/classes/FormData.js ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });


/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (typeof FormData !==
'undefined' ? FormData : null);

/***/ },

/***/ "./node_modules/axios/lib/platform/browser/classes/URLSearchParams.js"
/*!**************************************************************************!*\
  !*** ./node_modules/axios/lib/platform/browser/classes/URLSearchParams.js ***!
  \**************************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var
_helpers_AxiosURLSearchParams_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ../../../helpers/AxiosURLSearchParams.js */
"./node_modules/axios/lib/helpers/AxiosURLSearchParams.js");



/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = (typeof
URLSearchParams !== 'undefined' ? URLSearchParams :
_helpers_AxiosURLSearchParams_js__WEBPACK_IMPORTED_MODULE_0__["default"]);

/***/ },

/***/ "./node_modules/axios/lib/platform/browser/index.js"
/*!**********************************************************!*\
  !*** ./node_modules/axios/lib/platform/browser/index.js ***!
```

```
  \*******************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _classes_URLSearchParams_js__WEBPACK_IMPORTED_MODULE_0__
= __webpack_require__(/*! ./classes/URLSearchParams.js */
"./node_modules/axios/lib/platform/browser/classes/URLSearchParams.js");
/* harmony import */ var _classes_FormData_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./classes/FormData.js */
"./node_modules/axios/lib/platform/browser/classes/FormData.js");
/* harmony import */ var _classes_Blob_js__WEBPACK_IMPORTED_MODULE_2__ =
__webpack_require__(/*! ./classes/Blob.js */
"./node_modules/axios/lib/platform/browser/classes/Blob.js");



/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  isBrowser: true,
  classes: {
    URLSearchParams:
_classes_URLSearchParams_js__WEBPACK_IMPORTED_MODULE_0__["default"],
    FormData: _classes_FormData_js__WEBPACK_IMPORTED_MODULE_1__["default"],
    Blob: _classes_Blob_js__WEBPACK_IMPORTED_MODULE_2__["default"]
  },
  protocols: ['http', 'https', 'file', 'blob', 'url', 'data']
});

/***/ },

/***/ "./node_modules/axios/lib/platform/common/utils.js"
/*!*********************************************************!*\
  !*** ./node_modules/axios/lib/platform/common/utils.js ***!
  \*********************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   hasBrowserEnv: () => (/* binding */ hasBrowserEnv),
/* harmony export */   hasStandardBrowserEnv: () => (/* binding */ hasStandardBrowserEnv),
/* harmony export */   hasStandardBrowserWebWorkerEnv: () => (/* binding */
hasStandardBrowserWebWorkerEnv),
/* harmony export */   navigator: () => (/* binding */ _navigator),
/* harmony export */   origin: () => (/* binding */ origin)
/* harmony export */ });
```

```
const hasBrowserEnv = typeof window !== 'undefined' && typeof document !== 'undefined';
const _navigator = typeof navigator === 'object' && navigator || undefined;

/**
 * Determine if we're running in a standard browser environment
 *
 * This allows axios to run in a web worker, and react-native.
 * Both environments support XMLHttpRequest, but not fully standard globals.
 *
 * web workers:
 *  typeof window -> undefined
 *  typeof document -> undefined
 *
 * react-native:
 *  navigator.product -> 'ReactNative'
 * nativescript
 *  navigator.product -> 'NativeScript' or 'NS'
 *
 * @returns {boolean}
 */
const hasStandardBrowserEnv = hasBrowserEnv && (!_navigator || ['ReactNative', 'NativeScript',
'NS'].indexOf(_navigator.product) < 0);

/**
 * Determine if we're running in a standard browser webWorker environment
 *
 * Although the `isStandardBrowserEnv` method indicates that
 * `allows axios to run in a web worker`, the WebWorker will still be
 * filtered out due to its judgment standard
 * `typeof window !== 'undefined' && typeof document !== 'undefined'`.
 * This leads to a problem when axios post `FormData` in webWorker
 */
const hasStandardBrowserWebWorkerEnv = (() => {
  return typeof WorkerGlobalScope !== 'undefined' &&
  // eslint-disable-next-line no-undef
  self instanceof WorkerGlobalScope && typeof self.importScripts === 'function';
})();
const origin = hasBrowserEnv && window.location.href || 'http://localhost';


/***/ },

/***/ "./node_modules/axios/lib/platform/index.js"
/*!**************************************************!*\
  !*** ./node_modules/axios/lib/platform/index.js ***!
  \**************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
```

```
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _node_index_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./node/index.js */ "./node_modules/axios/lib/platform/browser/index.js");
/* harmony import */ var _common_utils_js__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! ./common/utils.js */ "./node_modules/axios/lib/platform/common/utils.js");


/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  ..._common_utils_js__WEBPACK_IMPORTED_MODULE_1__,
  ..._node_index_js__WEBPACK_IMPORTED_MODULE_0__["default"]
});

/***/
 },

/***/ "./node_modules/axios/lib/utils.js"
/*!*****************************************!*\
  !*** ./node_modules/axios/lib/utils.js ***!
  \*****************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   "default": () => (__WEBPACK_DEFAULT_EXPORT__)
/* harmony export */ });
/* harmony import */ var _helpers_bind_js__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! ./helpers/bind.js */ "./node_modules/axios/lib/helpers/bind.js");




// utils is a library of generic helper functions non-specific to axios

const {
  toString
} = Object.prototype;
const {
  getPrototypeOf
} = Object;
const {
  iterator,
  toStringTag
} = Symbol;

/* Creating a function that will check if an object has a property. */
```

```
const hasOwnProperty = (({
  hasOwnProperty
}) => (obj, prop) => hasOwnProperty.call(obj, prop))(Object.prototype);

/**
 * Walk the prototype chain (excluding the shared Object.prototype) looking for
 * an own `prop`. This distinguishes genuine own/inherited members — including
 * class accessors and template prototypes — from members injected via
 * Object.prototype pollution (e.g. `Object.prototype.username = '...'`), which
 * live on Object.prototype itself and are therefore never matched.
 *
 * @param {*} thing The value whose chain to inspect
 * @param {string|symbol} prop The property key to look for
 *
 * @returns {boolean} True when `prop` is owned below Object.prototype
 */
const hasOwnInPrototypeChain = (thing, prop) => {
  let obj = thing;
  const seen = [];
  while (obj != null && obj !== Object.prototype) {
    if (seen.indexOf(obj) !== -1) {
      return false;
    }
    seen.push(obj);
    if (hasOwnProperty(obj, prop)) {
      return true;
    }
    obj = getPrototypeOf(obj);
  }
  return false;
};

/**
 * Read `obj[prop]` only when it is safe from Object.prototype pollution. Own
 * properties and members inherited from a non-Object.prototype source (a class
 * instance or template object) are honored; a value reachable only through a
 * polluted Object.prototype is ignored and `undefined` is returned.
 *
 * @param {*} obj The source object
 * @param {string|symbol} prop The property key to read
 *
 * @returns {*} The resolved value, or undefined when unsafe/absent
 */
const getSafeProp = (obj, prop) => obj != null && hasOwnInPrototypeChain(obj, prop) ? obj[prop] :
undefined;
const kindOf = (cache => thing => {
  const str = toString.call(thing);
  return cache[str] || (cache[str] = str.slice(8, -1).toLowerCase());
})(Object.create(null));
```

```
const kindOfTest = type => {
  type = type.toLowerCase();
  return thing => kindOf(thing) === type;
};
const typeOfTest = type => thing => typeof thing === type;

/**
 * Determine if a value is a non-null object
 *
 * @param {Object} val The value to test
 *
 * @returns {boolean} True if value is an Array, otherwise false
 */
const {
  isArray
} = Array;

/**
 * Determine if a value is undefined
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if the value is undefined, otherwise false
 */
const isUndefined = typeOfTest('undefined');

/**
 * Determine if a value is a Buffer
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a Buffer, otherwise false
 */
function isBuffer(val) {
  return val !== null && !isUndefined(val) && val.constructor !== null && !
isUndefined(val.constructor) && isFunction(val.constructor.isBuffer) && val.constructor.isBuffer(val);
}

/**
 * Determine if a value is an ArrayBuffer
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is an ArrayBuffer, otherwise false
 */
const isArrayBuffer = kindOfTest('ArrayBuffer');

/**
 * Determine if a value is a view on an ArrayBuffer
```

```
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a view on an ArrayBuffer, otherwise false
 */
function isArrayBufferView(val) {
  let result;
  if (typeof ArrayBuffer !== 'undefined' && ArrayBuffer.isView) {
    result = ArrayBuffer.isView(val);
  } else {
    result = val && val.buffer && isArrayBuffer(val.buffer);
  }
  return result;
}

/**
 * Determine if a value is a String
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a String, otherwise false
 */
const isString = typeOfTest('string');

/**
 * Determine if a value is a Function
 *
 * @param {*} val The value to test
 * @returns {boolean} True if value is a Function, otherwise false
 */
const isFunction = typeOfTest('function');

/**
 * Determine if a value is a Number
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a Number, otherwise false
 */
const isNumber = typeOfTest('number');

/**
 * Determine if a value is an Object
 *
 * @param {*} thing The value to test
 *
 * @returns {boolean} True if value is an Object, otherwise false
 */
const isObject = thing => thing !== null && typeof thing === 'object';
```

```
/**
 * Determine if a value is a Boolean
 *
 * @param {*} thing The value to test
 * @returns {boolean} True if value is a Boolean, otherwise false
 */
const isBoolean = thing => thing === true || thing === false;

/**
 * Determine if a value is a plain Object
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a plain Object, otherwise false
 */
const isPlainObject = val => {
  if (!isObject(val)) {
    return false;
  }
  const prototype = getPrototypeOf(val);
  return (prototype === null || prototype === Object.prototype || getPrototypeOf(prototype) === null)
&&
  // Treat any genuine (non-Object.prototype-polluted) Symbol.toStringTag or
  // Symbol.iterator as evidence the value is a tagged/iterable type rather
  // than a plain object, while ignoring keys injected onto Object.prototype.
  !hasOwnInPrototypeChain(val, toStringTag) && !hasOwnInPrototypeChain(val, iterator);
};

/**
 * Determine if a value is an empty object (safely handles Buffers)
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is an empty object, otherwise false
 */
const isEmptyObject = val => {
  // Early return for non-objects or Buffers to prevent RangeError
  if (!isObject(val) || isBuffer(val)) {
    return false;
  }
  try {
    return Object.keys(val).length === 0 && Object.getPrototypeOf(val) === Object.prototype;
  } catch (e) {
    // Fallback for any other objects that might cause RangeError with Object.keys()
    return false;
  }
};
```

```
/**
 * Determine if a value is a Date
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a Date, otherwise false
 */
const isDate = kindOfTest('Date');

/**
 * Determine if a value is a File
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a File, otherwise false
 */
const isFile = kindOfTest('File');

/**
 * Determine if a value is a React Native Blob
 * React Native "blob": an object with a `uri` attribute. Optionally, it can
 * also have a `name` and `type` attribute to specify filename and content type
 *
 * @see https://github.com/facebook/react-
native/blob/26684cf3adf4094eb6c405d345a75bf8c7c0bf88/Libraries/Network/FormData.js#L68-L71
 *
 * @param {*} value The value to test
 *
 * @returns {boolean} True if value is a React Native Blob, otherwise false
 */
const isReactNativeBlob = value => {
  return !!(value && typeof value.uri !== 'undefined');
};

/**
 * Determine if environment is React Native
 * ReactNative `FormData` has a non-standard `getParts()` method
 *
 * @param {*} formData The formData to test
 *
 * @returns {boolean} True if environment is React Native, otherwise false
 */
const isReactNative = formData => formData && typeof formData.getParts !== 'undefined';

/**
 * Determine if a value is a Blob
 *
 * @param {*} val The value to test
 *
```

```
 * @returns {boolean} True if value is a Blob, otherwise false
 */
const isBlob = kindOfTest('Blob');

/**
 * Determine if a value is a FileList
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a FileList, otherwise false
 */
const isFileList = kindOfTest('FileList');

/**
 * Determine if a value is a Stream
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a Stream, otherwise false
 */
const isStream = val => isObject(val) && isFunction(val.pipe);

/**
 * Determine if a value is a FormData
 *
 * @param {*} thing The value to test
 *
 * @returns {boolean} True if value is an FormData, otherwise false
 */
function getGlobal() {
  if (typeof globalThis !== 'undefined') return globalThis;
  if (typeof self !== 'undefined') return self;
  if (typeof window !== 'undefined') return window;
  if (typeof globalThis !== 'undefined') return globalThis;
  return {};
}
const G = getGlobal();
const FormDataCtor = typeof G.FormData !== 'undefined' ? G.FormData : undefined;
const isFormData = thing => {
  if (!thing) return false;
  if (FormDataCtor && thing instanceof FormDataCtor) return true;
  // Reject plain objects inheriting directly from Object.prototype so prototype-pollution gadgets can't
spoof FormData.
  const proto = getPrototypeOf(thing);
  if (!proto || proto === Object.prototype) return false;
  if (!isFunction(thing.append)) return false;
  const kind = kindOf(thing);
  return kind === 'formdata' ||
  // detect form-data instance
```

```
  kind === 'object' && isFunction(thing.toString) && thing.toString() === '[object FormData]';
};

/**
 * Determine if a value is a URLSearchParams object
 *
 * @param {*} val The value to test
 *
 * @returns {boolean} True if value is a URLSearchParams object, otherwise false
 */
const isURLSearchParams = kindOfTest('URLSearchParams');
const [isReadableStream, isRequest, isResponse, isHeaders] = ['ReadableStream', 'Request', 'Response',
'Headers'].map(kindOfTest);

/**

 * Trim excess whitespace off the beginning and end of a string
 *
 * @param {String} str The String to trim
 *
 * @returns {String} The String freed of excess whitespace
 */
const trim = str => {
  return str.trim ? str.trim() : str.replace(/^[\s\uFEFF\xA0]+|[\s\uFEFF\xA0]+$/g, '');
};
/**
 * Iterate over an Array or an Object invoking a function for each item.
 *
 * If `obj` is an Array callback will be called passing
 * the value, index, and complete array for each item.
 *
 * If 'obj' is an Object callback will be called passing
 * the value, key, and complete object for each property.
 *
 * @param {Object|Array<unknown>} obj The object to iterate
 * @param {Function} fn The callback to invoke for each item
 *
 * @param {Object} [options]
 * @param {Boolean} [options.allOwnKeys = false]
 * @returns {any}
 */
function forEach(obj, fn, {
  allOwnKeys = false
} = {}) {
  // Don't bother if no value provided
  if (obj === null || typeof obj === 'undefined') {
    return;
  }
  let i;
```

```
  let l;

  // Force an array if not already something iterable
  if (typeof obj !== 'object') {
    /*eslint no-param-reassign:0*/
    obj = [obj];
  }
  if (isArray(obj)) {
    // Iterate over array values
    for (i = 0, l = obj.length; i < l; i++) {
      fn.call(null, obj[i], i, obj);
    }
  } else {
    // Buffer check
    if (isBuffer(obj)) {
      return;
    }

    // Iterate over object keys
    const keys = allOwnKeys ? Object.getOwnPropertyNames(obj) : Object.keys(obj);
    const len = keys.length;
    let key;
    for (i = 0; i < len; i++) {
      key = keys[i];
      fn.call(null, obj[key], key, obj);
    }
  }
}

/**
 * Finds a key in an object, case-insensitive, returning the actual key name.
 * Returns null if the object is a Buffer or if no match is found.
 *
 * @param {Object} obj - The object to search.
 * @param {string} key - The key to find (case-insensitive).
 * @returns {?string} The actual key name if found, otherwise null.
 */
function findKey(obj, key) {
  if (isBuffer(obj)) {
    return null;
  }
  key = key.toLowerCase();
  const keys = Object.keys(obj);
  let i = keys.length;
  let _key;
  while (i-- > 0) {
    _key = keys[i];
    if (key === _key.toLowerCase()) {
      return _key;
```

```
    }
  }
  return null;
}
const _global = (() => {
  /*eslint no-undef:0*/
  if (typeof globalThis !== 'undefined') return globalThis;
  return typeof self !== 'undefined' ? self : typeof window !== 'undefined' ? window : globalThis;
})();
const isContextDefined = context => !isUndefined(context) && context !== _global;

/**
 * Accepts varargs expecting each argument to be an object, then
 * immutably merges the properties of each object and returns result.
 *
 * When multiple objects contain the same key the later object in
 * the arguments list will take precedence.
 *
 * Example:
 *
 * ```js
 * const result = merge({foo: 123}, {foo: 456});
 * console.log(result.foo); // outputs 456
 * ```
 *
 * @param {Object} obj1 Object to merge
 *
 * @returns {Object} Result of all merge properties
 */
function merge(...objs) {
  const {
    caseless,
    skipUndefined
  } = isContextDefined(this) && this || {};
  const result = {};
  const assignValue = (val, key) => {
    // Skip dangerous property names to prevent prototype pollution
    if (key === '__proto__' || key === 'constructor' || key === 'prototype') {
      return;
    }

    // findKey lowercases the key, so caseless lookup only applies to strings —
    // symbol keys are identity-matched.
    const targetKey = caseless && typeof key === 'string' && findKey(result, key) || key;
    // Read via own-prop only — a bare `result[targetKey]` walks the prototype
    // chain, so a polluted Object.prototype value could surface here and get
    // copied into the merged result.
    const existing = hasOwnProperty(result, targetKey) ? result[targetKey] : undefined;
    if (isPlainObject(existing) && isPlainObject(val)) {
```

```
      result[targetKey] = merge(existing, val);
    } else if (isPlainObject(val)) {
      result[targetKey] = merge({}, val);
    } else if (isArray(val)) {
      result[targetKey] = val.slice();
    } else if (!skipUndefined || !isUndefined(val)) {
      result[targetKey] = val;
    }
  };
  for (let i = 0, l = objs.length; i < l; i++) {
    const source = objs[i];
    if (!source || isBuffer(source)) {
      continue;
    }
    forEach(source, assignValue);
    if (typeof source !== 'object' || isArray(source)) {
      continue;
    }
    const symbols = Object.getOwnPropertySymbols(source);
    for (let j = 0; j < symbols.length; j++) {
      const symbol = symbols[j];
      if (propertyIsEnumerable.call(source, symbol)) {
        assignValue(source[symbol], symbol);
      }
    }
  }
  return result;
}

/**
 * Extends object a by mutably adding to it the properties of object b.
 *
 * @param {Object} a The object to be extended
 * @param {Object} b The object to copy properties from
 * @param {Object} thisArg The object to bind function to
 *
 * @param {Object} [options]
 * @param {Boolean} [options.allOwnKeys]
 * @returns {Object} The resulting value of object a
 */
const extend = (a, b, thisArg, {
  allOwnKeys
} = {}) => {
  forEach(b, (val, key) => {
    if (thisArg && isFunction(val)) {
      Object.defineProperty(a, key, {
        // Null-proto descriptor so a polluted Object.prototype.get cannot
        // hijack defineProperty's accessor-vs-data resolution.
        __proto__: null,
```

```
        value: (0,_helpers_bind_js__WEBPACK_IMPORTED_MODULE_0__["default"])(val, thisArg),
        writable: true,
        enumerable: true,
        configurable: true
      });
    } else {
      Object.defineProperty(a, key, {
        __proto__: null,
        value: val,
        writable: true,
        enumerable: true,
        configurable: true
      });
    }
  }, {
    allOwnKeys
  });
  return a;
};

/**
 * Remove byte order marker. This catches EF BB BF (the UTF-8 BOM)
 *
 * @param {string} content with BOM
 *
 * @returns {string} content value without BOM
 */
const stripBOM = content => {
  if (content.charCodeAt(0) === 0xfeff) {
    content = content.slice(1);
  }
  return content;
};

/**
 * Inherit the prototype methods from one constructor into another
 * @param {function} constructor
 * @param {function} superConstructor
 * @param {object} [props]
 * @param {object} [descriptors]
 *
 * @returns {void}
 */
const inherits = (constructor, superConstructor, props, descriptors) => {
  constructor.prototype = Object.create(superConstructor.prototype, descriptors);
  Object.defineProperty(constructor.prototype, 'constructor', {
    __proto__: null,
    value: constructor,
    writable: true,
```

```
    enumerable: false,
    configurable: true
  });
  Object.defineProperty(constructor, 'super', {
    __proto__: null,
    value: superConstructor.prototype
  });
  props && Object.assign(constructor.prototype, props);
};

/**
 * Resolve object with deep prototype chain to a flat object
 * @param {Object} sourceObj source object
 * @param {Object} [destObj]
 * @param {Function|Boolean} [filter]
 * @param {Function} [propFilter]
 *
 * @returns {Object}
 */
const toFlatObject = (sourceObj, destObj, filter, propFilter) => {
  let props;
  let i;
  let prop;
  const merged = {};
  destObj = destObj || {};
  // eslint-disable-next-line no-eq-null,eqeqeq
  if (sourceObj == null) return destObj;
  do {
    props = Object.getOwnPropertyNames(sourceObj);
    i = props.length;
    while (i-- > 0) {
      prop = props[i];
      if ((!propFilter || propFilter(prop, sourceObj, destObj)) && !merged[prop]) {
        destObj[prop] = sourceObj[prop];
        merged[prop] = true;
      }
    }
    sourceObj = filter !== false && getPrototypeOf(sourceObj);
  } while (sourceObj && (!filter || filter(sourceObj, destObj)) && sourceObj !== Object.prototype);
  return destObj;
};

/**
 * Determines whether a string ends with the characters of a specified string
 *
 * @param {String} str
 * @param {String} searchString
 * @param {Number} [position= 0]
 *
```

```
 * @returns {boolean}
 */
const endsWith = (str, searchString, position) => {
  str = String(str);
  if (position === undefined || position > str.length) {
    position = str.length;
  }
  position -= searchString.length;
  const lastIndex = str.indexOf(searchString, position);
  return lastIndex !== -1 && lastIndex === position;
};

/**
 * Returns new array from array like object or null if failed
 *
 * @param {*} [thing]
 *
 * @returns {?Array}
 */
const toArray = thing => {
  if (!thing) return null;
  if (isArray(thing)) return thing;
  let i = thing.length;
  if (!isNumber(i)) return null;
  const arr = new Array(i);
  while (i-- > 0) {
    arr[i] = thing[i];
  }
  return arr;
};

/**
 * Checking if the Uint8Array exists and if it does, it returns a function that checks if the
 * thing passed in is an instance of Uint8Array
 *
 * @param {TypedArray}
 *
 * @returns {Array}
 */
// eslint-disable-next-line func-names
const isTypedArray = (TypedArray => {
  // eslint-disable-next-line func-names
  return thing => {
    return TypedArray && thing instanceof TypedArray;
  };
})(typeof Uint8Array !== 'undefined' && getPrototypeOf(Uint8Array));

/**
 * For each entry in the object, call the function with the key and value.
```

```
 *
 * @param {Object<any, any>} obj - The object to iterate over.
 * @param {Function} fn - The function to call for each entry.
 *
 * @returns {void}
 */
const forEachEntry = (obj, fn) => {
  const generator = obj && obj[iterator];
  const _iterator = generator.call(obj);
  let result;
  while ((result = _iterator.next()) && !result.done) {
    const pair = result.value;
    fn.call(obj, pair[0], pair[1]);
  }
};

/**
 * It takes a regular expression and a string, and returns an array of all the matches
 *
 * @param {string} regExp - The regular expression to match against.
 * @param {string} str - The string to search.
 *
 * @returns
 {Array<boolean>}
 */
const matchAll = (regExp, str) => {
  let matches;
  const arr = [];
  while ((matches = regExp.exec(str)) !== null) {
    arr.push(matches);
  }
  return arr;
};

/* Checking if the kindOfTest function returns true when passed an HTMLFormElement. */
const isHTMLForm = kindOfTest('HTMLFormElement');
const toCamelCase = str => {
  return str.toLowerCase().replace(/[-_\s]([a-z\d])(\w*)/g, function replacer(m, p1, p2) {
    return p1.toUpperCase() + p2;
  });
};
const {
  propertyIsEnumerable
} = Object.prototype;

/**
 * Determine if a value is a RegExp object
 *
 * @param {*} val The value to test
```

```
 *
 * @returns {boolean} True if value is a RegExp object, otherwise false
 */
const isRegExp = kindOfTest('RegExp');
const reduceDescriptors = (obj, reducer) => {
  const descriptors = Object.getOwnPropertyDescriptors(obj);
  const reducedDescriptors = {};
  forEach(descriptors, (descriptor, name) => {
    let ret;
    if ((ret = reducer(descriptor, name, obj)) !== false) {
      reducedDescriptors[name] = ret || descriptor;
    }
  });
  Object.defineProperties(obj, reducedDescriptors);
};

/**
 * Makes all methods read-only
 * @param {Object} obj
 */

const freezeMethods = obj => {
  reduceDescriptors(obj, (descriptor, name) => {
    // skip restricted props in strict mode
    if (isFunction(obj) && ['arguments', 'caller', 'callee'].includes(name)) {
      return false;
    }
    const value = obj[name];
    if (!isFunction(value)) return;
    descriptor.enumerable = false;
    if ('writable' in descriptor) {
      descriptor.writable = false;
      return;
    }
    if (!descriptor.set) {
      descriptor.set = () => {
        throw Error("Can not rewrite read-only method '" + name + "'");
      };
    }
  });
};

/**
 * Converts an array or a delimited string into an object set with values as keys and true as values.
 * Useful for fast membership checks.
 *
 * @param {Array|string} arrayOrString - The array or string to convert.
 * @param {string} delimiter - The delimiter to use if input is a string.
 * @returns {Object} An object with keys from the array or string, values set to true.
```

```
 */
const toObjectSet = (arrayOrString, delimiter) => {
  const obj = {};
  const define = arr => {
    arr.forEach(value => {
      obj[value] = true;
    });
  };
  isArray(arrayOrString) ? define(arrayOrString) : define(String(arrayOrString).split(delimiter));
  return obj;
};
const noop = () => {};
const toFiniteNumber = (value, defaultValue) => {
  return value != null && Number.isFinite(value = +value) ? value : defaultValue;
};

/**
 * If the thing is a FormData object, return true, otherwise return false.
 *
 * @param {unknown} thing - The thing to check.
 *
 * @returns {boolean}
 */
function isSpecCompliantForm(thing) {
  return !!(thing && isFunction(thing.append) && thing[toStringTag] === 'FormData' &&
thing[iterator]);
}

/**
 * Recursively converts an object to a JSON-compatible object, handling circular references and
Buffers.
 *
 * @param {Object} obj - The object to convert.
 * @returns {Object} The JSON-compatible object.
 */
const toJSONObject = obj => {
  const visited = new WeakSet();
  const visit = source => {
    if (isObject(source)) {
      if (visited.has(source)) {
        return;
      }

      //Buffer check
      if (isBuffer(source)) {
        return source;
      }
      if (!('toJSON' in source)) {
        // add-on descent / delete-on-ascent: preserves path semantics, so DAG nodes serialise at every
```

```
occurrence (see #7230).
        visited.add(source);
        const target = isArray(source) ? [] : {};
        forEach(source, (value, key) => {
          const reducedValue = visit(value);
          !isUndefined(reducedValue) && (target[key] = reducedValue);
        });
        visited.delete(source);
        return target;
      }
    }
    return source;
  };
  return visit(obj);
};

/**
 * Determines if a value is an async function.
 *
 * @param {*} thing - The value to test.
 * @returns {boolean} True if value is an async function, otherwise false.
 */
const isAsyncFn = kindOfTest('AsyncFunction');

/**
 * Determines if a value is thenable (has then and catch methods).
 *
 * @param {*} thing - The value to test.
 * @returns {boolean} True if value is thenable, otherwise false.
 */
const isThenable = thing => thing && (isObject(thing) || isFunction(thing)) && isFunction(thing.then)
&& isFunction(thing.catch);

// original code
//
https://github.com/DigitalBrainJS/AxiosPromise/blob/16deab13710ec09779922131f3fa5954320f83ab/l
ib/utils.js#L11-L34

/**
 * Provides a cross-platform setImmediate implementation.
 * Uses native setImmediate if available, otherwise falls back to postMessage or setTimeout.
 *
 * @param {boolean} setImmediateSupported - Whether setImmediate is supported.
 * @param {boolean} postMessageSupported - Whether postMessage is supported.
 * @returns {Function} A function to schedule a callback asynchronously.
 */
const _setImmediate = ((setImmediateSupported, postMessageSupported) => {
  if (setImmediateSupported) {
    return setImmediate;
```

```
  }
  return postMessageSupported ? ((token, callbacks) => {
    _global.addEventListener('message', ({
      source,
      data
    }) => {
      if (source === _global && data === token) {
        callbacks.length && callbacks.shift()();
      }
    }, false);
    return cb => {
      callbacks.push(cb);
      _global.postMessage(token, '*');
    };
  })(`axios@${Math.random()}`, []) : cb => setTimeout(cb);
})(typeof setImmediate === 'function', isFunction(_global.postMessage));

/**
 * Schedules a microtask or asynchronous callback as soon as possible.
 * Uses queueMicrotask if available, otherwise falls back to process.nextTick or _setImmediate.
 *
 * @type {Function}
 */
const asap = typeof queueMicrotask !== 'undefined' ? queueMicrotask.bind(_global) : typeof process !
== 'undefined' && process.nextTick || _setImmediate;

// **********************

const isIterable = thing => thing != null && isFunction(thing[iterator]);

/**
 * Determine if a value is iterable via an iterator that is NOT sourced solely
 * from a polluted Object.prototype. Use this instead of `isIterable` whenever
 * the iterable comes from untrusted input (e.g. user-supplied header sources),
 * so `Object.prototype[Symbol.iterator] = ...` cannot turn an ordinary object
 * into an attacker-controlled entries iterator.
 *
 * @param {*} thing The value to test
 *
 * @returns {boolean} True if value has a non-polluted iterator
 */
const isSafeIterable = thing => thing != null && hasOwnInPrototypeChain(thing, iterator) &&
isIterable(thing);
/* harmony default export */ const __WEBPACK_DEFAULT_EXPORT__ = ({
  isArray,
  isArrayBuffer,
  isBuffer,
  isFormData,
  isArrayBufferView,
```

isString,
isNumber,
isBoolean,
isObject,
isPlainObject,
isEmptyObject,
isReadableStream,
isRequest,
isResponse,
isHeaders,
isUndefined,
isDate,
isFile,
isReactNativeBlob,
isReactNative,
isBlob,
isRegExp,
isFunction,
isStream,
isURLSearchParams,
isTypedArray,
isFileList,
forEach,
merge,
extend,
trim,
stripBOM,
inherits,
toFlatObject,
kindOf,
kindOfTest,
endsWith,
toArray,
forEachEntry,
matchAll,
isHTMLForm,
hasOwnProperty,
hasOwnProp: hasOwnProperty,
// an alias to avoid ESLint no-prototype-builtins detection
hasOwnInPrototypeChain,
getSafeProp,
reduceDescriptors,
freezeMethods,
toObjectSet,
toCamelCase,
noop,
toFiniteNumber,
findKey,
global: _global,

```
  isContextDefined,
  isSpecCompliantForm,
  toJSONObject,
  isAsyncFn,
  isThenable,
  setImmediate: _setImmediate,
  asap,
  isIterable,
  isSafeIterable
});

/***/ },

/***/ "./node_modules/react-router/dist/development/chunk-4N6VE7H7.mjs"
/*!**********************************************************************!*\
  !*** ./node_modules/react-router/dist/development/chunk-4N6VE7H7.mjs ***!
  \**********************************************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
var react__WEBPACK_IMPORTED_MODULE_0___namespace_cache;
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Action: () => (/* binding */ Action),
/* harmony export */   Await: () => (/* binding */ Await),
/* harmony export */   AwaitContextProvider: () => (/* binding */ AwaitContextProvider),
/* harmony export */   BrowserRouter: () => (/* binding */ BrowserRouter),
/* harmony export */   CRITICAL_CSS_DATA_ATTRIBUTE: () => (/* binding */
CRITICAL_CSS_DATA_ATTRIBUTE),
/* harmony export */   DataRouterContext: () => (/* binding */ DataRouterContext),
/* harmony export */   DataRouterStateContext: () => (/* binding */ DataRouterStateContext),
/* harmony export */   ENABLE_DEV_WARNINGS: () => (/* binding */
ENABLE_DEV_WARNINGS),
/* harmony export */   ErrorResponseImpl: () => (/* binding */ ErrorResponseImpl),
/* harmony export */   FetchersContext: () => (/* binding */ FetchersContext),
/* harmony export */   Form: () => (/* binding */ Form),
/* harmony export */   FrameworkContext: () => (/* binding */ FrameworkContext),
/* harmony export */   HashRouter: () => (/* binding */ HashRouter),
/* harmony export */   HistoryRouter: () => (/* binding */ HistoryRouter),
/* harmony export */   IDLE_BLOCKER: () => (/* binding */ IDLE_BLOCKER),
/* harmony export */   IDLE_FETCHER: () => (/* binding */ IDLE_FETCHER),
/* harmony export */   IDLE_NAVIGATION: () => (/* binding */ IDLE_NAVIGATION),
/* harmony export */   Link: () => (/* binding */ Link),
/* harmony export */   Links: () => (/* binding */ Links),
/* harmony export */   LocationContext: () => (/* binding */ LocationContext),
/* harmony export */   MemoryRouter: () => (/* binding */ MemoryRouter),
/* harmony export */   Meta: () => (/* binding */ Meta),
/* harmony
 export */   NO_BODY_STATUS_CODES: () => (/* binding */ NO_BODY_STATUS_CODES),
```

```
/* harmony export */   NavLink: () => (/* binding */ NavLink),
/* harmony export */   Navigate: () => (/* binding */ Navigate),
/* harmony export */   NavigationContext: () => (/* binding */ NavigationContext),
/* harmony export */   Outlet: () => (/* binding */ Outlet),
/* harmony export */   PrefetchPageLinks: () => (/* binding */ PrefetchPageLinks),
/* harmony export */   RSCRouterContext: () => (/* binding */ RSCRouterContext),
/* harmony export */   RemixErrorBoundary: () => (/* binding */ RemixErrorBoundary),
/* harmony export */   Route: () => (/* binding */ Route),
/* harmony export */   RouteContext: () => (/* binding */ RouteContext),
/* harmony export */   Router: () => (/* binding */ Router),
/* harmony export */   RouterContextProvider: () => (/* binding */ RouterContextProvider),
/* harmony export */   RouterProvider: () => (/* binding */ RouterProvider),
/* harmony export */   Routes: () => (/* binding */ Routes),
/* harmony export */   SINGLE_FETCH_REDIRECT_STATUS: () => (/* binding */
SINGLE_FETCH_REDIRECT_STATUS),
/* harmony export */   Scripts: () => (/* binding */ Scripts),
/* harmony export */   ScrollRestoration: () => (/* binding */ ScrollRestoration),
/* harmony export */   SingleFetchRedirectSymbol: () => (/* binding */ SingleFetchRedirectSymbol),
/* harmony export */   StaticRouter: () => (/* binding */ StaticRouter),
/* harmony export */   StaticRouterProvider: () => (/* binding */ StaticRouterProvider),
/* harmony export */   StreamTransfer: () => (/* binding */ StreamTransfer),
/* harmony export */   URL_LIMIT: () => (/* binding */ URL_LIMIT),
/* harmony export */   ViewTransitionContext: () => (/* binding */ ViewTransitionContext),
/* harmony export */   WithComponentProps: () => (/* binding */ WithComponentProps),
/* harmony export */   WithErrorBoundaryProps: () => (/* binding */ WithErrorBoundaryProps),
/* harmony export */   WithHydrateFallbackProps: () => (/* binding */ WithHydrateFallbackProps),
/* harmony export */   convertRoutesToDataRoutes: () => (/* binding */ convertRoutesToDataRoutes),
/* harmony export */   createBrowserHistory: () => (/* binding */ createBrowserHistory),
/* harmony export */   createBrowserRouter: () => (/* binding */ createBrowserRouter),
/* harmony export */   createClientRoutes: () => (/* binding */ createClientRoutes),
/* harmony export */   createClientRoutesWithHMRRevalidationOptOut: () => (/* binding */
createClientRoutesWithHMRRevalidationOptOut),
/* harmony export */   createContext: () => (/* binding */ createContext),
/* harmony export */   createHashHistory: () => (/* binding */ createHashHistory),
/* harmony export */   createHashRouter: () => (/* binding */ createHashRouter),
/* harmony export */   createMemoryHistory: () => (/* binding */ createMemoryHistory),
/* harmony export */   createMemoryRouter: () => (/* binding */ createMemoryRouter),
/* harmony export */   createPath: () => (/* binding */ createPath),
/* harmony export */   createRequestInit: () => (/* binding */ createRequestInit),
/* harmony export */   createRouter: () => (/* binding */ createRouter),
/* harmony export */   createRoutesFromChildren: () => (/* binding */ createRoutesFromChildren),
/* harmony export */   createRoutesFromElements: () => (/* binding */ createRoutesFromElements),
/* harmony export */   createSearchParams: () => (/* binding */ createSearchParams),
/* harmony export */   createServerRoutes: () => (/* binding */ createServerRoutes),
/* harmony export */   createStaticHandler: () => (/* binding */ createStaticHandler),
/* harmony export */   createStaticHandler2: () => (/* binding */ createStaticHandler2),
/* harmony export */   createStaticRouter: () => (/* binding */ createStaticRouter),
/* harmony export */   data: () => (/* binding */ data),
/* harmony export */   decodeRedirectErrorDigest: () => (/* binding */ decodeRedirectErrorDigest),
```

```
/* harmony export */   decodeRouteErrorResponseDigest: () => (/* binding */
decodeRouteErrorResponseDigest),
/* harmony export */   decodeViaTurboStream: () => (/* binding */ decodeViaTurboStream),
/* harmony export */   encode: () => (/* binding */ encode),
/* harmony export */   escapeHtml: () => (/* binding */ escapeHtml),
/* harmony export */   generatePath: () => (/* binding */ generatePath),
/* harmony export */   getManifestPath: () => (/* binding */ getManifestPath),
/* harmony export */   getPatchRoutesOnNavigationFunction: () => (/* binding */
getPatchRoutesOnNavigationFunction),
/* harmony export */   getSingleFetchDataStrategyImpl: () => (/* binding */
getSingleFetchDataStrategyImpl),
/* harmony export */   getStaticContextFromError: () => (/* binding */ getStaticContextFromError),
/* harmony export */   getTurboStreamSingleFetchDataStrategy: () => (/* binding */
getTurboStreamSingleFetchDataStrategy),
/* harmony export */   hydrationRouteProperties: () => (/* binding */ hydrationRouteProperties),
/* harmony export */   instrumentHandler: () => (/* binding */ instrumentHandler),
/* harmony export */   invalidProtocols: () => (/* binding */ invalidProtocols),
/* harmony export */   invariant: () => (/* binding */ invariant),
/* harmony export */   isDataWithResponseInit: () => (/* binding */ isDataWithResponseInit),
/* harmony export */   isMutationMethod: () => (/* binding */ isMutationMethod),
/* harmony export */   isRedirectResponse: () => (/* binding */ isRedirectResponse),
/* harmony export */   isRedirectStatusCode: () => (/* binding */ isRedirectStatusCode),
/* harmony export */   isResponse: () => (/* binding */ isResponse),
/* harmony export */   isRouteErrorResponse: () => (/* binding */ isRouteErrorResponse),
/* harmony export */   mapRouteProperties: () => (/* binding */ mapRouteProperties),
/* harmony export */   matchPath: () => (/* binding */ matchPath),
/* harmony export */   matchRoutes: () => (/* binding */ matchRoutes),
/* harmony export */   matchRoutesImpl: () => (/* binding */ matchRoutesImpl),
/* harmony export */   noActionDefinedError: () => (/* binding */ noActionDefinedError),
/* harmony export */   parsePath: () => (/* binding */ parsePath),
/* harmony export */   redirect: () => (/* binding */ redirect),
/* harmony export */   redirectDocument: () => (/* binding */ redirectDocument),
/* harmony export */   renderMatches: () => (/* binding */ renderMatches),
/* harmony export */   replace: () => (/* binding */ replace),
/* harmony export */   resolvePath: () => (/* binding */ resolvePath),
/* harmony export */   setIsHydrated: () => (/* binding */ setIsHydrated),
/* harmony export */   shouldHydrateRouteLoader: () => (/* binding */ shouldHydrateRouteLoader),
/* harmony export */   singleFetchUrl: () => (/* binding */ singleFetchUrl),
/* harmony export */   stripBasename: () => (/* binding */ stripBasename),
/* harmony export */   stripIndexParam: () => (/* binding */ stripIndexParam),
/* harmony export */   useActionData: () => (/* binding */ useActionData),
/* harmony export */   useAsyncError: () => (/* binding */ useAsyncError),
/* harmony export */   useAsyncValue: () => (/* binding */ useAsyncValue),
/* harmony export */   useBeforeUnload: () => (/* binding */ useBeforeUnload),
/* harmony export */   useBlocker: () => (/* binding */ useBlocker),
/* harmony export */   useFetcher: () => (/* binding */ useFetcher),
/* harmony export */   useFetchers: () => (/* binding */ useFetchers),
/* harmony export */   useFogOFWarDiscovery: () => (/* binding */ useFogOFWarDiscovery),
/* harmony export */   useFormAction: () => (/* binding */ useFormAction),
```

```
/* harmony export */   useHref: () => (/* binding */ useHref),
/* harmony export */   useInRouterContext: () => (/* binding */ useInRouterContext),
/* harmony export */   useLinkClickHandler: () => (/* binding */ useLinkClickHandler),
/* harmony export */   useLoaderData: () => (/* binding */ useLoaderData),
/* harmony export */   useLocation: () => (/* binding */ useLocation),
/* harmony export */   useMatch: () => (/* binding */ useMatch),
/* harmony export */   useMatches: () => (/* binding */ useMatches),
/* harmony export */   useNavigate: () => (/* binding */ useNavigate),
/* harmony export */   useNavigation: () => (/* binding */ useNavigation),
/* harmony export */   useNavigationType: () => (/* binding */ useNavigationType),
/* harmony export */   useOutlet: () => (/* binding */ useOutlet),
/* harmony export */   useOutletContext: () => (/* binding */ useOutletContext),
/* harmony export */   useParams: () => (/* binding */ useParams),
/* harmony export */   usePrompt: () => (/* binding */ usePrompt),
/* harmony export */   useResolvedPath: () => (/* binding */ useResolvedPath),
/* harmony export */   useRevalidator: () => (/* binding */ useRevalidator),
/* harmony export */   useRoute: () => (/* binding */ useRoute),
/* harmony export */   useRouteError: () => (/* binding */ useRouteError),
/* harmony export */   useRouteLoaderData: () => (/* binding */ useRouteLoaderData),
/* harmony export */   useRouterState: () => (/* binding */ useRouterState),
/* harmony export */   useRoutes: () => (/* binding */ useRoutes),
/* harmony export */   useScrollRestoration: () => (/* binding */ useScrollRestoration),
/* harmony export */   useSearchParams: () => (/* binding */ useSearchParams),
/* harmony export */   useSubmit: () => (/* binding */ useSubmit),
/* harmony export */   useViewTransitionState: () => (/* binding */ useViewTransitionState),
/* harmony export */   warnOnce: () => (/* binding */ warnOnce),
/* harmony export */   withComponentProps: () => (/* binding */ withComponentProps),
/* harmony export */   withErrorBoundaryProps: () => (/* binding */ withErrorBoundaryProps),
/* harmony export */   withHydrateFallbackProps: () => (/* binding */ withHydrateFallbackProps)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__
 = __webpack_require__(/*! react */ "./node_modules/react/index.js");
/**
 * react-router v7.15.1
 *
 * Copyright (c) Remix Software Inc.
 *
 * This source code is licensed under the MIT license found in the
 * LICENSE.md file in the root directory of this source tree.
 *
 * @license MIT
 */
var __typeError = msg => {
  throw TypeError(msg);
};
var __accessCheck = (obj, member, msg) => member.has(obj) || __typeError("Cannot " + msg);
var __privateGet = (obj, member, getter) => (__accessCheck(obj, member, "read from private field"),
getter ? getter.call(obj) : member.get(obj));
var __privateAdd = (obj, member, value) => member.has(obj) ? __typeError("Cannot add the same
```

```
private member more than once") : member instanceof WeakSet ? member.add(obj) : member.set(obj,
value);
var __privateSet = (obj, member, value, setter) => (__accessCheck(obj, member, "write to private
field"), setter ? setter.call(obj, value) : member.set(obj, value), value);

// lib/router/history.ts
var Action = /* @__PURE__ */(Action2 => {
  Action2["Pop"] = "POP";
  Action2["Push"] = "PUSH";
  Action2["Replace"] = "REPLACE";
  return Action2;
})(Action || {});
var PopStateEventType = "popstate";
function isLocation(obj) {
  return typeof obj === "object" && obj != null && "pathname" in obj && "search" in obj && "hash"
in obj && "state" in obj && "key" in obj;
}
function createMemoryHistory(options = {}) {
  let {
    initialEntries = ["/"],
    initialIndex,
    v5Compat = false
  } = options;
  let entries;
  entries = initialEntries.map((entry, index2) => createMemoryLocation(entry, typeof entry ===
"string" ? null : entry.state, index2 === 0 ? "default" : void 0, typeof entry === "string" ? void 0 :
entry.mask));
  let index = clampIndex(initialIndex == null ? entries.length - 1 : initialIndex);
  let action = "POP" /* Pop */;
  let listener = null;
  function clampIndex(n) {
    return Math.min(Math.max(n, 0), entries.length - 1);
  }
  function getCurrentLocation() {
    return entries[index];
  }
  function createMemoryLocation(to, state = null, key, mask) {
    let location = createLocation(entries ? getCurrentLocation().pathname : "/", to, state, key, mask);
    warning(location.pathname.charAt(0) === "/", `relative pathnames are not supported in memory
history: ${JSON.stringify(to)}`);
    return location;
  }
  function createHref2(to) {
    return typeof to === "string" ? to : createPath(to);
  }
  let history = {
    get index() {
      return index;
    },
```

```
get action() {
  return action;
},
get location() {
  return getCurrentLocation();
},
createHref: createHref2,
createURL(to) {
  return new URL(createHref2(to), "http://localhost");
},
encodeLocation(to) {
  let path = typeof to === "string" ? parsePath(to) : to;
  return {
    pathname: path.pathname || "",
    search: path.search || "",
    hash: path.hash || ""
  };
},
push(to, state) {
  action = "PUSH" /* Push */;
  let nextLocation = isLocation(to) ? to : createMemoryLocation(to, state);
  index += 1;
  entries.splice(index, entries.length, nextLocation);
  if (v5Compat && listener) {
    listener({
      action,
      location: nextLocation,
      delta: 1
    });
  }
},
replace(to, state) {
  action = "REPLACE" /* Replace */;
  let nextLocation = isLocation(to) ? to : createMemoryLocation(to, state);
  entries[index] = nextLocation;
  if (v5Compat && listener) {
    listener({
      action,
      location: nextLocation,
      delta: 0
    });
  }
},
go(delta) {
  action = "POP" /* Pop */;
  let nextIndex = clampIndex(index + delta);
  let nextLocation = entries[nextIndex];
  index = nextIndex;
  if (listener) {
```

```
        listener({
          action,
          location: nextLocation,
          delta
        });
      }
    },
    listen(fn) {
      listener = fn;
      return () => {
        listener = null;
      };
    }
  };
  return history;
}
function createBrowserHistory(options = {}) {
  function createBrowserLocation(window2, globalHistory) {
    let maskedLocation = globalHistory.state?.masked;
    let {
      pathname,
      search,
      hash
    } = maskedLocation || window2.location;
    return createLocation("", {
      pathname,
      search,
      hash
    },
    // state defaults to `null` because `window.history.state` does
    globalHistory.state && globalHistory.state.usr || null, globalHistory.state && globalHistory.state.key
|| "default", maskedLocation ? {
      pathname: window2.location.pathname,
      search: window2.location.search,
      hash: window2.location.hash
    } : void 0);
  }
  function createBrowserHref(window2, to) {
    return typeof to === "string" ? to : createPath(to);
  }
  return getUrlBasedHistory(createBrowserLocation, createBrowserHref, null, options);
}
function createHashHistory(options = {}) {
  function createHashLocation(window2, globalHistory) {
    let {
      pathname = "/",
      search = "",
      hash = ""
    } = parsePath(window2.location.hash.substring(1));
```

```
    if (!pathname.startsWith("/") && !pathname.startsWith(".")) {
      pathname = "/" + pathname;
    }
    return createLocation("", {
      pathname,
      search,
      hash
    },
    // state defaults to `null` because `window.history.state` does
    globalHistory.state && globalHistory.state.usr || null, globalHistory.state && globalHistory.state.key
|| "default");
  }
  function createHashHref(window2, to) {
    let base = window2.document.querySelector("base");
    let href = "";
    if (base && base.getAttribute("href")) {
      let url = window2.location.href;
      let hashIndex = url.indexOf("#");
      href = hashIndex === -1 ? url : url.slice(0, hashIndex);
    }
    return href + "#" + (typeof to === "string" ? to : createPath(to));
  }
  function validateHashLocation(location, to) {
    warning(location.pathname.charAt(0) === "/", `relative pathnames are not supported in hash
history.push(${JSON.stringify(to)})`);
  }
  return getUrlBasedHistory(createHashLocation, createHashHref, validateHashLocation, options);
}
function invariant(value, message) {
  if (value === false || value === null || typeof value === "undefined") {
    throw new Error(message);
  }
}
function warning(cond, message) {
  if (!cond) {
    if (typeof console !== "undefined") console.warn(message);
    try {
      throw new Error(message);
    } catch (e) {}
  }
}
function createKey() {
  return Math.random().toString(36).substring(2, 10);
}
function getHistoryState(location, index) {
  return {
    usr: location.state,
    key: location.key,
    idx: index,
```

```
    masked: location.mask ? {
      pathname: location.pathname,
      search: location.search,
      hash: location.hash
    } : void 0
  };
}
function createLocation(current, to, state = null, key, mask) {
  let location = {
    pathname: typeof current === "string" ? current : current.pathname,
    search: "",
    hash: "",
    ...(typeof to === "string" ? parsePath(to) : to),
    state,
    // TODO: This could be cleaned up.  push/replace should probably just take
    // full Locations now and avoid the need to run through this flow at all
    // But that's a pretty big refactor to the current test suite so going to
    // keep as is for the time being and just let any incoming keys take precedence
    key: to && to.key || key || createKey(),
    mask
  };
  return location;
}
function createPath({
  pathname = "/",
  search = "",
  hash = ""
}) {
  if (search && search !== "?") pathname += search.charAt(0) === "?" ? search : "?" + search;
  if (hash && hash !== "#") pathname += hash.charAt(0) === "#" ? hash : "#" + hash;
  return pathname;
}
function parsePath(path) {
  let parsedPath = {};
  if (path) {
    let hashIndex = path.indexOf("#");
    if (hashIndex >= 0) {
      parsedPath.hash = path.substring(hashIndex);
      path = path.substring(0, hashIndex);
    }
    let searchIndex = path.indexOf("?");
    if (searchIndex >= 0) {
      parsedPath.search = path.substring(searchIndex);
      path = path.substring(0, searchIndex);
    }
    if (path) {
      parsedPath.pathname = path;
    }
  }
```

```
  return parsedPath;
}
function getUrlBasedHistory(getLocation, createHref2, validateLocation, options = {}) {
  let {
    window: window2 = document.defaultView,
    v5Compat = false
  } = options;
  let globalHistory = window2.history;
  let action = "POP" /* Pop */;
  let listener = null;
  let index = getIndex();
  if (index == null) {
    index = 0;
    globalHistory.replaceState({
      ...globalHistory.state,
      idx: index
    }, "");
  }
  function getIndex() {
    let state = globalHistory.state || {
      idx: null
    };
    return state.idx;
  }
  function handlePop() {
    action = "POP" /* Pop */;
    let nextIndex = getIndex();
    let delta = nextIndex == null ? null : nextIndex - index;
    index = nextIndex;
    if (listener) {
      listener({
        action,
        location: history.location,
        delta
      });
    }
  }
  function push(to, state) {
    action = "PUSH" /* Push */;
    let location = isLocation(to) ? to : createLocation(history.location, to, state);
    if (validateLocation) validateLocation(location, to);
    index = getIndex() + 1;
    let historyState = getHistoryState(location, index);
    let url = history.createHref(location.mask || location);
    try {
      globalHistory.pushState(historyState, "", url);
    } catch (error) {
      if (error instanceof DOMException && error.name === "DataCloneError") {
        throw error;
```

```
    }
    window2.location.assign(url);
  }
  if (v5Compat && listener) {
    listener({
      action,
      location: history.location,
      delta: 1
    });
  }
}
function replace2(to, state) {
  action = "REPLACE" /* Replace */;

  let location = isLocation(to) ? to : createLocation(history.location, to, state);
  if (validateLocation) validateLocation(location, to);
  index = getIndex();
  let historyState = getHistoryState(location, index);
  let url = history.createHref(location.mask || location);
  globalHistory.replaceState(historyState, "", url);
  if (v5Compat && listener) {
    listener({
      action,
      location: history.location,
      delta: 0
    });
  }
}
function createURL(to) {
  return createBrowserURLImpl(to);
}
let history = {
  get action() {
    return action;
  },
  get location() {
    return getLocation(window2, globalHistory);
  },
  listen(fn) {
    if (listener) {
      throw new Error("A history only accepts one active listener");
    }
    window2.addEventListener(PopStateEventType, handlePop);
    listener = fn;
    return () => {
      window2.removeEventListener(PopStateEventType, handlePop);
      listener = null;
    };
  },
```

```
    createHref(to) {
      return createHref2(window2, to);
    },
    createURL,
    encodeLocation(to) {
      let url = createURL(to);
      return {
        pathname: url.pathname,
        search: url.search,
        hash: url.hash
      };
    },
    push,
    replace: replace2,
    go(n) {
      return globalHistory.go(n);
    }
  };
  return history;
}
function createBrowserURLImpl(to, isAbsolute = false) {
  let base = "http://localhost";
  if (typeof window !== "undefined") {
    base = window.location.origin !== "null" ? window.location.origin : window.location.href;
  }
  invariant(base, "No window.location.(origin|href) available to create URL");
  let href = typeof to === "string" ? to : createPath(to);
  href = href.replace(/ $/, "%20");
  if (!isAbsolute && href.startsWith("//")) {
    href = base + href;
  }
  return new URL(href, base);
}

// lib/router/utils.ts
function createContext(defaultValue) {
  return {
    defaultValue
  };
}
var _map;
var RouterContextProvider = class {
  /**
   * Create a new `RouterContextProvider` instance
   * @param init An optional initial context map to populate the provider with
   */
  constructor(init) {
    __privateAdd(this, _map, /* @__PURE__ */new Map());
    if (init) {
```

```
      for (let [context, value] of init) {
        this.set(context, value);
      }
    }
  }
  /**
   * Access a value from the context. If no value has been set for the context,
   * it will return the context's `defaultValue` if provided, or throw an error
   * if no `defaultValue` was set.
   * @param context The context to get the value for
   * @returns The value for the context, or the context's `defaultValue` if no
   * value was set
   */
  get(context) {
    if (__privateGet(this, _map).has(context)) {
      return __privateGet(this, _map).get(context);
    }
    if (context.defaultValue !== void 0) {
      return context.defaultValue;
    }
    throw new Error("No value found for context");
  }
  /**
   * Set a value for the context. If the context already has a value set, this
   * will overwrite it.
   *
   * @param context The context to set the value for
   * @param value The value to set for the context
   * @returns {void}
   */
  set(context, value) {
    __privateGet(this, _map).set(context, value);
  }
};
_map = new WeakMap();
var unsupportedLazyRouteObjectKeys = /* @__PURE__ */new Set(["lazy", "caseSensitive", "path",
"id", "index", "children"]);
function isUnsupportedLazyRouteObjectKey(key) {
  return unsupportedLazyRouteObjectKeys.has(key);
}
var unsupportedLazyRouteFunctionKeys = /* @__PURE__ */new Set(["lazy", "caseSensitive", "path",
"id", "index", "middleware", "children"]);
function isUnsupportedLazyRouteFunctionKey(key) {
  return unsupportedLazyRouteFunctionKeys.has(key);
}
function isIndexRoute(route) {
  return route.index === true;
}
function convertRoutesToDataRoutes(routes, mapRouteProperties2, parentPath = [], manifest = {},
```

```
allowInPlaceMutations = false) {
  return routes.map((route, index) => {
    let treePath = [...parentPath, String(index)];
    let id = typeof route.id === "string" ? route.id : treePath.join("-");
    invariant(route.index !== true || !route.children, `Cannot specify children on an index route`);
    invariant(allowInPlaceMutations || !manifest[id], `Found a route id collision on id "${id}".  Route
id's must be globally unique within Data Router usages`);
    if (isIndexRoute(route)) {
      let indexRoute = {
        ...route,
        id
      };
      manifest[id] = mergeRouteUpdates(indexRoute, mapRouteProperties2(indexRoute));
      return indexRoute;
    } else {
      let pathOrLayoutRoute = {
        ...route,
        id,
        children: void 0
      };
      manifest[id] = mergeRouteUpdates(pathOrLayoutRoute,
mapRouteProperties2(pathOrLayoutRoute));
      if (route.children) {
        pathOrLayoutRoute.children = convertRoutesToDataRoutes(route.children, mapRouteProperties2,
treePath, manifest, allowInPlaceMutations);
      }
      return pathOrLayoutRoute;
    }
  });
}
function mergeRouteUpdates(route, updates) {
  return Object.assign(route, {
    ...updates,
    ...(typeof updates.lazy === "object" && updates.lazy != null ? {
      lazy: {
        ...route.lazy,
        ...updates.lazy
      }
    } : {})
  });
}
function matchRoutes(routes, locationArg, basename = "/") {
  return matchRoutesImpl(routes, locationArg, basename, false);
}
function matchRoutesImpl(routes, locationArg, basename, allowPartial, precomputedBranches) {
  let location = typeof locationArg === "string" ? parsePath(locationArg) : locationArg;
  let pathname = stripBasename(location.pathname || "/", basename);
  if (pathname == null) {
    return null;
```

```
  }
  let branches = precomputedBranches ?? flattenAndRankRoutes(routes);
  let matches = null;
  let decoded = decodePath(pathname);
  for (let i = 0; matches == null && i < branches.length; ++i) {
    matches = matchRouteBranch(branches[i], decoded, allowPartial);
  }
  return matches;
}
function convertRouteMatchToUiMatch(match, loaderData) {
  let {
    route,
    pathname,
    params
  } = match;
  return {
    id: route.id,
    pathname,
    params,
    data: loaderData[route.id],
    loaderData: loaderData[route.id],
    handle: route.handle
  };
}
function flattenAndRankRoutes(routes) {
  let branches = flattenRoutes(routes);
  rankRouteBranches(branches);
  return branches;
}
function flattenRoutes(routes, branches = [], parentsMeta = [], parentPath = "",
_hasParentOptionalSegments = false) {
  let flattenRoute = (route, index, hasParentOptionalSegments = _hasParentOptionalSegments,
relativePath) => {
    let meta = {
      relativePath: relativePath === void 0 ? route.path || "" : relativePath,
      caseSensitive: route.caseSensitive === true,
      childrenIndex: index,
      route
    };
    if (meta.relativePath.startsWith("/")) {
      if (!meta.relativePath.startsWith(parentPath) && hasParentOptionalSegments) {
        return;
      }
      invariant(meta.relativePath.startsWith(parentPath), `Absolute route path "${meta.relativePath}"
nested under path "${parentPath}" is not valid. An absolute child route path must start with the
combined path of all its parent routes.`);
      meta.relativePath = meta.relativePath.slice(parentPath.length);
    }
    let path = joinPaths([parentPath, meta.relativePath]);
```

```
    let routesMeta = parentsMeta.concat(meta);
    if (route.children && route.children.length > 0) {
      invariant(
      // Our types know better, but runtime JS may not!
      // @ts-expect-error
      route.index !== true, `Index routes must not have child routes. Please remove all child routes from
route path "${path}".`);
      flattenRoutes(route.children, branches, routesMeta, path, hasParentOptionalSegments);
    }
    if (route.path == null && !route.index) {
      return;
    }
    branches.push({
      path,
      score: computeScore(path, route.index),
      routesMeta
    });
  };
  routes.forEach((route, index) => {
    if (route.path === "" || !route.path?.includes("?")) {
      flattenRoute(route, index);
    } else {
      for (let exploded of explodeOptionalSegments(route.path)) {
        flattenRoute(route, index, true, exploded);
      }
    }
  });
  return branches;
}
function explodeOptionalSegments(path) {
  let segments = path.split("/");
  if (segments.length === 0) return [];
  let [first, ...rest] = segments;
  let isOptional = first.endsWith("?");
  let required = first.replace(/\?$/, "");
  if (rest.length === 0) {
    return isOptional ? [required, ""] : [required];
  }
  let restExploded = explodeOptionalSegments(rest.join("/"));
  let result = [];
  result.push(...restExploded.map(subpath => subpath === "" ? required : [required,
subpath].join("/")));
  if (isOptional) {
    result.push(...restExploded);
  }
  return result.map(exploded => path.startsWith("/") && exploded === "" ? "/" : exploded);
}
function rankRouteBranches(branches) {
  branches.sort((a, b) => a.score !== b.score ? b.score - a.score :
```

```
compareIndexes(a.routesMeta.map(meta => meta.childrenIndex), b.routesMeta.map(meta =>
meta.childrenIndex)));
}
var paramRe = /^:[\w-]+$/;
var dynamicSegmentValue = 3;
var indexRouteValue = 2;
var emptySegmentValue = 1;
var staticSegmentValue = 10;
var splatPenalty = -2;
var isSplat = s => s === "*";
function computeScore(path, index) {
  let segments = path.split("/");
  let initialScore = segments.length;
  if (segments.some(isSplat)) {
    initialScore += splatPenalty;
  }
  if (index) {
    initialScore += indexRouteValue;
  }
  return segments.filter(s => !isSplat(s)).reduce((score, segment) => score + (paramRe.test(segment) ?
dynamicSegmentValue : segment === "" ? emptySegmentValue : staticSegmentValue), initialScore);
}
function compareIndexes(a, b) {
  let siblings = a.length === b.length && a.slice(0, -1).every((n, i) => n === b[i]);
  return
 siblings ?
  // If two routes are siblings, we should try to match the earlier sibling
  // first. This allows people to have fine-grained control over the matching
  // behavior by simply putting routes with identical paths in the order they
  // want them tried.
  a[a.length - 1] - b[b.length - 1] :
  // Otherwise, it doesn't really make sense to rank non-siblings by index,
  // so they sort equally.
  0;
}
function matchRouteBranch(branch, pathname, allowPartial = false) {
  let {
    routesMeta
  } = branch;
  let matchedParams = {};
  let matchedPathname = "/";
  let matches = [];
  for (let i = 0; i < routesMeta.length; ++i) {
    let meta = routesMeta[i];
    let end = i === routesMeta.length - 1;
    let remainingPathname = matchedPathname === "/" ? pathname :
pathname.slice(matchedPathname.length) || "/";
    let match = matchPath({
      path: meta.relativePath,
```

```
      caseSensitive: meta.caseSensitive,
      end
    }, remainingPathname);
    let route = meta.route;
    if (!match && end && allowPartial && !routesMeta[routesMeta.length - 1].route.index) {
      match = matchPath({
        path: meta.relativePath,
        caseSensitive: meta.caseSensitive,
        end: false
      }, remainingPathname);
    }
    if (!match) {
      return null;
    }
    Object.assign(matchedParams, match.params);
    matches.push({
      // TODO: Can this as be avoided?
      params: matchedParams,
      pathname: joinPaths([matchedPathname, match.pathname]),
      pathnameBase: normalizePathname(joinPaths([matchedPathname, match.pathnameBase])),
      route
    });
    if (match.pathnameBase !== "/") {
      matchedPathname = joinPaths([matchedPathname, match.pathnameBase]);
    }
  }
  return matches;
}
function generatePath(originalPath, params = {}) {
  let path = originalPath;
  if (path.endsWith("*") && path !== "*" && !path.endsWith("/*")) {
    warning(false, `Route path "${path}" will be treated as if it were "${path.replace(/\*$/, "/*")}"
because the \`*\` character must always follow a \`/\` in the pattern. To get rid of this warning, please
change the route path to "${path.replace(/\*$/, "/*")}".`);
    path = path.replace(/\*$/, "/*");
  }
  const prefix = path.startsWith("/") ? "/" : "";
  const stringify2 = p => p == null ? "" : typeof p === "string" ? p : String(p);
  const segments = path.split(/\/+/).map((segment, index, array) => {
    const isLastSegment = index === array.length - 1;
    if (isLastSegment && segment === "*") {
      return stringify2(params["*"]);
    }
    const keyMatch = segment.match(/^:([\w-]+)(\??)(.*)/);
    if (keyMatch) {
      const [, key, optional, suffix] = keyMatch;
      let param = params[key];
      invariant(optional === "?" || param != null, `Missing ":${key}" param`);
      return encodeURIComponent(stringify2(param)) + suffix;
```

```
    }
    return segment.replace(/\?$/g, "");
  }).filter(segment => !!segment);
  return prefix + segments.join("/");
}
function matchPath(pattern, pathname) {
  if (typeof pattern === "string") {
    pattern = {
      path: pattern,
      caseSensitive: false,
      end: true
    };
  }
  let [matcher, compiledParams] = compilePath(pattern.path, pattern.caseSensitive, pattern.end);
  let match = pathname.match(matcher);
  if (!match) return null;
  let matchedPathname = match[0];
  let pathnameBase = matchedPathname.replace(/(.)\/+$/, "$1");
  let captureGroups = match.slice(1);
  let params = compiledParams.reduce((memo2, {
    paramName,
    isOptional
  }, index) => {
    if (paramName === "*") {
      let splatValue = captureGroups[index] || "";
      pathnameBase = matchedPathname.slice(0, matchedPathname.length - splatValue.length).replace(/
(.)\/+$/, "$1");
    }
    const value = captureGroups[index];
    if (isOptional && !value) {
      memo2[paramName] = void 0;
    } else {
      memo2[paramName] = (value || "").replace(/%2F/g, "/");
    }
    return memo2;
  }, {});
  return {
    params,
    pathname: matchedPathname,
    pathnameBase,
    pattern
  };
}
function compilePath(path, caseSensitive = false, end = true) {
  warning(path === "*" || !path.endsWith("*") || path.endsWith("/*"), `Route path "${path}" will be
treated as if it were "${path.replace(/\*$/, "/*")}" because the \`*\` character must always follow a \`/\`
in the pattern. To get rid of this warning, please change the route path to "${path.replace(/\*$/,
"/*")}".`);
  let params = [];
```

```
  let regexpSource = "^" + path.replace(/\/*\*?$/, "").replace(/^\/*/, "/").replace(/[\\.*+^${}|()[\]]/g, "\\
$&").replace(/\/:([\w-]+)(\?)?/g, (match, paramName, isOptional, index, str) => {
    params.push({
      paramName,
      isOptional: isOptional != null
    });
    if (isOptional) {
      let nextChar = str.charAt(index + match.length);
      if (nextChar && nextChar !== "/") {
        return "/([^\\/]*)";
      }
      return "(?:/([^\\/]*))?";
    }
    return "/([^\\/]+)";
  }).replace(/\/([\w-]+)\?(\/|$)/g, "(/$1)?$2");
  if (path.endsWith("*")) {
    params.push({
      paramName: "*"
    });
    regexpSource += path === "*" || path === "/*" ? "(.*)$" : "(?:\\/(.+)|\\/*)$";
  } else if (end) {
    regexpSource += "\\/*$";
  } else if (path !== "" && path !== "/") {
    regexpSource += "(?:(?=\\/|$))";
  } else {}
  let matcher = new RegExp(regexpSource, caseSensitive ? void 0 : "i");
  return [matcher, params];
}
function decodePath(value) {
  try {
    return value.split("/").map(v => decodeURIComponent(v).replace(/\//g, "%2F")).join("/");
  } catch (error) {
    warning(false, `The URL path "${value}" could not be decoded because it is a malformed URL
segment. This is probably due to a bad percent encoding (${error}).`);
    return value;
  }
}
function stripBasename(pathname, basename) {
  if (basename === "/") return pathname;
  if (!pathname.toLowerCase().startsWith(basename.toLowerCase())) {
    return null;
  }
  let startIndex = basename.endsWith("/") ? basename.length - 1 : basename.length;
  let nextChar = pathname.charAt(startIndex);
  if (nextChar && nextChar !== "/") {
    return null;
  }
  return pathname.slice(startIndex) || "/";
}
```

```
function prependBasename({
  basename,
  pathname
}) {
  return pathname === "/" ? basename : joinPaths([basename, pathname]);
}
var ABSOLUTE_URL_REGEX = /^(?:[a-z][a-z0-9+.-]*:|\/\/)/i;
var isAbsoluteUrl = url => ABSOLUTE_URL_REGEX.test(url);
function resolvePath(to, fromPathname = "/") {
  let {
    pathname: toPathname,
    search = "",
    hash = ""
  } = typeof to === "string" ? parsePath(to) : to;
  let pathname;
  if (toPathname) {
    toPathname = removeDoubleSlashes(toPathname);
    if (toPathname.startsWith("/")) {
      pathname = resolvePathname(toPathname.substring(1), "/");
    } else {
      pathname = resolvePathname(toPathname, fromPathname);
    }
  } else {
    pathname = fromPathname;
  }
  return {
    pathname,
    search: normalizeSearch(search),
    hash: normalizeHash(hash)
  };
}
function resolvePathname(relativePath, fromPathname) {
  let segments = removeTrailingSlash(fromPathname).split("/");
  let relativeSegments = relativePath.split("/");
  relativeSegments.forEach(segment => {
    if (segment === "..") {
      if (segments.length > 1) segments.pop();
    } else if (segment !== ".") {
      segments.push(segment);
    }
  });
  return segments.length > 1 ? segments.join("/") : "/";
}
function getInvalidPathError(char, field, dest, path) {
  return `Cannot include a '${char}' character in a manually specified \`to.${field}\` field [$
{JSON.stringify(path)}].  Please separate it out to the \`to.${dest}\` field. Alternatively you may
provide the full path as a string in <Link to="..."> and the router will parse it for you.`;
}
function getPathContributingMatches(matches) {
```

```
  return matches.filter((match, index) => index === 0 || match.route.path && match.route.path.length >
0);
}
function getResolveToMatches(matches) {
  let pathMatches = getPathContributingMatches(matches);
  return pathMatches.map((match, idx) => idx === pathMatches.length - 1 ? match.pathname :
match.pathnameBase);
}
function resolveTo(toArg, routePathnames, locationPathname, isPathRelative = false) {
  let to;
  if (typeof toArg === "string") {
    to = parsePath(toArg);
  } else {
    to = {
      ...toArg
    };
    invariant(!to.pathname || !to.pathname.includes("?"), getInvalidPathError("?", "pathname", "search",
to));
    invariant(!to.pathname || !to.pathname.includes("#"), getInvalidPathError("#", "pathname", "hash",
to));
    invariant(!to.search || !to.search.includes("#"), getInvalidPathError("#", "search", "hash", to));
  }
  let isEmptyPath = toArg === "" || to.pathname === "";
  let toPathname = isEmptyPath ? "/" : to.pathname;
  let from;
  if (toPathname == null) {
    from = locationPathname;
  } else {
    let routePathnameIndex = routePathnames.length - 1;
    if (!isPathRelative && toPathname.startsWith("..")) {
      let toSegments = toPathname.split("/");
      while (toSegments[0] === "..") {
        toSegments.shift();
        routePathnameIndex -= 1;
      }
      to.pathname = toSegments.join("/");
    }
    from = routePathnameIndex >= 0 ? routePathnames[routePathnameIndex] : "/";
  }
  let path = resolvePath(to, from);
  let hasExplicitTrailingSlash = toPathname && toPathname !== "/" && toPathname.endsWith("/");
  let hasCurrentTrailingSlash = (isEmptyPath || toPathname === ".") &&
locationPathname.endsWith("/");
  if (!path.pathname.endsWith("/") && (hasExplicitTrailingSlash || hasCurrentTrailingSlash)) {
    path.pathname += "/";
  }
  return path;
}
var removeDoubleSlashes = path => path.replace(/\/\/+/g, "/");
```

```
var joinPaths = paths => removeDoubleSlashes(paths.join("/"));
var removeTrailingSlash = path => path.replace(/\/+$/, "");
var normalizePathname = pathname => removeTrailingSlash(pathname).replace(/^\/*/, "/");
var normalizeSearch = search => !search || search === "?" ? "" : search.startsWith("?")
 ? search : "?" + search;
var normalizeHash = hash => !hash || hash === "#" ? "" : hash.startsWith("#") ? hash : "#" + hash;
var DataWithResponseInit = class {
  constructor(data2, init) {
    this.type = "DataWithResponseInit";
    this.data = data2;
    this.init = init || null;
  }
};
function data(data2, init) {
  return new DataWithResponseInit(data2, typeof init === "number" ? {
    status: init
  } : init);
}
var redirect = (url, init = 302) => {
  let responseInit = init;
  if (typeof responseInit === "number") {
    responseInit = {
      status: responseInit
    };
  } else if (typeof responseInit.status === "undefined") {
    responseInit.status = 302;
  }
  let headers = new Headers(responseInit.headers);
  headers.set("Location", url);
  return new Response(null, {
    ...responseInit,
    headers
  });
};
var redirectDocument = (url, init) => {
  let response = redirect(url, init);
  response.headers.set("X-Remix-Reload-Document", "true");
  return response;
};
var replace = (url, init) => {
  let response = redirect(url, init);
  response.headers.set("X-Remix-Replace", "true");
  return response;
};
var ErrorResponseImpl = class {
  constructor(status, statusText, data2, internal = false) {
    this.status = status;
    this.statusText = statusText || "";
    this.internal = internal;
```

```
    if (data2 instanceof Error) {
      this.data = data2.toString();
      this.error = data2;
    } else {
      this.data = data2;
    }
  }
};
function isRouteErrorResponse(error) {
  return error != null && typeof error.status === "number" && typeof error.statusText === "string" &&
typeof error.internal === "boolean" && "data" in error;
}
function getRoutePattern(matches) {
  let parts = matches.map(m => m.route.path).filter(Boolean);
  return joinPaths(parts) || "/";
}
var isBrowser = typeof window !== "undefined" && typeof window.document !== "undefined" &&
typeof window.document.createElement !== "undefined";
function parseToInfo(_to, basename) {
  let to = _to;
  if (typeof to !== "string" || !ABSOLUTE_URL_REGEX.test(to)) {
    return {
      absoluteURL: void 0,
      isExternal: false,
      to
    };
  }
  let absoluteURL = to;
  let isExternal = false;
  if (isBrowser) {
    try {
      let currentUrl = new URL(window.location.href);
      let targetUrl = to.startsWith("//") ? new URL(currentUrl.protocol + to) : new URL(to);
      let path = stripBasename(targetUrl.pathname, basename);
      if (targetUrl.origin === currentUrl.origin && path != null) {
        to = path + targetUrl.search + targetUrl.hash;
      } else {
        isExternal = true;
      }
    } catch (e) {
      warning(false, `<Link to="${to}"> contains an invalid URL which will probably break when
clicked - please update to a valid URL path.`);
    }
  }
  return {
    absoluteURL,
    isExternal,
    to
  };
```

```
}

// lib/router/instrumentation.ts
var UninstrumentedSymbol = Symbol("Uninstrumented");
function getRouteInstrumentationUpdates(fns, route) {
  let aggregated = {
    lazy: [],
    "lazy.loader": [],
    "lazy.action": [],
    "lazy.middleware": [],
    middleware: [],
    loader: [],
    action: []
  };
  fns.forEach(fn => fn({
    id: route.id,
    index: route.index,
    path: route.path,
    instrument(i) {
      let keys = Object.keys(aggregated);
      for (let key of keys) {
        if (i[key]) {
          aggregated[key].push(i[key]);
        }
      }
    }
  }));
  let updates = {};
  if (typeof route.lazy === "function" && aggregated.lazy.length > 0) {
    let instrumented = wrapImpl(aggregated.lazy, route.lazy, () => void 0);
    if (instrumented) {
      updates.lazy = instrumented;
    }
  }
  if (typeof route.lazy === "object") {
    let lazyObject = route.lazy;
    ["middleware", "loader", "action"].forEach(key => {
      let lazyFn = lazyObject[key];
      let instrumentations = aggregated[`lazy.${key}`];
      if (typeof lazyFn === "function" && instrumentations.length > 0) {
        let instrumented = wrapImpl(instrumentations, lazyFn, () => void 0);
        if (instrumented) {
          updates.lazy = Object.assign(updates.lazy || {}, {
            [key]: instrumented
          });
        }
      }
    });
  }
```

```
  ["loader", "action"].forEach(key => {
    let handler = route[key];
    if (typeof handler === "function" && aggregated[key].length > 0) {
      let original = handler[UninstrumentedSymbol] ?? handler;
      let instrumented = wrapImpl(aggregated[key], original, (...args) => getHandlerInfo(args[0]));
      if (instrumented) {
        if (key === "loader" && original.hydrate === true) {
          instrumented.hydrate = true;
        }
        instrumented[UninstrumentedSymbol] = original;
        updates[key] = instrumented;
      }
    }
  });
  if (route.middleware && route.middleware.length > 0 && aggregated.middleware.length > 0) {
    updates.middleware = route.middleware.map(middleware => {
      let original = middleware[UninstrumentedSymbol] ?? middleware;
      let instrumented = wrapImpl(aggregated.middleware, original, (...args) =>
getHandlerInfo(args[0]));
      if (instrumented) {
        instrumented[UninstrumentedSymbol] = original;
        return instrumented;
      }
      return middleware;
    });
  }
  return updates;
}
function instrumentClientSideRouter(router, fns) {
  let aggregated = {
    navigate: [],
    fetch: []
  };
  fns.forEach(fn => fn({
    instrument(i) {
      let keys = Object.keys(i);
      for (let key of keys) {
        if (i[key]) {
          aggregated[key].push(i[key]);
        }
      }
    }
  }));
  if (aggregated.navigate.length > 0) {
    let navigate = router.navigate[UninstrumentedSymbol] ?? router.navigate;
    let instrumentedNavigate = wrapImpl(aggregated.navigate, navigate, (...args) => {
      let [to, opts] = args;
      return {
        to: typeof to === "number" || typeof to === "string" ? to : to ? createPath(to) : ".",
```

```
        ...getRouterInfo(router, opts ?? {})
      };
    });
    if (instrumentedNavigate) {
      instrumentedNavigate[UninstrumentedSymbol] = navigate;
      router.navigate = instrumentedNavigate;
    }
  }
  if (aggregated.fetch.length > 0) {
    let fetch2 = router.fetch[UninstrumentedSymbol] ?? router.fetch;
    let instrumentedFetch = wrapImpl(aggregated.fetch, fetch2, (...args) => {
      let [key,, href, opts] = args;
      return {
        href: href ?? ".",
        fetcherKey: key,
        ...getRouterInfo(router, opts ?? {})
      };
    });
    if (instrumentedFetch) {
      instrumentedFetch[UninstrumentedSymbol] = fetch2;
      router.fetch = instrumentedFetch;
    }
  }
  return router;
}
function instrumentHandler(handler, fns) {
  let aggregated = {
    request: []
  };
  fns.forEach(fn => fn({
    instrument(i) {
      let keys = Object.keys(i);
      for (let key of keys) {
        if (i[key]) {
          aggregated[key].push(i[key]);
        }
      }
    }
  }));
  let instrumentedHandler = handler;
  if (aggregated.request.length > 0) {
    instrumentedHandler = wrapImpl(aggregated.request, handler, (...args) => {
      let [request, context] = args;
      return {
        request: getReadonlyRequest(request),
        context: context != null ? getReadonlyContext(context) : context
      };
    });
  }
```

```
  return instrumentedHandler;
}
function wrapImpl(impls, handler, getInfo) {
  if (impls.length === 0) {
    return null;
  }
  return async (...args) => {
    let result = await recurseRight(impls, getInfo(...args), () => handler(...args), impls.length - 1);
    if (result.type === "error") {
      throw result.value;
    }
    return result.value;
  };
}
async function recurseRight(impls, info, handler, index) {
  let impl = impls[index];
  let result;
  if (!impl) {
    try {
      let value = await handler();
      result = {
        type: "success",
        value
      };
    } catch (e) {
      result = {
        type: "error",
        value: e
      };
    }
  } else {
    let handlerPromise = void 0;
    let callHandler = async () => {
      if (handlerPromise) {
        console.error("You cannot call instrumented handlers more than once");
      } else {
        handlerPromise = recurseRight(impls, info, handler, index - 1);
      }
      result = await handlerPromise;
      invariant(result, "Expected a result");
      if (result.type === "error" && result.value instanceof Error) {
        return {
          status: "error",
          error: result.value
        };
      }
      return {
        status: "success",
        error: void 0
```

```
      };
    };
    try {
      await impl(callHandler, info);
    } catch (e) {
      console.error("An instrumentation function threw an error:", e);
    }
    if (!handlerPromise) {
      await callHandler();
    }
    await handlerPromise;
  }
  if (result) {
    return result;
  }
  return {
    type: "error",
    value: new Error("No result assigned in instrumentation chain.")
  };
}
function getHandlerInfo(args) {
  let {
    request,
    context,
    params,
    pattern
  } = args;
  return {
    request: getReadonlyRequest(request),
    params: {
      ...params
    },
    pattern,
    context: getReadonlyContext(context)
  };
}
function getRouterInfo(router, opts) {
  return {
    currentUrl: createPath(router.state.location),
    ...("formMethod" in opts ? {
      formMethod: opts.formMethod
    } : {}),
    ...("formEncType" in opts ? {
      formEncType: opts.formEncType
    } : {}),
    ...("formData" in opts ? {
      formData: opts.formData
    } : {}),
    ...("body" in opts ? {
```

```
      body: opts.body
    } : {})
  };
}
function getReadonlyRequest(request) {
  return {
    method: request.method,
    url: request.url,
    headers: {
      get: (...args) => request.headers.get(...args)
    }
  };
}
function getReadonlyContext(context) {
  if (isPlainObject(context)) {
    let frozen = {
      ...context
    };
    Object.freeze(frozen);
    return frozen;

  } else {
    return {
      get: ctx => context.get(ctx)
    };
  }
}
var objectProtoNames = Object.getOwnPropertyNames(Object.prototype).sort().join("\0");
function isPlainObject(thing) {
  if (thing === null || typeof thing !== "object") {
    return false;
  }
  const proto = Object.getPrototypeOf(thing);
  return proto === Object.prototype || proto === null ||
Object.getOwnPropertyNames(proto).sort().join("\0") === objectProtoNames;
}

// lib/router/router.ts
var validMutationMethodsArr = ["POST", "PUT", "PATCH", "DELETE"];
var validMutationMethods = new Set(validMutationMethodsArr);
var validRequestMethodsArr = ["GET", ...validMutationMethodsArr];
var validRequestMethods = new Set(validRequestMethodsArr);
var redirectStatusCodes = /* @__PURE__ */new Set([301, 302, 303, 307, 308]);
var redirectPreserveMethodStatusCodes = /* @__PURE__ */new Set([307, 308]);
var IDLE_NAVIGATION = {
  state: "idle",
  location: void 0,
  matches: void 0,
  historyAction: void 0,
```

```
  formMethod: void 0,
  formAction: void 0,
  formEncType: void 0,
  formData: void 0,
  json: void 0,
  text: void 0
};
var IDLE_FETCHER = {
  state: "idle",
  data: void 0,
  formMethod: void 0,
  formAction: void 0,
  formEncType: void 0,
  formData: void 0,
  json: void 0,
  text: void 0
};
var IDLE_BLOCKER = {
  state: "unblocked",
  proceed: void 0,
  reset: void 0,
  location: void 0
};
var defaultMapRouteProperties = route => ({
  hasErrorBoundary: Boolean(route.hasErrorBoundary)
});
var TRANSITIONS_STORAGE_KEY = "remix-router-transitions";
var ResetLoaderDataSymbol = Symbol("ResetLoaderData");
var _routes, _branches, _hmrRoutes, _hmrBranches;
var DataRoutes = class {
  constructor(routes) {
    __privateAdd(this, _routes);
    __privateAdd(this, _branches);
    __privateAdd(this, _hmrRoutes);
    __privateAdd(this, _hmrBranches);
    __privateSet(this, _routes, routes);
    __privateSet(this, _branches, flattenAndRankRoutes(routes));
  }
  /** The stable route tree */
  get stableRoutes() {
    return __privateGet(this, _routes);
  }
  /** The in-flight route tree if one is active, otherwise the stable tree */
  get activeRoutes() {
    return __privateGet(this, _hmrRoutes) ?? __privateGet(this, _routes);
  }
  /** Pre-computed branches */
  get branches() {
    return __privateGet(this, _hmrBranches) ?? __privateGet(this, _branches);
```

```
  }
  get hasHMRRoutes() {
    return __privateGet(this, _hmrRoutes) != null;
  }
  /** Replace the stable route tree and recompute its branches */
  setRoutes(routes) {
    __privateSet(this, _routes, routes);
    __privateSet(this, _branches, flattenAndRankRoutes(routes));
  }
  /** Set a new in-flight route tree and recompute its branches */
  setHmrRoutes(routes) {
    __privateSet(this, _hmrRoutes, routes);
    __privateSet(this, _hmrBranches, flattenAndRankRoutes(routes));
  }
  /** Commit in-flight routes/branches to the stable slot and clear in-flight */
  commitHmrRoutes() {
    if (__privateGet(this, _hmrRoutes)) {
      __privateSet(this, _routes, __privateGet(this, _hmrRoutes));
      __privateSet(this, _branches, __privateGet(this, _hmrBranches));
      __privateSet(this, _hmrRoutes, void 0);
      __privateSet(this, _hmrBranches, void 0);
    }
  }
};
_routes = new WeakMap();
_branches = new WeakMap();
_hmrRoutes = new WeakMap();
_hmrBranches = new WeakMap();
function createRouter(init) {
  const routerWindow = init.window ? init.window : typeof window !== "undefined" ? window : void
0;
  const isBrowser3 = typeof routerWindow !== "undefined" && typeof routerWindow.document !==
"undefined" && typeof routerWindow.document.createElement !== "undefined";
  invariant(init.routes.length > 0, "You must provide a non-empty routes array to createRouter");
  let hydrationRouteProperties2 = init.hydrationRouteProperties || [];
  let _mapRouteProperties = init.mapRouteProperties || defaultMapRouteProperties;
  let mapRouteProperties2 = _mapRouteProperties;
  if (init.instrumentations) {
    let instrumentations = init.instrumentations;
    mapRouteProperties2 = route => {
      return {
        ..._mapRouteProperties(route),
        ...getRouteInstrumentationUpdates(instrumentations.map(i => i.route).filter(Boolean), route)
      };
    };
  }
  let manifest = {};
  let dataRoutes = new DataRoutes(convertRoutesToDataRoutes(init.routes, mapRouteProperties2, void
0, manifest));
```

```
  let basename = init.basename || "/";
  if (!basename.startsWith("/")) {
    basename = `/${basename}`;
  }
  let dataStrategyImpl = init.dataStrategy || defaultDataStrategyWithMiddleware;
  let future = {
    ...init.future
  };
  let unlistenHistory = null;
  let subscribers = /* @__PURE__ */new Set();
  let bufferedInitialStateUpdate = null;
  let savedScrollPositions2 = null;
  let getScrollRestorationKey2 = null;
  let getScrollPosition = null;
  let initialScrollRestored = init.hydrationData != null;
  let initialMatches = matchRoutesImpl(dataRoutes.activeRoutes, init.history.location, basename, false,
dataRoutes.branches);
  let initialMatchesIsFOW = false;
  let initialErrors = null;
  let initialized;
  let renderFallback;
  if (initialMatches == null && !init.patchRoutesOnNavigation) {
    let error = getInternalRouterError(404, {
      pathname: init.history.location.pathname
    });
    let {
      matches,
      route
    } = getShortCircuitMatches(dataRoutes.activeRoutes);
    initialized = true;
    renderFallback = !initialized;
    initialMatches = matches;
    initialErrors = {
      [route.id]: error
    };
  } else {
    if (initialMatches && !init.hydrationData) {
      let fogOfWar = checkFogOfWar(initialMatches, dataRoutes.activeRoutes,
init.history.location.pathname);
      if (fogOfWar.active) {
        initialMatches = null;
      }
    }
    if (!initialMatches) {
      initialized = false;
      renderFallback = !initialized;
      initialMatches = [];
      let fogOfWar = checkFogOfWar(null, dataRoutes.activeRoutes, init.history.location.pathname);
      if (fogOfWar.active && fogOfWar.matches) {
```

```
      initialMatchesIsFOW = true;
      initialMatches = fogOfWar.matches;
    }
  } else if (initialMatches.some(m => m.route.lazy)) {
    initialized = false;
    renderFallback = !initialized;
  } else if (!initialMatches.some(m => routeHasLoaderOrMiddleware(m.route))) {
    initialized = true;
    renderFallback = !initialized;
  } else {
    let loaderData = init.hydrationData ? init.hydrationData.loaderData : null;
    let errors = init.hydrationData ? init.hydrationData.errors : null;
    let relevantMatches = initialMatches;
    if (errors) {
      let idx = initialMatches.findIndex(m => errors[m.route.id] !== void 0);
      relevantMatches = relevantMatches.slice(0, idx + 1);
    }
    renderFallback = false;
    initialized = true;
    relevantMatches.forEach(m => {
      let status = getRouteHydrationStatus(m.route, loaderData, errors);
      renderFallback = renderFallback || status.renderFallback;
      initialized = initialized && !status.shouldLoad;
    });
  }
}
let router;
let state = {
  historyAction: init.history.action,
  location: init.history.location,
  matches: initialMatches,
  initialized,
  renderFallback,
  navigation: IDLE_NAVIGATION,
  // Don't restore on initial updateState() if we were SSR'd
  restoreScrollPosition: init.hydrationData != null ? false : null,
  preventScrollReset: false,
  revalidation: "idle",
  loaderData: init.hydrationData && init.hydrationData.loaderData || {},
  actionData: init.hydrationData && init.hydrationData.actionData || null,
  errors: init.hydrationData && init.hydrationData.errors || initialErrors,
  fetchers: /* @__PURE__ */new Map(),
  blockers: /* @__PURE__ */new Map()
};
let pendingAction = "POP" /* Pop */;
let pendingPopstateNavigationDfd = null;
let pendingPreventScrollReset = false;
let pendingNavigationController;
let pendingViewTransitionEnabled = false;
```

```
  let appliedViewTransitions = /* @__PURE__ */new Map();
  let removePageHideEventListener = null;
  let isUninterruptedRevalidation = false;
  let isRevalidationRequired = false;
  let cancelledFetcherLoads = /* @__PURE__ */new Set();
  let fetchControllers = /* @__PURE__ */new Map();
  let incrementingLoadId = 0;
  let pendingNavigationLoadId = -1;
  let fetchReloadIds = /* @__PURE__ */new Map();
  let fetchRedirectIds = /* @__PURE__ */new Set();
  let fetchLoadMatches = /* @__PURE__ */new Map();
  let activeFetchers = /* @__PURE__ */new Map();
  let fetchersQueuedForDeletion = /* @__PURE__ */new Set();
  let blockerFunctions = /* @__PURE__ */new Map();
  let unblockBlockerHistoryUpdate = void 0;
  let pendingRevalidationDfd = null;
  function initialize() {
    unlistenHistory = init.history.listen(({
      action: historyAction,
      location,
      delta
    }) => {
      if (unblockBlockerHistoryUpdate) {
        unblockBlockerHistoryUpdate();
        unblockBlockerHistoryUpdate = void 0;
        return;
      }
      warning(blockerFunctions.size === 0 || delta != null, "You are trying to use a blocker on a POP navigation to a location that was not created by @remix-run/router. This will fail silently in production. This can happen if you are navigating outside the router via `window.history.pushState`/`window.location.hash` instead of using router navigation APIs.  This can also happen if you are using createHashRouter and the user manually changes the URL.");
      let blockerKey = shouldBlockNavigation({
        currentLocation: state.location,
        nextLocation: location,
        historyAction
      });
      if (blockerKey && delta != null) {
        let nextHistoryUpdatePromise = new Promise(resolve => {
          unblockBlockerHistoryUpdate = resolve;
        });
        init.history.go(delta * -1);
        updateBlocker(blockerKey, {
          state: "blocked",
          location,

          proceed() {
            updateBlocker(blockerKey, {
              state: "proceeding",
```

```
            proceed: void 0,
            reset: void 0,
            location
          });
          nextHistoryUpdatePromise.then(() => init.history.go(delta));
        },
        reset() {
          let blockers = new Map(state.blockers);
          blockers.set(blockerKey, IDLE_BLOCKER);
          updateState({
            blockers
          });
        }
      });
      pendingPopstateNavigationDfd?.resolve();
      pendingPopstateNavigationDfd = null;
      return;
    }
    return startNavigation(historyAction, location);
  });
  if (isBrowser3) {
    restoreAppliedTransitions(routerWindow, appliedViewTransitions);
    let _saveAppliedTransitions = () => persistAppliedTransitions(routerWindow,
appliedViewTransitions);
    routerWindow.addEventListener("pagehide", _saveAppliedTransitions);
    removePageHideEventListener = () => routerWindow.removeEventListener("pagehide",
_saveAppliedTransitions);
  }
  if (!state.initialized) {
    startNavigation("POP" /* Pop */, state.location, {
      initialHydration: true
    });
  }
  return router;
}
function dispose() {
  if (unlistenHistory) {
    unlistenHistory();
  }
  if (removePageHideEventListener) {
    removePageHideEventListener();
  }
  subscribers.clear();
  pendingNavigationController && pendingNavigationController.abort();
  state.fetchers.forEach((_, key) => deleteFetcher(state.fetchers, key));
  state.blockers.forEach((_, key) => deleteBlocker(key));
}
function subscribe(fn) {
  subscribers.add(fn);
```

```
    if (bufferedInitialStateUpdate) {
      let {
        newErrors
      } = bufferedInitialStateUpdate;
      bufferedInitialStateUpdate = null;
      fn(state, {
        deletedFetchers: [],
        newErrors,
        viewTransitionOpts: void 0,
        flushSync: false
      });
    }
    return () => subscribers.delete(fn);
  }
  function updateState(newState, opts = {}) {
    if (newState.matches) {
      newState.matches = newState.matches.map(m => {
        let route = manifest[m.route.id];
        let matchRoute = m.route;
        if (matchRoute.element !== route.element || matchRoute.errorElement !== route.errorElement ||
matchRoute.hydrateFallbackElement !== route.hydrateFallbackElement) {
          return {
            ...m,
            route
          };
        }
        return m;
      });
    }
    state = {
      ...state,
      ...newState
    };
    let unmountedFetchers = [];
    let mountedFetchers = [];
    state.fetchers.forEach((fetcher, key) => {
      if (fetcher.state === "idle") {
        if (fetchersQueuedForDeletion.has(key)) {
          unmountedFetchers.push(key);
        } else {
          mountedFetchers.push(key);
        }
      }
    });
    fetchersQueuedForDeletion.forEach(key => {
      if (!state.fetchers.has(key) && !fetchControllers.has(key)) {
        unmountedFetchers.push(key);
      }
    });
```

```
    if (subscribers.size === 0) {
      bufferedInitialStateUpdate = {
        newErrors: newState.errors ?? null
      };
    }
    [...subscribers].forEach(subscriber => subscriber(state, {
      deletedFetchers: unmountedFetchers,
      newErrors: newState.errors ?? null,
      viewTransitionOpts: opts.viewTransitionOpts,
      flushSync: opts.flushSync === true
    }));
    unmountedFetchers.forEach(key => deleteFetcher(state.fetchers, key));
    mountedFetchers.forEach(key => state.fetchers.delete(key));
  }
  function completeNavigation(location, newState, {
    flushSync
  } = {}) {
    let isActionReload = state.actionData != null && state.navigation.formMethod != null &&
isMutationMethod(state.navigation.formMethod) && state.navigation.state === "loading" &&
location.state?._isRedirect !== true;
    let actionData;
    if (newState.actionData) {
      if (Object.keys(newState.actionData).length > 0) {
        actionData = newState.actionData;
      } else {
        actionData = null;
      }
    } else if (isActionReload) {
      actionData = state.actionData;
    } else {
      actionData = null;
    }
    let loaderData = newState.loaderData ? mergeLoaderData(state.loaderData, newState.loaderData,
newState.matches || [], newState.errors) : state.loaderData;
    let blockers = state.blockers;
    if (blockers.size > 0) {
      blockers = new Map(blockers);
      blockers.forEach((_, k) => blockers.set(k, IDLE_BLOCKER));
    }
    let restoreScrollPosition = isUninterruptedRevalidation ? false : getSavedScrollPosition(location,
newState.matches || state.matches);
    let preventScrollReset = pendingPreventScrollReset === true || state.navigation.formMethod != null
&& isMutationMethod(state.navigation.formMethod) && location.state?._isRedirect !== true;
    dataRoutes.commitHmrRoutes();
    if (isUninterruptedRevalidation) {} else if (pendingAction === "POP" /* Pop */) {} else if
(pendingAction === "PUSH" /* Push */) {
      init.history.push(location, location.state);
    } else if (pendingAction === "REPLACE" /* Replace */) {
      init.history.replace(location, location.state);
```

```
}
let viewTransitionOpts;
if (pendingAction === "POP" /* Pop */) {
  let priorPaths = appliedViewTransitions.get(state.location.pathname);
  if (priorPaths && priorPaths.has(location.pathname)) {
    viewTransitionOpts = {
      currentLocation: state.location,
      nextLocation: location
    };
  } else if (appliedViewTransitions.has(location.pathname)) {
    viewTransitionOpts = {
      currentLocation: location,
      nextLocation: state.location
    };
  }
} else if (pendingViewTransitionEnabled) {
  let toPaths = appliedViewTransitions.get(state.location.pathname);
  if (toPaths) {
    toPaths.add(location.pathname);
  } else {
    toPaths = /* @__PURE__ */new Set([location.pathname]);
    appliedViewTransitions.set(state.location.pathname, toPaths);
  }
  viewTransitionOpts = {
    currentLocation: state.location,
    nextLocation: location
  };
}
updateState({
  ...newState,
  // matches, errors, fetchers go through as-is
  actionData,
  loaderData,
  historyAction: pendingAction,
  location,
  initialized: true,
  renderFallback: false,
  navigation: IDLE_NAVIGATION,
  revalidation: "idle",
  restoreScrollPosition,
  preventScrollReset,
  blockers
}, {
  viewTransitionOpts,
  flushSync: flushSync === true
});
pendingAction = "POP" /* Pop */;
pendingPreventScrollReset = false;
pendingViewTransitionEnabled = false;
```

```
    isUninterruptedRevalidation = false;
    isRevalidationRequired = false;
    pendingPopstateNavigationDfd?.resolve();
    pendingPopstateNavigationDfd = null;
    pendingRevalidationDfd?.resolve();
    pendingRevalidationDfd = null;
  }
  async function navigate(to, opts) {
    pendingPopstateNavigationDfd?.resolve();
    pendingPopstateNavigationDfd = null;
    if (typeof to === "number") {
      if (!pendingPopstateNavigationDfd) {
        pendingPopstateNavigationDfd = createDeferred();
      }
      let promise = pendingPopstateNavigationDfd.promise;
      init.history.go(to);
      return promise;
    }
    let normalizedPath = normalizeTo(state.location, state.matches, basename, to, opts?.fromRouteId,
opts?.relative);
    let {
      path,
      submission,
      error
    } = normalizeNavigateOptions(false, normalizedPath, opts);
    let maskPath;
    if (opts?.mask) {
      let partialPath = typeof opts.mask === "string" ? parsePath(opts.mask) : {
        ...state.location.mask,
        ...opts.mask
      };
      maskPath = {
        pathname: "",
        search: "",
        hash: "",
        ...partialPath
      };
    }
    let currentLocation = state.location;
    let nextLocation = createLocation(currentLocation, path, opts && opts.state, void 0, maskPath);
    nextLocation = {
      ...nextLocation,
      ...init.history.encodeLocation(nextLocation)
    };
    let userReplace = opts && opts.replace != null ? opts.replace : void 0;
    let historyAction = "PUSH" /* Push */;
    if (userReplace === true) {
      historyAction = "REPLACE" /* Replace */;
    } else if (userReplace === false) {} else if (submission != null &&
```

```
isMutationMethod(submission.formMethod) && submission.formAction === state.location.pathname
+ state.location.search) {
      historyAction = "REPLACE" /* Replace */;
    }
    let preventScrollReset = opts && "preventScrollReset" in opts ? opts.preventScrollReset === true :
void 0;
    let flushSync = (opts && opts.flushSync) === true;
    let blockerKey = shouldBlockNavigation({
      currentLocation,
      nextLocation,
      historyAction
    });
    if (blockerKey) {
      updateBlocker(blockerKey, {
        state: "blocked",
        location: nextLocation,
        proceed() {
          updateBlocker(blockerKey, {
            state: "proceeding",
            proceed: void 0,
            reset: void 0,
            location: nextLocation
          });
          navigate(to, opts);
        },
        reset() {
          let blockers = new Map(state.blockers);
          blockers.set(blockerKey, IDLE_BLOCKER);
          updateState({
            blockers
          });
        }
      });
      return;
    }
    await startNavigation(historyAction, nextLocation, {
      submission,
      // Send through the formData serialization error if we have one so we can
      // render at the right error boundary after we match routes
      pendingError: error,
      preventScrollReset,
      replace: opts && opts.replace,
      enableViewTransition: opts && opts.viewTransition,
      flushSync,
      callSiteDefaultShouldRevalidate: opts && opts.defaultShouldRevalidate
    });
  }
  function revalidate() {
    if
```

```
 (!pendingRevalidationDfd) {
      pendingRevalidationDfd = createDeferred();
    }
    interruptActiveLoads();
    updateState({
      revalidation: "loading"
    });
    let promise = pendingRevalidationDfd.promise;
    if (state.navigation.state === "submitting") {
      return promise;
    }
    if (state.navigation.state === "idle") {
      startNavigation(state.historyAction, state.location, {
        startUninterruptedRevalidation: true
      });
      return promise;
    }
    startNavigation(pendingAction || state.historyAction, state.navigation.location, {
      overrideNavigation: state.navigation,
      // Proxy through any rending view transition
      enableViewTransition: pendingViewTransitionEnabled === true
    });
    return promise;
  }
  async function startNavigation(historyAction, location, opts) {
    pendingNavigationController && pendingNavigationController.abort();
    pendingNavigationController = null;
    pendingAction = historyAction;
    isUninterruptedRevalidation = (opts && opts.startUninterruptedRevalidation) === true;
    saveScrollPosition(state.location, state.matches);
    pendingPreventScrollReset = (opts && opts.preventScrollReset) === true;
    pendingViewTransitionEnabled = (opts && opts.enableViewTransition) === true;
    let routesToUse = dataRoutes.activeRoutes;
    let matches = opts?.initialHydration && state.matches && state.matches.length > 0 && !
initialMatchesIsFOW ?
    // `matchRoutes()` has already been called if we're in here via `router.initialize()`
    state.matches : matchRoutesImpl(routesToUse, location, basename, false, dataRoutes.branches);
    let flushSync = (opts && opts.flushSync) === true;
    if (matches && state.initialized && !isRevalidationRequired && isHashChangeOnly(state.location,
location) && !(opts && opts.submission && isMutationMethod(opts.submission.formMethod))) {
      completeNavigation(location, {
        matches
      }, {
        flushSync
      });
      return;
    }
    let fogOfWar = checkFogOfWar(matches, routesToUse, location.pathname);
    if (fogOfWar.active && fogOfWar.matches) {
```

```
      matches = fogOfWar.matches;
    }
    if (!matches) {
      let {
        error,
        notFoundMatches,
        route
      } = handleNavigational404(location.pathname);
      completeNavigation(location, {
        matches: notFoundMatches,
        loaderData: {},
        errors: {
          [route.id]: error
        }
      }, {
        flushSync
      });
      return;
    }
    let loadingNavigation = opts && opts.overrideNavigation ? {
      ...opts.overrideNavigation,
      matches,
      historyAction
    } : void 0;
    pendingNavigationController = new AbortController();
    let request = createClientSideRequest(init.history, location, pendingNavigationController.signal, opts
&& opts.submission);
    let scopedContext = init.getContext ? await init.getContext() : new RouterContextProvider();
    let pendingActionResult;
    if (opts && opts.pendingError) {
      pendingActionResult = [findNearestBoundary(matches).route.id, {
        type: "error" /* error */,
        error: opts.pendingError
      }];
    } else if (opts && opts.submission && isMutationMethod(opts.submission.formMethod)) {
      let actionResult = await handleAction(request, location, opts.submission, matches, historyAction,
scopedContext, fogOfWar.active, opts && opts.initialHydration === true, {
        replace: opts.replace,
        flushSync
      });
      if (actionResult.shortCircuited) {
        return;
      }
      if (actionResult.pendingActionResult) {
        let [routeId, result] = actionResult.pendingActionResult;
        if (isErrorResult(result) && isRouteErrorResponse(result.error) && result.error.status === 404) {
          pendingNavigationController = null;
          completeNavigation(location, {
            matches: actionResult.matches,
```

```
          loaderData: {},
          errors: {
            [routeId]: result.error
          }
        });
        return;
      }
    }
    matches = actionResult.matches || matches;
    pendingActionResult = actionResult.pendingActionResult;
    loadingNavigation = getLoadingNavigation(location, matches, historyAction, opts.submission);
    flushSync = false;
    fogOfWar.active = false;
    request = createClientSideRequest(init.history, request.url, request.signal);
  }
  let {
    shortCircuited,
    matches: updatedMatches,
    loaderData,
    errors,
    workingFetchers
  } = await handleLoaders(request, location, matches, historyAction, scopedContext, fogOfWar.active,
loadingNavigation, opts && opts.submission, opts && opts.fetcherSubmission, opts && opts.replace,
opts && opts.initialHydration === true, flushSync, pendingActionResult, opts &&
opts.callSiteDefaultShouldRevalidate);
  if (shortCircuited) {
    return;
  }
  pendingNavigationController = null;
  completeNavigation(location, {
    matches: updatedMatches || matches,
    ...getActionDataForCommit(pendingActionResult),
    loaderData,
    errors,
    ...(workingFetchers ? {
      fetchers: workingFetchers
    } : {})
  });
}
async function handleAction(request, location, submission, matches, historyAction, scopedContext,
isFogOfWar, initialHydration, opts = {}) {
  interruptActiveLoads();
  let navigation = getSubmittingNavigation(location, matches, historyAction, submission);
  updateState({
    navigation
  }, {
    flushSync: opts.flushSync === true
  });
  if (isFogOfWar) {
```

```
  let discoverResult = await discoverRoutes(matches, location.pathname, request.signal);
  if (discoverResult.type === "aborted") {
    return {
      shortCircuited: true
    };
  } else if (discoverResult.type === "error") {
    if (discoverResult.partialMatches.length === 0) {
      let {
        matches: matches2,
        route
      } = getShortCircuitMatches(dataRoutes.activeRoutes);
      return {
        matches: matches2,
        pendingActionResult: [route.id, {
          type: "error" /* error */,
          error: discoverResult.error
        }]
      };
    }
    let boundaryId = findNearestBoundary(discoverResult.partialMatches).route.id;
    return {
      matches: discoverResult.partialMatches,
      pendingActionResult: [boundaryId, {
        type: "error" /* error */,
        error: discoverResult.error
      }]
    };
  } else if (!discoverResult.matches) {
    let {
      notFoundMatches,
      error,
      route
    } = handleNavigational404(location.pathname);
    return {
      matches: notFoundMatches,
      pendingActionResult: [route.id, {
        type: "error" /* error */,
        error
      }]
    };
  } else {
    matches = discoverResult.matches;
  }
}
let result;
let actionMatch = getTargetMatch(matches, location);
if (!actionMatch.route.action && !actionMatch.route.lazy) {
  result = {
    type: "error" /* error */,
```

```
        error: getInternalRouterError(405, {
          method: request.method,
          pathname: location.pathname,
          routeId: actionMatch.route.id
        })
      };
    } else {
      let dsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest, request,
location, matches, actionMatch, initialHydration ? [] : hydrationRouteProperties2, scopedContext);
      let results = await callDataStrategy(request, location, dsMatches, scopedContext, null);
      result = results[actionMatch.route.id];
      if (!result) {
        for (let match of matches) {
          if (results[match.route.id]) {
            result = results[match.route.id];
            break;
          }
        }
      }
      if (request.signal.aborted) {
        return {
          shortCircuited: true
        };
      }
    }
    if (isRedirectResult(result)) {
      let replace2;
      if (opts && opts.replace != null) {
        replace2 = opts.replace;
      } else {
        let location2 = normalizeRedirectLocation(result.response.headers.get("Location"), new
URL(request.url), basename, init.history);
        replace2 = location2 === state.location.pathname + state.location.search;
      }
      await startRedirectNavigation(request, result, true, {
        submission,
        replace: replace2
      });
      return {
        shortCircuited: true
      };
    }
    if (isErrorResult(result)) {
      let boundaryMatch = findNearestBoundary(matches, actionMatch.route.id);
      if ((opts && opts.replace) !== true) {
        pendingAction = "PUSH" /* Push */;
      }
      return {
        matches,
```

```
      pendingActionResult: [boundaryMatch.route.id, result, actionMatch.route.id]
    };
  }
  return {
    matches,
    pendingActionResult: [actionMatch.route.id, result]
  };
}
 async function handleLoaders(request, location, matches, historyAction, scopedContext, isFogOfWar,
overrideNavigation, submission, fetcherSubmission, replace2, initialHydration, flushSync,
pendingActionResult, callSiteDefaultShouldRevalidate) {
  let loadingNavigation = overrideNavigation || getLoadingNavigation(location, matches,
historyAction, submission);
  let activeSubmission = submission || fetcherSubmission ||
getSubmissionFromNavigation(loadingNavigation);
  let shouldUpdateNavigationState = !isUninterruptedRevalidation && !initialHydration;
  if (isFogOfWar) {
    if (shouldUpdateNavigationState) {
      let actionData = getUpdatedActionData(pendingActionResult);
      updateState({
        navigation: loadingNavigation,
        ...(actionData !== void 0 ? {
          actionData
        } : {})
      }, {
        flushSync
      });
    }
    let discoverResult = await discoverRoutes(matches, location.pathname, request.signal);

    if (discoverResult.type === "aborted") {
      return {
        shortCircuited: true
      };
    } else if (discoverResult.type === "error") {
      if (discoverResult.partialMatches.length === 0) {
        let {
          matches: matches2,
          route
        } = getShortCircuitMatches(dataRoutes.activeRoutes);
        return {
          matches: matches2,
          loaderData: {},
          errors: {
            [route.id]: discoverResult.error
          }
        };
      }
      let boundaryId = findNearestBoundary(discoverResult.partialMatches).route.id;
```

```
        return {
          matches: discoverResult.partialMatches,
          loaderData: {},
          errors: {
            [boundaryId]: discoverResult.error
          }
        };
      } else if (!discoverResult.matches) {
        let {
          error,
          notFoundMatches,
          route
        } = handleNavigational404(location.pathname);
        return {
          matches: notFoundMatches,
          loaderData: {},
          errors: {
            [route.id]: error
          }
        };
      } else {
        matches = discoverResult.matches;
      }
    }
    let routesToUse = dataRoutes.activeRoutes;
    let {
      dsMatches,
      revalidatingFetchers
    } = getMatchesToLoad(request, scopedContext, mapRouteProperties2, manifest, init.history, state,
matches, activeSubmission, location, initialHydration ? [] : hydrationRouteProperties2, initialHydration
=== true, isRevalidationRequired, cancelledFetcherLoads, fetchersQueuedForDeletion,
fetchLoadMatches, fetchRedirectIds, routesToUse, basename, init.patchRoutesOnNavigation != null,
dataRoutes.branches, pendingActionResult, callSiteDefaultShouldRevalidate);
    pendingNavigationLoadId = ++incrementingLoadId;
    if (!init.dataStrategy && !dsMatches.some(m => m.shouldLoad) && !dsMatches.some(m =>
m.route.middleware && m.route.middleware.length > 0) && revalidatingFetchers.length === 0) {
      let workingFetchers2 = new Map(state.fetchers);
      let didUpdateFetcherRedirects2 = markFetchRedirectsDone(workingFetchers2);
      completeNavigation(location, {
        matches,
        loaderData: {},
        // Commit pending error if we're short circuiting
        errors: pendingActionResult && isErrorResult(pendingActionResult[1]) ? {
          [pendingActionResult[0]]: pendingActionResult[1].error
        } : null,
        ...getActionDataForCommit(pendingActionResult),
        ...(didUpdateFetcherRedirects2 ? {
          fetchers: workingFetchers2
        } : {})
```

```
      }, {
        flushSync
      });
      return {
        shortCircuited: true
      };
    }
    if (shouldUpdateNavigationState) {
      let updates = {};
      if (!isFogOfWar) {
        updates.navigation = loadingNavigation;
        let actionData = getUpdatedActionData(pendingActionResult);
        if (actionData !== void 0) {
          updates.actionData = actionData;
        }
      }
      if (revalidatingFetchers.length > 0) {
        updates.fetchers = getUpdatedRevalidatingFetchers(revalidatingFetchers);
      }
      updateState(updates, {
        flushSync
      });
    }
    revalidatingFetchers.forEach(rf => {
      abortFetcher(rf.key);
      if (rf.controller) {
        fetchControllers.set(rf.key, rf.controller);
      }
    });
    let abortPendingFetchRevalidations = () => revalidatingFetchers.forEach(f => abortFetcher(f.key));
    if (pendingNavigationController) {
      pendingNavigationController.signal.addEventListener("abort", abortPendingFetchRevalidations);
    }
    let {
      loaderResults,
      fetcherResults
    } = await callLoadersAndMaybeResolveData(dsMatches, revalidatingFetchers, request, location,
scopedContext);
    if (request.signal.aborted) {
      return {
        shortCircuited: true
      };
    }
    if (pendingNavigationController) {
      pendingNavigationController.signal.removeEventListener("abort",
abortPendingFetchRevalidations);
    }
    revalidatingFetchers.forEach(rf => fetchControllers.delete(rf.key));
    let redirect2 = findRedirect(loaderResults);
```

```
    if (redirect2) {
      await startRedirectNavigation(request, redirect2.result, true, {
        replace: replace2
      });
      return {
        shortCircuited: true
      };
    }
    redirect2 = findRedirect(fetcherResults);
    if (redirect2) {
      fetchRedirectIds.add(redirect2.key);
      await startRedirectNavigation(request, redirect2.result, true, {
        replace: replace2
      });
      return {
        shortCircuited: true
      };
    }
    let workingFetchers = new Map(state.fetchers);
    let {
      loaderData,
      errors
    } = processLoaderData(state, matches, loaderResults, pendingActionResult, revalidatingFetchers,
fetcherResults, workingFetchers);
    if (initialHydration && state.errors) {
      errors = {
        ...state.errors,
        ...errors
      };
    }
    let didUpdateFetcherRedirects = markFetchRedirectsDone(workingFetchers);
    let didAbortFetchLoads = abortStaleFetchLoads(pendingNavigationLoadId, workingFetchers);
    let shouldUpdateFetchers = didUpdateFetcherRedirects || didAbortFetchLoads ||
revalidatingFetchers.length > 0;
    return {
      matches,
      loaderData,
      errors,
      ...(shouldUpdateFetchers ? {
        workingFetchers
      } : {})
    };
  }
  function getUpdatedActionData(pendingActionResult) {
    if (pendingActionResult && !isErrorResult(pendingActionResult[1])) {
      return {
        [pendingActionResult[0]]: pendingActionResult[1].data
      };
    } else if (state.actionData) {
```

```
      if (Object.keys(state.actionData).length === 0) {
        return null;
      } else {
        return state.actionData;
      }
    }
  }
  function getUpdatedRevalidatingFetchers(revalidatingFetchers) {
    let workingFetchers = new Map(state.fetchers);
    revalidatingFetchers.forEach(rf => {
      let fetcher = workingFetchers.get(rf.key);
      let revalidatingFetcher = getLoadingFetcher(void 0, fetcher ? fetcher.data : void 0);
      workingFetchers.set(rf.key, revalidatingFetcher);
    });
    return workingFetchers;
  }
  async function fetch2(key, routeId, href, opts) {
    abortFetcher(key);
    let flushSync = (opts && opts.flushSync) === true;
    let routesToUse = dataRoutes.activeRoutes;
    let normalizedPath = normalizeTo(state.location, state.matches, basename, href, routeId,
opts?.relative);
    let matches = matchRoutesImpl(routesToUse, normalizedPath, basename, false,
dataRoutes.branches);
    let fogOfWar = checkFogOfWar(matches, routesToUse, normalizedPath);
    if (fogOfWar.active && fogOfWar.matches) {
      matches = fogOfWar.matches;
    }
    if (!matches) {
      setFetcherError(key, routeId, getInternalRouterError(404, {
        pathname: normalizedPath
      }), {
        flushSync
      });
      return;
    }
    let {
      path,
      submission,
      error
    } = normalizeNavigateOptions(true, normalizedPath, opts);
    if (error) {
      setFetcherError(key, routeId, error, {
        flushSync
      });
      return;
    }
    let scopedContext = init.getContext ? await init.getContext() : new RouterContextProvider();
    let preventScrollReset = (opts && opts.preventScrollReset) === true;
```

```
    if (submission && isMutationMethod(submission.formMethod)) {
      await handleFetcherAction(key, routeId, path, matches, scopedContext, fogOfWar.active,
flushSync, preventScrollReset, submission, opts && opts.defaultShouldRevalidate);
      return;
    }
    fetchLoadMatches.set(key, {
      routeId,
      path
    });
    await handleFetcherLoader(key, routeId, path, matches, scopedContext, fogOfWar.active, flushSync,
preventScrollReset, submission);
  }
  async function handleFetcherAction(key, routeId, path, requestMatches, scopedContext, isFogOfWar,
flushSync, preventScrollReset, submission, callSiteDefaultShouldRevalidate) {
    interruptActiveLoads();
    fetchLoadMatches.delete(key);
    let existingFetcher = state.fetchers.get(key);
    updateFetcherState(key, getSubmittingFetcher(submission, existingFetcher), {
      flushSync
    });
    let abortController = new AbortController();
    let fetchRequest = createClientSideRequest(init.history, path, abortController.signal, submission);
    if (isFogOfWar) {
      let discoverResult = await discoverRoutes(requestMatches, new URL(fetchRequest.url).pathname,
fetchRequest.signal, key);
      if (discoverResult.type === "aborted") {
        return;
      } else if (discoverResult.type === "error") {
        setFetcherError(key, routeId, discoverResult.error, {
          flushSync
        });
        return;
      } else if (!discoverResult.matches) {
        setFetcherError(key, routeId, getInternalRouterError(404, {
          pathname: path
        }), {
          flushSync
        });
        return;
      } else {
        requestMatches = discoverResult.matches;
      }
    }
    let match = getTargetMatch(requestMatches, path);
    if (!match.route.action && !match.route.lazy) {
      let error = getInternalRouterError(405, {
        method: submission.formMethod,
        pathname: path,
        routeId
```

```
      });
      setFetcherError(key, routeId, error, {
        flushSync
      });
      return;
    }
    fetchControllers.set(key, abortController);
    let originatingLoadId = incrementingLoadId;
    let fetchMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest, fetchRequest,
path, requestMatches, match, hydrationRouteProperties2, scopedContext);
    let actionResults = await callDataStrategy(fetchRequest, path, fetchMatches, scopedContext, key);
    let actionResult = actionResults[match.route.id];
    if (!actionResult) {
      for (let match2 of fetchMatches) {
        if (actionResults[match2.route.id]) {
          actionResult = actionResults[match2.route.id];
          break;
        }
      }
    }
    if
 (fetchRequest.signal.aborted) {
      if (fetchControllers.get(key) === abortController) {
        fetchControllers.delete(key);
      }
      return;
    }
    if (fetchersQueuedForDeletion.has(key)) {
      if (isRedirectResult(actionResult) || isErrorResult(actionResult)) {
        updateFetcherState(key, getDoneFetcher(void 0));
        return;
      }
    } else {
      if (isRedirectResult(actionResult)) {
        fetchControllers.delete(key);
        if (pendingNavigationLoadId > originatingLoadId) {
          updateFetcherState(key, getDoneFetcher(void 0));
          return;
        } else {
          fetchRedirectIds.add(key);
          updateFetcherState(key, getLoadingFetcher(submission));
          return startRedirectNavigation(fetchRequest, actionResult, false, {
            fetcherSubmission: submission,
            preventScrollReset
          });
        }
      }
      if (isErrorResult(actionResult)) {
        setFetcherError(key, routeId, actionResult.error);
```

```
      return;
    }
  }
  let nextLocation = state.navigation.location || state.location;
  let revalidationRequest = createClientSideRequest(init.history, nextLocation, abortController.signal);
  let routesToUse = dataRoutes.activeRoutes;
  let matches = state.navigation.state !== "idle" ? matchRoutesImpl(routesToUse,
state.navigation.location, basename, false, dataRoutes.branches) : state.matches;
  invariant(matches, "Didn't find any matches after fetcher action");
  let loadId = ++incrementingLoadId;
  fetchReloadIds.set(key, loadId);
  let {
    dsMatches,
    revalidatingFetchers
  } = getMatchesToLoad(revalidationRequest, scopedContext, mapRouteProperties2, manifest,
init.history, state, matches, submission, nextLocation, hydrationRouteProperties2, false,
isRevalidationRequired, cancelledFetcherLoads, fetchersQueuedForDeletion, fetchLoadMatches,
fetchRedirectIds, routesToUse, basename, init.patchRoutesOnNavigation != null, dataRoutes.branches,
[match.route.id, actionResult], callSiteDefaultShouldRevalidate);
  let loadFetcher = getLoadingFetcher(submission, actionResult.data);
  let workingFetchers = new Map(state.fetchers);
  workingFetchers.set(key, loadFetcher);
  revalidatingFetchers.filter(rf => rf.key !== key).forEach(rf => {
    let staleKey = rf.key;
    let existingFetcher2 = workingFetchers.get(staleKey);
    let revalidatingFetcher = getLoadingFetcher(void 0, existingFetcher2 ? existingFetcher2.data : void
0);
    workingFetchers.set(staleKey, revalidatingFetcher);
    abortFetcher(staleKey);
    if (rf.controller) {
      fetchControllers.set(staleKey, rf.controller);
    }
  });
  updateState({
    fetchers: workingFetchers
  });
  let abortPendingFetchRevalidations = () => revalidatingFetchers.forEach(rf =>
abortFetcher(rf.key));
  abortController.signal.addEventListener("abort", abortPendingFetchRevalidations);
  let {
    loaderResults,
    fetcherResults
  } = await callLoadersAndMaybeResolveData(dsMatches, revalidatingFetchers, revalidationRequest,
nextLocation, scopedContext);
  if (abortController.signal.aborted) {
    return;
  }
  abortController.signal.removeEventListener("abort", abortPendingFetchRevalidations);
  fetchReloadIds.delete(key);
```

```
    fetchControllers.delete(key);
    revalidatingFetchers.forEach(r => fetchControllers.delete(r.key));
    let fetcherIsMounted = state.fetchers.has(key);
    let getRedirectStateWithDoneFetcher = s => {
      if (!fetcherIsMounted) return s;
      let workingFetchers2 = new Map(s.fetchers);
      workingFetchers2.set(key, getDoneFetcher(actionResult.data));
      return {
        ...s,
        fetchers: workingFetchers2
      };
    };
    let redirect2 = findRedirect(loaderResults);
    if (redirect2) {
      state = getRedirectStateWithDoneFetcher(state);
      return startRedirectNavigation(revalidationRequest, redirect2.result, false, {
        preventScrollReset
      });
    }
    redirect2 = findRedirect(fetcherResults);
    if (redirect2) {
      fetchRedirectIds.add(redirect2.key);
      state = getRedirectStateWithDoneFetcher(state);
      return startRedirectNavigation(revalidationRequest, redirect2.result, false, {
        preventScrollReset
      });
    }
    let finalFetchers = new Map(state.fetchers);
    if (fetcherIsMounted) {
      finalFetchers.set(key, getDoneFetcher(actionResult.data));
    }
    let {
      loaderData,
      errors
    } = processLoaderData(state, matches, loaderResults, void 0, revalidatingFetchers, fetcherResults,
finalFetchers);
    abortStaleFetchLoads(loadId, finalFetchers);
    if (state.navigation.state === "loading" && loadId > pendingNavigationLoadId) {
      invariant(pendingAction, "Expected pending action");
      pendingNavigationController && pendingNavigationController.abort();
      completeNavigation(state.navigation.location, {
        matches,
        loaderData,
        errors,
        fetchers: finalFetchers
      });
    } else {
      updateState({
        errors,
```

```
      loaderData: mergeLoaderData(state.loaderData, loaderData, matches, errors),
      fetchers: finalFetchers
    });
    isRevalidationRequired = false;
  }
}
 async function handleFetcherLoader(key, routeId, path, matches, scopedContext, isFogOfWar,
flushSync, preventScrollReset, submission) {
  let existingFetcher = state.fetchers.get(key);
  updateFetcherState(key, getLoadingFetcher(submission, existingFetcher ? existingFetcher.data : void
0), {
    flushSync
  });
  let abortController = new AbortController();
  let fetchRequest = createClientSideRequest(init.history, path, abortController.signal);
  if (isFogOfWar) {
    let discoverResult = await discoverRoutes(matches, new URL(fetchRequest.url).pathname,
fetchRequest.signal, key);
    if (discoverResult.type === "aborted") {
      return;
    } else if (discoverResult.type === "error") {
      setFetcherError(key, routeId, discoverResult.error, {
        flushSync
      });
      return;
    } else if (!discoverResult.matches) {
      setFetcherError(key, routeId, getInternalRouterError(404, {
        pathname: path
      }), {
        flushSync
      });
      return;
    } else {
      matches = discoverResult.matches;
    }
  }
  let match = getTargetMatch(matches, path);
  fetchControllers.set(key, abortController);
  let originatingLoadId = incrementingLoadId;
  let dsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest, fetchRequest,
path, matches, match, hydrationRouteProperties2, scopedContext);
  let results = await callDataStrategy(fetchRequest, path, dsMatches, scopedContext, key);
  let result = results[match.route.id];
  if (!result) {
    for (let match2 of matches) {
      if (results[match2.route.id]) {
        result = results[match2.route.id];
        break;
      }
```

```
    }
  }
  if (fetchControllers.get(key) === abortController) {
    fetchControllers.delete(key);
  }
  if (fetchRequest.signal.aborted) {
    return;
  }
  if (fetchersQueuedForDeletion.has(key)) {
    updateFetcherState(key, getDoneFetcher(void 0));
    return;
  }
  if (isRedirectResult(result)) {
    if (pendingNavigationLoadId > originatingLoadId) {
      updateFetcherState(key, getDoneFetcher(void 0));
      return;
    } else {
      fetchRedirectIds.add(key);
      await startRedirectNavigation(fetchRequest, result, false, {
        preventScrollReset
      });
      return;
    }
  }
  if (isErrorResult(result)) {
    setFetcherError(key, routeId, result.error);
    return;
  }
  updateFetcherState(key, getDoneFetcher(result.data));
}
async function startRedirectNavigation(request, redirect2, isNavigation, {
  submission,
  fetcherSubmission,
  preventScrollReset,
  replace: replace2
} = {}) {
  if (!isNavigation) {
    pendingPopstateNavigationDfd?.resolve();
    pendingPopstateNavigationDfd = null;
  }
  if (redirect2.response.headers.has("X-Remix-Revalidate")) {
    isRevalidationRequired = true;
  }
  let location = redirect2.response.headers.get("Location");
  invariant(location, "Expected a Location header on the redirect Response");
  location = normalizeRedirectLocation(location, new URL(request.url), basename, init.history);
  let redirectLocation = createLocation(state.location, location, {
    _isRedirect: true
  });
```

```
    if (isBrowser3) {
      let isDocumentReload = false;
      if (redirect2.response.headers.has("X-Remix-Reload-Document")) {
        isDocumentReload = true;
      } else if (isAbsoluteUrl(location)) {
        const url = createBrowserURLImpl(location, true);
        isDocumentReload =
        // Hard reload if it's an absolute URL to a new origin
        url.origin !== routerWindow.location.origin ||
        // Hard reload if it's an absolute URL that does not match our basename
        stripBasename(url.pathname, basename) == null;
      }
      if (isDocumentReload) {
        if (replace2) {
          routerWindow.location.replace(location);
        } else {
          routerWindow.location.assign(location);
        }
        return;
      }
    }
    pendingNavigationController = null;
    let redirectNavigationType = replace2 === true || redirect2.response.headers.has("X-Remix-
Replace") ? "REPLACE" /* Replace */ : "PUSH" /* Push */;
    let {
      formMethod,
      formAction,
      formEncType
    } = state.navigation;
    if (!submission && !fetcherSubmission && formMethod && formAction && formEncType) {
      submission = getSubmissionFromNavigation(state.navigation);
    }
    let activeSubmission = submission || fetcherSubmission;
    if (redirectPreserveMethodStatusCodes.has(redirect2.response.status) && activeSubmission &&
isMutationMethod(activeSubmission.formMethod)) {

    await startNavigation(redirectNavigationType, redirectLocation, {
        submission: {
          ...activeSubmission,
          formAction: location
        },
        // Preserve these flags across redirects
        preventScrollReset: preventScrollReset || pendingPreventScrollReset,
        enableViewTransition: isNavigation ? pendingViewTransitionEnabled : void 0
      });
    } else {
      let overrideNavigation = getLoadingNavigation(redirectLocation, [], redirectNavigationType,
submission);
      await startNavigation(redirectNavigationType, redirectLocation, {
```

```
        overrideNavigation,
        // Send fetcher submissions through for shouldRevalidate
        fetcherSubmission,
        // Preserve these flags across redirects
        preventScrollReset: preventScrollReset || pendingPreventScrollReset,
        enableViewTransition: isNavigation ? pendingViewTransitionEnabled : void 0
      });
    }
  }
  async function callDataStrategy(request, path, matches, scopedContext, fetcherKey) {
    let results;
    let dataResults = {};
    try {
      results = await callDataStrategyImpl(dataStrategyImpl, request, path, matches, fetcherKey,
scopedContext, false);
    } catch (e) {
      matches.filter(m => m.shouldLoad).forEach(m => {
        dataResults[m.route.id] = {
          type: "error" /* error */,
          error: e
        };
      });
      return dataResults;
    }
    if (request.signal.aborted) {
      return dataResults;
    }
    if (!isMutationMethod(request.method)) {
      for (let match of matches) {
        if (results[match.route.id]?.type === "error" /* error */) {
          break;
        }
        if (!results.hasOwnProperty(match.route.id) && !
state.loaderData.hasOwnProperty(match.route.id) && (!state.errors || !
state.errors.hasOwnProperty(match.route.id)) && match.shouldCallHandler()) {
          results[match.route.id] = {
            type: "error" /* error */,
            result: new Error(`No result returned from dataStrategy for route ${match.route.id}`)
          };
        }
      }
    }
    for (let [routeId, result] of Object.entries(results)) {
      if (isRedirectDataStrategyResult(result)) {
        let response = result.result;
        dataResults[routeId] = {
          type: "redirect" /* redirect */,
          response: normalizeRelativeRoutingRedirectResponse(response, request, routeId, matches,
basename)
```

```
      };
    } else {
      dataResults[routeId] = await convertDataStrategyResultToDataResult(result);
    }
  }
  return dataResults;
}
async function callLoadersAndMaybeResolveData(matches, fetchersToLoad, request, location,
scopedContext) {
  let loaderResultsPromise = callDataStrategy(request, location, matches, scopedContext, null);
  let fetcherResultsPromise = Promise.all(fetchersToLoad.map(async f => {
    if (f.matches && f.match && f.request && f.controller) {
      let results = await callDataStrategy(f.request, f.path, f.matches, scopedContext, f.key);
      let result = results[f.match.route.id];
      return {
        [f.key]: result
      };
    } else {
      return Promise.resolve({
        [f.key]: {
          type: "error" /* error */,
          error: getInternalRouterError(404, {
            pathname: f.path
          })
        }
      });
    }
  }));
  let loaderResults = await loaderResultsPromise;
  let fetcherResults = (await fetcherResultsPromise).reduce((acc, r) => Object.assign(acc, r), {});
  return {
    loaderResults,
    fetcherResults
  };
}
function interruptActiveLoads() {
  isRevalidationRequired = true;
  fetchLoadMatches.forEach((_, key) => {
    if (fetchControllers.has(key)) {
      cancelledFetcherLoads.add(key);
    }
    abortFetcher(key);
  });
}
function updateFetcherState(key, fetcher, opts = {}) {
  let workingFetchers = new Map(state.fetchers);
  workingFetchers.set(key, fetcher);
  updateState({
    fetchers: workingFetchers
```

```
    }, {
      flushSync: (opts && opts.flushSync) === true
    });
  }
  function setFetcherError(key, routeId, error, opts = {}) {
    let boundaryMatch = findNearestBoundary(state.matches, routeId);
    let workingFetchers = new Map(state.fetchers);
    deleteFetcher(workingFetchers, key);
    updateState({
      errors: {
        [boundaryMatch.route.id]: error
      },
      fetchers: workingFetchers
    }, {
      flushSync: (opts && opts.flushSync) === true
    });
  }
  function getFetcher(key) {
    activeFetchers.set(key, (activeFetchers.get(key) || 0) + 1);
    if (fetchersQueuedForDeletion.has(key)) {
      fetchersQueuedForDeletion.delete(key);
    }
    return state.fetchers.get(key) || IDLE_FETCHER;
  }
  function resetFetcher(key, opts) {
    abortFetcher(key, opts?.reason);
    updateFetcherState(key, getDoneFetcher(null));
  }
  function deleteFetcher(fetchers, key) {
    let fetcher = state.fetchers.get(key);
    if (fetchControllers.has(key) && !(fetcher && fetcher.state === "loading" &&
fetchReloadIds.has(key))) {
      abortFetcher(key);
    }
    fetchLoadMatches.delete(key);
    fetchReloadIds.delete(key);
    fetchRedirectIds.delete(key);
    fetchersQueuedForDeletion.delete(key);
    cancelledFetcherLoads.delete(key);
    fetchers.delete(key);
  }
  function queueFetcherForDeletion(key) {
    let count = (activeFetchers.get(key) || 0) - 1;
    if (count <= 0) {
      activeFetchers.delete(key);
      fetchersQueuedForDeletion.add(key);
    } else {
      activeFetchers.set(key, count);
    }
```

```
  updateState({
    fetchers: new Map(state.fetchers)
  });
}
function abortFetcher(key, reason) {
  let controller = fetchControllers.get(key);
  if (controller) {
    controller.abort(reason);
    fetchControllers.delete(key);
  }
}
function markFetchersDone(keys, fetchers) {
  for (let key of keys) {
    let fetcher = fetchers.get(key);
    invariant(fetcher, `Expected fetcher: ${key}`);
    let doneFetcher = getDoneFetcher(fetcher.data);
    fetchers.set(key, doneFetcher);
  }
}
function markFetchRedirectsDone(fetchers) {
  let doneKeys = [];
  let didUpdateFetchers = false;
  for (let key of fetchRedirectIds) {
    let fetcher = fetchers.get(key);
    invariant(fetcher, `Expected fetcher: ${key}`);
    if (fetcher.state === "loading") {
      fetchRedirectIds.delete(key);
      doneKeys.push(key);
      didUpdateFetchers = true;
    }
  }
  markFetchersDone(doneKeys, fetchers);
  return didUpdateFetchers;
}
function abortStaleFetchLoads(landedId, fetchers) {
  let yeetedKeys = [];
  for (let [key, id] of fetchReloadIds) {
    if (id < landedId) {
      let fetcher = fetchers.get(key);
      invariant(fetcher, `Expected fetcher: ${key}`);
      if (fetcher.state === "loading") {
        abortFetcher(key);
        fetchReloadIds.delete(key);
        yeetedKeys.push(key);
      }
    }
  }
  markFetchersDone(yeetedKeys, fetchers);
  return yeetedKeys.length > 0;
```

```
  }
  function getBlocker(key, fn) {
    let blocker = state.blockers.get(key) || IDLE_BLOCKER;
    if (blockerFunctions.get(key) !== fn) {
      blockerFunctions.set(key, fn);
    }
    return blocker;
  }
  function deleteBlocker(key) {
    state.blockers.delete(key);
    blockerFunctions.delete(key);
  }
  function updateBlocker(key, newBlocker) {
    let blocker = state.blockers.get(key) || IDLE_BLOCKER;
    invariant(blocker.state === "unblocked" && newBlocker.state === "blocked" || blocker.state ===
"blocked" && newBlocker.state === "blocked" || blocker.state === "blocked" && newBlocker.state
=== "proceeding" || blocker.state === "blocked" && newBlocker.state === "unblocked" || blocker.state
=== "proceeding" && newBlocker.state === "unblocked", `Invalid blocker state transition: $
{blocker.state} -> ${newBlocker.state}`);
    let blockers = new Map(state.blockers);
    blockers.set(key, newBlocker);
    updateState({
      blockers
    });
  }
  function shouldBlockNavigation({
    currentLocation,
    nextLocation,
    historyAction
  }) {
    if (blockerFunctions.size === 0) {
      return;
    }
    if (blockerFunctions.size > 1) {
      warning(false, "A router only supports one blocker at a time");
    }
    let entries = Array.from(blockerFunctions.entries());
    let [blockerKey, blockerFunction] = entries[entries.length - 1];
    let blocker = state.blockers.get(blockerKey);
    if (blocker && blocker.state === "proceeding") {
      return;
    }
    if (blockerFunction({
      currentLocation,
      nextLocation,
      historyAction
    })) {
      return blockerKey;
    }
```

```
  }
  function handleNavigational404(pathname) {
    let error = getInternalRouterError(404, {
      pathname
    });
    let routesToUse = dataRoutes.activeRoutes;
    let {
      matches,
      route
    } = getShortCircuitMatches(routesToUse);
    return {
      notFoundMatches: matches,
      route,
      error
    };
  }
  function enableScrollRestoration(positions, getPosition, getKey) {
    savedScrollPositions2 = positions;
    getScrollPosition = getPosition;
    getScrollRestorationKey2 = getKey || null;
    if (!initialScrollRestored && state.navigation === IDLE_NAVIGATION) {
      initialScrollRestored = true;
      let y = getSavedScrollPosition(state.location, state.matches);
      if (y != null) {
        updateState({
          restoreScrollPosition: y
        });
      }
    }
    return () => {
      savedScrollPositions2 = null;
      getScrollPosition = null;
      getScrollRestorationKey2 = null;
    };
  }
  function getScrollKey(location, matches) {
    if (getScrollRestorationKey2) {
      let key = getScrollRestorationKey2(location, matches.map(m =>
convertRouteMatchToUiMatch(m, state.loaderData)));
      return key || location.key;
    }
    return location.key;
  }
  function saveScrollPosition(location, matches) {

  if (savedScrollPositions2 && getScrollPosition) {
      let key = getScrollKey(location, matches);
      savedScrollPositions2[key] = getScrollPosition();
    }
```

```
}
function getSavedScrollPosition(location, matches) {
  if (savedScrollPositions2) {
    let key = getScrollKey(location, matches);
    let y = savedScrollPositions2[key];
    if (typeof y === "number") {
      return y;
    }
  }
  return null;
}
function checkFogOfWar(matches, routesToUse, pathname) {
  if (init.patchRoutesOnNavigation) {
    let activeBranches = dataRoutes.branches;
    if (!matches) {
      let fogMatches = matchRoutesImpl(routesToUse, pathname, basename, true, activeBranches);
      return {
        active: true,
        matches: fogMatches || []
      };
    } else {
      if (Object.keys(matches[0].params).length > 0) {
        let partialMatches = matchRoutesImpl(routesToUse, pathname, basename, true, activeBranches);
        return {
          active: true,
          matches: partialMatches
        };
      }
    }
  }
  return {
    active: false,
    matches: null
  };
}
async function discoverRoutes(matches, pathname, signal, fetcherKey) {
  if (!init.patchRoutesOnNavigation) {
    return {
      type: "success",
      matches
    };
  }
  let partialMatches = matches;
  while (true) {
    let localManifest = manifest;
    try {
      await init.patchRoutesOnNavigation({
        signal,
        path: pathname,
```

```
        matches: partialMatches,
        fetcherKey,
        patch: (routeId, children) => {
          if (signal.aborted) return;
          patchRoutesImpl(routeId, children, dataRoutes, localManifest, mapRouteProperties2, false);
        }
      });
    } catch (e) {
      return {
        type: "error",
        error: e,
        partialMatches
      };
    }
    if (signal.aborted) {
      return {
        type: "aborted"
      };
    }
    let activeBranches = dataRoutes.branches;
    let newMatches = matchRoutesImpl(dataRoutes.activeRoutes, pathname, basename, false,
activeBranches);
    let newPartialMatches = null;
    if (newMatches) {
      if (Object.keys(newMatches[0].params).length === 0) {
        return {
          type: "success",
          matches: newMatches
        };
      } else {
        newPartialMatches = matchRoutesImpl(dataRoutes.activeRoutes, pathname, basename, true,
activeBranches);
        let matchedDeeper = newPartialMatches && partialMatches.length < newPartialMatches.length
&& compareMatches(partialMatches, newPartialMatches.slice(0, partialMatches.length));
        if (!matchedDeeper) {
          return {
            type: "success",
            matches: newMatches
          };
        }
      }
    }
    if (!newPartialMatches) {
      newPartialMatches = matchRoutesImpl(dataRoutes.activeRoutes, pathname, basename, true,
activeBranches);
    }
    if (!newPartialMatches || compareMatches(partialMatches, newPartialMatches)) {
      return {
        type: "success",
```

```
        matches: null
      };
    }
    partialMatches = newPartialMatches;
  }
}
function compareMatches(a, b) {
  return a.length === b.length && a.every((m, i) => m.route.id === b[i].route.id);
}
function _internalSetRoutes(newRoutes) {
  manifest = {};
  dataRoutes.setHmrRoutes(convertRoutesToDataRoutes(newRoutes, mapRouteProperties2, void 0,
manifest));
}
function patchRoutes(routeId, children, unstable_allowElementMutations = false) {
  patchRoutesImpl(routeId, children, dataRoutes, manifest, mapRouteProperties2,
unstable_allowElementMutations);
  if (!dataRoutes.hasHMRRoutes) {
    updateState({});
  }
}
router = {
  get basename() {
    return basename;
  },
  get future() {
    return future;
  },
  get state() {
    return state;
  },
  get routes() {
    return dataRoutes.stableRoutes;
  },
  get branches() {
    return dataRoutes.branches;
  },
  get manifest() {
    return manifest;
  },
  get window() {
    return routerWindow;
  },
  initialize,
  subscribe,
  enableScrollRestoration,
  navigate,
  fetch: fetch2,
  revalidate,
```

```
    // Passthrough to history-aware createHref used by useHref so we get proper
    // hash-aware URLs in DOM paths
    createHref: to => init.history.createHref(to),
    encodeLocation: to => init.history.encodeLocation(to),
    getFetcher,
    resetFetcher,
    deleteFetcher: queueFetcherForDeletion,
    dispose,
    getBlocker,
    deleteBlocker,
    patchRoutes,
    _internalFetchControllers: fetchControllers,
    // TODO: Remove setRoutes, it's temporary to avoid dealing with
    // updating the tree while validating the update algorithm.
    _internalSetRoutes,
    _internalSetStateDoNotUseOrYouWillBreakYourApp(newState) {
      updateState(newState);
    }
  };
  if (init.instrumentations) {
    router = instrumentClientSideRouter(router, init.instrumentations.map(i => i.router).filter(Boolean));
  }
  return router;
}
function createStaticHandler(routes, opts) {
  invariant(routes.length > 0, "You must provide a non-empty routes array to createStaticHandler");
  let manifest = {};
  let basename = (opts ? opts.basename : null) || "/";
  let _mapRouteProperties = opts?.mapRouteProperties || defaultMapRouteProperties;
  let mapRouteProperties2 = _mapRouteProperties;
  let future = {
    ...opts?.future
  };
  if (opts?.instrumentations) {
    let instrumentations = opts.instrumentations;
    mapRouteProperties2 = route => {
      return {
        ..._mapRouteProperties(route),
        ...getRouteInstrumentationUpdates(instrumentations.map(i => i.route).filter(Boolean), route)
      };
    };
  }
  let dataRoutes = convertRoutesToDataRoutes(routes, mapRouteProperties2, void 0, manifest);
  let routeBranches = flattenAndRankRoutes(dataRoutes);
  async function query(request, {
    requestContext,
    filterMatchesToLoad,
    skipLoaderErrorBubbling,
    skipRevalidation,
```

```
    dataStrategy,
    generateMiddlewareResponse,
    normalizePath
  } = {}) {
    let normalizePathImpl = normalizePath || defaultNormalizePath;
    let method = request.method;
    let location = createLocation("", normalizePathImpl(request), null, "default");
    let matches = matchRoutesImpl(dataRoutes, location, basename, false, routeBranches);
    requestContext = requestContext != null ? requestContext : new RouterContextProvider();
    if (!isValidMethod(method) && method !== "HEAD") {
      let error = getInternalRouterError(405, {
        method
      });
      let {
        matches: methodNotAllowedMatches,
        route
      } = getShortCircuitMatches(dataRoutes);
      let staticContext = {
        basename,
        location,
        matches: methodNotAllowedMatches,
        loaderData: {},
        actionData: null,
        errors: {
          [route.id]: error
        },
        statusCode: error.status,
        loaderHeaders: {},
        actionHeaders: {}
      };
      return generateMiddlewareResponse ? generateMiddlewareResponse(() =>
Promise.resolve(staticContext)) : staticContext;
    } else if (!matches) {
      let error = getInternalRouterError(404, {
        pathname: location.pathname
      });
      let {
        matches: notFoundMatches,
        route
      } = getShortCircuitMatches(dataRoutes);
      let staticContext = {
        basename,
        location,
        matches: notFoundMatches,
        loaderData: {},
        actionData: null,
        errors: {
          [route.id]: error
        },
```

```
        statusCode: error.status,
        loaderHeaders: {},
        actionHeaders: {}
      };
      return generateMiddlewareResponse ? generateMiddlewareResponse(() =>
Promise.resolve(staticContext)) : staticContext;
    }
    if (generateMiddlewareResponse) {
      invariant(requestContext instanceof RouterContextProvider, "When using middleware in
`staticHandler.query()`, any provided `requestContext` must be an instance of
`RouterContextProvider`");
      try {
        await loadLazyMiddlewareForMatches(matches, manifest, mapRouteProperties2);
        let renderedStaticContext;
        let response = await runServerMiddlewarePipeline({
          request,
          url: createDataFunctionUrl(request, location),
          pattern: getRoutePattern(matches),
          matches,
          params: matches[0].params,
          // If we're calling middleware then it must be enabled so we can cast
          // this to the proper type knowing it's not an `AppLoadContext`
          context: requestContext
        }, async () => {
          let res = await generateMiddlewareResponse(async (revalidationRequest, opts2 = {}) => {
            let result2 = await queryImpl(revalidationRequest, location, matches, requestContext,
dataStrategy || null, skipLoaderErrorBubbling === true, null, "filterMatchesToLoad" in opts2 ?
opts2.filterMatchesToLoad ?? null : filterMatchesToLoad ?? null, skipRevalidation === true);
            if (isResponse(result2)) {
              return result2;
            }
            renderedStaticContext = {
              location,
              basename,
              ...result2
            };
            return renderedStaticContext;
          });
          return res;
        }, async (error, routeId) => {
          if (isRedirectResponse(error)) {
            return error;
          }
          if (isResponse(error)) {
            try {
              error = new ErrorResponseImpl(error.status, error.statusText, await
parseResponseBody(error));
            } catch (e) {
              error = e;
```

```
          }
        }
        if (isDataWithResponseInit(error)) {
          error = dataWithResponseInitToErrorResponse(error);
        }
        if (renderedStaticContext) {
          if (routeId
 in renderedStaticContext.loaderData) {
            renderedStaticContext.loaderData[routeId] = void 0;
          }
          let staticContext = getStaticContextFromError(dataRoutes, renderedStaticContext, error,
skipLoaderErrorBubbling ? routeId : findNearestBoundary(matches, routeId).route.id);
          return generateMiddlewareResponse(() => Promise.resolve(staticContext));
        } else {
          let boundaryRouteId = skipLoaderErrorBubbling ? routeId : findNearestBoundary(matches,
matches.find(m => m.route.id === routeId || m.route.loader)?.route.id || routeId).route.id;
          let staticContext = {
            matches,
            location,
            basename,
            loaderData: {},
            actionData: null,
            errors: {
              [boundaryRouteId]: error
            },
            statusCode: isRouteErrorResponse(error) ? error.status : 500,
            actionHeaders: {},
            loaderHeaders: {}
          };
          return generateMiddlewareResponse(() => Promise.resolve(staticContext));
        }
      });
      invariant(isResponse(response), "Expected a response in query()");
      return response;
    } catch (e) {
      if (isResponse(e)) {
        return e;
      }
      throw e;
    }
  }
  let result = await queryImpl(request, location, matches, requestContext, dataStrategy || null,
skipLoaderErrorBubbling === true, null, filterMatchesToLoad || null, skipRevalidation === true);
  if (isResponse(result)) {
    return result;
  }
  return {
    location,
    basename,
```

```
      ...result
    };
  }
  async function queryRoute(request, {
    routeId,
    requestContext,
    dataStrategy,
    generateMiddlewareResponse,
    normalizePath
  } = {}) {
    let normalizePathImpl = normalizePath || defaultNormalizePath;
    let method = request.method;
    let location = createLocation("", normalizePathImpl(request), null, "default");
    let matches = matchRoutesImpl(dataRoutes, location, basename, false, routeBranches);
    requestContext = requestContext != null ? requestContext : new RouterContextProvider();
    if (!isValidMethod(method) && method !== "HEAD" && method !== "OPTIONS") {
      throw getInternalRouterError(405, {
        method
      });
    } else if (!matches) {
      throw getInternalRouterError(404, {
        pathname: location.pathname
      });
    }
    let match = routeId ? matches.find(m => m.route.id === routeId) : getTargetMatch(matches,
location);
    if (routeId && !match) {
      throw getInternalRouterError(403, {
        pathname: location.pathname,
        routeId
      });
    } else if (!match) {
      throw getInternalRouterError(404, {
        pathname: location.pathname
      });
    }
    if (generateMiddlewareResponse) {
      invariant(requestContext instanceof RouterContextProvider, "When using middleware in
`staticHandler.queryRoute()`, any provided `requestContext` must be an instance of
`RouterContextProvider`");
      await loadLazyMiddlewareForMatches(matches, manifest, mapRouteProperties2);
      let response = await runServerMiddlewarePipeline({
        request,
        url: createDataFunctionUrl(request, location),
        pattern: getRoutePattern(matches),
        matches,
        params: matches[0].params,
        // If we're calling middleware then it must be enabled so we can cast
        // this to the proper type knowing it's not an `AppLoadContext`
```

```
      context: requestContext
    }, async () => {
      let res = await generateMiddlewareResponse(async innerRequest => {
        let result2 = await queryImpl(innerRequest, location, matches, requestContext, dataStrategy ||
null, false, match, null, false);
        let processed = handleQueryResult(result2);
        return isResponse(processed) ? processed : typeof processed === "string" ? new
Response(processed) : Response.json(processed);
      });
      return res;
    }, error => {
      if (isDataWithResponseInit(error)) {
        return Promise.resolve(dataWithResponseInitToResponse(error));
      }
      if (isResponse(error)) {
        return Promise.resolve(error);
      }
      throw error;
    });
    return response;
  }
  let result = await queryImpl(request, location, matches, requestContext, dataStrategy || null, false,
match, null, false);
  return handleQueryResult(result);
  function handleQueryResult(result2) {
    if (isResponse(result2)) {
      return result2;
    }
    let error = result2.errors ? Object.values(result2.errors)[0] : void 0;
    if (error !== void 0) {
      throw error;
    }
    if (result2.actionData) {
      return Object.values(result2.actionData)[0];
    }
    if (result2.loaderData) {
      return Object.values(result2.loaderData)[0];
    }
    return void 0;
  }
}
 async function queryImpl(request, location, matches, requestContext, dataStrategy,
skipLoaderErrorBubbling, routeMatch, filterMatchesToLoad, skipRevalidation) {
  invariant(request.signal, "query()/queryRoute() requests must contain an AbortController signal");
  try {
    if (isMutationMethod(request.method)) {
      let result2 = await submit(request, location, matches, routeMatch || getTargetMatch(matches,
location), requestContext, dataStrategy, skipLoaderErrorBubbling, routeMatch != null,
filterMatchesToLoad, skipRevalidation);
```

```
      return result2;
    }
    let result = await loadRouteData(request, location, matches, requestContext, dataStrategy,
skipLoaderErrorBubbling, routeMatch, filterMatchesToLoad);
    return isResponse(result) ? result : {
      ...result,
      actionData: null,
      actionHeaders: {}
    };
  } catch (e) {
    if (isDataStrategyResult(e) && isResponse(e.result)) {
      if (e.type === "error" /* error */) {
        throw e.result;
      }
      return e.result;
    }
    if (isRedirectResponse(e)) {
      return e;
    }
    throw e;
  }
}
 async function submit(request, location, matches, actionMatch, requestContext, dataStrategy,
skipLoaderErrorBubbling, isRouteRequest, filterMatchesToLoad, skipRevalidation) {
  let result;
  if (!actionMatch.route.action && !actionMatch.route.lazy) {
    let error = getInternalRouterError(405, {
      method: request.method,
      pathname: new URL(request.url).pathname,
      routeId: actionMatch.route.id
    });
    if (isRouteRequest) {
      throw error;
    }
    result = {
      type: "error" /* error */,
      error
    };
  } else {
    let dsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest, request,
location, matches, actionMatch, [], requestContext);
    let results = await callDataStrategy(request, location, dsMatches, isRouteRequest, requestContext,
dataStrategy);
    result = results[actionMatch.route.id];
    if (request.signal.aborted) {
      throwStaticHandlerAbortedError(request, isRouteRequest);
    }
  }
  if (isRedirectResult(result)) {
```

```
      throw new Response(null, {
        status: result.response.status,
        headers: {
          Location: result.response.headers.get("Location")
        }
      });
    }
    if (isRouteRequest) {
      if (isErrorResult(result)) {
        throw result.error;
      }
      return {
        matches: [actionMatch],
        loaderData: {},
        actionData: {
          [actionMatch.route.id]: result.data
        },
        errors: null,
        // Note: statusCode + headers are unused here since queryRoute will
        // return the raw Response or value
        statusCode: 200,
        loaderHeaders: {},
        actionHeaders: {}
      };
    }
    if (skipRevalidation) {
      if (isErrorResult(result)) {
        let boundaryMatch = skipLoaderErrorBubbling ? actionMatch : findNearestBoundary(matches,
actionMatch.route.id);
        return {
          statusCode: isRouteErrorResponse(result.error) ? result.error.status : result.statusCode != null ?
result.statusCode : 500,
          actionData: null,
          actionHeaders: {
            ...(result.headers ? {
              [actionMatch.route.id]: result.headers
            } : {})
          },
          matches,
          loaderData: {},
          errors: {
            [boundaryMatch.route.id]: result.error
          },
          loaderHeaders: {}
        };
      } else {
        return {
          actionData: {
            [actionMatch.route.id]: result.data
```

```
        },
        actionHeaders: result.headers ? {
          [actionMatch.route.id]: result.headers
        } : {},
        matches,
        loaderData: {},
        errors: null,
        statusCode: result.statusCode || 200,
        loaderHeaders: {}
      };
    }
  }
  let loaderRequest = new Request(request.url, {
    headers: request.headers,
    redirect: request.redirect,
    signal: request.signal
  });
  if (isErrorResult(result)) {
    let boundaryMatch = skipLoaderErrorBubbling ? actionMatch : findNearestBoundary(matches,
actionMatch.route.id);
    let handlerContext2 = await loadRouteData(loaderRequest, location, matches, requestContext,
dataStrategy, skipLoaderErrorBubbling, null, filterMatchesToLoad, [boundaryMatch.route.id, result]);
    return {
      ...handlerContext2,
      statusCode: isRouteErrorResponse(result.error) ? result.error.status : result.statusCode != null ?
result.statusCode : 500,
      actionData: null,
      actionHeaders: {
        ...(result.headers ? {
          [actionMatch.route.id]: result.headers
        } : {})
      }
    };
  }
  let handlerContext = await loadRouteData(loaderRequest, location, matches, requestContext,
dataStrategy, skipLoaderErrorBubbling, null, filterMatchesToLoad);
  return {
    ...handlerContext,
    actionData: {

  [actionMatch.route.id]: result.data
    },
    // action status codes take precedence over loader status codes
    ...(result.statusCode ? {
      statusCode: result.statusCode
    } : {}),
    actionHeaders: result.headers ? {
      [actionMatch.route.id]: result.headers
    } : {}
```

```
    };
  }
  async function loadRouteData(request, location, matches, requestContext, dataStrategy,
skipLoaderErrorBubbling, routeMatch, filterMatchesToLoad, pendingActionResult) {
    let isRouteRequest = routeMatch != null;
    if (isRouteRequest && !routeMatch?.route.loader && !routeMatch?.route.lazy) {
      throw getInternalRouterError(400, {
        method: request.method,
        pathname: new URL(request.url).pathname,
        routeId: routeMatch?.route.id
      });
    }
    let dsMatches;
    if (routeMatch) {
      dsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest, request, location,
matches, routeMatch, [], requestContext);
    } else {
      let maxIdx = pendingActionResult && isErrorResult(pendingActionResult[1]) ?
      // Up to but not including the boundary
      matches.findIndex(m => m.route.id === pendingActionResult[0]) - 1 : void 0;
      let pattern = getRoutePattern(matches);
      dsMatches = matches.map((match, index) => {
        if (maxIdx != null && index > maxIdx) {
          return getDataStrategyMatch(mapRouteProperties2, manifest, request, location, pattern, match,
[], requestContext, false);
        }
        return getDataStrategyMatch(mapRouteProperties2, manifest, request, location, pattern, match, [],
requestContext, (match.route.loader || match.route.lazy) != null && (!filterMatchesToLoad ||
filterMatchesToLoad(match)));
      });
    }
    if (!dataStrategy && !dsMatches.some(m => m.shouldLoad)) {
      return {
        matches,
        loaderData: {},
        errors: pendingActionResult && isErrorResult(pendingActionResult[1]) ? {
          [pendingActionResult[0]]: pendingActionResult[1].error
        } : null,
        statusCode: 200,
        loaderHeaders: {}
      };
    }
    let results = await callDataStrategy(request, location, dsMatches, isRouteRequest, requestContext,
dataStrategy);
    if (request.signal.aborted) {
      throwStaticHandlerAbortedError(request, isRouteRequest);
    }
    let handlerContext = processRouteLoaderData(matches, results, pendingActionResult, true,
skipLoaderErrorBubbling);
```

```
    return {
      ...handlerContext,
      matches
    };
  }
  async function callDataStrategy(request, location, matches, isRouteRequest, requestContext,
dataStrategy) {
    let results = await callDataStrategyImpl(dataStrategy || defaultDataStrategy, request, location,
matches, null, requestContext, true);
    let dataResults = {};
    await Promise.all(matches.map(async match => {
      if (!(match.route.id in results)) {
        return;
      }
      let result = results[match.route.id];
      if (isRedirectDataStrategyResult(result)) {
        let response = result.result;
        throw normalizeRelativeRoutingRedirectResponse(response, request, match.route.id, matches,
basename);
      }
      if (isRouteRequest) {
        if (isResponse(result.result)) {
          throw result;
        } else if (isDataWithResponseInit(result.result)) {
          throw dataWithResponseInitToResponse(result.result);
        }
      }
      dataResults[match.route.id] = await convertDataStrategyResultToDataResult(result);
    }));
    return dataResults;
  }
  return {
    dataRoutes,
    _internalRouteBranches: routeBranches,
    query,
    queryRoute
  };
}
function getStaticContextFromError(routes, handlerContext, error, boundaryId) {
  let errorBoundaryId = boundaryId || handlerContext._deepestRenderedBoundaryId || routes[0].id;
  return {
    ...handlerContext,
    statusCode: isRouteErrorResponse(error) ? error.status : 500,
    errors: {
      [errorBoundaryId]: error
    }
  };
}
function throwStaticHandlerAbortedError(request, isRouteRequest) {
```

```
  if (request.signal.reason !== void 0) {
    throw request.signal.reason;
  }
  let method = isRouteRequest ? "queryRoute" : "query";
  throw new Error(`${method}() call aborted without an \`AbortSignal.reason\`: ${request.method} $
{request.url}`);
}
function isSubmissionNavigation(opts) {
  return opts != null && ("formData" in opts && opts.formData != null || "body" in opts &&
opts.body !== void 0);
}
function defaultNormalizePath(request) {
  let url = new URL(request.url);
  return {
    pathname: url.pathname,
    search: url.search,
    hash: url.hash
  };
}
function normalizeTo(location, matches, basename, to, fromRouteId, relative) {
  let contextualMatches;
  let activeRouteMatch;
  if (fromRouteId) {
    contextualMatches = [];
    for (let match of matches) {
      contextualMatches.push(match);
      if (match.route.id === fromRouteId) {
        activeRouteMatch = match;
        break;
      }
    }
  } else {
    contextualMatches = matches;
    activeRouteMatch = matches[matches.length - 1];
  }
  let path = resolveTo(to ? to : ".", getResolveToMatches(contextualMatches),
stripBasename(location.pathname, basename) || location.pathname, relative === "path");
  if (to == null) {
    path.search = location.search;
    path.hash = location.hash;
  }
  if ((to == null || to === "" || to === ".") && activeRouteMatch) {
    let nakedIndex = hasNakedIndexQuery(path.search);
    if (activeRouteMatch.route.index && !nakedIndex) {
      path.search = path.search ? path.search.replace(/^\?/, "?index&") : "?index";
    } else if (!activeRouteMatch.route.index && nakedIndex) {
      let params = new URLSearchParams(path.search);
      let indexValues = params.getAll("index");
      params.delete("index");
```

```
      indexValues.filter(v => v).forEach(v => params.append("index", v));
      let qs = params.toString();
      path.search = qs ? `?${qs}` : "";
    }
  }
  if (basename !== "/") {
    path.pathname = prependBasename({
      basename,
      pathname: path.pathname
    });
  }
  return createPath(path);
}
function normalizeNavigateOptions(isFetcher, path, opts) {
  if (!opts || !isSubmissionNavigation(opts)) {
    return {
      path
    };
  }
  if (opts.formMethod && !isValidMethod(opts.formMethod)) {
    return {
      path,
      error: getInternalRouterError(405, {
        method: opts.formMethod
      })
    };
  }
  let getInvalidBodyError = () => ({
    path,
    error: getInternalRouterError(400, {
      type: "invalid-body"
    })
  });
  let rawFormMethod = opts.formMethod || "get";
  let formMethod = rawFormMethod.toUpperCase();
  let formAction = stripHashFromPath(path);
  if (opts.body !== void 0) {
    if (opts.formEncType === "text/plain") {
      if (!isMutationMethod(formMethod)) {
        return getInvalidBodyError();
      }
      let text = typeof opts.body === "string" ? opts.body : opts.body instanceof FormData || opts.body
instanceof URLSearchParams ?
      // https://html.spec.whatwg.org/multipage/form-control-infrastructure.html#plain-text-form-data
      Array.from(opts.body.entries()).reduce((acc, [name, value]) => `${acc}${name}=${value}
`, "") : String(opts.body);
      return {
        path,
        submission: {
```

```
        formMethod,
        formAction,
        formEncType: opts.formEncType,
        formData: void 0,
        json: void 0,
        text
      }
    };
  } else if (opts.formEncType === "application/json") {
    if (!isMutationMethod(formMethod)) {
      return getInvalidBodyError();
    }
    try {
      let json = typeof opts.body === "string" ? JSON.parse(opts.body) : opts.body;
      return {
        path,
        submission: {
          formMethod,
          formAction,
          formEncType: opts.formEncType,
          formData: void 0,
          json,
          text: void 0
        }
      };
    } catch (e) {
      return getInvalidBodyError();
    }
  }
}
invariant(typeof FormData === "function", "FormData is not available in this environment");
let searchParams;
let formData;
if (opts.formData) {
  searchParams = convertFormDataToSearchParams(opts.formData);
  formData = opts.formData;
} else if (opts.body instanceof FormData) {
  searchParams = convertFormDataToSearchParams(opts.body);
  formData = opts.body;
} else if (opts.body instanceof URLSearchParams) {
  searchParams = opts.body;
  formData = convertSearchParamsToFormData(searchParams);
} else if (opts.body == null) {
  searchParams = new URLSearchParams();
  formData = new FormData();
} else {
  try {
    searchParams = new URLSearchParams(opts.body);
    formData = convertSearchParamsToFormData(searchParams);
```

```
    } catch (e) {
      return getInvalidBodyError();
    }
  }
  let submission = {
    formMethod,
    formAction,
    formEncType: opts && opts.formEncType || "application/x-www-form-urlencoded",
    formData,
    json: void 0,
    text: void 0
  };
  if (isMutationMethod(submission.formMethod)) {
    return {
      path,
      submission
    };
  }
  let parsedPath = parsePath(path);
  if (isFetcher && parsedPath.search && hasNakedIndexQuery(parsedPath.search)) {
    searchParams.append("index", "");
  }
  parsedPath.search = `?${searchParams}`;
  return {
    path: createPath(parsedPath),
    submission
  };
}
function getMatchesToLoad(request, scopedContext, mapRouteProperties2, manifest, history, state,
matches, submission, location, lazyRoutePropertiesToSkip, initialHydration, isRevalidationRequired,
cancelledFetcherLoads, fetchersQueuedForDeletion, fetchLoadMatches, fetchRedirectIds,
routesToUse, basename, hasPatchRoutesOnNavigation, branches, pendingActionResult,
callSiteDefaultShouldRevalidate) {
  let actionResult = pendingActionResult ? isErrorResult(pendingActionResult[1]) ?
pendingActionResult[1].error : pendingActionResult[1].data : void 0;
  let currentUrl = history.createURL(state.location);

  let nextUrl = history.createURL(location);
  let maxIdx;
  if (initialHydration && state.errors) {
    let boundaryId = Object.keys(state.errors)[0];
    maxIdx = matches.findIndex(m => m.route.id === boundaryId);
  } else if (pendingActionResult && isErrorResult(pendingActionResult[1])) {
    let boundaryId = pendingActionResult[0];
    maxIdx = matches.findIndex(m => m.route.id === boundaryId) - 1;
  }
  let actionStatus = pendingActionResult ? pendingActionResult[1].statusCode : void 0;
  let shouldSkipRevalidation = actionStatus && actionStatus >= 400;
  let baseShouldRevalidateArgs = {
```

```
    currentUrl,
    currentParams: state.matches[0]?.params || {},
    nextUrl,
    nextParams: matches[0].params,
    ...submission,
    actionResult,
    actionStatus
  };
  let pattern = getRoutePattern(matches);
  let dsMatches = matches.map((match, index) => {
    let {
      route
    } = match;
    let forceShouldLoad = null;
    if (maxIdx != null && index > maxIdx) {
      forceShouldLoad = false;
    } else if (route.lazy) {
      forceShouldLoad = true;
    } else if (!routeHasLoaderOrMiddleware(route)) {
      forceShouldLoad = false;
    } else if (initialHydration) {
      let {
        shouldLoad: shouldLoad2
      } = getRouteHydrationStatus(route, state.loaderData, state.errors);
      forceShouldLoad = shouldLoad2;
    } else if (isNewLoader(state.loaderData, state.matches[index], match)) {
      forceShouldLoad = true;
    }
    if (forceShouldLoad !== null) {
      return getDataStrategyMatch(mapRouteProperties2, manifest, request, location, pattern, match,
lazyRoutePropertiesToSkip, scopedContext, forceShouldLoad);
    }
    let defaultShouldRevalidate = false;
    if (typeof callSiteDefaultShouldRevalidate === "boolean") {
      defaultShouldRevalidate = callSiteDefaultShouldRevalidate;
    } else if (shouldSkipRevalidation) {
      defaultShouldRevalidate = false;
    } else if (isRevalidationRequired) {
      defaultShouldRevalidate = true;
    } else if (currentUrl.pathname + currentUrl.search === nextUrl.pathname + nextUrl.search) {
      defaultShouldRevalidate = true;
    } else if (currentUrl.search !== nextUrl.search) {
      defaultShouldRevalidate = true;
    } else if (isNewRouteInstance(state.matches[index], match)) {
      defaultShouldRevalidate = true;
    }
    let shouldRevalidateArgs = {
      ...baseShouldRevalidateArgs,
      defaultShouldRevalidate
```

```
    };
    let shouldLoad = shouldRevalidateLoader(match, shouldRevalidateArgs);
    return getDataStrategyMatch(mapRouteProperties2, manifest, request, location, pattern, match,
lazyRoutePropertiesToSkip, scopedContext, shouldLoad, shouldRevalidateArgs,
callSiteDefaultShouldRevalidate);
  });
  let revalidatingFetchers = [];
  fetchLoadMatches.forEach((f, key) => {
    if (initialHydration || !matches.some(m => m.route.id === f.routeId) ||
fetchersQueuedForDeletion.has(key)) {
      return;
    }
    let fetcher = state.fetchers.get(key);
    let isMidInitialLoad = fetcher && fetcher.state !== "idle" && fetcher.data === void 0;
    let fetcherMatches = matchRoutesImpl(routesToUse, f.path, basename ?? "/", false, branches);
    if (!fetcherMatches) {
      if (hasPatchRoutesOnNavigation && isMidInitialLoad) {
        return;
      }
      revalidatingFetchers.push({
        key,
        routeId: f.routeId,
        path: f.path,
        matches: null,
        match: null,
        request: null,
        controller: null
      });
      return;
    }
    if (fetchRedirectIds.has(key)) {
      return;
    }
    let fetcherMatch = getTargetMatch(fetcherMatches, f.path);
    let fetchController = new AbortController();
    let fetchRequest = createClientSideRequest(history, f.path, fetchController.signal);
    let fetcherDsMatches = null;
    if (cancelledFetcherLoads.has(key)) {
      cancelledFetcherLoads.delete(key);
      fetcherDsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest,
fetchRequest, f.path, fetcherMatches, fetcherMatch, lazyRoutePropertiesToSkip, scopedContext);
    } else if (isMidInitialLoad) {
      if (isRevalidationRequired) {
        fetcherDsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest,
fetchRequest, f.path, fetcherMatches, fetcherMatch, lazyRoutePropertiesToSkip, scopedContext);
      }
    } else {
      let defaultShouldRevalidate;
      if (typeof callSiteDefaultShouldRevalidate === "boolean") {
```

```
        defaultShouldRevalidate = callSiteDefaultShouldRevalidate;
      } else if (shouldSkipRevalidation) {
        defaultShouldRevalidate = false;
      } else {
        defaultShouldRevalidate = isRevalidationRequired;
      }
      let shouldRevalidateArgs = {
        ...baseShouldRevalidateArgs,
        defaultShouldRevalidate
      };
      if (shouldRevalidateLoader(fetcherMatch, shouldRevalidateArgs)) {
        fetcherDsMatches = getTargetedDataStrategyMatches(mapRouteProperties2, manifest,
fetchRequest, f.path, fetcherMatches, fetcherMatch, lazyRoutePropertiesToSkip, scopedContext,
shouldRevalidateArgs);
      }
    }
    if (fetcherDsMatches) {
      revalidatingFetchers.push({
        key,
        routeId: f.routeId,
        path: f.path,
        matches: fetcherDsMatches,
        match: fetcherMatch,
        request: fetchRequest,
        controller: fetchController
      });
    }
  });
  return {
    dsMatches,
    revalidatingFetchers
  };
}
function routeHasLoaderOrMiddleware(route) {
  return route.loader != null || route.middleware != null && route.middleware.length > 0;
}
function getRouteHydrationStatus(route, loaderData, errors) {
  if (route.lazy) {
    return {
      shouldLoad: true,
      renderFallback: true
    };
  }
  if (!routeHasLoaderOrMiddleware(route)) {
    return {
      shouldLoad: false,
      renderFallback: false
    };
  }
```

```
  let hasData = loaderData != null && route.id in loaderData;
  let hasError = errors != null && errors[route.id] !== void 0;
  if (!hasData && hasError) {
    return {
      shouldLoad: false,
      renderFallback: false
    };
  }
  if (typeof route.loader === "function" && route.loader.hydrate === true) {
    return {
      shouldLoad: true,
      renderFallback: !hasData
    };
  }
  let shouldLoad = !hasData && !hasError;
  return {
    shouldLoad,
    renderFallback: shouldLoad
  };
}
function isNewLoader(currentLoaderData, currentMatch, match) {
  let isNew =
  // [a] -> [a, b]
  !currentMatch ||
  // [a, b] -> [a, c]
  match.route.id !== currentMatch.route.id;
  let isMissingData = !currentLoaderData.hasOwnProperty(match.route.id);
  return isNew || isMissingData;
}
function isNewRouteInstance(currentMatch, match) {
  let currentPath = currentMatch.route.path;
  return (
    // param change for this match, /users/123 -> /users/456
    currentMatch.pathname !== match.pathname ||
    // splat param changed, which is not present in match.path
    // e.g. /files/images/avatar.jpg -> files/finances.xls
    currentPath != null && currentPath.endsWith("*") && currentMatch.params["*"] !==
match.params["*"]
  );
}
function shouldRevalidateLoader(loaderMatch, arg) {
  if (loaderMatch.route.shouldRevalidate) {
    let routeChoice = loaderMatch.route.shouldRevalidate(arg);
    if (typeof routeChoice === "boolean") {
      return routeChoice;
    }
  }
  return arg.defaultShouldRevalidate;
}
```

```
function patchRoutesImpl(routeId, children, dataRoutes, manifest, mapRouteProperties2,
allowElementMutations) {
  let childrenToPatch;
  if (routeId) {
    let route = manifest[routeId];
    invariant(route, `No route found to patch children into: routeId = ${routeId}`);
    if (!route.children) {
      route.children = [];
    }
    childrenToPatch = route.children;
  } else {
    childrenToPatch = dataRoutes.activeRoutes;
  }
  let uniqueChildren = [];
  let existingChildren = [];
  children.forEach(newRoute => {
    let existingRoute = childrenToPatch.find(existingRoute2 => isSameRoute(newRoute,
existingRoute2));
    if (existingRoute) {
      existingChildren.push({
        existingRoute,
        newRoute
      });
    } else {
      uniqueChildren.push(newRoute);
    }
  });
  if (uniqueChildren.length > 0) {
    let newRoutes = convertRoutesToDataRoutes(uniqueChildren, mapRouteProperties2, [routeId || "_",
"patch", String(childrenToPatch?.length || "0")], manifest);
    childrenToPatch.push(...newRoutes);
  }
  if (allowElementMutations && existingChildren.length > 0) {
    for (let i = 0; i < existingChildren.length; i++) {
      let {
        existingRoute,
        newRoute
      } = existingChildren[i];
      let existingRouteTyped = existingRoute;
      let [newRouteTyped] = convertRoutesToDataRoutes([newRoute], mapRouteProperties2, [],
      // Doesn't matter for mutated routes since they already have an id
      {},
      // Don't touch the manifest here since we're updating in place
      true);
      Object.assign(existingRouteTyped, {
        element: newRouteTyped.element ? newRouteTyped.element : existingRouteTyped.element,
        errorElement: newRouteTyped.errorElement ? newRouteTyped.errorElement :
existingRouteTyped.errorElement,
        hydrateFallbackElement: newRouteTyped.hydrateFallbackElement ?
```

```
newRouteTyped.hydrateFallbackElement : existingRouteTyped.hydrateFallbackElement
      });
    }
  }
  if (!dataRoutes.hasHMRRoutes) {
    dataRoutes.setRoutes([...dataRoutes.activeRoutes]);
  }
}
function isSameRoute(newRoute, existingRoute) {
  if ("id" in newRoute && "id" in existingRoute && newRoute.id === existingRoute.id) {
    return true;
  }
  if (!(newRoute.index === existingRoute.index && newRoute.path === existingRoute.path &&
newRoute.caseSensitive === existingRoute.caseSensitive)) {
    return false;
  }
  if ((!newRoute.children || newRoute.children.length === 0) && (!existingRoute.children ||
existingRoute.children.length === 0)) {
    return true;
  }
  return newRoute.children?.every((aChild, i) => existingRoute.children?.some(bChild
 => isSameRoute(aChild, bChild))) ?? false;
}
var lazyRoutePropertyCache = /* @__PURE__ */new WeakMap();
var loadLazyRouteProperty = ({
  key,
  route,
  manifest,
  mapRouteProperties: mapRouteProperties2
}) => {
  let routeToUpdate = manifest[route.id];
  invariant(routeToUpdate, "No route found in manifest");
  if (!routeToUpdate.lazy || typeof routeToUpdate.lazy !== "object") {
    return;
  }
  let lazyFn = routeToUpdate.lazy[key];
  if (!lazyFn) {
    return;
  }
  let cache = lazyRoutePropertyCache.get(routeToUpdate);
  if (!cache) {
    cache = {};
    lazyRoutePropertyCache.set(routeToUpdate, cache);
  }
  let cachedPromise = cache[key];
  if (cachedPromise) {
    return cachedPromise;
  }
  let propertyPromise = (async () => {
```

```
    let isUnsupported = isUnsupportedLazyRouteObjectKey(key);
    let staticRouteValue = routeToUpdate[key];
    let isStaticallyDefined = staticRouteValue !== void 0 && key !== "hasErrorBoundary";
    if (isUnsupported) {
      warning(!isUnsupported, "Route property " + key + " is not a supported lazy route property. This
property will be ignored.");
      cache[key] = Promise.resolve();
    } else if (isStaticallyDefined) {
      warning(false, `Route "${routeToUpdate.id}" has a static property "${key}" defined. The lazy
property will be ignored.`);
    } else {
      let value = await lazyFn();
      if (value != null) {
        Object.assign(routeToUpdate, {
          [key]: value
        });
        Object.assign(routeToUpdate, mapRouteProperties2(routeToUpdate));
      }
    }
    if (typeof routeToUpdate.lazy === "object") {
      routeToUpdate.lazy[key] = void 0;
      if (Object.values(routeToUpdate.lazy).every(value => value === void 0)) {
        routeToUpdate.lazy = void 0;
      }
    }
  })();
  cache[key] = propertyPromise;
  return propertyPromise;
};
var lazyRouteFunctionCache = /* @__PURE__ */new WeakMap();
function loadLazyRoute(route, type, manifest, mapRouteProperties2, lazyRoutePropertiesToSkip) {
  let routeToUpdate = manifest[route.id];
  invariant(routeToUpdate, "No route found in manifest");
  if (!route.lazy) {
    return {
      lazyRoutePromise: void 0,
      lazyHandlerPromise: void 0
    };
  }
  if (typeof route.lazy === "function") {
    let cachedPromise = lazyRouteFunctionCache.get(routeToUpdate);
    if (cachedPromise) {
      return {
        lazyRoutePromise: cachedPromise,
        lazyHandlerPromise: cachedPromise
      };
    }
    let lazyRoutePromise2 = (async () => {
      invariant(typeof route.lazy === "function", "No lazy route function found");
```

```
      let lazyRoute = await route.lazy();
      let routeUpdates = {};
      for (let lazyRouteProperty in lazyRoute) {
        let lazyValue = lazyRoute[lazyRouteProperty];
        if (lazyValue === void 0) {
          continue;
        }
        let isUnsupported = isUnsupportedLazyRouteFunctionKey(lazyRouteProperty);
        let staticRouteValue = routeToUpdate[lazyRouteProperty];
        let isStaticallyDefined = staticRouteValue !== void 0 &&
        // This property isn't static since it should always be updated based
        // on the route updates
        lazyRouteProperty !== "hasErrorBoundary";
        if (isUnsupported) {
          warning(!isUnsupported, "Route property " + lazyRouteProperty + " is not a supported property to be returned from a lazy route function. This property will be ignored.");
        } else if (isStaticallyDefined) {
          warning(!isStaticallyDefined, `Route "${routeToUpdate.id}" has a static property "${lazyRouteProperty}" defined but its lazy function is also returning a value for this property. The lazy route property "${lazyRouteProperty}" will be ignored.`);
        } else {
          routeUpdates[lazyRouteProperty] = lazyValue;
        }
      }
      Object.assign(routeToUpdate, routeUpdates);
      Object.assign(routeToUpdate, {
        // To keep things framework agnostic, we use the provided `mapRouteProperties`
        // function to set the framework-aware properties (`element`/`hasErrorBoundary`)
        // since the logic will differ between frameworks.
        ...mapRouteProperties2(routeToUpdate),
        lazy: void 0
      });
    })();
    lazyRouteFunctionCache.set(routeToUpdate, lazyRoutePromise2);
    lazyRoutePromise2.catch(() => {});
    return {
      lazyRoutePromise: lazyRoutePromise2,
      lazyHandlerPromise: lazyRoutePromise2
    };
  }
  let lazyKeys = Object.keys(route.lazy);
  let lazyPropertyPromises = [];
  let lazyHandlerPromise = void 0;
  for (let key of lazyKeys) {
    if (lazyRoutePropertiesToSkip && lazyRoutePropertiesToSkip.includes(key)) {
      continue;
    }
    let promise = loadLazyRouteProperty({
      key,
```

```
      route,
      manifest,
      mapRouteProperties: mapRouteProperties2
    });
    if (promise) {
      lazyPropertyPromises.push(promise);
      if (key === type) {
        lazyHandlerPromise = promise;
      }
    }
  }
  let lazyRoutePromise = lazyPropertyPromises.length > 0 ? Promise.all(lazyPropertyPromises).then(()
=> {}) : void 0;
  lazyRoutePromise?.catch(() => {});
  lazyHandlerPromise?.catch(() => {});
  return {
    lazyRoutePromise,
    lazyHandlerPromise
  };
}
function isNonNullable(value) {
  return value !== void 0;
}
function loadLazyMiddlewareForMatches(matches, manifest, mapRouteProperties2) {
  let promises = matches.map(({
    route
  }) => {
    if (typeof route.lazy !== "object" || !route.lazy.middleware) {
      return void 0;
    }
    return loadLazyRouteProperty({
      key: "middleware",
      route,
      manifest,
      mapRouteProperties: mapRouteProperties2
    });
  }).filter(isNonNullable);
  return promises.length > 0 ? Promise.all(promises) : void 0;
}
async function defaultDataStrategy(args) {
  let matchesToLoad = args.matches.filter(m => m.shouldLoad);
  let keyedResults = {};
  let results = await Promise.all(matchesToLoad.map(m => m.resolve()));
  results.forEach((result, i) => {
    keyedResults[matchesToLoad[i].route.id] = result;
  });
  return keyedResults;
}
async function defaultDataStrategyWithMiddleware(args) {
```

```
  if (!args.matches.some(m => m.route.middleware)) {
    return defaultDataStrategy(args);
  }
  return runClientMiddlewarePipeline(args, () => defaultDataStrategy(args));
}
function runServerMiddlewarePipeline(args, handler, errorHandler) {
  return runMiddlewarePipeline(args, handler, processResult, isResponse, errorHandler);
  function processResult(result) {
    return isDataWithResponseInit(result) ? dataWithResponseInitToResponse(result) : result;
  }
}
function runClientMiddlewarePipeline(args, handler) {
  return runMiddlewarePipeline(args, handler, r => {
    if (isRedirectResponse(r)) {
      throw r;
    }
    return r;
  }, isDataStrategyResults, errorHandler);
  function errorHandler(error, routeId, nextResult) {
    if (nextResult) {
      return Promise.resolve(Object.assign(nextResult.value, {
        [routeId]: {
          type: "error",
          result: error
        }
      }));
    } else {
      let {
        matches
      } = args;
      let maxBoundaryIdx = Math.min(
      // Throwing route
      Math.max(matches.findIndex(m => m.route.id === routeId), 0),
      // or the shallowest route that needs to load data
      Math.max(matches.findIndex(m => m.shouldCallHandler()), 0));
      let boundaryRouteId = findNearestBoundary(matches,
matches[maxBoundaryIdx].route.id).route.id;
      return Promise.resolve({
        [boundaryRouteId]: {
          type: "error",
          result: error
        }
      });
    }
  }
}
async function runMiddlewarePipeline(args, handler, processResult, isResult, errorHandler) {
  let {
    matches,
```

```
    ...dataFnArgs
  } = args;
  let tuples = matches.flatMap(m => m.route.middleware ? m.route.middleware.map(fn => [m.route.id,
fn]) : []);
  let result = await callRouteMiddleware(dataFnArgs, tuples, handler, processResult, isResult,
errorHandler);
  return result;
}
async function callRouteMiddleware(args, middlewares, handler, processResult, isResult, errorHandler,
idx = 0) {
  let {
    request
  } = args;
  if (request.signal.aborted) {
    throw request.signal.reason ?? new Error(`Request aborted: ${request.method} ${request.url}`);
  }
  let tuple = middlewares[idx];
  if (!tuple) {
    let result = await handler();
    return result;
  }
  let [routeId, middleware] = tuple;
  let nextResult;
  let next = async () => {
    if (nextResult) {
      throw new Error("You may only call `next()` once per middleware");
    }
    try {
      let result = await callRouteMiddleware(args, middlewares, handler, processResult, isResult,
errorHandler, idx + 1);
      nextResult = {
        value: result
      };
      return nextResult.value;
    } catch (error) {
      nextResult = {
        value: await errorHandler(error, routeId, nextResult)
      };
      return nextResult.value;
    }
  };
  try {
    let value = await middleware(args, next);
    let result = value != null ? processResult(value) : void 0;
    if (isResult(result)) {
      return result;
    } else if (nextResult) {
      return result ?? nextResult.value;
    } else {
```

```
      nextResult = {
        value: await next()
      };
      return nextResult.value;
    }
  } catch (error) {
    let response = await errorHandler(error, routeId, nextResult);
    return response;
  }
}
function getDataStrategyMatchLazyPromises(mapRouteProperties2, manifest, request, match,
lazyRoutePropertiesToSkip) {
  let lazyMiddlewarePromise = loadLazyRouteProperty({
    key: "middleware",
    route: match.route,
    manifest,
    mapRouteProperties: mapRouteProperties2
  });
  let lazyRoutePromises = loadLazyRoute(match.route, isMutationMethod(request.method) ? "action" :
"loader", manifest, mapRouteProperties2, lazyRoutePropertiesToSkip);
  return {
    middleware: lazyMiddlewarePromise,
    route: lazyRoutePromises.lazyRoutePromise,
    handler: lazyRoutePromises.lazyHandlerPromise

  };
}
function getDataStrategyMatch(mapRouteProperties2, manifest, request, path, pattern, match,
lazyRoutePropertiesToSkip, scopedContext, shouldLoad, shouldRevalidateArgs = null,
callSiteDefaultShouldRevalidate) {
  let isUsingNewApi = false;
  let _lazyPromises = getDataStrategyMatchLazyPromises(mapRouteProperties2, manifest, request,
match, lazyRoutePropertiesToSkip);
  return {
    ...match,
    _lazyPromises,
    shouldLoad,
    shouldRevalidateArgs,
    shouldCallHandler(defaultShouldRevalidate) {
      isUsingNewApi = true;
      if (!shouldRevalidateArgs) {
        return shouldLoad;
      }
      if (typeof callSiteDefaultShouldRevalidate === "boolean") {
        return shouldRevalidateLoader(match, {
          ...shouldRevalidateArgs,
          defaultShouldRevalidate: callSiteDefaultShouldRevalidate
        });
      }
```

```
      if (typeof defaultShouldRevalidate === "boolean") {
        return shouldRevalidateLoader(match, {
          ...shouldRevalidateArgs,
          defaultShouldRevalidate
        });
      }
      return shouldRevalidateLoader(match, shouldRevalidateArgs);
    },
    resolve(handlerOverride) {
      let {
        lazy,
        loader,
        middleware
      } = match.route;
      let callHandler = isUsingNewApi || shouldLoad || handlerOverride && !
isMutationMethod(request.method) && (lazy || loader);
      let isMiddlewareOnlyRoute = middleware && middleware.length > 0 && !loader && !lazy;
      if (callHandler && (isMutationMethod(request.method) || !isMiddlewareOnlyRoute)) {
        return callLoaderOrAction({
          request,
          path,
          pattern,
          match,
          lazyHandlerPromise: _lazyPromises?.handler,
          lazyRoutePromise: _lazyPromises?.route,
          handlerOverride,
          scopedContext
        });
      }
      return Promise.resolve({
        type: "data" /* data */,
        result: void 0
      });
    }
  };
}
function getTargetedDataStrategyMatches(mapRouteProperties2, manifest, request, path, matches,
targetMatch, lazyRoutePropertiesToSkip, scopedContext, shouldRevalidateArgs = null) {
  return matches.map(match => {
    if (match.route.id !== targetMatch.route.id) {
      return {
        ...match,
        shouldLoad: false,
        shouldRevalidateArgs,
        shouldCallHandler: () => false,
        _lazyPromises: getDataStrategyMatchLazyPromises(mapRouteProperties2, manifest, request,
match, lazyRoutePropertiesToSkip),
        resolve: () => Promise.resolve({
          type: "data",
```

```
        result: void 0
      })
    };
  }
  return getDataStrategyMatch(mapRouteProperties2, manifest, request, path,
getRoutePattern(matches), match, lazyRoutePropertiesToSkip, scopedContext, true,
shouldRevalidateArgs);
 });
}
async function callDataStrategyImpl(dataStrategyImpl, request, path, matches, fetcherKey,
scopedContext, isStaticHandler) {
 if (matches.some(m => m._lazyPromises?.middleware)) {
  await Promise.all(matches.map(m => m._lazyPromises?.middleware));
 }
 let dataStrategyArgs = {
  request,
  url: createDataFunctionUrl(request, path),
  pattern: getRoutePattern(matches),
  params: matches[0].params,
  context: scopedContext,
  matches
 };
 let runClientMiddleware = isStaticHandler ? () => {
  throw new Error("You cannot call `runClientMiddleware()` from a static handler `dataStrategy`.
Middleware is run outside of `dataStrategy` during SSR in order to bubble up the Response.  You can
enable middleware via the `respond` API in `query`/`queryRoute`");
 } : cb => {
  let typedDataStrategyArgs = dataStrategyArgs;
  return runClientMiddlewarePipeline(typedDataStrategyArgs, () => {
   return cb({
    ...typedDataStrategyArgs,
    fetcherKey,
    runClientMiddleware: () => {
     throw new Error("Cannot call `runClientMiddleware()` from within an `runClientMiddleware`
handler");
    }
   });
  });
 };
 let results = await dataStrategyImpl({
  ...dataStrategyArgs,
  fetcherKey,
  runClientMiddleware
 });
 try {
  await Promise.all(matches.flatMap(m => [m._lazyPromises?.handler, m._lazyPromises?.route]));
 } catch (e) {}
 return results;
}
```

```
async function callLoaderOrAction({
  request,
  path,
  pattern,
  match,
  lazyHandlerPromise,
  lazyRoutePromise,
  handlerOverride,
  scopedContext
}) {
  let result;
  let onReject;
  let isAction = isMutationMethod(request.method);
  let type = isAction ? "action" : "loader";
  let runHandler = handler => {
    let reject;
    let abortPromise = new Promise((_, r) => reject = r);
    onReject = () => reject();
    request.signal.addEventListener("abort", onReject);
    let actualHandler = ctx => {
      if (typeof handler !== "function") {
        return Promise.reject(new Error(`You cannot call the handler for a route which defines a boolean
"${type}" [routeId: ${match.route.id}]`));
      }
      return handler({
        request,
        url: createDataFunctionUrl(request, path),
        pattern,
        params: match.params,
        context: scopedContext
      }, ...(ctx !== void 0 ? [ctx] : []));
    };
    let handlerPromise = (async () => {
      try {
        let val = await (handlerOverride ? handlerOverride(ctx => actualHandler(ctx)) : actualHandler());
        return {
          type: "data",
          result: val
        };
      } catch (e) {
        return {
          type: "error",
          result: e
        };
      }
    })();
    return Promise.race([handlerPromise, abortPromise]);
  };
  try {
```

```
  let handler = isAction ? match.route.action : match.route.loader;
  if (lazyHandlerPromise || lazyRoutePromise) {
    if (handler) {
      let handlerError;
      let [value] = await Promise.all([
      // If the handler throws, don't let it immediately bubble out,
      // since we need to let the lazy() execution finish so we know if this
      // route has a boundary that can handle the error
      runHandler(handler).catch(e => {
        handlerError = e;
      }),
      // Ensure all lazy route promises are resolved before continuing
      lazyHandlerPromise, lazyRoutePromise]);
      if (handlerError !== void 0) {
        throw handlerError;
      }
      result = value;
    } else {
      await lazyHandlerPromise;
      let handler2 = isAction ? match.route.action : match.route.loader;
      if (handler2) {
        [result] = await Promise.all([runHandler(handler2), lazyRoutePromise]);
      } else if (type === "action") {
        let url = new URL(request.url);
        let pathname = url.pathname + url.search;
        throw getInternalRouterError(405, {
          method: request.method,
          pathname,
          routeId: match.route.id
        });
      } else {
        return {
          type: "data" /* data */,
          result: void 0
        };
      }
    }
  } else if (!handler) {
    let url = new URL(request.url);
    let pathname = url.pathname + url.search;
    throw getInternalRouterError(404, {
      pathname
    });
  } else {
    result = await runHandler(handler);
  }
} catch (e) {
  return {
    type: "error" /* error */,
```

```
      result: e
    };
  } finally {
    if (onReject) {
      request.signal.removeEventListener("abort", onReject);
    }
  }
  return result;
}
async function parseResponseBody(response) {
  let contentType = response.headers.get("Content-Type");
  if (contentType && /\bapplication\/json\b/.test(contentType)) {
    return response.body == null ? null : response.json();
  }
  return response.text();
}
async function convertDataStrategyResultToDataResult(dataStrategyResult) {
  let {
    result,
    type
  } = dataStrategyResult;
  if (isResponse(result)) {
    let data2;
    try {
      data2 = await parseResponseBody(result);
    } catch (e) {
      return {
        type: "error" /* error */,
        error: e
      };
    }
    if (type === "error" /* error */) {
      return {
        type: "error" /* error */,
        error: new ErrorResponseImpl(result.status, result.statusText, data2),
        statusCode: result.status,
        headers: result.headers
      };
    }
    return {
      type: "data" /* data */,
      data: data2,
      statusCode: result.status,
      headers: result.headers
    };
  }
  if (type === "error" /* error */) {
    if (isDataWithResponseInit(result)) {
      if (result.data instanceof Error) {
```

```
        return {
          type: "error" /* error */,
          error: result.data,
          statusCode: result.init?.status,
          headers: result.init?.headers ? new Headers(result.init.headers) : void 0
        };
      }
      return {
        type: "error" /* error */,
        error: dataWithResponseInitToErrorResponse(result),
        statusCode: isRouteErrorResponse(result) ? result.status : void 0,
        headers: result.init?.headers ? new Headers(result.init.headers) : void 0
      };
    }
    return {
      type: "error" /* error */,
      error: result,
      statusCode: isRouteErrorResponse(result) ? result.status : void 0
    };
  }
  if (isDataWithResponseInit(result)) {
    return {
      type: "data" /* data */,
      data: result.data,
      statusCode: result.init?.status,
      headers: result.init?.headers ? new Headers(result.init.headers) : void 0
    };
  }
  return {
    type: "data" /* data */,
    data: result
  };
}
function normalizeRelativeRoutingRedirectResponse(response, request, routeId, matches, basename) {
  let location = response.headers.get("Location");
  invariant(location, "Redirects returned/thrown from loaders/actions must have a Location header");
  if (!isAbsoluteUrl(location)) {
    let trimmedMatches = matches.slice(0, matches.findIndex(m => m.route.id === routeId) + 1);
    location = normalizeTo(new URL(request.url), trimmedMatches, basename, location);
    response.headers.set("Location",
 location);
  }
  return response;
}
var invalidProtocols = ["about:", "blob:", "chrome:", "chrome-untrusted:", "content:", "data:",
"devtools:", "file:", "filesystem:",
// eslint-disable-next-line no-script-url
"javascript:"];
function normalizeRedirectLocation(location, currentUrl, basename, historyInstance) {
```

```
  if (isAbsoluteUrl(location)) {
    let normalizedLocation = location;
    let url = normalizedLocation.startsWith("//") ? new URL(currentUrl.protocol +
normalizedLocation) : new URL(normalizedLocation);
    if (invalidProtocols.includes(url.protocol)) {
      throw new Error("Invalid redirect location");
    }
    let isSameBasename = stripBasename(url.pathname, basename) != null;
    if (url.origin === currentUrl.origin && isSameBasename) {
      return removeDoubleSlashes(url.pathname) + url.search + url.hash;
    }
  }
  try {
    let url = historyInstance.createURL(location);
    if (invalidProtocols.includes(url.protocol)) {
      throw new Error("Invalid redirect location");
    }
  } catch (e) {}
  return location;
}
function createClientSideRequest(history, location, signal, submission) {
  let url = history.createURL(stripHashFromPath(location)).toString();
  let init = {
    signal
  };
  if (submission && isMutationMethod(submission.formMethod)) {
    let {
      formMethod,
      formEncType
    } = submission;
    init.method = formMethod.toUpperCase();
    if (formEncType === "application/json") {
      init.headers = new Headers({
        "Content-Type": formEncType
      });
      init.body = JSON.stringify(submission.json);
    } else if (formEncType === "text/plain") {
      init.body = submission.text;
    } else if (formEncType === "application/x-www-form-urlencoded" && submission.formData) {
      init.body = convertFormDataToSearchParams(submission.formData);
    } else {
      init.body = submission.formData;
    }
  }
  return new Request(url, init);
}
function createDataFunctionUrl(request, path) {
  let url = new URL(request.url);
  let parsed = typeof path === "string" ? parsePath(path) : path;
```

```
  url.pathname = parsed.pathname || "/";
  if (parsed.search) {
    let searchParams = new URLSearchParams(parsed.search);
    let indexValues = searchParams.getAll("index");
    searchParams.delete("index");
    for (let value of indexValues.filter(Boolean)) {
      searchParams.append("index", value);
    }
    url.search = searchParams.size ? `?${searchParams.toString()}` : "";
  } else {
    url.search = "";
  }
  url.hash = parsed.hash || "";
  return url;
}
function convertFormDataToSearchParams(formData) {
  let searchParams = new URLSearchParams();
  for (let [key, value] of formData.entries()) {
    searchParams.append(key, typeof value === "string" ? value : value.name);
  }
  return searchParams;
}
function convertSearchParamsToFormData(searchParams) {
  let formData = new FormData();
  for (let [key, value] of searchParams.entries()) {
    formData.append(key, value);
  }
  return formData;
}
function processRouteLoaderData(matches, results, pendingActionResult, isStaticHandler = false,
skipLoaderErrorBubbling = false) {
  let loaderData = {};
  let errors = null;
  let statusCode;
  let foundError = false;
  let loaderHeaders = {};
  let pendingError = pendingActionResult && isErrorResult(pendingActionResult[1]) ?
pendingActionResult[1].error : void 0;
  matches.forEach(match => {
    if (!(match.route.id in results)) {
      return;
    }
    let id = match.route.id;
    let result = results[id];
    invariant(!isRedirectResult(result), "Cannot handle redirect results in processLoaderData");
    if (isErrorResult(result)) {
      let error = result.error;
      if (pendingError !== void 0) {
        error = pendingError;
```

```
      pendingError = void 0;
    }
    errors = errors || {};
    if (skipLoaderErrorBubbling) {
      errors[id] = error;
    } else {
      let boundaryMatch = findNearestBoundary(matches, id);
      if (errors[boundaryMatch.route.id] == null) {
        errors[boundaryMatch.route.id] = error;
      }
    }
    if (!isStaticHandler) {
      loaderData[id] = ResetLoaderDataSymbol;
    }
    if (!foundError) {
      foundError = true;
      statusCode = isRouteErrorResponse(result.error) ? result.error.status : 500;
    }
    if (result.headers) {
      loaderHeaders[id] = result.headers;
    }
  } else {
    loaderData[id] = result.data;
    if (result.statusCode && result.statusCode !== 200 && !foundError) {
      statusCode = result.statusCode;
    }
    if (result.headers) {
      loaderHeaders[id] = result.headers;
    }
  }
});
if (pendingError !== void 0 && pendingActionResult) {
  errors = {
    [pendingActionResult[0]]: pendingError
  };
  if (pendingActionResult[2]) {
    loaderData[pendingActionResult[2]] = void 0;
  }
}
return {
  loaderData,
  errors,
  statusCode: statusCode || 200,
  loaderHeaders
};
}
function processLoaderData(state, matches, results, pendingActionResult, revalidatingFetchers,
fetcherResults, workingFetchers) {
  let {
```

```
    loaderData,
    errors
  } = processRouteLoaderData(matches, results, pendingActionResult);
  revalidatingFetchers.filter(f => !f.matches || f.matches.some(m => m.shouldLoad)).forEach(rf => {
    let {
      key,
      match,
      controller
    } = rf;
    if (controller && controller.signal.aborted) {
      return;
    }
    let result = fetcherResults[key];
    invariant(result, "Did not find corresponding fetcher result");
    if (isErrorResult(result)) {
      let boundaryMatch = findNearestBoundary(state.matches, match?.route.id);
      if (!(errors && errors[boundaryMatch.route.id])) {
        errors = {
          ...errors,
          [boundaryMatch.route.id]: result.error
        };
      }
      workingFetchers.delete(key);
    } else if (isRedirectResult(result)) {
      invariant(false, "Unhandled fetcher revalidation redirect");
    } else {
      let doneFetcher = getDoneFetcher(result.data);
      workingFetchers.set(key, doneFetcher);
    }
  });
  return {
    loaderData,
    errors
  };
}
function mergeLoaderData(loaderData, newLoaderData, matches, errors) {
  let mergedLoaderData = Object.entries(newLoaderData).filter(([, v]) => v !==
ResetLoaderDataSymbol).reduce((merged, [k, v]) => {
    merged[k] = v;
    return merged;
  }, {});
  for (let match of matches) {
    let id = match.route.id;
    if (!newLoaderData.hasOwnProperty(id) && loaderData.hasOwnProperty(id) &&
match.route.loader) {
      mergedLoaderData[id] = loaderData[id];
    }
    if (errors && errors.hasOwnProperty(id)) {
      break;
```

```
    }
  }
  return mergedLoaderData;
}
function getActionDataForCommit(pendingActionResult) {
  if (!pendingActionResult) {
    return {};
  }
  return isErrorResult(pendingActionResult[1]) ? {
    // Clear out prior actionData on errors
    actionData: {}
  } : {
    actionData: {
      [pendingActionResult[0]]: pendingActionResult[1].data
    }
  };
}
function findNearestBoundary(matches, routeId) {
  let eligibleMatches = routeId ? matches.slice(0, matches.findIndex(m => m.route.id === routeId) +
1) : [...matches];
  return eligibleMatches.reverse().find(m => m.route.hasErrorBoundary === true) || matches[0];
}
function getShortCircuitMatches(routes) {
  let route = routes.length === 1 ? routes[0] : routes.find(r => r.index || !r.path || r.path === "/") || {
    id: `__shim-error-route__`
  };
  return {
    matches: [{
      params: {},
      pathname: "",
      pathnameBase: "",
      route
    }],
    route
  };
}
function getInternalRouterError(status, {
  pathname,
  routeId,
  method,
  type,
  message
} = {}) {
  let statusText = "Unknown Server Error";
  let errorMessage = "Unknown @remix-run/router error";
  if (status === 400) {
    statusText = "Bad Request";
    if (method && pathname && routeId) {
      errorMessage = `You made a ${method} request to "${pathname}" but did not provide a \`loader\`
```

```
for route "${routeId}", so there is no way to handle the request.`;
    } else if (type === "invalid-body") {
      errorMessage = "Unable to encode submission body";
    }
  } else if (status === 403) {
    statusText = "Forbidden";
    errorMessage = `Route "${routeId}" does not match URL "${pathname}"`;
  } else if (status === 404) {
    statusText = "Not Found";
    errorMessage = `No route matches URL "${pathname}"`;
  } else if (status === 405) {
    statusText = "Method Not Allowed";
    if (method && pathname && routeId) {
      errorMessage = `You made a ${method.toUpperCase()} request to "${pathname}" but did not
provide an \`action\` for route "${routeId}", so there is no way to handle the request.`;
    } else if (method) {
      errorMessage = `Invalid request method "${method.toUpperCase()}"`;
    }
  }
  return new ErrorResponseImpl(status || 500, statusText, new Error(errorMessage), true);
}
function findRedirect(results) {
  let entries = Object.entries(results);
  for (let i = entries.length - 1; i >= 0; i--) {
    let [key, result] = entries[i];
    if (isRedirectResult(result)) {
      return {
        key,
        result
      };
    }
  }
}
function stripHashFromPath(path) {
  let parsedPath = typeof path === "string" ? parsePath(path) : path;
  return createPath({
    ...parsedPath,
    hash: ""
  });
}
function isHashChangeOnly(a, b) {
  if (a.pathname !== b.pathname || a.search !== b.search) {
    return false;
  }
  if (a.hash === "") {
    return b.hash !== "";
  } else if (a.hash === b.hash) {
    return true;
  } else if (b.hash !== "") {
```

```
    return true;
  }
  return false;
}
function dataWithResponseInitToResponse(data2) {
  return Response.json(data2.data, data2.init ?? void 0);
}
function dataWithResponseInitToErrorResponse(data2) {
  return new ErrorResponseImpl(data2.init?.status ?? 500, data2.init?.statusText ?? "Internal Server
Error", data2.data);
}
function
 isDataStrategyResults(result) {
  return result != null && typeof result === "object" && Object.entries(result).every(([key, value]) =>
typeof key === "string" && isDataStrategyResult(value));
}
function isDataStrategyResult(result) {
  return result != null && typeof result === "object" && "type" in result && "result" in result &&
(result.type === "data" /* data */ || result.type === "error" /* error */);
}
function isRedirectDataStrategyResult(result) {
  return isResponse(result.result) && redirectStatusCodes.has(result.result.status);
}
function isErrorResult(result) {
  return result.type === "error" /* error */;
}
function isRedirectResult(result) {
  return (result && result.type) === "redirect" /* redirect */;
}
function isDataWithResponseInit(value) {
  return typeof value === "object" && value != null && "type" in value && "data" in value && "init"
in value && value.type === "DataWithResponseInit";
}
function isResponse(value) {
  return value != null && typeof value.status === "number" && typeof value.statusText === "string"
&& typeof value.headers === "object" && typeof value.body !== "undefined";
}
function isRedirectStatusCode(statusCode) {
  return redirectStatusCodes.has(statusCode);
}
function isRedirectResponse(result) {
  return isResponse(result) && isRedirectStatusCode(result.status) && result.headers.has("Location");
}
function isValidMethod(method) {
  return validRequestMethods.has(method.toUpperCase());
}
function isMutationMethod(method) {
  return validMutationMethods.has(method.toUpperCase());
}
```

```
function hasNakedIndexQuery(search) {
  return new URLSearchParams(search).getAll("index").some(v => v === "");
}
function getTargetMatch(matches, location) {
  let search = typeof location === "string" ? parsePath(location).search : location.search;
  if (matches[matches.length - 1].route.index && hasNakedIndexQuery(search || "")) {
    return matches[matches.length - 1];
  }
  let pathMatches = getPathContributingMatches(matches);
  return pathMatches[pathMatches.length - 1];
}
function getSubmissionFromNavigation(navigation) {
  let {
    formMethod,
    formAction,
    formEncType,
    text,
    formData,
    json
  } = navigation;
  if (!formMethod || !formAction || !formEncType) {
    return;
  }
  if (text != null) {
    return {
      formMethod,
      formAction,
      formEncType,
      formData: void 0,
      json: void 0,
      text
    };
  } else if (formData != null) {
    return {
      formMethod,
      formAction,
      formEncType,
      formData,
      json: void 0,
      text: void 0
    };
  } else if (json !== void 0) {
    return {
      formMethod,
      formAction,
      formEncType,
      formData: void 0,
      json,
      text: void 0
```

```
    };
  }
}
function getLoadingNavigation(location, matches, historyAction, submission) {
  if (submission) {
    let navigation = {
      state: "loading",
      location,
      matches,
      historyAction,
      formMethod: submission.formMethod,
      formAction: submission.formAction,
      formEncType: submission.formEncType,
      formData: submission.formData,
      json: submission.json,
      text: submission.text
    };
    return navigation;
  } else {
    let navigation = {
      state: "loading",
      location,
      matches,
      historyAction,
      formMethod: void 0,
      formAction: void 0,
      formEncType: void 0,
      formData: void 0,
      json: void 0,
      text: void 0
    };
    return navigation;
  }
}
function getSubmittingNavigation(location, matches, historyAction, submission) {
  let navigation = {
    state: "submitting",
    location,
    matches,
    historyAction,
    formMethod: submission.formMethod,
    formAction: submission.formAction,
    formEncType: submission.formEncType,
    formData: submission.formData,
    json: submission.json,
    text: submission.text
  };
  return navigation;
}
```

```
function getLoadingFetcher(submission, data2) {
  if (submission) {
    let fetcher = {
      state: "loading",
      formMethod: submission.formMethod,
      formAction: submission.formAction,
      formEncType: submission.formEncType,
      formData: submission.formData,
      json: submission.json,
      text: submission.text,
      data: data2
    };
    return fetcher;
  } else {
    let fetcher = {
      state: "loading",
      formMethod: void 0,
      formAction: void 0,
      formEncType: void 0,
      formData: void 0,
      json: void 0,
      text: void 0,
      data: data2
    };
    return fetcher;
  }
}
function getSubmittingFetcher(submission, existingFetcher) {
  let fetcher = {
    state: "submitting",
    formMethod: submission.formMethod,
    formAction: submission.formAction,
    formEncType: submission.formEncType,
    formData: submission.formData,
    json: submission.json,
    text: submission.text,
    data: existingFetcher ? existingFetcher.data : void 0
  };
  return fetcher;
}
function getDoneFetcher(data2) {
  let fetcher = {
    state: "idle",
    formMethod: void 0,
    formAction: void 0,
    formEncType: void 0,
    formData: void 0,
    json: void 0,
    text: void 0,
```

```
    data: data2
  };
  return fetcher;
}
function restoreAppliedTransitions(_window, transitions) {
  try {
    let sessionPositions = _window.sessionStorage.getItem(TRANSITIONS_STORAGE_KEY);
    if (sessionPositions) {
      let json = JSON.parse(sessionPositions);
      for (let [k, v] of Object.entries(json || {})) {
        if (v && Array.isArray(v)) {
          transitions.set(k, new Set(v || []));
        }
      }
    }
  } catch (e) {}
}
function persistAppliedTransitions(_window, transitions) {
  if (transitions.size > 0) {
    let json = {};
    for (let [k, v] of transitions) {
      json[k] = [...v];
    }
    try {
      _window.sessionStorage.setItem(TRANSITIONS_STORAGE_KEY, JSON.stringify(json));
    } catch (error) {
      warning(false, `Failed to save applied view transitions in sessionStorage (${error}).`);
    }
  }
}
function createDeferred() {
  let resolve;
  let reject;
  let promise = new Promise((res, rej) => {
    resolve = async val => {
      res(val);
      try {
        await promise;
      } catch (e) {}
    };
    reject = async error => {
      rej(error);
      try {
        await promise;
      } catch (e) {}
    };
  });
  return {
    promise,
```

```
    //@ts-ignore
    resolve,
    //@ts-ignore
    reject
  };
}

// lib/context.ts

var DataRouterContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
DataRouterContext.displayName = "DataRouter";
var DataRouterStateContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
DataRouterStateContext.displayName = "DataRouterState";
var RSCRouterContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(false);
function useIsRSCRouterContext() {
  return react__WEBPACK_IMPORTED_MODULE_0__.useContext(RSCRouterContext);
}
var ViewTransitionContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext({
  isTransitioning: false
});
ViewTransitionContext.displayName = "ViewTransition";
var FetchersContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(/*
@__PURE__ */new Map());
FetchersContext.displayName = "Fetchers";
var AwaitContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
AwaitContext.displayName = "Await";
var AwaitContextProvider = props =>
react__WEBPACK_IMPORTED_MODULE_0__.createElement(AwaitContext.Provider, props);
var NavigationContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
NavigationContext.displayName = "Navigation";
var LocationContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
LocationContext.displayName = "Location";
var RouteContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext({
  outlet: null,
  matches: [],
  isDataRoute: false
});
RouteContext.displayName = "Route";
var RouteErrorContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
RouteErrorContext.displayName = "RouteError";
var ENABLE_DEV_WARNINGS = true;

// lib/hooks.tsx


// lib/errors.ts
var ERROR_DIGEST_BASE = "REACT_ROUTER_ERROR";
var ERROR_DIGEST_REDIRECT = "REDIRECT";
var ERROR_DIGEST_ROUTE_ERROR_RESPONSE = "ROUTE_ERROR_RESPONSE";
```

```
function decodeRedirectErrorDigest(digest) {
  if (digest.startsWith(`${ERROR_DIGEST_BASE}:${ERROR_DIGEST_REDIRECT}:{`)) {
    try {
      let parsed = JSON.parse(digest.slice(28));
      if (typeof parsed === "object" && parsed && typeof parsed.status === "number" && typeof
parsed.statusText === "string" && typeof parsed.location === "string" && typeof
parsed.reloadDocument === "boolean" && typeof parsed.replace === "boolean") {
        return parsed;
      }
    } catch {}
  }
}
function decodeRouteErrorResponseDigest(digest) {
  if (digest.startsWith(`${ERROR_DIGEST_BASE}:$
{ERROR_DIGEST_ROUTE_ERROR_RESPONSE}:{`)) {
    try {
      let parsed = JSON.parse(digest.slice(40));
      if (typeof parsed === "object" && parsed && typeof parsed.status === "number" && typeof
parsed.statusText === "string") {
        return new ErrorResponseImpl(parsed.status, parsed.statusText, parsed.data);
      }
    } catch {}
  }
}

// lib/hooks.tsx
function useHref(to, {
  relative
} = {}) {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of the
  // router loaded. We can help them understand how to avoid that.
  `useHref() may be used only in the context of a <Router> component.`);
  let {
    basename,
    navigator
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let {
    hash,
    pathname,
    search
  } = useResolvedPath(to, {
    relative
  });
  let joinedPathname = pathname;
  if (basename !== "/") {
    joinedPathname = pathname === "/" ? basename : joinPaths([basename, pathname]);
  }
  return navigator.createHref({
```

```
    pathname: joinedPathname,
    search,
    hash
  });
}
function useInRouterContext() {
  return react__WEBPACK_IMPORTED_MODULE_0__.useContext(LocationContext)
 != null;
}
function useLocation() {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of the
  // router loaded. We can help them understand how to avoid that.
  `useLocation() may be used only in the context of a <Router> component.`);
  return react__WEBPACK_IMPORTED_MODULE_0__.useContext(LocationContext).location;
}
function useNavigationType() {
  return
react__WEBPACK_IMPORTED_MODULE_0__.useContext(LocationContext).navigationType;
}
function useMatch(pattern) {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of the
  // router loaded. We can help them understand how to avoid that.
  `useMatch() may be used only in the context of a <Router> component.`);
  let {
    pathname
  } = useLocation();
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => matchPath(pattern,
decodePath(pathname)), [pathname, pattern]);
}
var navigateEffectWarning = `You should call navigate() in a React.useEffect(), not when your
component is first rendered.`;
function useIsomorphicLayoutEffect(cb) {
  let isStatic = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext).static;
  if (!isStatic) {
    react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(cb);
  }
}
function useNavigate() {
  let {
    isDataRoute
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  return isDataRoute ? useNavigateStable() : useNavigateUnstable();
}
function useNavigateUnstable() {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of the
  // router loaded. We can help them understand how to avoid that.
```

```
  `useNavigate() may be used only in the context of a <Router> component.`);
  let dataRouterContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  let {
    basename,
    navigator
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let {
    matches
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  let {
    pathname: locationPathname
  } = useLocation();
  let routePathnamesJson = JSON.stringify(getResolveToMatches(matches));
  let activeRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(false);
  useIsomorphicLayoutEffect(() => {
    activeRef.current = true;
  });
  let navigate = react__WEBPACK_IMPORTED_MODULE_0__.useCallback((to, options = {}) => {
    warning(activeRef.current, navigateEffectWarning);
    if (!activeRef.current) return;
    if (typeof to === "number") {
      navigator.go(to);
      return;
    }
    let path = resolveTo(to, JSON.parse(routePathnamesJson), locationPathname, options.relative ===
"path");
    if (dataRouterContext == null && basename !== "/") {
      path.pathname = path.pathname === "/" ? basename : joinPaths([basename, path.pathname]);
    }
    (!!options.replace ? navigator.replace : navigator.push)(path, options.state, options);
  }, [basename, navigator, routePathnamesJson, locationPathname, dataRouterContext]);
  return navigate;
}
var OutletContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(null);
function useOutletContext() {
  return react__WEBPACK_IMPORTED_MODULE_0__.useContext(OutletContext);
}
function useOutlet(context) {
  let outlet = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext).outlet;
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => outlet && /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(OutletContext.Provider, {
    value: context
  }, outlet), [outlet, context]);
}
function useParams() {
  let {
    matches
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
```

```
  let routeMatch = matches[matches.length - 1];
  return routeMatch?.params ?? {};
}
function useResolvedPath(to, {
  relative
} = {}) {
  let {
    matches
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  let {
    pathname: locationPathname
  } = useLocation();
  let routePathnamesJson = JSON.stringify(getResolveToMatches(matches));
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => resolveTo(to,
JSON.parse(routePathnamesJson), locationPathname, relative === "path"), [to, routePathnamesJson,
locationPathname, relative]);
}
function useRoutes(routes, locationArg) {
  return useRoutesImpl(routes, locationArg);
}
function useRoutesImpl(routes, locationArg, dataRouterOpts) {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of the
  // router loaded. We can help them understand how to avoid that.
  `useRoutes() may be used only in the context of a <Router> component.`);
  let {
    navigator
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let {
    matches: parentMatches
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  let routeMatch = parentMatches[parentMatches.length - 1];
  let parentParams = routeMatch ? routeMatch.params : {};
  let parentPathname = routeMatch ? routeMatch.pathname : "/";
  let parentPathnameBase = routeMatch ? routeMatch.pathnameBase : "/";
  let parentRoute = routeMatch && routeMatch.route;
  if (ENABLE_DEV_WARNINGS) {
    let parentPath = parentRoute && parentRoute.path || "";
    warningOnce(parentPathname, !parentRoute || parentPath.endsWith("*") ||
parentPath.endsWith("*?"), `You rendered descendant <Routes> (or called \`useRoutes()\`) at "$
{parentPathname}" (under <Route path="${parentPath}">) but the parent route path has no trailing
"*". This means if you navigate deeper, the parent won't match anymore and therefore the child routes
will never render.

Please change the parent <Route path="${parentPath}"> to <Route path="${parentPath === "/" ? "*" :
`${parentPath}/*`}">.`);
  }
  let locationFromContext = useLocation();
  let location;
```

```
  if (locationArg) {
    let parsedLocationArg = typeof locationArg === "string" ? parsePath(locationArg) : locationArg;
    invariant(parentPathnameBase === "/" ||
parsedLocationArg.pathname?.startsWith(parentPathnameBase), `When overriding the location using \`<Routes location>\` or \`useRoutes(routes, location)\`, the location pathname must begin with the portion of the URL pathname that was matched by all parent routes. The current pathname base is "${parentPathnameBase}" but pathname "${parsedLocationArg.pathname}" was given in the \`location\` prop.`);
    location = parsedLocationArg;
  } else {
    location = locationFromContext;
  }
  let pathname = location.pathname || "/";
  let remainingPathname = pathname;
  if (parentPathnameBase !== "/") {
    let parentSegments = parentPathnameBase.replace(/^\//, "").split("/");
    let segments = pathname.replace(/^\//, "").split("/");
    remainingPathname = "/" + segments.slice(parentSegments.length).join("/");
  }
  let matches = dataRouterOpts && dataRouterOpts.state.matches.length ?
  // If we're in a data router, use the matches we've already identified but ensure
  // we have the latest route instances from the manifest in case elements have changed
  dataRouterOpts.state.matches.map(m => Object.assign(m, {
    route: dataRouterOpts.manifest[m.route.id] || m.route
  })) : matchRoutes(routes, {
    pathname: remainingPathname
  });
  if (ENABLE_DEV_WARNINGS) {
    warning(parentRoute || matches != null, `No routes matched location "${location.pathname}${location.search}${location.hash}" `);
    warning(matches == null || matches[matches.length - 1].route.element !== void 0 || matches[matches.length - 1].route.Component !== void 0 || matches[matches.length - 1].route.lazy !== void 0, `Matched leaf route at location "${location.pathname}${location.search}${location.hash}" does not have an element or Component. This means it will render an <Outlet /> with a null value by default resulting in an "empty" page.`);
  }
  let renderedMatches = _renderMatches(matches && matches.map(match => Object.assign({}, match, {
    params: Object.assign({}, parentParams, match.params),
    pathname: joinPaths([parentPathnameBase,
    // Re-encode pathnames that were decoded inside matchRoutes.
    // Pre-encode `%`, `?` and `#` ahead of `encodeLocation` because it uses
    // `new URL()` internally and we need to prevent it from treating
    // them as separators
    navigator.encodeLocation ? navigator.encodeLocation(match.pathname.replace(/%/g, "%25").replace(/\?/g, "%3F").replace(/#/g, "%23")).pathname : match.pathname]),
    pathnameBase: match.pathnameBase === "/" ? parentPathnameBase : joinPaths([parentPathnameBase,
    // Re-encode pathnames that were decoded inside matchRoutes
```

```
    // Pre-encode `%`, `?` and `#` ahead of `encodeLocation` because it uses
    // `new URL()` internally and we need to prevent it from treating
    // them as separators
    navigator.encodeLocation ? navigator.encodeLocation(match.pathnameBase.replace(/%/g,
"%25").replace(/\?/g, "%3F").replace(/#/g, "%23")).pathname : match.pathnameBase])
  })), parentMatches, dataRouterOpts);
  if (locationArg && renderedMatches) {
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(LocationContext.Provider, {
      value: {
        location: {
          pathname: "/",
          search: "",
          hash: "",
          state: null,
          key: "default",
          mask: void 0,
          ...location
        },
        navigationType: "POP" /* Pop */
      }
    }, renderedMatches);
  }
  return renderedMatches;
}
function DefaultErrorComponent() {
  let error = useRouteError();
  let message = isRouteErrorResponse(error) ? `${error.status} ${error.statusText}` : error instanceof
Error ? error.message : JSON.stringify(error);
  let stack = error instanceof Error ? error.stack : null;
  let lightgrey = "rgba(200,200,200, 0.5)";
  let preStyles = {
    padding: "0.5rem",
    backgroundColor: lightgrey
  };
  let codeStyles = {
    padding: "2px 4px",
    backgroundColor: lightgrey
  };
  let devInfo = null;

  if (ENABLE_DEV_WARNINGS) {
    console.error("Error handled by React Router default ErrorBoundary:", error);
    devInfo = /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("p", null, "\u{1F4BF} Hey
developer \u{1F44B}"), /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("p", null, "You can provide a way
```

```
better UX than this when your app throws errors by providing your own ", /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("code", {
      style: codeStyles
    }, "ErrorBoundary"), " or", " ", /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("code", {
      style: codeStyles
    }, "errorElement"), " prop on your route."));
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("h2", null, "Unexpected
Application Error!"), /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("h3", {
    style: {
      fontStyle: "italic"
    }
  }, message), stack ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("pre", {
    style: preStyles
  }, stack) : null, devInfo);
}
var defaultErrorElement = /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(DefaultErrorComponent, null);
var RenderErrorBoundary = class extends
react__WEBPACK_IMPORTED_MODULE_0__.Component {
  constructor(props) {
    super(props);
    this.state = {
      location: props.location,
      revalidation: props.revalidation,
      error: props.error
    };
  }
  static getDerivedStateFromError(error) {
    return {
      error
    };
  }
  static getDerivedStateFromProps(props, state) {
    if (state.location !== props.location || state.revalidation !== "idle" && props.revalidation === "idle")
{
      return {
        error: props.error,
        location: props.location,
        revalidation: props.revalidation
      };
    }
    return {
```

```
      error: props.error !== void 0 ? props.error : state.error,
      location: state.location,
      revalidation: props.revalidation || state.revalidation
    };
  }
  componentDidCatch(error, errorInfo) {
    if (this.props.onError) {
      this.props.onError(error, errorInfo);
    } else {
      console.error("React Router caught the following error during render", error);
    }
  }
  render() {
    let error = this.state.error;
    if (this.context && typeof error === "object" && error && "digest" in error && typeof error.digest
=== "string") {
      const decoded = decodeRouteErrorResponseDigest(error.digest);
      if (decoded) error = decoded;
    }
    let result = error !== void 0 ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RouteContext.Provider, {
      value: this.props.routeContext
    }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RouteErrorContext.Provider, {
      value: error,
      children: this.props.component
    })) : this.props.children;
    if (this.context) {
      return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RSCErrorHandler, {
        error
      }, result);
    }
    return result;
  }
};
RenderErrorBoundary.contextType = RSCRouterContext;
var errorRedirectHandledMap = /* @__PURE__ */new WeakMap();
function RSCErrorHandler({
  children,
  error
}) {
  let {
    basename
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  if (typeof error === "object" && error && "digest" in error && typeof error.digest === "string") {
    let redirect2 = decodeRedirectErrorDigest(error.digest);
    if (redirect2) {
      let existingRedirect = errorRedirectHandledMap.get(error);
```

```
      if (existingRedirect) throw existingRedirect;
      let parsed = parseToInfo(redirect2.location, basename);
      if (isBrowser && !errorRedirectHandledMap.get(error)) {
        if (parsed.isExternal || redirect2.reloadDocument) {
          window.location.href = parsed.absoluteURL || parsed.to;
        } else {
          const redirectPromise = Promise.resolve().then(() =>
window.__reactRouterDataRouter.navigate(parsed.to, {
            replace: redirect2.replace
          }));
          errorRedirectHandledMap.set(error, redirectPromise);
          throw redirectPromise;
        }
      }
      return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("meta",
{
        httpEquiv: "refresh",
        content: `0;url=${parsed.absoluteURL || parsed.to}`
      });
    }
  }
  return children;
}
function RenderedRoute({
  routeContext,
  match,
  children
}) {
  let dataRouterContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  if (dataRouterContext && dataRouterContext.static && dataRouterContext.staticContext &&
(match.route.errorElement || match.route.ErrorBoundary)) {
    dataRouterContext.staticContext._deepestRenderedBoundaryId = match.route.id;
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RouteContext.Provider, {
    value: routeContext
  }, children);
}
function _renderMatches(matches, parentMatches = [], dataRouterOpts) {
  let dataRouterState = dataRouterOpts?.state;
  if (matches == null) {
    if (!dataRouterState) {
      return null;
    }
    if (dataRouterState.errors) {
      matches = dataRouterState.matches;
    } else if (parentMatches.length === 0 && !dataRouterState.initialized &&
dataRouterState.matches.length > 0) {
```

```
      matches = dataRouterState.matches;
    } else {
      return null;
    }
  }
  let renderedMatches = matches;
  let errors = dataRouterState?.errors;
  if (errors != null) {
    let errorIndex = renderedMatches.findIndex(m => m.route.id && errors?.[m.route.id] !== void 0);
    invariant(errorIndex >= 0, `Could not find a matching route for errors on route IDs: $
{Object.keys(errors).join(",")}`);
    renderedMatches = renderedMatches.slice(0, Math.min(renderedMatches.length, errorIndex + 1));
  }
  let renderFallback = false;
  let fallbackIndex = -1;
  if (dataRouterOpts && dataRouterState) {
    renderFallback = dataRouterState.renderFallback;
    for (let i = 0; i < renderedMatches.length; i++) {
      let match = renderedMatches[i];
      if (match.route.HydrateFallback || match.route.hydrateFallbackElement) {
        fallbackIndex = i;
      }
      if (match.route.id) {
        let {
          loaderData,
          errors: errors2
        } = dataRouterState;
        let needsToRunLoader = match.route.loader && !loaderData.hasOwnProperty(match.route.id)
&& (!errors2 || errors2[match.route.id] === void 0);
        if (match.route.lazy || needsToRunLoader) {
          if (dataRouterOpts.isStatic) {
            renderFallback = true;
          }
          if (fallbackIndex >= 0) {
            renderedMatches = renderedMatches.slice(0, fallbackIndex + 1);
          } else {
            renderedMatches = [renderedMatches[0]];
          }
          break;
        }
      }
    }
  }
  let onErrorHandler = dataRouterOpts?.onError;
  let onError = dataRouterState && onErrorHandler ? (error, errorInfo) => {
    onErrorHandler(error, {
      location: dataRouterState.location,
      params: dataRouterState.matches?.[0]?.params ?? {},
      pattern: getRoutePattern(dataRouterState.matches),
```

```
      errorInfo
    });
  } : void 0;
  return renderedMatches.reduceRight((outlet, match, index) => {
    let error;
    let shouldRenderHydrateFallback = false;
    let errorElement = null;
    let hydrateFallbackElement = null;
    if (dataRouterState) {
      error = errors && match.route.id ? errors[match.route.id] : void 0;
      errorElement = match.route.errorElement || defaultErrorElement;
      if (renderFallback) {
        if (fallbackIndex < 0 && index === 0) {
          warningOnce("route-fallback", false, "No `HydrateFallback` element provided to render during
initial hydration");
          shouldRenderHydrateFallback = true;
          hydrateFallbackElement = null;
        } else if (fallbackIndex === index) {
          shouldRenderHydrateFallback = true;
          hydrateFallbackElement = match.route.hydrateFallbackElement || null;
        }
      }
    }
    let matches2 = parentMatches.concat(renderedMatches.slice(0, index + 1));
    let getChildren = () => {
      let children;
      if (error) {
        children = errorElement;
      } else if (shouldRenderHydrateFallback) {
        children = hydrateFallbackElement;
      } else if (match.route.Component) {
        children = /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(match.route.Component, null);
      } else if (match.route.element) {
        children = match.route.element;
      } else {
        children = outlet;
      }
      return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RenderedRoute, {
        match,
        routeContext: {
          outlet,
          matches: matches2,
          isDataRoute: dataRouterState != null
        },
        children
      });
    };
```

```
    return dataRouterState && (match.route.ErrorBoundary || match.route.errorElement || index === 0) ?
/* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RenderErrorBoundary, {
      location: dataRouterState.location,
      revalidation: dataRouterState.revalidation,
      component: errorElement,
      error,
      children: getChildren(),
      routeContext: {
        outlet: null,
        matches: matches2,
        isDataRoute: true
      },
      onError
    }) : getChildren();
  }, null);
}
function getDataRouterConsoleError(hookName) {
  return `${hookName} must be used within a data router.  See
https://reactrouter.com/en/main/routers/picking-a-router.`;
}
function useDataRouterContext(hookName) {
  let ctx = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  invariant(ctx, getDataRouterConsoleError(hookName));

  return ctx;
}
function useDataRouterState(hookName) {
  let state = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterStateContext);
  invariant(state, getDataRouterConsoleError(hookName));
  return state;
}
function useRouteContext(hookName) {
  let route = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  invariant(route, getDataRouterConsoleError(hookName));
  return route;
}
function useCurrentRouteId(hookName) {
  let route = useRouteContext(hookName);
  let thisRoute = route.matches[route.matches.length - 1];
  invariant(thisRoute.route.id, `${hookName} can only be used on routes that contain a unique "id"`);
  return thisRoute.route.id;
}
function useRouteId() {
  return useCurrentRouteId("useRouteId" /* UseRouteId */);
}
function useNavigation() {
  let state = useDataRouterState("useNavigation" /* UseNavigation */);
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
```

```
    let {
      matches,
      historyAction,
      ...rest
    } = state.navigation;
    return rest;
  }, [state.navigation]);
}
function useRevalidator() {
  let dataRouterContext = useDataRouterContext("useRevalidator" /* UseRevalidator */);
  let state = useDataRouterState("useRevalidator" /* UseRevalidator */);
  let revalidate = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(async () => {
    await dataRouterContext.router.revalidate();
  }, [dataRouterContext.router]);
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    revalidate,
    state: state.revalidation
  }), [revalidate, state.revalidation]);
}
function useMatches() {
  let {
    matches,
    loaderData
  } = useDataRouterState("useMatches" /* UseMatches */);
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => matches.map(m =>
convertRouteMatchToUiMatch(m, loaderData)), [matches, loaderData]);
}
function useLoaderData() {
  let state = useDataRouterState("useLoaderData" /* UseLoaderData */);
  let routeId = useCurrentRouteId("useLoaderData" /* UseLoaderData */);
  return state.loaderData[routeId];
}
function useRouteLoaderData(routeId) {
  let state = useDataRouterState("useRouteLoaderData" /* UseRouteLoaderData */);
  return state.loaderData[routeId];
}
function useActionData() {
  let state = useDataRouterState("useActionData" /* UseActionData */);
  let routeId = useCurrentRouteId("useLoaderData" /* UseLoaderData */);
  return state.actionData ? state.actionData[routeId] : void 0;
}
function useRouteError() {
  let error = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteErrorContext);
  let state = useDataRouterState("useRouteError" /* UseRouteError */);
  let routeId = useCurrentRouteId("useRouteError" /* UseRouteError */);
  if (error !== void 0) {
    return error;
  }
  return state.errors?.[routeId];
```

```
}
function useAsyncValue() {
  let value = react__WEBPACK_IMPORTED_MODULE_0__.useContext(AwaitContext);
  return value?._data;
}
function useAsyncError() {
  let value = react__WEBPACK_IMPORTED_MODULE_0__.useContext(AwaitContext);
  return value?._error;
}
var blockerId = 0;
function useBlocker(shouldBlock) {
  let {
    router,
    basename
  } = useDataRouterContext("useBlocker" /* UseBlocker */);
  let state = useDataRouterState("useBlocker" /* UseBlocker */);
  let [blockerKey, setBlockerKey] = react__WEBPACK_IMPORTED_MODULE_0__.useState("");
  let blockerFunction = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(arg => {
    if (typeof shouldBlock !== "function") {
      return !!shouldBlock;
    }
    if (basename === "/") {
      return shouldBlock(arg);
    }
    let {
      currentLocation,
      nextLocation,
      historyAction
    } = arg;
    return shouldBlock({
      currentLocation: {
        ...currentLocation,
        pathname: stripBasename(currentLocation.pathname, basename) || currentLocation.pathname
      },
      nextLocation: {
        ...nextLocation,
        pathname: stripBasename(nextLocation.pathname, basename) || nextLocation.pathname
      },
      historyAction
    });
  }, [basename, shouldBlock]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    let key = String(++blockerId);
    setBlockerKey(key);
    return () => router.deleteBlocker(key);
  }, [router]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (blockerKey !== "") {
      router.getBlocker(blockerKey, blockerFunction);
```

```
    }
  }, [router, blockerKey, blockerFunction]);
  return blockerKey && state.blockers.has(blockerKey) ? state.blockers.get(blockerKey) :
IDLE_BLOCKER;
}
function useNavigateStable() {
  let {
    router
  } = useDataRouterContext("useNavigate" /* UseNavigateStable */);
  let id = useCurrentRouteId("useNavigate" /* UseNavigateStable */);
  let activeRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(false);
  useIsomorphicLayoutEffect(() => {
    activeRef.current = true;
  });
  let navigate = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(async (to, options = {})
=> {
    warning(activeRef.current, navigateEffectWarning);
    if (!activeRef.current) return;
    if (typeof to === "number") {
      await router.navigate(to);
    } else {
      await router.navigate(to, {
        fromRouteId: id,
        ...options
      });
    }
  }, [router, id]);
  return navigate;
}
var alreadyWarned = {};
function warningOnce(key, cond, message) {
  if (!cond && !alreadyWarned[key]) {
    alreadyWarned[key] = true;
    warning(false, message);
  }
}
function useRoute(...args) {
  const currentRouteId = useCurrentRouteId("useRoute" /* UseRoute */);
  const id = args[0] ?? currentRouteId;
  const state = useDataRouterState("useRoute" /* UseRoute */);
  const route = state.matches.find(({
    route: route2
  }) => route2.id === id);
  if (route === void 0) return void 0;
  return {
    handle: route.route.handle,
    loaderData: state.loaderData[id],
    actionData: state.actionData?.[id]
  };
```

```
}
function toRouterStateMatch(match) {
  return {
    id: match.route.id,
    pathname: match.pathname,
    params: match.params,
    handle: match.route.handle
  };
}
function useRouterState() {
  let {
    location,
    historyAction: type,
    matches,
    navigation
  } = useDataRouterState("unstable_useRouterState" /* UseRouterState */);
  let active = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    type,
    location,
    searchParams: new URLSearchParams(location.search),
    params: matches[matches.length - 1]?.params ?? {},
    matches: matches.map(m => toRouterStateMatch(m))
  }), [location, matches, type]);
  let pending = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    if (navigation.state === "idle") return null;
    let shared = {
      type: navigation.historyAction,
      location: navigation.location,
      searchParams: new URLSearchParams(navigation.location.search),
      params: navigation.matches[navigation.matches.length - 1]?.params ?? {},
      matches: navigation.matches.map(m => toRouterStateMatch(m))
    };
    return navigation.state === "loading" ? {
      ...shared,
      state: "loading",
      formMethod: navigation.formMethod,
      formAction: navigation.formAction,
      formEncType: navigation.formEncType,
      formData: navigation.formData,
      json: navigation.json,
      text: navigation.text
    } : {
      ...shared,
      state: "submitting",
      formMethod: navigation.formMethod,
      formAction: navigation.formAction,
      formEncType: navigation.formEncType,
      formData: navigation.formData,
      json: navigation.json,
```

```
      text: navigation.text
    };
  }, [navigation]);
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    active,
    pending
  }), [active, pending]);
}

// lib/components.tsx


// lib/server-runtime/warnings.ts
var alreadyWarned2 = {};
function warnOnce(condition, message) {
  if (!condition && !alreadyWarned2[message]) {
    alreadyWarned2[message] = true;
    console.warn(message);
  }
}

// lib/components.tsx
var USE_OPTIMISTIC = "useOptimistic";
var useOptimisticImpl = /*#__PURE__*/
(react__WEBPACK_IMPORTED_MODULE_0___namespace_cache ||
(react__WEBPACK_IMPORTED_MODULE_0___namespace_cache =
__webpack_require__.t(react__WEBPACK_IMPORTED_MODULE_0__, 2)))[USE_OPTIMISTIC];
var stableUseOptimisticSetter = () => void 0;
function useOptimisticSafe(val) {
  if (useOptimisticImpl) {
    return useOptimisticImpl(val);
  } else {
    return [val, stableUseOptimisticSetter];
  }
}
function mapRouteProperties(route) {
  let updates = {
    // Note: this check also occurs in createRoutesFromChildren so update
    // there if you change this -- please and thank you!
    hasErrorBoundary: route.hasErrorBoundary || route.ErrorBoundary != null || route.errorElement !=
null
  };
  if (route.Component) {
    if (ENABLE_DEV_WARNINGS) {
      if (route.element) {
        warning(false, "You should not include both `Component` and `element` on your route -
`Component` will be used.");
      }
    }
```

```
    Object.assign(updates, {
      element: react__WEBPACK_IMPORTED_MODULE_0__.createElement(route.Component),
      Component: void 0
    });
  }
  if (route.HydrateFallback) {
    if (ENABLE_DEV_WARNINGS) {
      if (route.hydrateFallbackElement) {
        warning(false, "You should not include both `HydrateFallback` and `hydrateFallbackElement` on
your route - `HydrateFallback` will be used.");
      }
    }
    Object.assign(updates, {
      hydrateFallbackElement:
react__WEBPACK_IMPORTED_MODULE_0__.createElement(route.HydrateFallback),
      HydrateFallback: void 0
    });
  }
  if (route.ErrorBoundary) {
    if (ENABLE_DEV_WARNINGS) {
      if (route.errorElement) {
        warning(false, "You should not include both `ErrorBoundary` and `errorElement` on your route -
`ErrorBoundary` will be used.");
      }
    }
    Object.assign(updates, {
      errorElement:
react__WEBPACK_IMPORTED_MODULE_0__.createElement(route.ErrorBoundary),
      ErrorBoundary: void 0
    });
  }
  return updates;
}
var hydrationRouteProperties = ["HydrateFallback",
 "hydrateFallbackElement"];
function createMemoryRouter(routes, opts) {
  return createRouter({
    basename: opts?.basename,
    getContext: opts?.getContext,
    future: opts?.future,
    history: createMemoryHistory({
      initialEntries: opts?.initialEntries,
      initialIndex: opts?.initialIndex
    }),
    hydrationData: opts?.hydrationData,
    routes,
    hydrationRouteProperties,
    mapRouteProperties,
    dataStrategy: opts?.dataStrategy,
```

```
    patchRoutesOnNavigation: opts?.patchRoutesOnNavigation,
    instrumentations: opts?.instrumentations
  }).initialize();
}
var Deferred = class {
  constructor() {
    this.status = "pending";
    this.promise = new Promise((resolve, reject) => {
      this.resolve = value => {
        if (this.status === "pending") {
          this.status = "resolved";
          resolve(value);
        }
      };
      this.reject = reason => {
        if (this.status === "pending") {
          this.status = "rejected";
          reject(reason);
        }
      };
    });
  }
};
function RouterProvider({
  router,
  flushSync: reactDomFlushSyncImpl,
  onError,
  useTransitions
}) {
  let unstable_rsc = useIsRSCRouterContext();
  useTransitions = unstable_rsc || useTransitions;
  let [_state, setStateImpl] = react__WEBPACK_IMPORTED_MODULE_0__.useState(router.state);
  let [state, setOptimisticState] = useOptimisticSafe(_state);
  let [pendingState, setPendingState] = react__WEBPACK_IMPORTED_MODULE_0__.useState();
  let [vtContext, setVtContext] = react__WEBPACK_IMPORTED_MODULE_0__.useState({
    isTransitioning: false
  });
  let [renderDfd, setRenderDfd] = react__WEBPACK_IMPORTED_MODULE_0__.useState();
  let [transition, setTransition] = react__WEBPACK_IMPORTED_MODULE_0__.useState();
  let [interruption, setInterruption] = react__WEBPACK_IMPORTED_MODULE_0__.useState();
  let fetcherData = react__WEBPACK_IMPORTED_MODULE_0__.useRef(/* @__PURE__ */new
Map());
  let setState = react__WEBPACK_IMPORTED_MODULE_0__.useCallback((newState, {
    deletedFetchers,
    newErrors,
    flushSync,
    viewTransitionOpts
  }) => {
    if (newErrors && onError) {
```

```
    Object.values(newErrors).forEach(error => onError(error, {
      location: newState.location,
      params: newState.matches[0]?.params ?? {},
      pattern: getRoutePattern(newState.matches)
    }));
  }
  newState.fetchers.forEach((fetcher, key) => {
    if (fetcher.data !== void 0) {
      fetcherData.current.set(key, fetcher.data);
    }
  });
  deletedFetchers.forEach(key => fetcherData.current.delete(key));
  warnOnce(flushSync === false || reactDomFlushSyncImpl != null, 'You provided the `flushSync` option to a router update, but you are not using the `<RouterProvider>` from `react-router/dom` so `ReactDOM.flushSync()` is unavailable.  Please update your app to `import { RouterProvider } from "react-router/dom"` and ensure you have `react-dom` installed as a dependency to use the `flushSync` option.');
  let isViewTransitionAvailable = router.window != null && router.window.document != null && typeof router.window.document.startViewTransition === "function";
  warnOnce(viewTransitionOpts == null || isViewTransitionAvailable, "You provided the `viewTransition` option to a router update, but you do not appear to be running in a DOM environment as `window.startViewTransition` is not available.");
  if (!viewTransitionOpts || !isViewTransitionAvailable) {
    if (reactDomFlushSyncImpl && flushSync) {
      reactDomFlushSyncImpl(() => setStateImpl(newState));
    } else if (useTransitions === false) {
      setStateImpl(newState);
    } else {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => {
        if (useTransitions === true) {
          setOptimisticState(s => getOptimisticRouterState(s, newState));
        }
        setStateImpl(newState);
      });
    }
    return;
  }
  if (reactDomFlushSyncImpl && flushSync) {
    reactDomFlushSyncImpl(() => {
      if (transition) {
        renderDfd?.resolve();
        transition.skipTransition();
      }
      setVtContext({
        isTransitioning: true,
        flushSync: true,
        currentLocation: viewTransitionOpts.currentLocation,
        nextLocation: viewTransitionOpts.nextLocation
      });
```

```
      });
      let t = router.window.document.startViewTransition(() => {
        reactDomFlushSyncImpl(() => setStateImpl(newState));
      });
      t.finished.finally(() => {
        reactDomFlushSyncImpl(() => {
          setRenderDfd(void 0);
          setTransition(void 0);
          setPendingState(void 0);
          setVtContext({
            isTransitioning: false
          });
        });
      });
      reactDomFlushSyncImpl(() => setTransition(t));
      return;
    }
    if (transition) {
      renderDfd?.resolve();
      transition.skipTransition();
      setInterruption({
        state: newState,
        currentLocation: viewTransitionOpts.currentLocation,
        nextLocation: viewTransitionOpts.nextLocation
      });
    } else {
      setPendingState(newState);
      setVtContext({
        isTransitioning: true,
        flushSync: false,
        currentLocation: viewTransitionOpts.currentLocation,
        nextLocation: viewTransitionOpts.nextLocation
      });
    }
  }, [router.window, reactDomFlushSyncImpl, transition, renderDfd, useTransitions, setOptimisticState,
onError]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => router.subscribe(setState),
[router, setState]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (vtContext.isTransitioning && !vtContext.flushSync) {
      setRenderDfd(new Deferred());
    }
  }, [vtContext]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (renderDfd && pendingState && router.window) {
      let newState = pendingState;
      let renderPromise = renderDfd.promise;
      let transition2 = router.window.document.startViewTransition(async () => {
        if (useTransitions === false) {
```

```
        setStateImpl(newState);
      } else {
        react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => {
          if (useTransitions === true) {
            setOptimisticState(s => getOptimisticRouterState(s, newState));
          }
          setStateImpl(newState);
        });
      }
      await renderPromise;
    });
    transition2.finished.finally(() => {
      setRenderDfd(void 0);
      setTransition(void 0);
      setPendingState(void 0);
      setVtContext({
        isTransitioning: false
      });
    });
    setTransition(transition2);
  }
}, [pendingState, renderDfd, router.window, useTransitions, setOptimisticState]);
react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
  if (renderDfd && pendingState && state.location.key === pendingState.location.key) {
    renderDfd.resolve();
  }
}, [renderDfd, transition, state.location, pendingState]);
react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
  if (!vtContext.isTransitioning && interruption) {
    setPendingState(interruption.state);
    setVtContext({
      isTransitioning: true,
      flushSync: false,
      currentLocation: interruption.currentLocation,
      nextLocation: interruption.nextLocation
    });
    setInterruption(void 0);
  }
}, [vtContext.isTransitioning, interruption]);
let navigator = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
  return {
    createHref: router.createHref,
    encodeLocation: router.encodeLocation,
    go: n => router.navigate(n),
    push: (to, state2, opts) => router.navigate(to, {
      state: state2,
      preventScrollReset: opts?.preventScrollReset
    }),
    replace: (to, state2, opts) => router.navigate(to, {
```

```
        replace: true,
        state: state2,
        preventScrollReset: opts?.preventScrollReset
      })
    };
  }, [router]);
  let basename = router.basename || "/";
  let dataRouterContext = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    router,
    navigator,
    static: false,
    basename,
    onError
  }), [router, navigator, basename, onError]);
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(DataRouterContext.Provider, {
    value: dataRouterContext
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(DataRouterStateContext.Provider,
{
    value: state
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(FetchersContext.Provider, {
    value: fetcherData.current
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(ViewTransitionContext.Provider, {
    value: vtContext
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
    location: state.location,
    navigationType: state.historyAction,
    navigator,
    useTransitions
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(MemoizedDataRoutes, {
    routes: router.routes,
    manifest: router.manifest,
    future: router.future,
    state,
    isStatic: false,
    onError
  }))))), null);
}
function getOptimisticRouterState(currentState, newState) {
  return {
    // Don't surface "current location specific" stuff mid-navigation
    // (historyAction, location, matches, loaderData, errors, initialized,
```

```
    // restoreScroll, preventScrollReset, blockers, etc.)
    ...currentState,
    // Only surface "pending/in-flight stuff"
    // (navigation, revalidation, actionData, fetchers, )
    navigation: newState.navigation.state !== "idle" ? newState.navigation : currentState.navigation,
    revalidation: newState.revalidation !== "idle" ? newState.revalidation : currentState.revalidation,
    actionData: newState.navigation.state !== "submitting" ? newState.actionData :
currentState.actionData,

    fetchers: newState.fetchers
  };
}
var MemoizedDataRoutes = react__WEBPACK_IMPORTED_MODULE_0__.memo(DataRoutes2);
function DataRoutes2({
  routes,
  manifest,
  future,
  state,
  isStatic,
  onError
}) {
  return useRoutesImpl(routes, void 0, {
    manifest,
    state,
    isStatic,
    onError,
    future
  });
}
function MemoryRouter({
  basename,
  children,
  initialEntries,
  initialIndex,
  useTransitions
}) {
  let historyRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef();
  if (historyRef.current == null) {
    historyRef.current = createMemoryHistory({
      initialEntries,
      initialIndex,
      v5Compat: true
    });
  }
  let history = historyRef.current;
  let [state, setStateImpl] = react__WEBPACK_IMPORTED_MODULE_0__.useState({
    action: history.action,
    location: history.location
  });
```

```
  let setState = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(newState => {
    if (useTransitions === false) {
      setStateImpl(newState);
    } else {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => setStateImpl(newState));
    }
  }, [useTransitions]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => history.listen(setState),
[history, setState]);
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
    children,
    location: state.location,
    navigationType: state.action,
    navigator: history,
    useTransitions
  });
}
function Navigate({
  to,
  replace: replace2,
  state,
  relative
}) {
  invariant(useInRouterContext(),
  // TODO: This error is probably because they somehow have 2 versions of
  // the router loaded. We can help them understand how to avoid that.
  `<Navigate> may be used only in the context of a <Router> component.`);
  let {
    static: isStatic
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  warning(!isStatic, `<Navigate> must not be used on the initial render in a <StaticRouter>. This is a
no-op, but you should modify your code so the <Navigate> is only ever rendered in response to some
user interaction or state change.`);
  let {
    matches
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  let {
    pathname: locationPathname
  } = useLocation();
  let navigate = useNavigate();
  let path = resolveTo(to, getResolveToMatches(matches), locationPathname, relative === "path");
  let jsonPath = JSON.stringify(path);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    navigate(JSON.parse(jsonPath), {
      replace: replace2,
      state,
      relative
    });
```

```
  }, [navigate, jsonPath, relative, replace2, state]);
  return null;
}
function Outlet(props) {
  return useOutlet(props.context);
}
function Route(props) {
  invariant(false, `A <Route> is only ever to be used as the child of <Routes> element, never rendered directly. Please wrap your <Route> in a <Routes>.`);
}
function Router({
  basename: basenameProp = "/",
  children = null,
  location: locationProp,
  navigationType = "POP" /* Pop */,
  navigator,
  static: staticProp = false,
  useTransitions
}) {
  invariant(!useInRouterContext(), `You cannot render a <Router> inside another <Router>. You should never have more than one in your app.`);
  let basename = basenameProp.replace(/^\/*/, "/");
  let navigationContext = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    basename,
    navigator,
    static: staticProp,
    useTransitions,
    future: {}
  }), [basename, navigator, staticProp, useTransitions]);
  if (typeof locationProp === "string") {
    locationProp = parsePath(locationProp);
  }
  let {
    pathname = "/",
    search = "",
    hash = "",
    state = null,
    key = "default",
    mask
  } = locationProp;
  let locationContext = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    let trailingPathname = stripBasename(pathname, basename);
    if (trailingPathname == null) {
      return null;
    }
    return {
      location: {
        pathname: trailingPathname,
        search,
```

```
        hash,
        state,
        key,
        mask
      },
      navigationType
    };
  }, [basename, pathname, search, hash, state, key, navigationType, mask]);
  warning(locationContext != null, `<Router basename="${basename}"> is not able to match the URL
"${pathname}${search}${hash}" because it does not start with the basename, so the <Router> won't
render anything.`);
  if (locationContext == null) {
    return null;
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(NavigationContext.Provider, {
    value: navigationContext
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(LocationContext.Provider, {
    children,
    value: locationContext
  }));
}
function Routes({
  children,
  location
}) {
  return useRoutes(createRoutesFromChildren(children), location);
}
function Await({
  children,
  errorElement,
  resolve
}) {
  let dataRouterContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  let dataRouterStateContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterStateContext);
  let onError = react__WEBPACK_IMPORTED_MODULE_0__.useCallback((error, errorInfo) => {
    if (dataRouterContext && dataRouterContext.onError && dataRouterStateContext) {
      dataRouterContext.onError(error, {
        location: dataRouterStateContext.location,
        params: dataRouterStateContext.matches[0]?.params || {},
        pattern: getRoutePattern(dataRouterStateContext.matches),
        errorInfo
      });
    }
  }, [dataRouterContext, dataRouterStateContext]);
  return /* @__PURE__
```

```
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(AwaitErrorBoundary, {
    resolve,
    errorElement,
    onError
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(ResolveAwait,
null, children));
}
var AwaitErrorBoundary = class extends react__WEBPACK_IMPORTED_MODULE_0__.Component
{
  constructor(props) {
    super(props);
    this.state = {
      error: null
    };
  }
  static getDerivedStateFromError(error) {
    return {
      error
    };
  }
  componentDidCatch(error, errorInfo) {
    if (this.props.onError) {
      this.props.onError(error, errorInfo);
    } else {
      console.error("<Await> caught the following error during render", error, errorInfo);
    }
  }
  render() {
    let {
      children,
      errorElement,
      resolve
    } = this.props;
    let promise = null;
    let status = 0 /* pending */;
    if (!(resolve instanceof Promise)) {
      status = 1 /* success */;
      promise = Promise.resolve();
      Object.defineProperty(promise, "_tracked", {
        get: () => true
      });
      Object.defineProperty(promise, "_data", {
        get: () => resolve
      });
    } else if (this.state.error) {
      status = 2 /* error */;
      let renderError = this.state.error;
      promise = Promise.reject().catch(() => {});
      Object.defineProperty(promise, "_tracked", {
```

```
      get: () => true
    });
    Object.defineProperty(promise, "_error", {
      get: () => renderError
    });
  } else if (resolve._tracked) {
    promise = resolve;
    status = "_error" in promise ? 2 /* error */ : "_data" in promise ? 1 /* success */ : 0 /* pending */;
  } else {
    status = 0 /* pending */;
    Object.defineProperty(resolve, "_tracked", {
      get: () => true
    });
    promise = resolve.then(data2 => Object.defineProperty(resolve, "_data", {
      get: () => data2
    }), error => {
      this.props.onError?.(error);
      Object.defineProperty(resolve, "_error", {
        get: () => error
      });
    });
  }
  if (status === 2 /* error */ && !errorElement) {
    throw promise._error;
  }
  if (status === 2 /* error */) {
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(AwaitContext.Provider, {
      value: promise,
      children: errorElement
    });
  }
  if (status === 1 /* success */) {
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(AwaitContext.Provider, {
      value: promise,
      children
    });
  }
  throw promise;
 }
};
function ResolveAwait({
 children
}) {
 let data2 = useAsyncValue();
 let toRender = typeof children === "function" ? children(data2) : children;
 return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
```

```
MODULE_0__.Fragment, null, toRender);
}
function createRoutesFromChildren(children, parentPath = []) {
  let routes = [];
  react__WEBPACK_IMPORTED_MODULE_0__.Children.forEach(children, (element, index) => {
    if (!react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(element)) {
      return;
    }
    let treePath = [...parentPath, index];
    if (element.type === react__WEBPACK_IMPORTED_MODULE_0__.Fragment) {
      routes.push.apply(routes, createRoutesFromChildren(element.props.children, treePath));
      return;
    }
    invariant(element.type === Route, `[${typeof element.type === "string" ? element.type :
element.type.name}] is not a <Route> component. All component children of <Routes> must be a
<Route> or <React.Fragment>`);
    invariant(!element.props.index || !element.props.children, "An index route cannot have child
routes.");
    let route = {
      id: element.props.id || treePath.join("-"),
      caseSensitive: element.props.caseSensitive,
      element: element.props.element,
      Component: element.props.Component,
      index: element.props.index,
      path: element.props.path,
      middleware: element.props.middleware,
      loader: element.props.loader,
      action: element.props.action,
      hydrateFallbackElement: element.props.hydrateFallbackElement,
      HydrateFallback: element.props.HydrateFallback,
      errorElement: element.props.errorElement,
      ErrorBoundary: element.props.ErrorBoundary,
      hasErrorBoundary: element.props.hasErrorBoundary === true || element.props.ErrorBoundary
 != null || element.props.errorElement != null,
      shouldRevalidate: element.props.shouldRevalidate,
      handle: element.props.handle,
      lazy: element.props.lazy
    };
    if (element.props.children) {
      route.children = createRoutesFromChildren(element.props.children, treePath);
    }
    routes.push(route);
  });
  return routes;
}
var createRoutesFromElements = createRoutesFromChildren;
function renderMatches(matches) {
  return _renderMatches(matches);
}
```

```
function useRouteComponentProps() {
  return {
    params: useParams(),
    loaderData: useLoaderData(),
    actionData: useActionData(),
    matches: useMatches()
  };
}
function WithComponentProps({
  children
}) {
  const props = useRouteComponentProps();
  return react__WEBPACK_IMPORTED_MODULE_0__.cloneElement(children, props);
}
function withComponentProps(Component4) {
  return function WithComponentProps2() {
    const props = useRouteComponentProps();
    return react__WEBPACK_IMPORTED_MODULE_0__.createElement(Component4, props);
  };
}
function useHydrateFallbackProps() {
  return {
    params: useParams(),
    loaderData: useLoaderData(),
    actionData: useActionData()
  };
}
function WithHydrateFallbackProps({
  children
}) {
  const props = useHydrateFallbackProps();
  return react__WEBPACK_IMPORTED_MODULE_0__.cloneElement(children, props);
}
function withHydrateFallbackProps(HydrateFallback) {
  return function WithHydrateFallbackProps2() {
    const props = useHydrateFallbackProps();
    return react__WEBPACK_IMPORTED_MODULE_0__.createElement(HydrateFallback, props);
  };
}
function useErrorBoundaryProps() {
  return {
    params: useParams(),
    loaderData: useLoaderData(),
    actionData: useActionData(),
    error: useRouteError()
  };
}
function WithErrorBoundaryProps({
  children
```

```
}) {
  const props = useErrorBoundaryProps();
  return react__WEBPACK_IMPORTED_MODULE_0__.cloneElement(children, props);
}
function withErrorBoundaryProps(ErrorBoundary) {
  return function WithErrorBoundaryProps2() {
    const props = useErrorBoundaryProps();
    return react__WEBPACK_IMPORTED_MODULE_0__.createElement(ErrorBoundary, props);
  };
}

// lib/dom/dom.ts
var defaultMethod = "get";
var defaultEncType = "application/x-www-form-urlencoded";
function isHtmlElement(object) {
  return typeof HTMLElement !== "undefined" && object instanceof HTMLElement;
}
function isButtonElement(object) {
  return isHtmlElement(object) && object.tagName.toLowerCase() === "button";
}
function isFormElement(object) {
  return isHtmlElement(object) && object.tagName.toLowerCase() === "form";
}
function isInputElement(object) {
  return isHtmlElement(object) && object.tagName.toLowerCase() === "input";
}
function isModifiedEvent(event) {
  return !!(event.metaKey || event.altKey || event.ctrlKey || event.shiftKey);
}
function shouldProcessLinkClick(event, target) {
  return event.button === 0 && (
  // Ignore everything but left clicks
  !target || target === "_self") &&
  // Let browser handle "target=_blank" etc.
  !isModifiedEvent(event);
}
function createSearchParams(init = "") {
  return new URLSearchParams(typeof init === "string" || Array.isArray(init) || init instanceof
URLSearchParams ? init : Object.keys(init).reduce((memo2, key) => {
    let value = init[key];
    return memo2.concat(Array.isArray(value) ? value.map(v => [key, v]) : [[key, value]]);
  }, []));
}
function getSearchParamsForLocation(locationSearch, defaultSearchParams) {
  let searchParams = createSearchParams(locationSearch);
  if (defaultSearchParams) {
    defaultSearchParams.forEach((_, key) => {
      if (!searchParams.has(key)) {
        defaultSearchParams.getAll(key).forEach(value => {
```

```
          searchParams.append(key, value);
        });
      }
    });
  }
  return searchParams;
}
var _formDataSupportsSubmitter = null;
function isFormDataSubmitterSupported() {
  if (_formDataSupportsSubmitter === null) {
    try {
      new FormData(document.createElement("form"),
      // @ts-expect-error if FormData supports the submitter parameter, this will throw
      0);
      _formDataSupportsSubmitter = false;
    } catch (e) {
      _formDataSupportsSubmitter = true;
    }
  }
  return _formDataSupportsSubmitter;
}
var supportedFormEncTypes = /* @__PURE__ */new Set(["application/x-www-form-urlencoded",
"multipart/form-data", "text/plain"]);
function getFormEncType(encType) {
  if (encType != null && !supportedFormEncTypes.has(encType)) {
    warning(false, `"${encType}" is not a valid \`encType\` for \`<Form>\`/\`<fetcher.Form>\` and will
default to "${defaultEncType}"`);
    return null;
  }
  return encType;
}
function getFormSubmissionInfo(target, basename) {
  let method;
  let action;
  let encType;
  let formData;
  let body;
  if (isFormElement(target)) {
    let attr = target.getAttribute("action");
    action = attr ? stripBasename(attr, basename) : null;
    method = target.getAttribute("method") || defaultMethod;
    encType = getFormEncType(target.getAttribute("enctype")) || defaultEncType;
    formData = new FormData(target);
  } else if (isButtonElement(target) || isInputElement(target) && (target.type === "submit" || target.type
=== "image")) {
    let form = target.form;
    if (form == null) {
      throw new Error(`Cannot submit a <button> or <input type="submit"> without a <form>`);
    }
```

```
    let attr = target.getAttribute("formaction") || form.getAttribute("action");
    action = attr ? stripBasename(attr, basename) : null;
    method = target.getAttribute("formmethod") || form.getAttribute("method") || defaultMethod;
    encType = getFormEncType(target.getAttribute("formenctype")) ||
getFormEncType(form.getAttribute("enctype")) || defaultEncType;
    formData = new FormData(form, target);
    if (!isFormDataSubmitterSupported()) {
      let {
        name,
        type,
        value
      } = target;
      if (type === "image") {
        let prefix = name ? `${name}.` : "";
        formData.append(`${prefix}x`, "0");
        formData.append(`${prefix}y`, "0");
      } else if (name) {
        formData.append(name, value);
      }
    }
  } else if (isHtmlElement(target)) {
    throw new Error(`Cannot submit element that is not <form>, <button>, or <input type="submit|
image">`);
  } else {
    method = defaultMethod;
    action = null;
    encType = defaultEncType;
    body = target;
  }
  if (formData && encType === "text/plain") {
    body = formData;
    formData = void 0;
  }
  return {
    action,
    method: method.toLowerCase(),
    encType,
    formData,
    body
  };
}

// lib/dom/ssr/single-fetch.tsx


// vendor/turbo-stream-v2/utils.ts
var HOLE = -1;
var NAN = -2;
var NEGATIVE_INFINITY = -3;
```

```
var NEGATIVE_ZERO = -4;
var NULL = -5;
var POSITIVE_INFINITY = -6;
var UNDEFINED = -7;
var TYPE_BIGINT = "B";
var TYPE_DATE = "D";
var TYPE_ERROR = "E";
var TYPE_MAP = "M";
var TYPE_NULL_OBJECT = "N";
var TYPE_PROMISE = "P";
var TYPE_REGEXP = "R";
var TYPE_SET = "S";
var TYPE_SYMBOL = "Y";
var TYPE_URL = "U";
var TYPE_PREVIOUS_RESOLVED = "Z";
var SUPPORTED_ERROR_TYPES = ["EvalError", "RangeError", "ReferenceError", "SyntaxError",
"TypeError", "URIError"];
var Deferred2 = class {
  constructor() {
    this.promise = new Promise((resolve, reject) => {
      this.resolve = resolve;
      this.reject = reject;
    });
  }
};
function createLineSplittingTransform() {
  const decoder = new TextDecoder();
  let leftover = "";
  return new TransformStream({
    transform(chunk, controller) {
      const str = decoder.decode(chunk, {
        stream: true
      });
      const parts = (leftover + str).split("\n");
      leftover = parts.pop() || "";
      for (const part of parts) {
        controller.enqueue(part);
      }
    },
    flush(controller) {
      if (leftover) {
        controller.enqueue(leftover);
      }
    }
  });
}

// vendor/turbo-stream-v2/flatten.ts
var TIME_LIMIT_MS = 1;
```

```
var getNow = () => Date.now();
var yieldToMain = () => new Promise(resolve => setTimeout(resolve, 0));
async function flatten(input) {
  const {
    indices
  } = this;
  const existing = indices.get(input);
  if (existing) return [existing];
  if (input === void 0) return UNDEFINED;
  if (input === null) return NULL;
  if (Number.isNaN(input)) return NAN;
  if (input === Number.POSITIVE_INFINITY) return POSITIVE_INFINITY;
  if (input === Number.NEGATIVE_INFINITY) return NEGATIVE_INFINITY;
  if (input === 0 && 1 / input < 0) return NEGATIVE_ZERO;
  const index = this.index++;
  indices.set(input, index);
  const stack = [[input, index]];
  await stringify.call(this, stack);
  return index;
}
async function stringify(stack) {
  const {
    deferred,
    indices,
    plugins,
    postPlugins
  } = this;
  const str = this.stringified;
  let lastYieldTime = getNow();
  const flattenValue = value => {
    const existing = indices.get(value);
    if (existing) return [existing];
    if (value === void 0) return UNDEFINED;
    if (value === null) return NULL;
    if (Number.isNaN(value)) return NAN;
    if (value === Number.POSITIVE_INFINITY) return POSITIVE_INFINITY;
    if (value === Number.NEGATIVE_INFINITY) return NEGATIVE_INFINITY;
    if (value === 0 && 1 / value < 0) return NEGATIVE_ZERO;
    const index = this.index++;
    indices.set(value, index);
    stack.push([value, index]);
    return index;
  };
  let i = 0;
  while (stack.length > 0) {
    const now = getNow();
    if (++i % 6e3 === 0 && now - lastYieldTime >= TIME_LIMIT_MS) {
      await yieldToMain();
      lastYieldTime = getNow();
```

```
    }
    const [input, index] = stack.pop();
    const partsForObj = obj => Object.keys(obj).map(k => `"_${flattenValue(k)}":$
{flattenValue(obj[k])}`).join(",");
    let error = null;
    switch (typeof input) {
      case "boolean":
      case "number":
      case "string":
        str[index] = JSON.stringify(input);
        break;
      case "bigint":
        str[index] = `["${TYPE_BIGINT}","${input}"]`;

        break;
      case "symbol":
        {
          const keyFor = Symbol.keyFor(input);
          if (!keyFor) {
            error = new Error("Cannot encode symbol unless created with Symbol.for()");
          } else {
            str[index] = `["${TYPE_SYMBOL}",${JSON.stringify(keyFor)}]`;
          }
          break;
        }
      case "object":
        {
          if (!input) {
            str[index] = `${NULL}`;
            break;
          }
          const isArray = Array.isArray(input);
          let pluginHandled = false;
          if (!isArray && plugins) {
            for (const plugin of plugins) {
              const pluginResult = plugin(input);
              if (Array.isArray(pluginResult)) {
                pluginHandled = true;
                const [pluginIdentifier, ...rest] = pluginResult;
                str[index] = `[${JSON.stringify(pluginIdentifier)}`;
                if (rest.length > 0) {
                  str[index] += `,${rest.map(v => flattenValue(v)).join(",")}`;
                }
                str[index] += "]";
                break;
              }
            }
          }
          if (!pluginHandled) {
```

```
        let result = isArray ? "[" : "{";
        if (isArray) {
          for (let i2 = 0; i2 < input.length; i2++) result += (i2 ? "," : "") + (i2 in input ?
flattenValue(input[i2]) : HOLE);
          str[index] = `${result}]`;
        } else if (input instanceof Date) {
          const dateTime = input.getTime();
          str[index] = `["${TYPE_DATE}",${Number.isNaN(dateTime) ? JSON.stringify("invalid") :
dateTime}]`;
        } else if (input instanceof URL) {
          str[index] = `["${TYPE_URL}",${JSON.stringify(input.href)}]`;
        } else if (input instanceof RegExp) {
          str[index] = `["${TYPE_REGEXP}",${JSON.stringify(input.source)},$
{JSON.stringify(input.flags)}]`;
        } else if (input instanceof Set) {
          if (input.size > 0) {
            str[index] = `["${TYPE_SET}",${[...input].map(val => flattenValue(val)).join(",")}]`;
          } else {
            str[index] = `["${TYPE_SET}"]`;
          }
        } else if (input instanceof Map) {
          if (input.size > 0) {
            str[index] = `["${TYPE_MAP}",${[...input].flatMap(([k, v]) => [flattenValue(k),
flattenValue(v)]).join(",")}]`;
          } else {
            str[index] = `["${TYPE_MAP}"]`;
          }
        } else if (input instanceof Promise) {
          str[index] = `["${TYPE_PROMISE}",${index}]`;
          deferred[index] = input;
        } else if (input instanceof Error) {
          str[index] = `["${TYPE_ERROR}",${JSON.stringify(input.message)}`;
          if (input.name !== "Error") {
            str[index] += `,${JSON.stringify(input.name)}`;
          }
          str[index] += "]";
        } else if (Object.getPrototypeOf(input) === null) {
          str[index] = `["${TYPE_NULL_OBJECT}",{${partsForObj(input)}}]`;
        } else if (isPlainObject2(input)) {
          str[index] = `{${partsForObj(input)}}`;
        } else {
          error = new Error("Cannot encode object with prototype");
        }
      }
      break;
    }
  default:
    {
      const isArray = Array.isArray(input);
```

```
        let pluginHandled = false;
        if (!isArray && plugins) {
          for (const plugin of plugins) {
            const pluginResult = plugin(input);
            if (Array.isArray(pluginResult)) {
              pluginHandled = true;
              const [pluginIdentifier, ...rest] = pluginResult;
              str[index] = `[${JSON.stringify(pluginIdentifier)}`;
              if (rest.length > 0) {
                str[index] += `,${rest.map(v => flattenValue(v)).join(",")}`;
              }
              str[index] += "]";
              break;
            }
          }
        }
        if (!pluginHandled) {
          error = new Error("Cannot encode function or unexpected type");
        }
      }
    }
    if (error) {
      let pluginHandled = false;
      if (postPlugins) {
        for (const plugin of postPlugins) {
          const pluginResult = plugin(input);
          if (Array.isArray(pluginResult)) {
            pluginHandled = true;
            const [pluginIdentifier, ...rest] = pluginResult;
            str[index] = `[${JSON.stringify(pluginIdentifier)}`;
            if (rest.length > 0) {
              str[index] += `,${rest.map(v => flattenValue(v)).join(",")}`;
            }
            str[index] += "]";
            break;
          }
        }
      }
      if (!pluginHandled) {
        throw error;
      }
    }
  }
}
var objectProtoNames2 = Object.getOwnPropertyNames(Object.prototype).sort().join("\0");
function isPlainObject2(thing) {
  const proto = Object.getPrototypeOf(thing);
  return proto === Object.prototype || proto === null ||
Object.getOwnPropertyNames(proto).sort().join("\0") === objectProtoNames2;
```

```
}

// vendor/turbo-stream-v2/unflatten.ts
var globalObj = typeof window !== "undefined" ? window : typeof globalThis !== "undefined" ?
globalThis : void 0;
function unflatten(parsed) {
  const {
    hydrated,
    values
  } = this;
  if (typeof parsed === "number") return hydrate.call(this, parsed);
  if (!Array.isArray(parsed) || !parsed.length) throw new SyntaxError();
  const startIndex = values.length;
  for (const value of parsed) {
    values.push(value);
  }
  hydrated.length = values.length;
  return hydrate.call(this, startIndex);
}
function hydrate(index) {
  const {
    hydrated,
    values,
    deferred,
    plugins
  } = this;
  let result;
  const stack = [[index, v => {
    result = v;
  }]];
  let postRun = [];
  while (stack.length > 0) {
    const [index2, set] = stack.pop();
    switch (index2) {
      case UNDEFINED:
        set(void 0);
        continue;
      case NULL:
        set(null);
        continue;
      case NAN:
        set(NaN);
        continue;
      case POSITIVE_INFINITY:
        set(Infinity);
        continue;
      case NEGATIVE_INFINITY:
        set(-Infinity);
        continue;
```

```
  case NEGATIVE_ZERO:
    set(-0);
    continue;
}
if (hydrated[index2]) {
  set(hydrated[index2]);
  continue;
}
const value = values[index2];
if (!value || typeof value !== "object") {
  hydrated[index2] = value;
  set(value);
  continue;
}
if (Array.isArray(value)) {
  if (typeof value[0] === "string") {
    const [type, b, c] = value;
    switch (type) {
      case TYPE_DATE:
        set(hydrated[index2] = new Date(b));
        continue;
      case TYPE_URL:
        set(hydrated[index2] = new URL(b));
        continue;
      case TYPE_BIGINT:
        set(hydrated[index2] = BigInt(b));
        continue;
      case TYPE_REGEXP:
        set(hydrated[index2] = new RegExp(b, c));
        continue;
      case TYPE_SYMBOL:
        set(hydrated[index2] = Symbol.for(b));
        continue;
      case TYPE_SET:
        const newSet = /* @__PURE__ */new Set();
        hydrated[index2] = newSet;
        for (let i = value.length - 1; i > 0; i--) stack.push([value[i], v => {
          newSet.add(v);
        }]);
        set(newSet);
        continue;
      case TYPE_MAP:
        const map = /* @__PURE__ */new Map();
        hydrated[index2] = map;
        for (let i = value.length - 2; i > 0; i -= 2) {
          const r = [];
          stack.push([value[i + 1], v => {
            r[1] = v;
          }]);
```

```
            stack.push([value[i], k => {
              r[0] = k;
            }]);
            postRun.push(() => {
              map.set(r[0], r[1]);
            });
          }
          set(map);
          continue;
        case TYPE_NULL_OBJECT:
          const obj = /* @__PURE__ */Object.create(null);
          hydrated[index2] = obj;
          for (const key of Object.keys(b).reverse()) {
            const r = [];
            stack.push([b[key], v => {
              r[1] = v;
            }]);
            stack.push([Number(key.slice(1)), k => {
              r[0] = k;
            }]);
            postRun.push(() => {
              obj[r[0]] = r[1];
            });
          }
          set(obj);
          continue;
        case TYPE_PROMISE:
          if (hydrated[b]) {
            set(hydrated[index2] = hydrated[b]);
          } else {
            const d = new Deferred2();
            deferred[b] = d;
            set(hydrated[index2] = d.promise);
          }
          continue;
        case TYPE_ERROR:
          const [, message, errorType] = value;
          let error = errorType && globalObj && SUPPORTED_ERROR_TYPES.includes(errorType)
&& errorType in globalObj && typeof globalObj[errorType] === "function" ? new
globalObj[errorType](message) : new Error(message);
          hydrated[index2] = error;
          set(error);
          continue;
        case TYPE_PREVIOUS_RESOLVED:
          set(hydrated[index2] = hydrated[b]);
          continue;
        default:
          if (Array.isArray(plugins)) {
            const r = [];
```

```
        const vals = value.slice(1);
        for (let i = 0; i < vals.length; i++) {
          const v = vals[i];
          stack.push([v, v2 => {
            r[i] = v2;
          }]);
        }
        postRun.push(() => {
          for (const plugin of plugins) {
            const result2 = plugin(value[0], ...r);
            if (result2) {
              set(hydrated[index2] = result2.value);
              return;
            }

          }
          throw new SyntaxError();
        });
        continue;
      }
      throw new SyntaxError();
    }
  } else {
    const array = [];
    hydrated[index2] = array;
    for (let i = 0; i < value.length; i++) {
      const n = value[i];
      if (n !== HOLE) {
        stack.push([n, v => {
          array[i] = v;
        }]);
      }
    }
    set(array);
    continue;
  }
} else {
  const object = {};
  hydrated[index2] = object;
  for (const key of Object.keys(value).reverse()) {
    const r = [];
    stack.push([value[key], v => {
      r[1] = v;
    }]);
    stack.push([Number(key.slice(1)), k => {
      r[0] = k;
    }]);
    postRun.push(() => {
      object[r[0]] = r[1];
```

```
        });
      }
      set(object);
      continue;
    }
  }
  while (postRun.length > 0) {
    postRun.pop()();
  }
  return result;
}

// vendor/turbo-stream-v2/turbo-stream.ts
async function decode(readable, options) {
  const {
    plugins
  } = options ?? {};
  const done = new Deferred2();
  const reader = readable.pipeThrough(createLineSplittingTransform()).getReader();
  const decoder = {
    values: [],
    hydrated: [],
    deferred: {},
    plugins
  };
  const decoded = await decodeInitial.call(decoder, reader);
  let donePromise = done.promise;
  if (decoded.done) {
    done.resolve();
  } else {
    donePromise = decodeDeferred.call(decoder, reader).then(done.resolve).catch(reason => {
      for (const deferred of Object.values(decoder.deferred)) {
        deferred.reject(reason);
      }
      done.reject(reason);
    });
  }
  return {
    done: donePromise.then(() => reader.closed),
    value: decoded.value
  };
}
async function decodeInitial(reader) {
  const read = await reader.read();
  if (!read.value) {
    throw new SyntaxError();
  }
  let line;
  try {
```

```
    line = JSON.parse(read.value);
  } catch (reason) {
    throw new SyntaxError();
  }
  return {
    done: read.done,
    value: unflatten.call(this, line)
  };
}
async function decodeDeferred(reader) {
  let read = await reader.read();
  while (!read.done) {
    if (!read.value) continue;
    const line = read.value;
    switch (line[0]) {
      case TYPE_PROMISE:
        {
          const colonIndex = line.indexOf(":");
          const deferredId = Number(line.slice(1, colonIndex));
          const deferred = this.deferred[deferredId];
          if (!deferred) {
            throw new Error(`Deferred ID ${deferredId} not found in stream`);
          }
          const lineData = line.slice(colonIndex + 1);
          let jsonLine;
          try {
            jsonLine = JSON.parse(lineData);
          } catch (reason) {
            throw new SyntaxError();
          }
          const value = unflatten.call(this, jsonLine);
          deferred.resolve(value);
          break;
        }
      case TYPE_ERROR:
        {
          const colonIndex = line.indexOf(":");
          const deferredId = Number(line.slice(1, colonIndex));
          const deferred = this.deferred[deferredId];
          if (!deferred) {
            throw new Error(`Deferred ID ${deferredId} not found in stream`);
          }
          const lineData = line.slice(colonIndex + 1);
          let jsonLine;
          try {
            jsonLine = JSON.parse(lineData);
          } catch (reason) {
            throw new SyntaxError();
          }
```

```
          const value = unflatten.call(this, jsonLine);
          deferred.reject(value);
          break;
        }
      default:
        throw new SyntaxError();
    }
    read = await reader.read();
  }
}
function encode(input, options) {
  const {
    onComplete,
    plugins,
    postPlugins,
    signal
  } = options ?? {};
  const encoder = {
    deferred: {},
    index: 0,
    indices: /* @__PURE__ */new Map(),
    stringified: [],
    plugins,
    postPlugins,
    signal
  };
  const textEncoder = new TextEncoder();
  let lastSentIndex = 0;
  const readable = new ReadableStream({
    async start(controller) {
      const id = await flatten.call(encoder, input);
      if (Array.isArray(id)) {
        throw new Error("This should never happen");
      }
      if (id < 0) {
        controller.enqueue(textEncoder.encode(`${id}
`));
      } else {
        controller.enqueue(textEncoder.encode(`[${encoder.stringified.join(",")}]
`));
        lastSentIndex = encoder.stringified.length - 1;
      }
      const seenPromises = /* @__PURE__ */new WeakSet();
      let processingChain = Promise.resolve();
      if (Object.keys(encoder.deferred).length) {
        let raceDone;
        const racePromise = new Promise((resolve, reject) => {
          raceDone = resolve;
          if (signal) {
```

```
        const rejectPromise = () => reject(signal.reason || new Error("Signal was aborted."));
        if (signal.aborted) {
          rejectPromise();
        } else {
          signal.addEventListener("abort", event => {
            rejectPromise();
          });
        }
      }
    });
    while (Object.keys(encoder.deferred).length > 0) {
      for (const [deferredId, deferred] of Object.entries(encoder.deferred)) {
        if (seenPromises.has(deferred)) continue;
        seenPromises.add(
        // biome-ignore lint/suspicious/noAssignInExpressions: <explanation>
        encoder.deferred[Number(deferredId)] = Promise.race([racePromise, deferred]).then(resolved
=> {
          processingChain = processingChain.then(async () => {
            const id2 = await flatten.call(encoder, resolved);
            if (Array.isArray(id2)) {
              controller.enqueue(textEncoder.encode(`${TYPE_PROMISE}${deferredId}:[["$
{TYPE_PREVIOUS_RESOLVED}",${id2[0]}]]
`));
              encoder.index++;
              lastSentIndex++;
            } else if (id2 < 0) {
              controller.enqueue(textEncoder.encode(`${TYPE_PROMISE}${deferredId}:${id2}
`));
            } else {
              const values = encoder.stringified.slice(lastSentIndex + 1).join(",");
              controller.enqueue(textEncoder.encode(`${TYPE_PROMISE}${deferredId}:[${values}]
`));
              lastSentIndex = encoder.stringified.length - 1;
            }
          });
          return processingChain;
        }, reason => {
          processingChain = processingChain.then(async () => {
            if (!reason || typeof reason !== "object" || !(reason instanceof Error)) {
              reason = new Error("An unknown error occurred");
            }
            const id2 = await flatten.call(encoder, reason);
            if (Array.isArray(id2)) {
              controller.enqueue(textEncoder.encode(`${TYPE_ERROR}${deferredId}:[["$
{TYPE_PREVIOUS_RESOLVED}",${id2[0]}]]
`));
              encoder.index++;
              lastSentIndex++;
            } else if (id2 < 0) {
```

```
              controller.enqueue(textEncoder.encode(`${TYPE_ERROR}${deferredId}:${id2}
`));
            } else {
              const values = encoder.stringified.slice(lastSentIndex + 1).join(",");
              controller.enqueue(textEncoder.encode(`${TYPE_ERROR}${deferredId}:[${values}]
`));
              lastSentIndex = encoder.stringified.length - 1;
            }
          });
          return processingChain;
        }).finally(() => {
          delete encoder.deferred[Number(deferredId)];
        }));
      }
      await Promise.race(Object.values(encoder.deferred));
    }
    raceDone();
  }
  await Promise.all(Object.values(encoder.deferred));
  await processingChain;
  controller.close();
  onComplete?.();
 }
});
return readable;
}

// lib/dom/ssr/data.ts
async function createRequestInit(request) {
 let init = {
  signal: request.signal
 };
 if (request.method !== "GET") {
  init.method = request.method;
  let contentType = request.headers.get("Content-Type");
  if (contentType && /\bapplication\/json\b/.test(contentType)) {
   init.headers = {
    "Content-Type": contentType
   };
   init.body = JSON.stringify(await request.json());
  } else if (contentType && /\btext\/plain\b/.test(contentType)) {
   init.headers = {
    "Content-Type": contentType
   };
   init.body = await request.text();
  } else if (contentType && /\bapplication\/x-www-form-urlencoded\b/.test(contentType)) {
   init.body = new URLSearchParams(await request.text());
  } else {
   init.body = await request.formData();
```

```
    }
  }
  return init;
}

// lib/dom/ssr/markup.ts
var ESCAPE_LOOKUP = {
  "&": "\\u0026",
  ">": "\\u003e",
  "<": "\\u003c",
  "\u2028": "\\u2028",
  "\u2029": "\\u2029"
};
var ESCAPE_REGEX = /[&><\u2028\u2029]/g;
function escapeHtml(html) {
  return html.replace(ESCAPE_REGEX, match => ESCAPE_LOOKUP[match]);
}

// lib/dom/ssr/invariant.ts
function invariant2(value, message) {
  if (value === false || value === null || typeof value === "undefined") {
    throw new Error(message);
  }
}

// lib/dom/ssr/single-fetch.tsx
var SingleFetchRedirectSymbol = Symbol("SingleFetchRedirect");
var SingleFetchNoResultError = class extends Error {};
var SINGLE_FETCH_REDIRECT_STATUS = 202;
var NO_BODY_STATUS_CODES = /* @__PURE__ */new Set([100, 101, 204, 205]);
function StreamTransfer({
  context,
  identifier,
  reader,
  textDecoder,
  nonce
}) {
  if (!context.renderMeta || !context.renderMeta.didRenderScripts) {
    return null;
  }
  if (!context.renderMeta.streamCache) {
    context.renderMeta.streamCache = {};
  }
  let {
    streamCache
  } = context.renderMeta;
  let promise = streamCache[identifier];
  if (!promise) {
    promise = streamCache[identifier] = reader.read().then(result => {
```

```
    streamCache[identifier].result
= {
      done: result.done,
      value: textDecoder.decode(result.value, {
        stream: true
      })
    };
  }).catch(e => {
    streamCache[identifier].error = e;
  });
 }
 if (promise.error) {
  throw promise.error;
 }
 if (promise.result === void 0) {
  throw promise;
 }
 let {
  done,
  value
 } = promise.result;
 let scriptTag = value ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
  nonce,
  dangerouslySetInnerHTML: {
    __html: `window.__reactRouterContext.streamController.enqueue($
{escapeHtml(JSON.stringify(value))});`
  }
 }) : null;
 if (done) {
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, scriptTag, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    nonce,
    dangerouslySetInnerHTML: {
      __html: `window.__reactRouterContext.streamController.close();`
    }
  }));
 } else {
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, scriptTag, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Suspense, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(StreamTransfer, {
    context,
    identifier: identifier + 1,
    reader,
```

```
      textDecoder,
      nonce
    })));
  }
}
function getTurboStreamSingleFetchDataStrategy(getRouter, manifest, routeModules, ssr, basename,
trailingSlashAware) {
  let dataStrategy = getSingleFetchDataStrategyImpl(getRouter, match => {
    let manifestRoute = manifest.routes[match.route.id];
    invariant2(manifestRoute, "Route not found in manifest");
    return {
      hasLoader: manifestRoute.hasLoader,
      hasClientLoader: manifestRoute.hasClientLoader
    };
  }, fetchAndDecodeViaTurboStream, ssr, basename, trailingSlashAware);
  return async args => args.runClientMiddleware(dataStrategy);
}
function getSingleFetchDataStrategyImpl(getRouter, getRouteInfo, fetchAndDecode, ssr, basename,
trailingSlashAware, shouldAllowOptOut = () => true) {
  return async args => {
    let {
      request,
      matches,
      fetcherKey
    } = args;
    let router = getRouter();
    if (request.method !== "GET") {
      return singleFetchActionStrategy(args, fetchAndDecode, basename, trailingSlashAware);
    }
    let foundRevalidatingServerLoader = matches.some(m => {
      let {
        hasLoader,
        hasClientLoader
      } = getRouteInfo(m);
      return m.shouldCallHandler() && hasLoader && !hasClientLoader;
    });
    if (!ssr && !foundRevalidatingServerLoader) {
      return nonSsrStrategy(args, getRouteInfo, fetchAndDecode, basename, trailingSlashAware);
    }
    if (fetcherKey) {
      return singleFetchLoaderFetcherStrategy(args, fetchAndDecode, basename, trailingSlashAware);
    }
    return singleFetchLoaderNavigationStrategy(args, router, getRouteInfo, fetchAndDecode, ssr,
basename, trailingSlashAware, shouldAllowOptOut);
  };
}
async function singleFetchActionStrategy(args, fetchAndDecode, basename, trailingSlashAware) {
  let actionMatch = args.matches.find(m => m.shouldCallHandler());
  invariant2(actionMatch, "No action match found");
```

```
  let actionStatus = void 0;
  let result = await actionMatch.resolve(async handler => {
    let result2 = await handler(async () => {
      let {
        data: data2,
        status
      } = await fetchAndDecode(args, basename, trailingSlashAware, [actionMatch.route.id]);
      actionStatus = status;
      return unwrapSingleFetchResult(data2, actionMatch.route.id);
    });
    return result2;
  });
  if (isResponse(result.result) || isRouteErrorResponse(result.result) ||
isDataWithResponseInit(result.result)) {
    return {
      [actionMatch.route.id]: result
    };
  }
  return {
    [actionMatch.route.id]: {
      type: result.type,
      result: data(result.result, actionStatus)
    }
  };
}
async function nonSsrStrategy(args, getRouteInfo, fetchAndDecode, basename, trailingSlashAware) {
  let matchesToLoad = args.matches.filter(m => m.shouldCallHandler());
  let results = {};
  await Promise.all(matchesToLoad.map(m => m.resolve(async handler => {
    try {
      let {
        hasClientLoader
      } = getRouteInfo(m);
      let routeId = m.route.id;
      let result = hasClientLoader ? await handler(async () => {
        let {
          data: data2
        } = await fetchAndDecode(args, basename, trailingSlashAware, [routeId]);
        return unwrapSingleFetchResult(data2, routeId);
      }) : await handler();
      results[m.route.id] = {
        type: "data",
        result
      };
    } catch (e) {
      results[m.route.id] = {
        type: "error",
        result: e
      };
```

```
    }
  }));
  return results;
}
async function singleFetchLoaderNavigationStrategy(args, router, getRouteInfo, fetchAndDecode, ssr,
basename, trailingSlashAware, shouldAllowOptOut = () => true) {
  let routesParams = /* @__PURE__ */new Set();
  let foundOptOutRoute = false;
  let routeDfds = args.matches.map(() => createDeferred2());
  let singleFetchDfd = createDeferred2();
  let results = {};
  let resolvePromise = Promise.all(args.matches.map(async (m, i) => m.resolve(async handler => {
    routeDfds[i].resolve();
    let routeId = m.route.id;
    let {
      hasLoader,
      hasClientLoader
    } = getRouteInfo(m);
    let defaultShouldRevalidate = !m.shouldRevalidateArgs || m.shouldRevalidateArgs.actionStatus ==
null || m.shouldRevalidateArgs.actionStatus < 400;
    let shouldCall = m.shouldCallHandler(defaultShouldRevalidate);
    if (!shouldCall) {
      foundOptOutRoute || (foundOptOutRoute = m.shouldRevalidateArgs != null &&
      // This is a revalidation,
      hasLoader);
      return;
    }
    if (shouldAllowOptOut(m) && hasClientLoader) {
      if (hasLoader) {
        foundOptOutRoute = true;
      }
      try {
        let result = await handler(async () => {
          let {
            data: data2
          } = await fetchAndDecode(args, basename, trailingSlashAware, [routeId]);
          return unwrapSingleFetchResult(data2, routeId);
        });
        results[routeId] = {
          type: "data",
          result
        };
      } catch (e) {
        results[routeId] = {
          type: "error",
          result: e
        };
      }
      return;
```

```
    }
    if (hasLoader) {
      routesParams.add(routeId);
    }
    try {
      let result = await handler(async () => {
        let data2 = await singleFetchDfd.promise;
        return unwrapSingleFetchResult(data2, routeId);
      });
      results[routeId] = {
        type: "data",
        result
      };
    } catch (e) {
      results[routeId] = {
        type: "error",
        result: e
      };
    }
  }));
  await Promise.all(routeDfds.map(d => d.promise));
  let isInitialLoad = !router.state.initialized && router.state.navigation.state === "idle";
  if ((isInitialLoad || routesParams.size === 0) && !window.__reactRouterHdrActive) {
    singleFetchDfd.resolve({
      routes: {}
    });
  } else {
    let targetRoutes = ssr && foundOptOutRoute && routesParams.size > 0 ? [...routesParams.keys()] :
void 0;
    try {
      let data2 = await fetchAndDecode(args, basename, trailingSlashAware, targetRoutes);
      singleFetchDfd.resolve(data2.data);
    } catch (e) {
      singleFetchDfd.reject(e);
    }
  }
  await resolvePromise;
  await bubbleMiddlewareErrors(singleFetchDfd.promise, args.matches, routesParams, results);
  return results;
}
async function bubbleMiddlewareErrors(singleFetchPromise, matches, routesParams, results) {
  try {
    let middlewareError;
    let fetchedData = await singleFetchPromise;
    if ("routes" in fetchedData) {
      for (let match of matches) {
        if (match.route.id in fetchedData.routes) {
          let routeResult = fetchedData.routes[match.route.id];
          if ("error" in routeResult) {
```

```
            middlewareError = routeResult.error;
            if (results[match.route.id]?.result == null) {
              results[match.route.id] = {
                type: "error",
                result: middlewareError
              };
            }
            break;
          }
        }
      }
    }
    if (middlewareError !== void 0) {
      Array.from(routesParams.values()).forEach(routeId => {
        if (results[routeId].result instanceof SingleFetchNoResultError) {
          results[routeId].result = middlewareError;
        }
      });
    }
  } catch (e) {}
}
async function singleFetchLoaderFetcherStrategy(args, fetchAndDecode, basename,
trailingSlashAware) {
  let fetcherMatch = args.matches.find(m => m.shouldCallHandler());
  invariant2(fetcherMatch, "No fetcher match found");
  let routeId = fetcherMatch.route.id;
  let result = await fetcherMatch.resolve(async handler => handler(async () => {
    let {
      data: data2
    } = await fetchAndDecode(args, basename, trailingSlashAware, [routeId]);
    return unwrapSingleFetchResult(data2, routeId);
  }));
  return {
    [fetcherMatch.route.id]: result
  };
}
function stripIndexParam(url) {
  let indexValues = url.searchParams.getAll("index");
  url.searchParams.delete("index");
  let indexValuesToKeep = [];
  for (let indexValue of indexValues) {
    if (indexValue) {
      indexValuesToKeep.push(indexValue);
    }
  }
  for (let toKeep of indexValuesToKeep) {
    url.searchParams.append("index", toKeep);
  }
  return url;
```

```
}
function singleFetchUrl(reqUrl, basename, trailingSlashAware, extension) {
  let url = typeof reqUrl === "string" ? new URL(reqUrl,
  // This can be called during the SSR flow via PrefetchPageLinksImpl so
  // don't assume window is available
  typeof window === "undefined" ? "server://singlefetch/" : window.location.origin) : reqUrl;
  if (trailingSlashAware) {
    if (url.pathname.endsWith("/")) {
      url.pathname = `${url.pathname}_.${extension}`;

    } else {
      url.pathname = `${url.pathname}.${extension}`;
    }
  } else {
    if (url.pathname === "/") {
      url.pathname = `_root.${extension}`;
    } else if (basename && stripBasename(url.pathname, basename) === "/") {
      url.pathname = `${removeTrailingSlash(basename)}/_root.${extension}`;
    } else {
      url.pathname = `${removeTrailingSlash(url.pathname)}.${extension}`;
    }
  }
  return url;
}
async function fetchAndDecodeViaTurboStream(args, basename, trailingSlashAware, targetRoutes) {
  let {
    request
  } = args;
  let url = singleFetchUrl(request.url, basename, trailingSlashAware, "data");
  if (request.method === "GET") {
    url = stripIndexParam(url);
    if (targetRoutes) {
      url.searchParams.set("_routes", targetRoutes.join(","));
    }
  }
  let res = await fetch(url, await createRequestInit(request));
  if (res.status >= 400 && !res.headers.has("X-Remix-Response")) {
    throw new ErrorResponseImpl(res.status, res.statusText, await res.text());
  }
  if (res.status === 204 && res.headers.has("X-Remix-Redirect")) {
    return {
      status: SINGLE_FETCH_REDIRECT_STATUS,
      data: {
        redirect: {
          redirect: res.headers.get("X-Remix-Redirect"),
          status: Number(res.headers.get("X-Remix-Status") || "302"),
          revalidate: res.headers.get("X-Remix-Revalidate") === "true",
          reload: res.headers.get("X-Remix-Reload-Document") === "true",
          replace: res.headers.get("X-Remix-Replace") === "true"
```

```
      }
    }
  };
}
if (NO_BODY_STATUS_CODES.has(res.status)) {
  let routes = {};
  if (targetRoutes && request.method !== "GET") {
    routes[targetRoutes[0]] = {
      data: void 0
    };
  }
  return {
    status: res.status,
    data: {
      routes
    }
  };
}
invariant2(res.body, "No response body to decode");
try {
  let decoded = await decodeViaTurboStream(res.body, window);
  let data2;
  if (request.method === "GET") {
    let typed = decoded.value;
    if (SingleFetchRedirectSymbol in typed) {
      data2 = {
        redirect: typed[SingleFetchRedirectSymbol]
      };
    } else {
      data2 = {
        routes: typed
      };
    }
  } else {
    let typed = decoded.value;
    let routeId = targetRoutes?.[0];
    invariant2(routeId, "No routeId found for single fetch call decoding");
    if ("redirect" in typed) {
      data2 = {
        redirect: typed
      };
    } else {
      data2 = {
        routes: {
          [routeId]: typed
        }
      };
    }
  }
```

```
    return {
      status: res.status,
      data: data2
    };
  } catch (e) {
    throw new Error("Unable to decode turbo-stream response");
  }
}
function decodeViaTurboStream(body, global) {
  return decode(body, {
    plugins: [(type, ...rest) => {
      if (type === "SanitizedError") {
        let [name, message, stack] = rest;
        let Constructor = Error;
        if (name && SUPPORTED_ERROR_TYPES.includes(name) && name in global &&
        // @ts-expect-error
        typeof global[name] === "function") {
          Constructor = global[name];
        }
        let error = new Constructor(message);
        error.stack = stack;
        return {
          value: error
        };
      }
      if (type === "ErrorResponse") {
        let [data2, status, statusText] = rest;
        return {
          value: new ErrorResponseImpl(status, statusText, data2)
        };
      }
      if (type === "SingleFetchRedirect") {
        return {
          value: {
            [SingleFetchRedirectSymbol]: rest[0]
          }
        };
      }
      if (type === "SingleFetchClassInstance") {
        return {
          value: rest[0]
        };
      }
      if (type === "SingleFetchFallback") {
        return {
          value: void 0
        };
      }
    }]
```

```
  });
}
function unwrapSingleFetchResult(result, routeId) {
  if ("redirect" in result) {
    let {
      redirect: location,
      revalidate,
      reload,
      replace: replace2,
      status
    } = result.redirect;
    throw redirect(location, {
      status,
      headers: {
        // Three R's of redirecting (lol Veep)
        ...(revalidate ? {
          "X-Remix-Revalidate": "yes"
        } : null),
        ...(reload ? {
          "X-Remix-Reload-Document": "yes"
        } : null),
        ...(replace2 ? {
          "X-Remix-Replace": "yes"
        } : null)
      }
    });
  }
  let routeResult = result.routes[routeId];
  if (routeResult == null) {
    throw new SingleFetchNoResultError(`No result found for routeId "${routeId}"`);
  } else if ("error" in routeResult) {
    throw routeResult.error;
  } else if ("data" in routeResult) {
    return routeResult.data;
  } else {
    throw new Error(`Invalid response found for routeId "${routeId}"`);
  }
}
function createDeferred2() {
  let resolve;
  let reject;
  let promise = new Promise((res, rej) => {
    resolve = async val => {
      res(val);
      try {
        await promise;
      } catch (e) {}
    };
    reject = async error => {
```

```
      rej(error);
      try {
        await promise;
      } catch (e) {}
    };
  });
  return {
    promise,
    //@ts-ignore
    resolve,
    //@ts-ignore
    reject
  };
}

// lib/dom/ssr/errorBoundaries.tsx


// lib/dom/ssr/components.tsx


// lib/dom/ssr/routeModules.ts
async function loadRouteModule(route, routeModulesCache) {
  if (route.id in routeModulesCache) {
    return routeModulesCache[route.id];
  }
  try {
    let routeModule = await import(/* @vite-ignore */
    /* webpackIgnore: true */
    route.module);
    routeModulesCache[route.id] = routeModule;
    return routeModule;
  } catch (error) {
    console.error(`Error loading route module \`${route.module}\`, reloading page...`);
    console.error(error);
    if (window.__reactRouterContext && window.__reactRouterContext.isSpaMode &&
    // @ts-expect-error
    /* unsupported import.meta.hot */ undefined) // removed by dead control flow
{}
    window.location.reload();
    return new Promise(() => {});
  }
}

// lib/dom/ssr/links.ts
function getKeyedLinksForMatches(matches, routeModules, manifest) {
  let descriptors = matches.map(match => {
    let module = routeModules[match.route.id];
    let route = manifest.routes[match.route.id];
```

```
    return [route && route.css ? route.css.map(href => ({
      rel: "stylesheet",
      href
    })) : [], module?.links?.() || []];
  }).flat(2);
  let preloads = getModuleLinkHrefs(matches, manifest);
  return dedupeLinkDescriptors(descriptors, preloads);
}
function getRouteCssDescriptors(route) {
  if (!route.css) return [];
  return route.css.map(href => ({
    rel: "stylesheet",
    href
  }));
}
async function prefetchRouteCss(route) {
  if (!route.css) return;
  let descriptors = getRouteCssDescriptors(route);
  await Promise.all(descriptors.map(prefetchStyleLink));
}
async function prefetchStyleLinks(route, routeModule) {
  if (!route.css && !routeModule.links || !isPreloadSupported()) return;
  let descriptors = [];
  if (route.css) {
    descriptors.push(...getRouteCssDescriptors(route));
  }
  if (routeModule.links) {
    descriptors.push(...routeModule.links());
  }
  if (descriptors.length === 0) return;
  let styleLinks = [];
  for (let descriptor of descriptors) {
    if (!isPageLinkDescriptor(descriptor) && descriptor.rel === "stylesheet") {
      styleLinks.push({
        ...descriptor,
        rel: "preload",
        as: "style"
      });
    }
  }
  await Promise.all(styleLinks.map(prefetchStyleLink));
}
async function prefetchStyleLink(descriptor) {
  return new Promise(resolve => {
    if (descriptor.media && !window.matchMedia(descriptor.media).matches ||
document.querySelector(`link[rel="stylesheet"][href="${descriptor.href}"]`)) {
      return resolve();
    }
    let link = document.createElement("link");
```

```
    Object.assign(link, descriptor);
    function removeLink() {
      if (document.head.contains(link)) {
        document.head.removeChild(link);
      }
    }
    link.onload = () => {
      removeLink();
      resolve();
    };
    link.onerror = () => {
      removeLink();
      resolve();
    };
    document.head.appendChild(link);
  });
}
function isPageLinkDescriptor(object) {
  return object != null && typeof object.page === "string";
}
function isHtmlLinkDescriptor(object) {
  if (object == null) {
    return false;
  }
  if (object.href == null) {
    return object.rel === "preload" && typeof object.imageSrcSet === "string" && typeof
object.imageSizes === "string";
  }
  return typeof object.rel === "string" && typeof object.href === "string";
}
async function getKeyedPrefetchLinks(matches, manifest, routeModules) {
  let links = await Promise.all(matches.map(async match => {
    let route = manifest.routes[match.route.id];
    if (route) {
      let mod = await loadRouteModule(route, routeModules);
      return mod.links ? mod.links() : [];
    }
    return [];
  }));
  return dedupeLinkDescriptors(links.flat(1).filter(isHtmlLinkDescriptor).filter(link => link.rel ===
"stylesheet" || link.rel === "preload").map(link => link.rel === "stylesheet" ? {
    ...link,
    rel: "prefetch",
    as: "style"
  } : {
    ...link,
    rel: "prefetch"
  }));
}
```

```
function getNewMatchesForLinks(page, nextMatches, currentMatches, manifest, location, mode) {
  let isNew = (match, index) => {
    if (!currentMatches[index]) return true;
    return match.route.id !== currentMatches[index].route.id;
  };
  let matchPathChanged = (match, index) => {
    return (
      // param change, /users/123 -> /users/456
      currentMatches[index].pathname !== match.pathname ||
      // splat param changed, which is not present in match.path
      // e.g. /files/images/avatar.jpg -> files/finances.xls
      currentMatches[index].route.path?.endsWith("*") && currentMatches[index].params["*"] !==
match.params["*"]
    );
  };

  if (mode === "assets") {
    return nextMatches.filter((match, index) => isNew(match, index) || matchPathChanged(match,
index));
  }
  if (mode === "data") {
    return nextMatches.filter((match, index) => {
      let manifestRoute = manifest.routes[match.route.id];
      if (!manifestRoute || !manifestRoute.hasLoader) {
        return false;
      }
      if (isNew(match, index) || matchPathChanged(match, index)) {
        return true;
      }
      if (match.route.shouldRevalidate) {
        let routeChoice = match.route.shouldRevalidate({
          currentUrl: new URL(location.pathname + location.search + location.hash, window.origin),
          currentParams: currentMatches[0]?.params || {},
          nextUrl: new URL(page, window.origin),
          nextParams: match.params,
          defaultShouldRevalidate: true
        });
        if (typeof routeChoice === "boolean") {
          return routeChoice;
        }
      }
      return true;
    });
  }
  return [];
}
function getModuleLinkHrefs(matches, manifest, {
  includeHydrateFallback
} = {}) {
```

```
  return dedupeHrefs(matches.map(match => {
    let route = manifest.routes[match.route.id];
    if (!route) return [];
    let hrefs = [route.module];
    if (route.clientActionModule) {
      hrefs = hrefs.concat(route.clientActionModule);
    }
    if (route.clientLoaderModule) {
      hrefs = hrefs.concat(route.clientLoaderModule);
    }
    if (includeHydrateFallback && route.hydrateFallbackModule) {
      hrefs = hrefs.concat(route.hydrateFallbackModule);
    }
    if (route.imports) {
      hrefs = hrefs.concat(route.imports);
    }
    return hrefs;
  }).flat(1));
}
function dedupeHrefs(hrefs) {
  return [...new Set(hrefs)];
}
function sortKeys(obj) {
  let sorted = {};
  let keys = Object.keys(obj).sort();
  for (let key of keys) {
    sorted[key] = obj[key];
  }
  return sorted;
}
function dedupeLinkDescriptors(descriptors, preloads) {
  let set = /* @__PURE__ */new Set();
  let preloadsSet = new Set(preloads);
  return descriptors.reduce((deduped, descriptor) => {
    let alreadyModulePreload = preloads && !isPageLinkDescriptor(descriptor) && descriptor.as ===
"script" && descriptor.href && preloadsSet.has(descriptor.href);
    if (alreadyModulePreload) {
      return deduped;
    }
    let key = JSON.stringify(sortKeys(descriptor));
    if (!set.has(key)) {
      set.add(key);
      deduped.push({
        key,
        link: descriptor
      });
    }
    return deduped;
  }, []);
```

```
}
var _isPreloadSupported;
function isPreloadSupported() {
  if (_isPreloadSupported !== void 0) {
    return _isPreloadSupported;
  }
  let el = document.createElement("link");
  _isPreloadSupported = el.relList.supports("preload");
  el = null;
  return _isPreloadSupported;
}

// lib/dom/ssr/fog-of-war.ts


// lib/dom/ssr/routes.tsx


// lib/dom/ssr/fallback.tsx

function RemixRootDefaultHydrateFallback() {
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(BoundaryShell, {
    title: "Loading...",
    renderScripts: true
  }, ENABLE_DEV_WARNINGS ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    dangerouslySetInnerHTML: {
      __html: `
            console.log(
              "\u{1F4BF} Hey developer \u{1F44B}. You can provide a way better UX than this " +
              "when your app is loading JS modules and/or running \`clientLoader\` " +
              "functions. Check out https://reactrouter.com/start/framework/route-module#hydratefallback
" +
              "for more information."
            );
          `

    }
  }) : null);
}

// lib/dom/ssr/routes.tsx
function groupRoutesByParentId(manifest) {
  let routes = {};
  Object.values(manifest).forEach(route => {
    if (route) {
      let parentId = route.parentId || "";
      if (!routes[parentId]) {
        routes[parentId] = [];
```

```
      }
      routes[parentId].push(route);
    }
  });
  return routes;
}
function getRouteComponents(route, routeModule, isSpaMode) {
  let Component4 = getRouteModuleComponent(routeModule);
  let HydrateFallback = routeModule.HydrateFallback && (!isSpaMode || route.id === "root") ?
routeModule.HydrateFallback : route.id === "root" ? RemixRootDefaultHydrateFallback : void 0;
  let ErrorBoundary = routeModule.ErrorBoundary ? routeModule.ErrorBoundary : route.id ===
"root" ? () => /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RemixRootDefaultErrorBoundary,
{
    error: useRouteError()
  }) : void 0;
  if (route.id === "root" && routeModule.Layout) {
    return {
      ...(Component4 ? {
        element: /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(routeModule.Layout, null, /*
@__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Component4, null))
      } : {
        Component: Component4
      }),
      ...(ErrorBoundary ? {
        errorElement: /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(routeModule.Layout, null, /*
@__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(ErrorBoundary,
null))
      } : {
        ErrorBoundary
      }),
      ...(HydrateFallback ? {
        hydrateFallbackElement: /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(routeModule.Layout, null, /*
@__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(HydrateFallback,
null))
      } : {
        HydrateFallback
      })
    };
  }
  return {
    Component: Component4,
    ErrorBoundary,
    HydrateFallback
  };
}
```

```
function createServerRoutes(manifest, routeModules, future, isSpaMode, parentId = "",
routesByParentId = groupRoutesByParentId(manifest), spaModeLazyPromise = Promise.resolve({
  Component: () => null
})) {
  return (routesByParentId[parentId] || []).map(route => {
    let routeModule = routeModules[route.id];
    invariant2(routeModule, "No `routeModule` available to create server routes");
    let dataRoute = {
      ...getRouteComponents(route, routeModule, isSpaMode),
      caseSensitive: route.caseSensitive,
      id: route.id,
      index: route.index,
      path: route.path,
      handle: routeModule.handle,
      // For SPA Mode, all routes are lazy except root.  However we tell the
      // router root is also lazy here too since we don't need a full
      // implementation - we just need a `lazy` prop to tell the RR rendering
      // where to stop which is always at the root route in SPA mode
      lazy: isSpaMode ? () => spaModeLazyPromise : void 0,
      // For partial hydration rendering, we need to indicate when the route
      // has a loader/clientLoader, but it won't ever be called during the static
      // render, so just give it a no-op function so we can render down to the
      // proper fallback
      loader: route.hasLoader || route.hasClientLoader ? () => null : void 0
      // We don't need middleware/action/shouldRevalidate on these routes since
      // they're for a static render
    };
    let children = createServerRoutes(manifest, routeModules, future, isSpaMode, route.id,
routesByParentId, spaModeLazyPromise);
    if (children.length > 0) dataRoute.children = children;
    return dataRoute;
  });
}
function createClientRoutesWithHMRRevalidationOptOut(needsRevalidation, manifest,
routeModulesCache, initialState, ssr, isSpaMode) {
  return createClientRoutes(manifest, routeModulesCache, initialState, ssr, isSpaMode, "",
groupRoutesByParentId(manifest), needsRevalidation);
}
function preventInvalidServerHandlerCall(type, route) {
  if (type === "loader" && !route.hasLoader || type === "action" && !route.hasAction) {
    let fn = type === "action" ? "serverAction()" : "serverLoader()";
    let msg = `You are trying to call ${fn} on a route that does not have a server ${type} (routeId: "$
{route.id}")`;
    console.error(msg);
    throw new ErrorResponseImpl(400, "Bad Request", new Error(msg), true);
  }
}
function noActionDefinedError(type, routeId) {
  let article = type === "clientAction" ? "a" : "an";
```

```
  let msg = `Route "${routeId}" does not have ${article} ${type}, but you are trying to submit to it. To fix this, please add ${article} \`${type}\` function to the route`;
  console.error(msg);
  throw new ErrorResponseImpl(405, "Method Not Allowed", new Error(msg), true);
}
function createClientRoutes(manifest, routeModulesCache, initialState, ssr, isSpaMode, parentId = "", routesByParentId = groupRoutesByParentId(manifest), needsRevalidation) {
  return (routesByParentId[parentId] || []).map(route => {
    let routeModule = routeModulesCache[route.id];
    function fetchServerHandler(singleFetch) {
      invariant2(typeof singleFetch === "function", "No single fetch function available for route handler");
      return singleFetch();
    }
    function fetchServerLoader(singleFetch) {
      if (!route.hasLoader) return Promise.resolve(null);
      return fetchServerHandler(singleFetch);
    }
    function fetchServerAction(singleFetch) {
      if (!route.hasAction) {
        throw noActionDefinedError("action", route.id);
      }
      return fetchServerHandler(singleFetch);
    }
    function prefetchModule(modulePath) {
      import(/* @vite-ignore */
      /* webpackIgnore: true */
      modulePath);
    }
    function prefetchRouteModuleChunks(route2) {
      if (route2.clientActionModule) {
        prefetchModule(route2.clientActionModule);
      }
      if (route2.clientLoaderModule) {
        prefetchModule(route2.clientLoaderModule);
      }
    }
    async function prefetchStylesAndCallHandler(handler) {
      let cachedModule = routeModulesCache[route.id];
      let linkPrefetchPromise = cachedModule ? prefetchStyleLinks(route, cachedModule) : Promise.resolve();
      try {
        return handler();
      } finally {
        await linkPrefetchPromise;
      }
    }
    let dataRoute = {
      id: route.id,
```

```
    index: route.index,
    path: route.path
   };
   if (routeModule) {
    Object.assign(dataRoute,
 {
     ...dataRoute,
     ...getRouteComponents(route, routeModule, isSpaMode),
     middleware: routeModule.clientMiddleware,
     handle: routeModule.handle,
     shouldRevalidate: getShouldRevalidateFunction(dataRoute.path, routeModule, route, ssr,
needsRevalidation)
    });
    let hasInitialData = initialState && initialState.loaderData && route.id in initialState.loaderData;
    let initialData = hasInitialData ? initialState?.loaderData?.[route.id] : void 0;
    let hasInitialError = initialState && initialState.errors && route.id in initialState.errors;
    let initialError = hasInitialError ? initialState?.errors?.[route.id] : void 0;
    let isHydrationRequest = needsRevalidation == null && (routeModule.clientLoader?.hydrate ===
true || !route.hasLoader);
    dataRoute.loader = async ({
     request,
     params,
     context,
     pattern,
     url
    }, singleFetch) => {
     let _isHydrationRequest = isHydrationRequest;
     isHydrationRequest = false;
     let result = await prefetchStylesAndCallHandler(async () => {
      invariant2(routeModule, "No `routeModule` available for critical-route loader");
      if (!routeModule.clientLoader) {
       return fetchServerLoader(singleFetch);
      }
      return routeModule.clientLoader({
       request,
       params,
       context,
       pattern,
       url,
       async serverLoader() {
        preventInvalidServerHandlerCall("loader", route);
        if (_isHydrationRequest) {
         if (hasInitialData) {
          return initialData;
         }
         if (hasInitialError) {
          throw initialError;
         }
        }
```

```
            return fetchServerLoader(singleFetch);
          }
        });
      });
      return result;
    };
    dataRoute.loader.hydrate = shouldHydrateRouteLoader(route.id, routeModule.clientLoader,
route.hasLoader, isSpaMode);
    dataRoute.action = ({
      request,
      params,
      context,
      pattern,
      url
    }, singleFetch) => {
      return prefetchStylesAndCallHandler(async () => {
        invariant2(routeModule, "No `routeModule` available for critical-route action");
        if (!routeModule.clientAction) {
          if (isSpaMode) {
            throw noActionDefinedError("clientAction", route.id);
          }
          return fetchServerAction(singleFetch);
        }
        return routeModule.clientAction({
          request,
          params,
          context,
          pattern,
          url,
          async serverAction() {
            preventInvalidServerHandlerCall("action", route);
            return fetchServerAction(singleFetch);
          }
        });
      });
    };
  } else {
    if (!route.hasClientLoader) {
      dataRoute.loader = (_, singleFetch) => prefetchStylesAndCallHandler(() => {
        return fetchServerLoader(singleFetch);
      });
    }
    if (!route.hasClientAction) {
      dataRoute.action = (_, singleFetch) => prefetchStylesAndCallHandler(() => {
        if (isSpaMode) {
          throw noActionDefinedError("clientAction", route.id);
        }
        return fetchServerAction(singleFetch);
      });
```

```
}
let lazyRoutePromise;
async function getLazyRoute() {
  if (lazyRoutePromise) {
    return await lazyRoutePromise;
  }
  lazyRoutePromise = (async () => {
    if (route.clientLoaderModule || route.clientActionModule) {
      await new Promise(resolve => setTimeout(resolve, 0));
    }
    let routeModulePromise = loadRouteModuleWithBlockingLinks(route, routeModulesCache);
    prefetchRouteModuleChunks(route);
    return await routeModulePromise;
  })();
  return await lazyRoutePromise;
}
dataRoute.lazy = {
  loader: route.hasClientLoader ? async () => {
    let {
      clientLoader
    } = route.clientLoaderModule ? await import(/* @vite-ignore */
    /* webpackIgnore: true */
    route.clientLoaderModule) : await getLazyRoute();
    invariant2(clientLoader, "No `clientLoader` export found");
    return (args, singleFetch) => clientLoader({
      ...args,
      async serverLoader() {
        preventInvalidServerHandlerCall("loader", route);
        return fetchServerLoader(singleFetch);
      }
    });
  } : void 0,
  action: route.hasClientAction ? async () => {
    let clientActionPromise = route.clientActionModule ? import(/* @vite-ignore */
    /* webpackIgnore: true */
    route.clientActionModule) : getLazyRoute();
    prefetchRouteModuleChunks(route);
    let {
      clientAction
    } = await clientActionPromise;
    invariant2(clientAction, "No `clientAction` export found");
    return (args, singleFetch) => clientAction({
      ...args,
      async serverAction() {
        preventInvalidServerHandlerCall("action", route);
        return fetchServerAction(singleFetch);
      }
    });
  } : void 0,
```

```
      middleware: route.hasClientMiddleware ? async () => {
        let {
          clientMiddleware
        } = route.clientMiddlewareModule ? await import(/* @vite-ignore */
        /* webpackIgnore: true */
        route.clientMiddlewareModule) : await getLazyRoute();
        invariant2(clientMiddleware, "No `clientMiddleware` export found");
        return clientMiddleware;
      } : void 0,
      shouldRevalidate: async () => {
        let lazyRoute = await getLazyRoute();
        return getShouldRevalidateFunction(dataRoute.path, lazyRoute, route, ssr, needsRevalidation);
      },
      handle: async () => (await getLazyRoute()).handle,
      // No need to wrap these in layout since the root route is never
      // loaded via route.lazy()
      Component: async () => (await getLazyRoute()).Component,
      ErrorBoundary: route.hasErrorBoundary ? async () => (await getLazyRoute()).ErrorBoundary :
void 0
    };
  }
  let children = createClientRoutes(manifest, routeModulesCache, initialState, ssr, isSpaMode,
route.id, routesByParentId, needsRevalidation);
  if (children.length > 0) dataRoute.children = children;
  return dataRoute;
 });
}
function getShouldRevalidateFunction(path, route, manifestRoute, ssr, needsRevalidation) {
 if (needsRevalidation) {
  return wrapShouldRevalidateForHdr(manifestRoute.id, route.shouldRevalidate, needsRevalidation);
 }
 if (!ssr && manifestRoute.hasLoader && !manifestRoute.hasClientLoader) {
  let myParams = path ? compilePath(path)[1].map(p => p.paramName) : [];
  const didParamsChange = opts => myParams.some(p => opts.currentParams[p] !==
opts.nextParams[p]);
  if (route.shouldRevalidate) {
    let fn = route.shouldRevalidate;
    return opts => fn({
      ...opts,
      defaultShouldRevalidate: didParamsChange(opts)
    });
  } else {
    return opts => didParamsChange(opts);
  }
 }
 return route.shouldRevalidate;
}
function wrapShouldRevalidateForHdr(routeId, routeShouldRevalidate, needsRevalidation) {
 let handledRevalidation = false;
```

```
  return arg => {
    if (!handledRevalidation) {
      handledRevalidation = true;
      return needsRevalidation.has(routeId);
    }
    return routeShouldRevalidate ? routeShouldRevalidate(arg) : arg.defaultShouldRevalidate;
  };
}
async function loadRouteModuleWithBlockingLinks(route, routeModules) {
  let routeModulePromise = loadRouteModule(route, routeModules);
  let prefetchRouteCssPromise = prefetchRouteCss(route);
  let routeModule = await routeModulePromise;
  await Promise.all([prefetchRouteCssPromise, prefetchStyleLinks(route, routeModule)]);
  return {
    Component: getRouteModuleComponent(routeModule),
    ErrorBoundary: routeModule.ErrorBoundary,
    clientMiddleware: routeModule.clientMiddleware,
    clientAction: routeModule.clientAction,
    clientLoader: routeModule.clientLoader,
    handle: routeModule.handle,
    links: routeModule.links,
    meta: routeModule.meta,
    shouldRevalidate: routeModule.shouldRevalidate
  };
}
function getRouteModuleComponent(routeModule) {
  if (routeModule.default == null) return void 0;
  let isEmptyObject = typeof routeModule.default === "object" &&
Object.keys(routeModule.default).length === 0;
  if (!isEmptyObject) {
    return routeModule.default;
  }
}
function shouldHydrateRouteLoader(routeId, clientLoader, hasLoader, isSpaMode) {
  return isSpaMode && routeId !== "root" || clientLoader != null && (clientLoader.hydrate === true ||
hasLoader !== true);
}

// lib/dom/ssr/fog-of-war.ts
var nextPaths = /* @__PURE__ */new Set();
var discoveredPathsMaxSize = 1e3;
var discoveredPaths = /* @__PURE__ */new Set();
var URL_LIMIT = 7680;
function isFogOfWarEnabled(routeDiscovery, ssr) {
  return routeDiscovery.mode === "lazy" && ssr === true;
}
function getPartialManifest({
  sri,
  ...manifest
```

```
}, router) {
  let routeIds = new Set(router.state.matches.map(m => m.route.id));
  let segments = router.state.location.pathname.split("/").filter(Boolean);
  let paths = ["/"];
  segments.pop();
  while (segments.length > 0) {
    paths.push(`/${segments.join("/")}`);
    segments.pop();
  }
  paths.forEach(path => {
    let matches = matchRoutesImpl(router.routes, path, router.basename || "/", false, router.branches);
    if (matches) {
      matches.forEach(m => routeIds.add(m.route.id));
    }
  });
  let initialRoutes = [...routeIds].reduce((acc, id) => Object.assign(acc, {
    [id]: manifest.routes[id]
  }), {});
  return {
    ...manifest,
    routes: initialRoutes,
    sri: sri ? true : void 0
  };
}
function getPatchRoutesOnNavigationFunction(getRouter,
 manifest, routeModules, ssr, routeDiscovery, isSpaMode, basename) {
  if (!isFogOfWarEnabled(routeDiscovery, ssr)) {
    return void 0;
  }
  return async ({
    path,
    patch,
    signal,
    fetcherKey
  }) => {
    if (discoveredPaths.has(path)) {
      return;
    }
    let {
      state
    } = getRouter();
    await fetchAndApplyManifestPatches([path],
    // If we're patching for a fetcher call, reload the current location
    // Otherwise prefer any ongoing navigation location
    fetcherKey ? window.location.href : createPath(state.navigation.location || state.location), manifest,
routeModules, ssr, isSpaMode, basename, routeDiscovery.manifestPath, patch, signal);
  };
}
function useFogOFWarDiscovery(router, manifest, routeModules, ssr, routeDiscovery, isSpaMode) {
```

```
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (!isFogOfWarEnabled(routeDiscovery, ssr) ||
    // @ts-expect-error - TS doesn't know about this yet
    window.navigator?.connection?.saveData === true) {
      return;
    }
    function registerElement(el) {
      let path = el.tagName === "FORM" ? el.getAttribute("action") : el.getAttribute("href");
      if (!path) {
        return;
      }
      let pathname = el.tagName === "A" ? el.pathname : new URL(path,
window.location.origin).pathname;
      if (!discoveredPaths.has(pathname)) {
        nextPaths.add(pathname);
      }
    }
    async function fetchPatches() {
      document.querySelectorAll("a[data-discover], form[data-discover]").forEach(registerElement);
      let lazyPaths = Array.from(nextPaths.keys()).filter(path => {
        if (discoveredPaths.has(path)) {
          nextPaths.delete(path);
          return false;
        }
        return true;
      });
      if (lazyPaths.length === 0) {
        return;
      }
      try {
        await fetchAndApplyManifestPatches(lazyPaths, null, manifest, routeModules, ssr, isSpaMode,
router.basename, routeDiscovery.manifestPath, router.patchRoutes);
      } catch (e) {
        console.error("Failed to fetch manifest patches", e);
      }
    }
    let debouncedFetchPatches = debounce(fetchPatches, 100);
    fetchPatches();
    let observer = new MutationObserver(() => debouncedFetchPatches());
    observer.observe(document.documentElement, {
      subtree: true,
      childList: true,
      attributes: true,
      attributeFilter: ["data-discover", "href", "action"]
    });
    return () => observer.disconnect();
  }, [ssr, isSpaMode, manifest, routeModules, router, routeDiscovery]);
}
function getManifestPath(_manifestPath, basename) {
```

```
  let manifestPath = _manifestPath || "/__manifest";
  return basename == null ? manifestPath : joinPaths([basename, manifestPath]);
}
var MANIFEST_VERSION_STORAGE_KEY = "react-router-manifest-version";
async function fetchAndApplyManifestPatches(paths, errorReloadPath, manifest, routeModules, ssr,
isSpaMode, basename, manifestPath, patchRoutes, signal) {
  const searchParams = new URLSearchParams();
  searchParams.set("paths", paths.sort().join(","));
  searchParams.set("version", manifest.version);
  let url = new URL(getManifestPath(manifestPath, basename), window.location.origin);
  url.search = searchParams.toString();
  if (url.toString().length > URL_LIMIT) {
    nextPaths.clear();
    return;
  }
  let serverPatches;
  try {
    let res = await fetch(url, {
      signal
    });
    if (!res.ok) {
      throw new Error(`${res.status} ${res.statusText}`);
    } else if (res.status === 204 && res.headers.has("X-Remix-Reload-Document")) {
      if (!errorReloadPath) {
        console.warn("Detected a manifest version mismatch during eager route discovery. The next
navigation/fetch to an undiscovered route will result in a new document navigation to sync up with the
latest manifest.");
        return;
      }
      try {
        if (sessionStorage.getItem(MANIFEST_VERSION_STORAGE_KEY) === manifest.version) {
          console.error("Unable to discover routes due to manifest version mismatch.");
          return;
        }
        sessionStorage.setItem(MANIFEST_VERSION_STORAGE_KEY, manifest.version);
      } catch {}
      window.location.href = errorReloadPath;
      console.warn("Detected manifest version mismatch, reloading...");
      await new Promise(() => {});
    } else if (res.status >= 400) {
      throw new Error(await res.text());
    }
    try {
      sessionStorage.removeItem(MANIFEST_VERSION_STORAGE_KEY);
    } catch {}
    serverPatches = await res.json();
  } catch (e) {
    if (signal?.aborted) return;
    throw e;
```

```
  }
  let knownRoutes = new Set(Object.keys(manifest.routes));
  let patches = Object.values(serverPatches).reduce((acc, route) => {
    if (route && !knownRoutes.has(route.id)) {
      acc[route.id] = route;
    }
    return acc;
  }, {});
  Object.assign(manifest.routes, patches);
  paths.forEach(p => addToFifoQueue(p, discoveredPaths));
  let parentIds = /* @__PURE__ */new Set();
  Object.values(patches).forEach(patch => {
    if (patch && (!patch.parentId || !patches[patch.parentId])) {
      parentIds.add(patch.parentId);
    }
  });
  parentIds.forEach(parentId => patchRoutes(parentId || null, createClientRoutes(patches,
routeModules, null, ssr, isSpaMode, parentId)));
}
function addToFifoQueue(path, queue) {
  if (queue.size >= discoveredPathsMaxSize) {
    let first = queue.values().next().value;
    queue.delete(first);
  }
  queue.add(path);
}
function debounce(callback, wait) {
  let timeoutId;
  return (...args) => {
    window.clearTimeout(timeoutId);
    timeoutId = window.setTimeout(() => callback(...args), wait);
  };
}

// lib/dom/ssr/components.tsx
function useDataRouterContext2() {
  let context = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  invariant2(context, "You must render this element inside a <DataRouterContext.Provider> element");
  return context;
}
function useDataRouterStateContext() {
  let context = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterStateContext);
  invariant2(context, "You must render this element inside a <DataRouterStateContext.Provider>
element");
  return context;
}
var FrameworkContext = react__WEBPACK_IMPORTED_MODULE_0__.createContext(void 0);
FrameworkContext.displayName = "FrameworkContext";
function useFrameworkContext() {
```

```
  let context = react__WEBPACK_IMPORTED_MODULE_0__.useContext(FrameworkContext);
  invariant2(context, "You must render this element inside a <HydratedRouter> element");
  return context;
}
function usePrefetchBehavior(prefetch, theirElementProps) {
  let frameworkContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(FrameworkContext);
  let [maybePrefetch, setMaybePrefetch] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  let [shouldPrefetch, setShouldPrefetch] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  let {
    onFocus,
    onBlur,
    onMouseEnter,
    onMouseLeave,
    onTouchStart
  } = theirElementProps;
  let ref = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (prefetch === "render") {
      setShouldPrefetch(true);
    }
    if (prefetch === "viewport") {
      let callback = entries => {
        entries.forEach(entry => {
          setShouldPrefetch(entry.isIntersecting);
        });
      };
      let observer = new IntersectionObserver(callback, {
        threshold: 0.5
      });
      if (ref.current) observer.observe(ref.current);
      return () => {
        observer.disconnect();
      };
    }
  }, [prefetch]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (maybePrefetch) {
      let id = setTimeout(() => {
        setShouldPrefetch(true);
      }, 100);
      return () => {
        clearTimeout(id);
      };
    }
  }, [maybePrefetch]);
  let setIntent = () => {
```

```
    setMaybePrefetch(true);
  };
  let cancelIntent = () => {
    setMaybePrefetch(false);
    setShouldPrefetch(false);
  };
  if (!frameworkContext) {
    return [false, ref, {}];
  }
  if (prefetch !== "intent") {
    return [shouldPrefetch, ref, {}];
  }
  return [shouldPrefetch, ref, {
    onFocus: composeEventHandlers(onFocus, setIntent),
    onBlur: composeEventHandlers(onBlur, cancelIntent),
    onMouseEnter: composeEventHandlers(onMouseEnter, setIntent),
    onMouseLeave: composeEventHandlers(onMouseLeave, cancelIntent),
    onTouchStart: composeEventHandlers(onTouchStart, setIntent)
  }];
}
function composeEventHandlers(theirHandler, ourHandler) {
  return event => {
    theirHandler && theirHandler(event);
    if (!event.defaultPrevented) {
      ourHandler(event);
    }
  };
}
function getActiveMatches(matches, errors, isSpaMode) {
  if (isSpaMode && !isHydrated) {
    return [matches[0]];
  }
  if (errors) {
    let errorIdx = matches.findIndex(m => errors[m.route.id] !== void 0);
    return matches.slice(0, errorIdx + 1);
  }
  return matches;
}
var CRITICAL_CSS_DATA_ATTRIBUTE = "data-react-router-critical-css";
function Links({
  nonce,
  crossOrigin
}) {
  let {
    isSpaMode,
    manifest,
    routeModules,
    criticalCss
  } = useFrameworkContext();
```

```
  let {
    errors,
    matches: routerMatches
  } = useDataRouterStateContext();
  let matches = getActiveMatches(routerMatches, errors, isSpaMode);
  let keyedLinks = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
getKeyedLinksForMatches(matches, routeModules, manifest), [matches, routeModules, manifest]);
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, typeof criticalCss === "string" ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("style", {
    ...{
      [CRITICAL_CSS_DATA_ATTRIBUTE]: ""
    },
    nonce,
    dangerouslySetInnerHTML: {
      __html: criticalCss
    }
  }) : null, typeof criticalCss === "object" ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    ...{
      [CRITICAL_CSS_DATA_ATTRIBUTE]:
 ""
    },
    rel: "stylesheet",
    href: criticalCss.href,
    nonce,
    crossOrigin
  }) : null, keyedLinks.map(({
    key,
    link
  }) => isPageLinkDescriptor(link) ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(PrefetchPageLinks, {
    key,
    nonce,
    ...link,
    crossOrigin: link.crossOrigin ?? crossOrigin
  }) : /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    key,
    nonce,
    ...link,
    crossOrigin: link.crossOrigin ?? crossOrigin
  })));
}
function PrefetchPageLinks({
  page,
  ...linkProps
}) {
  let rsc = useIsRSCRouterContext();
```

```
  let {
    router
  } = useDataRouterContext2();
  let matches = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
matchRoutes(router.routes, page, router.basename), [router.routes, page, router.basename]);
  if (!matches) {
    return null;
  }
  if (rsc) {
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RSCPrefetchPageLinksImpl, {
      page,
      matches,
      ...linkProps
    });
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(PrefetchPageLinksImpl, {
    page,
    matches,
    ...linkProps
  });
}
function useKeyedPrefetchLinks(matches) {
  let {
    manifest,
    routeModules
  } = useFrameworkContext();
  let [keyedPrefetchLinks, setKeyedPrefetchLinks] =
react__WEBPACK_IMPORTED_MODULE_0__.useState([]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    let interrupted = false;
    void getKeyedPrefetchLinks(matches, manifest, routeModules).then(links => {
      if (!interrupted) {
        setKeyedPrefetchLinks(links);
      }
    });
    return () => {
      interrupted = true;
    };
  }, [matches, manifest, routeModules]);
  return keyedPrefetchLinks;
}
function RSCPrefetchPageLinksImpl({
  page,
  matches: nextMatches,
  ...linkProps
}) {
  let location = useLocation();
```

```
  let {
    future
  } = useFrameworkContext();
  let {
    basename
  } = useDataRouterContext2();
  let dataHrefs = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    if (page === location.pathname + location.search + location.hash) {
      return [];
    }
    let url = singleFetchUrl(page, basename, future.unstable_trailingSlashAwareDataRequests, "rsc");
    let hasSomeRoutesWithShouldRevalidate = false;
    let targetRoutes = [];
    for (let match of nextMatches) {
      if (typeof match.route.shouldRevalidate === "function") {
        hasSomeRoutesWithShouldRevalidate = true;
      } else {
        targetRoutes.push(match.route.id);
      }
    }
    if (hasSomeRoutesWithShouldRevalidate && targetRoutes.length > 0) {
      url.searchParams.set("_routes", targetRoutes.join(","));
    }
    return [url.pathname + url.search];
  }, [basename, future.unstable_trailingSlashAwareDataRequests, page, location, nextMatches]);
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, dataHrefs.map(href => /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    key: href,
    rel: "prefetch",
    as: "fetch",
    href,
    ...linkProps
  })));
}
function PrefetchPageLinksImpl({
  page,
  matches: nextMatches,
  ...linkProps
}) {
  let location = useLocation();
  let {
    future,
    manifest,
    routeModules
  } = useFrameworkContext();
  let {
    basename
```

```
  } = useDataRouterContext2();
  let {
    loaderData,
    matches
  } = useDataRouterStateContext();
  let newMatchesForData = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
getNewMatchesForLinks(page, nextMatches, matches, manifest, location, "data"), [page, nextMatches,
matches, manifest, location]);
  let newMatchesForAssets = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
getNewMatchesForLinks(page, nextMatches, matches, manifest, location, "assets"), [page,
nextMatches, matches, manifest, location]);
  let dataHrefs = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    if (page === location.pathname + location.search + location.hash) {
      return [];
    }
    let routesParams = /* @__PURE__ */new Set();
    let foundOptOutRoute = false;
    nextMatches.forEach(m => {
      let manifestRoute = manifest.routes[m.route.id];
      if (!manifestRoute || !manifestRoute.hasLoader) {
        return;
      }
      if (!newMatchesForData.some(m2 => m2.route.id === m.route.id) && m.route.id in loaderData
&& routeModules[m.route.id]?.shouldRevalidate) {
        foundOptOutRoute = true;
      } else if (manifestRoute.hasClientLoader) {
        foundOptOutRoute = true;
      } else {
        routesParams.add(m.route.id);
      }
    });
    if (routesParams.size === 0) {
      return [];
    }
    let url = singleFetchUrl(page, basename, future.unstable_trailingSlashAwareDataRequests, "data");
    if (foundOptOutRoute && routesParams.size > 0) {
      url.searchParams.set("_routes", nextMatches.filter(m => routesParams.has(m.route.id)).map(m =>
m.route.id).join(","));
    }
    return [url.pathname + url.search];
  }, [basename, future.unstable_trailingSlashAwareDataRequests, loaderData, location, manifest,
newMatchesForData, nextMatches, page, routeModules]);
  let moduleHrefs = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
getModuleLinkHrefs(newMatchesForAssets, manifest), [newMatchesForAssets, manifest]);
  let keyedPrefetchLinks = useKeyedPrefetchLinks(newMatchesForAssets);
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, dataHrefs.map(href => /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
```

```
    key: href,
    rel: "prefetch",
    as: "fetch",
    href,
    ...linkProps
  })), moduleHrefs.map(href => /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    key: href,
    rel: "modulepreload",
    href,
    ...linkProps
  })), keyedPrefetchLinks.map(({
    key,
    link
  }) =>
  // these don't spread `linkProps` because they are full link descriptors
  // already with their own props
  /* @__PURE__ */
  react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    key,
    nonce: linkProps.nonce,
    ...link,
    crossOrigin: link.crossOrigin ?? linkProps.crossOrigin
  })));
}
function Meta() {
  let {
    isSpaMode,
    routeModules
  } = useFrameworkContext();
  let {
    errors,
    matches: routerMatches,
    loaderData
  } = useDataRouterStateContext();
  let location = useLocation();
  let _matches = getActiveMatches(routerMatches, errors, isSpaMode);
  let error = null;
  if (errors) {
    error = errors[_matches[_matches.length - 1].route.id];
  }
  let meta = [];
  let leafMeta = null;
  let matches = [];
  for (let i = 0; i < _matches.length; i++) {
    let _match = _matches[i];
    let routeId = _match.route.id;
    let data2 = loaderData[routeId];
    let params = _match.params;
```

```
    let routeModule = routeModules[routeId];
    let routeMeta = [];
    let match = {
      id: routeId,
      data: data2,
      loaderData: data2,
      meta: [],
      params: _match.params,
      pathname: _match.pathname,
      handle: _match.route.handle,
      error
    };
    matches[i] = match;
    if (routeModule?.meta) {
      routeMeta = typeof routeModule.meta === "function" ? routeModule.meta({
        data: data2,
        loaderData: data2,
        params,
        location,
        matches,
        error
      }) : Array.isArray(routeModule.meta) ? [...routeModule.meta] : routeModule.meta;
    } else if (leafMeta) {
      routeMeta = [...leafMeta];
    }
    routeMeta = routeMeta || [];
    if (!Array.isArray(routeMeta)) {
      throw new Error("The route at " + _match.route.path + " returns an invalid value. All route meta
functions must return an array of meta objects.\n\nTo reference the meta function API, see
https://reactrouter.com/start/framework/route-module#meta");
    }
    match.meta = routeMeta;
    matches[i] = match;
    meta = [...routeMeta];
    leafMeta = meta;
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, meta.flat().map(metaProps => {
    if (!metaProps) {
      return null;
    }
    if ("tagName" in metaProps) {
      let {
        tagName,
        ...rest
      } = metaProps;
      if (!isValidMetaTag(tagName)) {
        console.warn(`A meta object uses an invalid tagName: ${tagName}. Expected either 'link' or
```

```
'meta'`);
        return null;
      }
      let Comp = tagName;
      return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Comp, {
        key: JSON.stringify(rest),
        ...rest
      });
    }
    if ("title" in metaProps) {
      return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("title", {
        key: "title"
      }, String(metaProps.title));
    }
    if ("charset" in metaProps) {
      metaProps.charSet ?? (metaProps.charSet = metaProps.charset);
      delete metaProps.charset;
    }
    if ("charSet" in metaProps && metaProps.charSet != null) {
      return typeof metaProps.charSet === "string" ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("meta", {
        key: "charSet",
        charSet: metaProps.charSet
      }) : null;
    }
    if ("script:ld+json" in metaProps) {
      try {
        let json = JSON.stringify(metaProps["script:ld+json"]);
        return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
          key: `script:ld+json:${json}`,
          type: "application/ld+json",
          dangerouslySetInnerHTML: {
            __html: escapeHtml(json)
          }
        });
      } catch (e) {
        return null;
      }
    }
    return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("meta", {
      key: JSON.stringify(metaProps),
      ...metaProps
    });
  }));
}
function isValidMetaTag(tagName) {
  return typeof tagName === "string" && /^(meta|link)$/.test(tagName);
}
```

```
var
 isHydrated = false;
function setIsHydrated() {
  isHydrated = true;
}
function Scripts(scriptProps) {
  let {
    manifest,
    serverHandoffString,
    isSpaMode,
    renderMeta,
    routeDiscovery,
    ssr
  } = useFrameworkContext();
  let {
    router,
    static: isStatic,
    staticContext
  } = useDataRouterContext2();
  let {
    matches: routerMatches
  } = useDataRouterStateContext();
  let isRSCRouterContext = useIsRSCRouterContext();
  let enableFogOfWar = isFogOfWarEnabled(routeDiscovery, ssr);
  if (renderMeta) {
    renderMeta.didRenderScripts = true;
  }
  let matches = getActiveMatches(routerMatches, null, isSpaMode);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    setIsHydrated();
  }, []);
  let initialScripts = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    if (isRSCRouterContext) {
      return null;
    }
    let streamScript = "window.__reactRouterContext.stream = new ReadableStream({start(controller)
{window.__reactRouterContext.streamController = controller;}}).pipeThrough(new
TextEncoderStream());";
    let contextScript = staticContext ? `window.__reactRouterContext = ${serverHandoffString};$
{streamScript}` : " ";
    let routeModulesScript = !isStatic ? " " : `${manifest.hmr?.runtime ? `import $
{JSON.stringify(manifest.hmr.runtime)};` : ""}${!enableFogOfWar ? `import $
{JSON.stringify(manifest.url)}` : ""};
${matches.map((match, routeIndex) => {
      let routeVarName = `route${routeIndex}`;
      let manifestEntry = manifest.routes[match.route.id];
      invariant2(manifestEntry, `Route ${match.route.id} not found in manifest`);
      let {
        clientActionModule,
```

```
        clientLoaderModule,
        clientMiddlewareModule,
        hydrateFallbackModule,
        module
      } = manifestEntry;
      let chunks = [...(clientActionModule ? [{
        module: clientActionModule,
        varName: `${routeVarName}_clientAction`
      }] : []), ...(clientLoaderModule ? [{
        module: clientLoaderModule,
        varName: `${routeVarName}_clientLoader`
      }] : []), ...(clientMiddlewareModule ? [{
        module: clientMiddlewareModule,
        varName: `${routeVarName}_clientMiddleware`
      }] : []), ...(hydrateFallbackModule ? [{
        module: hydrateFallbackModule,
        varName: `${routeVarName}_HydrateFallback`
      }] : []), {
        module,
        varName: `${routeVarName}_main`
      }];
      if (chunks.length === 1) {
        return `import * as ${routeVarName} from ${JSON.stringify(module)};`;
      }
      let chunkImportsSnippet = chunks.map(chunk => `import * as ${chunk.varName} from "$
{chunk.module}";`).join("\n");
      let mergedChunksSnippet = `const ${routeVarName} = {${chunks.map(chunk => `...$
{chunk.varName}`).join(",")}};`;
      return [chunkImportsSnippet, mergedChunksSnippet].join("\n");
    }).join("\n")}
  ${enableFogOfWar ?
    // Inline a minimal manifest with the SSR matches
    `window.__reactRouterManifest = ${JSON.stringify(getPartialManifest(manifest, router), null,
2)};` : ""}
  window.__reactRouterRouteModules = {${matches.map((match, index) => `$
{JSON.stringify(match.route.id)}:route${index}`).join(",")}};

import(${JSON.stringify(manifest.entry.module)});`;
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
      ...scriptProps,
      suppressHydrationWarning: true,
      dangerouslySetInnerHTML: {
        __html: contextScript
      },
      type: void 0
    }), /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
```

```
      ...scriptProps,
      suppressHydrationWarning: true,
      dangerouslySetInnerHTML: {
        __html: routeModulesScript
      },
      type: "module",
      async: true
    }));
  }, []);
  let preloads = isHydrated || isRSCRouterContext ? [] : [
  // Dedupe through a Set
  ...new Set(manifest.entry.imports.concat(getModuleLinkHrefs(matches, manifest, {
    includeHydrateFallback: true
  })))];
  let sri = typeof manifest.sri === "object" ? manifest.sri : {};
  warnOnce(!isRSCRouterContext, "The <Scripts /> element is a no-op when using RSC and can be
safely removed.");
  return isHydrated || isRSCRouterContext ? null : /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, typeof manifest.sri === "object" ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    ...scriptProps,
    "rr-importmap": "",
    type: "importmap",
    suppressHydrationWarning: true,
    dangerouslySetInnerHTML: {
      __html: JSON.stringify({
        integrity: sri
      })
    }
  }) : null, !enableFogOfWar ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    rel: "modulepreload",
    href: manifest.url,
    crossOrigin: scriptProps.crossOrigin,
    integrity: sri[manifest.url],
    nonce: scriptProps.nonce,
    suppressHydrationWarning: true
  }) : null, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    rel: "modulepreload",
    href: manifest.entry.module,
    crossOrigin: scriptProps.crossOrigin,
    integrity: sri[manifest.entry.module],
    nonce: scriptProps.nonce,
    suppressHydrationWarning: true
  }), preloads.map(path => /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("link", {
    key: path,
    rel: "modulepreload",
```

```
    href: path,
    crossOrigin: scriptProps.crossOrigin,
    integrity: sri[path],
    nonce: scriptProps.nonce,
    suppressHydrationWarning: true
  })), initialScripts);
}
function mergeRefs(...refs) {
  return value => {
    refs.forEach(ref => {
      if (typeof ref === "function") {
        ref(value);
      } else if (ref != null) {
        ref.current = value;
      }
    });
  };
}

// lib/dom/ssr/errorBoundaries.tsx
var RemixErrorBoundary = class extends
react__WEBPACK_IMPORTED_MODULE_0__.Component {
  constructor(props) {
    super(props);
    this.state = {
      error: props.error || null,
      location: props.location
    };
  }
  static getDerivedStateFromError(error) {
    return {
      error
    };
  }
  static getDerivedStateFromProps(props, state) {
    if (state.location !== props.location) {
      return {
        error: props.error || null,
        location: props.location
      };
    }
    return {
      error: props.error || state.error,
      location: state.location
    };
  }
  render() {
    if (this.state.error) {
      return /* @__PURE__
```

```
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(RemixRootDefaultErrorBoundary,
{
       error: this.state.error,
       isOutsideRemixApp: true
     });
   } else {
     return this.props.children;
   }
  }
};
function RemixRootDefaultErrorBoundary({
  error,
  isOutsideRemixApp
}) {
  console.error(error);
  let heyDeveloper = /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    dangerouslySetInnerHTML: {
      __html: `
        console.log(
          "\u{1F4BF} Hey developer \u{1F44B}. You can provide a way better UX than this when your
app throws errors. Check out https://reactrouter.com/how-to/error-boundary for more information."
        );
      `
    }
  });
  if (isRouteErrorResponse(error)) {
    return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(BoundaryShell, {
      title: "Unhandled Thrown Response!"
    }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("h1", {
      style: {
        fontSize: "24px"
      }
    }, error.status, " ", error.statusText), ENABLE_DEV_WARNINGS ? heyDeveloper : null);
  }
  let errorInstance;
  if (error instanceof Error) {
    errorInstance = error;
  } else {
    let errorString = error == null ? "Unknown Error" : typeof error === "object" && "toString" in
error ? error.toString() : JSON.stringify(error);
    errorInstance = new Error(errorString);
  }
  return /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(BoundaryShell, {
    title: "Application Error!",
    isOutsideRemixApp
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("h1", {
```

```
    style: {
      fontSize: "24px"
    }
  }, "Application Error"), /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("pre", {
    style: {
      padding: "2rem",
      background: "hsla(10, 50%, 50%, 0.1)",
      color: "red",
      overflow: "auto"
    }
  }, errorInstance.stack), heyDeveloper);
}
function BoundaryShell({
  title,
  renderScripts,
  isOutsideRemixApp,
  children
}) {
  let {
    routeModules
  } = useFrameworkContext();
  if (routeModules.root?.Layout && !isOutsideRemixApp) {
    return children;
  }
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("html", {
    lang: "en"
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("head", null, /*
@__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("meta", {
    charSet: "utf-8"
  }), /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("meta", {
    name: "viewport",
    content: "width=device-width,initial-scale=1,viewport-fit=cover"
  }), /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("title", null,
title)), /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("body",
null, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("main", {
    style: {
      fontFamily: "system-ui, sans-serif",
      padding: "2rem"
    }
  }, children, renderScripts ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(Scripts, null) : null)));
}

// lib/dom/lib.tsx

var isBrowser2 = typeof window !== "undefined" && typeof window.document !== "undefined" &&
typeof window.document.createElement !== "undefined";
try {
```

```
  if (isBrowser2) {
    window.__reactRouterVersion =
    // @ts-expect-error
    "7.15.1";
  }
} catch (e) {}
function createBrowserRouter(routes,
 opts) {
  return createRouter({
    basename: opts?.basename,
    getContext: opts?.getContext,
    future: opts?.future,
    history: createBrowserHistory({
      window: opts?.window
    }),
    hydrationData: opts?.hydrationData || parseHydrationData(),
    routes,
    mapRouteProperties,
    hydrationRouteProperties,
    dataStrategy: opts?.dataStrategy,
    patchRoutesOnNavigation: opts?.patchRoutesOnNavigation,
    window: opts?.window,
    instrumentations: opts?.instrumentations
  }).initialize();
}
function createHashRouter(routes, opts) {
  return createRouter({
    basename: opts?.basename,
    getContext: opts?.getContext,
    future: opts?.future,
    history: createHashHistory({
      window: opts?.window
    }),
    hydrationData: opts?.hydrationData || parseHydrationData(),
    routes,
    mapRouteProperties,
    hydrationRouteProperties,
    dataStrategy: opts?.dataStrategy,
    patchRoutesOnNavigation: opts?.patchRoutesOnNavigation,
    window: opts?.window,
    instrumentations: opts?.instrumentations
  }).initialize();
}
function parseHydrationData() {
  let state = window?.__staticRouterHydrationData;
  if (state && state.errors) {
    state = {
      ...state,
      errors: deserializeErrors(state.errors)
```

```
    };
  }
  return state;
}
function deserializeErrors(errors) {
  if (!errors) return null;
  let entries = Object.entries(errors);
  let serialized = {};
  for (let [key, val] of entries) {
    if (val && val.__type === "RouteErrorResponse") {
      serialized[key] = new ErrorResponseImpl(val.status, val.statusText, val.data, val.internal === true);
    } else if (val && val.__type === "Error") {
      if (val.__subType) {
        let ErrorConstructor = window[val.__subType];
        if (typeof ErrorConstructor === "function") {
          try {
            let error = new ErrorConstructor(val.message);
            error.stack = "";
            serialized[key] = error;
          } catch (e) {}
        }
      }
      if (serialized[key] == null) {
        let error = new Error(val.message);
        error.stack = "";
        serialized[key] = error;
      }
    } else {
      serialized[key] = val;
    }
  }
  return serialized;
}
function BrowserRouter({
  basename,
  children,
  useTransitions,
  window: window2
}) {
  let historyRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef();
  if (historyRef.current == null) {
    historyRef.current = createBrowserHistory({
      window: window2,
      v5Compat: true
    });
  }
  let history = historyRef.current;
  let [state, setStateImpl] = react__WEBPACK_IMPORTED_MODULE_0__.useState({
    action: history.action,
```

```
    location: history.location
  });
  let setState = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(newState => {
    if (useTransitions === false) {
      setStateImpl(newState);
    } else {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => setStateImpl(newState));
    }
  }, [useTransitions]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => history.listen(setState),
[history, setState]);
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
    children,
    location: state.location,
    navigationType: state.action,
    navigator: history,
    useTransitions
  });
}
function HashRouter({
  basename,
  children,
  useTransitions,
  window: window2
}) {
  let historyRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef();
  if (historyRef.current == null) {
    historyRef.current = createHashHistory({
      window: window2,
      v5Compat: true
    });
  }
  let history = historyRef.current;
  let [state, setStateImpl] = react__WEBPACK_IMPORTED_MODULE_0__.useState({
    action: history.action,
    location: history.location
  });
  let setState = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(newState => {
    if (useTransitions === false) {
      setStateImpl(newState);
    } else {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => setStateImpl(newState));
    }
  }, [useTransitions]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => history.listen(setState),
[history, setState]);
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
```

```
    children,
    location: state.location,
    navigationType: state.action,
    navigator: history,
    useTransitions
  });
}
function HistoryRouter({
  basename,
  children,
  history,
  useTransitions
}) {
  let [state, setStateImpl] = react__WEBPACK_IMPORTED_MODULE_0__.useState({
    action: history.action,
    location: history.location
  });
  let setState = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(newState => {
    if (useTransitions === false) {
      setStateImpl(newState);
    } else {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => setStateImpl(newState));
    }
  }, [useTransitions]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => history.listen(setState),
[history, setState]);
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
    children,
    location: state.location,
    navigationType: state.action,
    navigator: history,
    useTransitions
  });
}
HistoryRouter.displayName = "unstable_HistoryRouter";
var ABSOLUTE_URL_REGEX2 = /^(?:[a-z][a-z0-9+.-]*:|\/\/)/i;
var Link = react__WEBPACK_IMPORTED_MODULE_0__.forwardRef(function LinkWithRef({
  onClick,
  discover = "render",
  prefetch = "none",
  relative,
  reloadDocument,
  replace: replace2,
  mask,
  state,
  target,
  to,
  preventScrollReset,
```

```
  viewTransition,
  defaultShouldRevalidate,
  ...rest
}, forwardedRef) {
  let {
    basename,
    navigator,
    useTransitions
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let isAbsolute = typeof to === "string" && ABSOLUTE_URL_REGEX2.test(to);
  let parsed = parseToInfo(to, basename);
  to = parsed.to;
  let href = useHref(to, {
    relative
  });
  let location = useLocation();
  let maskedHref = null;
  if (mask) {
    let resolved = resolveTo(mask, [], location.mask ? location.mask.pathname : "/", true);
    if (basename !== "/") {
      resolved.pathname = resolved.pathname === "/" ? basename : joinPaths([basename,
resolved.pathname]);
    }
    maskedHref = navigator.createHref(resolved);
  }
  let [shouldPrefetch, prefetchRef, prefetchHandlers] = usePrefetchBehavior(prefetch, rest);
  let internalOnClick = useLinkClickHandler(to, {
    replace: replace2,
    mask,
    state,
    target,
    preventScrollReset,
    relative,
    viewTransition,
    defaultShouldRevalidate,
    useTransitions
  });
  function handleClick(event) {
    if (onClick) onClick(event);
    if (!event.defaultPrevented) {
      internalOnClick(event);
    }
  }
  let isSpaLink = !(parsed.isExternal || reloadDocument);
  let link =
  // eslint-disable-next-line jsx-a11y/anchor-has-content
  /* @__PURE__ */
  react__WEBPACK_IMPORTED_MODULE_0__.createElement("a", {
    ...rest,
```

```
    ...prefetchHandlers,
    href: (isSpaLink ? maskedHref : void 0) || parsed.absoluteURL || href,
    onClick: isSpaLink ? handleClick : onClick,
    ref: mergeRefs(forwardedRef, prefetchRef),
    target,
    "data-discover": !isAbsolute && discover === "render" ? "true" : void 0
  });
  return shouldPrefetch && !isAbsolute ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, link, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(PrefetchPageLinks, {
    page: href
  })) : link;
});
Link.displayName = "Link";
var NavLink = react__WEBPACK_IMPORTED_MODULE_0__.forwardRef(function
NavLinkWithRef({
  "aria-current": ariaCurrentProp = "page",
  caseSensitive = false,
  className: classNameProp = "",
  end = false,
  style: styleProp,
  to,
  viewTransition,
  children,
  ...rest
}, ref) {
  let path = useResolvedPath(to, {
    relative: rest.relative
  });
  let location = useLocation();
  let routerState =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterStateContext);
  let {
    navigator,
    basename
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let isTransitioning = routerState != null &&
  // Conditional usage is OK here because the usage of a data router is static
  // eslint-disable-next-line react-hooks/rules-of-hooks
  useViewTransitionState(path) && viewTransition === true;
  let toPathname = navigator.encodeLocation ? navigator.encodeLocation(path).pathname :
path.pathname;
  let locationPathname = location.pathname;
  let nextLocationPathname = routerState && routerState.navigation &&
routerState.navigation.location ? routerState.navigation.location.pathname : null;
  if (!caseSensitive) {
    locationPathname = locationPathname.toLowerCase();
    nextLocationPathname = nextLocationPathname ? nextLocationPathname.toLowerCase() : null;
```

```
    toPathname = toPathname.toLowerCase();
  }
  if (nextLocationPathname && basename) {
    nextLocationPathname = stripBasename(nextLocationPathname, basename) ||
nextLocationPathname;
  }
  const endSlashPosition = toPathname !== "/" && toPathname.endsWith("/") ? toPathname.length - 1 :
toPathname.length;
  let isActive = locationPathname === toPathname || !end &&
locationPathname.startsWith(toPathname) && locationPathname.charAt(endSlashPosition) === "/";
  let isPending = nextLocationPathname != null && (nextLocationPathname === toPathname || !end
&& nextLocationPathname.startsWith(toPathname) &&
nextLocationPathname.charAt(toPathname.length) === "/");
  let renderProps = {
    isActive,
    isPending,
    isTransitioning
  };
  let ariaCurrent = isActive ? ariaCurrentProp : void 0;
  let className;
  if (typeof classNameProp === "function") {
    className = classNameProp(renderProps);
  } else {
    className = [classNameProp, isActive ? "active" : null, isPending ? "pending" : null, isTransitioning
? "transitioning" : null].filter(Boolean).join(" ");

  }
  let style = typeof styleProp === "function" ? styleProp(renderProps) : styleProp;
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Link, {
    ...rest,
    "aria-current": ariaCurrent,
    className,
    ref,
    style,
    to,
    viewTransition
  }, typeof children === "function" ? children(renderProps) : children);
});
NavLink.displayName = "NavLink";
var Form = react__WEBPACK_IMPORTED_MODULE_0__.forwardRef(({
  discover = "render",
  fetcherKey,
  navigate,
  reloadDocument,
  replace: replace2,
  state,
  method = defaultMethod,
  action,
  onSubmit,
```

```
  relative,
  preventScrollReset,
  viewTransition,
  defaultShouldRevalidate,
  ...props
}, forwardedRef) => {
  let {
    useTransitions
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let submit = useSubmit();
  let formAction = useFormAction(action, {
    relative
  });
  let formMethod = method.toLowerCase() === "get" ? "get" : "post";
  let isAbsolute = typeof action === "string" && ABSOLUTE_URL_REGEX2.test(action);
  let submitHandler = event => {
    onSubmit && onSubmit(event);
    if (event.defaultPrevented) return;
    event.preventDefault();
    let submitter = event.nativeEvent.submitter;
    let submitMethod = submitter?.getAttribute("formmethod") || method;
    let doSubmit = () => submit(submitter || event.currentTarget, {
      fetcherKey,
      method: submitMethod,
      navigate,
      replace: replace2,
      state,
      relative,
      preventScrollReset,
      viewTransition,
      defaultShouldRevalidate
    });
    if (useTransitions && navigate !== false) {
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => doSubmit());
    } else {
      doSubmit();
    }
  };
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("form", {
    ref: forwardedRef,
    method: formMethod,
    action: formAction,
    onSubmit: reloadDocument ? onSubmit : submitHandler,
    ...props,
    "data-discover": !isAbsolute && discover === "render" ? "true" : void 0
  });
});
Form.displayName = "Form";
function ScrollRestoration({
```

```
  getKey,
  storageKey,
  ...props
}) {
  let remixContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(FrameworkContext);
  let {
    basename
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let location = useLocation();
  let matches = useMatches();
  useScrollRestoration({
    getKey,
    storageKey
  });
  let ssrKey = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    if (!remixContext || !getKey) return null;
    let userKey = getScrollRestorationKey(location, matches, basename, getKey);
    return userKey !== location.key ? userKey : null;
  },
  // Nah, we only need this the first time for the SSR render
  // eslint-disable-next-line react-hooks/exhaustive-deps
  []);
  if (!remixContext || remixContext.isSpaMode) {
    return null;
  }
  let restoreScroll = ((storageKey2, restoreKey) => {
    if (!window.history.state || !window.history.state.key) {
      let key = Math.random().toString(32).slice(2);
      window.history.replaceState({
        key
      }, "");
    }
    try {
      let positions = JSON.parse(sessionStorage.getItem(storageKey2) || "{}");
      let storedY = positions[restoreKey || window.history.state.key];
      if (typeof storedY === "number") {
        window.scrollTo(0, storedY);
      }
    } catch (error) {
      console.error(error);
      sessionStorage.removeItem(storageKey2);
    }
  }).toString();
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    ...props,
    suppressHydrationWarning: true,
    dangerouslySetInnerHTML: {
      __html: `(${restoreScroll})(${escapeHtml(JSON.stringify(storageKey ||
```

```
SCROLL_RESTORATION_STORAGE_KEY))}, ${escapeHtml(JSON.stringify(ssrKey))})`
    }
  });
}
ScrollRestoration.displayName = "ScrollRestoration";
function getDataRouterConsoleError2(hookName) {
  return `${hookName} must be used within a data router.  See
https://reactrouter.com/en/main/routers/picking-a-router.`;
}
function useDataRouterContext3(hookName) {
  let ctx = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterContext);
  invariant(ctx, getDataRouterConsoleError2(hookName));
  return ctx;
}
function useDataRouterState2(hookName) {
  let state = react__WEBPACK_IMPORTED_MODULE_0__.useContext(DataRouterStateContext);
  invariant(state, getDataRouterConsoleError2(hookName));
  return state;
}
function useLinkClickHandler(to, {
  target,
  replace: replaceProp,
  mask,
  state,
  preventScrollReset,
  relative,
  viewTransition,
  defaultShouldRevalidate,
  useTransitions
} = {}) {
  let navigate = useNavigate();
  let location = useLocation();
  let path = useResolvedPath(to, {
    relative
  });
  return react__WEBPACK_IMPORTED_MODULE_0__.useCallback(event => {
    if (shouldProcessLinkClick(event, target)) {
      event.preventDefault();
      let replace2 = replaceProp !== void 0 ? replaceProp : createPath(location) === createPath(path);
      let doNavigate = () => navigate(to, {
        replace: replace2,
        mask,
        state,
        preventScrollReset,
        relative,
        viewTransition,
        defaultShouldRevalidate
      });
      if (useTransitions) {
```

```
      react__WEBPACK_IMPORTED_MODULE_0__.startTransition(() => doNavigate());
    } else {
      doNavigate();
    }
  }
 }, [location, navigate, path, replaceProp, mask, state, target, to, preventScrollReset, relative,
viewTransition, defaultShouldRevalidate, useTransitions]);
}
function useSearchParams(defaultInit) {
 warning(typeof URLSearchParams !== "undefined", `You cannot use the \`useSearchParams\` hook in
a browser that does not support the URLSearchParams API. If you need to support Internet Explorer
11, we recommend you load a polyfill such as https://github.com/ungap/url-search-params.`);
 let defaultSearchParamsRef =
react__WEBPACK_IMPORTED_MODULE_0__.useRef(createSearchParams(defaultInit));
 let hasSetSearchParamsRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(false);
 let location = useLocation();
 let searchParams = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
 // Only merge in the defaults if we haven't yet called setSearchParams.
 // Once we call that we want those to take precedence, otherwise you can't
 // remove a param with setSearchParams({}) if it has an initial value
 getSearchParamsForLocation(location.search, hasSetSearchParamsRef.current ? null :
defaultSearchParamsRef.current), [location.search]);
 let navigate = useNavigate();
 let setSearchParams = react__WEBPACK_IMPORTED_MODULE_0__.useCallback((nextInit,
navigateOptions) => {
   const newSearchParams = createSearchParams(typeof nextInit === "function" ? nextInit(new
URLSearchParams(searchParams)) : nextInit);
   hasSetSearchParamsRef.current = true;
   navigate("?" + newSearchParams, navigateOptions);
 }, [navigate, searchParams]);
 return [searchParams, setSearchParams];
}
var fetcherId = 0;
var getUniqueFetcherId = () => `__${String(++fetcherId)}__`;
function useSubmit() {
 let {
   router
 } = useDataRouterContext3("useSubmit" /* UseSubmit */);
 let {
   basename
 } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
 let currentRouteId = useRouteId();
 let routerFetch = router.fetch;
 let routerNavigate = router.navigate;
 return react__WEBPACK_IMPORTED_MODULE_0__.useCallback(async (target, options = {}) =>
{
   let {
     action,
     method,
```

```
      encType,
      formData,
      body
    } = getFormSubmissionInfo(target, basename);
    if (options.navigate === false) {
      let key = options.fetcherKey || getUniqueFetcherId();
      await routerFetch(key, currentRouteId, options.action || action, {
        defaultShouldRevalidate: options.defaultShouldRevalidate,
        preventScrollReset: options.preventScrollReset,
        formData,
        body,
        formMethod: options.method || method,
        formEncType: options.encType || encType,
        flushSync: options.flushSync
      });
    } else {
      await routerNavigate(options.action || action, {
        defaultShouldRevalidate: options.defaultShouldRevalidate,
        preventScrollReset: options.preventScrollReset,
        formData,
        body,
        formMethod: options.method || method,
        formEncType: options.encType || encType,
        replace: options.replace,
        state: options.state,
        fromRouteId: currentRouteId,
        flushSync: options.flushSync,
        viewTransition: options.viewTransition
      });
    }
  }, [routerFetch, routerNavigate, basename, currentRouteId]);
}
function useFormAction(action, {
  relative
} = {}) {
  let {
    basename
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let routeContext = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  invariant(routeContext, "useFormAction must be used inside a RouteContext");
  let [match] = routeContext.matches.slice(-1);
  let path = {
    ...useResolvedPath(action ? action : ".", {
      relative
    })
  };
  let location = useLocation();
  if (action == null) {
    path.search = location.search;
```

```
    let params = new URLSearchParams(path.search);
    let indexValues = params.getAll("index");
    let hasNakedIndexParam = indexValues.some(v => v === "");
    if (hasNakedIndexParam) {
      params.delete("index");
      indexValues.filter(v => v).forEach(v => params.append("index", v));
      let qs = params.toString();
      path.search = qs ? `?${qs}` : "";
    }
  }
  if ((!action || action === ".") && match.route.index) {
    path.search = path.search ? path.search.replace(/^\?/, "?index&") : "?index";
  }
  if (basename !== "/") {
    path.pathname = path.pathname === "/" ? basename : joinPaths([basename, path.pathname]);
  }
  return createPath(path);
}
function useFetcher({
  key
} = {}) {
  let {
    router
  } = useDataRouterContext3("useFetcher"
 /* UseFetcher */);
  let state = useDataRouterState2("useFetcher" /* UseFetcher */);
  let fetcherData = react__WEBPACK_IMPORTED_MODULE_0__.useContext(FetchersContext);
  let route = react__WEBPACK_IMPORTED_MODULE_0__.useContext(RouteContext);
  let routeId = route.matches[route.matches.length - 1]?.route.id;
  invariant(fetcherData, `useFetcher must be used inside a FetchersContext`);
  invariant(route, `useFetcher must be used inside a RouteContext`);
  invariant(routeId != null, `useFetcher can only be used on routes that contain a unique "id"`);
  let defaultKey = react__WEBPACK_IMPORTED_MODULE_0__.useId();
  let [fetcherKey, setFetcherKey] = react__WEBPACK_IMPORTED_MODULE_0__.useState(key ||
defaultKey);
  if (key && key !== fetcherKey) {
    setFetcherKey(key);
  }
  let {
    deleteFetcher,
    getFetcher,
    resetFetcher,
    fetch: routerFetch
  } = router;
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    getFetcher(fetcherKey);
    return () => deleteFetcher(fetcherKey);
  }, [deleteFetcher, getFetcher, fetcherKey]);
  let load = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(async (href, opts) => {
```

```
    invariant(routeId, "No routeId available for fetcher.load()");
    await routerFetch(fetcherKey, routeId, href, opts);
  }, [fetcherKey, routeId, routerFetch]);
  let submitImpl = useSubmit();
  let submit = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(async (target, opts) => {
    await submitImpl(target, {
      ...opts,
      navigate: false,
      fetcherKey
    });
  }, [fetcherKey, submitImpl]);
  let reset = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(opts =>
resetFetcher(fetcherKey, opts), [resetFetcher, fetcherKey]);
  let FetcherForm = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    let FetcherForm2 = react__WEBPACK_IMPORTED_MODULE_0__.forwardRef((props, ref) => {
      return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Form, {
        ...props,
        navigate: false,
        fetcherKey,
        ref
      });
    });
    FetcherForm2.displayName = "fetcher.Form";
    return FetcherForm2;
  }, [fetcherKey]);
  let fetcher = state.fetchers.get(fetcherKey) || IDLE_FETCHER;
  let data2 = fetcherData.get(fetcherKey);
  let fetcherWithComponents = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => ({
    Form: FetcherForm,
    submit,
    load,
    reset,
    ...fetcher,
    data: data2
  }), [FetcherForm, submit, load, reset, fetcher, data2]);
  return fetcherWithComponents;
}
function useFetchers() {
  let state = useDataRouterState2("useFetchers" /* UseFetchers */);
  return react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
Array.from(state.fetchers.entries()).map(([key, fetcher]) => ({
    ...fetcher,
    key
  })), [state.fetchers]);
}
var SCROLL_RESTORATION_STORAGE_KEY = "react-router-scroll-positions";
var savedScrollPositions = {};
function getScrollRestorationKey(location, matches, basename, getKey) {
  let key = null;
```

```
  if (getKey) {
    if (basename !== "/") {
      key = getKey({
        ...location,
        pathname: stripBasename(location.pathname, basename) || location.pathname
      }, matches);
    } else {
      key = getKey(location, matches);
    }
  }
  if (key == null) {
    key = location.key;
  }
  return key;
}
function useScrollRestoration({
  getKey,
  storageKey
} = {}) {
  let {
    router
  } = useDataRouterContext3("useScrollRestoration" /* UseScrollRestoration */);
  let {
    restoreScrollPosition,
    preventScrollReset
  } = useDataRouterState2("useScrollRestoration" /* UseScrollRestoration */);
  let {
    basename
  } = react__WEBPACK_IMPORTED_MODULE_0__.useContext(NavigationContext);
  let location = useLocation();
  let matches = useMatches();
  let navigation = useNavigation();
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    window.history.scrollRestoration = "manual";
    return () => {
      window.history.scrollRestoration = "auto";
    };
  }, []);
  usePageHide(react__WEBPACK_IMPORTED_MODULE_0__.useCallback(() => {
    if (navigation.state === "idle") {
      let key = getScrollRestorationKey(location, matches, basename, getKey);
      savedScrollPositions[key] = window.scrollY;
    }
    try {
      sessionStorage.setItem(storageKey || SCROLL_RESTORATION_STORAGE_KEY,
JSON.stringify(savedScrollPositions));
    } catch (error) {
      warning(false, `Failed to save scroll positions in sessionStorage, <ScrollRestoration /> will not
work properly (${error}).`);
```

```
    }
    window.history.scrollRestoration = "auto";
  }, [navigation.state, getKey, basename, location, matches, storageKey]));
  if (typeof document !== "undefined") {
    react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => {
      try {
        let sessionPositions = sessionStorage.getItem(storageKey ||
SCROLL_RESTORATION_STORAGE_KEY);
        if (sessionPositions) {
          savedScrollPositions = JSON.parse(sessionPositions);
        }
      } catch (e) {}
    }, [storageKey]);
    react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => {
      let disableScrollRestoration = router?.enableScrollRestoration(savedScrollPositions, () =>
window.scrollY, getKey ? (location2, matches2) => getScrollRestorationKey(location2, matches2,
basename, getKey) : void 0);
      return () => disableScrollRestoration && disableScrollRestoration();
    }, [router, basename, getKey]);
    react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => {
      if (restoreScrollPosition === false) {
        return;
      }
      if (typeof restoreScrollPosition === "number") {
        window.scrollTo(0, restoreScrollPosition);
        return;
      }
      try {
        if (location.hash) {
          let el = document.getElementById(decodeURIComponent(location.hash.slice(1)));
          if (el) {
            el.scrollIntoView();
            return;
          }
        }
      } catch {
        warning(false, `"${location.hash.slice(1)}" is not a decodable element ID. The view will not scroll
to it.`);
      }
      if (preventScrollReset === true) {
        return;
      }
      window.scrollTo(0, 0);
    }, [location, restoreScrollPosition, preventScrollReset]);
  }
}
function useBeforeUnload(callback, options) {
  let {
    capture
```

```
  } = options || {};
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    let opts = capture != null ? {
      capture
    } : void 0;
    window.addEventListener("beforeunload", callback, opts);
    return () => {
      window.removeEventListener("beforeunload", callback, opts);
    };
  }, [callback, capture]);
}
function usePageHide(callback, options) {
  let {
    capture
  } = options || {};
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    let opts = capture != null ? {
      capture
    } : void 0;
    window.addEventListener("pagehide", callback, opts);
    return () => {
      window.removeEventListener("pagehide", callback, opts);
    };
  }, [callback, capture]);
}
function usePrompt({
  when,
  message
}) {
  let blocker = useBlocker(when);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (blocker.state === "blocked") {
      let proceed = window.confirm(message);
      if (proceed) {
        setTimeout(blocker.proceed, 0);
      } else {
        blocker.reset();
      }
    }
  }, [blocker, message]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (blocker.state === "blocked" && !when) {
      blocker.reset();
    }
  }, [blocker, when]);
}
function useViewTransitionState(to, {
  relative
} = {}) {
```

```
  let vtContext =
react__WEBPACK_IMPORTED_MODULE_0__.useContext(ViewTransitionContext);
  invariant(vtContext != null, "`useViewTransitionState` must be used within `react-router-dom`'s
`RouterProvider`.  Did you accidentally import `RouterProvider` from `react-router`?");
  let {
    basename
  } = useDataRouterContext3("useViewTransitionState" /* useViewTransitionState */);
  let path = useResolvedPath(to, {
    relative
  });
  if (!vtContext.isTransitioning) {
    return false;
  }
  let currentPath = stripBasename(vtContext.currentLocation.pathname, basename) ||
vtContext.currentLocation.pathname;
  let nextPath = stripBasename(vtContext.nextLocation.pathname, basename) ||
vtContext.nextLocation.pathname;
  return matchPath(path.pathname, nextPath) != null || matchPath(path.pathname, currentPath) != null;
}

// lib/dom/server.tsx

function StaticRouter({
  basename,
  children,
  location: locationProp = "/"
}) {
  if (typeof locationProp === "string") {
    locationProp = parsePath(locationProp);
  }
  let action = "POP" /* Pop */;
  let location = {
    pathname: locationProp.pathname || "/",
    search: locationProp.search || "",
    hash: locationProp.hash || "",
    state: locationProp.state != null ? locationProp.state : null,
    key: locationProp.key || "default",
    mask: void 0
  };
  let staticNavigator = getStatelessNavigator();
  return /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename,
    children,
    location,
    navigationType: action,
    navigator: staticNavigator,
    static: true,
    useTransitions: false
  });
```

```
}
function StaticRouterProvider({
  context,
  router,
  hydrate: hydrate2 = true,
  nonce
}) {
  invariant(router && context, "You must provide `router` and `context` to <StaticRouterProvider>");
  let dataRouterContext = {
    router,
    navigator: getStatelessNavigator(),
    static: true,
    staticContext: context,
    basename: context.basename || "/"
  };
  let fetchersContext = /* @__PURE__ */new Map();
  let hydrateScript = "";
  if (hydrate2 !== false) {
    let data2 = {
      loaderData: context.loaderData,
      actionData: context.actionData,
      errors: serializeErrors(context.errors)
    };
    let json = escapeHtml(JSON.stringify(JSON.stringify(data2)));
    hydrateScript = `window.__staticRouterHydrationData = JSON.parse(${json});`;
  }
  let {
    state
  } = dataRouterContext.router;
  return
 /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(react__WEBPACK_IMPORTED_
MODULE_0__.Fragment, null, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(DataRouterContext.Provider, {
    value: dataRouterContext
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(DataRouterStateContext.Provider,
{
    value: state
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(FetchersContext.Provider, {
    value: fetchersContext
  }, /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(ViewTransitionContext.Provider, {
    value: {
      isTransitioning: false
    }
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(Router, {
    basename: dataRouterContext.basename,
```

```
    location: state.location,
    navigationType: state.historyAction,
    navigator: dataRouterContext.navigator,
    static: dataRouterContext.static,
    useTransitions: false
  }, /* @__PURE__ */react__WEBPACK_IMPORTED_MODULE_0__.createElement(DataRoutes2, {
    manifest: router.manifest,
    routes: router.routes,
    future: router.future,
    state,
    isStatic: true
  }))))), hydrateScript ? /* @__PURE__
*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("script", {
    suppressHydrationWarning: true,
    nonce,
    dangerouslySetInnerHTML: {
      __html: hydrateScript
    }
  }) : null);
}
function serializeErrors(errors) {
  if (!errors) return null;
  let entries = Object.entries(errors);
  let serialized = {};
  for (let [key, val] of entries) {
    if (isRouteErrorResponse(val)) {
      serialized[key] = {
        ...val,
        __type: "RouteErrorResponse"
      };
    } else if (val instanceof Error) {
      serialized[key] = {
        message: val.message,
        __type: "Error",
        // If this is a subclass (i.e., ReferenceError), send up the type so we
        // can re-create the same type during hydration.
        ...(val.name !== "Error" ? {
          __subType: val.name
        } : {})
      };
    } else {
      serialized[key] = val;
    }
  }
  return serialized;
}
function getStatelessNavigator() {
  return {
    createHref,
```

```
    encodeLocation,
    push(to) {
      throw new Error(`You cannot use navigator.push() on the server because it is a stateless environment. This error was probably triggered when you did a \`navigate(${JSON.stringify(to)})\` somewhere in your app.`);
    },
    replace(to) {
      throw new Error(`You cannot use navigator.replace() on the server because it is a stateless environment. This error was probably triggered when you did a \`navigate(${JSON.stringify(to)}, { replace: true })\` somewhere in your app.`);
    },
    go(delta) {
      throw new Error(`You cannot use navigator.go() on the server because it is a stateless environment. This error was probably triggered when you did a \`navigate(${delta})\` somewhere in your app.`);
    },
    back() {
      throw new Error(`You cannot use navigator.back() on the server because it is a stateless environment.`);
    },
    forward() {
      throw new Error(`You cannot use navigator.forward() on the server because it is a stateless environment.`);
    }
  };
}
function createStaticHandler2(routes, opts) {
  return createStaticHandler(routes, {
    ...opts,
    mapRouteProperties
  });
}
function createStaticRouter(routes, context, opts = {}) {
  let manifest = {};
  let dataRoutes = convertRoutesToDataRoutes(routes, mapRouteProperties, void 0, manifest);
  let matches = context.matches.map(match => {
    let route = manifest[match.route.id] || match.route;
    return {
      ...match,
      route
    };
  });
  let msg = method => `You cannot use router.${method}() on the server because it is a stateless environment`;
  return {
    get basename() {
      return context.basename;
    },
    get future() {
      return {
```

```
    v8_middleware: false,
    v8_passThroughRequests: false,
    ...opts?.future
  };
},
get state() {
  return {
    historyAction: "POP" /* Pop */,
    location: context.location,
    matches,
    loaderData: context.loaderData,
    actionData: context.actionData,
    errors: context.errors,
    initialized: true,
    renderFallback: false,
    navigation: IDLE_NAVIGATION,
    restoreScrollPosition: null,
    preventScrollReset: false,
    revalidation: "idle",
    fetchers: /* @__PURE__ */new Map(),
    blockers: /* @__PURE__ */new Map()
  };
},
get routes() {
  return dataRoutes;
},
get branches() {
  return opts.branches;
},
get manifest() {
  return manifest;
},
get window() {
  return void 0;
},
initialize() {
  throw msg("initialize");
},
subscribe() {
  throw msg("subscribe");
},
enableScrollRestoration() {
  throw msg("enableScrollRestoration");
},
navigate() {
  throw msg("navigate");
},
fetch() {
  throw msg("fetch");
```

```
    },
    revalidate() {
      throw msg("revalidate");
    },
    createHref,
    encodeLocation,
    getFetcher() {
      return IDLE_FETCHER;
    },
    deleteFetcher() {
      throw msg("deleteFetcher");
    },
    resetFetcher() {
      throw msg("resetFetcher");
    },
    dispose() {
      throw msg("dispose");
    },
    getBlocker() {
      return IDLE_BLOCKER;
    },
    deleteBlocker() {
      throw msg("deleteBlocker");
    },
    patchRoutes() {
      throw msg("patchRoutes");
    },
    _internalFetchControllers: /* @__PURE__ */new Map(),
    _internalSetRoutes() {
      throw msg("_internalSetRoutes");
    },
    _internalSetStateDoNotUseOrYouWillBreakYourApp() {
      throw msg("_internalSetStateDoNotUseOrYouWillBreakYourApp");
    }
  };
}
function createHref(to) {
  return typeof to === "string" ? to : createPath(to);
}
function encodeLocation(to) {
  let href = typeof to === "string" ? to : createPath(to);
  href = href.replace(/ $/, "%20");
  let encoded = ABSOLUTE_URL_REGEX3.test(href) ? new URL(href) : new URL(href,
"http://localhost");
  return {
    pathname: encoded.pathname,
    search: encoded.search,
    hash: encoded.hash
  };
```

```
}
var ABSOLUTE_URL_REGEX3 = /^(?:[a-z][a-z0-9+.-]*:|\/\/)/i;


/***/ },

/***/ "./node_modules/sonner/dist/index.mjs"
/*!*****************************************!*\
  !*** ./node_modules/sonner/dist/index.mjs ***!
  \*****************************************/
(__unused_webpack___webpack_module__, __webpack_exports__, __webpack_require__) {

"use strict";
__webpack_require__.r(__webpack_exports__);
/* harmony export */ __webpack_require__.d(__webpack_exports__, {
/* harmony export */   Toaster: () => (/* binding */ Toaster),
/* harmony export */   toast: () => (/* binding */ toast),
/* harmony export */   useSonner: () => (/* binding */ useSonner)
/* harmony export */ });
/* harmony import */ var react__WEBPACK_IMPORTED_MODULE_0__ =
__webpack_require__(/*! react */ "./node_modules/react/index.js");
/* harmony import */ var react_dom__WEBPACK_IMPORTED_MODULE_1__ =
__webpack_require__(/*! react-dom */ "./node_modules/react-dom/index.js");
'use client';

function __insertCSS(code) {
  if (!code || typeof document == 'undefined') return;
  let head = document.head || document.getElementsByTagName('head')[0];
  let style = document.createElement('style');
  style.type = 'text/css';
  head.appendChild(style);
  style.styleSheet ? style.styleSheet.cssText = code :
style.appendChild(document.createTextNode(code));
}


const getAsset = type => {
  switch (type) {
    case 'success':
      return SuccessIcon;
    case 'info':
      return InfoIcon;
    case 'warning':
      return WarningIcon;
    case 'error':
      return ErrorIcon;
    default:
      return null;
  }
```

```
};
const bars = Array(12).fill(0);
const Loader = ({
  visible,
  className
}) => {
  return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    className: ['sonner-loading-wrapper', className].filter(Boolean).join(' '),
    "data-visible": visible
  }, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    className: "sonner-spinner"
  }, bars.map((_, i) =>
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    className: "sonner-loading-bar",
    key: `spinner-bar-${i}`
  }))));
};
const SuccessIcon =
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("svg", {
  xmlns: "http://www.w3.org/2000/svg",
  viewBox: "0 0 20 20",
  fill: "currentColor",
  height: "20",
  width: "20"
}, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("path", {
  fillRule: "evenodd",
  d: "M10 18a8 8 0 100-16 8 8 0 000 16zm3.857-9.809a.75.75 0 00-1.214-.882l-3.483 4.79-1.88-
1.88a.75.75 0 10-1.06 1.061l2.5 2.5a.75.75 0 001.137-.089l4-5.5z",
  clipRule: "evenodd"
}));
const WarningIcon =
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("svg", {
  xmlns: "http://www.w3.org/2000/svg",
  viewBox: "0 0 24 24",
  fill: "currentColor",
  height: "20",
  width: "20"
}, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("path", {
  fillRule: "evenodd",
  d: "M9.401 3.003c1.155-2 4.043-2 5.197 0l7.355 12.748c1.154 2-.29 4.5-2.599 4.5H4.645c-2.309 0-
3.752-2.5-2.598-4.5L9.4 3.003zM12 8.25a.75.75 0 01.75.75v3.75a.75.75 0 01-1.5 0V9a.75.75 0
01.75-.75zm0 8.25a.75.75 0 100-1.5.75.75 0 000 1.5z",
  clipRule: "evenodd"
}));
const InfoIcon =
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("svg", {
  xmlns: "http://www.w3.org/2000/svg",
  viewBox: "0 0 20 20",
  fill: "currentColor",
```

```
  height: "20",
  width: "20"
}, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("path", {
  fillRule: "evenodd",
  d: "M18 10a8 8 0 11-16 0 8 8 0 0116 0zm-7-4a1 1 0 11-2 0 1 1 0 012 0zM9 9a.75.75 0 000
1.5h.253a.25.25 0 01.244.304l-.459 2.066A1.75 1.75 0 0010.747 15H11a.75.75 0 000-1.5h-.253a.25.25
0 01-.244-.304l.459-2.066A1.75 1.75 0 009.253
 9H9z",
  clipRule: "evenodd"
}));
const ErrorIcon =
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("svg", {
  xmlns: "http://www.w3.org/2000/svg",
  viewBox: "0 0 20 20",
  fill: "currentColor",
  height: "20",
  width: "20"
}, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("path", {
  fillRule: "evenodd",
  d: "M18 10a8 8 0 11-16 0 8 8 0 0116 0zm-8-5a.75.75 0 01.75.75v4.5a.75.75 0 01-1.5 0v-4.5A.75.75 0
0110 5zm0 10a1 1 0 100-2 1 1 0 000 2z",
  clipRule: "evenodd"
}));
const CloseIcon =
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("svg", {
  xmlns: "http://www.w3.org/2000/svg",
  width: "12",
  height: "12",
  viewBox: "0 0 24 24",
  fill: "none",
  stroke: "currentColor",
  strokeWidth: "1.5",
  strokeLinecap: "round",
  strokeLinejoin: "round"
}, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("line", {
  x1: "18",
  y1: "6",
  x2: "6",
  y2: "18"
}), /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("line", {
  x1: "6",
  y1: "6",
  x2: "18",
  y2: "18"
}));
const useIsDocumentHidden = () => {
  const [isDocumentHidden, setIsDocumentHidden] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(document.hidden);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
```

```
    const callback = () => {
      setIsDocumentHidden(document.hidden);
    };
    document.addEventListener('visibilitychange', callback);
    return () => window.removeEventListener('visibilitychange', callback);
  }, []);
  return isDocumentHidden;
};
let toastsCounter = 1;
class Observer {
  constructor() {
    // We use arrow functions to maintain the correct `this` reference
    this.subscribe = subscriber => {
      this.subscribers.push(subscriber);
      return () => {
        const index = this.subscribers.indexOf(subscriber);
        this.subscribers.splice(index, 1);
      };
    };
    this.publish = data => {
      this.subscribers.forEach(subscriber => subscriber(data));
    };
    this.addToast = data => {
      this.publish(data);
      this.toasts = [...this.toasts, data];
    };
    this.create = data => {
      var _data_id;
      const {
        message,
        ...rest
      } = data;
      const id = typeof (data == null ? void 0 : data.id) === 'number' || ((_data_id = data.id) == null ?
void 0 : _data_id.length) > 0 ? data.id : toastsCounter++;
      const alreadyExists = this.toasts.find(toast => {
        return toast.id === id;
      });
      const dismissible = data.dismissible === undefined ? true : data.dismissible;
      if (this.dismissedToasts.has(id)) {
        this.dismissedToasts.delete(id);
      }
      if (alreadyExists) {
        this.toasts = this.toasts.map(toast => {
          if (toast.id === id) {
            this.publish({
              ...toast,
              ...data,
              id,
              title: message
```

```
        });
        return {
          ...toast,
          ...data,
          id,
          dismissible,
          title: message
        };
      }
      return toast;
    });
  } else {
    this.addToast({
      title: message,
      ...rest,
      dismissible,
      id
    });
  }
  return id;
};
this.dismiss = id => {
  if (id) {
    this.dismissedToasts.add(id);
    requestAnimationFrame(() => this.subscribers.forEach(subscriber => subscriber({
      id,
      dismiss: true
    })));
  } else {
    this.toasts.forEach(toast => {
      this.subscribers.forEach(subscriber => subscriber({
        id: toast.id,
        dismiss: true
      }));
    });
  }
  return id;
};
this.message = (message, data) => {
  return this.create({
    ...data,
    message
  });
};
this.error = (message, data) => {
  return this.create({
    ...data,
    message,
    type: 'error'
```

```
  });
};
this.success = (message, data) => {
  return this.create({
    ...data,
    type: 'success',
    message
  });
};
this.info = (message, data) => {
  return this.create({
    ...data,
    type: 'info',
    message
  });
};
this.warning = (message, data) => {
  return this.create({
    ...data,
    type: 'warning',
    message
  });
};
this.loading = (message, data) => {
  return this.create({
    ...data,
    type: 'loading',
    message
  });
};
this.promise = (promise, data) => {
  if (!data) {
    // Nothing to show
    return;
  }
  let id = undefined;
  if (data.loading !== undefined) {
    id = this.create({
      ...data,
      promise,
      type: 'loading',
      message: data.loading,
      description: typeof data.description !== 'function' ? data.description : undefined
    });
  }
  const p = Promise.resolve(promise instanceof Function ? promise() : promise);
  let shouldDismiss = id !== undefined;
  let result;
  const originalPromise = p.then(async response => {
```

```
      result = ['resolve', response];
      const isReactElementResponse =
react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(response);
      if (isReactElementResponse) {
        shouldDismiss = false;
        this.create({
          id,
          type: 'default',
          message: response
        });
      } else if (isHttpResponse(response) && !response.ok) {
        shouldDismiss = false;
        const promiseData = typeof data.error === 'function' ? await data.error(`HTTP error! status: $
{response.status}`) : data.error;
        const description = typeof data.description === 'function' ? await data.description(`HTTP error!
status: ${response.status}`) : data.description;
        const isExtendedResult = typeof promiseData === 'object' && !
react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(promiseData);
        const toastSettings = isExtendedResult ? promiseData : {
          message: promiseData
        };
        this.create({
          id,
          type: 'error',
          description,
          ...toastSettings
        });
      } else if (response instanceof Error) {
        shouldDismiss = false;
        const promiseData = typeof data.error === 'function' ? await data.error(response) : data.error;
        const description = typeof data.description === 'function' ? await data.description(response) :
data.description;
        const isExtendedResult = typeof promiseData === 'object' && !
react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(promiseData);
        const toastSettings = isExtendedResult ? promiseData : {
          message: promiseData
        };
        this.create({
          id,
          type: 'error',
          description,
          ...toastSettings
        });
      } else if (data.success !== undefined) {
        shouldDismiss = false;
        const promiseData = typeof data.success === 'function' ? await data.success(response) :
data.success;
        const description = typeof data.description === 'function' ? await data.description(response) :
data.description;
```

```
        const isExtendedResult = typeof promiseData === 'object' && !
react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(promiseData);
        const toastSettings = isExtendedResult ? promiseData : {
          message: promiseData
        };
        this.create({
          id,
          type: 'success',
          description,
          ...toastSettings
        });
      }
    }).catch(async error => {
      result = ['reject', error];
      if (data.error !== undefined) {
        shouldDismiss = false;
        const promiseData = typeof data.error === 'function' ? await data.error(error) : data.error;
        const description = typeof data.description === 'function' ? await data.description(error) :
data.description;
        const isExtendedResult = typeof promiseData === 'object' && !
react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(promiseData);
        const toastSettings = isExtendedResult ? promiseData : {
          message: promiseData
        };
        this.create({
          id,
          type: 'error',
          description,
          ...toastSettings
        });
      }
    }).finally(() => {
      if (shouldDismiss) {
        // Toast is still in load state (and will be indefinitely — dismiss it)
        this.dismiss(id);
        id = undefined;
      }
      data.finally == null ? void 0 : data.finally.call(data);
    });
    const unwrap = () => new Promise((resolve, reject) => originalPromise.then(() => result[0] ===
'reject' ? reject(result[1]) : resolve(result[1])).catch(reject));
    if (typeof id !== 'string' && typeof id !== 'number') {
      // cannot Object.assign on undefined
      return {
        unwrap
      };
    } else {
      return Object.assign(id, {
        unwrap
```

```
      });
    }
  };
  this.custom = (jsx, data) => {
    const id = (data == null ? void 0 : data.id) || toastsCounter++;
    this.create({
      jsx: jsx(id),
      id,
      ...data
    });
    return id;
  };
  this.getActiveToasts = () => {
    return this.toasts.filter(toast => !this.dismissedToasts.has(toast.id));
  };
  this.subscribers = [];
  this.toasts = [];
  this.dismissedToasts = new Set();
 }
}
const ToastState = new Observer();
// bind this to the toast function
const toastFunction = (message, data) => {
 const id = (data == null ? void 0 : data.id) || toastsCounter++;
 ToastState.addToast({
  title: message,
  ...data,
  id
 });
 return id;
};
const isHttpResponse = data => {
 return data && typeof data === 'object' && 'ok' in data && typeof data.ok === 'boolean' && 'status'
in data && typeof
 data.status === 'number';
};
const basicToast = toastFunction;
const getHistory = () => ToastState.toasts;
const getToasts = () => ToastState.getActiveToasts();
// We use `Object.assign` to maintain the correct types as we would lose them otherwise
const toast = Object.assign(basicToast, {
 success: ToastState.success,
 info: ToastState.info,
 warning: ToastState.warning,
 error: ToastState.error,
 custom: ToastState.custom,
 message: ToastState.message,
 promise: ToastState.promise,
 dismiss: ToastState.dismiss,
```

```
  loading: ToastState.loading
}, {
  getHistory,
  getToasts
});
__insertCSS("[data-sonner-toaster][dir=ltr],html[dir=ltr]{--toast-icon-margin-start:-3px;--toast-icon-margin-end:4px;--toast-svg-margin-start:-1px;--toast-svg-margin-end:0px;--toast-button-margin-start:auto;--toast-button-margin-end:0;--toast-close-button-start:0;--toast-close-button-end:unset;--toast-close-button-transform:translate(-35%, -35%)}[data-sonner-toaster][dir=rtl],html[dir=rtl]{--toast-icon-margin-start:4px;--toast-icon-margin-end:-3px;--toast-svg-margin-start:0px;--toast-svg-margin-end:-1px;--toast-button-margin-start:0;--toast-button-margin-end:auto;--toast-close-button-start:unset;--toast-close-button-end:0;--toast-close-button-transform:translate(35%, -35%)}[data-sonner-toaster]{position:fixed;width:var(--width);font-family:ui-sans-serif,system-ui,-apple-system,BlinkMacSystemFont,Segoe UI,Roboto,Helvetica Neue,Arial,Noto Sans,sans-serif,Apple Color Emoji,Segoe UI Emoji,Segoe UI Symbol,Noto Color Emoji;--gray1:hsl(0, 0%, 99%);--gray2:hsl(0, 0%, 97.3%);--gray3:hsl(0, 0%, 95.1%);--gray4:hsl(0, 0%, 93%);--gray5:hsl(0, 0%, 90.9%);--gray6:hsl(0, 0%, 88.7%);--gray7:hsl(0, 0%, 85.8%);--gray8:hsl(0, 0%, 78%);--gray9:hsl(0, 0%, 56.1%);--gray10:hsl(0, 0%, 52.3%);--gray11:hsl(0, 0%, 43.5%);--gray12:hsl(0, 0%, 9%);--border-radius:8px;box-sizing:border-box;padding:0;margin:0;list-style:none;outline:0;z-index:999999999;transition:transform .4s ease}[data-sonner-toaster][data-lifted=true]{transform:translateY(-8px)}@media (hover:none) and (pointer:coarse){[data-sonner-toaster][data-lifted=true]{transform:none}}[data-sonner-toaster][data-x-position=right]{right:var(--offset-right)}[data-sonner-toaster][data-x-position=left]{left:var(--offset-left)}[data-sonner-toaster][data-x-position=center]{left:50%;transform:translateX(-50%)}[data-sonner-toaster][data-y-position=top]{top:var(--offset-top)}[data-sonner-toaster][data-y-position=bottom]{bottom:var(--offset-bottom)}[data-sonner-toast]{--y:translateY(100%);--lift-amount:calc(var(--lift) * var(--gap));z-index:var(--z-index);position:absolute;opacity:0;transform:var(--y);touch-action:none;transition:transform .4s,opacity .4s,height .4s,box-shadow .2s;box-sizing:border-box;outline:0;overflow-wrap:anywhere}[data-sonner-toast][data-styled=true]{padding:16px;background:var(--normal-bg);border:1px solid var(--normal-border);color:var(--normal-text);border-radius:var(--border-radius);box-shadow:0 4px 12px rgba(0,0,0,.1);width:var(--width);font-size:13px;display:flex;align-items:center;gap:6px}[data-sonner-toast]:focus-visible{box-shadow:0 4px 12px rgba(0,0,0,.1),0 0 0 2px rgba(0,0,0,.2)}[data-sonner-toast][data-y-position=top]{top:0;--y:translateY(-100%);--lift:1;--lift-amount:calc(1 * var(--gap))}[data-sonner-toast][data-y-position=bottom]{bottom:0;--y:translateY(100%);--lift:-1;--lift-amount:calc(var(--lift) * var(--gap))}[data-sonner-toast][data-styled=true] [data-description]{font-weight:400;line-height:1.4;color:#3f3f3f}[data-rich-colors=true][data-sonner-toast][data-styled=true] [data-description]{color:inherit}[data-sonner-toaster][data-sonner-theme=dark] [data-description]{color:#e8e8e8}[data-sonner-toast][data-styled=true] [data-title]{font-weight:500;line-height:1.5;color:inherit}[data-sonner-toast][data-styled=true] [data-icon]{display:flex;height:16px;width:16px;position:relative;justify-content:flex-start;align-items:center;flex-shrink:0;margin-left:var(--toast-icon-margin-start);margin-right:var(--toast-icon-margin-end)}[data-sonner-toast][data-promise=true] [data-icon]>svg{opacity:0;transform:scale(.8);transform-origin:center;animation:sonner-fade-in .3s ease forwards}[data-sonner-toast][data-styled=true] [data-icon]>*{flex-shrink:0}[data-sonner-toast][data-styled=true] [data-icon] svg{margin-left:var(--toast-svg-margin-start);margin-right:var(--toast-svg-margin-end)}[data-sonner-toast][data-styled=true] [data-content]{display:flex;flex-direction:column;gap:2px}[data-sonner-toast][data-styled=true] [data-button]{border-radius:4px;padding-left:8px;padding-right:8px;height:24px;font-size:12px;color:var(--normal-bg);background:var(--normal-text);margin-left:var(--toast-button-margin-start);margin-right:var(--toast-button-margin-end);border:none;font-weight:500;cursor:pointer;outline:0;display:flex;align-
```

items:center;flex-shrink:0;transition:opacity .4s,box-shadow .2s}[data-sonner-toast][data-styled=true] [data-button]:focus-visible{box-shadow:0 0 0 2px rgba(0,0,0,.4)}[data-sonner-toast][data-styled=true] [data-button]:first-of-type{margin-left:var(--toast-button-margin-start);margin-right:var(--toast-button-margin-end)}[data-sonner-toast][data-styled=true] [data-cancel]{color:var(--normal-text);background:rgba(0,0,0,.08)}[data-sonner-toaster][data-sonner-theme=dark] [data-sonner-toast][data-styled=true] [data-cancel]{background:rgba(255,255,255,.3)}[data-sonner-toast][data-styled=true] [data-close-button]{position:absolute;left:var(--toast-close-button-start);right:var(--toast-close-button-end);top:0;height:20px;width:20px;display:flex;justify-content:center;align-items:center;padding:0;color:var(--gray12);background:var(--normal-bg);border:1px solid var(--gray4);transform:var(--toast-close-button-transform);border-radius:50%;cursor:pointer;z-index:1;transition:opacity .1s,background .2s,border-color .2s}[data-sonner-toast][data-styled=true] [data-close-button]:focus-visible{box-shadow:0 4px 12px rgba(0,0,0,.1),0 0 0 2px rgba(0,0,0,.2)}[data-sonner-toast][data-styled=true] [data-disabled=true]{cursor:not-allowed}[data-sonner-toast][data-styled=true]:hover [data-close-button]:hover{background:var(--gray2);border-color:var(--gray5)}[data-sonner-toast][data-swiping=true]::before{content:'';position:absolute;left:-100%;right:-100%;height:100%;z-index:-1}[data-sonner-toast][data-y-position=top][data-swiping=true]::before{bottom:50%;transform:scaleY(3) translateY(50%)}[data-sonner-toast][data-y-position=bottom][data-swiping=true]::before{top:50%;transform:scaleY(3) translateY(-50%)}[data-sonner-toast][data-swiping=false][data-removed=true]::before{content:'';position:absolute;inset:0;transform:scaleY(2)}[data-sonner-toast][data-expanded=true]::after{content:'';position:absolute;left:0;height:calc(var(--gap) + 1px);bottom:100%;width:100%}[data-sonner-toast][data-mounted=true]{--y:translateY(0);opacity:1}[data-sonner-toast][data-expanded=false][data-front=false]{--scale:var(--toasts-before) * 0.05 + 1;--y:translateY(calc(var(--lift-amount) * var(--toasts-before))) scale(calc(-1 * var(--scale)));height:var(--front-toast-height)}[data-sonner-toast]>*{transition:opacity .4s}[data-sonner-toast][data-x-position=right]{right:0}[data-sonner-toast][data-x-position=left]{left:0}[data-sonner-toast][data-expanded=false][data-front=false][data-styled=true]>*{opacity:0}[data-sonner-toast][data-visible=false]{opacity:0;pointer-events:none}[data-sonner-toast][data-mounted=true][data-expanded=true]{--y:translateY(calc(var(--lift) * var(--offset)));height:var(--initial-height)}[data-sonner-toast][data-removed=true][data-front=true][data-swipe-out=false]{--y:translateY(calc(var(--lift) * -100%));opacity:0}[data-sonner-toast][data-removed=true][data-front=false][data-swipe-out=false][data-expanded=true]{--y:translateY(calc(var(--lift) * var(--offset) + var(--lift) * -100%));opacity:0}[data-sonner-toast][data-removed=true][data-front=false][data-swipe-out=false][data-expanded=false]{--y:translateY(40%);opacity:0;transition:transform .5s,opacity .2s}[data-sonner-toast][data-removed=true][data-front=false]::before{height:calc(var(--initial-height) + 20%)}[data-sonner-toast][data-swiping=true]{transform:var(--y) translateY(var(--swipe-amount-y,0)) translateX(var(--swipe-amount-x,0));transition:none}[data-sonner-toast][data-swiped=true]{user-select:none}[data-sonner-toast][data-swipe-out=true][data-y-position=bottom],[data-sonner-toast][data-swipe-out=true][data-y-position=top]{animation-duration:.2s;animation-timing-function:ease-out;animation-fill-mode:forwards}[data-sonner-toast][data-swipe-out=true][data-swipe-direction=left]{animation-name:swipe-out-left}[data-sonner-toast][data-swipe-out=true][data-swipe-direction=right]{animation-name:swipe-out-right}[data-sonner-toast][data-swipe-out=true][data-swipe-direction=up]{animation-name:swipe-out-up}[data-sonner-toast][data-swipe-out=true][data-swipe-direction=down]{animation-name:swipe-out-down}@keyframes swipe-out-left{from{transform:var(--y) translateX(var(--swipe-amount-x));opacity:1}to{transform:var(--y) translateX(calc(var(--swipe-amount-x) - 100%));opacity:0}}@keyframes swipe-out-right{from{transform:var(--y) translateX(var(--swipe-amount-x));opacity:1}to{transform:var(--y) translateX(calc(var(--swipe-amount-x) + 100%));opacity:0}}@keyframes swipe-out-up{from{transform:var(--y) translateY(var(--swipe-amount-y));opacity:1}to{transform:var(--y) translateY(calc(var(--swipe-amount-y) -

100%));opacity:0}}@keyframes swipe-out-down{from{transform:var(--y) translateY(var(--swipe-amount-y));opacity:1}to{transform:var(--y) translateY(calc(var(--swipe-amount-y) + 100%));opacity:0}}@media (max-width:600px){[data-sonner-toaster]{position:fixed;right:var(--mobile-offset-right);left:var(--mobile-offset-left);width:100%}[data-sonner-toaster][dir=rtl]{left:calc(var(--mobile-offset-left) * -1)}[data-sonner-toaster] [data-sonner-toast]{left:0;right:0;width:calc(100% - var(--mobile-offset-left) * 2)}[data-sonner-toaster][data-x-position=left]{left:var(--mobile-offset-left)}[data-sonner-toaster][data-y-position=bottom]{bottom:var(--mobile-offset-bottom)}[data-sonner-toaster][data-y-position=top]{top:var(--mobile-offset-top)}[data-sonner-toaster][data-x-position=center]{left:var(--mobile-offset-left);right:var(--mobile-offset-right);transform:none}}[data-sonner-toaster][data-sonner-theme=light]{--normal-bg:#fff;--normal-border:var(--gray4);--normal-text:var(--gray12);--success-bg:hsl(143, 85%, 96%);--success-border:hsl(145, 92%, 87%);--success-text:hsl(140, 100%, 27%);--info-bg:hsl(208, 100%, 97%);--info-border:hsl(221, 91%, 93%);--info-text:hsl(210, 92%, 45%);--warning-bg:hsl(49, 100%, 97%);--warning-border:hsl(49, 91%, 84%);--warning-text:hsl(31, 92%, 45%);--error-bg:hsl(359, 100%, 97%);--error-border:hsl(359, 100%, 94%);--error-text:hsl(360, 100%, 45%)}[data-sonner-toaster][data-sonner-theme=light] [data-sonner-toast][data-invert=true]{--normal-bg:#000;--normal-border:hsl(0, 0%, 20%);--normal-text:var(--gray1)}[data-sonner-toaster][data-sonner-theme=dark] [data-sonner-toast][data-invert=true]{--normal-bg:#fff;--normal-border:var(--gray3);--normal-text:var(--gray12)}[data-sonner-toaster][data-sonner-theme=dark]{--normal-bg:#000;--normal-bg-hover:hsl(0, 0%, 12%);--normal-border:hsl(0, 0%, 20%);--normal-border-hover:hsl(0, 0%, 25%);--normal-text:var(--gray1);--success-bg:hsl(150, 100%, 6%);--success-border:hsl(147, 100%, 12%);--success-text:hsl(150, 86%, 65%);--info-bg:hsl(215, 100%, 6%);--info-border:hsl(223, 43%, 17%);--info-text:hsl(216, 87%, 65%);--warning-bg:hsl(64, 100%, 6%);--warning-border:hsl(60, 100%, 9%);--warning-text:hsl(46, 87%, 65%);--error-bg:hsl(358, 76%, 10%);--error-border:hsl(357, 89%, 16%);--error-text:hsl(358, 100%, 81%)}[data-sonner-toaster][data-sonner-theme=dark] [data-sonner-toast] [data-close-button]{background:var(--normal-bg);border-color:var(--normal-border);color:var(--normal-text)}[data-sonner-toaster][data-sonner-theme=dark] [data-sonner-toast] [data-close-button]:hover{background:var(--normal-bg-hover);border-color:var(--normal-border-hover)}[data-rich-colors=true][data-sonner-toast][data-type=success]{background:var(--success-bg);border-color:var(--success-border);color:var(--success-text)}[data-rich-colors=true][data-sonner-toast][data-type=success] [data-close-button]{background:var(--success-bg);border-color:var(--success-border);color:var(--success-text)}[data-rich-colors=true][data-sonner-toast][data-type=info]{background:var(--info-bg);border-color:var(--info-border);color:var(--info-text)}[data-rich-colors=true][data-sonner-toast][data-type=info] [data-close-button]{background:var(--info-bg);border-color:var(--info-border);color:var(--info-text)}[data-rich-colors=true][data-sonner-toast][data-type=warning]{background:var(--warning-bg);border-color:var(--warning-border);color:var(--warning-text)}[data-rich-colors=true][data-sonner-toast][data-type=warning] [data-close-button]{background:var(--warning-bg);border-color:var(--warning-border);color:var(--warning-text)}[data-rich-colors=true][data-sonner-toast][data-type=error]{background:var(--error-bg);border-color:var(--error-border);color:var(--error-text)}[data-rich-colors=true][data-sonner-toast][data-type=error] [data-close-button]{background:var(--error-bg);border-color:var(--error-border);color:var(--error-text)}.sonner-loading-wrapper{--size:16px;height:var(--size);width:var(--size);position:absolute;inset:0;z-index:10}.sonner-loading-wrapper[data-visible=false]{transform-origin:center;animation:sonner-fade-out .2s ease forwards}.sonner-spinner{position:relative;top:50%;left:50%;height:var(--size);width:var(--size)}.sonner-loading-bar{animation:sonner-spin 1.2s linear infinite;background:var(--gray11);border-radius:6px;height:8%;left:-10%;position:absolute;top:-3.9%;width:24%}.sonner-loading-bar:first-child{animation-delay:-1.2s;transform:rotate(.0001deg) translate(146%)}.sonner-loading-bar:nth-child(2){animation-delay:-1.1s;transform:rotate(30deg) translate(146%)}.sonner-loading-bar:nth-

```
child(3){animation-delay:-1s;transform:rotate(60deg) translate(146%)}.sonner-loading-bar:nth-child(4)
{animation-delay:-.9s;transform:rotate(90deg) translate(146%)}.sonner-loading-bar:nth-child(5)
{animation-delay:-.8s;transform:rotate(120deg) translate(146%)}.sonner-loading-bar:nth-child(6)
{animation-delay:-.7s;transform:rotate(150deg) translate(146%)}.sonner-loading-bar:nth-child(7)
{animation-delay:-.6s;transform:rotate(180deg) translate(146%)}.sonner-loading-bar:nth-child(8)
{animation-delay:-.5s;transform:rotate(210deg) translate(146%)}.sonner-loading-bar:nth-child(9)
{animation-delay:-.4s;transform:rotate(240deg) translate(146%)}.sonner-loading-bar:nth-child(10)
{animation-delay:-.3s;transform:rotate(270deg) translate(146%)}.sonner-loading-bar:nth-child(11)
{animation-delay:-.2s;transform:rotate(300deg) translate(146%)}.sonner-loading-bar:nth-child(12)
{animation-delay:-.1s;transform:rotate(330deg) translate(146%)}@keyframes sonner-fade-in{0%
{opacity:0;transform:scale(.8)}100%{opacity:1;transform:scale(1)}}@keyframes sonner-fade-out{0%
{opacity:1;transform:scale(1)}100%{opacity:0;transform:scale(.8)}}@keyframes sonner-spin{0%
{opacity:1}100%{opacity:.15}}@media (prefers-reduced-motion){.sonner-loading-bar,[data-sonner-
toast],[data-sonner-toast]>*{transition:none!important;animation:none!important}}.sonner-
loader{position:absolute;top:50%;left:50%;transform:translate(-50%,-50%);transform-
origin:center;transition:opacity .2s,transform .2s}.sonner-loader[data-visible=false]
{opacity:0;transform:scale(.8) translate(-50%,-50%)}");
function isAction(action) {
  return action.label !== undefined;
}

// Visible toasts amount
const VISIBLE_TOASTS_AMOUNT = 3;
// Viewport padding
const VIEWPORT_OFFSET = '24px';
// Mobile viewport padding
const MOBILE_VIEWPORT_OFFSET = '16px';
// Default lifetime of a toasts (in ms)
const TOAST_LIFETIME = 4000;
// Default toast width
const TOAST_WIDTH = 356;
// Default gap between toasts
const GAP = 14;
// Threshold to dismiss a toast
const SWIPE_THRESHOLD = 45;
// Equal to exit animation duration
const TIME_BEFORE_UNMOUNT = 200;
function cn(...classes) {
  return classes.filter(Boolean).join(' ');
}
function getDefaultSwipeDirections(position) {
  const [y, x] = position.split('-');
  const directions = [];
  if (y) {
    directions.push(y);
  }
  if (x) {
    directions.push(x);
  }
```

```
  return directions;
}
const Toast = props => {
  var _toast_classNames, _toast_classNames1, _toast_classNames2, _toast_classNames3,
_toast_classNames4, _toast_classNames5, _toast_classNames6, _toast_classNames7,
_toast_classNames8;
  const {
    invert: ToasterInvert,
    toast,
    unstyled,
    interacting,
    setHeights,
    visibleToasts,
    heights,
    index,
    toasts,
    expanded,
    removeToast,
    defaultRichColors,
    closeButton: closeButtonFromToaster,
    style,
    cancelButtonStyle,
    actionButtonStyle,
    className = '',
    descriptionClassName = '',
    duration: durationFromToaster,
    position,
    gap,
    expandByDefault,
    classNames,
    icons,
    closeButtonAriaLabel = 'Close toast'
  } = props;
  const [swipeDirection, setSwipeDirection] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(null);
  const [swipeOutDirection, setSwipeOutDirection] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(null);
  const [mounted, setMounted] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [removed, setRemoved] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [swiping, setSwiping] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [swipeOut, setSwipeOut] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [isSwiped, setIsSwiped] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [offsetBeforeRemove, setOffsetBeforeRemove] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(0);
  const [initialHeight, setInitialHeight] = react__WEBPACK_IMPORTED_MODULE_0__.useState(0);
  const remainingTime = react__WEBPACK_IMPORTED_MODULE_0__.useRef(toast.duration ||
durationFromToaster || TOAST_LIFETIME);
  const dragStartTime = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
  const toastRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
```

```
  const isFront = index === 0;
  const isVisible = index + 1 <= visibleToasts;
  const toastType = toast.type;
  const dismissible = toast.dismissible !== false;
  const toastClassname = toast.className || '';
  const toastDescriptionClassname = toast.descriptionClassName || '';
  // Height index is used to calculate the offset as it gets updated before the toast array, which means we
can calculate the new layout faster.
  const heightIndex = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() =>
heights.findIndex(height => height.toastId === toast.id) || 0, [heights, toast.id]);
  const closeButton = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    var _toast_closeButton;
    return (_toast_closeButton = toast.closeButton) != null ? _toast_closeButton :
closeButtonFromToaster;
  }, [toast.closeButton, closeButtonFromToaster]);
  const duration = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => toast.duration ||
durationFromToaster || TOAST_LIFETIME, [toast.duration, durationFromToaster]);
  const closeTimerStartTimeRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(0);
  const offset = react__WEBPACK_IMPORTED_MODULE_0__.useRef(0);
  const lastCloseTimerStartTimeRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(0);
  const pointerStartRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
  const [y, x] = position.split('-');
  const toastsHeightBefore = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    return heights.reduce((prev, curr, reducerIndex) => {
      // Calculate offset up until current toast
      if (reducerIndex >= heightIndex) {
        return prev;
      }
      return prev + curr.height;
    }, 0);
  }, [heights, heightIndex]);

  const isDocumentHidden = useIsDocumentHidden();
  const invert = toast.invert || ToasterInvert;
  const disabled = toastType === 'loading';
  offset.current = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => heightIndex * gap
+ toastsHeightBefore, [heightIndex, toastsHeightBefore]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    remainingTime.current = duration;
  }, [duration]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    // Trigger enter animation without using CSS animation
    setMounted(true);
  }, []);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    const toastNode = toastRef.current;
    if (toastNode) {
      const height = toastNode.getBoundingClientRect().height;
      // Add toast height to heights array after the toast is mounted
```

```
      setInitialHeight(height);
      setHeights(h => [{
        toastId: toast.id,
        height,
        position: toast.position
      }, ...h]);
      return () => setHeights(h => h.filter(height => height.toastId !== toast.id));
    }
  }, [setHeights, toast.id]);
  react__WEBPACK_IMPORTED_MODULE_0__.useLayoutEffect(() => {
    if (!mounted) return;
    const toastNode = toastRef.current;
    const originalHeight = toastNode.style.height;
    toastNode.style.height = 'auto';
    const newHeight = toastNode.getBoundingClientRect().height;
    toastNode.style.height = originalHeight;
    setInitialHeight(newHeight);
    setHeights(heights => {
      const alreadyExists = heights.find(height => height.toastId === toast.id);
      if (!alreadyExists) {
        return [{
          toastId: toast.id,
          height: newHeight,
          position: toast.position
        }, ...heights];
      } else {
        return heights.map(height => height.toastId === toast.id ? {
          ...height,
          height: newHeight
        } : height);
      }
    });
  }, [mounted, toast.title, toast.description, setHeights, toast.id]);
  const deleteToast = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(() => {
    // Save the offset for the exit swipe animation
    setRemoved(true);
    setOffsetBeforeRemove(offset.current);
    setHeights(h => h.filter(height => height.toastId !== toast.id));
    setTimeout(() => {
      removeToast(toast);
    }, TIME_BEFORE_UNMOUNT);
  }, [toast, removeToast, setHeights, offset]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (toast.promise && toastType === 'loading' || toast.duration === Infinity || toast.type === 'loading')
return;
    let timeoutId;
    // Pause the timer on each hover
    const pauseTimer = () => {
      if (lastCloseTimerStartTimeRef.current < closeTimerStartTimeRef.current) {
```

```
        // Get the elapsed time since the timer started
        const elapsedTime = new Date().getTime() - closeTimerStartTimeRef.current;
        remainingTime.current = remainingTime.current - elapsedTime;
      }
      lastCloseTimerStartTimeRef.current = new Date().getTime();
    };
    const startTimer = () => {
      // setTimeout(, Infinity) behaves as if the delay is 0.
      // As a result, the toast would be closed immediately, giving the appearance that it was never
rendered.
      // See: https://github.com/denysdovhan/wtfjs?tab=readme-ov-file#an-infinite-timeout
      if (remainingTime.current === Infinity) return;
      closeTimerStartTimeRef.current = new Date().getTime();
      // Let the toast know it has started
      timeoutId = setTimeout(() => {
        toast.onAutoClose == null ? void 0 : toast.onAutoClose.call(toast, toast);
        deleteToast();
      }, remainingTime.current);
    };
    if (expanded || interacting || isDocumentHidden) {
      pauseTimer();
    } else {
      startTimer();
    }
    return () => clearTimeout(timeoutId);
  }, [expanded, interacting, toast, toastType, isDocumentHidden, deleteToast]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    if (toast.delete) {
      deleteToast();
    }
  }, [deleteToast, toast.delete]);
  function getLoadingIcon() {
    var _toast_classNames;
    if (icons == null ? void 0 : icons.loading) {
      var _toast_classNames1;
      return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
        className: cn(classNames == null ? void 0 : classNames.loader, toast == null ? void 0 :
(_toast_classNames1 = toast.classNames) == null ? void 0 : _toast_classNames1.loader, 'sonner-
loader'),
        "data-visible": toastType === 'loading'
      }, icons.loading);
    }
    return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(Loader, {
      className: cn(classNames == null ? void 0 : classNames.loader, toast == null ? void 0 :
(_toast_classNames = toast.classNames) == null ? void 0 : _toast_classNames.loader),
      visible: toastType === 'loading'
    });
  }
  const icon = toast.icon || (icons == null ? void 0 : icons[toastType]) || getAsset(toastType);
```

```
  var _toast_richColors, _icons_close;
  return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("li", {
    tabIndex: 0,
    ref: toastRef,
    className: cn(className, toastClassname, classNames == null ? void 0 : classNames.toast, toast ==
null ? void 0 : (_toast_classNames = toast.classNames) == null ? void 0 : _toast_classNames.toast,
classNames == null ? void 0 : classNames.default, classNames == null ? void 0 :
classNames[toastType], toast == null ? void 0 : (_toast_classNames1 = toast.classNames) == null ?
void 0 : _toast_classNames1[toastType]),
    "data-sonner-toast": "",
    "data-rich-colors": (_toast_richColors = toast.richColors) != null ? _toast_richColors :
defaultRichColors,
    "data-styled": !Boolean(toast.jsx || toast.unstyled || unstyled),
    "data-mounted": mounted,
    "data-promise": Boolean(toast.promise),
    "data-swiped": isSwiped,
    "data-removed": removed,
    "data-visible": isVisible,
    "data-y-position": y,
    "data-x-position": x,
    "data-index": index,
    "data-front": isFront,
    "data-swiping": swiping,
    "data-dismissible": dismissible,
    "data-type": toastType,
    "data-invert": invert,
    "data-swipe-out": swipeOut,
    "data-swipe-direction": swipeOutDirection,
    "data-expanded": Boolean(expanded || expandByDefault && mounted),
    style: {
      '--index': index,
      '--toasts-before': index,
      '--z-index': toasts.length - index,
      '--offset': `${removed ? offsetBeforeRemove : offset.current}px`,
      '--initial-height': expandByDefault ? 'auto' : `${initialHeight}px`,
      ...style,
      ...toast.style
    },
    onDragEnd: () => {
      setSwiping(false);
      setSwipeDirection(null);
      pointerStartRef.current = null;
    },
    onPointerDown: event => {
      if (disabled || !dismissible) return;
      dragStartTime.current = new Date();
      setOffsetBeforeRemove(offset.current);
      // Ensure we maintain correct pointer capture even when going outside of the toast (e.g. when
swiping)
```

```
      event.target.setPointerCapture(event.pointerId);
      if (event.target.tagName === 'BUTTON') return;
      setSwiping(true);
      pointerStartRef.current = {
        x: event.clientX,
        y: event.clientY
      };
    },
    onPointerUp: () => {
      var _toastRef_current, _toastRef_current1, _dragStartTime_current;
      if (swipeOut || !dismissible) return;
      pointerStartRef.current = null;
      const swipeAmountX = Number(((_toastRef_current = toastRef.current) == null ? void 0 :
_toastRef_current.style.getPropertyValue('--swipe-amount-x').replace('px', '')) || 0);
      const swipeAmountY = Number(((_toastRef_current1 = toastRef.current) == null ? void 0 :
_toastRef_current1.style.getPropertyValue('--swipe-amount-y').replace('px', '')) || 0);
      const timeTaken = new Date().getTime() - ((_dragStartTime_current = dragStartTime.current) ==
null ? void 0 : _dragStartTime_current.getTime());
      const swipeAmount = swipeDirection === 'x' ? swipeAmountX : swipeAmountY;
      const velocity = Math.abs(swipeAmount) / timeTaken;
      if (Math.abs(swipeAmount) >= SWIPE_THRESHOLD || velocity > 0.11) {
        setOffsetBeforeRemove(offset.current);
        toast.onDismiss == null ? void 0 : toast.onDismiss.call(toast, toast);
        if (swipeDirection === 'x') {
          setSwipeOutDirection(swipeAmountX > 0 ? 'right' : 'left');
        } else {
          setSwipeOutDirection(swipeAmountY > 0 ? 'down' : 'up');
        }
        deleteToast();
        setSwipeOut(true);
        return;
      } else {
        var _toastRef_current2, _toastRef_current3;
        (_toastRef_current2 = toastRef.current) == null ? void 0 : _toastRef_current2.style.setProperty('--
swipe-amount-x', `0px`);
        (_toastRef_current3 = toastRef.current) == null ? void 0 : _toastRef_current3.style.setProperty('--
swipe-amount-y', `0px`);
      }
      setIsSwiped(false);
      setSwiping(false);
      setSwipeDirection(null);
    },
    onPointerMove: event => {
      var _window_getSelection,
        // Apply transform using both x and y values
        _toastRef_current, _toastRef_current1;
      if (!pointerStartRef.current || !dismissible) return;
      const isHighlighted = ((_window_getSelection = window.getSelection()) == null ? void 0 :
_window_getSelection.toString().length) > 0;
```

```
    if (isHighlighted) return;
    const yDelta = event.clientY - pointerStartRef.current.y;
    const xDelta = event.clientX - pointerStartRef.current.x;
    var _props_swipeDirections;
    const swipeDirections = (_props_swipeDirections = props.swipeDirections) != null ?
_props_swipeDirections : getDefaultSwipeDirections(position);
    // Determine swipe direction if not already locked
    if (!swipeDirection && (Math.abs(xDelta) > 1 || Math.abs(yDelta) > 1)) {
      setSwipeDirection(Math.abs(xDelta) > Math.abs(yDelta) ? 'x' : 'y');
    }
    let swipeAmount = {
      x: 0,
      y: 0
    };
    const getDampening = delta => {
      const factor = Math.abs(delta)
 / 20;
      return 1 / (1.5 + factor);
    };
    // Only apply swipe in the locked direction
    if (swipeDirection === 'y') {
      // Handle vertical swipes
      if (swipeDirections.includes('top') || swipeDirections.includes('bottom')) {
        if (swipeDirections.includes('top') && yDelta < 0 || swipeDirections.includes('bottom') &&
yDelta > 0) {
          swipeAmount.y = yDelta;
        } else {
          // Smoothly transition to dampened movement
          const dampenedDelta = yDelta * getDampening(yDelta);
          // Ensure we don't jump when transitioning to dampened movement
          swipeAmount.y = Math.abs(dampenedDelta) < Math.abs(yDelta) ? dampenedDelta : yDelta;
        }
      }
    } else if (swipeDirection === 'x') {
      // Handle horizontal swipes
      if (swipeDirections.includes('left') || swipeDirections.includes('right')) {
        if (swipeDirections.includes('left') && xDelta < 0 || swipeDirections.includes('right') && xDelta
> 0) {
          swipeAmount.x = xDelta;
        } else {
          // Smoothly transition to dampened movement
          const dampenedDelta = xDelta * getDampening(xDelta);
          // Ensure we don't jump when transitioning to dampened movement
          swipeAmount.x = Math.abs(dampenedDelta) < Math.abs(xDelta) ? dampenedDelta : xDelta;
        }
      }
    }
    if (Math.abs(swipeAmount.x) > 0 || Math.abs(swipeAmount.y) > 0) {
      setIsSwiped(true);
```

```
      }
      (_toastRef_current = toastRef.current) == null ? void 0 : _toastRef_current.style.setProperty('--
swipe-amount-x', `${swipeAmount.x}px`);
      (_toastRef_current1 = toastRef.current) == null ? void 0 : _toastRef_current1.style.setProperty('--
swipe-amount-y', `${swipeAmount.y}px`);
    }
  }, closeButton && !toast.jsx && toastType !== 'loading' ?
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("button", {
    "aria-label": closeButtonAriaLabel,
    "data-disabled": disabled,
    "data-close-button": true,
    onClick: disabled || !dismissible ? () => {} : () => {
      deleteToast();
      toast.onDismiss == null ? void 0 : toast.onDismiss.call(toast, toast);
    },
    className: cn(className == null ? void 0 : className.closeButton, toast == null ? void 0 :
(_toast_classNames2 = toast.classNames) == null ? void 0 : _toast_classNames2.closeButton)
  }, (_icons_close = icons == null ? void 0 : icons.close) != null ? _icons_close : CloseIcon) : null,
(toastType || toast.icon || toast.promise) && toast.icon !== null && ((icons == null ? void 0 :
icons[toastType]) !== null || toast.icon) ?
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    "data-icon": "",
    className: cn(className == null ? void 0 : className.icon, toast == null ? void 0 :
(_toast_classNames3 = toast.classNames) == null ? void 0 : _toast_classNames3.icon)
  }, toast.promise || toast.type === 'loading' && !toast.icon ? toast.icon || getLoadingIcon() : null,
toast.type !== 'loading' ? icon : null) : null,
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    "data-content": "",
    className: cn(className == null ? void 0 : className.content, toast == null ? void 0 :
(_toast_classNames4 = toast.classNames) == null ? void 0 : _toast_classNames4.content)
  }, /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    "data-title": "",
    className: cn(className == null ? void 0 : className.title, toast == null ? void 0 :
(_toast_classNames5 = toast.classNames) == null ? void 0 : _toast_classNames5.title)
  }, toast.jsx ? toast.jsx : typeof toast.title === 'function' ? toast.title() : toast.title), toast.description ?
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("div", {
    "data-description": "",
    className: cn(descriptionClassName, toastDescriptionClassname, className == null ? void 0 :
className.description, toast == null ? void 0 : (_toast_classNames6 = toast.classNames) == null ?
void 0 : _toast_classNames6.description)
  }, typeof toast.description === 'function' ? toast.description() : toast.description) : null),
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(toast.cancel) ?
toast.cancel : toast.cancel && isAction(toast.cancel) ?
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("button", {
    "data-button": true,
    "data-cancel": true,
    style: toast.cancelButtonStyle || cancelButtonStyle,
    onClick: event => {
      // We need to check twice because typescript
```

```
      if (!isAction(toast.cancel)) return;
      if (!dismissible) return;
      toast.cancel.onClick == null ? void 0 : toast.cancel.onClick.call(toast.cancel, event);
      deleteToast();
    },
    className: cn(className == null ? void 0 : className.cancelButton, toast == null ? void 0 :
(_toast_classNames7 = toast.classNames) == null ? void 0 : _toast_classNames7.cancelButton)
  }, toast.cancel.label) : null,
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.isValidElement(toast.action) ?
toast.action : toast.action && isAction(toast.action) ?
/*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("button", {
    "data-button": true,
    "data-action": true,
    style: toast.actionButtonStyle || actionButtonStyle,
    onClick: event => {
      // We need to check twice because typescript
      if (!isAction(toast.action)) return;
      toast.action.onClick == null ? void 0 : toast.action.onClick.call(toast.action, event);
      if (event.defaultPrevented) return;
      deleteToast();
    },
    className: cn(className == null ? void 0 : className.actionButton, toast == null ? void 0 :
(_toast_classNames8 = toast.classNames) == null ? void 0 : _toast_classNames8.actionButton)
  }, toast.action.label) : null);
};
function getDocumentDirection() {
  if (typeof window === 'undefined') return 'ltr';
  if (typeof document === 'undefined') return 'ltr'; // For Fresh purpose
  const dirAttribute = document.documentElement.getAttribute('dir');
  if (dirAttribute === 'auto' || !dirAttribute) {
    return window.getComputedStyle(document.documentElement).direction;
  }
  return dirAttribute;
}
function assignOffset(defaultOffset, mobileOffset) {
  const styles = {};
  [defaultOffset, mobileOffset].forEach((offset, index) => {
    const isMobile = index === 1;
    const prefix = isMobile ? '--mobile-offset' : '--offset';
    const defaultValue = isMobile ? MOBILE_VIEWPORT_OFFSET : VIEWPORT_OFFSET;
    function assignAll(offset) {
      ['top', 'right', 'bottom', 'left'].forEach(key => {
        styles[`${prefix}-${key}`] = typeof offset === 'number' ? `${offset}px` : offset;
      });
    }
    if (typeof offset === 'number' || typeof offset === 'string') {
      assignAll(offset);
    } else if (typeof offset === 'object') {
      ['top', 'right', 'bottom', 'left'].forEach(key => {
```

```
      if (offset[key] === undefined) {
        styles[`${prefix}-${key}`] = defaultValue;
      } else {
        styles[`${prefix}-${key}`] = typeof offset[key] === 'number' ? `${offset[key]}px` : offset[key];
      }
    });
  } else {
    assignAll(defaultValue);
  }
});
return styles;
}
function useSonner() {
  const [activeToasts, setActiveToasts] =
react__WEBPACK_IMPORTED_MODULE_0__.useState([]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    return ToastState.subscribe(toast => {
      if (toast.dismiss) {
        setTimeout(() => {
          react_dom__WEBPACK_IMPORTED_MODULE_1__.flushSync(() => {
            setActiveToasts(toasts => toasts.filter(t => t.id !== toast.id));
          });
        });
        return;
      }
      // Prevent batching, temp solution.
      setTimeout(() => {
        react_dom__WEBPACK_IMPORTED_MODULE_1__.flushSync(() => {
          setActiveToasts(toasts => {
            const indexOfExistingToast = toasts.findIndex(t => t.id === toast.id);
            // Update the toast if it already exists
            if (indexOfExistingToast !== -1) {
              return [...toasts.slice(0, indexOfExistingToast), {
                ...toasts[indexOfExistingToast],
                ...toast
              }, ...toasts.slice(indexOfExistingToast + 1)];
            }
            return [toast, ...toasts];
          });
        });
      });
    });
  }, []);
  return {
    toasts: activeToasts
  };
}
const Toaster = /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.forwardRef(function
Toaster(props, ref) {
```

```
  const {
    invert,
    position = 'bottom-right',
    hotkey = ['altKey', 'KeyT'],
    expand,
    closeButton,
    className,
    offset,
    mobileOffset,
    theme = 'light',
    richColors,
    duration,
    style,
    visibleToasts = VISIBLE_TOASTS_AMOUNT,
    toastOptions,
    dir = getDocumentDirection(),
    gap = GAP,
    icons,
    containerAriaLabel = 'Notifications'
  } = props;
  const [toasts, setToasts] = react__WEBPACK_IMPORTED_MODULE_0__.useState([]);
  const possiblePositions = react__WEBPACK_IMPORTED_MODULE_0__.useMemo(() => {
    return Array.from(new Set([position].concat(toasts.filter(toast => toast.position).map(toast =>
toast.position))));
  }, [toasts, position]);
  const [heights, setHeights] = react__WEBPACK_IMPORTED_MODULE_0__.useState([]);
  const [expanded, setExpanded] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [interacting, setInteracting] = react__WEBPACK_IMPORTED_MODULE_0__.useState(false);
  const [actualTheme, setActualTheme] =
react__WEBPACK_IMPORTED_MODULE_0__.useState(theme !== 'system' ? theme : typeof
window !== 'undefined' ? window.matchMedia && window.matchMedia('(prefers-color-scheme:
dark)').matches ? 'dark' : 'light' : 'light');
  const listRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
  const hotkeyLabel = hotkey.join('+').replace(/Key/g, '').replace(/Digit/g, '');
  const lastFocusedElementRef = react__WEBPACK_IMPORTED_MODULE_0__.useRef(null);
  const isFocusWithinRef
 = react__WEBPACK_IMPORTED_MODULE_0__.useRef(false);
  const removeToast = react__WEBPACK_IMPORTED_MODULE_0__.useCallback(toastToRemove
=> {
    setToasts(toasts => {
      var _toasts_find;
      if (!((_toasts_find = toasts.find(toast => toast.id === toastToRemove.id)) == null ? void 0 :
_toasts_find.delete)) {
        ToastState.dismiss(toastToRemove.id);
      }
      return toasts.filter(({
        id
      }) => id !== toastToRemove.id);
    });
```

```
}, []);
react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
  return ToastState.subscribe(toast => {
    if (toast.dismiss) {
      // Prevent batching of other state updates
      requestAnimationFrame(() => {
        setToasts(toasts => toasts.map(t => t.id === toast.id ? {
          ...t,
          delete: true
        } : t));
      });
      return;
    }
    // Prevent batching, temp solution.
    setTimeout(() => {
      react_dom__WEBPACK_IMPORTED_MODULE_1__.flushSync(() => {
        setToasts(toasts => {
          const indexOfExistingToast = toasts.findIndex(t => t.id === toast.id);
          // Update the toast if it already exists
          if (indexOfExistingToast !== -1) {
            return [...toasts.slice(0, indexOfExistingToast), {
              ...toasts[indexOfExistingToast],
              ...toast
            }, ...toasts.slice(indexOfExistingToast + 1)];
          }
          return [toast, ...toasts];
        });
      });
    });
  });
}, [toasts]);
react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
  if (theme !== 'system') {
    setActualTheme(theme);
    return;
  }
  if (theme === 'system') {
    // check if current preference is dark
    if (window.matchMedia && window.matchMedia('(prefers-color-scheme: dark)').matches) {
      // it's currently dark
      setActualTheme('dark');
    } else {
      // it's not dark
      setActualTheme('light');
    }
  }
  if (typeof window === 'undefined') return;
  const darkMediaQuery = window.matchMedia('(prefers-color-scheme: dark)');
  try {
```

```
      // Chrome & Firefox
      darkMediaQuery.addEventListener('change', ({
        matches
      }) => {
        if (matches) {
          setActualTheme('dark');
        } else {
          setActualTheme('light');
        }
      });
    } catch (error) {
      // Safari < 14
      darkMediaQuery.addListener(({
        matches
      }) => {
        try {
          if (matches) {
            setActualTheme('dark');
          } else {
            setActualTheme('light');
          }
        } catch (e) {
          console.error(e);
        }
      });
    }
  }, [theme]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    // Ensure expanded is always false when no toasts are present / only one left
    if (toasts.length <= 1) {
      setExpanded(false);
    }
  }, [toasts]);
  react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
    const handleKeyDown = event => {
      var _listRef_current;
      const isHotkeyPressed = hotkey.every(key => event[key] || event.code === key);
      if (isHotkeyPressed) {
        var _listRef_current1;
        setExpanded(true);
        (_listRef_current1 = listRef.current) == null ? void 0 : _listRef_current1.focus();
      }
      if (event.code === 'Escape' && (document.activeElement === listRef.current || ((_listRef_current =
listRef.current) == null ? void 0 : _listRef_current.contains(document.activeElement)))) {
        setExpanded(false);
      }
    };
    document.addEventListener('keydown', handleKeyDown);
    return () => document.removeEventListener('keydown', handleKeyDown);
```

```
}, [hotkey]);
react__WEBPACK_IMPORTED_MODULE_0__.useEffect(() => {
  if (listRef.current) {
    return () => {
      if (lastFocusedElementRef.current) {
        lastFocusedElementRef.current.focus({
          preventScroll: true
        });
        lastFocusedElementRef.current = null;
        isFocusWithinRef.current = false;
      }
    };
  }
}, [listRef.current]);
return (
  // Remove item from normal navigation flow, only available via hotkey
  /*#__PURE__*/
  react__WEBPACK_IMPORTED_MODULE_0__.createElement("section", {
    ref: ref,
    "aria-label": `${containerAriaLabel} ${hotkeyLabel}`,
    tabIndex: -1,
    "aria-live": "polite",
    "aria-relevant": "additions text",
    "aria-atomic": "false",
    suppressHydrationWarning: true
  }, possiblePositions.map((position, index) => {
    var _heights_;
    const [y, x] = position.split('-');
    if (!toasts.length) return null;
    return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement("ol", {
      key: position,
      dir: dir === 'auto' ? getDocumentDirection() : dir,
      tabIndex: -1,
      ref: listRef,
      className: className,
      "data-sonner-toaster": true,
      "data-sonner-theme": actualTheme,
      "data-y-position": y,
      "data-lifted": expanded && toasts.length > 1 && !expand,
      "data-x-position": x,
      style: {
        '--front-toast-height': `${((_heights_ = heights[0]) == null ? void 0 : _heights_.height) || 0}px`,
        '--width': `${TOAST_WIDTH}px`,
        '--gap': `${gap}px`,
        ...style,
        ...assignOffset(offset, mobileOffset)
      },
      onBlur: event => {
        if (isFocusWithinRef.current && !event.currentTarget.contains(event.relatedTarget)) {
```

```
          isFocusWithinRef.current = false;
          if (lastFocusedElementRef.current) {
            lastFocusedElementRef.current.focus({
              preventScroll: true
            });
            lastFocusedElementRef.current = null;
          }
        }
      },
      onFocus: event => {
        const isNotDismissible = event.target instanceof HTMLElement &&
event.target.dataset.dismissible === 'false';
        if (isNotDismissible) return;
        if (!isFocusWithinRef.current) {
          isFocusWithinRef.current = true;
          lastFocusedElementRef.current = event.relatedTarget;
        }
      },
      onMouseEnter: () => setExpanded(true),
      onMouseMove: () => setExpanded(true),
      onMouseLeave: () => {
        // Avoid setting expanded to false when interacting with a toast, e.g. swiping
        if (!interacting) {
          setExpanded(false);
        }
      },
      onDragEnd: () => setExpanded(false),
      onPointerDown: event => {
        const isNotDismissible = event.target instanceof HTMLElement &&
event.target.dataset.dismissible === 'false';
        if (isNotDismissible) return;
        setInteracting(true);
      },
      onPointerUp: () => setInteracting(false)
    }, toasts.filter(toast => !toast.position && index === 0 || toast.position === position).map((toast,
index) => {
      var _toastOptions_duration, _toastOptions_closeButton;
      return /*#__PURE__*/react__WEBPACK_IMPORTED_MODULE_0__.createElement(Toast, {
        key: toast.id,
        icons: icons,
        index: index,
        toast: toast,
        defaultRichColors: richColors,
        duration: (_toastOptions_duration = toastOptions == null ? void 0 : toastOptions.duration) !=
null ? _toastOptions_duration : duration,
        className: toastOptions == null ? void 0 : toastOptions.className,
        descriptionClassName: toastOptions == null ? void 0 : toastOptions.descriptionClassName,
        invert: invert,
        visibleToasts: visibleToasts,
```

```
        closeButton: (_toastOptions_closeButton = toastOptions == null ? void 0 :
toastOptions.closeButton) != null ? _toastOptions_closeButton : closeButton,
        interacting: interacting,
        position: position,
        style: toastOptions == null ? void 0 : toastOptions.style,
        unstyled: toastOptions == null ? void 0 : toastOptions.unstyled,
        classNames: toastOptions == null ? void 0 : toastOptions.classNames,
        cancelButtonStyle: toastOptions == null ? void 0 : toastOptions.cancelButtonStyle,
        actionButtonStyle: toastOptions == null ? void 0 : toastOptions.actionButtonStyle,
        closeButtonAriaLabel: toastOptions == null ? void 0 : toastOptions.closeButtonAriaLabel,
        removeToast: removeToast,
        toasts: toasts.filter(t => t.position == toast.position),
        heights: heights.filter(h => h.position == toast.position),
        setHeights: setHeights,
        expandByDefault: expand,
        gap: gap,
        expanded: expanded,
        swipeDirections: props.swipeDirections
      });
    }));
  }))
 );
});


/***/ }

/******/ 	});
/************************************************************************/
/******/ 	// The module cache
/******/ 	var __webpack_module_cache__ = {};
/******/
/******/ 	// The require function
/******/ 	function __webpack_require__(moduleId) {
/******/ 		// Check if module is in cache
/******/ 		var cachedModule = __webpack_module_cache__[moduleId];
/******/ 		if (cachedModule !== undefined) {
/******/ 			return cachedModule.exports;
/******/ 		}
/******/ 		// Create a new module (and put it into the cache)
/******/ 		var module = __webpack_module_cache__[moduleId] = {
/******/ 			id: moduleId,
/******/ 			loaded: false,
/******/ 			exports: {}
/******/ 		};
/******/
/******/ 		// Execute the module function
/******/ 		var execOptions = { id: moduleId, module: module, factory:
__webpack_modules__[moduleId], require: __webpack_require__ };
```

```
/******/ 		__webpack_require__.i.forEach(function(handler) { handler(execOptions); });
/******/ 		if (!execOptions.factory) {
/******/ 			delete __webpack_module_cache__[moduleId];
/******/ 			var e = new Error("Cannot find module '" + moduleId + "'");
/******/ 			e.code = 'MODULE_NOT_FOUND';
/******/ 			throw e;
/******/ 		}
/******/ 		module = execOptions.module;
/******/ 		execOptions.factory.call(module.exports,
 module, module.exports, execOptions.require);
/******/
/******/ 		// Flag the module as loaded
/******/ 		module.loaded = true;
/******/
/******/ 		// Return the exports of the module
/******/ 		return module.exports;
/******/ 	}
/******/
/******/ 	// expose the modules object (__webpack_modules__)
/******/ 	__webpack_require__.m = __webpack_modules__;
/******/
/******/ 	// expose the module cache
/******/ 	__webpack_require__.c = __webpack_module_cache__;
/******/
/******/ 	// expose the module execution interceptor
/******/ 	__webpack_require__.i = [];
/******/
/************************************************************************/
/******/ 	/* webpack/runtime/compat get default export */
/******/ 	(() => {
/******/ 		// getDefaultExport function for compatibility with non-harmony modules
/******/ 		__webpack_require__.n = (module) => {
/******/ 			var getter = module && module.__esModule ?
/******/ 				() => (module['default']) :
/******/ 				() => (module);
/******/ 			__webpack_require__.d(getter, { a: getter });
/******/ 			return getter;
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/create fake namespace object */
/******/ 	(() => {
/******/ 		var getProto = Object.getPrototypeOf ? (obj) => (Object.getPrototypeOf(obj)) :
(obj) => (obj.__proto__);
/******/ 		var leafPrototypes;
/******/ 		// create a fake namespace object
/******/ 		// mode & 1: value is a module id, require it
/******/ 		// mode & 2: merge all properties of value into the ns
/******/ 		// mode & 4: return value when already ns object
```

```
/******/ 		// mode & 16: return value when it's Promise-like
/******/ 		// mode & 8|1: behave like require
/******/ 		__webpack_require__.t = function(value, mode) {
/******/ 			if(mode & 1) value = this(value);
/******/ 			if(mode & 8) return value;
/******/ 			if(typeof value === 'object' && value) {
/******/ 				if((mode & 4) && value.__esModule) return value;
/******/ 				if((mode & 16) && typeof value.then === 'function') return value;
/******/ 			}
/******/ 			var ns = Object.create(null);
/******/ 			__webpack_require__.r(ns);
/******/ 			var def = {};
/******/ 			leafPrototypes = leafPrototypes || [null, getProto({}), getProto([]),
getProto(getProto)];
/******/ 			for(var current = mode & 2 && value; (typeof current == 'object' || typeof
current == 'function') && !~leafPrototypes.indexOf(current); current = getProto(current)) {
/******/ 				Object.getOwnPropertyNames(current).forEach((key) =>
(def[key] = () => (value[key])));
/******/ 			}
/******/ 			def['default'] = () => (value);
/******/ 			__webpack_require__.d(ns, def);
/******/ 			return ns;
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/define property getters */
/******/ 	(() => {
/******/ 		// define getter functions for harmony exports
/******/ 		__webpack_require__.d = (exports, definition) => {
/******/ 			for(var key in definition) {
/******/ 				if(__webpack_require__.o(definition, key) && !
__webpack_require__.o(exports, key)) {
/******/ 					Object.defineProperty(exports, key, { enumerable: true,
get: definition[key] });
/******/ 				}
/******/ 			}
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/get javascript update chunk filename */
/******/ 	(() => {
/******/ 		// This function allow to reference all chunks
/******/ 		__webpack_require__.hu = (chunkId) => {
/******/ 			// return url for filenames based on template
/******/ 			return "" + chunkId + "." + __webpack_require__.h() + ".hot-update.js";
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/get update manifest filename */
```

```
/******/	(() => {
/******/		__webpack_require__.hmrF = () => ("main." + __webpack_require__.h() +
".hot-update.json");
/******/	})();
/******/
/******/	/* webpack/runtime/getFullHash */
/******/	(() => {
/******/		__webpack_require__.h = () => ("728774945148e86667a7")
/******/	})();
/******/
/******/	/* webpack/runtime/hasOwnProperty shorthand */
/******/	(() => {
/******/		__webpack_require__.o = (obj, prop) =>
(Object.prototype.hasOwnProperty.call(obj, prop))
/******/	})();
/******/
/******/	/* webpack/runtime/load script */
/******/	(() => {
/******/		var inProgress = {};
/******/		var dataWebpackPrefix = "frontend:";
/******/		// loadScript function to load a script via script tag
/******/		__webpack_require__.l = (url, done, key, chunkId) => {
/******/			if(inProgress[url]) { inProgress[url].push(done); return; }
/******/			var script, needAttach;
/******/			if(key !== undefined) {
/******/				var scripts = document.getElementsByTagName("script");
/******/				for(var i = 0; i < scripts.length; i++) {
/******/					var s = scripts[i];
/******/					if(s.getAttribute("src") == url || s.getAttribute("data-
webpack") == dataWebpackPrefix + key) { script = s; break; }
/******/				}
/******/			}
/******/			if(!script) {
/******/				needAttach = true;
/******/				script = document.createElement('script');
/******/
/******/				script.charset = 'utf-8';
/******/				if (__webpack_require__.nc) {
/******/					script.setAttribute("nonce", __webpack_require__.nc);
/******/				}
/******/				script.setAttribute("data-webpack", dataWebpackPrefix + key);
/******/
/******/				script.src = url;
/******/			}
/******/			inProgress[url] = [done];
/******/			var onScriptComplete = (prev, event) => {
/******/				// avoid mem leaks in IE.
/******/				script.onerror = script.onload = null;
/******/				clearTimeout(timeout);
```

```
/******/ 				var doneFns = inProgress[url];
/******/ 				delete inProgress[url];
/******/ 				script.parentNode && script.parentNode.removeChild(script);
/******/ 				doneFns && doneFns.forEach((fn) => (fn(event)));
/******/ 				if(prev) return prev(event);
/******/ 			}
/******/ 			var timeout = setTimeout(onScriptComplete.bind(null, undefined, { type:
'timeout', target: script }), 120000);
/******/ 			script.onerror = onScriptComplete.bind(null, script.onerror);
/******/ 			script.onload = onScriptComplete.bind(null, script.onload);
/******/ 			needAttach && document.head.appendChild(script);
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/make namespace object */
/******/ 	(() => {
/******/ 		// define __esModule on exports
/******/ 		__webpack_require__.r = (exports) => {
/******/ 			if(typeof Symbol !== 'undefined' && Symbol.toStringTag) {
/******/ 				Object.defineProperty(exports, Symbol.toStringTag, { value:
'Module' });
/******/ 			}
/******/ 			Object.defineProperty(exports, '__esModule', { value: true });
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/node module decorator */
/******/ 	(() => {
/******/ 		__webpack_require__.nmd = (module) => {
/******/ 			module.paths = [];
/******/ 			if (!module.children) module.children = [];
/******/ 			return module;
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/set anonymous default export name */
/******/ 	(() => {
/******/ 		// set .name for anonymous default exports per ES spec
/******/ 		__webpack_require__.dn = (x) => {
/******/ 			(Object.getOwnPropertyDescriptor(x, "name") || {}).writable ||
Object.defineProperty(x, "name", { value: "default", configurable: true });
/******/ 		};
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/hot module replacement */
/******/ 	(() => {
/******/ 		var currentModuleData = {};
/******/ 		var installedModules = __webpack_require__.c;
/******/
```

```
/******/ 	// module and require creation
/******/ 	var currentChildModule;
/******/ 	var currentParents = [];
/******/
/******/ 	// status
/******/ 	var registeredStatusHandlers = [];
/******/ 	var currentStatus = "idle";
/******/
/******/ 	// while downloading
/******/ 	var blockingPromises = 0;
/******/ 	var blockingPromisesWaiting = [];
/******/
/******/ 	// The update info
/******/ 	var currentUpdateApplyHandlers;
/******/ 	var queuedInvalidatedModules;
/******/
/******/ 	__webpack_require__.hmrD = currentModuleData;
/******/
/******/ 	__webpack_require__.i.push(function (options) {
/******/ 		var module = options.module;
/******/ 		var require = createRequire(options.require, options.id);
/******/ 		module.hot = createModuleHotObject(options.id, module);
/******/ 		module.parents = currentParents;
/******/ 		module.children = [];
/******/ 		currentParents = [];
/******/ 		options.require = require;
/******/ 	});
/******/
/******/ 	__webpack_require__.hmrC = {};
/******/ 	__webpack_require__.hmrI = {};
/******/
/******/ 	function createRequire(require, moduleId) {
/******/ 		var me = installedModules[moduleId];
/******/ 		if (!me) return require;
/******/ 		var fn = function (request) {
/******/ 			if (me.hot.active) {
/******/ 				if (installedModules[request]) {
/******/ 					var parents = installedModules[request].parents;
/******/ 					if (parents.indexOf(moduleId) === -1) {
/******/ 						parents.push(moduleId);
/******/ 					}
/******/ 				} else {
/******/ 					currentParents = [moduleId];
/******/ 					currentChildModule = request;
/******/ 				}
/******/ 				if (me.children.indexOf(request) === -1) {
/******/ 					me.children.push(request);
/******/ 				}
/******/ 			} else {
```

```
/******/ 				console.warn(
/******/ 					"[HMR] unexpected require(" +
/******/ 						request +
/******/ 						") from disposed module " +
/******/ 						moduleId
/******/ 				);
/******/ 				currentParents = [];
/******/ 			}
/******/ 			return require(request);
/******/ 		};
/******/ 		var createPropertyDescriptor = function (name) {
/******/ 			return {
/******/ 				configurable: true,
/******/ 				enumerable: true,
/******/ 				get: function () {
/******/ 					return require[name];
/******/ 				},
/******/ 				set: function (value) {
/******/ 					require[name] = value;
/******/ 				}
/******/ 			};
/******/ 		};
/******/ 		for (var
 name in require) {
/******/ 			if (Object.prototype.hasOwnProperty.call(require, name) &&
name !== "e") {
/******/ 				Object.defineProperty(fn, name,
createPropertyDescriptor(name));
/******/ 			}
/******/ 		}
/******/ 		fn.e = function (chunkId, fetchPriority) {
/******/ 			return trackBlockingPromise(require.e(chunkId, fetchPriority));
/******/ 		};
/******/ 		return fn;
/******/ 	}
/******/
/******/ 	function createModuleHotObject(moduleId, me) {
/******/ 		var _main = currentChildModule !== moduleId;
/******/ 		var hot = {
/******/ 			// private stuff
/******/ 			_acceptedDependencies: {},
/******/ 			_acceptedErrorHandlers: {},
/******/ 			_declinedDependencies: {},
/******/ 			_selfAccepted: false,
/******/ 			_selfDeclined: false,
/******/ 			_selfInvalidated: false,
/******/ 			_disposeHandlers: [],
/******/ 			_main: _main,
/******/ 			_requireSelf: function () {
```

```
/******/ 			currentParents = me.parents.slice();
/******/ 			currentChildModule = _main ? undefined : moduleId;
/******/ 			__webpack_require__(moduleId);
/******/ 		},
/******/
/******/ 		// Module API
/******/ 		active: true,
/******/ 		accept: function (dep, callback, errorHandler) {
/******/ 			if (dep === undefined) hot._selfAccepted = true;
/******/ 			else if (typeof dep === "function") hot._selfAccepted =
dep;
/******/ 			else if (typeof dep === "object" && dep !== null) {
/******/ 				for (var i = 0; i < dep.length; i++) {
/******/ 					hot._acceptedDependencies[dep[i]] =
callback || function () {};
/******/ 					hot._acceptedErrorHandlers[dep[i]] =
errorHandler;
/******/ 				}
/******/ 			} else {
/******/ 				hot._acceptedDependencies[dep] = callback ||
function () {};
/******/ 				hot._acceptedErrorHandlers[dep] = errorHandler;
/******/ 			}
/******/ 		},
/******/ 		decline: function (dep) {
/******/ 			if (dep === undefined) hot._selfDeclined = true;
/******/ 			else if (typeof dep === "object" && dep !== null)
/******/ 				for (var i = 0; i < dep.length; i++)
/******/ 					hot._declinedDependencies[dep[i]] = true;
/******/ 			else hot._declinedDependencies[dep] = true;
/******/ 		},
/******/ 		dispose: function (callback) {
/******/ 			hot._disposeHandlers.push(callback);
/******/ 		},
/******/ 		addDisposeHandler: function (callback) {
/******/ 			hot._disposeHandlers.push(callback);
/******/ 		},
/******/ 		removeDisposeHandler: function (callback) {
/******/ 			var idx = hot._disposeHandlers.indexOf(callback);
/******/ 			if (idx >= 0) hot._disposeHandlers.splice(idx, 1);
/******/ 		},
/******/ 		invalidate: function () {
/******/ 			this._selfInvalidated = true;
/******/ 			switch (currentStatus) {
/******/ 				case "idle":
/******/ 					currentUpdateApplyHandlers = [];
/******/
	Object.keys(__webpack_require__.hmrI).forEach(function (key) {
/******/ 				__webpack_require__.hmrI[key](
```

```
/******/                                                                 moduleId,
/******/                                                                 currentUpdateApplyHandlers
/******/                                                         );
/******/                                                 });
/******/                                                 setStatus("ready");
/******/                                                 break;
/******/                                         case "ready":
/******/
        Object.keys(__webpack_require__.hmrI).forEach(function (key) {
/******/                                                         __webpack_require__.hmrI[key](
/******/                                                                 moduleId,
/******/                                                                 currentUpdateApplyHandlers
/******/                                                         );
/******/                                                 });
/******/                                                 break;
/******/                                         case "prepare":
/******/                                         case "check":
/******/                                         case "dispose":
/******/                                         case "apply":
/******/                                                 (queuedInvalidatedModules =
queuedInvalidatedModules || []).push(
/******/                                                                 moduleId
/******/                                                 );
/******/                                                 break;
/******/                                         default:
/******/                                                 // ignore requests in error states
/******/                                                 break;
/******/                                 }
/******/                         },
/******/
/******/                         // Management API
/******/                         check: hotCheck,
/******/                         apply: hotApply,
/******/                         status: function (l) {
/******/                                 if (!l) return currentStatus;
/******/                                 registeredStatusHandlers.push(l);
/******/                         },
/******/                         addStatusHandler: function (l) {
/******/                                 registeredStatusHandlers.push(l);
/******/                         },
/******/                         removeStatusHandler: function (l) {
/******/                                 var idx = registeredStatusHandlers.indexOf(l);
/******/                                 if (idx >= 0) registeredStatusHandlers.splice(idx, 1);
/******/                         },
/******/
/******/                         // inherit from previous dispose call
/******/                         data: currentModuleData[moduleId]
/******/                 };
/******/                 currentChildModule = undefined;
```

```
/******/ 		return hot;
/******/ 	}
/******/
/******/ 	function setStatus(newStatus) {
/******/ 		currentStatus = newStatus;
/******/ 		var results = [];
/******/
/******/ 		for (var i = 0; i < registeredStatusHandlers.length; i++)
/******/ 			results[i] = registeredStatusHandlers[i].call(null, newStatus);
/******/
/******/ 		return Promise.all(results).then(function () {});
/******/ 	}
/******/
/******/ 	function unblock() {
/******/ 		if (--blockingPromises === 0) {
/******/ 			setStatus("ready").then(function () {
/******/ 				if (blockingPromises === 0) {
/******/ 					var list = blockingPromisesWaiting;
/******/ 					blockingPromisesWaiting = [];
/******/ 					for (var i = 0; i < list.length; i++) {
/******/ 						list[i]();
/******/ 					}
/******/ 				}
/******/ 			});
/******/ 		}
/******/ 	}
/******/
/******/ 	function trackBlockingPromise(promise) {
/******/ 		switch (currentStatus) {
/******/ 			case "ready":
/******/ 				setStatus("prepare");
/******/ 			/* fallthrough */
/******/ 			case "prepare":
/******/ 				blockingPromises++;
/******/ 				promise.then(unblock, unblock);
/******/ 				return promise;
/******/ 			default:
/******/ 				return promise;
/******/ 		}
/******/ 	}
/******/
/******/ 	function waitForBlockingPromises(fn) {
/******/ 		if (blockingPromises === 0) return fn();
/******/ 		return new Promise(function (resolve) {
/******/ 			blockingPromisesWaiting.push(function () {
/******/ 				resolve(fn());
/******/ 			});
/******/ 		});
/******/ 	}
```

```
/******/
/******/ 		function hotCheck(applyOnUpdate) {
/******/ 			if (currentStatus !== "idle") {
/******/ 				throw new Error("check() is only allowed in idle status");
/******/ 			}
/******/ 			return setStatus("check")
/******/ 				.then(__webpack_require__.hmrM)
/******/ 				.then(function (update) {
/******/ 					if (!update) {
/******/ 						return setStatus(applyInvalidatedModules() ?
"ready" : "idle").then(
/******/ 							function () {
/******/ 								return null;
/******/ 							}
/******/ 						);
/******/ 					}
/******/
/******/ 					return setStatus("prepare").then(function () {
/******/ 						var updatedModules = [];
/******/ 						currentUpdateApplyHandlers = [];
/******/
/******/ 						return Promise.all(
/******/
        Object.keys(__webpack_require__.hmrC).reduce(function (
/******/ 								promises,
/******/ 								key
/******/ 							) {
/******/ 								__webpack_require__.hmrC[key](
/******/ 									update.c,
/******/ 									update.r,
/******/ 									update.m,
/******/ 									promises,
/******/
        currentUpdateApplyHandlers,
/******/ 									updatedModules,
/******/ 									update.css
/******/ 								);
/******/ 								return promises;
/******/ 							}, [])
/******/ 						).then(function () {
/******/ 							return waitForBlockingPromises(function ()
{
/******/ 								if (applyOnUpdate) {
/******/ 									return
internalApply(applyOnUpdate);
/******/ 								}
/******/ 								return
setStatus("ready").then(function () {
/******/ 									return updatedModules;
```

```
/******/                                                        });
/******/                                                });
/******/                                        });
/******/                                });
/******/                        });
/******/        }
/******/
/******/        function hotApply(options) {
/******/                if (currentStatus !== "ready") {
/******/                        return Promise.resolve().then(function () {
/******/                                throw new Error(
/******/                                        "apply() is only allowed in ready status (state: " +
/******/                                                currentStatus +
/******/                                                ")"
/******/                                );
/******/                        });
/******/                }
/******/                return internalApply(options);
/******/        }
/******/
/******/        function internalApply(options) {
/******/                options = options || {};
/******/
/******/                applyInvalidatedModules();
/******/
/******/                var results = currentUpdateApplyHandlers.map(function (handler) {
/******/                        return handler(options);
/******/                });
/******/                currentUpdateApplyHandlers = undefined;
/******/
/******/                var errors = results
/******/                        .map(function (r) {
/******/                                return r.error;
/******/                        })
/******/                        .filter(Boolean);
/******/
/******/                if (errors.length > 0) {
/******/                        return setStatus("abort").then(function () {
/******/                                throw errors[0];
/******/                        });
/******/                }
/******/
/******/                // Now in "dispose" phase
/******/                var disposePromise = setStatus("dispose");
/******/
/******/                results.forEach(function (result) {
/******/                        if (result.dispose) result.dispose();
/******/                });
/******/
```

```
/******/ 		// Now in "apply" phase
/******/ 		var applyPromise = setStatus("apply");
/******/
/******/ 		var error;
/******/ 		var reportError = function (err) {
/******/ 			if (!error) error = err;
/******/ 		};
/******/
/******/ 		var outdatedModules = [];
/******/
/******/ 		var onAccepted = function () {
/******/ 			return Promise.all([disposePromise, applyPromise]).then(function
() {
/******/ 				// handle errors in accept handlers and self accepted
module load
/******/ 				if (error) {
/******/ 					return setStatus("fail").then(function () {
/******/ 						throw error;
/******/ 					});
/******/ 				}
/******/
/******/ 				if (queuedInvalidatedModules) {
/******/ 					return internalApply(options).then(function (list) {
/******/ 						outdatedModules.forEach(function
(moduleId) {
/******/ 							if (list.indexOf(moduleId)
 < 0) list.push(moduleId);
/******/ 						});
/******/ 						return list;
/******/ 					});
/******/ 				}
/******/
/******/ 				return setStatus("idle").then(function () {
/******/ 					return outdatedModules;
/******/ 				});
/******/ 			});
/******/ 		};
/******/
/******/ 		return Promise.all(
/******/ 			results
/******/ 				.filter(function (result) {
/******/ 					return result.apply;
/******/ 				})
/******/ 				.map(function (result) {
/******/ 					return result.apply(reportError);
/******/ 				})
/******/ 		)
/******/ 			.then(function (applyResults) {
/******/ 				applyResults.forEach(function (modules) {
```

```
/******/                                                if (modules) {
/******/                                                        for (var i = 0; i < modules.length; i++) {
/******/                                                                outdatedModules.push(modules[i]);
/******/                                                        }
/******/                                                }
/******/                                        });
/******/                                })
/******/                                .then(onAccepted);
/******/                }
/******/
/******/                function applyInvalidatedModules() {
/******/                        if (queuedInvalidatedModules) {
/******/                                if (!currentUpdateApplyHandlers) currentUpdateApplyHandlers =
[];
/******/                                Object.keys(__webpack_require__.hmrI).forEach(function (key) {
/******/                                        queuedInvalidatedModules.forEach(function (moduleId) {
/******/                                                __webpack_require__.hmrI[key](
/******/                                                        moduleId,
/******/                                                        currentUpdateApplyHandlers
/******/                                                );
/******/                                        });
/******/                                });
/******/                                queuedInvalidatedModules = undefined;
/******/                                return true;
/******/                        }
/******/                }
/******/        })();
/******/
/******/        /* webpack/runtime/publicPath */
/******/        (() => {
/******/                __webpack_require__.p = "/";
/******/        })();
/******/
/******/        /* webpack/runtime/react refresh */
/******/        (() => {
/******/                const setup = (moduleId) => {
/******/                        const refresh = {
/******/                                moduleId: moduleId,
/******/                                register: (type, id) => {
/******/                                        const typeId = moduleId + " " + id;
/******/                                        refresh.runtime.register(type, typeId);
/******/                                },
/******/                                signature: () =>
(refresh.runtime.createSignatureFunctionForTransform()),
/******/                                runtime: {
/******/                                        createSignatureFunctionForTransform: () => ((type) =>
(type)),
/******/                                        register: x => {}
/******/                                },
```

```
/******/ 			};
/******/ 			return refresh;
/******/ 		}
/******/
/******/ 		__webpack_require__.i.push((options) => {
/******/ 			const originalFactory = options.factory;
/******/ 			options.factory = function(moduleObject, moduleExports,
webpackRequire) {
/******/ 				const hotRequire = (request) => (webpackRequire(request));
/******/ 				const createPropertyDescriptor = (name) => {
/******/ 					return {
/******/ 						configurable: true,
/******/ 						enumerable: true,
/******/ 						get: () => (webpackRequire[name]),
/******/ 						set: (value) => {
/******/ 							webpackRequire[name] = value;
/******/ 						},
/******/ 					};
/******/ 				};
/******/ 				for (const name in webpackRequire) {
/******/ 					if
(Object.prototype.hasOwnProperty.call(webpackRequire, name) && name !== "$Refresh$") {
/******/ 						Object.defineProperty(hotRequire, name,
createPropertyDescriptor(name));
/******/ 					}
/******/ 				}
/******/ 				hotRequire.$Refresh$ = setup(options.id);
/******/ 				originalFactory.call(this, moduleObject, moduleExports,
hotRequire);
/******/ 			};
/******/ 		});
/******/ 	})();
/******/
/******/ 	/* webpack/runtime/jsonp chunk loading */
/******/ 	(() => {
/******/ 		// no baseURI
/******/
/******/ 		// object to store loaded and loading chunks
/******/ 		// undefined = chunk not loaded, null = chunk preloaded/prefetched
/******/ 		// [resolve, reject, Promise] = chunk loading, 0 = chunk loaded
/******/ 		var installedChunks = __webpack_require__.hmrS_jsonp =
__webpack_require__.hmrS_jsonp || {
/******/ 			"main": 0
/******/ 		};
/******/
/******/ 		// no chunk on demand loading
/******/
/******/ 		// no prefetching
/******/
```

```
/******/ 		// no preloaded
/******/
/******/ 		var currentUpdatedModulesList;
/******/ 		var waitingUpdateResolves = {};
/******/ 		function loadUpdateChunk(chunkId, updatedModulesList) {
/******/ 			currentUpdatedModulesList = updatedModulesList;
/******/ 			return new Promise((resolve, reject) => {
/******/ 				waitingUpdateResolves[chunkId] = resolve;
/******/ 				// start update chunk loading
/******/ 				var url = __webpack_require__.p +
__webpack_require__.hu(chunkId);
/******/ 				// create error before stack unwound to get useful stacktrace later
/******/ 				var error = new Error();
/******/ 				var loadingEnded = (event) => {
/******/ 					if(waitingUpdateResolves[chunkId]) {
/******/ 						waitingUpdateResolves[chunkId] = undefined
/******/ 						var errorType = event && (event.type === 'load' ?
'missing' : event.type);
/******/ 						var realSrc = event && event.target &&
event.target.src;
/******/ 						error.message = 'Loading hot update chunk ' +
chunkId + ' failed.\n(' + errorType + ': ' + realSrc + ')';
/******/ 						error.name = 'ChunkLoadError';
/******/ 						error.type = errorType;
/******/ 						error.request = realSrc;
/******/ 						reject(error);
/******/ 					}
/******/ 				};
/******/ 				__webpack_require__.l(url, loadingEnded);
/******/ 			});
/******/ 		}
/******/
/******/ 		globalThis["webpackHotUpdatefrontend"] = (chunkId, moreModules, runtime)
=> {
/******/ 			for(var moduleId in moreModules) {
/******/ 				if(__webpack_require__.o(moreModules, moduleId)) {
/******/ 					currentUpdate[moduleId] = moreModules[moduleId];
/******/ 					if(currentUpdatedModulesList)
currentUpdatedModulesList.push(moduleId);
/******/ 				}
/******/ 			}
/******/ 			if(runtime) currentUpdateRuntime.push(runtime);
/******/ 			if(waitingUpdateResolves[chunkId]) {
/******/ 				waitingUpdateResolves[chunkId]();
/******/ 				waitingUpdateResolves[chunkId] = undefined;
/******/ 			}
/******/ 		};
/******/
/******/ 		var currentUpdateChunks;
```

```
/******/ 		var currentUpdate;
/******/ 		var currentUpdateRemovedChunks;
/******/ 		var currentUpdateRuntime;
/******/ 		function applyHandler(options) {
/******/ 			if (__webpack_require__.f) delete __webpack_require__.f.jsonpHmr;
/******/ 			currentUpdateChunks = undefined;
/******/ 			function getAffectedModuleEffects(updateModuleId) {
/******/ 				var outdatedModules = [updateModuleId];
/******/ 				var outdatedDependencies = {};
/******/
/******/ 				var queue = outdatedModules.map(function (id) {
/******/ 					return {
/******/ 						chain: [id],
/******/ 						id: id
/******/ 					};
/******/ 				});
/******/ 				while (queue.length > 0) {
/******/ 					var queueItem = queue.pop();
/******/ 					var moduleId = queueItem.id;
/******/ 					var chain = queueItem.chain;
/******/ 					var module = __webpack_require__.c[moduleId];
/******/ 					if (
/******/ 						!module ||
/******/ 						(module.hot._selfAccepted && !
module.hot._selfInvalidated)
/******/ 					)
/******/ 						continue;
/******/ 					if (module.hot._selfDeclined) {
/******/ 						return {
/******/ 							type: "self-declined",
/******/ 							chain: chain,
/******/ 							moduleId: moduleId
/******/ 						};
/******/ 					}
/******/ 					if (module.hot._main) {
/******/ 						return {
/******/ 							type: "unaccepted",
/******/ 							chain: chain,
/******/ 							moduleId: moduleId
/******/ 						};
/******/ 					}
/******/ 					for (var i = 0; i < module.parents.length; i++) {
/******/ 						var parentId = module.parents[i];
/******/ 						var parent = __webpack_require__.c[parentId];
/******/ 						if (!parent) continue;
/******/ 						if (parent.hot._declinedDependencies[moduleId]) {
/******/ 							return {
/******/ 								type: "declined",
/******/ 								chain: chain.concat([parentId]),
```

```
/******/                                                moduleId: moduleId,
/******/                                                parentId: parentId
/******/                                        };
/******/                                }
/******/                                if (outdatedModules.indexOf(parentId) !== -1)
continue;
/******/                                if (parent.hot._acceptedDependencies[moduleId]) {
/******/                                        if (!outdatedDependencies[parentId])
/******/                                                outdatedDependencies[parentId] =
[];
/******/
        addAllToSet(outdatedDependencies[parentId], [moduleId]);
/******/                                        continue;
/******/                                }
/******/                                delete outdatedDependencies[parentId];
/******/                                outdatedModules.push(parentId);
/******/                                queue.push({
/******/                                        chain: chain.concat([parentId]),
/******/                                        id: parentId
/******/                                });
/******/                        }
/******/                }
/******/
/******/                return {
/******/                        type: "accepted",
/******/                        moduleId: updateModuleId,
/******/                        outdatedModules: outdatedModules,
/******/                        outdatedDependencies: outdatedDependencies
/******/                };
/******/        }
/******/
/******/        function addAllToSet(a, b) {
/******/                for (var i = 0; i < b.length; i++) {
/******/                        var item = b[i];
/******/                        if (a.indexOf(item) === -1) a.push(item);
/******/                }
/******/        }
/******/
/******/        // at begin all updates modules are outdated
/******/        // the "outdated" status can propagate to parents if they don't accept the
children
/******/        var outdatedDependencies = {};
/******/        var outdatedModules = [];
/******/        var appliedUpdate = {};
/******/
/******/        var warnUnexpectedRequire = function warnUnexpectedRequire(module)
{
/******/                console.warn(
/******/                        "[HMR] unexpected require(" + module.id + ") to disposed
```

```
module"
/******/ 			);
/******/ 		};
/******/
/******/ 		for (var moduleId in currentUpdate) {
/******/ 			if (__webpack_require__.o(currentUpdate, moduleId)) {
/******/ 				var newModuleFactory = currentUpdate[moduleId];
/******/ 				var result = newModuleFactory
/******/ 					? getAffectedModuleEffects(moduleId)
/******/ 					: {
/******/ 						type: "disposed",
/******/ 						moduleId: moduleId
/******/ 					};
/******/ 				/** @type {Error|false} */
/******/ 				var abortError = false;
/******/ 				var doApply =
 false;
/******/ 				var doDispose = false;
/******/ 				var chainInfo = "";
/******/ 				if (result.chain) {
/******/ 					chainInfo = "\nUpdate propagation: " +
result.chain.join(" -> ");
/******/ 				}
/******/ 				switch (result.type) {
/******/ 					case "self-declined":
/******/ 						if (options.onDeclined)
options.onDeclined(result);
/******/ 						if (!options.ignoreDeclined)
/******/ 							abortError = new Error(
/******/ 								"Aborted because of self
decline: " +
/******/ 									result.moduleId +
/******/ 									chainInfo
/******/ 							);
/******/ 						break;
/******/ 					case "declined":
/******/ 						if (options.onDeclined)
options.onDeclined(result);
/******/ 						if (!options.ignoreDeclined)
/******/ 							abortError = new Error(
/******/ 								"Aborted because of declined
dependency: " +
/******/ 									result.moduleId +
/******/ 									" in " +
/******/ 									result.parentId +
/******/ 									chainInfo
/******/ 							);
/******/ 						break;
/******/ 					case "unaccepted":
```

```
/******/ 				if (options.onUnaccepted)
options.onUnaccepted(result);
/******/ 				if (!options.ignoreUnaccepted)
/******/ 					abortError = new Error(
/******/ 						"Aborted because " +
moduleId + " is not accepted" + chainInfo
/******/ 					);
/******/ 				break;
/******/ 			case "accepted":
/******/ 				if (options.onAccepted)
options.onAccepted(result);
/******/ 				doApply = true;
/******/ 				break;
/******/ 			case "disposed":
/******/ 				if (options.onDisposed)
options.onDisposed(result);
/******/ 				doDispose = true;
/******/ 				break;
/******/ 			default:
/******/ 				throw new Error("Unexception type " +
result.type);
/******/ 		}
/******/ 		if (abortError) {
/******/ 			return {
/******/ 				error: abortError
/******/ 			};
/******/ 		}
/******/ 		if (doApply) {
/******/ 			appliedUpdate[moduleId] = newModuleFactory;
/******/ 			addAllToSet(outdatedModules,
result.outdatedModules);
/******/ 			for (moduleId in result.outdatedDependencies) {
/******/ 				if
(__webpack_require__.o(result.outdatedDependencies, moduleId)) {
/******/ 					if (!
outdatedDependencies[moduleId])
/******/
	outdatedDependencies[moduleId] = [];
/******/ 					addAllToSet(
/******/
	outdatedDependencies[moduleId],
/******/
	result.outdatedDependencies[moduleId]
/******/ 					);
/******/ 				}
/******/ 			}
/******/ 		}
/******/ 		if (doDispose) {
/******/ 			addAllToSet(outdatedModules, [result.moduleId]);
```

```
/******/ 					appliedUpdate[moduleId] =
warnUnexpectedRequire;
/******/ 				}
/******/ 			}
/******/ 		}
/******/ 		currentUpdate = undefined;
/******/
/******/ 		// Store self accepted outdated modules to require them later by the
module system
/******/ 		var outdatedSelfAcceptedModules = [];
/******/ 		for (var j = 0; j < outdatedModules.length; j++) {
/******/ 			var outdatedModuleId = outdatedModules[j];
/******/ 			var module = __webpack_require__.c[outdatedModuleId];
/******/ 			if (
/******/ 				module &&
/******/ 				(module.hot._selfAccepted || module.hot._main) &&
/******/ 				// removed self-accepted modules should not be required
/******/ 				appliedUpdate[outdatedModuleId] !==
warnUnexpectedRequire &&
/******/ 				// when called invalidate self-accepting is not possible
/******/ 				!module.hot._selfInvalidated
/******/ 			) {
/******/ 				outdatedSelfAcceptedModules.push({
/******/ 					module: outdatedModuleId,
/******/ 					require: module.hot._requireSelf,
/******/ 					errorHandler: module.hot._selfAccepted
/******/ 				});
/******/ 			}
/******/ 		}
/******/
/******/ 		var moduleOutdatedDependencies;
/******/
/******/ 		return {
/******/ 			dispose: function () {
/******/ 				currentUpdateRemovedChunks.forEach(function
(chunkId) {
/******/ 					delete installedChunks[chunkId];
/******/ 				});
/******/ 				currentUpdateRemovedChunks = undefined;
/******/
/******/ 				var idx;
/******/ 				var queue = outdatedModules.slice();
/******/ 				while (queue.length > 0) {
/******/ 					var moduleId = queue.pop();
/******/ 					var module = __webpack_require__.c[moduleId];
/******/ 					if (!module) continue;
/******/
/******/ 					var data = {};
/******/
```

```
/******/
/******/
module.hot._disposeHandlers;
/******/
/******/
/******/
/******/
/******/
/******/
module)
/******/
/******/
/******/
/******/
/******/
/******/
handler
/******/
/******/
/******/
/******/
/******/
__webpack_require__.c[module.children[j]];
/******/
/******/
/******/
/******/
/******/
/******/
/******/
/******/
/******/
/******/
/******/
outdatedModuleId)) {
/******/
__webpack_require__.c[outdatedModuleId];
/******/
/******/
/******/
        outdatedDependencies[outdatedModuleId];
/******/
moduleOutdatedDependencies.length; j++) {
/******/
moduleOutdatedDependencies[j];
/******/
module.children.indexOf(dependency);
/******/
                // Call dispose handlers
                var disposeHandlers =

                for (j = 0; j < disposeHandlers.length; j++) {
                        disposeHandlers[j].call(null, data);
                }
                __webpack_require__.hmrD[moduleId] = data;

                // disable module (this disables requires from this

                module.hot.active = false;

                // remove module from cache
                delete __webpack_require__.c[moduleId];

                // when disposing there is no need to call dispose

                delete outdatedDependencies[moduleId];

                // remove "parents" references from all children
                for (j = 0; j < module.children.length; j++) {
                        var child =

                        if (!child) continue;
                        idx = child.parents.indexOf(moduleId);
                        if (idx >= 0) {
                                child.parents.splice(idx, 1);
                        }
                }
        }

        // remove outdated dependency from module children
        var dependency;
        for (var outdatedModuleId in outdatedDependencies) {
                if (__webpack_require__.o(outdatedDependencies,

                        module =

                        if (module) {
                                moduleOutdatedDependencies =


                                for (j = 0; j <

                                        dependency =

                                        idx =

                                        if (idx >= 0)
```

```
module.children.splice(idx, 1);
/******/                                                    }
/******/                                                }
/******/                                            }
/******/                                        }
/******/                                    },
/******/                                    apply: function (reportError) {
/******/                                        var acceptPromises = [];
/******/                                        // insert new code
/******/                                        for (var updateModuleId in appliedUpdate) {
/******/                                            if (__webpack_require__.o(appliedUpdate,
updateModuleId)) {
/******/                                                __webpack_require__.m[updateModuleId]
= appliedUpdate[updateModuleId];
/******/                                            }
/******/                                        }
/******/
/******/                                        // run new runtime modules
/******/                                        for (var i = 0; i < currentUpdateRuntime.length; i++) {
/******/                                            currentUpdateRuntime[i](__webpack_require__);
/******/                                        }
/******/
/******/                                        // call accept handlers
/******/                                        for (var outdatedModuleId in outdatedDependencies) {
/******/                                            if (__webpack_require__.o(outdatedDependencies,
outdatedModuleId)) {
/******/                                                var module =
__webpack_require__.c[outdatedModuleId];
/******/                                                if (module) {
/******/                                                    moduleOutdatedDependencies =
/******/
        outdatedDependencies[outdatedModuleId];
/******/                                                    var callbacks = [];
/******/                                                    var errorHandlers = [];
/******/                                                    var dependenciesForCallbacks = [];
/******/                                                    for (var j = 0; j <
moduleOutdatedDependencies.length; j++) {
/******/                                                        var dependency =
moduleOutdatedDependencies[j];
/******/                                                        var acceptCallback =
/******/
        module.hot._acceptedDependencies[dependency];
/******/                                                        var errorHandler =
/******/
        module.hot._acceptedErrorHandlers[dependency];
/******/                                                        if (acceptCallback) {
/******/                                                            if
(callbacks.indexOf(acceptCallback) !== -1) continue;
/******/
```

```
        callbacks.push(acceptCallback);
/******/
        errorHandlers.push(errorHandler);
/******/
        dependenciesForCallbacks.push(dependency);
/******/                                                          }
/******/                                                      }
/******/                                                      for (var k = 0; k < callbacks.length;
k++) {
/******/                                                          var result;
/******/                                                          try {
/******/                                                              result =
callbacks[k].call(null, moduleOutdatedDependencies);
/******/                                                          } catch (err) {
/******/                                                              if (typeof
errorHandlers[k] === "function") {
/******/                                                                  try {
/******/
        errorHandlers[k](err, {
/******/
        moduleId: outdatedModuleId,
/******/
        dependencyId: dependenciesForCallbacks[k]
/******/                                                                  });
/******/                                                              } catch (err2) {
/******/                                                                  if
(options.onErrored) {
/******/
        options.onErrored({
/******/
        type: "accept-error-handler-errored",
/******/
        moduleId: outdatedModuleId,
/******/
        dependencyId: dependenciesForCallbacks[k],
/******/
        error: err2,
/******/
        originalError: err
/******/
        });
/******/                                                                  }
/******/                                                                  if (!
options.ignoreErrored) {
/******/
        reportError(err2);
/******/
        reportError(err);
/******/                                                              }
```

```
/******/                                                                                                  }
/******/                                                                                          } else {
/******/                                                                                                  if
(options.onErrored) {
/******/
        options.onErrored({
/******/
        type: "accept-errored",
/******/
        moduleId: outdatedModuleId,
/******/
        dependencyId: dependenciesForCallbacks[k],
/******/
        error: err
/******/                                                                                                          });
/******/                                                                                                  }
/******/                                                                                                  if (!
options.ignoreErrored) {
/******/
        reportError(err);
/******/                                                                                                  }
/******/                                                                                          }
/******/                                                                                  }
/******/                                                                                  if (result && typeof
result.then === "function") {
/******/
        acceptPromises.push(result);
/******/                                                                                  }
/******/                                                                          }
/******/                                                                  }
/******/                                                          }
/******/                                                  }
/******/                                                  var
 onAccepted = function () {
/******/                                                          // Load self accepted modules
/******/                                                          for (var o = 0; o <
outdatedSelfAcceptedModules.length; o++) {
/******/                                                                  var item =
outdatedSelfAcceptedModules[o];
/******/                                                                  var moduleId = item.module;
/******/                                                                  try {
/******/                                                                          item.require(moduleId);
/******/                                                                  } catch (err) {
/******/                                                                          if (typeof item.errorHandler ===
"function") {
/******/                                                                                  try {
/******/                                                                                          item.errorHandler(err,
{
```

```
/******/ 
moduleId,
/******/ 
__webpack_require__.c[moduleId]
/******/ 
/******/ 
/******/ 
{
/******/ 
	options.onErrored({
/******/ 
"self-accept-error-handler-errored",
/******/ 
	moduleId: moduleId,
/******/ 
err1,
/******/ 
	originalError: err
/******/ 
/******/ 
/******/ 
options.ignoreErrored) {
/******/ 
	reportError(err1);
/******/ 
	reportError(err);
/******/ 
/******/ 
/******/ 
```

```
/******/                                                 return outdatedModules;
/******/                                         });
/******/                         }
/******/                 };
/******/         }
/******/         __webpack_require__.hmrI.jsonp = function (moduleId, applyHandlers) {
/******/                 if (!currentUpdate) {
/******/                         currentUpdate = {};
/******/                         currentUpdateRuntime = [];
/******/                         currentUpdateRemovedChunks = [];
/******/                         applyHandlers.push(applyHandler);
/******/                 }
/******/                 if (!__webpack_require__.o(currentUpdate, moduleId)) {
/******/                         currentUpdate[moduleId] = __webpack_require__.m[moduleId];
/******/                 }
/******/         };
/******/         __webpack_require__.hmrC.jsonp = function (
/******/                 chunkIds,
/******/                 removedChunks,
/******/                 removedModules,
/******/                 promises,
/******/                 applyHandlers,
/******/                 updatedModulesList
/******/         ) {
/******/                 applyHandlers.push(applyHandler);
/******/                 currentUpdateChunks = {};
/******/                 currentUpdateRemovedChunks = removedChunks;
/******/                 currentUpdate = removedModules.reduce(function (obj, key) {
/******/                         obj[key] = false;
/******/                         return obj;
/******/                 }, {});
/******/                 currentUpdateRuntime = [];
/******/                 chunkIds.forEach(function (chunkId) {
/******/                         if (
/******/                                 __webpack_require__.o(installedChunks, chunkId) &&
/******/                                 installedChunks[chunkId] !== undefined
/******/                         ) {
/******/                                 promises.push(loadUpdateChunk(chunkId,
updatedModulesList));
/******/                                 currentUpdateChunks[chunkId] = true;
/******/                         } else {
/******/                                 currentUpdateChunks[chunkId] = false;
/******/                         }
/******/                 });
/******/                 if (__webpack_require__.f) {
/******/                         __webpack_require__.f.jsonpHmr = function (chunkId, promises)
{
/******/                                 if (
/******/                                         currentUpdateChunks &&
```

```
/******/ 				__webpack_require__.o(currentUpdateChunks, chunkId) &&
/******/ 				!currentUpdateChunks[chunkId]
/******/ 			) {
/******/ 				promises.push(loadUpdateChunk(chunkId));
/******/ 				currentUpdateChunks[chunkId] = true;
/******/ 			}
/******/ 		};
/******/ 	}
/******/ };
/******/
/******/ __webpack_require__.hmrM = () => {
/******/ 	if (typeof fetch === "undefined") throw new Error("No browser support: need fetch API");
/******/ 	return fetch(__webpack_require__.p + __webpack_require__.hmrF()).then((response) => {
/******/ 		if(response.status === 404) return; // no update available
/******/ 		if(!response.ok) throw new Error("Failed to fetch update manifest " + response.statusText);
/******/ 		return response.json();
/******/ 	});
/******/ };
/******/
/******/ // no on chunks loaded
/******/
/******/ // no jsonp function
/******/ })();
/******/
/******/ /* webpack/runtime/nonce */
/******/ (() => {
/******/ 	__webpack_require__.nc = undefined;
/******/ })();
/******/
/************************************************************************/
/******/
/******/ // module cache are used so entry inlining is disabled
/******/ // startup
/******/ // Load entry module and return exports
/******/ __webpack_require__("./node_modules/@pmmmwh/react-refresh-webpack-plugin/client/ReactRefreshEntry.js");
/******/ __webpack_require__("./node_modules/webpack-dev-server/client/index.js?protocol=ws%3A&hostname=0.0.0.0&port=443&pathname=%2Fws&logging=none&overlay=%7B%22errors%22%3Atrue%2C%22warnings%22%3Afalse%7D&reconnect=10&hot=true&live-reload=true");
/******/ __webpack_require__("./node_modules/webpack/hot/dev-server.js");
/******/ var __webpack_exports__ = __webpack_require__("./src/index.js");
/******/
/******/ })()
;
```

```
//# sourceMappingURL=bundle.js.map
```