

```

# include < stdio .h >
# include < stdlib .h >
# include < string .h >
# include < unistd .h >
# include < arpa / inet .h >
# define PORT 8080
# define BUFFER_SIZE 1024
int main () {
    int sock = 0;
    struct sockaddr_in serv_addr ;
    char reg_no [ BUFFER_SIZE ];
    char buffer [ BUFFER_SIZE ];
    sock = socket(AF_INET, SOCK_STREAM, 0);

    if (sock < 0) {
        printf("Socket creation error\n");
        return -1;
    }
    serv_addr . sin_family = AF_INET ;
    serv_addr . sin_port = htons ( PORT ) ;
    inet_pton ( AF_INET , " 127.0.0.1 " , & serv_addr . sin_addr )
;
    inet_pton(AF_INET, "127.0.0.1", &serv_addr.sin_addr);

    if (connect(sock, (struct sockaddr *)&serv_addr, sizeof(serv_addr)) < 0) {

```

```

    printf("Connection Failed\n");
    return -1;
}

while (1) {
    printf ("\nEnter _ Registration _ Number _ (or _ type _ '
    bye _ to _ exit _):_");
    fgets ( reg_no , BUFFER_SIZE , stdin );
    reg_no [ strchr ( reg_no , "\n" ) ] = 0;
    send ( sock , reg_no , strlen ( reg_no ) , 0 );
    // Exit condition
    if ( strcmp ( reg_no , "bye " ) == 0 ) {
        printf ( " Connection _ closed .\n" );
        break ;
    }
    memset ( buffer , 0 , BUFFER_SIZE );
    read ( sock , buffer , BUFFER_SIZE );
    printf ( " Server _ Response :_ %s\n" , buffer );
}
close ( sock );
return 0;
}

```