

# Announcements



---

- The makeup date for Midterm 1 is tomorrow (October 9) from 10am-11:30am in Hayden Hall room 358
  - You are allowed to bring a cheat sheet
  - 1 page printer paper with handwritten notes (writing on both sides is OK)
- Upcoming:
  - HW4 – Sudoku Solver and Games – is due tonight
  - Extra Credit assignment 1 has been released, it is due on Thursday
  - There are several additional extra credit assignments, which will be due on Thursdays
  - HW5 – Markov Decision Processes is due in 2 weeks on Tuesday Oct 22
- You can check out an R2D2 today before lecture or after lecture
- My office hours are today from 3-4pm in 3401 Walnut room 463C


# MDP Wrap-up + Reinforcement Learning

Sutton and Barto, Chapter 6.1, 6.2, 6.5  
AIMA Chapter 21

Slides courtesy of Dan Klein and Pieter Abbeel  
University of California, Berkeley




# Markov Decision Processes -wrapup



Slides courtesy of Dan Klein and Pieter Abbeel --- University of California, Berkeley

[These slides were created by Dan Klein and Pieter Abbeel for CS188 Intro to AI at UC Berkeley. All CS188 materials are available at <http://ai.berkeley.edu>.]

# Review: The Bellman Equations



How to be optimal:

Step 1: Take correct first action

Step 2: Keep being optimal


# Review: The Bellman Equations

- Definition of “optimal utility” via expectimax recurrence gives a simple one-step lookahead relationship amongst optimal utility values

$$V^*(s) = \max_a Q^*(s, a)$$

$$Q^*(s, a) = \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^*(s')]$$

$$V^*(s) = \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^*(s')]$$




- These are the Bellman equations, and they characterize optimal values in a way we'll use over and over

# Review: Value Iteration

- Start with  $V_0(s) = 0$ : no time steps left means an expected reward sum of zero
- Given vector of  $V_k(s)$  values, do one ply of expectimax from each state:


$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$

- Repeat until convergence
- Complexity of each iteration:  $O(S^2A)$
- **Theorem: will converge to unique optimal values**
  - Basic idea: approximations get refined towards optimal values
  - Policy may converge long before values do



# Review: Value Iteration

$V_2$	3.5	2.5	0
$V_1$	2	1	0
$V_0$	0	0	0




(Here we assume no discount)

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$


# Policy Methods

---




# Policy Evaluation

---




# Fixed Policies

Do the optimal action



Do what  $\pi$  says to do




- Expectimax trees max over all actions to compute the optimal values
- If we fixed some policy  $\pi(s)$ , then the tree would be simpler – only one action per state
  - ... though the tree's value would depend on which policy we fixed

# Utilities for a Fixed Policy


- Another basic operation: compute the utility of a state  $s$  under a fixed (generally non-optimal) policy
- Define the utility of a state  $s$ , under a fixed policy  $\pi$ :  
 $V^\pi(s)$  = expected total discounted rewards starting in  $s$  and following  $\pi$
- Recursive relation (one-step look-ahead / Bellman equation):

$$V^\pi(s) = \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V^\pi(s')]$$




# Example: Policy Evaluation

Always Go Right



Always Go Forward



# Example: Policy Evaluation

Always Go Right



Always Go Forward




# Policy Evaluation

- How do we calculate the V's for a fixed policy  $\pi$ ?
- Idea 1: Turn recursive Bellman equations into updates (like value iteration)


$$V_0^\pi(s) = 0$$

$$V_{k+1}^\pi(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V_k^\pi(s')]$$



- Efficiency:  $O(S^2)$  per iteration
- Idea 2: Without the maxes, the Bellman equations are just a linear system
  - Solve with Matlab (or your favorite linear system solver)

# Policy Extraction



# Computing Actions from Values

- Let's imagine we have the optimal values  $V^*(s)$
- How should we act?
  - It's not obvious!
- We need to do a mini-expectimax (one step)



$$\pi^*(s) = \arg \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^*(s')]$$

- This is called **policy extraction**, since it gets the policy implied by the values


# Computing Actions from Q-Values

- Let's imagine we have the optimal q-values:

- How should we act?

- Completely trivial to decide!


$$\pi^*(s) = \arg \max_a Q^*(s, a)$$



- Important lesson: actions are easier to select from q-values than values!

# Policy Iteration

---




# Problems with Value Iteration


- Value iteration repeats the Bellman updates:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$


- Problem 1: It's slow –  $O(S^2A)$  per iteration
- Problem 2: The “max” at each state rarely changes
- Problem 3: The policy often converges long before the values



$k=0$



$k=1$



$k=2$




**k=3**



# k=4



**k=5**



**VALUES AFTER 5 ITERATIONS**

Noise = 0.2  
Discount = 0.9  
Living reward = 0

# k=6



**k=7**



**k=8**



k=9



# k=10




Noise = 0.2  
Discount = 0.9  
Living reward = 0

**k=11**



**k=12**



**VALUES AFTER 12 ITERATIONS**

Noise = 0.2  
Discount = 0.9  
Living reward = 0

**k=100**




# Problems with Value Iteration

- Value iteration repeats the Bellman updates:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$

- Problem 1: It's slow –  $O(S^2A)$  per iteration
- Problem 2: The “max” at each state rarely changes
- Problem 3: The policy often converges long before the values



# Policy Iteration

---

- Alternative approach for optimal values:
  - Step 1: Policy evaluation: calculate utilities for some fixed policy (not optimal utilities!) until convergence
  - Step 2: Policy improvement: update policy using one-step look-ahead with resulting converged (but not optimal!) utilities as future values
  - Repeat steps until policy converges
- This is policy iteration
  - It's still optimal!
  - Can converge (much) faster under some conditions

# Policy Iteration

---

- Evaluation: For fixed current policy  $\pi$ , find values with policy evaluation:
  - Iterate until values converge:

$$V_{k+1}^{\pi_i}(s) \leftarrow \sum_{s'} T(s, \pi_i(s), s') [R(s, \pi_i(s), s') + \gamma V_k^{\pi_i}(s')]$$

- Improvement: For fixed values, get a better policy using policy extraction
  - One-step look-ahead:

$$\pi_{i+1}(s) = \arg \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V^{\pi_i}(s')]$$

# Comparison

---

- Both value iteration and policy iteration compute the same thing (all optimal values)
- In value iteration:
  - Every iteration updates both the values and (implicitly) the policy
  - We don't track the policy, but taking the max over actions implicitly recomputes it
- In policy iteration:
  - We do several passes that update utilities with fixed policy (each pass is fast because we consider only one action, not all of them)
  - After the policy is evaluated, a new policy is chosen (slow like a value iteration pass)
  - The new policy will be better (or we're done)
- Both are dynamic programs for solving MDPs



# Summary: MDP Algorithms

---

- So you want to...
  - Compute optimal values: use value iteration or policy iteration
  - Compute values for a particular policy: use policy evaluation
  - Turn your values into a policy: use policy extraction (one-step lookahead)
- These all look the same!
  - They basically are – they are all variations of Bellman updates
  - They all use one-step lookahead expectimax fragments
  - They differ only in whether we plug in a fixed policy or max over actions


# Double Bandits

---



# Double-Bandit MDP

- Actions: *Blue, Red*
- States: *Win, Lose*




# Offline Planning

- Solving MDPs is offline planning

- You determine all quantities through computation
- You need to know the details of the MDP
- You do not actually play the game!


*No discount  
100 time steps  
Both states have  
the same value*

	Value
Play Red	150
Play Blue	100



# Let's Play!

---




\$2 \$2 \$0 \$2 \$2

\$2 \$2 \$0 \$0 \$0


# Online Planning

- Rules changed! Red's win chance is different.



# Let's Play!

---



\$0	\$0	\$0	\$2	\$0
\$2	\$0	\$0	\$0	\$0

# What Just Happened?



- That wasn't planning, it was learning!
  - Specifically, reinforcement learning
  - There was an MDP, but you couldn't solve it with just computation
  - You needed to actually act to figure it out
- Important ideas in reinforcement learning that came up
  - **Exploration:** you have to try unknown actions to get information
  - **Exploitation:** eventually, you have to use what you know
  - **Regret:** even if you learn intelligently, you make mistakes
  - **Sampling:** because of chance, you have to try things repeatedly
  - **Difficulty:** learning can be much harder than solving a known MDP




# Reinforcement Learning

Read AIMA 21

Also read Sutton and Barto Chapter  
6.1, 6.2 and 6.5 (see link on course  
web site)



# Reinforcement Learning



- Basic idea:
  - Receive feedback in the form of **rewards**
  - Agent's utility is defined by the reward function
  - Must (learn to) act so as to **maximize expected rewards**
  - All learning is based on observed samples of outcomes!

# Reinforcement Learning

- Still assume a Markov decision process (MDP):

- A set of states  $s \in S$
- A set of actions (per state)  $A$
- A model  $T(s,a,s')$
- A reward function  $R(s,a,s')$

- Still looking for a policy  $\pi(s)$


- New twist: don't know  $T$  or  $R$

- I.e. we don't know which states are good or what the actions do
- Must actually try actions and states out to learn



# Offline (MDPs) vs. Online (RL)

---




Offline Solution



Online Learning


# Model-Based Learning

---




# Model-Based Learning

- Model-Based Idea:
  - Learn an approximate model based on experiences
  - Solve for values as if the learned model were correct
- Step 1: Learn empirical MDP model
  - Count outcomes  $s'$  for each  $s, a$
  - Normalize to give an estimate of  $\hat{T}(s, a, s')$
  - Discover each  $\hat{R}(s, a, s')$  when we experience  $(s, a, s')$
- Step 2: Solve the learned MDP
  - For example, use value iteration, as before



# Example: Model-Based Learning

Input Policy  $\pi$



Assume:  $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 2

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 3

E, north, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 4

E, north, C, -1  
C, east, A, -1  
A, exit, x, -10

Learned Model

$\hat{T}(s, a, s')$

$T(B, \text{east}, C) = 1.00$   
 $T(C, \text{east}, D) = 0.75$   
 $T(C, \text{east}, A) = 0.25$   
...

$\hat{R}(s, a, s')$

$R(B, \text{east}, C) = -1$   
 $R(C, \text{east}, D) = -1$   
 $R(D, \text{exit}, x) = +10$   
...

# Example: Expected Age

Goal: Compute expected age of CIS 421/521 students

Known  $P(A)$

$$E[A] = \sum_a P(a) \cdot a = 0.01 \times 42 + \dots$$

Without  $P(A)$ , instead collect samples  $[a_1, a_2, \dots a_N]$

Unknown  $P(A)$ : “Model Based”

Why does this work? Because eventually you learn the right model.

$$\hat{P}(a) = \frac{\text{num}(a)}{N}$$

$$E[A] \approx \sum_a \hat{P}(a) \cdot a$$


Unknown  $P(A)$ : “Model Free”

$$E[A] \approx \frac{1}{N} \sum_i a_i$$

Why does this work? Because samples appear with the right frequencies.


# Model-Free Learning

---



# Passive Reinforcement Learning

---




# Passive Reinforcement Learning

- Simplified task: policy evaluation

- Input: a fixed policy  $\pi(s)$
- You don't know the transitions  $T(s,a,s')$
- You don't know the rewards  $R(s,a,s')$
- Goal: learn the state values

- In this case:


- Learner is “along for the ride”
- No choice about what actions to take
- Just execute the policy and learn from experience
- This is NOT offline planning! You actually take actions in the world.



# Direct Evaluation


---

- Goal: Compute values for each state under  $\pi$
- Idea: Average together observed sample values
  - Act according to  $\pi$
  - Every time you visit a state, write down what the sum of discounted rewards turned out to be
  - Average those samples
- This is called direct evaluation



# Example: Direct Evaluation

Input Policy  $\pi$



Assume:  $\gamma = 1$

Observed Episodes (Training)

Episode 1

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 2

B, east, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 3

E, north, C, -1  
C, east, D, -1  
D, exit, x, +10

Episode 4

E, north, C, -1  
C, east, A, -1  
A, exit, x, -10

Output Values

	-10	
A	+4	+10
B	+8	
C		D
E	-2	

# Problems with Direct Evaluation


- What's good about direct evaluation?

- It's easy to understand
- It doesn't require any knowledge of T, R
- It eventually computes the correct average values, using just sample transitions

- What bad about it?

- It wastes information about state connections
- Each state must be learned separately
- So, it takes a long time to learn

## Output Values




*If B and E both go to C under this policy, how can their values be different?*

# Why Not Use Policy Evaluation?

- Simplified Bellman updates calculate  $V$  for a fixed policy:
  - Each round, replace  $V$  with a one-step-look-ahead layer over  $V$

$$V_0^\pi(s) = 0$$

$$V_{k+1}^\pi(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V_k^\pi(s')]$$



- This approach fully exploited the connections between the states
- Unfortunately, we need  $T$  and  $R$  to do it!
- Key question: how can we do this update to  $V$  without knowing  $T$  and  $R$ ?
  - In other words, how to we take a weighted average without knowing the weights?

# Sample-Based Policy Evaluation?

- We want to improve our estimate of  $V$  by computing these averages:

$$V_{k+1}^{\pi}(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V_k^{\pi}(s')]$$

- Idea: Take samples of outcomes  $s'$  (by doing the action!) and average


$$sample_1 = R(s, \pi(s), s'_1) + \gamma V_k^{\pi}(s'_1)$$

$$sample_2 = R(s, \pi(s), s'_2) + \gamma V_k^{\pi}(s'_2)$$

...


$$sample_n = R(s, \pi(s), s'_n) + \gamma V_k^{\pi}(s'_n)$$

$$V_{k+1}^{\pi}(s) \leftarrow \frac{1}{n} \sum_i sample_i$$




# Temporal Difference Learning

---



# Temporal Difference Learning

- Big idea: learn from every experience!
  - Update  $V(s)$  each time we experience a transition  $(s, a, s', r)$
  - Likely outcomes  $s'$  will contribute updates more often
- Temporal difference learning of values
  - Policy still fixed, still doing evaluation!
  - Move values toward value of whatever successor occurs: running average



Sample of  $V(s)$ :      $sample = R(s, \pi(s), s') + \gamma V^\pi(s')$

Update to  $V(s)$ :      $V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + (\alpha)sample$

Same update:      $V^\pi(s) \leftarrow V^\pi(s) + \alpha(sample - V^\pi(s))$

# Exponential Moving Average

---

- Exponential moving average

- The running interpolation update:  $\bar{x}_n = (1 - \alpha) \cdot \bar{x}_{n-1} + \alpha \cdot x_n$
- Makes recent samples more important:

$$\bar{x}_n = \frac{x_n + (1 - \alpha) \cdot x_{n-1} + (1 - \alpha)^2 \cdot x_{n-2} + \dots}{1 + (1 - \alpha) + (1 - \alpha)^2 + \dots}$$

- Forgets about the past (distant past values were wrong anyway)
- Decreasing learning rate (alpha) can give converging averages

# Example: Temporal Difference Learning

States

	A	
B	C	D
	E	

Observed Transitions

B, east, C, -2

	0	
0	0	8
	0	

C, east, D, -2

	0	
-1	0	8
	0	

	0	
-1	3	8
	0	

Assume:  $\gamma = 1, \alpha = 1/2$

$$V^\pi(s) \leftarrow (1 - \alpha)V^\pi(s) + \alpha [R(s, \pi(s), s') + \gamma V^\pi(s')]$$


# Problems with TD Value Learning

- TD value learning is a model-free way to do policy evaluation, mimicking Bellman updates with running sample averages
- However, if we want to turn values into a (new) policy, we're sunk:

$$\pi(s) = \arg \max_a Q(s, a)$$


$$Q(s, a) = \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V(s')]$$

- Idea: learn Q-values, not values
- Makes action selection model-free too!




# Active Reinforcement Learning

---



# Active Reinforcement Learning

- Full reinforcement learning: optimal policies (like value iteration)
  - You don't know the transitions  $T(s,a,s')$
  - You don't know the rewards  $R(s,a,s')$
  - You choose the actions now
  - Goal: learn the optimal policy / values
- In this case:
  - Learner makes choices!
  - Fundamental tradeoff: exploration vs. exploitation
  - This is NOT offline planning! You actually take actions in the world and find out what happens...



# Detour: Q-Value Iteration

- Value iteration: find successive (depth-limited) values

- Start with  $V_0(s) = 0$ , which we know is right
- Given  $V_k$ , calculate the depth  $k+1$  values for all states:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma V_k(s')]$$

- But Q-values are more useful, so compute them instead

- Start with  $Q_0(s, a) = 0$ , which we know is right
- Given  $Q_k$ , calculate the depth  $k+1$  q-values for all q-states:

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') [R(s, a, s') + \gamma \max_{a'} Q_k(s', a')]$$

# Q-Learning

- Q-Learning: sample-based Q-value iteration

$$Q_{k+1}(s, a) \leftarrow \sum_{s'} T(s, a, s') \left[ R(s, a, s') + \gamma \max_{a'} Q_k(s', a') \right]$$


- Learn Q(s,a) values as you go

- Receive a sample  $(s, a, s', r)$
- Consider your old estimate:  $Q(s, a)$
- Consider your new sample estimate:

$$\text{sample} = R(s, a, s') + \gamma \max_{a'} Q(s', a')$$

- Incorporate the new estimate into a running average:

$$Q(s, a) \leftarrow (1 - \alpha)Q(s, a) + (\alpha) [\text{sample}]$$



# Video of Demo Q-Learning -- Gridworld

---



# Q-Learning Properties

- Amazing result: Q-learning converges to optimal policy -- even if you're acting suboptimally!
- This is called **off-policy learning**
- Caveats:
  - You have to explore enough
  - You have to eventually make the learning rate small enough
  - ... but not decrease it too quickly
  - Basically, in the limit, it doesn't matter how you select actions (!)

