KLEYM / QUALITY ASSURANCE
Comprehensive regression plan v2

26 October 2026 | Desktop + Android | Testnet and Mainnet preparation

373 detailed cases | 24 pages | 121 API methods | 296 static control declarations

PLAN + TRACEABLE CHECKLIST. All catalog statuses start Not Run. Executed evidence is reported separately.

Candidate: b842fe3ac451dbfd4e563b3478c5951944c8dbb5

Purpose and build boundary

Comprehensive regression plan for candidate b842fe3ac451dbfd4e563b3478c5951944c8dbb5. Kleym source is available. 24 page routes, 96 API files / 121 method handlers and the static control register are inventoried. A source declaration is not proof of a working button; conditional states and every data-bound row still require execution. No finite test plan proves all possible inputs. This plan covers observable journeys, failures, boundaries, roles and lifecycle transitions; residual risks remain explicit. Older v1 artifacts are preserved.

Current environments and entry gates

G0: freeze SHA/tree/lockfile and deployed web/worker/landing identities. G1: isolated populated PostgreSQL and Redis with resettable disposable users, roles, keys, provider fixtures and approved test budgets. G2: Testnet passphrase Test SDF Network ; September 2015, official USDC issuer GBBD47IF6LWK7P7MDEVSCWR7DPUWV3NY3DTQEVFL4NAT4AQH3ZLLFLA5 and fresh Horizon snapshots before every write. G3: team app https://kleym-testnet.up.railway.app and static home https://kleym-home-testnet.up.railway.app. Mainnet is disabled and has no approved separate URL. Current credentials are injected privately, never copied into the plan.

Platform matrix and Android Studio

Desktop: Brave/Chrome with Freighter extension; Firefox/WebKit compatibility where supported. Android: dedicated Android Studio AVD kleym-qa-api36 using existing API36.1 Google Play x86_64 image, Pixel6 geometry1080x2400/420dpi,3GiB RAM,2cores; data on D:/Android-AVDs. Emulator is actual Android, not viewport emulation, but does not qualify OEM lifecycle, real biometrics, Play Integrity or every physical device. Physical Freighter v1.26.29 desktop/Android EMAIL success is prior evidence on merge623e2bc, not automatically a full v2 pass. Lantern is deferred until an approved curated build includes Kleym.

Fixtures and exact accounting

Use two disposable organisations and OWNER/APPROVER/OPERATOR/VIEWER plus system-admin identities; never alter the real operator role/password. Test funded and literal-zero-XLM sponsored senders; recipient absent/existing-no-trustline/existing-trustline. Assets: official TestnetUSDC andXLM; custom issuer only for freeze/revoke/conversion faults. Main tutorial:3links x1USDC, desktop claim, Android claim and unused expiry reclaim. Final owner net debit2; recipients +1each; reclaim+1; exact fees and reserve deltas from Horizon. Custom prizes20,15,10,5,5=55 are fixture-only until approved balance budget exists. Pure int64 extremes never go on-chain.

Execution sequence

1. Source/runtime identity, CI and security prerequisites. 2. Static homepage/login, all role-based page/control smoke on desktop and emulator. 3. Invalid input/CSV/policy matrices using isolated fixtures. 4. Real DB/Redis concurrency, crash recovery and queues. 5. Deliberate wallet Testnet creation/export/funding/claim/reclaim matrix. 6. State/compatibility/a11y/performance and cold-recipient UAT. 7. Backup/restore, monitoring and release rehearsal. Re-run affected regressions after any defect patch and freeze the new candidate; never silently combine results from different builds.

Runbook: guided three-link campaign

Login on approved Testnet host. Select intended sender or manually paste its G-address for balance lookup; manual entry does not authorize signing. Create3links/1USDC, labels Desktop/Android/Unused, choose appropriate expiry and policy. Review count,total,issuer,deadline,reserves,fees. Generate keys privately, save phrase and current secrets export, approve one intended funding batch. Wait for ledger confirmation. Claim desktop link to controlled receiver, Android link in emulator/Freighter if installed and independently snapshot balances. Leave third unused; after actual expiry approve sender reclaim and reconcile. Do not share secrets/export in evidence. For EMAIL upload owned-inbox assignment before review; use new OTP only. For WALLET enforce the assigned owner. Do not reuse settled links to obtain screenshots.

Evidence and status rules

Catalog rows begin Not Run; expected results are written before execution. Execution records need caseID,candidate,platform/tester/UTC,input-fixture,actual,status,evidence and defect. Statuses: Not Run,Ongoing,Passed,Failed,Blocked,For Re-test,N/A. Blocked needs a named missing prerequisite and cause class (tester, infrastructure, dependency, product). Not Run is not a failure or a pass. N/A needs explicit scope reason. CI proof qualifies only what the named scripts actually executed. Reusing same-candidate immutable CI evidence avoids unnecessary full-suite reruns; prior SHA/device proof stays separately labelled. Store safe evidence under evidences/runs/<run>/<caseID>; sanitize screenshots, HAR and logs before retention.

Money, secrets and stop conditions

Stop on network/issuer/signer mismatch, unintended approval/broadcast, seed/phrase/bearer leakage, unexplained principal/reserve loss, double payout, false ledger-success state or candidate mismatch. Never persist private keys, OTP values, session/API tokens, private recipient lists, raw claim URLs or secret-bearing XDR dumps in test artifacts. The chain is authoritative. HTTP202 is not delivered mail, submitted is not funded, expired is not automatically refunded, and unchanged native balance does not by itself prove reserves released. Compare charged fees and live reserve obligations, retaining recipient permanent sponsorship separately.

Release gates and current gaps

All mandatory financial/authentication/recovery cases must pass with required evidence; unresolved critical/high, mandatory Blocked or Not Run prevents full sign-off. Plan completion does not enable Mainnet. Mainnet needs separate approved HTTPS deployment/credentials/queues, sponsor/treasury and incident ownership, measured restore/rollback/alert proof, sender authentication/provider tracking confirmation and explicit real-asset pilot approval. No arbitrary global campaign-USDC cap is introduced; wallet capacity, protocol precision and sponsor admission remain. Automated treasury refill is not presumed implemented. EMAIL/CODE are application gates rather than additional on-chain signer restrictions; WALLET binds the assigned owner on-chain.

Traceability and reference method

Stable original KLM-D1..D4 IDs retained; new KLM-V2 cases cover current features, each page, each API handler and every declared claim state. Controls sheet lists every static JSX declaration with source line and an explicit execution field. D1-D4 Lantern methodology is reused for independent money proof, adversarial boundaries, installed-artifact identity and cold-recipient UAT; Lantern contract addresses and its product assumptions are not copied. Automated proof, deployed smoke, physical-device proof and operational sign-off remain distinct.

Detailed cases / TER

KLM-D1-TER-001 / Equal prizes: three 1-USDC links

P1 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Create a campaign with count 3, amount 1 and a future custom expiry. Review; save export privately. Fund once after approval.
Expected	Declared total is exactly 3.0000000 USDC; three distinct public link keys; only funded links can be shared.
Proof	Review screenshot without phrase/keys; redacted CSV index/amount comparison; public registration and ledger JSON.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-TER-002 / Custom prizes: 20, 15, 10 and two default 5

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Create count 5/default 5. Set rows 1-3 to 20,15,10; leave rows 4-5 unchanged. Review, export and inspect public registration.
Expected	Row order is stable; amounts are 20,15,10,5,5; exact total 55.0000000; labels, CSV and ledger amounts match.
Proof	Review screenshot without phrase/keys; redacted CSV index/amount comparison; public registration and ledger JSON.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-TER-003 / Edit custom prizes across pages

P1 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Create 25 rows/default 5. Override row 1 and row 21. Move next/back through all pages and return to review.
Expected	Overrides persist at their original indices; no duplicate rows or lost edits; displayed total equals exact decimal sum.
Proof	Review screenshot without phrase/keys; redacted CSV index/amount comparison; public registration and ledger JSON.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-TER-004 / Shrink and expand the recipient count

P1 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Set overrides on rows 1 and 12; shrink count to 10; inspect review. Expand back to 12 and inspect again.
Expected	Only current rows affect totals. Removed overrides never silently fund additional rows; new rows use displayed default.
Proof	Review screenshot without phrase/keys; redacted CSV index/amount comparison; public registration and ledger JSON.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-TER-005 / Change default with existing overrides

P1 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Override one row, change default 5 to 7, then review and export the current list.
Expected	Explicit override is preserved; remaining rows reflect current default; review is the exact list sent for registration.
Proof	Review screenshot without phrase/keys; redacted CSV index/amount comparison; public registration and ledger JSON.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / AMT

KLM-D1-AMT-001 / Minimum positive amount

P0 | Boundary | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 0.0000001 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Accept exactly one stroop; no rounding to zero.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-AMT-002 / Zero / negative / text / exponent

P0 | Negative | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 0; -1; abc; 1e3 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Refuse each with a useful amount error; no registration or wallet request.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-AMT-003 / Eighth decimal place

P0 | Negative | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 1.12345678 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Refuse rather than round or truncate.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-AMT-004 / Maximum classic int64 amount

P0 | Boundary | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 922337203685.4775807 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Pure validation accepts the exact maximum. Do not attempt funding this boundary fixture.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-AMT-005 / Amount one stroop above int64

P0 | Negative | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 922337203685.4775808 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Pure validation rejects overflow before envelope creation.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-AMT-006 / Exact aggregate and persistence precision

P0 | Boundary | Testnet release | Not Run

Preconditions	Pure amount fixtures; isolated migrated PostgreSQL required only for DB precision assertion.
Steps / inputs	Validate 20;15;10;5;5;0.0000001 through client and API schemas; inspect exact normalized strings; attempt no chain write for extreme fixtures.
Expected	Decimal/stroop total is 55.0000001; DB round trip retains all seven decimal places.
Proof	Validator output and API error; sanitized DB round-trip record when applicable.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / EXP

KLM-D1-EXP-001 / Relative expiry buttons

P1 | Boundary | Testnet release | Not Run

Preconditions	Isolated clock fixtures first; live stale-review case uses approved small Testnet campaign.
Steps / inputs	Select 1 hour, 24 hours, 7 days and 30 days from a fixed clock; inspect local and UTC summary for each.
Expected	Each deadline is rounded to minute precision without shortening the selected interval; rerenders do not extend it.
Proof	Local/UTC screenshots; fixed-clock output; submitted predicate timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-EXP-002 / Custom date and time entry

P1 | Boundary | Testnet release | Not Run

Preconditions	Isolated clock fixtures first; live stale-review case uses approved small Testnet campaign.
Steps / inputs	Choose Custom; type a future complete date/time; tab through fields and inspect the review summary.
Expected	Typed date/time works without calendar dragging; visible timezone and UTC conversion agree with submitted expiry.
Proof	Local/UTC screenshots; fixed-clock output; submitted predicate timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-EXP-003 / Invalid or past deadline

P1 | Negative | Testnet release | Not Run

Preconditions	Isolated clock fixtures first; live stale-review case uses approved small Testnet campaign.
Steps / inputs	Try empty, partial, impossible calendar date, current instant and past time; continue after each.
Expected	Refuse each invalid/past expiry with a useful inline message; no keys generated or funding prepared.
Proof	Local/UTC screenshots; fixed-clock output; submitted predicate timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-EXP-004 / Timezone and DST boundaries

P1 | Boundary | Testnet release | Not Run

Preconditions	Isolated clock fixtures first; live stale-review case uses approved small Testnet campaign.
Steps / inputs	Run browser fixtures in Asia/Manila and America/New_York; test DST skipped and repeated local times.
Expected	Skipped local times are refused; chosen offset on a repeated hour is preserved; server and reviewed predicate agree.
Proof	Local/UTC screenshots; fixed-clock output; submitted predicate timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-EXP-005 / Expiry while review stays open

P1 | Negative | Testnet release | Not Run

Preconditions	Isolated clock fixtures first; live stale-review case uses approved small Testnet campaign.
Steps / inputs	Hold a saved draft until its expiry, then try prepare/sign without changing the reviewed deadline.
Expected	Reject stale expiry; never silently extend a previously reviewed balance predicate.
Proof	Local/UTC screenshots; fixed-clock output; submitted predicate timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / KEY

KLM-D1-KEY-001 / Private export is a funding gate

P0 | Security | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Generate keys; try sign before saving export. Save it privately and retry.
Expected	Funding stays blocked before export acknowledgment; save unlocks review/sign; no secret reaches the server.
Proof	Screenshots with private regions excluded; allowlisted request fields; offline public-key comparison.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-KEY-002 / Recovery phrase normalization

P0 | Security | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Privately generate a disposable phrase, then paste it as words and as a numbered list in a new draft; compare public key derivation.
Expected	Valid supported BIP39 phrase normalizes deterministically; invalid checksum refuses. Never use a Freighter wallet phrase as test data.
Proof	Screenshots with private regions excluded; allowlisted request fields; offline public-key comparison.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-KEY-003 / Lost export recovery from saved phrase

P0 | Security | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	In a clean tab restore the campaign phrase and original derivation index/count; compare public keys offline.
Expected	Same phrase/index recreates the same keys; wrong phrase/index does not. Kleym cannot recover missing private material.
Proof	Screenshots with private regions excluded; allowlisted request fields; offline public-key comparison.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-KEY-004 / Fragment removal and data minimization

P0 | Security | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Open a disposable private claim locally; inspect address bar and sanitized request body after initialization.
Expected	Fragment is cleared from visible history; only public key and signatures/intended public fields leave the browser; no full bearer URL in evidence.
Proof	Screenshots with private regions excluded; allowlisted request fields; offline public-key comparison.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / MAT

KLM-D1-MAT-001 / USDC lifecycle: literal-zero-XLM sponsored sender; absent account

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision literal-zero-XLM sponsored sender and absent account; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-MAT-002 / USDC lifecycle: literal-zero-XLM sponsored sender; existing zero-XLM account without USDC trustline

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision literal-zero-XLM sponsored sender and existing zero-XLM account without USDC trustline; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-MAT-003 / USDC lifecycle: literal-zero-XLM sponsored sender; existing zero-XLM account with USDC trustline

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision literal-zero-XLM sponsored sender and existing zero-XLM account with USDC trustline; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-MAT-004 / USDC lifecycle: funded sender with nonzero XLM; absent account

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision funded sender with nonzero XLM and absent account; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-MAT-005 / USDC lifecycle: funded sender with nonzero XLM; existing zero-XLM account without USDC trustline

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision funded sender with nonzero XLM and existing zero-XLM account without USDC trustline; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-MAT-006 / USDC lifecycle: funded sender with nonzero XLM; existing zero-XLM account with USDC trustline

P0 | Positive | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Provision funded sender with nonzero XLM and existing zero-XLM account with USDC trustline; reserve/capacity snapshots recorded.
Steps / inputs	Create two distinct 1-USDC links: one claim and one expiry reclaim. Fund; inspect both balances. Materialise first link; wait for a strictly later ledger; explicitly claim. After the second expiry, sender approves reclaim.
Expected	Sender supplies exactly 2 USDC, receives exactly 1 back; recipient gains exactly 1. Sponsor pays actual fees/reserves. Zero-XLM actors remain zero. Temporary account/trustline removed, persistent recipient entries correctly sponsored.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Include materialisation hash and ledger, claim hash and later ledger, reclaim hash; IDs removed independently.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / FUN

KLM-D1-FUN-001 / Funding envelope ownership

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Prepare a fresh 3-link USDC campaign; decode operations, source accounts, signers, asset and predicates before approving.
Expected	Classic source is operational sponsor; sender supplies principal in createClaimableBalance ops; sponsoring brackets wrap funding; no fee bump substitutes for reserve sponsorship.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-002 / Funding signer rejection

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Remove sender signature, then sponsor signature from disposable prepared fixture; submit to isolated API.
Expected	Missing/wrong required signature is refused before network submission; pending journal cannot mark funding confirmed.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-003 / Balance ID derivation and reserve units

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Fund 3 links once; compare stored IDs against createClaimableBalance operation order and Horizon.
Expected	Three exact asset/amount/claimant predicates and balance IDs match; sponsor adds 6 reserve units for two claimants per balance.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-004 / 200 links across batches

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	With approved Testnet budget, create 200 one-USDC links; prepare and sign sequentially using configured batch size; wait for every batch confirmation.
Expected	All 200 IDs unique and confirmed exactly once. Number/signature count follows effective per-envelope operation cap; no invalid >100-op envelope; campaign active only after all required confirmations.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-005 / Principal shortage

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Use sender with 2 USDC and request three 1-USDC links; try funding.
Expected	Fresh preflight refuses insufficient USDC before wallet signature; no link marked funded or active.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-006 / Sponsor shortage / liabilities

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Use isolated sponsor fixtures with low spendable XLM and native selling liabilities; prepare full remaining campaign.
Expected	Spendable uses fresh base reserve, entries, sponsorship and selling liabilities; insufficient full remaining capacity refuses before signing.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-007 / Account clone and sequence stability

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Prepare twice from shared account fixture and compare originals; then perform actual sequential confirmed batches in isolated harness.
Expected	SDK builder does not mutate cached sender/sponsor account records; each accepted envelope uses coordinated correct source sequence.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-FUN-008 / Legacy native-XLM compatibility

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Create a small XLM campaign using explicitly approved test identity with spendable XLM; fund, claim and reclaim unused balance.
Expected	Legacy native funding path remains compatible; exact native principal, fees and reserves reconcile; sponsor policy follows reviewed envelope.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / SET

KLM-D1-SET-001 / Claim exactly once

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	For a funded link, connect recipient; record no mutation on connect; claim once and reload/click again.
Expected	Only explicit claim moves funds; exact amount credited once; claimed screen shows confirmed hash; repeated claim cannot pay again.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-002 / One-stroop custom claim

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Fund a custom 0.0000001-USDC link after approval; claim to trusted recipient.
Expected	Recipient gets exactly 0.0000001; totals and receipt preserve seven decimals; no zero rounding.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-003 / Frozen / unauthorized / full trustline

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Use disposable issuer fixture with unauthorized or full receiving trustline; try prepare and claim.
Expected	Refuse unusable destination without losing balance or misreporting success; Circle USDC must not be altered for this test.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-004 / Claim before / at / after expiry

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Using controlled ledger close-time fixture, test T-1,T,T+1. In approved live boundary run, compare actual Horizon predicate seconds and ledger close time.
Expected	Ephemeral claimant eligible only abs_before T; sender reclaim eligible at/after T. Host clock and millisecond UI cannot redefine predicate.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-005 / Temporary reserve release

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Record sponsor before materialisation, after materialisation and after claim. Independently check temporary account absence and removed balance.
Expected	Temporary account 2 plus trustline 1 reserve units released; claimable-balance 2 units released; permanent recipient sponsored entries remain and are separately explained.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-006 / Sender-authorized reclaim after expiry

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Keep third link unused. Wait for on-chain expiry; select sender; review single reclaim amount/signers; approve once.
Expected	Unused 1 USDC returns only to original sender; balance disappears; 2 claimant reserve units released; sponsor pays actual fee; recipient state unchanged.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-007 / Pre-expiry reclaim / wrong sender

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Try reclaim one second before deadline and with another sender identity in controlled API/ledger fixtures.
Expected	Refuse both; no sender refund, no removed balance and no journal settlement from a rejection.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-008 / Partial reclaim and duplicate reconciliation

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Use 3 expired links with one already claimed; reclaim remaining links; replay worker/event and refresh campaign.
Expected	Only reclaimable amounts are returned; sum/receipt count matches exact settled links; duplicate processing cannot credit twice.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-009 / Renewal uses verified refunded budget

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Expire an equal-amount campaign, reclaim remaining links, wait for confirmed accounting, then renew from original campaign.
Expected	Original lineage retained; renewed link count and principal equal verified refund only; claimed links are excluded; renewed funding still requires sender review.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-010 / Renewal refuses unsafe terms

P0 | Negative | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Try renewal before expiry, before refund settles, with changed sender/asset/count, after second renewal, and on custom-amount campaign.
Expected	Refuse invalid terms; variable-amount renewal is currently unsupported and clearly refused; no second principal distribution hidden as renewal.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-SET-011 / Ledger-derived receipt time

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys.
Steps / inputs	Claim, stop UI before DB settles, and run reconciliation; compare direct and recovered receipt timestamps with confirmed operation created_at.
Expected	Both paths use ledger settlement time consistently. Current issue #110 remains a known gap until verified/fixed; app wall-clock time is insufficient.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Sanitized receipt canonical bytes/signature/public verification key when relevant.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / SIG

KLM-D2-SIG-001 / Network/provider mismatch

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Configure Testnet passphrase with public Horizon or vice versa; attempt every write preparation.
Expected	Refuse mismatched network identity before wallet or network write; read-only Mainnet checks cannot submit.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-002 / Wrong asset issuer

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Alter prepared or requested USDC issuer while keeping display code USDC.
Expected	Match full asset code+issuer+network; refuse unauthorized issuer, never silently map by ticker.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-003 / Reviewed XDR tampering

P0 | Security | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Alter amount, destination, source, operation order, predicates, timebounds and fee separately in signing fixtures.
Expected	Every altered reviewed transaction hash is refused; no mutation accepted because a wallet signed it.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-004 / Signed envelope preservation

P0 | Security | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Return signed fixtures missing sponsor/local signatures or containing a signature for another passphrase/account.
Expected	Require exact reviewed hash and all required valid signatures; do not reconstruct or drop prior signatures.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-005 / Wallet account/network changes mid-review

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Connect sender, prepare; switch selected wallet or network before sign. Retry only after fresh review.
Expected	Refuse changed identity; reconnect/review clearly; no automatic retry with different account/network.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-006 / Cancel / timeout / lock wallet

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Cancel connection and signing separately; lock wallet; let acknowledgment/review timeout; retry from saved draft.
Expected	Useful bounded error; no funding or claim on cancel; cleanup permits safe retry; no leaked wallet error contents.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-007 / Unknown submission outcome

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Drop response after provider accepts exact signed hash; refresh/retry and run reconciliation.
Expected	Exact signed bytes/hash retained durably; lookup same hash before any retry; no replacement payment or duplicate funding.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-008 / Process crash at durable boundaries

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Kill isolated worker before send, after send, after confirm and during settlement; restart for each journal fixture.
Expected	Recover prepared/submitted/confirmed/settled state deterministically; exactly one final accounting mutation per hash.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-009 / Real source concurrency across processes

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Run two processes sharing sponsor and separate web/worker instances against fresh PostgreSQL; prepare claims/funding/reclaim simultaneously.
Expected	PostgreSQL advisory source lock serializes all spenders; fresh sequence/headroom under lock; no stale capacity double admission.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-010 / Unresolved legacy attempt

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Seed old submitted row with missing signed XDR and ambiguous hash; attempt new prepare and recovery.
Expected	Do not discard unresolved financial liability by guessing; refuse/reconcile explicitly; no duplicate operation.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-011 / Strictly later ledger enforcement

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Hold TX1 confirmed ledger N; provide provider latest ledger N for TX2 then N+1; attempt claim preparation both times.
Expected	Refuse N; permit after verified N+1. Fixed sleep or browser time alone is insufficient.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-012 / Queue/DB unavailable

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Interrupt Redis/PG before and after financial write; restore and replay pending jobs.
Expected	No false success; durable attempts survive lost queue notification; recover accounting after reconnection without duplicate payout.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-013 / Source rejection classification

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Inject tx_bad_seq, insufficient balance, expired timebound and operation failure into isolated submission/reconcile harness.
Expected	Distinguish explicit rejection from unknown outcome; settle nothing on rejection; preserve useful safe correlation metadata.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SIG-014 / SDK sequential multi-batch handling

P0 | Negative | Testnet release | Not Run

Preconditions	Isolated source/DB/provider fixtures; network-fault injection is local only; no public denial-of-service.
Steps / inputs	Use published SDK/API client for >one batch; introduce delayed confirmation and exercise resume.
Expected	SDK waits/queries confirmation or surfaces actionable resumable state before next preparation; SUBMITTED is not CONFIRMED. Issue #105 remains open.
Proof	Full sanitized harness output; exact hashes; journal/DB snapshots; process IDs and timestamps.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / SEC

KLM-D2-SEC-001 / Cross-organisation and role controls

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Create two disposable orgs; try reading/registering/funding/reclaiming other org campaign with session and API key; try read-only role.
Expected	Resource/role denial without secret/object leakage; no rows or chain submissions created for unauthorized request.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-002 / Idempotency scope and request mismatch

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Reuse same key with same request, changed body and different user/org; run concurrently.
Expected	Same authorized request replays one result; changed body refuses; key never returns another org response.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-003 / API key underscores and secret at rest

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Use deterministic full API-key fixtures with underscores in suffix; verify authentication, revoke/wrong-key denial and database representation.
Expected	Parser/hash covers whole token; no probabilistic generation assumption or partial split token check; no cleartext key at rest. Issue #112 harness gap must be fixed.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-004 / Claim proof and body guard

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Submit malformed/oversize body, planted secret field, wrong preparation proof, replayed nonce and altered recipient.
Expected	Refuse at API boundary; no logs reflect bearer material; only valid matching proof advances intended claim.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-005 / Frame-origin and message spoofing

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Send bridge replies from wrong origin/window with wrong ID; trusted parent attempts changed XDR.
Expected	Ignore untrusted replies and refuse tampered trusted replies; no wildcard origins, no broad frame access.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-006 / Session cookie and CSRF boundaries

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Enable exact Lantern origin; login in trusted partition; issue cookie mutation from foreign/originless browser; log out.
Expected	HttpOnly/Secure/Partitioned cookie matches deployment; unsafe browser mutations require exact Kleym origin; logout revokes/clears matching partition.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-007 / Outbound URL canonicalization and redirects

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Configure webhook/screening/OIDC/federation URL fixtures with local/private/reserved hosts, credentials, alternative numeric IPs, backslashes and 3xx.
Expected	Public HTTPS guard rejects unsafe forms and redirects; permitted loopback only in explicit development; network errors are safe and bounded.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-008 / DNS rebinding and deployment egress

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	In controlled deployment resolve a public-looking allowed hostname to private IP; test socket egress policy with security owner.
Expected	No connection to private/internal address; DNS/socket or platform egress enforcement must prove this. Current URL-only guards do not satisfy this case.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-009 / Audit seed emitted log and future key guard

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Run secret-classification focused tests and guard using planted root/nested fields; add unclassified seed fixture; verify fixed public signature.
Expected	Audit/sponsor/encryption/provider fields censored; future seed name fails classification; safe public IDs observable; signature bytes/verification format unchanged.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-010 / Client bundle and evidence leak scan

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Scan candidate source/build and proposed report text for seeds, mnemonic fixtures, bearer URLs, tokens and credentials; inspect all intended screenshots.
Expected	No real secret or complete claim fragment is published; public IDs/hashes permitted; scan scope/limitations recorded, not called security assurance.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-SEC-011 / Bearer-email exclusion for pilot

P0 | Security | Testnet release | Not Run

Preconditions	Disposable accounts/fixtures only; local authorized fault injection; owner-approved egress test target for DNS case.
Steps / inputs	Enable campaign/self-delivery mode; invoke legacy email/reminder queue path and inspect sanitized message metadata.
Expected	Pilot cannot enqueue/send full bearer links via built-in email; server never receives browser link key. Legacy behavior requires explicit gated product decision.
Proof	Sanitized request/response and DB evidence; guard test logs; no credential values or bearer URLs.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / FRE

KLM-D3-FRE-001 / Desktop Freighter sender connection

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Cold-open approved HTTPS sender page with unlocked desktop Freighter/Testnet. Connect intended public sender and prepare one funding batch.
Expected	Desktop extension control only; no Android app button; exact address/network visible; connection alone moves no funds.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-002 / Desktop Freighter funding approval

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Save private export; sign intended batch; inspect popup and submit; wait for campaign ledger confirmation.
Expected	Popup appears; correct official issuer/principal/signers; sender XLM warning, if wallet displays it, does not substitute for sponsor-paid ledger proof.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-003 / Desktop recipient claim

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Open link A privately in recipient browser; connect intended recipient; click Claim; review signatures and wait for settlement.
Expected	Exact one USDC credited once; confirmed transaction link uses Testnet; cleanup/reserves satisfy D1 accounting.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-004 / Stale extension tab recovery

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Keep saved draft, invalidate/restart extension bridge, compare original/fresh tabs, reopen only after private backup.
Expected	No endless spinner or false funded state; helpful reconnect guidance; new tab can recover public draft and keys only from user-held backup.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-005 / Android Chrome phone controls

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Open link B privately in Android Chrome without desktop extension. Inspect wallet controls and press phone connect.
Expected	No desktop-specific Connect wallet button. Freighter phone open/pair action is clear; connection is distinct from claim; installed/uninstalled fallback is truthful.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-006 / Android Freighter connection return

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Approve connection in installed Android Freighter, return to original Chrome tab and inspect account/network.
Expected	Tab reaches explicit Claim control with intended public account; connection alone cannot transfer; return guidance explains next step.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-007 / Android Freighter full claim signing

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	From connected link B in Chrome press Claim; open wallet review, explicitly approve, return and confirm independently.
Expected	Actual v1.25.28 or recorded installed-version mobile signatures work for required operations; exact one USDC; no manual raw-XDR or key entry.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-008 / Android reconnect/background lifecycle

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Background Chrome/Freighter during connection, review and submission; resume; test expiry and user rejection separately.
Expected	No duplicate submission on resume; usable safe recovery; stale wallet context cannot sign a changed transaction; keys remain private.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-FRE-009 / App not installed / pairing expiry

P0 | UAT | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Exact browser, extension/APK, Android and Freighter versions recorded; approved public Testnet candidate.
Steps / inputs	Use Android without installed app or expired WalletConnect pairing; press connect and cancel/retry.
Expected	Usable fallback/help and bounded timeout; no claim or phantom connected state; no promise that app opening equals approval.
Proof	Physical-device/desktop screenshots with private link hidden; recorded approvals, public hashes and independent balances.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / LAN

KLM-D3-LAN-001 / Curated directory entry and package identity

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Hash senior-provided Lantern APK/extension; inspect Apps directory for exact approved Kleym HTTPS origin/session=true; compare effective installed extension origin.
Expected	Kleym is explicitly curated; Android directory metadata generated; exact approved frame origins. Current 0.6.2 without Kleym cannot pass this prerequisite.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-002 / Android public sender handoff

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	From public Kleym sender/login in Chrome select Open in Lantern; inspect opened page and browser fallback with app absent.
Expected	Only public path handed off; query/fragment removed; app opens curated Kleym, fallback is intended public page; no private claim fragment copied into intent.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-003 / Lantern sender authenticated session

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Inside curated trusted Lantern frame login, connect wallet, create draft, leave/reopen Apps and log out.
Expected	Authenticated sender experience works in correct cookie partition; desktop browser session is separate; logout terminates partition session.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-004 / Lantern desktop funding and management

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	In rebuilt extension open Apps > Kleym. Create saved 3-link campaign; approve funding; inspect campaign and reclaim unused link after expiry.
Expected	Lantern receives exact sign-only XDR; no external Freighter phone control; API submits and confirms exactly once; auth/organization management remains intact.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-005 / Lantern Android funding and management

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Repeat saved 3-link campaign creation/funding in rebuilt APK; inspect scrolling, approve review and confirmed dashboard.
Expected	Full creator journey works on physical phone, not only mocked bridge; exact hash/account/network preserved; no overflow or inaccessible signing action.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-006 / Recipient claim already in trusted Lantern frame

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Open disposable link inside curated trusted frame using owner-approved private-link route; connect Lantern and explicitly claim.
Expected	Connect Lantern selected; no Freighter pairing control; exact claim review inside wallet; confirmed asset reaches selected recipient; public launcher is not claimed to move private links.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-007 / Uncurated generic URL sandbox

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Open Kleym via Lantern generic URL bar instead of approved Apps directory; attempt login/connect safely.
Expected	Opaque sandbox is not treated as trusted authenticated integration; honest guidance; no fallback widening origins or copying private fragments.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-008 / Lantern delayed idless connection reply

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Delay getPublicKey reply past timeout, retry without reopening, then deliver old response in bridge fixture.
Expected	Late response cannot complete a different connection; reopen requirement visible; signing still correlates exact request ID/source/origin.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-LAN-009 / Lantern wrong network / account / permissions

P0 | UAT | Deferred Lantern | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. G3-Lantern: rebuilt curated package, verified origins and HTTPS partition-cookie support required.
Steps / inputs	Switch network/account or revoke app grant before sign; return wrong identity or tampered signature via fixture.
Expected	Fresh grant/account/network checks refuse; never signAndSubmit behind Kleym journal; original reviewed transaction unchanged.
Proof	Package SHA256, exact origin/config record, sanitized bridge type/ID trace, physical wallet review and public ledger proof.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / UX

KLM-D3-UX-001 / Keyboard and focus order

P1 | UAT | Testnet release | Not Run

Preconditions	Isolated UI candidate; disposable public snapshots; real assistive tools for accessibility assertions.
Steps / inputs	Use Tab/Shift-Tab/Enter/Space from login through amount editor, expiry picker, review, export and wallet controls.
Expected	All interactive elements reachable with visible focus; logical order; no keyboard trap.
Proof	Screenshots/notes with private areas excluded; tool/browser versions; elapsed journey and exact confusing text.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-UX-002 / TalkBack / NVDA status announcements

P1 | UAT | Testnet release | Not Run

Preconditions	Isolated UI candidate; disposable public snapshots; real assistive tools for accessibility assertions.
Steps / inputs	Use Android TalkBack and desktop NVDA for invalid amount, funding pending and claim result.
Expected	Errors and new states announced meaningfully; controls labelled; no reliance on colour alone.
Proof	Screenshots/notes with private areas excluded; tool/browser versions; elapsed journey and exact confusing text.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-UX-003 / Phone viewport and 200% zoom

P1 | UAT | Testnet release | Not Run

Preconditions	Isolated UI candidate; disposable public snapshots; real assistive tools for accessibility assertions.
Steps / inputs	Test 360px/393px portrait, landscape, keyboard-open state and desktop 200% zoom across creation/review/claim.
Expected	No sideways scrolling or clipped primary controls; amount/date input and signing return usable.
Proof	Screenshots/notes with private areas excluded; tool/browser versions; elapsed journey and exact confusing text.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-UX-004 / Cold recipient without team help

P1 | UAT | Testnet release | Not Run

Preconditions	Isolated UI candidate; disposable public snapshots; real assistive tools for accessibility assertions.
Steps / inputs	Give independent reviewer only their private test link and minimal Testnet warning; time connection/claim and record hesitation.
Expected	Reviewer identifies asset/network, connection versus claim and result without keys/raw-XDR instruction; friction recorded as UAT findings, not fabricated passes.
Proof	Screenshots/notes with private areas excluded; tool/browser versions; elapsed journey and exact confusing text.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-V2-UX-001 / Mobile header navigation and history

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	At320,360,412px and landscape visit every menu using top navigation, close with Escape/Back/outside tap and switch routes.
Expected	Header/menu accessible; active route correct; focus restored; no bottom-nav overlap, jumping viewport or horizontal document overflow.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-002 / Keyboard, screen reader and motion

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Complete form navigation by keyboard and TalkBack/NVDA; test validation announcements, modal traps and prefers-reduced-motion.
Expected	Meaningful labels/focus/status; no keyboard trap; animation does not hide essential content; reduced motion respected.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-003 / Native Android input behavior

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In emulator Chrome enter decimal amounts/date, paste G-address, upload/download CSV and rotate with keyboard open.
Expected	Correct keyboards, caret/value preserved; input controls reachable; Downloads accessible; browser Back does not silently lose protected keys.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-004 / Desktop browser compatibility

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Run critical creation/export/claim/logout in Brave/Chrome, Firefox and WebKit/Safari with exact versions.
Expected	Supported flows meet same invariants; unsupported wallet provider has explicit fallback, not hanging button.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-005 / Freighter unavailable and connection cancel

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open mobile with app absent, expired pairing and denied connection; desktop without extension; choose manual address.
Expected	Correct platform-specific button only; actionable install/reconnect fallback; manual destination never substitutes for required sender/bound-wallet signature.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-006 / Chrome-to-Freighter return lifecycle

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Connect/sign on emulator and physical Android; background Chrome, switch account/network, cancel, return by Back and app switcher.
Expected	One pending operation; correct address/network revalidated; no leave-warning on deliberate handoff; no stale connected account or duplicate signing.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-007 / Empty, error, loading and unavailable states

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated responses for every page: empty200,401,403/404,409,429,500,timeout and offline then recover.
Expected	No endless spinner/raw stack; appropriate retry/read-only state; retained safe user input; no success until confirmed.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-UX-008 / Static website to app boundary

P1 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open marketing root and all anchors/FAQ/Open App at desktop/mobile; follow login and Back to home in trusted frame fixture.
Expected	Correct separate HTTPSapp/login; no sponsor/database secrets or auth middleware on static site; no open redirect; frame origin remains allowlisted only.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / OPS

KLM-D4-OPS-001 / Candidate freeze and deployed parity

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Record feature commit, dependency lock hash, migrations, runtime/package-manager versions, effective public URL and server build identity; compare release manifest; run dependency audit with supported package manager.
Expected	Tested source, built bytes and deployed candidate match; unknown identity blocks qualification. Unresolved critical/high dependency advisories block release until remediated or explicitly assessed by the security owner.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-002 / Migration and rollback on populated copy

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Backup isolated seeded DB with campaigns/attempts/receipts; apply candidate migration; exercise old/new states; rehearse documented rollback from copy.
Expected	No precision/history/lineage loss; safe recovery of pending attempts; rollback decision tested and source/deploy artifact preserved.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-003 / Real DB/Redis CI qualification

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Run full isolated PostgreSQL/Redis suites from candidate in CI; include keys, receipts, batches, claims, source coordination, backup and recovery.
Expected	Green evidence for candidate includes meaningful assertions; unavailable Docker/local services mean Blocked for execution, not pass from mocks.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-004 / Public HTTPS cold sender and recipient

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	After owner-approved deployment, cold-open public URL on desktop and Android outside team network; execute 3-link tutorial.
Expected	HTTPS reachable, Testnet clearly labelled; no localhost dependency; account/claim links work without team browser profile.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-005 / 200-link cost/capacity budget

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Record fresh base reserve, fees, sponsor liabilities and configured campaign/recipient caps; quote 200 one-USDC links then enforce limiting budgets.
Expected	Principal separate from operational XLM; fee bid versus charged fee distinguished; persistent recipient reserves included in lifecycle budget; configured limits enforced before spend.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-006 / Performance latency/provider-read budget

P0 | Load | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Measure 30 representative prepare/resolve requests at agreed concurrency with recorded network and fixture dataset; report median/p95, provider calls and errors.
Expected	Baseline and candidate measured comparably; no invented speedup; static 10-to-5 provider call reduction is not latency evidence. Owner sets SLO before sign-off.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-007 / API throttling / provider rate limits

P0 | Load | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Use bounded local load within agreed test budget; return 429/503/timeouts from isolated provider; observe recovery and queues.
Expected	Useful bounded response/backoff; no storm, duplicate spend or false active state; rate limit shown honestly and financial journal retained.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-008 / Sponsor failover / shortage / refill

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Exhaust primary fixture below working threshold; select secondary; test total pool shortage and alert routing; rehearse refill procedure without cold signing.
Expected	Fresh sponsor choice respects outstanding liability and pinned campaign sponsor; alerts actionable; no unauthorized automatic cold refill; approved owners recorded.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-009 / Worker pause and drain

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Pause creation with pending submitted attempts; drain/reconcile workers before planned shutdown, then restart isolated services.
Expected	User-facing pause clear; accepted attempts remain durable and settle; no stranded state hidden by queue deletion.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-010 / Backup restore and disaster recovery

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Restore encrypted DB backup to isolated environment; restore matching configuration via secret store; reconcile exact pending hashes before unpausing.
Expected	Audit/history and financial journals preserved; no key in reports; measured recovery time/loss against owner-approved RTO/RPO.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-011 / Monitoring and signed evidence cadence

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Trigger stale pending attempt, low spendable reserve, queue delay and mismatch fixture; inspect dashboards/alerts and generate verified export.
Expected	Owner can trace safe correlation ID/hash; alerts reach approved operator; signed receipts verify; production cadence/gates documented and actually wired.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-012 / Mainnet read-only config and issuer

P0 | UAT | Mainnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	Inspect public passphrase/official USDC issuer and exact public Horizon identity; verify release checklist without signing or submission.
Expected	Public issuer GA5ZSEJYB37JRC5AVCIA5MOP4RHTM335X2KGX3IHOJAPP5RE34K4KZVN matches configured asset; no Testnet address/passphrase/issuer crossover. No live movement authorized by this plan.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-013 / Owner-approved Mainnet pilot and operational controls

P0 | UAT | Mainnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	After mandatory Testnet and operations cases pass, record approved deployment, sponsor capital, incident/refill owners and rollback criteria. Obtain explicit approval for a small real-asset pilot.
Expected	No arbitrary global campaign-USDC cap is introduced. Creator wallet capacity and protocol bounds remain enforced. Mainnet stays disabled until all mandatory gates and explicit real-asset approval are satisfied.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-OPS-014 / Issue closure and evidence consistency

P0 | UAT | Testnet release | Not Run

Preconditions	G0 candidate recorded; isolated infrastructure available; deployment and Mainnet changes require separate approval.
Steps / inputs	For each proposed closure map every criterion to candidate source and executed case log; verify tracker totals/evidence/defect references.
Expected	Close only satisfied criteria; keep missing device/DB/ledger/deployment proof open; roadmap reflects qualified scope rather than promised launch date.
Proof	Release manifest, sanitized logs/runbook observations, owner decisions, metrics/restore notes and independent public ledger data where authorized.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-V2-OPS-001 / Exact deployed version and runtime

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Compare GitSHA/tree/lock/runtime and web/worker/landing deployment IDs; query health/readiness and worker heartbeat.
Expected	All identify approved candidate; Node24.22.1; health not mistaken for worker/ledger readiness; no mismatch hidden by old deployment.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-002 / Dependency/runtime regression gates

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Run frozen install, production audit, typecheck, lint, tests, build and secret guards on exact candidate.
Expected	No failing gate or suppressed advisory; dependency/runtime fixes persist across Docker deployment, not only local machine.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-003 / Backup, restore and populated migration

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Restore encrypted backup into isolated env; migrate populated old data, validate receipts and queues, rehearse rollback.
Expected	Measured RPO/RTO recorded; no duplicate send from restored jobs; additive schema rollback preserves signed historical bytes; encryption keys restored privately.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-004 / Concurrent load and provider budgets

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Measure1/10/100concurrent claims and200/10000link source fixtures; inject rate limits and shared source contention without public abuse.
Expected	Exact once-only accounting; bounded queues/memory; agreed p95/p99 and error SLO measured before claiming capacity; no fabricated throughput from rate-limit constants.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-005 / External alerts and incident ownership

P0 | Positive + Negative + Boundary | Mainnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Trigger controlled queue failure, sponsor shortage, reconciliation drift, provider outage; deliver alert to approved operator.
Expected	Observed notification and acknowledged owner/escalation; logs-only state not called monitored; OTLPunset is recorded as unmet operational gate.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-006 / Network deployment separation

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated public-mode config test missing MainnetURL, wrong passphrase/issuer, mixed sponsor/queue/database namespace and Testnet link on public host.
Expected	Startup/admission refuses invalid identities; no chain crossover or shared real/test signing material.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-007 / Mainnet read-only rehearsal

P0 | Positive + Negative + Boundary | Mainnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Verify public Horizon identity, official issuer and unsigned review using no real secret or broadcast.
Expected	Zero asset writes; read-only rehearsal explicitly cannot qualify funded public transactions.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-OPS-008 / Mainnet controlled release gate

P0 | Positive + Negative + Boundary | Mainnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Require all mandatory Testnet cases, no unresolved critical/high findings, restore/alert/treasury ownership, approved domain and explicit live pilot decision.
Expected	Keep Mainnet disabled until sign-off; no arbitrary totalUSDCcap added; real transactions separately authorized and independently reconciled.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / POL

KLM-D1-POL-001 / Bearer policy versus named recipient

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Use isolated policy/conversion fixtures and disposable issuers; real exchange deposits are not authorized.
Steps / inputs	Share a disposable bearer link with a different controlled recipient; compare with an explicitly configured strict-policy fixture.
Expected	Bearer policy is not email/address binding; strict policy follows its documented authorization. Never describe sender labels as claimant enforcement.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Safe policy result, destination asset/minimum and memo type; no OTP/token capture.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-POL-002 / Receive-as quote and slippage floor

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Use isolated policy/conversion fixtures and disposable issuers; real exchange deposits are not authorized.
Steps / inputs	In an approved disposable asset pair, quote an allowlisted receive-as asset; change quote liquidity and try below-minimum destination before submission.
Expected	Delivered asset and minimum are explicitly reviewed; failed conversion preserves claimable principal; no silent ticker/issuer substitution.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Safe policy result, destination asset/minimum and memo type; no OTP/token capture.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D1-POL-003 / Exchange deposit memo boundaries

P0 | Regression | Testnet release | Not Run

Preconditions	Current v2 G0-G3 gates passed; disposable Testnet identities; fresh campaign; privately backed-up keys. Use isolated policy/conversion fixtures and disposable issuers; real exchange deposits are not authorized.
Steps / inputs	Use controlled exchange-style account fixture; test required ID/text memo, missing/wrong-type/overflow memo and disabled exchange-deposit campaign.
Expected	Only permitted reviewed destination/memo is accepted; no recipient account merge; missing or altered memo is refused before transfer; actual delivered asset appears on receipt.
Proof	Public before/after Horizon account JSON, transaction and operation JSON, prepared-XDR hash, DB rows with bearer material excluded. Safe policy result, destination asset/minimum and memo type; no OTP/token capture.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / AUTH

KLM-D2-AUTH-001 / Fresh-auth and MFA protected operations

P0 | Security | Testnet release | Not Run

Preconditions	Isolated migrated DB/Redis; disposable authentication configuration and public verification fixtures.
Steps / inputs	With disposable sender/admin, exercise protected operations with missing/expired fresh auth; complete TOTP/WebAuthn, revoke session and retry.
Expected	Required second factor and fresh-auth gate cannot be bypassed; no protected mutation with revoked session; recovery material never enters evidence.
Proof	Sanitized authorization result, public export/signature and verifier output; no MFA codes/keys.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-AUTH-002 / Approval / screening hold and outage

P0 | Security | Testnet release | Not Run

Preconditions	Isolated migrated DB/Redis; disposable authentication configuration and public verification fixtures.
Steps / inputs	Create approval-required and screened campaign fixtures; attempt funding before approval, on explicit hold and while screening dependency is unreachable.
Expected	Authorization and hold gates enforced; unavailable screening fails closed with safe actionable result; only authorized approved campaign can advance.
Proof	Sanitized authorization result, public export/signature and verifier output; no MFA codes/keys.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D2-AUTH-003 / Signed export tampering and key history

P0 | Security | Testnet release | Not Run

Preconditions	Isolated migrated DB/Redis; disposable authentication configuration and public verification fixtures.
Steps / inputs	Generate receipts/audit export with disposable signing configuration; verify publicly; alter row/amount/signature and verify again; verify archived public-key fixture.
Expected	Valid evidence verifies without a signing seed; tamper fails; canonical/version/key history preserved; private credentials and bearer metadata absent.
Proof	Sanitized authorization result, public export/signature and verifier output; no MFA codes/keys.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-V2-AUTH-001 / Empty and incorrect login

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Submit empty username/password; then disposable unknown username and wrong password.
Expected	Required-field feedback; indistinguishable invalid-credentials responses; no authenticated session.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-002 / Login retries and account lock

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated accounts/IPs; exercise attempts at 4/5/6 per IP and 9/10/11 per account; retry a valid credential during lock.
Expected	Limits and Retry-After match auth policy; locking cannot be bypassed by another IP; other accounts retain their own budget.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-003 / Logout and browser history

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Log in, log out, press Back and reload a protected route in a second tab.
Expected	Logout ends the server session; protected data is unavailable after revalidation; no browser-close logout promise.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-004 / Session expiry during funding

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Prepare but do not submit a batch; expire the disposable session; attempt prepare/submit, reauthenticate and resume.
Expected	Expired session cannot mutate; draft/key backup preserved; resumed submission reconciles an existing attempt before another transfer.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-005 / Password validation and rotation

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	On disposable account test missing/wrong current password, short new value and valid rotation; replay old sessions.
Expected	No change for invalid input; valid change rotates current session and revokes others. Do not alter the real operator credential.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-006 / Organisation switch isolation

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use an owner in two disposable orgs; switch with a detail page and draft open in another tab.
Expected	Every request uses current permitted organisation; foreign IDs reveal no data; old draft cannot bypass ownership.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-007 / Invitation invalid, reused and expired

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open nonexistent token, expired token, used token and valid invitation; try mismatched user.
Expected	Invalid tokens produce safe refusal; valid single-use acceptance grants only intended membership; no elevation by replay.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-008 / MFA recovery and step-up expiry

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use fixture TOTP/passkey; cancel authenticator, replay recovery code, exhaust guesses and age the five-minute step-up.
Expected	Fail closed; one recovery use only; protected signing/reclaim/key creation needs fresh factor. No factors captured in evidence.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-AUTH-009 / SSO state, issuer and deprovision

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated IdP; alter state/nonce/issuer, test email collision and deactivate via SCIM.
Expected	Reject altered handshake; bind stable subject rather than email; deprovision immediately revokes live access.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / ADM

KLM-D3-ADM-001 / Campaign list, filters and per-link history

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated UI/API fixtures or approved public candidate; private claim URL never captured.
Steps / inputs	Create mixed-status equal/custom campaigns in two orgs; filter/search/page dashboard and campaign details; refresh after settlement.
Expected	No cross-org data; stable paging/counts; exact per-link amount and confirmed lifecycle status; no stale active totals from submitted-only attempts.
Proof	Scoped API snapshots, dashboard screenshots and safe state fixture output.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-ADM-002 / Templates and historical funding compatibility

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated UI/API fixtures or approved public candidate; private claim URL never captured.
Steps / inputs	Create draft from existing template and inspect funding mode; compare with new sponsored API campaign and historical sender-paid campaign.
Expected	Template/historical mode remains explicit and supported; no silent migration to sponsored version; funding signatures/costs match actual reviewed protocol.
Proof	Scoped API snapshots, dashboard screenshots and safe state fixture output.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D3-ADM-003 / Claimed / expired / invalid link copy

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated UI/API fixtures or approved public candidate; private claim URL never captured.
Steps / inputs	Open safe local fixtures for already claimed, expired-unclaimed, invalid/missing fragment and provider outage.
Expected	Correct distinct states and actionable messages; no false funds-in-wallet message before confirmation; no spinner stuck or secret-bearing error.
Proof	Scoped API snapshots, dashboard screenshots and safe state fixture output.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / DOC

KLM-D4-DOC-001 / Privacy deletion and organization isolation

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated data and telemetry sinks; source candidate and API docs frozen.
Steps / inputs	With disposable org/test user, export personal data, request allowed erasure, and verify financial audit retention and unrelated org isolation.
Expected	Only permitted personal data returned/erased; immutable financial proof preserved under documented retention; keys/bearer URLs absent.
Proof	Sanitized export/schema/attributes output; docs-to-case mapping and reviewer notes.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-DOC-002 / Telemetry and error observability minimization

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated data and telemetry sinks; source candidate and API docs frozen.
Steps / inputs	Trigger bounded funding/claim failures; inspect emitted logs and tracing attributes using planted secret/bearer fixtures.
Expected	Safe correlation IDs/hash/state observable; no mnemonic, seed, complete bearer URL, signed-body dump or private token retained in logs/traces.
Proof	Sanitized export/schema/attributes output; docs-to-case mapping and reviewer notes.
Source / mode	SPEC.md; AGENT.md; original v1 case

KLM-D4-DOC-003 / API documentation and support limits

P1 | Regression | Testnet release | Not Run

Preconditions	Isolated data and telemetry sinks; source candidate and API docs frozen.
Steps / inputs	Compare public write API/SDK examples, wallet support matrix, funding versions and recovery help with executed candidate cases.
Expected	Docs describe only proved support, explicit async confirmation and custom-amount renewal limitation; unsupported Android/Lantern/Mainnet claims withheld.
Proof	Sanitized export/schema/attributes output; docs-to-case mapping and reviewer notes.
Source / mode	SPEC.md; AGENT.md; original v1 case

Detailed cases / CREATE

KLM-V2-CREATE-001 / Sender address malformed and secret-shaped

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Paste empty text, invalid checksum, a fixture secret seed, absent account and valid G-address into Funding account.
Expected	Reject malformed/secret inputs safely before lookup; absent-account state actionable; valid manual address only checks balance, never grants signing authority.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-002 / Wallet owner differs from typed sender

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Type controlled sender A; connect wallet B; attempt funding approval.
Expected	Clear mismatch refusal before submission; no silent sender replacement or transfer from B.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-003 / Name and labels boundaries

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Test empty name, whitespace-only, exact schema maximum and maximum+1; labels with quotes, comma, newline, Unicode and HTML.
Expected	Validation at both UI/API; safe text rendering; CSV round-trips labels without column displacement or script execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-004 / Asset authenticity and available balance

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Select XLM then official Testnet USDC; enter same ticker with another issuer fixture; exhaust balance with pending liabilities.
Expected	Correct issuer/network displayed; ticker alone is insufficient; spending capacity is fresh and conservative.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-005 / Every prize amount boundary

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Try blank, 0, -1, 0.0000001, 0.00000001, 1e3, NaN, comma separator, seven/eight decimal places and int64 extremes in isolated fixtures.
Expected	Only exact supported positive string amounts within ledger range accepted; no Number rounding; field-specific error blocks advancing.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-006 / Count and custom-prize lifecycle

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Test 0,1, max,max+1,fraction/text; edit prizes over multiple pages, shrink/grow count, reset one/all and change default.
Expected	Current count/order/labels/overrides remain aligned; exact sum; no invisible funded rows or stale values.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-007 / Policy switch resets incompatible recipients

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Import wallet CSV, switch EMAIL then OPEN then CODE; move Back/Next and review.
Expected	Old wallet/email assignments do not leak into another policy; incompatible fields reset visibly; registration matches selected policy.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-008 / All expiry presets and custom entry

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Choose each preset, type custom date/time, set past/invalid date, near-now and future; keep Review open past deadline.
Expected	Human-readable deadline matches UTC predicate to ledger seconds; expired terms cannot be signed; fresh validation on submission.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-009 / Vesting unlock boundaries

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Create disposable unlock schedule before/equal/after expiry and one valid future unlock; test claim just before/at/after unlock.
Expected	Impossible windows refused; on-chain predicate enforces unlock and expiry, not the browser clock.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-010 / Draft history and lost-navigation recovery

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Move through stages; browser Back/Forward; reload before and after export; navigate Go to campaign after confirmed funding.
Expected	No duplicate campaign or payment; loss of browser-only keys explained honestly; saved phrase/export recovers exact registered keys.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-011 / Review totals and batch-count consistency

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Review 3 equal prizes, 5 variable prizes and 90/91/200 boundaries under actual funding operation count.
Expected	Links shows exact integer, never dash; amount/reserve/fee-bid values match decoded transactions; sponsorship operations included in batch sizing.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-012 / Download cancelled or blocked

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Block download, cancel picker where applicable, click Generate again, attempt keyboard/programmatic Continue.
Expected	Cannot fund unexported/currently regenerated keys; download feedback actionable; no gate bypass.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-013 / Phrase import normalization and invalid checksum

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Privately enter numbered/space/newline phrase fixtures of supported lengths; test bad word/checksum, missing word and wrong renewal phrase.
Expected	Supported normalization succeeds; invalid phrase refuses without logging; mismatched renewal cannot replace registered keys.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-014 / Funding rejection and repeated click

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Cancel Freighter, lock wallet, double-tap Sign, approve then background browser and return.
Expected	No duplicate send; pending status reconciles; successful submission clears stale in-progress error; rejected signature leaves retryable draft.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-015 / Offline and unknown funding outcome

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Disconnect after wallet signs and after server broadcasts; reload and retry same intent.
Expected	Journal and hash lookup resolve before retry; one on-chain funding transaction; no false failure or extra debit.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CREATE-016 / Mainnet selector currently disabled

P0 | Positive + Negative + Boundary | Mainnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Inspect network selector and try direct public-network payload on Testnet deployment.
Expected	Unavailable Mainnet has explanation; server rejects network mismatch; no secret, queue or sponsor crossover.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / CSV

KLM-V2-CSV-001 / One consistent template across policies

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Download OPEN, CODE, EMAIL and WALLET templates; compare common header order and additional required columns.
Expected	Shared core columns consistent; policy-specific Claim Code / Email Address / Wallet Address correctly appended; no secret in recipient-only template.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-002 / Wallet CSV ordered amount binding

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Import five controlled G-addresses with 20,15,10,5,5 and labels; review row order and funded claimants.
Expected	Top-to-bottom order preserved; total55; each balance bound to the correct wallet; recipient owner signature mandatory.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-003 / Wallet CSV wrong and duplicate recipients

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Test malformed/checksum-invalid, secret-shaped, funding address, duplicated valid address, blank middle row and mixed-network assumptions.
Expected	Unsafe/invalid rows refuse with row guidance; duplicate-address behavior explicitly shown without merging amounts or reordering; no invalid row silently skipped.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-004 / Email CSV parsing and normalization

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Import valid owned test mailbox aliases, mixed case, whitespace, invalid format, blank row and duplicate mailbox.
Expected	One valid assigned email per link; canonical binding consistent; duplicates do not mix links or remove mailbox throttling.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-005 / CSV syntax and encoding

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Upload quoted commas/newlines, escaped quotes, UTF-8 BOM, CRLF/LF, empty file, broken quote, duplicate/missing/unknown headers.
Expected	Documented formats parse consistently; malformed ambiguity refuses with row/header error; no shifted recipient/prize binding.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-006 / Wrong type and oversized file

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Upload XLSX renamed CSV, PDF, executable, huge byte/row file and max allowed rows+1; cancel chooser and upload again.
Expected	CSV-only accepted by content/parser checks as well as UI; bounded error without freeze, unsafe preview or partial registration.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-007 / Formula injection and HTML

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use labels beginning =,+,-,@ and markup in cells; export receipts/template and inspect safely as text.
Expected	Spreadsheet formula execution prevented for untrusted text; legitimate negative money still invalid; UI escapes markup.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-008 / Reimport and stale asynchronous parse

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Import A then immediately B, edit count/default and switch policies while parsing.
Expected	Only latest valid file drives review; no stale async result overwrites the chosen mapping.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-CSV-009 / Immutable recipient assignment

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Register email/wallet bindings; replay identical payload then same public keys with different assignment/order.
Expected	Identical retry idempotent; changed binding refuses atomically; no partial registrations or leaked recipient lists across orgs.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / POLICY

KLM-V2-POLICY-001 / OPEN link happy path and bearer risk

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Claim controlled OPEN link in wallet A; try the same link in B after confirmation.
Expected	First authorized bearer claim pays once; second refuses. UI does not imply OPEN is address or email bound.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-002 / Claim code correct, wrong and replay

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use exported code with its matching link; try blank/wrong code, another link code and token replay.
Expected	Only matching verification advances; bounded guessing; token scoped to link; no code or token in logs/URL.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-003 / Code export and phrase recovery

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Regenerate CODE secrets export from original phrase/index and compare privately.
Expected	Codes, public keys and corresponding links recover exactly in stable order; no code is submitted during registration.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-004 / Wallet-bound wrong owner and tampering

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open bound link with wrong wallet; bypass UI with changed destination and altered reviewed XDR; cancel signer.
Expected	Assigned wallet signature and claimant checked at ledger level; wrong owner cannot redirect funds even if link/export leaks.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-005 / Bound wallet compatibility restrictions

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Enable wallet binding then try receive-as conversion or exchange memo deposit.
Expected	Unsupported combinations unavailable/refused; original asset and assigned address remain invariant.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-006 / Passkey registration, cancel and recovery

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use disposable browser profiles; enroll claim passkey, cancel prompt, replay challenge, try another origin/browser.
Expected	No bypass on cancellation or replay; challenge RP/origin scoped; recovery/unsupported-browser behavior accurate rather than silent OPEN downgrade.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-007 / Policy gate cannot be downgraded

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Alter claim-policy fields in registration, request body and persisted-cache fixture; remove mail credential mid-flow.
Expected	Enforced policy stays authoritative; configuration outage refuses securely; no upgrade/downgrade from client assertions.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-POLICY-008 / Security boundaries explained honestly

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Review help for OPEN/CODE/EMAIL/WALLET/PASSKEY; compare builders and off-app key possession.
Expected	OTP and claim code are Kleym application gates, not additional on-chain inbox/code signatures. Only wallet-bound policy enforces assigned owner on-chain.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / EMAIL

KLM-V2-EMAIL-001 / Owned-inbox OTP desktop lifecycle

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Create/fund one EMAIL link for owned inbox; request OTP, enter privately, connect intended Freighter desktop wallet and claim.
Expected	Exactly reviewed USDC delivered once; no XLM top-up; safe receipt and independent ledger cleanup; queued mail not labelled delivered.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-002 / Owned-inbox OTP Android lifecycle

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Repeat EMAIL campaign creation/export/funding and receiving in Android Chrome and Freighter; switch sender to receiver.
Expected	Correct wallet after reconnect; no leave-page warning during intentional handoff; claim success resumes original tab; independent before/after balances.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-003 / OTP malformed, wrong, expired and replaced

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Try empty, letters, five/seven digits, five wrong guesses, expired10min code and old code after resend; then valid fresh code.
Expected	Validation precise; five guesses invalidate challenge; old/expired codes fail; newest valid code consumed once.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-004 / OTP verification token scope and TTL

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Obtain test token, use with another link and after30min, race two correct verifications and replay consumed code.
Expected	No cross-link authorization; expiry requires new challenge; exactly one successful consumption under concurrency.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-005 / OTP mailbox enumeration and settled links

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Request unknown, expired, suspended, claimed, redacted and valid bindings; compare public response and provider sends.
Expected	Uniform safe response; no assigned address or provider error disclosed; only eligible valid binding sends.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-006 / Shared Wi-Fi and individual rate limits

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use four distinct links/mailboxes on one IP, then one mailbox across four links and one link repeated eleven verifies; test aggregate300/301 and600/601 in fixtures.
Expected	Independent recipients retain budgets; three sends per link/mailbox, ten verifies per link, five guesses per challenge; aggregate bounds and Retry-After enforced.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-007 / Zender 429, 5xx, network timeout and 4xx

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Inject provider429/Retry-After,5xx,timeout,403,409,malformed202,suppressed response; inspect bounded retries.
Expected	Same body/key on transient retries; at most3within15s; honor budget; permanent errors not retried; no false delivered result or OTP body logged.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-008 / Queued status and dead monitor job

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Simulate accepted/queued/sent/delivered/bounced/failed; stop/restart worker and exhaust status polls.
Expected	Identifier-only job survives; sent/opened alone not delivery; terminal/exhausted observable; polling never resends OTP; retention bounded.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-009 / Web crash during email send

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Terminate isolated web after challenge creation/provider acceptance; restart and request new code.
Expected	No durable plaintext OTP retry payload; user can request replacement; earlier challenge invalidated; no automatic duplicate email on restart.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-010 / Email design across mail clients

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Inspect sanitized HTML/plaintext on Gmail desktop/Android, Outlook and dark mode; increase font size and select code.
Expected	Readable contiguous6digits,10min guidance, no subject OTP, no external assets/scripts or clipped code; no claim URL in email.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-011 / Provider absence and insufficient scope

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Remove Zender config in isolated env, use403 credential, missing emails:read and disabled application.
Expected	Creation option unavailable when unconfigured; existing EMAIL links remain gated; actionable operator error; browser never receives API key.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-012 / OTP reminders and template exclusion

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Attempt reusable EMAIL template and invitation/reminder sends for new OTP-only bindings; inspect legacy queued bearer jobs.
Expected	EMAIL recipient templates refused; no unsolicited invitation/claim URL; no unusable reminder controls; legacy bearer jobs held, not silently sent/deleted.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-EMAIL-013 / Sender authentication and tracking qualification

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Provider owner confirms SPF/DKIM/DMARC alignment and disabled open/click tracking; send to fresh owned mailbox.
Expected	Record authentication verdicts and placement, not private headers/code. Previous Not spam action and zero events alone do not prove general deliverability.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / MANAGE

KLM-V2-MANAGE-001 / Campaign IDs and funding receipts visible

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open funded/partial/draft campaigns; refresh funding status and copy public IDs/hashes.
Expected	Campaign ID and each batch hash visible; explorer points to correct network; only ledger-confirmed funding marked confirmed.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-002 / List filters, paging and empty states

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use mixed statuses/assets, date range, search, page size and no-match; Back/Forward and reset.
Expected	Stable order/counts within org; no repeated/missing entries or zero-match crash; filter URL/history stays consistent.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-003 / Link table and safe export

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Page large mixed-status campaign; inspect custom amount/bound recipient/code-policy metadata and download receipts.
Expected	Stable per-row mapping; no server-generated bearer URL or recovery material; receipt totals match ledger and exact decimal values.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-004 / Suspend and resume boundaries

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	On disposable campaign/link pause before claim, during preparation and after submitted transaction; retry unauthorized role.
Expected	Suspension blocks future app admission but cannot reverse a confirmed ledger transfer or pretend to revoke a leaked key on-chain.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-005 / Expiry is eligibility, not automatic payout

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Leave unused link past chain deadline; observe status and connect sender for reclaim.
Expected	Deadline enables sender-signed reclaim; no guaranteed automatic transfer at expiry; worker cannot forge sender signature.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-006 / Refund and renewal exact accounting

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Claim two of three equal links; expire/reclaim third; renew once and race two renewal requests.
Expected	Exactly1refund and1renewal budget; original history retained; no additional unfunded promise or second independent spend; repeated request reuses same renewal.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-007 / Unsafe renewal refused

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Renew unexpired, partially reclaimed, missing receipt, zero returned or custom-amount campaign; alter sender/network/amount.
Expected	Clear documented refusal; no wallet debit or new campaign; variable prizes currently require separately reviewed new distribution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-008 / Templates CRUD and schedule boundaries

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Create non-email template; run now, enable/disable cadence, modify schedule/day/hour, remove while draft run exists; invalid cadence/time.
Expected	Owner-scoped changes; disabled schedule no new runs; each scheduled run is an unsigned draft requiring export and wallet approval.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-009 / Approvals self-approval and revoked member

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Create threshold case with two approvers; self-approve, approve twice, revoke membership, change campaign terms.
Expected	Required distinct authorized approvals; stale approvals cannot authorize changed payload; creator cannot bypass dual control.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-MANAGE-010 / History, receipts and valuation provenance

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Compare claim/refund hashes, ledger timestamps, unknown fees, v1/v2 archived signatures and current v3 receipts.
Expected	No invented timestamp/zero fee; historical signatures unchanged; correct actual asset and delivered amount; tampering fails verification.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / SETTINGS

KLM-V2-SETTINGS-001 / Password field mobile geometry

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	At320/360/412px open Settings, focus both password fields, show keyboard, rotate, use200%text.
Expected	Inputs and submit usable with readable labels; no page-wide overflow, hidden focus or clipped controls.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-SETTINGS-002 / API key create/read/write/revoke

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use disposable org key; issue minimal scope, copy one-time key, refresh, revoke and retry requests; test blank/max+1name.
Expected	Secret shown once, only hash retained; scope/rate/ownership enforced; immediate revocation; fresh factor gate honored.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-SETTINGS-003 / Org membership and last owner

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Add existing/new user; change role/remove last owner/self; attempt forbidden viewer/operator operations.
Expected	Explicit allowed role matrix; cannot orphan org or elevate oneself; invitation not privileged until accepted; safe error.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-SETTINGS-004 / Organisation form invalid values

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Try whitespace name, invalid approval threshold, approvals0/11, unsupported currency and non-HTTPS screening URL.
Expected	Boundary validation; no partial policy update; valid values persist after reload and apply server-side.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-SETTINGS-005 / SSO and SCIM secret minimization

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Save disposable connection, edit without secret, rotate/revoke SCIM key and inspect page after reload.
Expected	Existing secret retained when blank by design; no recoverable secret in read API/HTML; changes require owner scope.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-SETTINGS-006 / Webhook URL and delivery failures

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Create scoped endpoint; test private/IP/redirect/DNS-change targets, bad signature,429/5xx,replay and revocation.
Expected	Egress guards fail closed; signed timestamped bounded delivery and retries; no claim secrets; disabled endpoint stops new sends.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / ADMIN

KLM-V2-ADMIN-001 / Admin read and role isolation

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Open all six admin routes as admin then sender/viewer with directURL/API; inspect tenant-scoped exports.
Expected	Admin only; unauthorized gets safe refusal; no cross-org secrets or sponsor credentials exposed.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-ADMIN-002 / User invitation and suspension

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use disposable user; cancel invitation dialog, invalid username, create/revoke, deactivate active session and try last-admin lockout.
Expected	Validation and confirmation correct; deactivation revokes sessions; no unintended real-account change.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-ADMIN-003 / Reconciliation dry run and resync

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Plant DB drift in isolated ledger fixture, run scoped resync, pause worker and restore; repeat same pass.
Expected	Chain wins; no duplicate journal/receipt; pending transactions not misclassified from temporary404; unauthorized resync refused.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-ADMIN-004 / Audit filters, paging and signed export

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Filter action/actor/campaign/date with invalid ranges and no-match; export and verify chain, tamper middle entry.
Expected	Scoped stable results; valid checkpoint signature; tampering detected; no credential, code or bearer payload.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-ADMIN-005 / Privacy erasure and retention

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use disposable EMAIL binding; redact, attempt OTP afterward, run retention twice, compare immutable receipt/audit.
Expected	PII erased only under documented scope; gate not downgraded; financial evidence preserved; unrelated org untouched.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

KLM-V2-ADMIN-006 / Sponsor pool and stranded accounts

P0 | Positive + Negative + Boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Inject shortage, stale RPC, depleted sponsor and abandoned materialization; inspect status then recovery runbook.
Expected	Admission prevents unfunded obligations; chosen sponsor/sequence coordinated; persistent recipient reserves distinguished from temporary leaks; no unauthorized seedless recovery promise.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app; src/lib; AGENT.md; current feature docs

Detailed cases / PAGE

KLM-V2-PAGE-001 / Page contract: /admin/audit

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin/audit with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/audit/page.tsx

KLM-V2-PAGE-002 / Page contract: /admin/campaigns

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin/campaigns with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/campaigns/page.tsx

KLM-V2-PAGE-003 / Page contract: /admin

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/page.tsx

KLM-V2-PAGE-004 / Page contract: /admin/privacy

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin/privacy with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/privacy/page.tsx

KLM-V2-PAGE-005 / Page contract: /admin/reconciliation

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin/reconciliation with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/reconciliation/page.tsx

KLM-V2-PAGE-006 / Page contract: /admin/users

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /admin/users with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(admin)/admin/users/page.tsx

KLM-V2-PAGE-007 / Page contract: /settings/security

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /settings/security with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(mfa)/settings/security/page.tsx

KLM-V2-PAGE-008 / Page contract: /claim

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /claim with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/claim/page.tsx

KLM-V2-PAGE-009 / Page contract: /invite/[token]

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /invite/[token] with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/invite/[token]/page.tsx

KLM-V2-PAGE-010 / Page contract: /login/mfa

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /login/mfa with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/login/mfa/page.tsx

KLM-V2-PAGE-011 / Page contract: /login

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /login with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/login/page.tsx

KLM-V2-PAGE-012 / Page contract: /login/sso

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /login/sso with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/login/sso/page.tsx

KLM-V2-PAGE-013 / Page contract: /

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open / with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/page.tsx

KLM-V2-PAGE-014 / Page contract: /status

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /status with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(public)/status/page.tsx

KLM-V2-PAGE-015 / Page contract: /approvals

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /approvals with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/approvals/page.tsx

KLM-V2-PAGE-016 / Page contract: /campaigns/new

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /campaigns/new with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/campaigns/new/page.tsx

KLM-V2-PAGE-017 / Page contract: /campaigns

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /campaigns with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/campaigns/page.tsx

KLM-V2-PAGE-018 / Page contract: /campaigns/[id]/links

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /campaigns/[id]/links with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/campaigns/[id]/links/page.tsx

KLM-V2-PAGE-019 / Page contract: /campaigns/[id]

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /campaigns/[id] with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/campaigns/[id]/page.tsx

KLM-V2-PAGE-020 / Page contract: /dashboard

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /dashboard with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/dashboard/page.tsx

KLM-V2-PAGE-021 / Page contract: /history

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /history with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/history/page.tsx

KLM-V2-PAGE-022 / Page contract: /settings

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /settings with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/settings/page.tsx

KLM-V2-PAGE-023 / Page contract: /templates

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /templates with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/templates/page.tsx

KLM-V2-PAGE-024 / Page contract: /templates/[id]

P1 | Negative | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	1. Open /templates/[id] with correct role and valid fixture ID. 2. Exercise each visible control against the Controls sheet, including Cancel/Back/empty search. 3. Reload, navigate away/back, repeat at360px and200%text. 4. Use missing/foreign ID and wrong role. Do not submit live administrative or financial mutations.
Expected	Correct heading, route, role and state; no broken navigation, unhandled error, hidden essential controls or foreign data. Each conditional control requires its own recorded actual/evidence row.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/(sender)/templates/[id]/page.tsx

Detailed cases / API

KLM-V2-API-001 / GET /api/admin/audit/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/audit/export/route.ts:8

KLM-V2-API-002 / GET /api/admin/audit/verify

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/audit/verify/route.ts:8

KLM-V2-API-003 / POST /api/admin/privacy/erase

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/privacy/erase/route.ts:17

KLM-V2-API-004 / POST /api/admin/reconcile

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/reconcile/route.ts:21

KLM-V2-API-005 / POST /api/admin/users

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/users/route.ts:18

KLM-V2-API-006 / DELETE /api/admin/users/[id]/invitation

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/users/[id]/invitation/route.ts:19

KLM-V2-API-007 / PATCH /api/admin/users/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/admin/users/[id]/route.ts:20

KLM-V2-API-008 / POST /api/auth/login

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/login/route.ts:26

KLM-V2-API-009 / POST /api/auth/logout

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/logout/route.ts:8

KLM-V2-API-010 / POST /api/auth/mfa/passkey/authenticate/options

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/passkey/authenticate/options/route.ts:8

KLM-V2-API-011 / POST /api/auth/mfa/passkey/authenticate

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/passkey/authenticate/route.ts:17

KLM-V2-API-012 / POST /api/auth/mfa/passkey/register/options

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/passkey/register/options/route.ts:10

KLM-V2-API-013 / POST /api/auth/mfa/passkey/register

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/passkey/register/route.ts:15

KLM-V2-API-014 / DELETE /api/auth/mfa/passkey/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/passkey/[id]/route.ts:13

KLM-V2-API-015 / GET /api/auth/mfa/status

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/status/route.ts:9

KLM-V2-API-016 / POST /api/auth/mfa/totp/confirm

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/totp/confirm/route.ts:15

KLM-V2-API-017 / POST /api/auth/mfa/totp/enrol

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/totp/enrol/route.ts:10

KLM-V2-API-018 / POST /api/auth/mfa/totp/remove

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/totp/remove/route.ts:10

KLM-V2-API-019 / POST /api/auth/mfa/verify

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/mfa/verify/route.ts:23

KLM-V2-API-020 / POST /api/auth/password

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/password/route.ts:35

KLM-V2-API-021 / GET /api/auth/session

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/session/route.ts:8

KLM-V2-API-022 / GET /api/auth/sso/callback

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/sso/callback/route.ts:26

KLM-V2-API-023 / GET /api/auth/sso/start

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/auth/sso/start/route.ts:22

KLM-V2-API-024 / GET /api/campaigns

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/route.ts:31

KLM-V2-API-025 / POST /api/campaigns

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/route.ts:72

KLM-V2-API-026 / GET /api/campaigns/[id]/approvals

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/approvals/route.ts:18

KLM-V2-API-027 / POST /api/campaigns/[id]/approvals

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/approvals/route.ts:27

KLM-V2-API-028 / POST /api/campaigns/[id]/batches/prepare

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/batches/prepare/route.ts:20

KLM-V2-API-029 / POST /api/campaigns/[id]/batches/retry

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/batches/retry/route.ts:19

KLM-V2-API-030 / GET /api/campaigns/[id]/batches

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/batches/route.ts:18

KLM-V2-API-031 / POST /api/campaigns/[id]/batches/submit

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/batches/submit/route.ts:28

KLM-V2-API-032 / POST /api/campaigns/[id]/deliver

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/deliver/route.ts:65

KLM-V2-API-033 / POST /api/campaigns/[id]/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/export/route.ts:22

KLM-V2-API-034 / GET /api/campaigns/[id]/links

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/links/route.ts:29

KLM-V2-API-035 / POST /api/campaigns/[id]/links

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/links/route.ts:67

KLM-V2-API-036 / GET /api/campaigns/[id]/links/[linkId]/receipt

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/links/[linkId]/receipt/route.ts:22

KLM-V2-API-037 / PATCH /api/campaigns/[id]/links/[linkId]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/links/[linkId]/route.ts:22

KLM-V2-API-038 / POST /api/campaigns/[id]/links/[linkId]/suspend

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/links/[linkId]/suspend/route.ts:19

KLM-V2-API-039 / GET /api/campaigns/[id]/outstanding

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/outstanding/route.ts:17

KLM-V2-API-040 / GET /api/campaigns/[id]/receipts

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/receipts/route.ts:24

KLM-V2-API-041 / POST /api/campaigns/[id]/reclaim/prepare

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/reclaim/prepare/route.ts:25

KLM-V2-API-042 / POST /api/campaigns/[id]/reclaim/submit

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/reclaim/submit/route.ts:26

KLM-V2-API-043 / GET /api/campaigns/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/route.ts:20

KLM-V2-API-044 / PATCH /api/campaigns/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/route.ts:59

KLM-V2-API-045 / POST /api/campaigns/[id]/suspend

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/suspend/route.ts:21

KLM-V2-API-046 / GET /api/campaigns/[id]/template

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/campaigns/[id]/template/route.ts:11

KLM-V2-API-047 / POST /api/claims/code/verify

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/code/verify/route.ts:27

KLM-V2-API-048 / POST /api/claims/federation

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/federation/route.ts:92

KLM-V2-API-049 / POST /api/claims/otp/request

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/otp/request/route.ts:35

KLM-V2-API-050 / POST /api/claims/otp/verify

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/otp/verify/route.ts:34

KLM-V2-API-051 / POST /api/claims/passkey/authenticate/options

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/passkey/authenticate/options/route.ts:17

KLM-V2-API-052 / POST /api/claims/passkey/authenticate

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/passkey/authenticate/route.ts:23

KLM-V2-API-053 / POST /api/claims/passkey/register/options

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/passkey/register/options/route.ts:17

KLM-V2-API-054 / POST /api/claims/passkey/register

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/passkey/register/route.ts:26

KLM-V2-API-055 / POST /api/claims/prepare/claim

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/prepare/claim/route.ts:34

KLM-V2-API-056 / POST /api/claims/prepare/materialise

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/prepare/materialise/route.ts:33

KLM-V2-API-057 / POST /api/claims/quote

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/quote/route.ts:33

KLM-V2-API-058 / GET /api/claims/resolve

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/resolve/route.ts:24

KLM-V2-API-059 / POST /api/claims/submit

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/claims/submit/route.ts:28

KLM-V2-API-060 / GET /api/health

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/health/route.ts:10

KLM-V2-API-061 / POST /api/invite/redeem

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/invite/redeem/route.ts:30

KLM-V2-API-062 / GET /api/org/accounting/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/accounting/export/route.ts:19

KLM-V2-API-063 / GET /api/org/audit/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/audit/export/route.ts:12

KLM-V2-API-064 / GET /api/org/compliance/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/compliance/export/route.ts:16

KLM-V2-API-065 / GET /api/org/members

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/members/route.ts:16

KLM-V2-API-066 / POST /api/org/members

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/members/route.ts:22

KLM-V2-API-067 / PATCH /api/org/members/[userId]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/members/[userId]/route.ts:19

KLM-V2-API-068 / DELETE /api/org/members/[userId]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/members/[userId]/route.ts:36

KLM-V2-API-069 / GET /api/org/receipts

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/receipts/route.ts:18

KLM-V2-API-070 / GET /api/org

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/route.ts:18

KLM-V2-API-071 / PATCH /api/org

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/route.ts:28

KLM-V2-API-072 / GET /api/org/sso

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/sso/route.ts:20

KLM-V2-API-073 / PUT /api/org/sso

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PUT with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/sso/route.ts:27

KLM-V2-API-074 / DELETE /api/org/sso

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/sso/route.ts:44

KLM-V2-API-075 / POST /api/org/sso/scim-tokens

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/sso/scim-tokens/route.ts:15

KLM-V2-API-076 / DELETE /api/org/sso/scim-tokens/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/sso/scim-tokens/[id]/route.ts:11

KLM-V2-API-077 / POST /api/org/switch

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/switch/route.ts:18

KLM-V2-API-078 / GET /api/org/webhooks

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/webhooks/route.ts:17

KLM-V2-API-079 / POST /api/org/webhooks

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/webhooks/route.ts:24

KLM-V2-API-080 / GET /api/org/webhooks/[id]/deliveries

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/webhooks/[id]/deliveries/route.ts:10

KLM-V2-API-081 / DELETE /api/org/webhooks/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/webhooks/[id]/route.ts:15

KLM-V2-API-082 / PATCH /api/org/webhooks/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/org/webhooks/[id]/route.ts:23

KLM-V2-API-083 / GET /api/ready

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/ready/route.ts:20

KLM-V2-API-084 / GET /api/scim/v2/Groups

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/route.ts:10

KLM-V2-API-085 / POST /api/scim/v2/Groups

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/route.ts:21

KLM-V2-API-086 / GET /api/scim/v2/Groups/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/[id]/route.ts:12

KLM-V2-API-087 / PUT /api/scim/v2/Groups/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PUT with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/[id]/route.ts:20

KLM-V2-API-088 / PATCH /api/scim/v2/Groups/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/[id]/route.ts:30

KLM-V2-API-089 / DELETE /api/scim/v2/Groups/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Groups/[id]/route.ts:41

KLM-V2-API-090 / GET /api/scim/v2/ServiceProviderConfig

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/ServiceProviderConfig/route.ts:7

KLM-V2-API-091 / GET /api/scim/v2/Users

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/route.ts:8

KLM-V2-API-092 / POST /api/scim/v2/Users

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/route.ts:19

KLM-V2-API-093 / GET /api/scim/v2/Users/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/[id]/route.ts:10

KLM-V2-API-094 / PUT /api/scim/v2/Users/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PUT with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/[id]/route.ts:30

KLM-V2-API-095 / PATCH /api/scim/v2/Users/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/[id]/route.ts:42

KLM-V2-API-096 / DELETE /api/scim/v2/Users/[id]

P0 | API contract / authorization / boundary | Configured feature | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/scim/v2/Users/[id]/route.ts:66

KLM-V2-API-097 / GET /api/settings/api-keys

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/settings/api-keys/route.ts:22

KLM-V2-API-098 / POST /api/settings/api-keys

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/settings/api-keys/route.ts:34

KLM-V2-API-099 / DELETE /api/settings/api-keys/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/settings/api-keys/[id]/route.ts:19

KLM-V2-API-100 / GET /api/status

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/status/route.ts:10

KLM-V2-API-101 / GET /api/stellar/account

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/stellar/account/route.ts:22

KLM-V2-API-102 / GET /api/stellar/network

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with intended public proof/schema. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/stellar/network/route.ts:8

KLM-V2-API-103 / GET /api/stellar/reserve

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/stellar/reserve/route.ts:18

KLM-V2-API-104 / GET /api/templates

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/route.ts:17

KLM-V2-API-105 / POST /api/templates

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/route.ts:29

KLM-V2-API-106 / GET /api/templates/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/[id]/route.ts:20

KLM-V2-API-107 / PATCH /api/templates/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PATCH with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/[id]/route.ts:29

KLM-V2-API-108 / DELETE /api/templates/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid DELETE with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/[id]/route.ts:55

KLM-V2-API-109 / POST /api/templates/[id]/run

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/[id]/run/route.ts:18

KLM-V2-API-110 / GET /api/templates/[id]/runs

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/templates/[id]/runs/route.ts:11

KLM-V2-API-111 / GET /api/v1/campaigns

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/route.ts:31

KLM-V2-API-112 / POST /api/v1/campaigns

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/route.ts:72

KLM-V2-API-113 / POST /api/v1/campaigns/[id]/batches/prepare

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/batches/prepare/route.ts:18

KLM-V2-API-114 / POST /api/v1/campaigns/[id]/batches/submit

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/batches/submit/route.ts:20

KLM-V2-API-115 / POST /api/v1/campaigns/[id]/export

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/export/route.ts:17

KLM-V2-API-116 / GET /api/v1/campaigns/[id]/links

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/links/route.ts:34

KLM-V2-API-117 / POST /api/v1/campaigns/[id]/links

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/links/route.ts:76

KLM-V2-API-118 / GET /api/v1/campaigns/[id]

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/campaigns/[id]/route.ts:15

KLM-V2-API-119 / GET /api/v1/templates

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid GET with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/templates/route.ts:11

KLM-V2-API-120 / PUT /api/v1/templates/[id]/recipients

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid PUT with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/templates/[id]/recipients/route.ts:47

KLM-V2-API-121 / POST /api/v1/templates/[id]/run

P0 | API contract / authorization / boundary | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	In isolated fixture server: 1. Send valid POST with required session/key/SCIM credential and least-privileged role. 2. Repeat missing/expired/wrong-scope credential, foreign object ID and unknown ID. 3. For bodies test malformed JSON, extra fields, secret-shaped fixture, wrong types and schema boundaries. 4. For mutation replay identical idempotency key, changed-body key and concurrent calls; for reads test stable pagination/query bounds. 5. Compare durable state before/after every rejected request.
Expected	Valid request follows its handler contract; expected4xx uses safe problem details and leaves state unchanged; no authorization/seed bypass, duplicate asset action or private data. Public routes are not incorrectly expected to require an admin session. Record exact code from applicable handler before execution.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/app/api/v1/templates/[id]/run/route.ts:18

Detailed cases / STATE

KLM-V2-STATE-001 / Claim screen: loading

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach loading; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-002 / Claim screen: invalid

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach invalid; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-003 / Claim screen: ready

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach ready; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-004 / Claim screen: otp_required

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach otp_required; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-005 / Claim screen: code_required

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach code_required; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-006 / Claim screen: passkey_required

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach passkey_required; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-007 / Claim screen: email_only

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach email_only; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-008 / Claim screen: wallet_connecting

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach wallet_connecting; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-009 / Claim screen: preparing

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach preparing; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-010 / Claim screen: materialising

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach materialising; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-011 / Claim screen: awaiting_ledger

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach awaiting_ledger; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-012 / Claim screen: awaiting_signature

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach awaiting_signature; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-013 / Claim screen: submitting

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach submitting; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-014 / Claim screen: claimed_success

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach claimed_success; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-015 / Claim screen: already_claimed

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach already_claimed; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-016 / Claim screen: expired

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach expired; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts

KLM-V2-STATE-017 / Claim screen: failed

P0 | State transition | Testnet release | Not Run

Preconditions	Frozen candidate; isolated migrated DB/Redis and disposable fixtures for mutations. Live browser reads may use the team Testnet host. Wallet signs remain deliberate and private.
Steps / inputs	Use isolated claim-page/API fixture to reach failed; check copy, visible actions, busy/disabled states, screen-reader announcement, retry/cancel and reload at desktop and360px. If a transaction is pending, preserve its exact hash and materialisation state.
Expected	Designed state is reachable under intended conditions; no premature success, duplicate materialisation, secret display or incorrect retry target. Terminal states cannot pay again; transient failures allow safe recovery.
Proof	Exact candidate, input fixture ID, expected/actual result, safe screenshot or response, and durable-state/ledger checks where relevant. No OTP, token, phrase, private CSV or full claim URL.
Source / mode	src/lib/claim/machine.ts; e2e/claim-page.spec.ts