

Deep Learning Forecasting Customer Behavior


Artit “Art” Wangperawong
artitw@gmail.com

Telco customer – will he leave the service?




Artit Wangperawong

Target Data Selection




Parameter	Value	Implied date range
30 day churn window start	24 Sep 2015	24 Sep- 23 Oct
Last call window	14 days	10 Sep – 23 Sep
Time before last call	14 days	27 Aug – 23 Sep
Predictor window	30 days	28 Jul – 9 Sep
Minimum age on network	90 days	< 28 Jul


Telco churn DL – customer as image



One architecture: DL-1




One architecture: DL-1



DL versus SPSS

AUC	Training	Test
SPSS CHAID	0.699	0.665
DL-1	0.751	0.706
DL-2	0.748	0.743

Autoencoder – unsupervised learning




$$a_i^{(2)} = f \left(\sum_{j=1}^{100} W_{ij}^{(1)} x_j + b_i^{(1)} \right).$$


$$x_j = \frac{W_{ij}^{(1)}}{\sqrt{\sum_{j=1}^{100} (W_{ij}^{(1)})^2}}.$$



http://deeplearning.stanford.edu/wiki/index.php/Visualizing_a_Trained_Autoencoder

Images that maximally activate hidden units of autoencoder for all customers



Images that maximally activate the weights of the autoencoder for churn





Customer who
churned

- 1) Very high usage of data and only data
- 2) Usage of the phone only from 14-16th days
- 3) Almost no usage during the 30 days period

Churn analysis using deep convolutional neural networks and autoencoders

Artit Wangperawong^{a,b,*}

Cyrille Brun^c

Dr. Olav Laudy^c

Rujikorn Pavasuthipaisit^a

<http://arxiv.org/abs/1604.05377>

^a True Corporation Public Company Limited, Bangkok 10310, Thailand

^b Department of Electrical Engineering, Faculty of Engineering, King Mongkut's University of Technology Thonburi, Bangkok 10140, Thailand

^c International Business Machines Corporation, Singapore 486048

* To whom correspondence should be addressed; Email: artitw@gmail.com

Customer temporal behavioral data was represented as images in order to perform churn prediction by leveraging deep learning architectures prominent in image classification. Supervised learning was performed on labeled data of over 6 million customers using deep convolutional neural networks, which achieved an AUC of 0.743 on the test dataset using no more than 12 temporal features for each customer. Unsupervised learning was conducted using autoencoders to better understand the reasons for customer churn. Images that maximally activate the hidden units of an autoencoder trained with churned customers reveal ample opportunities for action to be taken to prevent churn among strong data, no voice users.

Keywords: machine learning, deep learning, big data, churn prediction, telecommunications

Deep learning by convolutional neural networks (CNNs) has demonstrated superior performance in many image processing tasks [1,2,3]. In order to leverage such advances to predict churn and take pro-active measures to prevent it, we represent customers as images. Specifically, we construct a 2-dimensional array of normalized pixels where each row is for each day and each column is for each type of behavior tracked (Fig. 1). The type of behavior can include data usage, top up amount, top up frequency, voice calls, voice minutes, SMS messages, etc. In the training and testing data, each image is also accompanied by its label – 1 for churned and 0 for not churned. For this analysis, we examine prepaid customers in particular.

true



What's next? Reinforcement Learning

- No need to classify target
 - Can forecast real values
- Not specific to telco or churn
 - Applicable across industries and use-cases, including retail and advertising
 - How much will customers spend next month?
 - How much revenue will advertisements generate?