Simulating magic in quantum error correction

Arthur Pesah

FU Berlin

GitHub

mark-koch/
merlin-sim

Joint work with



Serban Cercelescu
Oxford




Mark Koch
Oxford


arXiv

2610.06811

What quantum circuits are classically simulable?




What quantum circuits are classically simulable?



Magic: non-Clifford ingredients, such as T gates.

What quantum circuits are classically simulable?



Magic: non-Clifford ingredients, such as T gates.

The answer has practical consequences for **quantum error correction**.

Quantum error correction

The idea: add redundancy to protect information against errors.

Quantum error correction

The idea: add redundancy to protect information against errors.


Classical example: repeat each bit three times.

$$011 \xrightarrow{\text{encode}} 000\,111\,111$$

Quantum error correction

The idea: add redundancy to protect information against errors.


Classical example: repeat each bit three times.



Quantum error correction

The idea: add redundancy to protect information against errors.


Classical example: repeat each bit three times.



Quantum error correction

The idea: add redundancy to protect information against errors.

Classical example: repeat each bit three times.



Quantum version: encode each logical qubit across several physical qubits.

Measure error checks without reading out the stored information.

Gates on encoded qubits

Each gate in the algorithm needs a **fault-tolerant logical implementation**.

Algorithm




Gates on encoded qubits

Each gate in the algorithm needs a **fault-tolerant logical implementation**.

Algorithm



Encoded implementation




Gates on encoded qubits

Each gate in the algorithm needs a **fault-tolerant logical implementation**.

Algorithm




Encoded implementation



A small circuit becomes a **larger circuit on more qubits**.


Benchmarking quantum error correction

A protocol converts physical errors into a logical error rate:



Benchmarking quantum error correction


A protocol converts physical errors into a logical error rate:



Goal: make ϵ_L as small as possible at an affordable cost.

Benchmarking quantum error correction

A protocol converts physical errors into a logical error rate:



Goal: make ϵ_L as small as possible at an affordable cost.

How? Simulate noisy protocols, count logical failures, and compare designs.

The simulation bottleneck

- **Clifford circuits**: efficient classical simulation, even with many qubits.

The simulation bottleneck

- **Clifford circuits**: efficient classical simulation, even with many qubits.
- Universal quantum computing also needs **non-Clifford ingredients**, often supplied as magic states.

The simulation bottleneck

- **Clifford circuits**: efficient classical simulation, even with many qubits.
- Universal quantum computing also needs **non-Clifford ingredients**, often supplied as magic states.
- Generic simulation methods can become **exponentially costly** as magic increases.

The simulation bottleneck

- **Clifford circuits**: efficient classical simulation, even with many qubits.
- Universal quantum computing also needs **non-Clifford ingredients**, often supplied as magic states.
- Generic simulation methods can become **exponentially costly** as magic increases.

Until our work: only **small-scale** benchmarking of logical magic protocols possible.

The simulation bottleneck

- **Clifford circuits**: efficient classical simulation, even with many qubits.
- Universal quantum computing also needs **non-Clifford ingredients**, often supplied as magic states.
- Generic simulation methods can become **exponentially costly** as magic increases.

Until our work: only **small-scale** benchmarking of logical magic protocols possible.

Can we exploit the structure of quantum error correction?

Efficient simulation of quantum error correction

- QEC implementations of magic gates have **structure we can exploit**.

Efficient simulation of quantum error correction

- QEC implementations of magic gates have **structure we can exploit**.
- For a broad class of these protocols, we obtain **polynomial-time classical simulation**.

Efficient simulation of quantum error correction

- QEC implementations of magic gates have **structure we can exploit**.
- For a broad class of these protocols, we obtain **polynomial-time classical simulation**.
- **MERLIN**: our open-source simulator for benchmarking logical magic protocols.

Efficient simulation of quantum error correction

- QEC implementations of magic gates have **structure we can exploit**.
- For a broad class of these protocols, we obtain **polynomial-time classical simulation**.
- **MERLIN**: our open-source simulator for benchmarking logical magic protocols.

If magic alone is not enough, what makes quantum circuits hard to simulate?

2610.06811

mark-koch/merlin-sim

Efficient simulation of quantum error correction

- QEC implementations of magic gates have **structure we can exploit**.
- For a broad class of these protocols, we obtain **polynomial-time classical simulation**.
- **MERLIN**: our open-source simulator for benchmarking logical magic protocols.

If magic alone is not enough, what makes quantum circuits hard to simulate?

Thanks!

2610.06811

mark-koch/merlin-sim