

Causality



- When a test case fails we start debugging
- We assume that the fault (what we're really after) *causes* the failure
 - Remember RIP (Reachability, Infection, Propagation)?
- What do we mean when we say that
 - “A causes B”?

Causality




- *We don't know*
- Though it is central to everyday life – and to the aims of science
 - A real understanding of causality eludes us to this day
 - Still no non-controversial way to answer the question “does A cause B”?

Causality



- Philosophy of causality is a fairly active area, back to Aristotle, and (more modern approaches) Hume
 - General agreement that a cause is something that “makes a difference” – if the cause had not been, then the effect wouldn’t have been
 - One theory that is rather popular with computer scientists is David Lewis’ *counterfactual* approach
 - Probably because it (and probabilistic or statistical approaches) are amenable to mathematical treatment and automation



Causality (According to Lewis)

- For Lewis (roughly – I'm conflating his *counterfactual dependency* and *causal dependency*)
 - A causes B (in world w) iff
 - In all *possible worlds* that are *maximally similar* to w , and in which A does not take place, B also does not take place

Causality (According to Lewis)

- Causality does not depend on
 - B being *impossible* without A
 - Seems reasonable: we don't, when asking "Was Larry slipping on the banana peel causally dependent on Curly dropping it?" consider worlds in which new circumstances (Moe dropping a banana peel) are introduced




Causality (According to Lewis)




- Many objections to Lewis in the literature
 - e.g. cause precedes the event in time seems to not be required by his approach
- One is not a problem for our purposes
 - Distance metrics (how similar is world w to world w') are problematic for “worlds”
 - Counterfactuals are tricky
 - Not a problem for *program executions*
 - May be details to handle, but no one has in-principle objections to asking how similar two program executions are
 - Or philosophical problems with multiple executions (no run is “privileged by actuality”)



Causality (According to Lewis)



Yes! $d < d'$



No. $d > d'$

Did A cause B in this program execution?

Formally



A predicate e is causally dependent on a predicate c in an execution a iff:

- 1. $c(a) \wedge e(a)$***
- 2. $\exists b . (\neg c(b) \wedge \neg e(b) \wedge$
 $(\forall b' . (\neg c(b') \wedge e(b')) \Rightarrow (d(a, b) < d(a, b')))))$***

What does this have to do with automated debugging??

- A **fault** is an incorrect part of a program
- In a failing test case, some fault is reached and executes
 - *Causing* the state of the program to be corrupted (**error**)
 - This incorrect state is propagated through the program (propagation is a series of “A causes B”s)
 - Finally, bad state is observable as a **failure** – *caused* by the **fault**

Fault Localization

- **Fault localization**, then, is:

- An effort to automatically find (one of the) causes of an observable failure
- It is inherently difficult because there are many causes of the failure that are not the fault
 - We don't mind seeing the chain of cause and effect reaching back to the fault
 - But the fact that we reached the fault at all is also a cause!