

Print representation of an object

- Left to its own devices, Python uses a unique but uninformative print presentation for an object

```
>>> print c
```

```
<__main__.Coordinate object at 0x7fa918510488>
```

Print representation of an object

- Left to its own devices, Python uses a unique but uninformative print presentation for an object

```
>>> print c
```

```
<__main__.Coordinate object at 0x7fa918510488>
```

- One can define a `__str__` method for a class, which Python will call when it needs a string to print. This method will be called with the object as the first argument and should return a `str`.

```
class Coordinate(object):  
    def __init__(self, x, y):  
        self.x = x  
        self.y = y  
    def __str__(self):  
        return "<" + self.x + ", " + self.y + ">"
```

Print representation of an object

- Left to its own devices, Python uses a unique but uninformative print presentation for an object

```
>>> print c
```

```
<__main__.Coordinate object at 0x7fa918510488>
```

- One can define a `__str__` method for a class, which Python will call when it needs a string to print. This method will be called with the object as the first argument and should return a `str`.

```
class Coordinate(object):  
    def __init__(self, x, y):  
        self.x = x  
        self.y = y  
    def __str__(self):  
        return "<" + self.x + ", " + self.y + ">"
```

```
>>> print c
```

```
<3, 4>
```

Type of an Object

- We can ask for the type of an object

```
>>> print type(c)  
<class __main__.Coordinate>
```

- This makes sense since

```
>>> print Coordinate, type(Coordinate)  
<class __main__.Coordinate> <type 'type'>
```

Type of an Object

- We can ask for the type of an object

```
>>> print type(c)  
<class __main__.Coordinate>
```

- This makes sense since

```
>>> print Coordinate, type(Coordinate)  
<class __main__.Coordinate> <type 'type'>
```

- Use `isinstance()` to check if an object is a **Coordinate**

```
>>> print isinstance(c, Coordinate)  
True
```

Adding other methods

- Can add our own methods, not just change built-in ones

```
class Coordinate(object):  
    def __init__(self, x, y):  
        self.x = x  
        self.y = y  
    def __str__(self):  
        return "<" + self.x + ", " + self.y + ">"  
    def distance(self, other):  
        return math.sqrt(sq(self.x - other.x)  
                           + sq(self.y -  
other.y))
```