


In one line: You use GoF patterns daily: the **responder chain** is Chain of Responsibility, **target-action/UndoManager** is Command (+ Memento), NotificationCenter/KVO/Combine are Observer, **class clusters** are Abstract Factory, appearance() is a Proxy, a ViewModifier a Decorator. Each row: **pattern + API + mechanism + the gist**.

Pattern	Where Apple put it	Mechanism	In short
Chain of Resp.	responder chain: UIResponder.next; sendAction(_to: nil, from:for:)	selector not implemented? pass to next until someone does, or the chain ends	<i>Copy/Paste find a handler by walking the chain.</i>
Command	target-action, UIAction, UIKeyCommand, ObjC	request stored as data, run later; the undo closure captures the <i>old value</i> = the memento	<i>UndoManager is a command stack over snapshots.</i>
+Memento	NSNotification; UndoManager	notify subscribers you don't know; @Observable tracks the properties a body <i>read</i>	<i>broadcast → KVO → typed streams → access tracking</i>
Observer	NotificationCenter · KVO · Combine @Published · @Observable (iOS 17)	weak helper called at fixed hooks; a layout object = a whole algorithm, swapped at runtime	<i>Delegate: many hooks, one owner. Layout: Strategy.</i>
Delegation	table delegate + data source; UICollectionViewLayout; keyDecodingStrategy	public abstract class; init returns a <i>private</i> subclass (NSArrayI, NSMutableArrayM)	<i>Apple documents clusters as Abstract Factory.</i>
+Strategy	UIAppearance: UINavigationController.appearance(); ObjC NSProxy	proxy records setters, applies them when a view enters a window	<i>Not the bar — a recorder.</i>
Abstract Factory	SwiftUI ViewModifier, .padding(), .background()	each call wraps: ModifiedContent<Content, Modifier>, nested	<i>The wrapping is in the type — order matters.</i>
Proxy		leaf + container share one interface; operations recurse	<i>Hit-test walks it down, the chain up.</i>
Decorator	UIView/CALayer trees, SwiftUI view tree, UIMenu(children:)	makeUIView/updateUIView; its Coordinator adapts UIKit delegates	<i>Imperative view behind a declarative protocol.</i>
Composite	UIViewRepresentable (UIKit→SwiftUI), UIHostingController (SwiftUI→UIKit)	makeIterator(), then next() until nil	<i>for-in is sugar for it.</i>
Adapter	Sequence + IteratorProtocol, AsyncSequence	hop 1 dispatches on the <i>value's</i> type, hop 2 on the <i>encoder's</i> (= format)	<i>Double dispatch: one encode(to:), any format.</i>
Iterator	Codable: JSONEncoder().encode(v) → v.encode(to:) → c.encode(x, forKey:)	first class whose canInit(with:) says true loads it (registered: reverse order)	<i>The standard network stub in tests.</i>
Visitor-like	URLProtocol; config.protocolClasses; URLProtocol.registerClass	copy a configured instance; Foundation copies are shallow	<i>Swift: var b = a.</i>
Chain→Strategy	NSCopying: copy(), mutableCopy()	only UIApplication is one per process (UIApplicationMain); others you may create	<i>Shared instance ≠ singleton; inject it any-way.</i>
Prototype			
Singleton	UIApplication.shared vs shared <i>instances</i> (URLSession.shared, FileManager.default)		

Also, on other folios: Template Method = VC lifecycle, LayoutSubviews · Factory Method = class var layerClass · Facade = URLSession · Flyweight = UIImage(named:) · Interpreter = NSPredicate · Object Pool = cell reuse.

The responder chain, exact rules



Touches start at the hit-tested view; keys, menus and nil-target actions at the **first responder**. Scene step: Apple forum answer — the article still says window → app.

Traps

- ! Hit-test (down) ≠ responder chain (up): two walks over one Composite.
- ! A nil-target action nobody implements does **nothing** — no crash, no log.
- ! appearance() changed while a view is on screen: no effect until it re-enters a window.
- ! type(of: NSArray()) is a private subclass — never compare a cluster's class.
- ! URLSession.shared is a shared *instance*, not a singleton.

Remember

Chain walks up · Command stores the request · Observer fans out · Delegate answers back · Cluster hides the subclass · Proxy records · Modifier wraps · Codable dispatches twice.

Example — drive the patterns yourself

```
// Chain: nil target -> first responder -> up ("hide keyboard")
UIApplication.shared.sendAction(#selector(UIResponder
.resignFirstResponder), to: nil, from: nil, for: nil)
// Chain -> Strategy: URLProtocol stubs the network in tests
final class StubProtocol: URLProtocol {
    nonisolated(unsafe) static var body = Data()
    override class func canInit(with r: URLRequest) -> Bool { true }
    override class func canonicalRequest(for r: URLRequest)
        -> URLRequest { r }
    override func startLoading() {
        client?.urlProtocol(self, didLoad: Self.body)
        client?.urlProtocolDidFinishLoading(self) }
    override func stopLoading() {} }
let cfg = URLSessionConfiguration.ephemeral
cfg.protocolClasses = [StubProtocol.self]
// Command + Memento: the closure captures the OLD value
@MainActor func rename(_ doc: Doc, to: new: String,
    undo: UndoManager) {
    let old = doc.title // the memento
    undo.registerUndo(withTarget: doc) { d in // use d, not doc
        rename(d, to: old, undo: undo) } // = registers redo
    undo.setActionName("Rename"); doc.title = new }
```

Doc: a final class with var title. Registering *inside* the undo handler is what makes **redo** work — during undo, UndoManager puts new registrations on the redo stack.